

Manual on Codes

International Codes

Volume I.2

Annex II to the WMO Technical Regulations

Part B – Binary Codes

Part C – Common Features to Binary and Alphanumeric Codes

2019 edition

Updated in 2022



WORLD
METEOROLOGICAL
ORGANIZATION

Provisional Copy
2023

Manual on Codes

International Codes

Volume I.2

Annex II to the WMO Technical Regulations

Part B – Binary Codes

Part C – Common Features to Binary and Alphanumeric Codes

2019 edition

Updated in 2022



WORLD
METEOROLOGICAL
ORGANIZATION

WMO-No. 306

EDITORIAL NOTE

Considering that code forms, regulations, tables and notes in Volume I.2 form the basis for correct encoding/decoding, all these must be abided by regardless of the use of "shall" or "should".

Typefaces employed in this volume therefore do not signify standard or recommended practices, and are used solely for legibility.

Regardless of the above, the standard coding procedures are distinguished by the use of the term "shall" in the English text and by suitable equivalent terms in the French, Russian and Spanish texts in Part C, section d.

WMO-No. 306

© **World Meteorological Organization, 2019**

The right of publication in print, electronic and any other form and in any language is reserved by WMO. Short extracts from WMO publications may be reproduced without authorization, provided that the complete source is clearly indicated. Editorial correspondence and requests to publish, reproduce or translate this publication in part or in whole should be addressed to:

Chair, Publications Board
World Meteorological Organization (WMO)
7 bis, avenue de la Paix
P.O. Box 2300
CH-1211 Geneva 2, Switzerland

Tel.: +41 (0) 22 730 84 03
Fax: +41 (0) 22 730 81 17
Email: publications@wmo.int

ISBN 978-92-63-10306-2

NOTE

The designations employed in WMO publications and the presentation of material in this publication do not imply the expression of any opinion whatsoever on the part of WMO concerning the legal status of any country, territory, city or area, or of its authorities, or concerning the delimitation of its frontiers or boundaries.

The mention of specific companies or products does not imply that they are endorsed or recommended by WMO in preference to others of a similar nature which are not mentioned or advertised.

PUBLICATION REVISION TRACK RECORD

<i>Date</i>	<i>Part/chapter/section</i>	<i>Purpose of amendment</i>	<i>Proposed by</i>	<i>Approved by</i>
May 2022	Definitions	Add acronym table	INFCOM/SC-IMT/ET-Data	Fast-track procedure 2022-1
May 2022	Part B - Binary Codes: FM 92 GRIB	New product definition templates to represent local time. New code table for Character of precipitation. New values in code tables.	INFCOM/SC-IMT/ET-Data	Fast-track procedures 2021-2 and 2022-1
May 2022	Part B - Binary Codes: FM 94 BUFR	Remove attachment for definition of Backus-Naur form. New sequences in Table D for vertical sounding, DAYCLI, satellite radar observations and lidar observations from satellites, New descriptors in Table B and new values in Code and Flag tables.	INFCOM/SC-IMT/ET-Data	Fast-track procedures 2021-2 and 2022-1
May 2022	Part C - Common features to Binary and Alphanumeric Codes	New code in Table A for Uncrewed surface vehicle. New codes for radiosonde systems, satellites, originating centers and atmospheric chemicals.	INFOM/SC-IMT/ET-Data	Fast-track procedures 2021-2 and 2022-1
	<u>Part B - Binary Codes: FM 92 GRIB, FM 94 BUFR and Part C</u>	<u>New GRIB codes for land surface modelling, new GRIB code tables for thermodynamic properties, urban areas and wetland type, and fixed mathematical error in Attachment III. New BUFR sequences for tagged marine animals and snow cover.</u>	<u>INFOM/SC-IMT/ET-Data</u>	<u>Fast-track procedures 2022-2</u>
	<u>Part B - Binary Codes: FM 92 GRIB, FM 94 BUFR and Part C</u>	<u>New GRIB definition templates. New BUFR sequences for satellite sounding data, observations from a single glider trajectory profile, aerosol optical depth and TROPICS.</u>	<u>INFOM/SC-IMT/ET-Data</u>	<u>Fast-track procedures 2023-2</u>
	<u>Part B – Binary Codes: FM ...</u>	<u>New section on CF-NetCDF</u>	<u>INFOM/SC-IMT/ET-Data</u>	<u>EC-76</u>
	<u>Part C - Common features to Binary and Alphanumeric Codes</u>	<u>New section on GBON reporting practices</u>	<u>INFOM/SC-IMT/ET-Data</u>	<u>EC-76</u>

	<u>Where needed</u>	<u>Edits based on WMO reform</u>	<u>INFOM/SC-IMT/ET-Data</u>	<u>EC-76</u>
	<u>General Provisions</u>	<u>Remove section and its Appendix</u>	<u>SERCOM/INFCOM</u>	<u>EC-76/Cg-19</u>

Provisional Copy
2023

Provisional Copy
2023

CONTENTS

VOLUME I.2 – INTERNATIONAL CODES

	<i>Page</i>
Introduction	vii
General provisions	ix
Definitions	xix
Acronyms	xxvi
 Part B – Binary Codes	
a. FM system of numbering binary codes	I.2 – Bi – 1
b. List of binary codes with their specifications and associated code tables	I.2 – GRIB Reg – 1
FM 92 GRIB – General regularly distributed information in binary form	
I.2 – GRIB Reg – 1	
GRIB – Identification templates	
I.2 – GRIB IT – 1	
GRIB – Grid definition templates	
I.2 – GRIB GDT – 1	
GRIB – Product definition templates	
I.2 – GRIB PDT – 1	
GRIB – Data representation templates	
I.2 – GRIB DRT – 1	
GRIB – Data templates	
I.2 – GRIB DT – 1	
GRIB – Code and flag tables	
I.2 – GRIB CF0 – 1	
Attachment I: Definition of a triangular grid based on an icosahedron	
I.2 – Att.I/GRIB – 1	
Attachment II: Arakawa grids	
I.2 – Att.II/GRIB – 1	
Attachment III: Distribution functions in GRIB	
I.2 – Att.III/GRIB – 1	
Attachment IV: Definition of "tiles" with time-dependent attributes	
I.2 – Att.IV/GRIB – 1	
FM 94 BUFR – Binary universal form for the representation of meteorological data	
I.2 – BUFR Reg – 1	
BUFR Table A – Data category	
I.2 – BUFR Table A – 1	
BUFR/CREX Table B – Classification of elements	
I.2 – BUFR/CREX Table B – 1	
BUFR Table C – Data description operators	
I.2 – BUFR Table C – 1	
BUFR Table D – List of common sequences	
I.2 – BUFR Table D – 1	
Code tables and flag tables associated with BUFR/CREX Table B	
I.2 – CODE/FLAG Tables – 1	

Part C – Common Features to Binary and Alphanumeric Codes

a. FM system of numbering table-driven alphanumeric codes	I.2 – Co – 1
b. List of table-driven alphanumeric codes with their specifications and associated code tables	I.2 – CREX Reg – 1
FM 95 CREX – Character form for the representation and exchange of data	I.2 – CREX Reg – 1
CREX Table A – Data category	I.2 – CREX Table A – 1
CREX Table B – Classification of elements	I.2 – CREX Table B – 1
CREX Table C – Data description operators	I.2 – CREX Table C – 1
CREX Table D – List of common sequences	I.2 – CREX Table D – 1
Attachment: CREX template examples	I.2 – Att.CREX – 1
c. Common code tables to binary and alphanumeric codes	I.2 – Co Tab – 1
d. Regulations for reporting traditional observation data in Table-Driven Code Forms (TDCF): BUFR or CREX	I.2 – RegTradObs – 1
B/C1 – Regulations for reporting SYNOP data in TDCF	I.2 – RegTradObs/BC1 – 1
Annex: Regional regulations for reporting SYNOP data in TDCF	
B/C5 – Regulations for reporting SYNOP MOBIL data in TDCF	I.2 – RegTradObs/BC5 – 1
B/C10 – Regulations for reporting SHIP data in TDCF	I.2 – RegTradObs/BC10 – 1
B/C20 – Regulations for reporting PILOT, PILOT SHIP and PILOT MOBIL data in TDCF	I.2 – RegTradObs/BC20 – 1
B/C25 – Regulations for reporting TEMP, TEMP SHIP and TEMP MOBIL data in TDCF	I.2 – RegTradObs/BC25 – 1
Annex I: Regional regulations for reporting TEMP, TEMP SHIP and TEMP MOBIL data in TDCF	
Annex II: List of parameters for representation of additional information on sounding instrumentation	
B/C26 – Regulations for reporting TEMP DROP data in TDCF	I.2 – RegTradObs/BC26 – 1
B/C30 – Regulations for reporting CLIMAT data in TDCF	I.2 – RegTradObs/BC30 – 1
B/C32 – Regulations for reporting CLIMAT SHIP data in TDC	I.2 – RegTradObs/BC32 – 1
Attachment I: Examples of templates for the transmission in BUFR or CREX of other data types	I.2 – Att.I/Co – 1
Attachment II: List of alphanumeric code tables related to BUFR and CREX code tables and flag tables	I.2 – Att.II/Co – 1

INTRODUCTION

Volume I of the *Manual on Codes* contains WMO international codes for meteorological data and other geophysical data relating to meteorology; it constitutes Annex II to the *Technical Regulations* (WMO-No. 49) and has therefore the status of a Technical Regulation. It is issued in three volumes: Volume I.1, containing Part A; Volume I.2, containing Part B and Part C; and Volume I.3 containing Part D.

Coded messages are used for the international exchange of meteorological information comprising observational data provided by the [WMO Integrated Global Observing System](#) ~~World Weather Watch (WWW) Global Observing System~~ and processed data provided by the [WMO Integrated Processing and Prediction System \(formerly WWW Global Data-processing and Forecasting System\)](#). Coded messages are also used for the international exchange of observed and processed data required in specific applications of meteorology to various human activities and for exchanges of information related to meteorology.

The codes are composed of a set of CODE FORMS and BINARY CODES made up of SYMBOLIC LETTERS (or groups of letters) representing meteorological or, as the case may be, other geophysical elements. In messages, these symbolic letters (or groups of letters) are transcribed into figures indicating the value or the state of the elements described. SPECIFICATIONS have been defined for the various symbolic letters to permit their transcription into figures. In some cases, the specification of the symbolic letter is sufficient to permit a direct transcription into figures. In other cases, it requires the use of CODE FIGURES, the specifications of which are given in CODE TABLES. Furthermore, a certain number of SYMBOLIC WORDS and SYMBOLIC FIGURE GROUPS have been developed for use as code names, code words, symbolic prefixes or indicator groups.

Rules concerning the selection of code forms to be exchanged for international purposes, and the selection of their symbolic words, figure groups and letters, are laid down in the *Technical Regulations* (WMO-No. 49), Volume I, Part II, section 2 (2015 edition, updated in 2017). These code forms are contained in Volume I of the *Manual on Codes*, issued as Volume I.1 – Part A, Volume I.2 – Part B and Part C, and Volume I.3 – Part D.

Apart from these international codes, several sets of *regional codes* exist which are intended only for exchanges within a given WMO Region. These codes are contained in Volume II of the *Manual on Codes*, which also contains descriptions of the following:

- Regional coding procedures for the use of international code forms;
- National coding practices in the use of international or regional codes of which the WMO Secretariat has been informed;
- National code forms.

A number of special codes that are used in messages exchanged over the WWW Global Telecommunication System circuits, and which comprise ice and satellite ephemeris codes, are included in Volume II as an appendix.

VOLUME I.1:

Part A – Alphanumeric Codes consists of five sections. The standard coding procedures are distinguished by the use of the term “shall” in the English text, and by suitable equivalent terms in the French, Russian and Spanish texts. Where national practices do not conform with these regulations, Members concerned shall formally notify the Secretary-General of WMO for the benefit of other Members.

INTRODUCTION

VOLUME I.2:

Part B – Binary Codes consists of the list of binary codes with their specifications and associated code tables. Explanatory notes are sometimes added to regulations.

Part C – Common Features to Binary and Alphanumeric Codes consists of the list of table-driven alphanumeric codes with their specifications and associated code tables, and of common code tables to binary and alphanumeric codes.

The attachments (yellow background) to Volume I.2 do not have the status of WMO Technical Regulations and are given for information only.

This edition of Volume I.2 of the *Manual on Codes* replaces the 2011 edition.

VOLUME I.3:

Part D – Representations derived from data models consists of the specification of the list of standard representations derived from data models, including those using extensible markup language (XML), with their specifications and associated code tables.

Notes:

1. The General Provisions to the Technical Regulations, formerly reproduced as a part of the present manual, can be found in the publication *Technical Regulations (WMO-No. 49), Volume I – General Meteorological Standards and Recommended Practices*.
2. The former appendix to the General Provisions, entitled "Procedures for amending WMO manuals and guides that are the responsibility of the Commission for Observation, Infrastructure and Information Systems", previously a part of the present manual, has been updated and can be found in the publication *Rules of Procedure for Technical Commissions (WMO-No. 1240)*.

GENERAL PROVISIONS

1. — The *Technical Regulations* (WMO No. 49) of the World Meteorological Organization are presented in three volumes:

Volume I — General meteorological standards and recommended practices

Volume II — Meteorological service for international air navigation

Volume III — Hydrology

Purpose of the Technical Regulations

2. — The Technical Regulations are determined by the World Meteorological Congress in accordance with Article 8 (d) of the Convention.

3. — These Regulations are designed:

- (a) — To facilitate cooperation in meteorology and hydrology among Members;
- (b) — To meet, in the most effective manner, specific needs in the various fields of application of meteorology and operational hydrology in the international sphere;
- (c) — To ensure adequate uniformity and standardization in the practices and procedures employed in achieving (a) and (b) above.

Types of Regulations

4. — The Technical Regulations comprise *standard* practices and procedures, *recommended* practices and procedures, and references to constants, definitions, formulas and specifications.

5. — The definitions of these three types of Regulations are as follows:

The *standard* practices and procedures:

- (a) — Shall be the practices and procedures that Members are required to follow or implement;
- (b) — Shall have the status of requirements in a technical resolution in respect of which Article 9 (b) of the Convention is applicable;
- (c) — Shall invariably be distinguished by the use of the term *shall* in the English text, and by suitable equivalent terms in the Arabic, Chinese, French, Russian and Spanish texts.

The *recommended* practices and procedures:

- (a) — Shall be the practices and procedures with which Members are urged to comply;
- (b) — Shall have the status of recommendations to Members, to which Article 9 (b) of the Convention shall not be applied;
- (c) — Shall be distinguished by the use of the term *should* in the English text (except where otherwise provided by decision of Congress) and by suitable equivalent terms in the Arabic, Chinese, French, Russian and Spanish texts.

GENERAL PROVISIONS

References to constants, definitions, formulas and specifications:

Members should use the definitions, formulas, values of constants and specifications indicated in the relevant Guides published by the Organization.

6. In accordance with the above definitions, Members shall do their utmost to implement the *standard* practices and procedures. In accordance with Article 9 (b) of the Convention and in conformity with Regulation 101 of the General Regulations, Members shall formally notify the Secretary General, in writing, of their intention to apply the *standard* practices and procedures of the Technical Regulations, except those for which they have lodged a specific deviation. Members shall also inform the Secretary General, at least three months in advance, of any change in the degree of their implementation of a *standard* practice or procedure as previously notified and the effective date of the change.

7. Members are urged to comply with *recommended* practices and procedures, but it is not necessary to notify the Secretary General of non-observance except with regard to practices and procedures contained in Volume II.

8. In order to clarify the status of the various Regulations, the *standard* practices and procedures are distinguished from the *recommended* practices and procedures by a difference in typographical practice, as indicated in the editorial note.

Status of annexes and appendices

9. The following annexes to the *Technical Regulations* (Volumes I to III), also called Manuals, are published separately and contain regulatory material. They are established by decision of Congress and are intended to facilitate the application of Technical Regulations to specific fields. Manuals may contain both *standard* and *recommended* practices and procedures.

I—*International Cloud Atlas* (WMO No. 407)—Manual on the Observation of Clouds and Other Meteors, sections 1, 2.1.1, 2.1.4, 2.1.5, 2.2.2, 1 to 4 in 2.3.1 to 2.3.10 (for example, 2.3.1.1, 2.3.1.2, etc.), 2.8.2, 2.8.3, 2.8.5, 3.1 and the definitions (in grey shaded boxes) of 3.2;

II—*Manual on Codes* (WMO No. 306), Volume I;

III—*Manual on the Global Telecommunication System* (WMO No. 386);

IV—*Manual on the Global Data processing and Forecasting System* (WMO No. 485);

VI—*Manual on Marine Meteorological Services* (WMO No. 558), Volume I;

VII—*Manual on the WMO Information System* (WMO No. 1060);

VIII—*Manual on the WMO Integrated Global Observing System* (WMO No. 1160).

IX—*Manual on the High quality Global Data Management Framework for Climate* (WMO No. 1238).

10. Texts called appendices, appearing in the *Technical Regulations* or in an annex to the *Technical Regulations*, have the same status as the Regulations to which they refer.

GENERAL PROVISIONS

Status of notes and attachments

11. — Certain notes (preceded by the indication "Note") are included in the *Technical Regulations* for explanatory purposes; they may, for instance, refer to relevant WMO Guides and publications. These notes do not have the status of Technical Regulations.

12. — The *Technical Regulations* may also include attachments, which usually contain detailed guidelines related to *standard* and *recommended* practices and procedures. Attachments, however, do not have regulatory status.

Updating of the *Technical Regulations* and their annexes (Manuals)

13. — The *Technical Regulations* are updated, as necessary, in the light of developments in meteorology and hydrology and related techniques, and in the application of meteorology and operational hydrology. Certain principles previously agreed upon by Congress and applied in the selection of material for inclusion in the Technical Regulations are reproduced below. These principles provide guidance for constituent bodies, in particular technical commissions, when dealing with matters pertaining to the Technical Regulations:

- (a) Technical commissions should not recommend that a Regulation be a *standard* practice unless it is supported by a strong majority;
- (b) Technical Regulations should contain appropriate instructions to Members regarding implementation of the provision in question;
- (c) No major changes should be made to the Technical Regulations without consulting the appropriate technical commissions;
- (d) Any amendments to the Technical Regulations submitted by Members or by constituent bodies should be communicated to all Members at least three months before they are submitted to Congress.

14. — Amendments to the *Technical Regulations* — as a rule — are approved by Congress.

15. — If a recommendation for an amendment is made by a session of the appropriate technical commission and if the new regulation needs to be implemented before the next session of Congress, the Executive Council may, on behalf of the Organization, approve the amendment in accordance with Article 14 (c) of the Convention. Amendments to annexes to the *Technical Regulations* proposed by the appropriate technical commissions are normally approved by the Executive Council.

16. — If a recommendation for an amendment is made by the appropriate technical commission and the implementation of the new regulation is urgent, the President of the Organization may, on behalf of the Executive Council, take action as provided by Regulation 8 (5) of the General Regulations.

Note: — A simple (fast-track) procedure may be used for amendments to technical specifications in Annexes II (*Manual on Codes* (WMO-No. 306)), III (*Manual on the Global Telecommunication System* (WMO-No. 386)), IV (*Manual on the Global Data-processing and Forecasting System* (WMO-No. 485)), VII (*Manual on the WMO Information System* (WMO-No. 1060)) and VIII (*Manual on the WMO Integrated Global Observing System* (WMO-No. 1160)). Application of the simple (fast-track) procedure is defined in the appendix to these General Provisions.

17. — After each session of Congress (every four years), a new edition of the *Technical Regulations*, including the amendments approved by Congress, is issued. With

GENERAL PROVISIONS

regard to the amendments between sessions of Congress, Volumes I and III of the *Technical Regulations* are updated, as necessary, upon approval of changes thereto by the Executive Council. The *Technical Regulations* updated as a result of an approved amendment by the Executive Council are considered a new update of the current edition. The material in Volume II is prepared by the World Meteorological Organization and the International Civil Aviation Organization working in close cooperation, in accordance with the Working Arrangements agreed by these Organizations. In order to ensure consistency between Volume II and Annex 3 to the Convention on International Civil Aviation—*Meteorological Service for International Air Navigation*, the issuance of amendments to Volume II is synchronized with the respective amendments to Annex 3 by the International Civil Aviation Organization.

Note: — Editions are identified by the year of the respective session of Congress whereas updates are identified by the year of approval by the Executive Council, for example “Updated in 2018”.

WMO Guides

18. — In addition to the *Technical Regulations*, appropriate Guides are published by the Organization. They describe practices, procedures and specifications which Members are invited to follow or implement in establishing and conducting their arrangements for compliance with the Technical Regulations, and in otherwise developing meteorological and hydrological services in their respective countries. The Guides are updated, as necessary, in the light of scientific and technological developments in hydrometeorology, climatology and their applications. The technical commissions are responsible for the selection of material to be included in the Guides. These Guides and their subsequent amendments shall be considered by the Executive Council.

~~APPENDIX. PROCEDURES FOR AMENDING WMO MANUALS AND GUIDES THAT ARE THE RESPONSIBILITY OF THE COMMISSION FOR BASIC SYSTEMS~~

~~1. DESIGNATION OF RESPONSIBLE COMMITTEES~~

~~The Commission for Basic Systems (CBS) shall, for each Manual and Guide, designate one of its Open Programme Area Groups (OPAGs) as being responsible for that Manual and its associated technical guides. The Open Programme Area Group may choose to designate one of its Expert Teams as the designated committee for managing changes to all or part of that Manual; if no Expert Team is designated, the Implementation Coordination Team for the OPAG takes on the role of the designated committee.~~

~~2. GENERAL VALIDATION AND IMPLEMENTATION PROCEDURES~~

~~2.1 Proposal of amendments~~

~~Amendments to a Manual or a Guide managed by CBS shall be proposed in writing to the Secretariat. The proposal shall specify the needs, purposes and requirements and include information on a contact point for technical matters.~~

~~2.2 Drafting recommendation~~

~~The designated committee for the relevant part of a Manual or a Guide, supported by the Secretariat, shall validate the stated requirement (unless it is consequential to an amendment to the WMO Technical Regulations) and develop a draft recommendation to respond to the requirement, as appropriate.~~

~~2.3 Procedures for approval~~

~~After a draft recommendation of the designated committee is validated in accordance with the procedure given in section 7 below, depending on the type of amendments, the designated committee should select one of the following procedures for the approval of the amendments:~~

- ~~(a) Simple (fast track) procedure (see section 3 below);~~
- ~~(b) Standard (adoption of amendments between CBS sessions) procedure (see section 4 below);~~
- ~~(c) Complex (adoption of amendments during CBS sessions) procedure (see section 5 below).~~

~~2.4 Date of implementation~~

~~The designated committee should define an implementation date in order to give WMO Members sufficient time to implement the amendments after the date of notification. For procedures other than the simple (fast track) one, if the time between the date of notification and implementation date is less than six months, the designated committee shall document the reasons for its decision.~~

GENERAL PROVISIONS

2.5 — Urgent introduction

Regardless of the above procedures, as an exceptional measure, the following procedure accommodates urgent user needs to introduce elements in lists of technical details, or to correct errors:

- (a) A draft recommendation developed by the designated committee shall be validated according to the steps defined in section 7 below;
- (b) The draft recommendation for pre-operational use of a list entry, which can be used in operational data and products, shall be approved by the chair of the designated committee and the chair of the responsible OPAG, and the president of CBS. A listing of pre-operational list entries is kept online on the WMO web server;
- (c) Pre-operational list entries shall then be submitted for approval by one of the procedures in 2.3 above for operational use;
- (d) Any version numbers associated with the technical implementation should be incremented at the least significant level.

2.6 — Issuing updated version

Once amendments to a Manual or a Guide are adopted, an updated version of the relevant part of the Manual shall be issued in the languages agreed for its publication. The Secretariat shall inform all Members of the availability of a new updated version of that part at the date of notification mentioned in 2.4 above. If amendments are not incorporated into the published text of the relevant Manual or Guide at the time of the amendment, there should be a mechanism to publish the amendments at the time of their implementation and to retain a permanent record of the sequence of amendments.

3. — SIMPLE (FAST TRACK) PROCEDURE

3.1 — Scope

The simple (fast track) procedure shall be used only for changes to components of the Manual that have been designated and marked as "technical specifications to which the simple (fast track) procedure for the approval of amendments may be applied".

Note: — An example would be the addition of code list items in the *Manual on Codes* (WMO-No. 306).

3.2 — Endorsement

Draft recommendations developed by the responsible committee, including a date for implementation of the amendments, shall be submitted to the chair of the relevant OPAG for endorsement.

3.3 — Approval**3.3.1 — Minor adjustments**

Correcting typographical errors in descriptive text is considered a minor adjustment, and will be done by the Secretariat in consultation with the president of CBS. See Figure 1.




Figure 1. Adoption of amendments to a Manual by minor adjustment

3.3.2 — Other types of amendments

For other types of amendments, the English version of the draft recommendation, including a date of implementation, should be distributed to the focal points for matters concerning the relevant Manual for comments, with a deadline of two months for the reply. It should then be submitted to the president of CBS for consultation with presidents of technical commissions affected by the change. If endorsed by the president of CBS, the change should be passed to the President of WMO for consideration and adoption on behalf of the Executive Council (EC).

3.3.3 — Frequency

The implementation of amendments approved through the simple (fast-track) procedure can be twice a year in May and November. See Figure 2.




Figure 2. Adoption of amendments to a Manual by simple (fast-track) procedure

4. — STANDARD (ADOPTION OF AMENDMENTS BETWEEN CBS SESSIONS) PROCEDURE**4.1 — Scope**

The standard (adoption of amendments between CBS sessions) procedure shall be used for changes that have an operational impact on those Members who do not wish to exploit the change, but that have only minor financial impact, or that are required to implement changes in the *Technical Regulations* (WMO No. 49), Volume II—Meteorological Service for International Air Navigation.

4.2 — Approval of draft recommendations

For the direct adoption of amendments between CBS sessions, the draft recommendation developed by the designated committee, including a date of implementation of the amendments, shall be submitted to the chair of the responsible OPAG and president and vice-president of CBS for approval. The president of CBS shall consult with the presidents of technical commissions affected by the change. In the case of recommendations in response to changes in the *Technical Regulations* (WMO No. 49), Volume II—Meteorological Service for International Air Navigation, the president of CBS shall consult with the president of the Commission for Aeronautical Meteorology.

4.3 — Circulation to Members

Upon approval of the president of CBS, the Secretariat sends the recommendation to all Members, in the languages in which the Manual is published, including a date of implementation of the amendments, for comments to be submitted within two months following the dispatch of the amendments. If the recommendation is sent to Members via electronic mail, there shall be public announcement of the amendment process including dates, for example by WMO Operational Newsletter on the WMO website, to ensure all relevant Members are informed.

4.4 — Agreement

Those Members not having replied within the two months following the dispatch of the amendments are implicitly considered as having agreed with the amendments.

4.5 — Coordination

Members are invited to designate a focal point responsible to discuss any comments/disagreements with the designated committee. If the discussion between the designated committee and the focal point cannot result in an agreement on a specific amendment by a Member, this amendment will be reconsidered by the designated committee. If a Member cannot agree that the financial or operational impact is minor, the redrafted amendment shall be approved by the complex (adoption of amendments during CBS sessions) procedure described in section 5 below.

4.6 — Notification

Once amendments are agreed by Members, and after consultation with the chair of the responsible OPAG, the vice-president of CBS and the president of CBS (who should consult with presidents of other commissions affected by the change), the Secretariat notifies at the same time the Members and the members of the Executive Council of the approved amendments and of the date of their implementation. See Figure 3.




Figure 3. Adoption of between CBS sessions

5. ~~COMPLEX (ADOPTION OF AMENDMENTS DURING CBS SESSIONS) PROCEDURE~~

5.1 ~~Scope~~

The complex (adoption of amendments during CBS sessions) procedure shall be used for changes for which the simple (fast track) procedure or standard (adoption of amendments between CBS sessions) procedure cannot be applied.

5.2 ~~Procedure~~

For the adoption of amendments during CBS sessions, the designated committee submits its recommendation, including a date of implementation of the amendments, to the Implementation Coordination Team of the responsible Open Programme Area Group. The recommendation is then passed to the presidents of technical commissions affected by the change for consultation, and to a CBS session that shall be invited to consider comments submitted by presidents of technical commissions. The document for the CBS session shall be distributed not later than 45 days before the opening of the session. Following the CBS session, the recommendation shall then be submitted to a session of the Executive Council for decision. See Figure 4.




Figure 4. ~~Adoption of amendments during CBS sessions~~

6. ~~PROCEDURE FOR THE CORRECTION OF EXISTING MANUAL CONTENTS~~

6.1 ~~Correcting errors in items within Manuals~~

Where a minor error in the specification of an item that defines elements within a Manual is found, for example, a typing error or an incomplete definition, the item shall be amended and re-published. Any version numbers associated with items edited as a result of the change should be incremented at their lowest level of significance. If, however, the change has an impact on the meaning of the item, then a new item should be created and the existing (erroneous) item marked as deprecated. This situation is considered a minor adjustment according to 3.3.1 above.

Note: — An example of an item for which this type of change applies is a code list entry for the Table Driven Code Forms or WMO Core Metadata Profile, in which the description contains typographical errors that can be corrected without changing the meaning of the description.

6.2 ~~Correcting an error in the specification of how conformance with the requirements of the Manual can be checked~~

If an erroneous specification of a conformance checking rule is found, the preferred approach is to add a new specification using the simple (fast-track) procedure or standard (adoption of amendments between CBS sessions) procedure approach. The new conformance checking rule should be used instead of the old. An appropriate explanation shall be added to the description of the conformance checking rule to clarify the practice along with the date of the change.

Note: ~~An example of such a change would be correcting a conformance checking rule in the WMO Core Metadata Profile.~~

6.3 ~~Submission of corrections to errors~~

Such changes shall be submitted through the simple (fast-track) procedure.

7. ~~VALIDATION PROCEDURE~~

7.1 ~~Documentation of need and purpose~~

The need for, and the purpose of, the proposal for changes should be documented.

7.2 ~~Documentation of result~~

This documentation shall include the results of validation testing of the proposal as described in 7.3 below.

7.3 ~~Testing with relevant applications~~

For changes that have an impact on automated processing systems, the extent of the testing required before validation should be decided by the designated committee on a case-by-case basis, depending on the nature of the change. Changes involving a relatively high risk and/or impact on the systems should be tested by the use of at least two independently developed tool sets and two independent centres. In that case, results should be made available to the designated committee with a view to verifying the technical specifications.

DEFINITIONS

Actual time of observation.

- (1) In the case of a surface synoptic observation, the time at which the barometer is read.
- (2) In the case of upper-air observations, the time at which the balloon, parachute or rocket is actually released.

All-components schema document. An XML schema document that includes, either directly, or indirectly, all the components defined and declared in a namespace.

Alpine glow. Pink or yellow colouring assumed by mountain tops opposite the Sun when it is only just below the horizon before it rises and after it sets. This phenomenon vanishes after a brief interval of blue colouring, when the Earth's shadow reaches these summits.

Anomalous propagation. Propagation of radio energy in abnormal conditions of vertical distribution of refractive index, in association with abnormal distribution of atmospheric temperature and humidity. Use of the term is mainly confined to conditions in which abnormally large distances of propagation are attained.

Application schema. A conceptual schema for data required by one or more applications. (Source: International Organization for Standardization (ISO) 19101:2002, definition 4.2)

Atmospheric – Sferic. Electromagnetic wave resulting from an electric discharge (lightning) in the atmosphere.

Automatic station. Meteorological station at which instruments make and transmit observations, the conversion to code form for international exchange being made either directly or at an editing station.

Aviation routine weather report. A statement of the observed meteorological conditions related to a specified time and location, issued on a routine basis for use in international air navigation.

BUFR – Binary universal form for the representation of meteorological data. BUFR is the name of a binary code for the exchange and storage of data.

BUFR message. A single complete BUFR entity.

Category. The lists of sequence descriptors tabulated in BUFR or CREX Table D are categorized according to their application; categories are provided for non-meteorological sequences, for various types of meteorological sequences, and for sequences which define reports, or major subsets of reports.

Class. A set of elements tabulated together in BUFR/CREX Table B.

Condensation trails (contrails). Clouds which form in the wake of an aircraft when the atmosphere at flying level is sufficiently cold and humid.

Coordinate class. Classes 0–9 inclusive in BUFR/CREX Table B define elements which assist in the definition of elements from subsequent classes; each of these classes is referred to as a coordinate class.

DEFINITIONS

CREX – Character form for the representation and exchange of data. CREX is the name of a table-driven alphanumeric code for the exchange and storage of data.

Data description operator. Operators which define replication or the operations listed in BUFR or CREX Table C.

Data entity. A single data item.

Data subset. A set of data corresponding to the data description in a BUFR or CREX message; for observational data, a data subset usually corresponds to one observation.

Day darkness. Sky covered with clouds with very strong optical thickness (dark clouds) having a threatening appearance.

Descriptor. An entity entered within the Data description section to describe or define data; a descriptor may take the form of an element descriptor, a replication operator, an operator descriptor, or a sequence descriptor.

Dry thunderstorm. A thunderstorm without precipitation reaching the ground (distinct from a nearby thunderstorm with precipitation reaching the ground but not at the station at the time of observation).

Dust wall or sand wall. Front of a duststorm or sandstorm, having the appearance of a gigantic high wall which moves more or less rapidly.

Element descriptor. A descriptor containing a code figure reference to BUFR/CREX Table B; the referenced entry defines an element, together with the units, scale factor, reference value and data width to be used to represent that element as data.

Equatorial region. For the purpose of the analysis codes, the region between 30 °N and 30 °S latitudes.

Extensible markup language (XML). A markup language that defines a set of rules for encoding documents in a format that is both human-readable and machine-readable. It is defined in the World Wide Web Consortium (W3C) [XML 1.0 Specification](#).

Geography markup language (GML). An XML encoding in compliance with ISO 19118 for the transport and storage of geographic information modelled in accordance with the conceptual modelling framework used in the ISO 19100 series of International Standards and including both the spatial and non-spatial properties of geographic features.

Geometric altitude. Vertical distance (Z) of a level, a point or an object considered as a point, measured from mean sea level.

Geopotential. That potential with which the Earth's gravitational field is associated. It is equivalent to the potential energy of unit mass relative to a standard level (mean sea level by convention) and is numerically equal to the work which would be done against gravity in raising the unit mass from sea level to the level at which the mass is located.

Geopotential ϕ at geometric height z is given by

$$\phi = \int_0^z g \, dz$$

where g is the acceleration of gravity.

DEFINITIONS

Geopotential height. Height of a point in the atmosphere expressed in units (geopotential metres) proportional to $g/9.8$ the geopotential at that height. Geopotential height expressed in geopotential metres is approximately equal to times the geometric height expressed in (geometric) metres, g being the local acceleration of gravity.

GML application schema. An application schema written in XML schema in accordance with the rules specified in ISO 19136:2007.

GML document. An XML document with a root element that is one of the XML elements AbstractFeature, Dictionary or TopoComplex specified in the GML schema or any element of a substitution group of any of these XML elements.

GML schema. The XML schema components in the XML namespace <http://www.opengis.net/gml/3.2> as specified in ISO 19136:2007.

Haboob. A strong wind and duststorm or sandstorm in northern and central Sudan. Its average duration is three hours; the average maximum wind velocity is over 15 m s^{-1} . The dust or sand forms a dense whirling wall which may be 1 000 m high; it is often preceded by isolated dust whirls. Haboobs usually occur after a few days of rising temperature and falling pressure.

Ice crust (ice slick).

- (1) A type of snow crust; a layer of ice, thicker than a film crust, upon a snow surface. It is formed by the freezing of melt water or rainwater which has flowed into it.
- (2) See *Ice rind*.

Ice rind. A thin but hard layer of sea ice, river ice or lake ice. Apparently this term is used in at least two ways: (a) for a new encrustation upon old ice; and (b) for a single layer of ice usually found in bays and fjords where freshwater freezes on top of slightly colder sea water.

Instrumental wave data. Data on measured characteristics relating to period and height of the wave motion of the sea surface.

Inversion (layer). Atmospheric layer, horizontal or approximately so, in which the temperature increases with increasing height.

Isothermal layer. Atmospheric layer through which there is no change of temperature with height.

Jet stream. Flat tubular current of air, quasi-horizontal, whose axis is along a line of maximum speed and which is characterized not only by great speeds but also by strong transverse gradients of speed.

Line squall. Squall which occurs along a squall line.

Lithometeor. Meteor consisting of an ensemble of particles most of which are solid and non-aqueous. The particles are more or less suspended in the air, or lifted by the wind from the ground.

Mountain waves. Oscillatory motions of the atmosphere induced by flow over a mountain; such waves are formed over and to the lee of the mountain or mountain chain.

Namespace. A collection of names, identified by a uniform resource identifier reference, which are used in XML documents as element names and attribute names.

DEFINITIONS

Normals. Period averages computed for over a uniform and relatively long period comprising at least three consecutive 10-year periods.

Obscured sky. Occasions of hydrometeors or lithometeors which are so dense as to make it impossible to tell whether there is cloud above or not.

Ocean weather station. A station aboard a suitably equipped and staffed ship that endeavours to remain at a fixed sea position and that makes and reports surface and upper-air observations and may also make and report subsurface observations.

Operator descriptor. A descriptor containing a code figure reference to BUFR or CREX Table C, together with data to be used as an operand.

Past weather. Predominant characteristic of weather which had existed at the station during a given period of time.

Persistent condensation trail. Long-lived condensation trails which have spread to form clouds having the appearance of cirrus or patches of cirrocumulus or cirrostratus. It is sometimes impossible to distinguish such clouds from other cirrus, cirrocumulus or cirrostratus.

Present weather. Weather existing at the time of observation, or under certain conditions, during the hour preceding the time of observation.

Prevailing visibility. The greatest visibility value, observed in accordance with the definition of "visibility", which is reached within at least half the horizon circle or within at least half of the surface of the aerodrome. These areas could comprise contiguous or non-contiguous sectors.

Note: This value may be assessed by human observation and/or instrumented systems. When instruments are installed, they are used to obtain the best estimate of the prevailing visibility.

Purple light. Glow with a hue varying between pink and red, which is to be seen in the direction of the Sun before it rises and after it sets and is about 3° to 6° below the horizon. It takes the form of a segment of a more or less large luminous disc which appears above the horizon.

Reference value. All data are represented within a BUFR or CREX message by positive integers; to enable negative values to be represented, suitable negative base values are specified as reference values. The true value is obtained by addition of the reference value and the data as represented.

Replication descriptor. A special descriptor is reserved to define the replication operation; it is used to enable a given number of subsequent descriptors to be replicated a given number of times.

Root element. Each XML document has exactly one root element. This element, also known as the document element, encloses all the other elements and is therefore the sole parent element to all the other elements. The root element provides the starting point for processing the document.

Runway visual range. The range over which the pilot of an aircraft on the centre line of the runway can see the runway markings or the lights delineating the runway or identifying its centre line.

Schematron. A definition language for making assertions about patterns found in XML documents, differing in basic concept from other schema languages in that it is not based on grammars but on finding patterns in the parsed document.

DEFINITIONS

Sea station. An observing station situated at sea. Sea stations include ships, ocean weather stations and stations on fixed or drifting platforms (rigs, platforms, lightships and buoys).

Section. A logical subdivision of a BUFR or CREX message, to aid description and definition.

Sequence descriptor. A descriptor used as a code figure to reference a single entry in BUFR or CREX Table D; the referenced entry contains a list of descriptors to be substituted for the sequence descriptor.

Severe line squall. Severe squall which occurs along squall line (see *Line squall*).

Snow haze. A suspension in the air of numerous minute snow particles, considerably reducing the visibility at the Earth's surface (visibility in snow haze often decreases to 50 m). Snow haze is observed most frequently in Arctic regions, before or after a snowstorm.

Squall. Atmospheric phenomenon characterized by a very large variation of wind speed: it begins suddenly, has a duration of the order of minutes and decreases rather suddenly in speed. It is often accompanied by a shower or thunderstorm.

Squall line. Fictitious moving line, sometimes of considerable extent, along which squall phenomena occur.

Sun pillar. Pillar of white light, which may or may not be continuous, which may be observed vertically above or below the sun. Sun pillars are most frequently observed near sunrise or sunset; they may extend to about 20° above the Sun, and generally end in a point. When a sun pillar appears together with a well-developed parhelic circle, a sun cross may appear at their intersection.

Synoptic hour. Hour, expressed in terms of universal time coordinated (UTC), at which, by international agreement, meteorological observations are made simultaneously throughout the globe.

Synoptic observation. A surface or upper-air observation made at standard time.

Synoptic surface observation. Synoptic observation, other than an upper-air observation, made by an observer or an automatic weather station on the Earth's surface.

Template. Description of the standardized layout of a set of data entities.

Tropical (Tropic). Pertaining to that region of the Earth's surface lying between the Tropic of Cancer and Tropic of Capricorn at 23° 30' N and S, respectively.

Tropical cyclone. Cyclone of tropical origin of small diameter (some hundreds of kilometres) with minimum surface pressure in some cases less than 900 hPa, very violent winds and torrential rain; sometimes accompanied by thunderstorms. It usually contains a central region, known as the "eye" of the storm, with a diameter of the order of some tens of kilometres, and with light winds and more or less lightly clouded sky.

Tropical revolving storm. Tropical cyclone.

DEFINITIONS

Tropopause.

- (1) Upper limit of the troposphere. By convention, the “first tropopause” is defined as the lowest level at which the lapse rate decreases to 2 °C km⁻¹ or less, provided also the average lapse rate between this level and all higher levels within 2 km does not exceed 2 °C km⁻¹.
- (2) If, above the first tropopause, the average lapse rate between any level and all higher levels within 1 km exceeds 3 °C km⁻¹, then a “second tropopause” is defined by the same criterion as under (1). This second tropopause may be either within or above the 1-km layer.

Twilight glow. See Purple light.

Twilight glow in the mountains (Alpenglühen). See Alpine glow.

Uniform resource identifier (URI). A compact sequence of characters that identifies an abstract or physical resource. URI syntax is defined in the Internet Engineering Task Force (IETF) [RFC 3986](#).

Unit of geopotential ($H_{m'}$). 1 standard geopotential metre = 0.980 665 dynamic metre

$$H_{m'} = \frac{1}{9.80665} \int_0^z g(z) dz$$

where

$g(z)$ = acceleration of gravity, in m s⁻², as a function of geometric height;

z = geometric height, in metres;

$H_{m'}$ = geopotential, in geopotential metres.

Vertical visibility. Maximum distance at which an observer can see and identify an object on the same vertical as himself, above or below.

Visibility (for aeronautical purposes). Visibility for aeronautical purposes is the greater of:

- (a) The greatest distance at which a black object of suitable dimensions, situated near the ground, can be seen and recognized when observed against a bright background;
- (b) The greatest distance at which lights in the vicinity of 1 000 candelas can be seen and identified against an unlit background.

Note: The two distances have different values in air of a given extinction coefficient, and the latter (b) varies with the background illumination. The former (a) is represented by the meteorological optical range (MOR).

Whiteout. Uniformly white appearance of the landscape when the ground is snow covered and the sky is uniformly covered with clouds. An atmospheric optical phenomenon of the polar regions in which the observer appears to be engulfed in a uniformly white glow. Neither shadows, horizon, nor clouds are discernible; sense of depth and orientation are lost; only very dark, nearby objects can be seen. Whiteout occurs over an unbroken snow cover and beneath a uniformly overcast sky, when, with the aid of the snowblink effect, the light from the sky is about equal to that from the snow surface. Blowing snow may be an additional cause. The phenomenon is experienced in the air as well as on the ground.

DEFINITIONS

Wind (mean wind, spot wind). Air motion relative to the Earth's surface. Unless it is otherwise specified, only the horizontal component is considered.

- (1) Mean wind: For the purpose of upper air reports from aircraft, mean wind is derived from the drift of the aircraft when flying from one fixed point to another or obtained by flying on a circuit around a fixed observed point and an immediate wind deduced from the drift of the aircraft.
- (2) Spot wind: For the purpose of upper-air reports from aircraft, the wind velocity, observed or predicted, for a specified location, height and time.

XML attribute. A start tag delimiting an XML element may contain one or more attributes. Attributes are Name-Value pairs, with the Name in each pair referred to as the attribute name and the Value (the text between the quote delimiters, that is, ' or ") as the attribute value. The order of attribute specifications in a start-tag or empty-element tag is not significant.

XML document. A structured document conforming to the rules specified in Extensible Markup Language (XML) 1.0 (Second Edition).

XML element. Each XML document contains one or more elements, the boundaries of which are either delimited by start-tags and end-tags, or, for empty elements, by an empty-element tag. Each element has a type, identified by name, sometimes called its generic identifier (GI), and may have a set of attribute specifications. An XML element may contain other XML elements, XML attributes or character data.

XML schema. A definition language offering facilities for describing the structure and constraining the contents of XML documents. The set of definitions for describing a particular XML document structure and associated constraints is referred to as an XML schema document.

XML schema document (XSD). An XML document containing XML schema component definitions and declarations.

Zodiacal light. White or yellowish light which spreads out, in the night sky, more or less along the zodiac from the horizon on the side on which the Sun is hidden. It is observed when the sky is sufficiently dark and the atmosphere sufficiently clear.

ACRONYMS

ADCP	Acoustic Doppler Current Profile
AMV	atmospheric motion vector
AOT	aerosol optical thickness
APSP	aerosol particle size parameter
BGAN	Broadband Global Area Network
DORIS	Doppler orbitography and radio-positioning integrated by Satellite
DSR	data set record
DU	Dobson Unit
EDR	eddy dissipation rate
GAN	global area network
GHR SST	GODAE high-resolution sea-surface temperature
GNSS	global navigation satellite system
GRP	glass-reinforced plastic
GRUAN	GCOS Reference Upper-Air Network
GTSP	Global Temperature Salinity Profile Programme
HPA	high-power amplifier
IFOV	instantaneous field of view
IW	infrared window
JMR	JASON-1 Microwave Radiometer
LRM	low-resolution mode
MMCC	Mission Management Control Centre
MWR	microwave radiometer
NOF	normalized objective function
OBC	on-board calibration
OCOG	offset centre of gravity
PRF	pulse repetition frequency
PRT	platinum resistance temperature
PTR	pulse target response
RDR	raw data record
RED	redundancy
RF	radio frequency
RFSS	radio-frequency subsystem
SAR	synthetic aperture radar
SDR	sensor data record
SSI	surface solar irradiance
SWH	significant wave height
WV	water vapour

PART B

BINARY CODES

- a. FM system of numbering binary codes**
- b. List of binary codes with their specifications and associated code tables**

FM 92 GRIB

Attachment I: Definition of a triangular grid based on an icosahedron

Attachment II: Arakawa grids

Attachment III: Distribution functions in GRIB

Attachment IV: Definition of "tiles" with time-dependent attributes

a. FM SYSTEM OF NUMBERING BINARY CODES

Each binary code bears a number, preceded by the letters FM. Before 2018, this number is was followed by a Roman numeral to identify the session of CBS which either approved the binary code as a new one or made the latest amendment to its previous version. A binary code approved or amended by correspondence after a session of CBS ~~receives~~ received the number of that session. After 2018, this number is followed by the year it was approved and the sequence number of the fast-track procedure, if applicable.

Furthermore, an indicator term is used to designate the binary code colloquially and is therefore called a “code name”.

Notes on nomenclature:

- (a) Changes and augmentations to the structure of the GRIB data representation shall be identified as different “GRIB edition numbers”. The current edition number is 2.

Changes to the content of any of the tables, including the grid definitions, shall be identified as different “table versions”. Previous tables were Version 23; the version described in this edition is “Tables Version 24”. Further GRIB editions and table versions may be generated independently of one another in the future as requirements dictate;

- (b) Changes and augmentations to the structure of the BUFR data representation shall be identified as different “BUFR edition numbers”. The current edition number is 4.

Changes to the content of the parameter Tables A, B, C and D shall be identified as different “table versions”. The previous tables were Version 32; the changes described in this edition will become “Tables A, B, C and D, Version 33”. Further BUFR editions and table versions may be generated independently of one another in the future as requirements dictate.

The FM system of numbering the binary codes, together with the corresponding code names and their reference list of ~~CBS~~-approved decisions, is the following:

FM SYSTEM OF BINARY CODES

FM 92–XIV GRIB

General regularly distributed information in binary form

Res. 4 (EC-LIII), Rec. 9 (CBS-01), approved by the President of WMO, Res. 8 (EC-LV), Res. 2 (EC-LVII), Res. 10 (EC-LIX), Res. 7 (EC-LXI) and adoption between CBS sessions (2010, 2012, 2013 and 2014)

FM 94–XIV BUFR

Binary universal form for the representation of meteorological data


Res. 1 (EC-XL), Rec. 23 (CBS-89), approved by the President of WMO, Rec. 22 (CBS-91), approved by the President of WMO, Rec. 15 (CBS-93), approved by the President of WMO, Rec. 16 (CBS-94), approved by the President of WMO, Res. 4 (EC-XLVII), Rec. 14 (CBS-95), approved by the President of WMO, Rec. 15 (CBS-96), approved by the President of WMO, Res. 4 (EC-XLIX), Rec. 9 (CBS-97), approved by the President of WMO, Rec. 10 (CBS-98), approved by the President of WMO, Res. 8 (EC-LI), Rec. 8 (CBS-99), Rec. 9 (CBS-00), approved by the President of WMO, Res. 4 (EC-LIII), Rec. 9 (CBS-01), approved by the President of WMO, Res. 8 (EC-LV), Res. 2 (EC-LVII), Res. 10 (EC-LIX), Res. 7 (EC-LXI), and adoption between CBS sessions (2010, 2012 and 2013)

b. LIST OF BINARY CODES WITH THEIR SPECIFICATIONS AND ASSOCIATED CODE TABLES

FM 92–XIV GRIB

General regularly distributed information in binary form

CODE FORM :



Notes:

- (1) GRIB is the name of a data representation form for general regularly distributed information in binary.
- (2) Data encoded in GRIB consists of a continuous bit-stream made of a sequence of octets (1 octet = 8 bits).
- (3) The octets of a GRIB message are grouped in sections:

<i>Section number</i>	<i>Name</i>	<i>Contents</i>
0	Indicator section	"GRIB", discipline, GRIB edition number, length of message
1	Identification section	Length of section, section number, characteristics that apply to all processed data in the GRIB message
2	Local use section (optional)	Length of section, section number, additional items for local use by originating centres
3	Grid definition section	Length of section, section number, definition of grid surface and geometry of data values within the surface
4	Product definition section	Length of section, section number, description of the nature of the data
5	Data representation section	Length of section, section number, description of how the data values are represented
6	Bit-map section	Length of section, section number, indication of presence or absence

FM 92 GRIB

		of data at each of the grid points, as applicable
7	Data section	Length of section, section number, data values
8	End section	"7777"

- (4) Sequences of GRIB sections 2 to 7, sections 3 to 7 or sections 4 to 7 may be repeated within a single GRIB message. All sections within such repeated sequences must be present and shall appear in the numerical order noted above. Unrepeated sections remain in effect until redefined.
- (5) It will be noted that the GRIB code is not suitable for visual data recognition without computer interpretation.
- (6) The representation of data by means of a series of bits is independent of any particular machine representation.
- (7) Message and section lengths are expressed in octets. Octets are numbered 1, 2, 3, etc., starting at the beginning of each section. Therefore, octet numbers in a template refer to the respective section.
- (8) Bit positions within octets are referred to as bit 1 to bit 8, where bit 1 is the most significant and bit 8 is the least significant. Thus, an octet with only bit 8 set to 1 would have the integer value 1.
- (9) As used in "GRIB", "International Alphabet No. 5" is regarded as an 8-bit alphabet with bit 1 set to zero.
- (10) The IEEE single precision floating point representation is specified in the standard ISO/IEC 559-1985 and ANSI/IEEE 754-1985 (R1991), which should be consulted for more details. The representation occupies four octets and is:

seeeeeee emmmmmmm mmmmmmmmm mmmmmmmmm

where:

s is the sign bit, 0 means positive, 1 negative

e...e is an 8 bit biased exponent

m...m is the mantissa, with the first bit deleted.

The value of the number is given by the following table:

e...e	m...m	Value of number
0	Any	$(-1)^s (m...m) 2^{-23} 2^{-126} = (-1)^s (m...m) 2^{-149}$
1...254	Any	$(-1)^s (1.0 + (m...m) 2^{-23}) 2^{((e...e)-127)}$
255	0	Positive (s=0) or Negative (s=1) infinity
255	>0	NaN (Not a valid Number, result of illegal operation)

Normally, only biased exponent values from 1 through 254 inclusive are used, except for positive or negative zero which is represented by setting both the biased exponent and the mantissa to 0.

The numbers are stored with the high-order octet first. The sign bit will be the first bit of the first octet. The low-order bit of the mantissa will be the last (eighth) bit of the fourth octet.

This floating point representation has been chosen because it is in common use in modern computer hardware. Some computers use this representation with the order of the octets reversed. They will have to convert the representation, either by reversing the octets or by computing the floating point value directly using the above formulas.

REGULATIONS:**92.1 General**

- 92.1.1 The GRIB code shall be used for the exchange and storage of general regularly distributed information expressed in binary form.
- 92.1.2 The beginning and the end of the code shall be identified by 4 octets coded according to the International Alphabet No. 5 to represent the indicators "GRIB" and "7777" in Indicator section 0 and End section 8, respectively. All other octets included in the code shall represent data in binary form.
- 92.1.3 Each section included in the code shall always end on an octet boundary. This rule shall be applied by appending bits set to zero to the section, where necessary.
- 92.1.4 All bits set to "1" for any value indicates that value is missing. This rule shall not apply to packed data.
- 92.1.5 If applicable, negative values shall be indicated by setting the most significant bit to "1".
- 92.1.6 Latitude, longitude and angle values shall be in units of 10^{-6} degree, except for specific cases explicitly stated in some grid definitions.
- 92.1.7 The latitude values shall be limited to the range 0 to 90 degrees inclusive. The orientation shall be north latitude positive, south latitude negative. Bit 1 is set to 1 to indicate south latitude.
- 92.1.8 The longitude values shall be limited to the range 0 to 360 degrees inclusive. The orientation shall be east longitude positive, with only positive values being used.
- 92.1.9 The latitude and longitude of the first grid point and the last grid point shall always be given for regular grids.
- 92.1.10 Vector components at the North and South Poles shall be coded according to the following conventions.
- 92.1.10.1 If the resolution and component flags in section 3 (Flag table 3.3) indicate that the vector components are relative to the defined grid, the vector components at the Pole shall be resolved relative to the grid.
- 92.1.10.2 Otherwise, for projections where there are multiple points at a given pole, the vector components shall be resolved as if measured an infinitesimal distance from the Pole at the longitude corresponding to each grid point. At the North Pole, the West to East (x direction) component at a grid point with longitude L shall be resolved along the meridian 90 degrees East of L, and the South to North (y direction) component shall be resolved along the meridian 180 degrees from L. At the South Pole, the West to East component at a grid point with longitude L shall be resolved along the meridian 90 degrees East of L and the South to North component shall be resolved along L.
- 92.1.10.3 Otherwise, if there is only one Pole point, either on a cylindrical projection with all but one Pole point deleted, or on any projection (such as polar stereographic) where the Pole maps to a unique point, the West to East and South to North components shall be resolved along longitudes 270° and 0°, respectively at the North Pole and along longitudes 270° and 180°, respectively at the South Pole.
- Note: This differs from the treatment of the Poles in the WMO traditional alphanumeric codes.
- 92.1.11 The first and last grid points shall not necessarily correspond to the first and last data points, respectively, if the bit-map is used.

- 92.1.12 Items in sections 3 and 4 which consist of a scale factor F and a scaled value V are related to the original value L as follows:

$$L \times 10^F = V$$

92.2 **Section 0 – Indicator section**

- 92.2.1 Section 0 shall always be 16 octets long.

- 92.2.2 The first four octets shall always be character coded according to the International Alphabet No. 5 as "GRIB".

- 92.2.3 The remainder of the section shall contain reserved octets, followed by the Discipline, the GRIB edition number, and the length of the entire GRIB message (including the Indicator section).

92.3 **Section 1 – Identification section**

- 92.3.1 The length of the section, in units of octets, shall be expressed over the group of the first four octets, i.e. over the first 32 bits.

- 92.3.2 The section number shall be expressed in the fifth octet.

- 92.3.3 Octets beyond 21 are for an Identification template. If no Identification template is used, optional section must not be present.

- 92.3.4 Calendar is assumed to be Gregorian unless otherwise stated in an Identification template.

92.4 **Section 2 – Local use section**

- 92.4.1 Regulations 92.3.1 and 92.3.2 shall apply.

- 92.4.2 Section 2 is optional.

92.5 **Section 3 – Grid definition section**

- 92.5.1 Regulations 92.3.1 and 92.3.2 shall apply.

92.6 **Section 4 – Product definition section**

- 92.6.1 Regulations 92.3.1 and 92.3.2 shall apply.

- 92.6.2 To maintain orthogonal structure of GRIB Edition 2, parameter names in Code table 4.2 should not contain surface type and statistical process as part of the name.

- 92.6.3 In product definition templates that refer to a forecast time or to offset from the reference time, this may be negative to refer to times or intervals that begin before the reference time, if this is applicable.

92.7 **Section 5 – Data representation section**

- 92.7.1 Regulations 92.3.1 and 92.3.2 shall apply.

92.8 **Section 6 – Bit-map section**

- 92.8.1 Regulations 92.3.1 and 92.3.2 shall apply.

92.9 **Section 7 – Data section**

- 92.9.1 Regulations 92.3.1 and 92.3.2 shall apply.

- 92.9.2 Data shall be coded using the minimum number of bits necessary to provide the accuracy required by international agreement. This required accuracy/precision shall be achieved by scaling the data by multiplication by an appropriate power of 10 (the power may be 0) before forming the non-negative differences, and then using the binary scaling to select the precision of the transmitted value.
- 92.9.3 The data shall be packed by the method identified in section 5.
- 92.9.4 Data shall be coded in the form of non-negative scaled differences from a reference value of the whole field plus, if applicable, a local reference value.

Notes:

- (1) A reference value is normally the minimum value of the data set which is represented.
- (2) For grid-point values, complex packing features are intended to reduce the whole size of the GRIB message (data compression without loss of information with respect to simple packing). The basic concept is to reduce data size thanks to local redundancy. This is achieved just before packing, by splitting the whole set of scaled data values into groups, on which local references (such as local minima) are removed. It is done with some overhead, because extra descriptors are needed to manage the groups' characteristics. An optional pre-processing of the scaled values (spatial differencing) may also be applied before splitting into groups, and combined methods, along with use of alternate row scanning mode, are very efficient on interpolated data.
- (3) For spectral data, complex packing is provided for better accuracy of packing. This is because many spectral coefficients have small values (regardless of the sign), especially for large wave numbers. The first principle is not to pack a subset of coefficients, associated with small wave numbers so that the amplitude of the packed coefficients is reduced. The second principle is to apply an operator to the remaining part of the spectrum: with appropriate tuning it leads to a more homogeneous set of values to pack.
- (4) The original data value Y (in the units of Code table 4.2, unless Notes in Code table 4.10 apply) can be recovered with the formula:

$$Y \times 10^D = R + (X1 + X2) \times 2^E$$

For simple packing and all spectral data

- E = Binary scale factor
- D = Decimal scale factor
- R = Reference value of the whole field
- X1 = 0
- X2 = Scaled (encoded) value.

For complex grid-point packing schemes, E, D and R are as above, but

- X1 = Reference value (scaled integer) of the group the data value belongs to
- X2 = Scaled (encoded) value with the group reference value (X1) removed.

92.10 **Section 8 – End section**

- 92.10.1 The end section shall always be 4 octets long, character coded according to the International Alphabet No. 5 as "7777".

SPECIFICATIONS OF OCTET CONTENTS

Section 0 – Indicator section

Octet No.	Contents
1–4	GRIB (coded according to the International Alphabet No. 5)
5–6	Reserved
7	Discipline – GRIB Master table number (see Code table 0.0)
8	GRIB edition number (currently 2)
9–16	Total length of GRIB message in octets (including Section 0)

Section 1 – Identification section

Octet No.	Contents
1–4	Length of section in octets (21 or nn)
5	Number of section (1)
6–7	Identification of originating/generating centre (see Common Code table C–11)
8–9	Identification of originating/generating subcentre (allocated by originating/ generating centre)
10	GRIB master table version number (see Common Code table C–0 and Note 1)
11	Version number of GRIB Local tables used to augment Master tables (see Code table 1.1 and Note 2)
12	Significance of reference time (see Code table 1.2)
13–14	Year (4 digits)
15	Month
16	Day
17	Hour
18	Minute
19	Second
20	Production status of processed data in this GRIB message (see Code table 1.3)
21	Type of processed data in this GRIB message (see Code table 1.4)
22–23	Identification template number (optional, see Code table 1.5)
24–nn	Identification template (optional, see template 1.X, where X is the identification template number given in octets 22–23)

Notes:

- (1) Local tables shall define those parts of the Master table which are reserved for local use except for the case described below. In any case, the use of Local tables in messages intended for non-local or international exchange is strongly discouraged.
- (2) If octet 10 contains 255 then only Local tables are in use, the Local table version number (octet 11) must not be zero nor missing, and Local tables may include entries from the entire range of the tables.
- (3) If octet 11 is zero, octet 10 must contain a valid Master table version number and only those parts of the tables not reserved for local use may be used.

Section 2 – Local use section

Octet No.	Contents
1–4	Length of section in octets (nn)
5	Number of section (2)
6–nn	Local use

Section 3 – Grid definition section

Octet No.	Contents
1–4	Length of section in octets (nn)
5	Number of section (3)
6	Source of grid definition (see Code table 3.0 and Note 1)
7–10	Number of data points
11	Number of octets for optional list of numbers (see Note 2)
12	Interpretation of list of numbers (see Code table 3.11)
13–14	Grid definition template number (= N) (see Code table 3.1)
15–xx	Grid definition template (see template 3.N, where N is the grid definition template number given in octets 13–14)
[xx+1]–nn	Optional list of numbers defining number of points (see Notes 2, 3 and 4)

Notes:

- (1) If octet 6 is not zero, octets 15–xx (15–nn if octet 11 is zero) may not be supplied. This should be documented with all bits set to 1 (missing value) in the grid definition template number.
- (2) An optional list of numbers may be used to document a quasi-regular grid. In such a case, octet 11 is non zero and gives the number of octets used per item on the list. For all other cases, such as regular grids, octets 11 and 12 are zero and no list is appended to the grid definition template.
- (3) If a list of numbers defining number of points is present, it is appended at the end of the grid definition template (or directly after the grid definition template number if the template is missing), the length of the list is given by the grid definition. When the grid definition template is present, the length is given according to bit 3 of scanning mode flag octet (length is Nj or Ny for flag value 0). List ordering is implied by data scanning.
- (4) Depending on code value given in octet 12, the list of numbers either:
 - corresponds to the coordinate lines as given in the grid definition, or
 - corresponds to a full circle, or
 - does not apply.

Section 4 – Product definition section

Octet No.	Contents
1–4	Length of section in octets (nn)
5	Number of section (4)
6–7	Number of coordinate values after template or number of information according to 3D vertical coordinate GRIB2 message (see Notes 1 and 5)
8–9	Product definition template number (see Code table 4.0)
10–xx	Product definition template (see template 4.X, where X is the product definition template number given in octets 8–9)
[xx+1]–nn	Optional list of coordinate values or vertical grid information (see Notes 2, 3, 4 and 5)

Notes:

- (1) Coordinate values are intended to document the vertical discretization associated with model data on hybrid coordinate vertical levels. A number of zero in octets 6–7 indicates that no such values are present. Otherwise the number corresponds to the whole set of values.
- (2) Hybrid systems, in this context, employ a means of representing vertical coordinates in terms of a mathematical combination of pressure and sigma coordinates. When used in conjunction with a surface pressure field and an appropriate mathematical expression, the vertical coordinate parameters may be used to interpret the hybrid vertical coordinate.
- (3) Hybrid coordinate values, if present, should be encoded in IEEE 32-bit floating point format. They are intended to be encoded as pairs.
- (4) Two distinct pressure-based hybrid coordinate formulations can be expressed in GRIB Edition 2. If the hybrid coordinate being used is based on pressure, then level type 105 (Code table 4.5) shall be used to specify the vertical level type. If the formulation is based on the natural logarithm of pressure then level type 113 (Code table 4.5) shall be used. In both cases Notes 1 to 3 (above) apply fully.

- (5) In the case of a generalized vertical height coordinate (fixed surface type 150), no pairs of coordinate values follow after the template, but six sets of additional information (each 4 octets long and encoded in IEEE 32-bit floating point format) follow, starting with the number of vertical levels and the identification number of the used vertical system in the additional GRIB2 message with the 3D vertical system. This identification number together with an UUID (Universally Unique Identifier) in four parts allows a unique identification of the grid.

[xx+1] – [xx+4]	Number of vertical levels
[xx+5] – [xx+8]	Identification number of 3D vertical grid GRIB2 message (defined by originating centre)
[xx+9] – [xx+12]	UUID part 1 of 4
[xx+13] – [xx+16]	UUID part 2 of 4
[xx+17] – [xx+20]	UUID part 3 of 4
[xx+21] – [xx+24]	UUID part 4 of 4

Section 5 – Data representation section

Octet No.	Contents
1–4	Length of section in octets (nn)
5	Number of section (5)
6–9	Number of data points where one or more values are specified in Section 7 when a bit map is present, total number of data points when a bit map is absent.
10–11	Data representation template number (see Code table 5.0)
12–nn	Data representation template (see template 5.X, where X is the data representation template number given in octets 10–11)

Section 6 – Bit-map section

Octet No.	Contents
1–4	Length of section in octets (nn)
5	Number of section (6)
6	Bit-map indicator (see Code table 6.0 and the Note)
7–nn	Bit-map – Contiguous bits with a bit to data point correspondence, ordered as defined in Section 3. A bit set to 1 implies the presence of a data value at the corresponding data point, whereas a value of 0 implies the absence of such a value.

Note: If octet 6 is not zero, the length of the section is 6 and octets 7–nn are not present.

Section 7 – Data section

Octet No.	Contents
1–4	Length of section in octets (nn)
5	Number of section (7)
6–nn	Data in a format described by data template 7.X, where X is the data representation template number given in octets 10–11 of Section 5.

Section 8 – End section

Octet No.	Contents
1–4	“7777” (coded according to the International Alphabet No. 5)

TEMPLATE DEFINITIONS USED IN SECTION 1**Identification template 1.0 – calendar definition**

<i>Identification template 1.0</i>	
Octet No.	Contents
24	Type of calendar (see Code table 1.6)

Identification template 1.1 – paleontological offset

<i>Identification template 1.1</i>	
Octet No.	Contents
24–25	Number of tens of thousands of years of offset

Notes:

- (1) The year can be recovered with the formula:

$$\text{Year (real/decoded)} = \text{Year} + 10\,000 \times \text{Offset}$$
- (2) Years before year 1 shall be coded as defined in ISO 8601 (year 1 is followed by year 0).
 If applicable, year –1 or before shall be indicated by setting the most significant bit of octets 13–14 and 24–25 to "1" in accordance with Regulation 92.1.5.

Identification template 1.2 – calendar definition and paleontological offset

<i>Identification template 1.2</i>	
Octet No.	Contents
24	Type of calendar (see Code table 1.6)
25–26	Number of tens of thousands of years of offset

Notes:

- (1) The year can be recovered with the formula:

$$\text{Year (real/decoded)} = \text{Year} + 10\,000 \times \text{Offset}$$
- (2) Years before year 1 shall be coded as defined in ISO 8601 (year 1 is followed by year 0).
 If applicable, year –1 or before shall be indicated by setting the most significant bit of octets 13–14 and 24–25 to "1" in accordance with Regulation 92.1.5.

TEMPLATE DEFINITIONS USED IN SECTION 3

Grid definition template 3.0 – latitude/longitude (or equidistant cylindrical, or Plate Carrée)

<i>Grid definition template 3.0</i>	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Ni – number of points along a parallel
35–38	Nj – number of points along a meridian
39–42	Basic angle of the initial production domain (see Note 1)
43–46	Subdivisions of basic angle used to define extreme longitudes and latitudes, and direction increments (see Note 1)
47–50	La1 – latitude of first grid point (see Note 1)
51–54	Lo1 – longitude of first grid point (see Note 1)
55	Resolution and component flags (see Flag table 3.3)
56–59	La2 – latitude of last grid point (see Note 1)
60–63	Lo2 – longitude of last grid point (see Note 1)
64–67	Di – i direction increment (see Notes 1 and 5)
68–71	Dj – j direction increment (see Notes 1 and 5)
72	Scanning mode (see Flag table 3.4)
73–nn	List of number of points along each meridian or parallel (see Notes 2, 3 and 7)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the extreme longitudes and latitudes, and direction increments. For these last six descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number. For ordinary cases, zero and missing values should be coded, equivalent to respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) For data on a quasi-regular grid, where all the rows or columns do not necessarily have the same number of grid points, either Ni (octets 31–34) or Nj (octets 35–38) and the corresponding Di (octets 64–67) or Dj (octets 68–71) shall be coded with all bits set to 1 (missing). The actual number of points along each parallel or meridian shall be coded in the octets immediately following the grid definition template (octets [xx+1]–nn), as described in the description of the grid definition section.
- (3) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points or variable spacing. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).
- (4) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth is derived from applying the appropriate scale factor to the value expressed in metres.
- (5) It is recommended to use unsigned direction increments.
- (6) In most cases, multiplying Ni (octets 31–34) by Nj (octets 35–38) yields the total number of points in the grid. However, this may not be true if bit 8 of the scanning mode flags (octet 72) is set to 1.
- (7) These octets are only present for quasi-regular grids.

Grid definition template 3.1 – rotated latitude/longitude (or equidistant cylindrical, or Plate Carrée)

Grid definition template 3.1	
Octet No.	Contents
15–72	Same as grid definition template 3.0 (see Note 1)
73–76	Latitude of the southern pole of projection
77–80	Longitude of the southern pole of projection
81–84	Angle of rotation of projection
85–nn	List of number of points along each meridian or parallel (see Notes 3 and 4)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the extreme longitudes and latitudes, and direction increments. For these last six descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number. For ordinary cases, zero and missing values should be coded, equivalent to respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) Three parameters define a general latitude/longitude coordinate system, formed by a general rotation of the sphere. One choice for these parameters is:
 - (a) The geographic latitude in degrees of the southern pole of the coordinate system, θ_p for example;
 - (b) The geographic longitude in degrees of the southern pole of the coordinate system, λ_p for example;
 - (c) The angle of rotation in degrees about the new polar axis (measured clockwise when looking from the southern to the northern pole) of the coordinate system, assuming the new axis to have been obtained by first rotating the sphere through λ_p degrees about the geographic polar axis, and then rotating through $(90 + \theta_p)$ degrees so that the southern pole moved along the (previously rotated) Greenwich meridian.
- (3) These octets are only present for quasi-regular grids.
- (4) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points or variable spacing. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).

Grid definition template 3.2 – stretched latitude/longitude (or equidistant cylindrical, or Plate Carrée)

Grid definition template 3.2	
Octet No.	Contents
15–72	Same as grid definition template 3.0 (see Note 1)
73–76	Latitude of the pole of stretching
77–80	Longitude of the pole of stretching
81–84	Stretching factor
85–nn	List of number of points along each meridian or parallel (see Notes 3 and 4)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the extreme longitudes and latitudes, and direction increments. For these last six descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number. For ordinary cases, zero and missing values should be coded, equivalent to respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) The stretching is defined by three parameters:
 - (a) The latitude in degrees (measured in the model coordinate system) of the "pole of stretching";

- (b) The longitude in degrees (measured in the model coordinate system) of the "pole of stretching"; and
- (c) The stretching factor C in units of 10^{-6} represented as an integer.

The stretching is defined by representing data uniformly in a coordinate system with longitude λ and latitude θ^1 , where:

$$\theta^1 = \sin^{-1} \frac{(1 - C^2) + (1 + C^2) \sin \theta}{(1 + C^2) + (1 - C^2) \sin \theta}$$

and λ and θ are longitude and latitude in a coordinate system in which the "pole of stretching" is the northern pole.

$C = 1$ gives uniform resolution, while $C > 1$ gives enhanced resolution around the pole of stretching.

- (3) These octets are only present for quasi-regular grids.
- (4) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points or variable spacing. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).

**Grid definition template 3.3 – stretched and rotated latitude/longitude
(or equidistant cylindrical, or Plate Carrée)**

Grid definition template 3.3	
Octet No.	Contents
15–72	Same as grid definition template 3.0 (see Note 1)
73–76	Latitude of the southern pole of projection
77–80	Longitude of the southern pole of projection
81–84	Angle of rotation of projection
85–88	Latitude of the pole of stretching
89–92	Longitude of the pole of stretching
93–96	Stretching factor
97–nn	List of number of points along each meridian or parallel (see Notes 3 and 4)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the extreme longitudes and latitudes, and direction increments. For these last six descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number. For ordinary cases, zero and missing values should be coded, equivalent to respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) Three parameters define a general latitude/longitude coordinate system, formed by a general rotation of the sphere. One choice for these parameters is:
- The geographic latitude in degrees of the southern pole of the coordinate system, θ_p for example;
 - The geographic longitude in degrees of the southern pole of the coordinate system, λ_p for example;
 - The angle of rotation in degrees about the new polar axis (measured clockwise when looking from the southern to the northern pole) of the coordinate system, assuming the new axis to have been obtained by first rotating the sphere through λ_p degrees about the geographic polar axis, and then rotating through $(90 + \theta_p)$ degrees so that the southern pole moved along the (previously rotated) Greenwich meridian.
- (3) The stretching is defined by three parameters:
- The latitude in degrees (measured in the model coordinate system) of the "pole of stretching";
 - The longitude in degrees (measured in the model coordinate system) of the "pole of stretching"; and

(c) The stretching factor C in units of 10^{-6} represented as an integer.

The stretching is defined by representing data uniformly in a coordinate system with longitude λ and latitude θ^1 , where:

$$\theta^1 = \sin^{-1} \frac{(1 - C^2) + (1 + C^2) \sin \theta}{(1 + C^2) + (1 - C^2) \sin \theta}$$

and λ and θ are longitude and latitude in a coordinate system in which the "pole of stretching" is the northern pole. $C = 1$ gives uniform resolution, while $C > 1$ gives enhanced resolution around the pole of stretching.

- (4) These octets are only present for quasi-regular grids.
- (5) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points or variable spacing. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).

Grid definition template 3.4 – variable resolution latitude/longitude

Grid definition template 3.4	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	N_i – number of points along a parallel
35–38	N_j – number of points along a meridian
39–42	Basic angle of the initial production domain (see Note 1)
43–46	Subdivisions of basic angle used to define extreme longitudes and latitudes, and direction increments (see Note 1)
47	Resolution and component flags (see Flag table 3.3 and Note 2)
48	Scanning mode (see Flag table 3.4)
49–ii	List of longitudes (see Notes 1 and 3)
(ii+1)–jj	List of latitudes (see Notes 1 and 3)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the longitudes and latitudes, and direction increments. For these descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number.
For ordinary cases, zero and missing values should be coded, equivalent to the respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) The resolution flags (bit 3–4 of Flag table 3.3) are not applicable.
- (3) The list of N_i longitudes and N_j latitudes shall be coded in the octets immediately following the grid definition template in octets 49 to ii and octets ii+1 to jj respectively, where $ii = 48 + 4N_i$ and $jj = 48 + 4N_i + 4N_j$.
- (4) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.

Grid definition template 3.5 – variable resolution rotated latitude/longitude

Grid definition template 3.5	
Octet No.	Contents
15–48	Same as grid definition template 3.4 (see Note 1)
49–52	Latitude of the southern pole of projection (see Note 4)
53–56	Longitude of the southern pole of projection (see Note 4)
57–60	Angle of rotation of projection (see Note 4)
61–ii	List of longitudes (see Notes 1 and 3)
(ii+1)–jj	List of latitudes (see Notes 1 and 3)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the longitudes and latitudes, and direction increments. For these descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number.
For ordinary cases, zero and missing values should be coded, equivalent to the respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) Three parameters define a general latitude/longitude coordinate system, formed by a general rotation of the sphere. One choice for these parameters is:
 - (a) The geographic latitude in degrees of the southern pole of the coordinate system, for example, θ_p ;
 - (b) The geographic longitude in degrees of the southern pole of the coordinate system, for example, λ_p ;
 - (c) The angle of rotation in degrees about the new polar axis (measured clockwise when looking from the southern to the northern pole) of the coordinate system, assuming the new axis to have been obtained by first rotating the sphere through λ_p degrees about the geographic polar axis, and then rotating through $(90 + \theta_p)$ degrees so that the southern pole moved along the (previously rotated) Greenwich meridian.
- (3) For the list of N_i longitude bounds and N_j latitude bounds at the end of the section:

$$ii = 60 + 4N_i \quad \text{and} \quad jj = 60 + 4N_i + 4N_j$$
- (4) Regulation 92.1.6 applies.

Grid definition template 3.10 – Mercator

Grid definition template 3.10	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	N_i – number of points along a parallel
35–38	N_j – number of points along a meridian
39–42	La_1 – latitude of first grid point
43–46	Lo_1 – longitude of first grid point
47	Resolution and component flags (see Flag table 3.3)
48–51	La_D – latitude(s) at which the Mercator projection intersects the Earth (Latitude(s) where D_i and D_j are specified)
52–55	La_2 – latitude of last grid point
56–59	Lo_2 – longitude of last grid point
60	Scanning mode (see Flag table 3.4)

Grid definition template 3.10

Octet No.	Contents
61–64	Orientation of the grid, angle between i direction on the map and the Equator (see Note 1)
65–68	D_i – longitudinal direction grid length (see Note 2)
69–72	D_j – latitudinal direction grid length (see Note 2)
73–nn	List of number of points along each meridian or parallel (see Notes 4, 5 and 6)

Notes:

- (1) Limited to the range of 0 to 90 degrees; if the angle of orientation of the grid is neither 0 nor 90 degrees, D_i and D_j must be equal to each other.
- (2) Grid length is in units of 10^{-3} m at the latitude specified by LaD .
- (3) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.
- (4) These octets are only present for quasi-regular grids.
- (5) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points or variable spacing. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).
- (6) Three parameters define a general latitude/longitude coordinate system, formed by a general rotation of the sphere. One choice for these parameters is:
 - (a) The geographic latitude in degrees of the southern pole of the coordinate system, θ_p for example;
 - (b) The geographic longitude in degrees of the southern pole of the coordinate system, λ_p for example;
 - (c) The angle of rotation in degrees about the new polar axis (measured clockwise when looking from the southern to the northern pole) of the coordinate system, assuming the new axis to have been obtained by first rotating the sphere through λ_p degrees about the geographic polar axis, and then rotating through $(90 + \theta_p)$ degrees so that the southern pole moved along the (previously rotated) Greenwich meridian.

Grid definition template 3.12 – transverse Mercator*Grid definition template 3.12*

Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	N_i – number of points along i-axis
35–38	N_j – number of points along j-axis
39–42	LaR – geographic latitude of reference point
43–46	LoR – geographic longitude of reference point
47	Resolution and component flags (see Flag table 3.3)
48–51	m – scale factor at reference point ratio of distance on map to distance on spheroid (IEEE 32-bit floating-point values)
52–55	XR – false easting, i-direction coordinate of reference point in units of 10^{-2} m
56–59	YR – false northing, j-direction coordinate of reference point in units of 10^{-2} m
60	Scanning mode (see Flag table 3.4)
61–64	D_i – i-direction increment length in units of 10^{-2} m

Grid definition template 3.12

Octet No.	Contents
65–68	Dj – j-direction increment length in units of 10^{-2} m
69–72	x1 – i-direction coordinate of the first grid point in units of 10^{-2} m
73–76	y1 – j-direction coordinate of the first grid point in units of 10^{-2} m
77–80	x2 – i-direction coordinate of the last grid point in units of 10^{-2} m
81–84	y2 – j-direction coordinate of the last grid point in units of 10^{-2} m

Grid definition template 3.13 – Mercator with modelling subdomains definition*Grid definition template 3.13*

Octet No.	Contents
15–nn	Same as grid definition template 3.10
[nn+1]–[nn+4]	Nux – size of model forecast subdomain in x-direction (number of grid points)
[nn+5]–[nn+8]	Ncx – width of coupling area within forecast domain in x-direction (number of grid points)
[nn+9]–[nn+12]	Nuy – size of model forecast subdomain in y-direction (number of grid points)
[nn+13]–[nn+16]	Ncy – width of coupling area within forecast domain in y-direction (number of grid points)

Grid definition template 3.20 – polar stereographic projection*Grid definition template 3.20*

Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Nx – number of points along the x-axis
35–38	Ny – number of points along the y-axis
39–42	La1 – latitude of first grid point
43–46	Lo1 – longitude of first grid point
47	Resolution and component flags (see Flag table 3.3 and Note 1)
48–51	LaD – latitude where Dx and Dy are specified
52–55	LoV – orientation of the grid (see Note 2)
56–59	Dx – x-direction grid length (see Note 3)
60–63	Dy – y-direction grid length (see Note 3)
64	Projection centre (see Flag table 3.5)
65	Scanning mode (see Flag table 3.4)

Notes:

- (1) The resolution flags (bits 3–4 of Flag table 3.3) are not applicable.
- (2) LoV is the longitude value of the meridian which is parallel to the y-axis (or columns of the grid) along which latitude increases as the y-coordinate increases (the orientation longitude may or may not appear on a particular grid).

- (3) Grid length is in units of 10^{-3} m at the latitude specified by LaD.
- (4) Bit 2 of the projection flag is not applicable to the polar stereographic projection.
- (5) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.

Grid definition template 3.23 – Polar stereographic with modelling subdomains definition

Grid definition template 3.23	
Octet No.	Contents
15–65	Same as grid definition template 3.20
66–69	Nux – size of model forecast subdomain in x-direction (number of grid points)
70–73	Ncx – width of coupling area within forecast domain in x-direction (number of grid points)
74–77	Nuy – size of model forecast subdomain in y-direction (number of grid points)
78–81	Ncy – width of coupling area within forecast domain in y-direction (number of grid points)

Grid definition template 3.30 – Lambert conformal

Grid definition template 3.30	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Nx – number of points along the x-axis
35–38	Ny – number of points along the y-axis
39–42	La1 – latitude of first grid point
43–46	Lo1 – longitude of first grid point
47	Resolution and component flags (see Note 3 and Flag table 3.3)
48–51	LaD – latitude where Dx and Dy are specified
52–55	LoV – longitude of meridian parallel to y-axis along which latitude increases as the y-coordinate increases (see Note 4)
56–59	Dx – x-direction grid length (see Note 1)
60–63	Dy – y-direction grid length (see Note 1)
64	Projection centre (see Flag table 3.5)
65	Scanning mode (see Flag table 3.4)
66–69	Latin 1 – first latitude from the pole at which the secant cone cuts the sphere
70–73	Latin 2 – second latitude from the pole at which the secant cone cuts the sphere
74–77	Latitude of the southern pole of projection
78–81	Longitude of the southern pole of projection

Notes:

- (1) Grid length is in units of 10^{-3} m, at the latitude specified by LaD.
- (2) If Latin 1 = Latin 2, then the projection is on a tangent cone.
- (3) The resolution flags (bits 3–4 of Flag table 3.3) are not applicable.

- (4) LoV is the longitude value of the meridian which is parallel to the y-axis (or columns of the grid) along which latitude increases as the y-coordinate increases (the orientation longitude may or may not appear on a particular grid).
- (5) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.

Grid definition template 3.31 – Albers equal area

<i>Grid definition template 3.31</i>	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Nx – number of points along the x-axis
35–38	Ny – number of points along the y-axis
39–42	La1 – latitude of first grid point
43–46	Lo1 – longitude of first grid point
47	Resolution and component flags (see Note 3 and Flag table 3.3)
48–51	LaD – latitude where Dx and Dy are specified
52–55	LoV – longitude of meridian parallel to y-axis along which latitude increases as the y-coordinate increases (see Note 4)
56–59	Dx – x-direction grid length (see Note 1)
60–63	Dy – y-direction grid length (see Note 1)
64	Projection centre (see Flag table 3.5)
65	Scanning mode (see Flag table 3.4)
66–69	Latin 1 – first latitude from the pole at which the secant cone cuts the sphere
70–73	Latin 2 – second latitude from the pole at which the secant cone cuts the sphere
74–77	Latitude of the southern pole of projection
78–81	Longitude of the southern pole of projection

Notes:

- (1) Grid length is in units of 10^{-3} m, at the latitude specified by LaD.
- (2) If Latin 1 = Latin 2, then the projection is on a tangent cone.
- (3) The resolution flags (bits 3–4 of Flag table 3.3) are not applicable.
- (4) LoV is the longitude value of the meridian which is parallel to the y-axis (or columns of the grid) along which latitude increases as the y-coordinate increases (the orientation longitude may or may not appear on a particular grid).
- (5) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.

Grid definition template 3.33 – Lambert conformal with modelling subdomains definition

Grid definition template 3.33	
Octet No.	Contents
15–81	Same as grid definition template 3.30
82–85	Nux – size of model forecast subdomain in x-direction (number of grid points)
86–89	Ncx – width of coupling area within forecast domain in x-direction (number of grid points)
90–93	Nuy – size of model forecast subdomain in y-direction (number of grid points)
94–97	Ncy – width of coupling area within forecast domain in y-direction (number of grid points)

Grid definition template 3.40 – Gaussian latitude/longitude

Grid definition template 3.40	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Ni – number of points along a parallel
35–38	Nj – number of points along a meridian
39–42	Basic angle of the initial production domain (see Note 1)
43–46	Subdivisions of basic angle used to define extreme longitudes and latitudes, and direction increments (see Note 1)
47–50	La1 – latitude of first grid point (see Note 1)
51–54	Lo1 – longitude of first grid point (see Note 1)
55	Resolution and component flags (see Flag table 3.3)
56–59	La2 – latitude of last grid point (see Note 1)
60–63	Lo2 – longitude of last grid point (see Note 1)
64–67	Di – i direction increment (see Notes 1 and 5)
68–71	N – number of parallels between a pole and the Equator (see Note 2)
72	Scanning mode (see Flag table 3.4)
73–nn	List of number of points along each meridian or parallel (see Notes 4 and 6)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the extreme longitudes and latitudes, and direction increments. For these last six descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number. For ordinary cases, zero and missing values should be coded, equivalent to respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) The number of parallels between a pole and the Equator is used to establish the variable (Gaussian) spacing of the parallels; this value must always be given.
- (3) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.

- (4) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).
- (5) It is recommended to use unsigned direction increments.
- (6) These octets are only present for quasi-regular grids.

Grid definition template 3.41 – rotated Gaussian latitude/longitude

<i>Grid definition template 3.41</i>	
Octet No.	Contents
15–72	Same as grid definition template 3.40 (see Note 1)
73–76	Latitude of the southern pole of projection
77–80	Longitude of the southern pole of projection
81–84	Angle of rotation of projection
85–nn	List of number of points along each meridian or parallel (see Notes 4 and 5)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the longitudes and latitudes, and direction increments. For these descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number. For ordinary cases, zero and missing values should be coded, equivalent to the respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) The number of parallels between a pole and the Equator is used to establish the variable (Gaussian) spacing of the parallels; this value must always be given.
- (3) Three parameters define a general latitude/longitude coordinate system, formed by a general rotation of the sphere. One choice for these parameters is:
 - (a) The geographic latitude in degrees of the southern pole of the coordinate system, θ_p for example;
 - (b) The geographic longitude in degrees of the southern pole of the coordinate system, λ_p for example;
 - (c) The angle of rotation in degrees about the new polar axis (measured clockwise when looking from the southern to the northern pole) of the coordinate system, assuming the new axis to have been obtained by first rotating the sphere through λ_p degrees about the geographic polar axis, and then rotating through $(90 + \theta_p)$ degrees so that the southern pole moved along the (previously rotated) Greenwich meridian.
- (4) These octets are only present for quasi-regular grids.
- (5) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points or variable spacing. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).

Grid definition template 3.42 – stretched Gaussian latitude/longitude

Grid definition template 3.42	
Octet No.	Contents
15–72	Same as grid definition template 3.40 (see Note 1)
73–76	Latitude of the pole of stretching
77–80	Longitude of the pole of stretching
81–84	Stretching factor
85–nn	List of number of points along each meridian or parallel (see Notes 4 and 5)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the longitudes and latitudes, and direction increments. For these descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number.

For ordinary cases, zero and missing values should be coded, equivalent to the respective values of 1 and 10^6 (10^{-6} degrees unit).

- (2) The number of parallels between a pole and the Equator is used to establish the variable (Gaussian) spacing of the parallels; this value must always be given.

- (3) The stretching is defined by three parameters:

- (a) The latitude in degrees (measured in the model coordinate system) of the “pole of stretching”;
- (b) The longitude in degrees (measured in the model coordinate system) of the “pole of stretching”; and
- (c) The stretching factor C in units of 10^{-6} represented as an integer. The stretching is defined by representing data uniformly in a coordinate system with longitude λ and latitude θ^1 , where:

$$\theta^1 = \sin^{-1} \frac{(1 - C^2) + (1 + C^2) \sin \theta}{(1 + C^2) + (1 - C^2) \sin \theta}$$

and λ and θ are longitude and latitude in a coordinate system in which the “pole of stretching” is the northern pole.

$C = 1$ gives uniform resolution, while $C > 1$ gives enhanced resolution around the pole of stretching.

- (4) These octets are only present for quasi-regular grids.
- (5) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points or variable spacing. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).

Grid definition template 3.43 – stretched and rotated Gaussian latitude/longitude

Grid definition template 3.43	
Octet No.	Contents
15–72	Same as grid definition template 3.40 (see Note 1)
73–76	Latitude of the southern pole of projection
77–80	Longitude of the southern pole of projection
81–84	Angle of rotation of projection
85–88	Latitude of the pole of stretching
89–92	Longitude of the pole of stretching
93–96	Stretching factor
97–nn	List of number of points along each meridian or parallel (see Notes 5 and 6)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the longitudes and latitudes, and direction increments. For these descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number. For ordinary cases, zero and missing values should be coded, equivalent to the respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) The number of parallels between a pole and the Equator is used to establish the variable (Gaussian) spacing of the parallels; this value must always be given.
- (3) The stretching is defined by three parameters:
 - (a) The latitude in degrees (measured in the model coordinate system) of the “pole of stretching”;
 - (b) The longitude in degrees (measured in the model coordinate system) of the “pole of stretching”; and
 - (c) The stretching factor C in units of 10^{-6} represented as an integer. The stretching is defined by representing data uniformly in a coordinate system with longitude λ and latitude θ^1 , where:

$$\theta^1 = \sin^{-1} \frac{(1 - C^2) + (1 + C^2) \sin \theta}{(1 + C^2) + (1 - C^2) \sin \theta}$$

and λ and θ are longitude and latitude in a coordinate system in which the “pole of stretching” is the northern pole. $C = 1$ gives uniform resolution, while $C > 1$ gives enhanced resolution around the pole of stretching.

- (4) Three parameters define a general latitude/longitude coordinate system, formed by a general rotation of the sphere. One choice for these parameters is:
 - (a) The geographic latitude in degrees of the southern pole of the coordinate system, θ_p for example;
 - (b) The geographic longitude in degrees of the southern pole of the coordinate system, λ_p for example;
 - (c) The angle of rotation in degrees about the new polar axis (measured clockwise when looking from the southern to the northern pole) of the coordinate system, assuming the new axis to have been obtained by first rotating the sphere through λ_p degrees about the geographic polar axis, and then rotating through $(90 + \theta_p)$ degrees so that the southern pole moved along the (previously rotated) Greenwich meridian.
- (5) These octets are only present for quasi-regular grids.
- (6) A quasi-regular grid is only defined for appropriate grid scanning modes. Either rows or columns, but not both simultaneously, may have variable numbers of points or variable spacing. The first point in each row (column) shall be positioned at the meridian (parallel) indicated by octets 47–54. The grid points shall be evenly spaced in latitude (longitude).

Grid definition template 3.50 – spherical harmonic coefficients

Grid definition template 3.50	
Octet No.	Contents
15–18	J – pentagonal resolution parameter
19–22	K – pentagonal resolution parameter
23–26	M – pentagonal resolution parameter
27	Representation type indicating the method used to define the norm (see Code table 3.6)
28	Representation mode indicating the order of the coefficients (see Code table 3.7)

Note: The pentagonal representation of resolution is general. Some common truncations are special cases of the pentagonal one:

Triangular: $M = J = K$

Rhomboidal: $K = J + M$

Trapezoidal: $K = J, K > M$

Grid definition template 3.51 – rotated spherical harmonic coefficients

Grid definition template 3.51	
Octet No.	Contents
15–28	Same as grid definition template 3.50
29–32	Latitude of the southern pole of projection
33–36	Longitude of the southern pole of projection
37–40	Angle of rotation of projection

Notes:

- (1) The pentagonal representation of resolution is general. Some common truncations are special cases of the pentagonal one:
 - Triangular: $M = J = K$
 - Rhomboidal: $K = J + M$
 - Trapezoidal: $K = J, K > M$
- (2) The stretching is defined by three parameters:
 - (a) The latitude in degrees (measured in the model coordinate system) of the “pole of stretching”;
 - (b) The longitude in degrees (measured in the model coordinate system) of the “pole of stretching”; and
 - (c) The stretching factor C in units of 10^{-6} represented as an integer. The stretching is defined by representing data uniformly in a coordinate system with longitude λ and latitude θ^1 , where:

$$\theta^1 = \sin^{-1} \frac{(1 - C^2) + (1 + C^2) \sin \theta}{(1 + C^2) + (1 - C^2) \sin \theta}$$

and λ and θ are longitude and latitude in a coordinate system in which the “pole of stretching” is the northern pole. $C = 1$ gives uniform resolution, while $C > 1$ gives enhanced resolution around the pole of stretching.

Grid definition template 3.52 – stretched spherical harmonic coefficients

Grid definition template 3.52	
Octet No.	Contents
15–28	Same as grid definition template 3.50
29–32	Latitude of the pole of stretching
33–36	Longitude of the pole of stretching
37–40	Stretching factor

Notes:

- (1) The pentagonal representation of resolution is general. Some common truncations are special cases of the pentagonal one:
- Triangular: $M = J = K$
 Rhomboidal: $K = J + M$
 Trapezoidal: $K = J, K > M$
- (2) The stretching is defined by three parameters:
- (a) The latitude in degrees (measured in the model coordinate system) of the “pole of stretching”;
- (b) The longitude in degrees (measured in the model coordinate system) of the “pole of stretching”; and
- (c) The stretching factor C in units of 10^{-6} represented as an integer. The stretching is defined by representing data uniformly in a coordinate system with longitude λ and latitude θ^1 , where:

$$\theta^1 = \sin^{-1} \frac{(1 - C^2) + (1 + C^2) \sin \theta}{(1 + C^2) + (1 - C^2) \sin \theta}$$

and λ and θ are longitude and latitude in a coordinate system in which the “pole of stretching” is the northern pole. $C = 1$ gives uniform resolution, while $C > 1$ gives enhanced resolution around the pole of stretching.

Grid definition template 3.53 – stretched and rotated spherical harmonic coefficients

Grid definition template 3.53	
Octet No.	Contents
15–28	Same as grid definition template 3.50
29–32	Latitude of the southern pole of projection
33–36	Longitude of the southern pole of projection
37–40	Angle of rotation of projection
41–44	Latitude of pole of stretching
45–48	Longitude of pole of stretching
49–52	Stretching factor

Notes:

- (1) The pentagonal representation of resolution is general. Some common truncations are special cases of the pentagonal one:
- Triangular: $M = J = K$
 Rhomboidal: $K = J + M$
 Trapezoidal: $K = J, K > M$
- (2) The stretching is defined by three parameters:
- (a) The latitude in degrees (measured in the model coordinate system) of the “pole of stretching”;

- (b) The longitude in degrees (measured in the model coordinate system) of the "pole of stretching"; and
- (c) The stretching factor C in units of 10^{-6} represented as an integer. The stretching is defined by representing data uniformly in a coordinate system with longitude λ and latitude θ^1 , where:

$$\theta^1 = \sin^{-1} \frac{(1 - C^2) + (1 + C^2) \sin \theta}{(1 + C^2) + (1 - C^2) \sin \theta}$$

and λ and θ are longitude and latitude in a coordinate system in which the "pole of stretching" is the northern pole. $C = 1$ gives uniform resolution, while $C > 1$ gives enhanced resolution around the pole of stretching.

- (3) The stretching is defined by three parameters:
 - (a) The latitude in degrees (measured in the model coordinate system) of the "pole of stretching";
 - (b) The longitude in degrees (measured in the model coordinate system) of the "pole of stretching"; and
 - (c) The stretching factor C in units of 10^{-6} represented as an integer. The stretching is defined by representing data uniformly in a coordinate system with longitude λ and latitude θ^1 , where:

$$\theta^1 = \sin^{-1} \frac{(1 - C^2) + (1 + C^2) \sin \theta}{(1 + C^2) + (1 - C^2) \sin \theta}$$

and λ and θ are longitude and latitude in a coordinate system in which the "pole of stretching" is the northern pole. $C = 1$ gives uniform resolution, while $C > 1$ gives enhanced resolution around the pole of stretching.

Grid definition template 3.61 – spectral Mercator with modelling subdomains definition

Grid definition template 3.61	
Octet No.	Contents
15	Spectral data representation type (see Code table 3.6)
16–19	N – bi-Fourier resolution parameter
20–23	M – bi-Fourier resolution parameter
24	Type of bi-Fourier truncation (see Code table 3.25)
25–32	Lx – size in meters of the domain along x-axis
33–40	Lux – size in meters of model forecast subdomain along x-axis
41–48	Lcx – width in meters of coupling area within forecast domain along x-axis
49–56	Ly – size in meters of the domain along y-axis
57–64	Luy – size in meters of model forecast subdomain along y-axis
65–72	Lcy – width in meters of coupling area within forecast domain along y-axis
73	Shape of the Earth (see Code table 3.2)
74	Scale factor of radius of spherical Earth
75–78	Scaled value of radius of spherical Earth
79	Scale factor of major axis of oblate spheroid Earth
80–83	Scaled value of major axis of oblate spheroid Earth
84	Scale factor of minor axis of oblate spheroid Earth
85–88	Scaled value of minor axis of oblate spheroid Earth
89–92	La1 – latitude of first grid point
93–96	Lo1 – longitude of first grid point
97–100	LaD – latitude(s) at which the Mercator projection intersects the Earth (latitude(s) where Di and Dj are specified)
101–104	La2 – latitude of last grid point

Grid definition template 3.61	
Octet No.	Contents
105–108	Lo2 – longitude of last grid point
109–112	Orientation of the grid, angle between i–direction on the map and the Equator (see Note)

Note: Limited to the range of 0 to 90 degrees.

Grid definition template 3.62 – spectral polar stereographic with modelling subdomains definition

Grid definition template 3.62	
Octet No.	Contents
15	Spectral data representation type (see Code table 3.6)
16–19	N – bi-Fourier resolution parameter
20–23	M – bi-Fourier resolution parameter
24	Type of bi-Fourier truncation (see Code table 3.25)
25–32	Lx – size in meters of the domain along x-axis
33–40	Lux – size in meters of model forecast subdomain along x-axis
41–48	Lcx – width in meters of coupling area within forecast domain along x-axis
49–56	Ly – size in meters of the domain along y-axis
57–64	Luy – size in meters of model forecast subdomain along y-axis
65–72	Lcy – width in metres of coupling area within forecast domain along y-axis
73	Shape of the Earth (see Code table 3.2)
74	Scale factor of radius of spherical Earth
75–78	Scaled value of radius of spherical Earth
79	Scale factor of major axis of oblate spheroid Earth
80–83	Scaled value of major axis of oblate spheroid Earth
84	Scale factor of minor axis of oblate spheroid Earth
85–88	Scaled value of minor axis of oblate spheroid Earth
89–92	La1 – latitude of first grid point
93–96	Lo1 – longitude of first grid point
97	Resolution and component flags (see Flag table 3.3)
98–101	LaD – latitude where Dx and Dy are specified
102–105	LoV – orientation of the grid
106	Projection centre (see Flag table 3.5)

Grid definition template 3.63 – spectral Lambert conformal with modelling subdomains definition

Grid definition template 3.63	
Octet No.	Contents
15	Spectral data representation type (see Code table 3.6)
16–19	N – bi-Fourier resolution parameter
20–23	M – bi-Fourier resolution parameter
24	Type of bi-Fourier truncation (see Code table 3.25)
25–32	Lx – size in meters of the domain along x-axis
33–40	Lux – size in meters of model forecast subdomain along x-axis
41–48	Lcx – width in meters of coupling area within forecast domain along x-axis
49–56	Ly – size in meters of the domain along y-axis
57–64	Luy – size in meters of model forecast subdomain along y-axis

<i>Grid definition template 3.63</i>	
Octet No.	Contents
65–72	Lcy – width in meters of coupling area within forecast domain along y-axis
73	Shape of the Earth (see Code table 3.2)
74	Scale factor of radius of spherical Earth
75–78	Scaled value of radius of spherical Earth
79	Scale factor of major axis of oblate spheroid Earth
80–83	Scaled value of major axis of oblate spheroid Earth
84	Scale factor of minor axis of oblate spheroid Earth
85–88	Scaled value of minor axis of oblate spheroid Earth
89–92	La1 – latitude of first grid point
93–96	Lo1 – longitude of first grid point
97–100	LaD – latitude where Dx and Dy are specified
101–104	LoV – longitude of meridian parallel to y-axis along which latitude increases as the y-coordinate increases
105	Projection centre (see Flag table 3.5)
106–109	Latin 1 – first latitude from the pole at which the secant cone cuts the sphere
110–113	Latin 2 – second latitude from the pole at which the secant cone cuts the sphere
114–117	Latitude of the southern pole of projection
118–121	Longitude of the southern pole of projection

Grid definition template 3.90 – space view perspective or orthographic

<i>Grid definition template 3.90</i>	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Nx – number of points along x-axis (columns)
35–38	Ny – number of points along y-axis (rows or lines)
39–42	Lap – latitude of sub-satellite point
43–46	Lop – longitude of sub-satellite point
47	Resolution and component flags (see Flag table 3.3)
48–51	dx – apparent diameter of Earth in grid lengths, in x-direction
52–55	dy – apparent diameter of Earth in grid lengths, in y-direction
56–59	Xp – x-coordinate of sub-satellite point (in units of 10^{-3} grid length expressed as an integer)
60–63	Yp – y-coordinate of sub-satellite point (in units of 10^{-3} grid length expressed as an integer)
64	Scanning mode (see Flag table 3.4)
65–68	Orientation of the grid; i.e. the angle between the increasing y-axis and the meridian of the sub-satellite point in the direction of increasing latitude (see Note 3)
69–72	Nr – altitude of the camera from the Earth's centre, measured in units of the Earth's (equatorial) radius multiplied by a scale factor of 10^6 (see Notes 2, 4 and 5)
73–76	Xo – x-coordinate of origin of sector image
77–80	Yo – y-coordinate of origin of sector image

Notes:

- (1) It is assumed that the satellite is at its nominal position, i.e. it is looking directly at its sub-satellite point.
- (2) Octets 69–72 shall be set to all ones (missing) to indicate the orthographic view (from infinite distance).
- (3) It is the angle between the increasing y-axis and the meridian 180°E if the sub-satellite point is the North Pole; or the meridian 0° if the sub-satellite point is the South Pole.
- (4) The apparent angular size of the Earth will be given by $2 \times \arcsin((10^6)/Nr)$.
- (5) For orthographic view from infinite distance, the value of Nr should be encoded as missing (all bits set to 1).
- (6) The horizontal and vertical angular resolutions of the sensor (Rx and Ry), needed for navigation equation, can be calculated from the following:

$$Rx = 2 \times \arcsin((10^6)/Nr)/dx$$

$$Ry = 2 \times \arcsin((10^6)/Nr)/dy$$
- (7) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.
- (8) General reference information pertaining to the projections used for satellite data can be found in Section 4.4 of "LRIT/HRIT Global Specification", Doc. No. CGMS 03, issue 2.6, dated 12 August 1999.

Grid definition template 3.100 – triangular grid based on an icosahedron (see Part B, GRIB Attachment I)

Grid definition template 3.100	
Octet No.	Contents
15	n2 – exponent of 2 for the number of intervals on main triangle sides
16	n3 – exponent of 3 for the number of intervals on main triangle sides
17–18	ni – number of intervals on main triangle sides of the icosahedron
19	nd – number of diamonds
20–23	Latitude of the pole point of the icosahedron on the sphere
24–27	Longitude of the pole point of the icosahedron on the sphere
28–31	Longitude of the centre line of the first diamond of the icosahedron on the sphere
32	Grid point position (see Code table 3.8)
33	Numbering order of diamonds (see Flag table 3.9)
34	Scanning mode for one diamond (see Flag table 3.10)
35–38	nt – total number of grid points


Notes:

- (1) For more details, see Part B, GRIB Attachment I.
- (2) The origin of the grid is an icosahedron with 20 triangles and 12 vertices. The triangles are combined to nd quadrangles, the so-called diamonds (e.g. if nd = 10, two of the icosahedron triangles form a diamond, and if nd = 5, 4 icosahedron triangles form a diamond). There are two resolution values called n2 and n3 describing the division of each triangle side. Each triangle side is divided into ni equal parts, where $ni = 3^{n3} \times 2^{n2}$ with n3 either equal to 0 or to 1. In the example in GRIB Attachment I, the numbering order of the rectangles is anti-clockwise with a view from the pole point on both hemispheres. Diamonds 1 to 5 are northern hemisphere and diamonds 6 to 10 are southern hemisphere.
- (3) The exponent of 3 for the number of divisions of triangle sides is used only with a value of either 0 or 1.
- (4) The total number of grid points for one global field depends on the grid point position. If e.g. the grid points are located at the vertices of the triangles, then $nt = (ni + 1) \times (ni + 1) \times nd$ since grid points at diamond edges are contained in both adjacent diamonds and for the same reason the pole points are contained in each of the five adjacent diamonds.

Grid definition template 3.101 – general unstructured grid

Grid definition template 3.101	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16–18	Number of grid used (defined by originating centre)
19	Number of grid in reference (to allow annotating for Arakawa C-grid on arbitrary grid) (see Note)
20–35	Universally Unique Identifier of horizontal grid

Note: The number given refers to a specific grid required for formulating differential operators. The grid may consist of a centre and an arbitrary surrounding polygon. As model variables may be defined on vertices of the polygons or in the middle of a polygon edge, this generates some different grid descriptions, because each of those is defining their own centre and surrounding polygon. Each of these dependent grids needs their own set of centre longitude/latitude and the longitude/latitude of the boundary polygon vertices. The following picture shows a triangle as base, a hexagon around the triangle's vertices and a quadrilateral around the edge midpoints.



- (a) Triangles (i) (pressure, temperature, ...)
- (b) Quadrilaterals (l) (wind velocity ...)
- (c) Hexagons (or pentagons, respectively) (v) (vorticity, ...)

Grid definition template 3.110 – equatorial azimuthal equidistant projection

Grid definition template 3.110	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Nx – number of points along x-axis
35–38	Ny – number of points along y-axis
39–42	La1 – latitude of tangency point (centre of grid)
43–46	Lo1 – longitude of tangency point
47	Resolution and component flags (see Flag table 3.3)
48–51	Dx – x-direction grid length in units of 10^{-3} m as measured at the point of the axis
52–55	Dy – y-direction grid length in units of 10^{-3} m as measured at the point of the axis
56	Projection centre
57	Scanning mode (see Flag table 3.4)

Note: A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.

Grid definition template 3.120 – azimuth–range projection

<i>Grid definition template 3.120</i>	
Octet No.	Contents
15–18	Nb – number of data bins along radials (see Note)
19–22	Nr – number of radials
23–26	La1 – latitude of centre point
27–30	Lo1 – longitude of centre point
31–34	Dx – spacing of bins along radials
35–38	Dstart – offset from origin to inner bound
39	Scanning mode (flags – see Flag table 3.4)
40–(39+4Nr)	For each of Nr radials
(40+4(X–1))–(41+4(X–1))	Azi – starting azimuth, degrees x 10 (degrees as north)
(42+4(X–1))–(43+4(X–1))	Adelta – azimuthal width, degrees x 100 (+ clockwise, – counterclockwise), with X = 1 to Nr

Note: A data bin is a data point representing the volume centred on it.

Grid definition template 3.140 – Lambert azimuthal equal area projection

<i>Grid definition template 3.140</i>	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Nx – number of points along the x-axis
35–38	Ny – number of points along the y-axis
39–42	La1 – latitude of first grid point
43–46	Lo1 – longitude of first grid point
47–50	Standard parallel
51–54	Central longitude
55	Resolution and component flags (see Flag table 3.3)
56–59	Dx – x-direction grid length (see Note)
60–63	Dy – y-direction grid length (see Note)
64	Scanning mode (see Flag table 3.4)

Note: Grid lengths are in units of 10^{-3} m, at the latitude specified by the standard parallel.

Grid definition template 3.1000 – cross-section grid with points equally spaced on the horizontal

<i>Grid definition template 3.1000</i>	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Number of horizontal points
35–38	Basic angle of the initial production domain (see Note 1)
39–42	Subdivisions of basic angle used to define extreme longitudes and latitudes (see Note 1)
43–46	La1 – latitude of first grid point (see Note 1)
47–50	Lo1 – longitude of first grid point (see Note 1)
51	Scanning mode (flags – see Flag table 3.4)
52–55	La2 – latitude of last grid point (see Note 1)
56–59	Lo2 – longitude of last grid point (see Note 1)
60	Type of horizontal line (see Code table 3.20)
61–62	Number of vertical points
63	Physical meaning of vertical coordinate (see Code table 3.15)
64	Vertical dimension coordinate values definition (see Code table 3.21)
65–66	NC – number of coefficients or values used to specify vertical coordinates
67–(66+NCx4)	Coefficients to define vertical dimension coordinate values in functional form, or the explicit coordinate values (IEEE 32-bit floating-point values)

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the longitudes and latitudes, and direction increments. For these descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number.
For ordinary cases, zero and missing values should be coded, equivalent to the respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.
- (3) This template is simply experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests.

Grid definition template 3.1100 – Hovmöller diagram grid with points equally spaced on the horizontal

Grid definition template 3.1100	
Octet No.	Contents
15	Shape of the Earth (see Code table 3.2)
16	Scale factor of radius of spherical Earth
17–20	Scaled value of radius of spherical Earth
21	Scale factor of major axis of oblate spheroid Earth
22–25	Scaled value of major axis of oblate spheroid Earth
26	Scale factor of minor axis of oblate spheroid Earth
27–30	Scaled value of minor axis of oblate spheroid Earth
31–34	Number of horizontal points
35–38	Basic angle of the initial production domain (see Note 1)
39–42	Subdivisions of basic angle used to define extreme longitudes and latitudes (see Note 1)
43–46	La1 – latitude of first grid point (see Note 1)
47–50	Lo1 – longitude of first grid point (see Note 1)
51	Scanning mode (see Flag table 3.4)
52–55	La2 – latitude of last grid point (see Note 1)
56–59	Lo2 – longitude of last grid point (see Note 1)
60	Type of horizontal line (see Code table 3.20)
61–64	NT – number of time steps
65	Unit of offset from reference time (see Code table 4.4)
66–69	Offset from reference of first time (negative value when first bit set)
70	Type of time increment (see Code table 4.11)
71	Unit of time increment (see Code table 4.4)
72–75	Time increment (negative value when first bit set)
76–82	Last date/time
76–77	Year
78	Month
79	Day
80	Hour
81	Minute
82	Second

Notes:

- (1) Basic angle of the initial production domain and subdivisions of this basic angle are provided to manage cases where the recommended unit of 10^{-6} degrees is not applicable to describe the longitudes and latitudes, and direction increments. For these descriptors, the unit is equal to the ratio of the basic angle and the subdivisions number.
For ordinary cases, zero and missing values should be coded, equivalent to the respective values of 1 and 10^6 (10^{-6} degrees unit).
- (2) A scaled value of radius of spherical Earth, or major or minor axis of oblate spheroid Earth, is derived by applying the appropriate scale factor to the value expressed in metres.
- (3) This template is simply experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests.

Grid definition template 3.1200 – time section grid

<i>Grid definition template 3.1200</i>	
Octet No.	Contents
15–18	NT – number of time steps
19	Unit of offset from reference time (see Code table 4.4)
20–23	Offset from reference of first time (negative value when first bit set)
24	Type of time increment (see Code table 4.11)
25	Unit of time increment (see Code table 4.4)
26–29	Time increment (negative value when first bit set)
<i>30–36 Last date/time</i>	
30–31	Year
32	Month
33	Day
34	Hour
35	Minute
36	Second
37–38	Number of vertical points
39	Physical meaning of vertical coordinate (see Code table 3.15)
40	Vertical dimension coordinate values definition (see Code table 3.21)
41–42	NC – number of coefficients or values used to specify vertical coordinates
43– (42+NCx4)	Coefficients to define vertical dimension coordinate values in functional form, or the explicit coordinate values (IEEE 32-bit floating-point values)

Note: This template is simply experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests.

TEMPLATE DEFINITIONS USED IN SECTION 4***Product definition template 4.0 – analysis or forecast at a horizontal level or in a horizontal layer at a point in time***

<i>Product definition template 4.0</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours of observational data cut-off after reference time (see Note)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.1 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time

<i>Product definition template 4.1</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Type of ensemble forecast (see Code table 4.6)
36	Perturbation number
37	Number of forecasts in ensemble

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.2 – derived forecasts based on all ensemble members at a horizontal level or in a horizontal layer at a point in time

Product definition template 4.2	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Derived forecast (see Code table 4.7)
36	Number of forecasts in ensemble

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.3 – derived forecasts based on a cluster of ensemble members over a rectangular area at a horizontal level or in a horizontal layer at a point in time

Product definition template 4.3	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Derived forecast (see Code table 4.7)
36	Number of forecasts in the ensemble (N)
37	Cluster identifier
38	Number of cluster to which the high-resolution control belongs
39	Number of cluster to which the low-resolution control belongs
40	Total number of clusters

<i>Product definition template 4.3</i>	
Octet No.	Contents
41	Clustering method (see Code table 4.8)
42–45	Northern latitude of cluster domain
46–49	Southern latitude of cluster domain
50–53	Eastern longitude of cluster domain
54–57	Western longitude of cluster domain
58	N_c – number of forecasts in the cluster
59	Scale factor of standard deviation in the cluster
60–63	Scaled value of standard deviation in the cluster
64	Scale factor of distance of the cluster from ensemble mean
65–68	Scaled value of distance of the cluster from ensemble mean
69–(68+ N_c)	List of N_c ensemble forecast numbers (N_c is given in octet 58)

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.4 – derived forecasts based on a cluster of ensemble members over a circular area at a horizontal level or in a horizontal layer at a point in time

<i>Product definition template 4.4</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Derived forecast (see Code table 4.7)
36	Number of forecasts in the ensemble (N)
37	Cluster identifier
38	Number of cluster to which the high-resolution control belongs
39	Number of cluster to which the low-resolution control belongs
40	Total number of clusters
41	Clustering method (see Code table 4.8)
42–45	Latitude of central point in cluster domain
46–49	Longitude of central point in cluster domain
50–53	Radius of cluster domain
54	N_c – number of forecasts in the cluster
55	Scale factor of standard deviation in the cluster
56–59	Scaled value of standard deviation in the cluster

<i>Product definition template 4.4</i>	
Octet No.	Contents
60	Scale factor of distance of the cluster from ensemble mean
61–64	Scaled value of distance of the cluster from ensemble mean
65–(64+N _c)	List of N _c ensemble forecast numbers (N _c is given in octet 54)

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.5 – probability forecasts at a horizontal level or in a horizontal layer at a point in time

<i>Product definition template 4.5</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Forecast probability number
36	Total number of forecast probabilities
37	Probability type (see Code table 4.9)
38	Scale factor of lower limit
39–42	Scaled value of lower limit
43	Scale factor of upper limit
44–47	Scaled value of upper limit

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.6 – percentile forecasts at a horizontal level or in a horizontal layer at a point in time

<i>Product definition template 4.6</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)

<i>Product definition template 4.6</i>	
Octet No.	Contents
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Percentile value (from 100% to 0%)

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.7 – analysis or forecast error at a horizontal level or in a horizontal layer at a point in time

<i>Product definition template 4.7</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) This template should not be used. Product definition template 4.0 should be used instead.

Product definition template 4.8 – average, accumulation and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

<i>Product definition template 4.8</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time of data cut-off

Product definition template 4.8	
Octet No.	Contents
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35–36	Year
37	Month
38	Day
39	Hour
40	Minute
41	Second
42	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
43–46	Total number of data values missing in statistical process
	<i>47–58 Specification of the outermost (or only) time range over which statistical processing is done</i>
47	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
48	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
49	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
50–53	Length of the time range over which statistical processing is done, in units defined by the previous octet
54	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
55–58	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
	<i>59–nn These octets are included only if $n > 1$, where $nn = 46 + 12 \times n$</i>
59–70	As octets 47 to 58, next innermost step of processing
71–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 47 to 58, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 48, 60, 72, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.9 – probability forecasts at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.9	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Forecast probability number
36	Total number of forecast probabilities
37	Probability type (see Code table 4.9)
38	Scale factor of lower limit
39–42	Scaled value of lower limit
43	Scale factor of upper limit
44–47	Scaled value of upper limit
48–49	Year of end of overall time interval
50	Month of end of overall time interval
51	Day of end of overall time interval
52	Hour of end of overall time interval
53	Minute of end of overall time interval
54	Second of end of overall time interval
55	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
56–59	Total number of data values missing in the statistical process
60–71	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
60	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
61	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
62	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
63–66	Length of the time range over which statistical processing is done, in units defined by the previous octet
67	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
68–71	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)

Product definition template 4.9	
Octet No.	Contents
	72–nn These octets are included only if $n > 1$, where $nn = 59 + 12 \times n$
72–83	As octets 60 to 71, next innermost step of processing
84–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 60 to 71, repeated as necessary.

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 46, 58, 70, ...). For all but the innermost (last) time range, the next inner range is then processed using these references and forecast times as the initial reference and forecast times.

Product definition template 4.10 – percentile forecasts at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.10	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time for data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by previous octet (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Percentile value (from 100% to 0%)
36–37	Year of end of overall time interval
38	Month of end of overall time interval
39	Day of end of overall time interval
40	Hour of end of overall time interval
41	Minute of end of overall time interval
42	Second of end of overall time interval
43	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
44–47	Total number of data values missing in the statistical process

Product definition template 4.10	
Octet No.	Contents
	<i>48–59 Specification of the outermost (or only) time range over which statistical processing is done</i>
48	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
49	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
50	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
51–54	Length of the time range over which statistical processing is done, in units defined by the previous octet
55	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
56–59	Time increment between successive fields, in units defined by the previous octet (see Note 3)
	<i>60–nn These octets are included only if $n > 1$, where $nn = 47 + 12 \times n$</i>
60–71	As octets 48–59, next innermost step of processing
72–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 48 to 59, repeated as necessary.

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) This template was not validated at the time of publication and should be used with caution. Please report any use to the WMO Secretariat to assist with validation.

Product definition template 4.11 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.11	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see : 1)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Type of ensemble forecast (see Code table 4.6)

Product definition template 4.11

Octet No.	Contents
36	Perturbation number
37	Number of forecasts in ensemble
38–39	Year of end of overall time interval
40	Month of end of overall time interval
41	Day of end of overall time interval
42	Hour of end of overall time interval
43	Minute of end of overall time interval
44	Second of end of overall time interval
45	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
46–49	Total number of data values missing in statistical process
	<i>50–61 Specification of the outermost (or only) time range over which statistical processing is done</i>
50	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
51	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
52	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
53–56	Length of the time range over which statistical processing is done, in units defined by the previous octet
57	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
58–61	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
	<i>62–nn These octets are included only if $n > 1$, where $nn = 49 + 12 \times n$</i>
62–73	As octets 50 to 61, next innermost step of processing
74–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 50 to 61, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 51, 63, 75, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.12 – derived forecasts based on all ensemble members at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.12	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Derived forecast (see Code table 4.7)
36	Number of forecasts in the ensemble (N)
37–38	Year of end of overall time interval
39	Month of end of overall time interval
40	Day of end of overall time interval
41	Hour of end of overall time interval
42	Minute of end of overall time interval
43	Second of end of overall time interval
44	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
45–48	Total number of data values missing in statistical process
49–60	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
49	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
50	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
51	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
52–55	Length of the time range over which statistical processing is done, in units defined by the previous octet
56	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
57–60	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
61–nn	<i>These octets are included only if $n > 1$, where $nn = 48 + 12 \times n$</i>
61–72	As octets 49 to 60, next innermost step of processing
73–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 49 to 60, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 50, 62, 74, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.13 – derived forecasts based on a cluster of ensemble members over a rectangular area at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

<i>Product definition template 4.13</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Derived forecast (see Code table 4.7)
36	Number of forecasts in the ensemble (N)
37	Cluster identifier
38	Number of cluster to which the high-resolution control belongs
39	Number of cluster to which the low-resolution control belongs
40	Total number of clusters
41	Clustering method (see Code table 4.8)
42–45	Northern latitude of cluster domain
46–49	Southern latitude of cluster domain
50–53	Eastern longitude of cluster domain
54–57	Western longitude of cluster domain
58	N _c – number of forecasts in the cluster
59	Scale factor of standard deviation in the cluster
60–63	Scaled value of standard deviation in the cluster
64	Scale factor of distance of the cluster from ensemble mean
65–68	Scaled value of distance of the cluster from ensemble mean
69–70	Year of end of overall time interval
71	Month of end of overall time interval

Product definition template 4.13	
Octet No.	Contents
72	Day of end of overall time interval
73	Hour of end of overall time interval
74	Minute of end of overall time interval
75	Second of end of overall time interval
76	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
77–80	Total number of data values missing in statistical process
	<i>81–92 Specification of the outermost (or only) time range over which statistical processing is done</i>
81	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
82	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
83	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
84–87	Length of the time range over which statistical processing is done, in units defined by the previous octet
88	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
89–92	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
	<i>93–nn These octets are included only if $n > 1$, where $nn = 80 + 12 \times n$</i>
93–104	As octets 81 to 92, next innermost step of processing
105–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 81 to 92, repeated as necessary
(nn+1)–(nn+N _C)	List of N _C ensemble forecast numbers (N _C is given in octet 58)

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 82, 94, 106,...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.14 – derived forecasts based on a cluster of ensemble members over a circular area at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.14	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)

Product definition template 4.14

Octet No.	Contents
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Derived forecast (see Code table 4.7)
36	Number of forecasts in the ensemble (N)
37	Cluster identifier
38	Number of cluster to which the high-resolution control belongs
39	Number of cluster to which the low-resolution control belongs
40	Total number of clusters
41	Clustering method (see Code table 4.8)
42–45	Latitude of central point in cluster domain
46–49	Longitude of central point in cluster domain
50–53	Radius of cluster domain
54	N_c – number of forecasts in the cluster
55	Scale factor of standard deviation in the cluster
56–59	Scaled value of standard deviation in the cluster
60	Scale factor of distance of the cluster from ensemble mean
61–64	Scaled value of distance of the cluster from ensemble mean
65–66	Year of end of overall time interval
67	Month of end of overall time interval
68	Day of end of overall time interval
69	Hour of end of overall time interval
70	Minute of end of overall time interval
71	Second of end of overall time interval
72	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
73–76	Total number of data values missing in statistical process
	<i>77–88 Specification of the outermost (or only) time range over which statistical processing is done</i>
77	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
78	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
79	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
80–83	Length of the time range over which statistical processing is done, in units defined by the previous octet
84	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
85–88	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)

Product definition template 4.14	
Octet No.	Contents
	89–nn These octets are included only if $n > 1$, where $nn = 76 + 12 \times n$
89–110	As octets 77 to 88, next innermost step of processing
111–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 77 to 88, repeated as necessary
(nn+1)–(nn+N _C)	List of N _C ensemble forecast numbers (N _C is given in octet 54)

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 78, 90, 112, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.15 – average, accumulation, extreme values, or other statistically processed values over a spatial area at a horizontal level or in a horizontal layer at a point in time

Product definition template 4.15	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours of observational data cut-off after reference time (see Note)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Statistical process used within the spatial area defined by octet 36 (see Code table 4.10)
36	Type of spatial processing used to arrive at given data value from the source data (see Code table 4.15)
37	Number of data points used in spatial processing defined in octet 36

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.20 – radar product

<i>Product definition template 4.20</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Number of radar sites used
14	Indicator of unit of time range
15–18	Site latitude (in 10^{-6} degree)
19–22	Site longitude (in 10^{-6} degree)
23–24	Site elevation (metres)
25–28	Site ID (alphanumeric)
29–30	Site ID (numeric)
31	Operating mode (see Code table 4.12)
32	Reflectivity calibration constant (tenths of dB)
33	Quality control indicator (see Code table 4.13)
34	Clutter filter indicator (see Code table 4.14)
35	Constant antenna elevation angle (tenths of degree true)
36–37	Accumulation interval (minutes)
38	Reference reflectivity for echo top (dB)
39–41	Range bin spacing (metres)
42–43	Radial angular spacing (tenths of degree true)

Product definition template 4.30 – satellite product

<i>Product definition template 4.30</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Observation generating process identifier (defined by originating centres)
14	Number of contributing spectral bands (NB)
15–	<i>Repeat the following 10 octets for each contributing band (nb = 1, NB)</i>
(15+10(nb–1))–(16+10(nb–1))	Satellite series of band nb (code table defined by originating/generating centre) (see Note 2)
(17+10(nb–1))–(18+10(nb–1))	Satellite numbers of band nb (code table defined by originating/generating centre) (see Note 2)
(19+10(nb–1))	Instrument types of band nb (code table defined by originating/generating centre) (see Note 2)
(20+10(nb–1))	Scale factor of central wave number of band nb
(21+10(nb–1))–(24+10(nb–1))	Scaled value of central wave number of band nb (units: m^{-1})

Notes:

- (1) This template is deprecated. Template 4.31 should be used instead.
- (2) For “satellite series of band nb”, “satellite numbers of band nb” and “instrument types of band nb”, it is recommended to encode the values as per BUFR Code tables 0 02 020, 0 01 007 (Common Code table C–5) and 0 02 019 (Common Code table C–8), respectively.

Product definition template 4.31 – satellite product

Product definition template 4.31	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Observation generating process identifier (defined by originating centres)
14	Number of contributing spectral bands (NB)
15– Repeat the following 11 octets for each contributing band ($nb = 1, NB$)	
(15+11(nb-1))–(16+11(nb-1))	Satellite series of band nb (code table defined by originating/generating centre) (see Note)
(17+11(nb-1))–(18+11(nb-1))	Satellite numbers of band nb (code table defined by originating/generating centre) (see Note)
(19+11(nb-1))–(20+11(nb-1))	Instrument types of band nb (code table defined by originating/generating centre) (see Note)
(21+11(nb-1))	Scale factor of central wave number of band nb
(22+11(nb-1))–(25+11(nb-1))	Scaled value of central wave number of band nb (units: m^{-1})

Note: For "satellite series of band nb", "satellite numbers of band nb" and "instrument types of band nb", it is recommended to encode the values as per BUFR Code tables 0 02 020, 0 01 007 (Common Code table C-5) and 0 02 019 (Common Code table C-8), respectively.

Product definition template 4.32 – analysis or forecast at a horizontal level or in a horizontal layer at a point in time for simulated (synthetic) satellite data

Product definition template 4.32	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier
15–16	Hours of observational data cut-off after reference time (see Note 2)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Number of contributing spectral bands (NB)
24– Repeat the following 11 octets for each contributing band ($nb = 1, NB$)	
(24+11(nb-1))–(25+11(nb-1))	Satellite series of band nb (Code table defined by originating/generating centre) (see Note 1)
(26+11(nb-1))–(27+11(nb-1))	Satellite number of band nb (Code table defined by originating/generating centre) (see Note 1)
(28+11(nb-1))–(29+11(nb-1))	Instrument types of band nb (Code table defined by originating/generating centre) (see Note 1)
(30 +11(nb-1))	Scale factor of central wave number of band nb
(31+11(nb-1))–(34+11(nb-1))	Scaled value of central wave number of band nb (units: m^{-1})

Notes:

- (1) For "satellite series of band nb", "satellite numbers of band nb" and "instrument types of band nb", it is recommended to encode the values as per BUFR Code tables 0 02 020, 0 01 007 (Common Code table C-5) and 0 02 019 (Common Code table C-8), respectively.
- (2) Hours greater than 65534 will be coded as 65534.

Product definition template 4.33 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for simulated (synthetic) satellite data

Product definition template 4.33	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier
15–16	Hours of observational data cut-off after reference time (see Note)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Number of contributing spectral bands (NB)
24– Repeat the following 11 octets for each contributing band ($nb = 1, NB$)	
(24+11(nb-1))–(25+11(nb-1))	Satellite series of band nb (code table defined by originating/generating centre)
(26+11(nb-1))–(27+11(nb-1))	Satellite number of band nb (code table defined by originating/generating centre)
(28+11(nb-1))–(29+11(nb-1))	Instrument types of band nb (code table defined by originating/generating centre)
(30+11(nb-1))	Scale factor of central wave number of band nb
(31+11(nb-1))–(34+11(nb-1))	Scaled value of central wave number of band nb (units: m^{-1})
(24+11NB)	Type of ensemble forecast (see Code table 4.6)
(24+11NB+1)	Perturbation number
(24+11NB+2)	Number of forecasts in ensemble

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.34 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous interval for simulated (synthetic) satellite data

Product definition template 4.34	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier
15–16	Hours of observational data cut-off after reference time (see Note 1)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Number of contributing spectral bands (NB)
24– Repeat the following 11 octets for each contributing band ($nb = 1, NB$)	
(24+11(nb-1))–(25+11(nb-1))	Satellite series of band nb (code table defined by originating/generating centre)
(26+11(nb-1))–(27+11(nb-1))	Satellite number of band nb (code table defined by originating/generating centre)

		Product definition template 4.34
Octet No.	Contents	
(28+11(nb-1))-(29+11(nb-1))		Instrument types of band nb (code table defined by originating/generating centre)
(30+11(nb-1))		Scale factor of central wave number of band nb
(31+11(nb-1))-(34+11(nb-1))		Scaled value of central wave number of band nb (units: m ⁻¹)
(24+11NB)		Type of ensemble forecast (see Code table 4.6)
(25+11NB)		Perturbation number
(26+11NB)		Number of forecasts in ensemble
(27+11NB)-(28+11NB)		Year of end of overall time interval
(29+11NB)		Month of end of overall time interval
(30+11NB)		Day of end of overall time interval
(31+11NB)		Hour of end of overall time interval
(32+11NB)		Minute of end of overall time interval
(33+11NB)		Second of end of overall time interval
(34+11NB)		n – number of time range specifications describing the time intervals used to calculate the statistically processed field
(35+11NB)-(38+11NB)		Total number of data values missing in statistical process
		(39+11NB)– Repeat the following 12 octets for each time range spec (i = 1, n)
(39+11NB+12(i-1))		Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
(40+11NB+12(i-1))		Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
(41+11NB+12(i-1))		Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
(42+11NB+12(i-1))– (45+11NB+12(i-1))		Length of the time range over which statistical processing is done, in units defined by the previous octet
(46+11NB+12(i-1))		Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
(47+11NB+12(i-1))– (50+11NB+12(i-1))		Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 51, 62, 73, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.35 – satellite product with or without associated quality values

<i>Product definition template 4.35</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Observation generating process identifier (defined by originating centres)
14	Quality value associated with parameter (see Code table 4.16)
15	Number of contributing spectral bands (NB)
<i>16– Repeat the following 11 octets for each contributing band (nb = 1,NB)</i>	
(16+11(nb-1))–(17+11(nb-1))	Satellite series of band nb (code table defined by originating/generating centre) (see Note)
(18+11(nb-1))–(19+11(nb-1))	Satellite numbers of band nb (code table defined by originating/generating centre) (see Note)
(20+11(nb-1))–(21+11(nb-1))	Instrument types of band nb (code table defined by originating/generating centre) (see Note)
(22+11(nb-1))	Scale factor of central wave number of band nb
(23+11(nb-1))–(26+11(nb-1))	Scaled value of central wave number of band nb (units: m ⁻¹)

Note: For “satellite series of band nb”, “satellite numbers of band nb” and “instrument types of band nb”, it is recommended to encode the values as per BUFR Code tables 0 02 020, 0 01 007 (Common Code table C-5) and 0 02 019 (Common Code table C-8), respectively.

Product definition template 4.40 – analysis or forecast at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents

<i>Product definition template 4.40</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14	Type of generating process (see Code table 4.3)
15	Background generating process identifier (defined by originating centre)
16	Analysis or forecast generating process identifier (defined by originating centre)
17–18	Hours of observational data cut-off after reference time (see Note)
19	Minutes of observational data cut-off after reference time
20	Indicator of unit of time range (see Code table 4.4)
21–24	Forecast time in units defined by octet 20
25	Type of first fixed surface (see Code table 4.5)
26	Scale factor of first fixed surface
27–30	Scaled value of first fixed surface
31	Type of second fixed surface (see Code table 4.5)
32	Scale factor of second fixed surface
33–36	Scaled value of second fixed surface

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.41 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents

Product definition template 4.41	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14	Type of generating process (see Code table 4.3)
15	Background generating process identifier (defined by originating centre)
16	Forecast generating process identifier (defined by originating centre)
17–18	Hours after reference time of data cut-off (see Note)
19	Minutes after reference time of data cut-off
20	Indicator of unit of time range (see Code table 4.4)
21–24	Forecast time in units defined by octet 20
25	Type of first fixed surface (see Code table 4.5)
26	Scale factor of first fixed surface
27–30	Scaled value of first fixed surface
31	Type of second fixed surface (see Code table 4.5)
32	Scale factor of second fixed surface
33–36	Scaled value of second fixed surface
37	Type of ensemble forecast (see Code table 4.6)
38	Perturbation number
39	Number of forecasts in ensemble

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.42 – average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents

Product definition template 4.42	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14	Type of generating process (see Code table 4.3)
15	Background generating process identifier (defined by originating centre)
16	Analysis or forecast generating process identifier (defined by originating centre)
17–18	Hours after reference time of data cut-off (see Note 1)
19	Minutes after reference time of data cut-off
20	Indicator of unit of time range (see Code table 4.4)
21–24	Forecast time in units defined by octet 20 (see Note 2)
25	Type of first fixed surface (see Code table 4.5)
26	Scale factor of first fixed surface
27–30	Scaled value of first fixed surface
31	Type of second fixed surface (see Code table 4.5)
32	Scale factor of second fixed surface
33–36	Scaled value of second fixed surface
37–38	Year

Product definition template 4.42	
Octet No.	Contents
39	Month
40	Day
41	Hour
42	Minute
43	Second
44	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
45–48	Total number of data values missing in statistical process
49–60	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
49	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
50	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
51	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
52–55	Length of the time range over which statistical processing is done, in units defined by the previous octet
56	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
57–60	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
61–nn	<i>These octets are included only if $n > 1$, where $nn = 48 + 12 \times n$</i>
61–72	As octets 49 to 60, next innermost step of processing
73–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 49 to 60, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 50, 62, 74, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.43 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents

Product definition template 4.43	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14	Type of generating process (see Code table 4.3)
15	Background generating process identifier (defined by originating centre)
16	Forecast generating process identifier (defined by originating centre)
17–18	Hours after reference time of data cut-off (see Note 1)
19	Minutes after reference time of data cut-off
20	Indicator of unit of time range (see Code table 4.4)
21–24	Forecast time in units defined by octet 20 (see Note 2)
25	Type of first fixed surface (see Code table 4.5)
26	Scale factor of first fixed surface
27–30	Scaled value of first fixed surface
31	Type of second fixed surface (see Code table 4.5)
32	Scale factor of second fixed surface
33–36	Scaled value of second fixed surface
37	Type of ensemble forecast (see Code table 4.6)
38	Perturbation number
39	Number of forecasts in ensemble
40–41	Year of end of overall time interval
42	Month of end of overall time interval
43	Day of end of overall time interval
44	Hour of end of overall time interval
45	Minute of end of overall time interval
46	Second of end of overall time interval
47	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
48–51	Total number of data values missing in statistical process
52–63	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
52	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
53	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
54	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
55–58	Length of the time range over which statistical processing is done, in units defined by the previous octet
59	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
60–63	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
64–nn	<i>These octets are included only if $n > 1$, where $nn = 51 + 12 \times n$</i>
64–75	As octets 52 to 63, next innermost step of processing
76–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 52 to 63, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 53, 65, 77, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

**Product definition template 4.44 – analysis or forecast at a horizontal level
or in a horizontal layer at a point in time for aerosol**

<i>Product definition template 4.44</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Code table 4.233)
14	Type of interval for first and second sizes (see Code table 4.91)
15	Scale factor of first size
16–19	Scaled value of first size in metres
20	Scale factor of second size
21–24	Scaled value of second size in metres
25	Type of generating process (see Code table 4.3)
26	Background generating process identifier (defined by originating centre)
27	Analysis or forecast generating process identifier (defined by originating centre)
28–29	Hours of observational data cut-off after reference time (see Note 1)
30	Minutes of observational data cut-off after reference time
31	Indicator of unit of time range (see Code table 4.4)
32–33	Forecast time in units defined by octet 31
34	Type of first fixed surface (see Code table 4.5)
35	Scale factor of first fixed surface
36–39	Scaled value of first fixed surface
40	Type of second fixed surface (see Code table 4.5)
41	Scale factor of second fixed surface
42–45	Scaled value of second fixed surface

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) It is recommended not to use this template. PDT 4.48 should be used instead with optical wavelength range set to missing.

Product definition template 4.45 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for aerosol

Product definition template 4.45	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Code table 4.233)
14	Type of interval for first and second sizes (see Code table 4.91)
15	Scale factor of first size
16–19	Scaled value of first size in metres
20	Scale factor of second size
21–24	Scaled value of second size in metres
25	Type of generating process (see Code table 4.3)
26	Background generating process identifier (defined by originating centre)
27	Forecast generating process identifier (defined by originating centre)
28–29	Hours after reference time of data cut-off (see Note)
30	Minutes after reference time of data cut-off
31	Indicator of unit of time range (see Code table 4.4)
32–35	Forecast time in units defined by octet 31
36	Type of first fixed surface (see Code table 4.5)
37	Scale factor of first fixed surface
38–41	Scaled value of first fixed surface
42	Type of second fixed surface (see Code table 4.5)
43	Scale factor of second fixed surface
44–47	Scaled value of second fixed surface
48	Type of ensemble forecast (see Code table 4.6)
49	Perturbation number
50	Number of forecasts in ensemble

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.46 – average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol

Product definition template 4.46	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Code table 4.233)
14	Type of interval for first and second sizes (see Code table 4.91)
15	Scale factor of first size
16–19	Scaled value of first size in metres
20	Scale factor of second size
21–24	Scaled value of second size in metres
25	Type of generating process (see Code table 4.3)
26	Background generating process identifier (defined by originating centre)
27	Analysis or forecast generating process identifier (defined by originating centre)
28–29	Hours after reference time of data cut-off (see Note 1)
30	Minutes after reference time of data cut-off

Product definition template 4.46	
Octet No.	Contents
31	Indicator of unit of time range (see Code table 4.4)
32–35	Forecast time in units defined by octet 31 (see Note 2)
36	Type of first fixed surface (see Code table 4.5)
37	Scale factor of first fixed surface
38–41	Scaled value of first fixed surface
42	Type of second fixed surface (see Code table 4.5)
43	Scale factor of second fixed surface
44–47	Scaled value of second fixed surface
48–49	Year
50	Month
51	Day
52	Hour
53	Minute
54	Second
55	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
56–59	Total number of data values missing in statistical process
60–71	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
60	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
61	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
62	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
63–66	Length of the time range over which statistical processing is done, in units defined by the previous octet
67	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
68–71	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
72–nn	<i>These octets are included only if $n > 1$, where $nn = 59 + 12 \times n$</i>
72–83	As octets 60 to 71, next innermost step of processing
84–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 60 to 71, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 61, 72, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.47 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol

Product definition template 4.47	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13–14	Aerosol type (see Code table 4.233)
15	Type of interval for first and second sizes (see Code table 4.91)
16	Scale factor of first size
17–20	Scaled value of first size in metres
21	Scale factor of second size
22–25	Scaled value of second size in metres
26	Background generating process identifier (defined by originating centre)
27	Forecast generating process identifier (defined by originating centre)
28–29	Hours after reference time of data cut-off (see Note 1)
30	Minutes after reference time of data cut-off
31	Indicator of unit of time range (see Code table 4.4)
32–35	Forecast time in units defined by octet 31 (see Note 2)
36	Type of first fixed surface (see Code table 4.5)
37	Scale factor of first fixed surface
38–41	Scaled value of first fixed surface
42	Type of second fixed surface (see Code table 4.5)
43	Scale factor of second fixed surface
44–47	Scaled value of second fixed surface
48	Type of ensemble forecast (see Code table 4.6)
49	Perturbation number
50	Number of forecasts in ensemble
51–52	Year of end of overall time interval
53	Month of end of overall time interval
54	Day of end of overall time interval
55	Hour of end of overall time interval
56	Minute of end of overall time interval
57	Second of end of overall time interval
58	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
59–62	Total number of data values missing in statistical process
63–74	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
63	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
64	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
65	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
66–69	Length of the time range over which statistical processing is done, in units defined by the previous octet
70	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
71–74	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)

Product definition template 4.47

Octet No.	Contents
	<i>75–nn These octets are included only if $n > 1$, where $nn = 62 + 12 \times n$</i>
75–86	As octets 63 to 74, next innermost step of processing
87–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 63 to 74, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 63, 75, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.48 – analysis or forecast at a horizontal level or in a horizontal layer at a point in time for optical properties of aerosol

Product definition template 4.48

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Common Code table C-14)
14	Type of interval for first and second size (see Code table 4.91)
15	Scale factor of first size
16–19	Scaled value of first size in metres
20	Scale factor of second size
21–24	Scaled value of second size in metres
25	Type of interval for first and second wavelength (see Code table 4.91)
26	Scale factor of first wavelength
27–30	Scaled value of first wavelength in metres
31	Scale factor of second wavelength
32–35	Scaled value of second wavelength in metres
36	Type of generating process (see Code table 4.3)
37	Background generating process identifier (defined by originating centre)
38	Analysis or forecast generating process identifier (defined by originating centre)
39–40	Hours of observational data cut-off after reference time (see Note)
41	Minutes of observational data cut-off after reference time
42	Indicator of unit of time range (see Code table 4.4)
43–46	Forecast time in units defined by octet 42
47	Type of first fixed surface (see Code table 4.5)
48	Scale factor of first fixed surface
49–52	Scaled value of first fixed surface
53	Type of second fixed surface (see Code table 4.5)
54	Scale factor of second fixed surface
55–58	Scaled value of second fixed surface

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.49 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for optical properties of aerosol

<i>Product definition template 4.49</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Common Code table C–14)
14	Type of interval for first and second size (see Code table 4.91)
15	Scale factor of first size
16–19	Scaled value of first size in metres
20	Scale factor of second size
21–24	Scaled value of second size in metres
25	Type of interval for first and second wavelength (see Code table 4.91)
26	Scale factor of first wavelength
27–30	Scaled value of first wavelength in metres
31	Scale factor of second wavelength
32–35	Scaled value of second wavelength in metres
36	Type of generating process (see Code table 4.3)
37	Background generating process identifier (defined by originating centre)
38	Analysis or forecast generating process identifier (defined by originating centre)
39–40	Hours of observational data cut-off after reference time (see Note)
41	Minutes of observational data cut-off after reference time
42	Indicator of unit of time range (see Code table 4.4)
43–46	Forecast time in units defined by octet 42
47	Type of first fixed surface (see Code table 4.5)
48	Scale factor of first fixed surface
49–52	Scaled value of first fixed surface
53	Type of second fixed surface (see Code table 4.5)
54	Scale factor of second fixed surface
55–58	Scaled value of second fixed surface
59	Type of ensemble forecast (see Code table 4.6)
60	Perturbation number
61	Number of forecasts in ensemble

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.51 – categorical forecasts at a horizontal level or in a horizontal layer at a point in time

<i>Product definition template 4.51</i>	
Octet No.	Contents
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)

<i>Product definition template 4.51</i>	
Octet No.	Contents
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	NC – number of categories
	<i>36– Repeat the following 12 octets for each category (i = 1, NC)</i>
(36+12(i–1))	Code figure
(37+12(i–1))	Type of interval for first and second limits (see Code table 4.91)
(38+12(i–1))	Scale factor of first limit
(39+12(i–1))–(42+12(i–1))	Scaled value of first limit
(43+12(i–1))	Scale factor of second limit
(44+12(i–1))–(47+12(i–1))	Scaled value of second limit

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.53 – partitioned parameters at a horizontal level or in a horizontal layer at a point in time

<i>Product definition template 4.53</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2 and Notes 2 and 3)
12	Partition Table Number (PTN) (see Notes 1 and 3)
13	Number of Partitions (NP) (see Note 1)
14–(14+2NP–1)	Partition set (list all partition numbers in the partition) (see Code table 4.PTN and Note 1)
(14+2NP)–(15+2NP)	Partition number (PN) (see Code table 4.PTN and Note 3)
(16+2NP)	Type of generating process (see Code table 4.3)
(17+2NP)	Background generating process identifier (defined by originating centre)
(18+2NP)	Analysis or forecast generating process identifier (defined by originating centre)
(19+2NP)–(20+2NP)	Hours of observational data cut-off after reference time (see Note 1)
(21+2NP)	Minutes of observational data cut-off after reference time
(22+2NP)	Indicator of unit of time range (see Code table 4.4)
(23+2NP)–(26+2NP)	Forecast time in units defined by previous octet
(27+2NP)	Type of first fixed surface (see Code table 4.5)
(28+2NP)	Scale factor of first fixed surface
(29+2NP)–(32+2NP)	Scaled value of first fixed surface
(33+2NP)	Type of second fixed surface (see Code table 4.5)
(34+2NP)	Scale factor of second fixed surface
(35+2NP)–(38+2NP)	Scaled value of second fixed surface

Notes:

- (1) A single partition with code value PN from the partition set composed by the NP partitions is represented in the template. The code values of the NP partitions are expressed in octets 14 to 14+2NP–1. The NP partitions are linked by the normalization formula stating that the sum of all the NP partitions must be equal to a normalization term (N) on each point of the grid.

- (2) Only parameters expressing fractions or percentages can be used in this template. Code tables shall state clearly that they are meant to be used in partitioned parameters context.
- (3) The word "fraction" or the word "percentage" has to be explicitly used in the name of the parameter to refer to a normalization term $N = 1$ in the case of "fraction" and $N = 100$ in the case of percentage.

Product definition template 4.54 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for partitioned parameters

<i>Product definition template 4.54</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2 and Notes 2 and 3)
12	Partition Table Number (PTN) (see Notes 1 and 3)
13	Number of Partitions (NP) (see Note 1)
14–(14+2NP–1)	Partition set (list all partition numbers in the partition) (see Code table 4.PTN and Note 1)
(14+2NP)–(15+2NP)	Partition number (PN) (see Code table 4.PTN and Note 3)
(16+2NP)	Type of generating process (see Code table 4.3)
(17+2NP)	Background generating process identifier (defined by originating centre)
(18+2NP)	Analysis or forecast generating process identifier (defined by originating centre)
(19+2NP)–(20+2NP)	Hours of observational data cut-off after reference time (see Note 1)
(21+2NP)	Minutes of observational data cut-off after reference time
(22+2NP)	Indicator of unit of time range (see Code table 4.4)
(23+2NP)–(26+2NP)	Forecast time in units defined by octet (22+2NP)
(27+2NP)	Type of first fixed surface (see Code table 4.5)
(28+2NP)	Scale factor of first fixed surface
(29+2NP)–(32+2NP)	Scaled value of first fixed surface
(33+2NP)	Type of second fixed surface (see Code table 4.5)
(34+2NP)	Scale factor of second fixed surface
(35+2NP)–(38+2NP)	Scaled value of second fixed surface
(39+2NP)	Type of ensemble forecast (see Code table 4.6)
(40+2NP)	Perturbation number
(41+2NP)	Number of forecasts in ensemble

Notes:

- (1) A single partition with code value PN from the partition set composed by the NP partitions is represented in the template. The code values of the NP partitions are expressed in octets 14 to 14+2NP–1. The NP partitions are linked by the normalization formula stating that the sum of all the NP partitions must be equal to a normalization term (N) on each point of the grid.
- (2) Only parameters expressing fractions or percentages can be used in this template. Code tables shall state clearly that they are meant to be used in partitioned parameters context.
- (3) The word "fraction" or the word "percentage" has to be explicitly used in the name of the parameter to refer to a normalization term $N = 1$ in the case of "fraction" and $N = 100$ in the case of percentage.

Product definition template 4.55 – spatio-temporal changing tiles at a horizontal level or horizontal layer at a point in time

Product definition template 4.55	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Tile classification (see Code table 4.242)
13	Total number (NT) of tile/attribute pairs (see Notes 1 and 2)
14	Number of used spatial tiles (NUT) (see Notes 1 and 2)
15	Tile index (ITN = {1,..., NUT}) (see Note 1)
16	Number of used tile attributes (NAT) for tile ITN (see Note 1)
17	Attribute of tile (see Code table 4.241)) ($A = \{A(1), \dots, A(NAT(ITN))\}$) (see Note 1)
18	Type of generating process (see Code table 4.3)
19	Background generating process identifier (defined by originating centre)
20	Analysis or forecast generating process identifier (defined by originating centre)
21–22	Hours of observational data cut-off after reference time (see Note 3)
23	Minutes of observational data cut-off after reference time
24	Indicator of unit of time range (see Code table 4.4)
25–28	Forecast time in units defined by octet 24
29	Type of first fixed surface (see Code table 4.5)
30	Scale factor of first fixed surface
31–34	Scaled value of first fixed surface
35	Type of second fixed surface (see Code table 4.5)
36	Scale factor of second fixed surface
37–40	Scaled value of second fixed surface

Notes:

- (1) NUT is the number of used different spatial tiles, defining the cover structure of a point. As each of these tiles has one or more different tile attributes $A(NAT(ITN))$, ($ITN=1, \dots, NUT$), for example, (unmodified, snow-covered,...), there are $NT = \sum_{ITN=1}^{NUT} NAT(ITN)$ fields (that is, the total number of tile/attribute pairs, defined in octet 13) with indices (ITN, IAN) with the following meaning ($IAN = \{1, \dots, NAT(ITN)\}$):

1,1	First tile – first attribute (e.g. unmodified)
....
1,NAT(1)	First tile – NAT of first tile (last, e.g. snow-covered) attribute
2,1	Second tile – first attribute (e.g. unmodified)
....
2,NAT(2)	Second tile – NAT of second tile (last, e.g. snow-covered) attribute
.	.
.	.
NUT,1	NUT tile – first attribute (e.g. unmodified)
....
NUT,NAT(NUT)	NUT tile – NAT of last tile (last) attribute

A single tile/attribute index (ITN, IAN) with spatial tile index ITN (1,...,NUT) and attribute A(IAN) with IAN = (1,...,NAT(ITN)) is represented in the template. All NT partitions are linked by the normalization formula, which states that the sum of all partitions must be equal to a normalization term ($N = 1$ for fractions and $N = 100$ for percentage) on each point of the grid.

The fields "tile class" and "tile fraction" must be provided in order to obtain the tile structure of each grid point. Note that the field "tile fraction" is time-dependent in the case of defined attributes, whereas the field "tile class" is not affected by attributes ($NT = NUT$).

- (2) For more information, see Part B, GRIB Attachment IV.
- (3) Hours greater than 65534 will be coded as 65534.

Product definition template 4.56 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for spatio-temporal changing tile parameters

Product definition template 4.56	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Tile classification (see Code table 4.242)
13	Total number (NT) of tile/attribute pairs (see Notes 1 and 2)
14	Number of used spatial tiles (NUT) (see Notes 1 and 2)
15	Tile index (ITN = {1,..., NUT}) (see Note 1)
16	Number of used tile attributes (NAT) for tile ITN (see Note 1)
17	Attribute of tile (see Code table 4.241)) ($A = \{A(1),..., A(NAT(ITN))\}$) (see Note 1)
18	Type of generating process (see Code table 4.3)
19	Background generating process identifier (defined by originating centre)
20	Analysis or forecast generating process identifier (defined by originating centre)
21–22	Hours of observational data cut-off after reference time (see Note 3)
23	Minutes of observational data cut-off after reference time
24	Indicator of unit of time range (see Code table 4.4)
25–28	Forecast time in units defined by octet 24
29	Type of first fixed surface (see Code table 4.5)
30	Scale factor of first fixed surface
31–34	Scaled value of first fixed surface
35	Type of second fixed surface (see Code table 4.5)
36	Scale factor of second fixed surface
37–40	Scaled value of second fixed surface
41	Perturbation number
42	Number of forecasts in ensemble

Notes:

- (1) NUT is the number of used different spatial tiles, defining the cover structure of a point. As each of these tiles has one or more different tile attributes $A(NAT(ITN))$, ($ITN=1,...,NUT$), for example, (unmodified, snow-covered,...), there are $NT = \sum_{ITN=1}^{NUT} NAT(ITN)$ fields (that is, the total number of tile/attribute pairs, defined in octet 13) with indices (ITN, IAN) with the following meaning ($IAN = \{1,..., NAT(ITN)\}$):

1,1	First tile – first attribute (e.g. unmodified)
....
1,NAT(1)	First tile – NAT of first tile (last, e.g. snow-covered) attribute
2,1	Second tile – first attribute (e.g. unmodified)
....
2,NAT(2)	Second tile – NAT of second tile (last, e.g. snow-covered) attribute
.	.
.	.
NUT,1	NUT tile – first attribute (e.g. unmodified)
....
NUT,NAT(NUT)	NUT tile – NAT of last tile (last) attribute

A single tile/attribute index (ITN, IAN) with spatial tile index ITN (1,...,NUT) and attribute A(IAN) with IAN = (1,...,NAT(ITN)) is represented in the template. All NT partitions are linked by the normalization formula, which states that the sum of all partitions must be equal to a normalization term ($N = 1$ for fractions and $N = 100$ for percentage) on each point of the grid.

The fields "tile class" and "tile fraction" must be provided in order to obtain the tile structure of each grid point. Note that the field "tile fraction" is time-dependent in the case of defined attributes, whereas the field "tile class" is not affected by attributes ($NT = NUT$).

- (2) For more information, see Part B, GRIB Attachment IV.
- (3) Hours greater than 65534 will be coded as 65534.

Product definition template 4.57 – analysis or forecast at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents based on a distribution function

Product definition template 4.57	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14–15	Number of modes (N) of distribution (see Note 1)
16–17	Mode number (I)
18–19	Type of distribution function (see Code table 4.240)
20	Number of following function parameters (N_p), defined by type given in octets 18–19 (Type of distribution function)
<i>Repeat the following 5 octets for the number of function parameters ($n = 1, N_p$), if $N_p > 0$</i>	
21+5($n-1$)	List of scale factor of fixed distribution function parameter ($p_1-p_{N_p}$), defined by type of distribution in octets 18–19
(22+5($n-1$))–(25+5($n-1$))	List of scaled value of fixed distribution function parameter ($p_1-p_{N_p}$), defined by type of distribution in octets 18–19
21+5 N_p	Type of generating process (see Code table 4.3)
22+5 N_p	Background generating process identifier (defined by originating centre)
23+5 N_p	Analysis or forecast generating process identifier (defined by originating centre)
(24+5 N_p)–(25+5 N_p)	Hours of observational data cut-off after reference time (see Note 2)
26+5 N_p	Minutes of observational data cut-off after reference time
27+5 N_p	Indicator of unit of time range (see Code table 4.4)
(28+5 N_p)–(31+5 N_p)	Forecast time in units defined by the previous octet

Product definition template 4.57

Octet No.	Contents
32+5Np	Type of first fixed surface (see Code table 4.5)
33+5Np	Scale factor of first fixed surface
(34+5Np)–(37+5Np)	Scaled value of first fixed surface
38+5Np	Type of second fixed surface (see Code table 4.5)
39+5Np	Scale factor of second fixed surface
(40+5Np)–(43+5Np)	Scaled value of second fixed surface

Notes:

- (1) If Number of modes (N) > 1, then between x N fields with mode number l = 1, ..., N define the distribution function. x is the number of variable parameters in the distribution function.
- (2) Hours greater than 65534 will be coded as 65534.
- (3) For more information, see Part B, GRIB Attachment III.

Product definition template 4.58 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents based on a distribution function

Product definition template 4.58

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14–15	Number of modes (N) of distribution (see Note 1)
16–17	Mode number (l)
18–19	Type of distribution function (see Code table 4.240)
20	Number of following function parameters (Np), defined by type given in octets 18–19 (Type of distribution function)
<i>Repeat the following 5 octets for the number of function parameters (n = 1, Np), if Np > 0</i>	
21+5(n–1)	List of scale factor of fixed distribution function parameter (p1–pNp), defined by type of distribution in octets 18–19
(22+5(n–1))–(25+5(n–1))	List of scaled value of fixed distribution function parameter (p1–pNp), defined by type of distribution in octets 18–19
21+5Np	Type of generating process (see Code table 4.3)
22+5Np	Background generating process identifier (defined by originating centre)
23+5Np	Analysis or forecast generating process identifier (defined by originating centre)
(24+5Np)–(25+5Np)	Hours of observational data cut-off after reference time (see Note 2)
26+5Np	Minutes of observational data cut-off after reference time
27+5Np	Indicator of unit of time range (see Code table 4.4)
(28+5Np)–(31+5Np)	Forecast time in units defined by the previous octet
32+5Np	Type of first fixed surface (see Code table 4.5)
33+5Np	Scale factor of first fixed surface
(34+5Np)–(37+5Np)	Scaled value of first fixed surface
38+5Np	Type of second fixed surface (see Code table 4.5)
39+5Np	Scale factor of second fixed surface
(40+5Np)–(43+5Np)	Scaled value of second fixed surface

Product definition template 4.58

Octet No.	Contents
44+5Np	Type of ensemble forecast (see Code table 4.6)
45+5Np	Perturbation number
46+5Np	Number of forecasts in ensemble

Notes:

- (1) If Number of modes (N) > 1, then between x N fields with mode number l = 1, ..., N define the distribution function. x is the number of variable parameters in the distribution function.
- (2) Hours greater than 65534 will be coded as 65534.
- (3) For more information, see Part B, GRIB Attachment III.

Product definition template 4.59 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for spatio-temporal changing tile parameters

Product definition template 4.59

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Tile classification (see Code table 4.242)
13	Total number (NT) of tile/attribute pairs (see Notes 1 and 2)
14	Number of used spatial tiles (NUT) (see Notes 1 and 2)
15	Tile index (ITN = {1,..., NUT}) (see Note 1)
16	Number of used tile attributes (NAT) for tile ITN (see Note 1)
17	Attribute of tile (see Code table 4.241) (A = {A(1),..., A(NAT(ITN))}) (see Note 1)
18	Type of generating process (see Code table 4.3)
19	Background generating process identifier (defined by originating centre)
20	Analysis or forecast generating process identifier (defined by originating centre)
21–22	Hours of observational data cut-off after reference time (see Note 3)
23	Minutes of observational data cut-off after reference time
24	Indicator of unit of time range (see Code table 4.4)
25–28	Forecast time in units defined by octet 24
29	Type of first fixed surface (see Code table 4.5)
30	Scale factor of first fixed surface
31–34	Scaled value of first fixed surface
35	Type of second fixed surface (see Code table 4.5)
36	Scale factor of second fixed surface
37–40	Scaled value of second fixed surface
41	Type of ensemble forecast (see Code table 4.6)
42	Perturbation number
43	Number of forecasts in ensemble

Notes:

- (1) See Note 1 under product definition template 4.55.
- (2) For more information, see Part B, GRIB Attachment IV.
- (3) Hours greater than 65534 will be coded as 65534.

Product definition template 4.60 – individual ensemble reforecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time

Product definition template 4.60	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours of observational data cut-off after reference time (see Note 1)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Type of ensemble forecast (see Code table 4.6)
36	Perturbation number
37	Number of forecasts in ensemble
38–39	Year of model version date (see Note 2)
40	Month of model version date
41	Day of model version date
42	Hour of model version date
43	Minute of model version date
44	Second of model version date

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) This is the date when the reforecast is produced with a particular version of the model.

Product definition template 4.61 – individual ensemble reforecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous time interval

Product definition template 4.61	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface

Product definition template 4.61

Octet No.	Contents
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	Type of ensemble forecast (see Code table 4.6)
36	Perturbation number
37	Number of forecasts in ensemble
38–39	Year of model version date (see Note 3)
40	Month of model version date
41	Day of model version date
42	Hour of model version date
43	Minute of model version date
44	Second of model version date
45–46	Year of end of overall time interval
47	Month of end of overall time interval
48	Day of end of overall time interval
49	Hour of end of overall time interval
50	Minute of end of overall time interval
51	Second of end of overall time interval
52	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
53–56	Total number of data values missing in statistical process <i>57–68 Specification of the outermost (or only) time range over which statistical processing is done</i>
57	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
58	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
59	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
60–63	Length of the time range over which statistical processing is done, in units defined by the previous octet
64	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
65–68	Time increment between successive fields, in units defined by the previous octet (see Notes 4 and 5) <i>69–nn These octets are included only if $n > 1$, where $nn = 56 + 12 \times n$</i>
69–80	As octets 57 to 68, next innermost step of processing
81–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 57 to 68, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) This is the date when the reforecast is produced with a particular version of the model.

- (4) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (5) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 51, 63, 75 ...). For all but the innermost (last) time range, the next inner range is then processed using these references and forecast times as the initial reference and forecast times.

Product definition template 4.62 – average, accumulation and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for spatio-temporal changing tiles at a horizontal level or horizontal layer at a point in time

Product definition template 4.62	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Tile classification (see Code table 4.242)
13	Total number (NT) of tile/attribute pairs (see Notes 1 and 2)
14	Number of used spatial tiles (NUT) (see Notes 1 and 2)
15	Tile index (ITN = {1,..., NUT}) (see Note 1)
16	Number of used tile attributes (NAT) for tile ITN (see Note 1)
17	Attribute of tile (see Code table 4.241) ($A = \{A(1), \dots, A(NAT(ITN))\}$) (see Note 1)
18	Type of generating process (see Code table 4.3)
19	Background generating process identifier (defined by originating centre)
20	Analysis or forecast generating process identifier (defined by originating centre)
21–22	Hours of observational data cut-off after reference time (see Note 3)
23	Minutes of observational data cut-off after reference time
24	Indicator of unit of time range (see Code table 4.4)
25–28	Forecast time in units defined by octet 24 (see Note 4)
29	Type of first fixed surface (see Code table 4.5)
30	Scale factor of first fixed surface
31–34	Scaled value of first fixed surface
35	Type of second fixed surface (see Code table 4.5)
36	Scale factor of second fixed surface
37–40	Scaled value of second fixed surface
41–42	Year
43	Month
44	Day
45	Hour
46	Minute
47	Second
48	n – number of time range specifications describing the time intervals used to calculate the statistically
49–52	Total number of data values missing in statistical process
53–64	Specification of the outermost (or only) time range over which statistical processing is done
53	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
54	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)

Product definition template 4.62	
Octet No.	Contents
55	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
56–59	Length of the time range over which statistical processing is done, in units defined by the previous octet
60	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
61–64	Time increment between successive fields, in units defined by the previous octet (see Notes 5 and 6)
65–nn	<i>These octets are included only if $n > 1$, where $nn = 52 + 12 \times n$</i>
65–76	As octets 53 to 64, next innermost step of processing
77–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 53 to 64, repeated as necessary

Notes:

- (1) See Note 1 under product definition template 4.55.
- (2) For more information, see Part B, GRIB Attachment IV.
- (3) Hours greater than 65534 will be coded as 65534.
- (4) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (5) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (6) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 54, 66, 78, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.63 – Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for spatio-temporal changing tiles

Product definition template 4.63	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Tile classification (see Code table 4.242)
13	Total number (NT) of tile/attribute pairs (see Notes 1 and 2)
14	Number of used spatial tiles (NUT) (see Notes 1 and 2)
15	Tile index (ITN = {1,..., NUT}) (see Note 1)
16	Number of used tile attributes (NAT) for tile ITN (see Note 1)
17	Attribute of tile (see Code table 4.241) ($A = \{A(1), \dots, A(NAT(ITN))\}$) (see Note 1)
18	Type of generating process (see Code table 4.3)
19	Background generating process identifier (defined by originating centre)
20	Analysis or forecast generating process identifier (defined by originating centre)
21–22	Hours of observational data cut-off after reference time (see Note 3)
23	Minutes of observational data cut-off after reference time
24	Indicator of unit of time range (see Code table 4.4)
25–28	Forecast time in units defined by octet 24 (see Note 4)
29	Type of first fixed surface (see Code table 4.5)
30	Scale factor of first fixed surface

Product definition template 4.63

Octet No.	Contents
31–34	Scaled value of first fixed surface
35	Type of second fixed surface (see Code table 4.5)
36	Scale factor of second fixed surface
37–40	Scaled value of second fixed surface
41	Type of ensemble forecast (see Code table 4.6)
42	Perturbation number
43	Number of forecasts in ensemble
44–45	Year
46	Month
47	Day
48	Hour
49	Minute
50	Second
51	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
52–55	Total number of data values missing in statistical process
56–67	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
56	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
57	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
58	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
59–62	Length of the time range over which statistical processing is done, in units defined by the previous octet
63	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
64–67	Time increment between successive fields, in units defined by the previous octet (see Notes 5 and 6)
68–nn	<i>These octets are included only if $n > 1$, where $nn = 55 + 12 \times n$</i>
68–79	As octets 56 to 67, next innermost step of processing
80–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 56 to 67, repeated as necessary

Notes:

- (1) See Note 1 under product definition template 4.55.
- (2) For more information, see Part B, GRIB Attachment IV.
- (3) Hours greater than 65534 will be coded as 65534
- (4) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (5) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (6) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 57, 69, 81, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.67 – average, accumulation and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents based on a distribution function

Product definition template 4.67	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14–15	Number of modes (N) of distribution (see Note 1)
16–17	Mode number (I)
18–19	Type of distribution function (see Code table 4.240 and Note 2)
20	Number of following function parameters (Np), defined by type given in octets 18–19 (Type of distribution function)
	<i>Repeat the following 5 octets for the number of function parameters (n = 1, Np), if Np > 0</i>
21+5(n–1)	List of scale factor of fixed distribution function parameter (p1–pNp), defined by type of distribution in octets 18–19
(22+5(n–1))–(25+5(n–1))	List of scaled value of fixed distribution function parameter (p1–pNp), defined by type of distribution in octets 18–19
21+5Np	Type of generating process (see Code table 4.3)
22+5Np	Background generating process identifier (defined by originating centre)
23+5Np	Analysis or forecast generating process identifier (defined by originating centre)
(24+5Np)–(25+5Np)	Hours of observational data cut-off after reference time (see Note 3)
26+5Np	Minutes of observational data cut-off after reference time
27+5Np	Indicator of unit of time range (see Code table 4.4)
(28+5Np)–(31+5Np)	Forecast time in units defined by the previous octet (see Note 4)
32+5Np	Type of first fixed surface (see Code table 4.5)
33+5Np	Scale factor of first fixed surface
(34+5Np)–(37+5Np)	Scaled value of first fixed surface
38+5Np	Type of second fixed surface (see Code table 4.5)
39+5Np	Scale factor of second fixed surface
(40+5Np)–(43+5Np)	Scaled value of second fixed surface
(44+5Np)–(45+5Np)	Year
(46+5Np)	Month
(47+5Np)	Day
(48+5Np)	Hour
(49+5Np)	Minute
(50+5Np)	Second
(51+5Np)	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
(52+5Np)–(55+5Np)	Total number of data values missing in statistical process
(56+5Np)–(67+5Np)	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
(56+5Np)	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
(57+5Np)	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)

Product definition template 4.67		
Octet No.	Contents	
(58+5Np)	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)	
(59+5Np)–(62+5Np)	Length of the time range over which statistical processing is done, in units defined by the previous octet	
(63+5Np)	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)	
(64+5Np)–(67+5Np)	Time increment between successive fields, in units defined by the previous octet (see Notes 5 and 6)	
(68+5Np)–nn	<i>These octets are included only if $n > 1$, where $nn = (55+5Np) + 12 \times n$</i>	
(68+5Np)–(79+5Np)	As octets (56+5Np) to (67+5Np), next innermost step of processing	
(80+5Np)–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets (56+5Np) to (67+5Np), repeated as necessary	

Notes:

- (1) If Number of modes (N) > 1, then between x N fields with mode number I = 1, ..., N define the distribution function. x is the number of variable parameters in the distribution function.
- (2) For more information, see Part B, GRIB Attachment III.
- (3) Hours greater than 65534 will be coded as 65534.
- (4) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (5) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (6) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment. For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.68 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents based on a distribution function

Product definition template 4.68		
Octet No.	Contents	
10	Parameter category (see Code table 4.1)	
11	Parameter number (see Code table 4.2)	
12–13	Atmospheric chemical constituent type (see Code table 4.230)	
14–15	Number of modes (N) of distribution (see Note 1)	
16–17	Mode number (I)	
18–19	Type of distribution function (see Code table 4.240 and Note 2)	
20	Number of following function parameters (Np), defined by type given in octets 18–19 (Type of distribution function)	
	<i>Repeat the following 5 octets for the number of function parameters ($n = 1, Np$), if $Np > 0$</i>	
21+5(n–1)	List of scale factor of fixed distribution function parameter (p1–pNp), defined by type of distribution in octets 18–19	
(22+5(n–1))–(25+5(n–1))	List of scaled value of fixed distribution function parameter (p1–pNp), defined by type of distribution in octets 18–19	
21+5Np	Type of generating process (see Code table 4.3)	

Product definition template 4.68		
Octet No.	Contents	
22+5Np	Background generating process identifier (defined by originating centre)	
23+5Np	Analysis or forecast generating process identifier (defined by originating centre)	
(24+5Np)–(25+5Np)	Hours of observational data cut-off after reference time (see Note 3)	
26+5Np	Minutes of observational data cut-off after reference time	
27+5Np	Indicator of unit of time range (see Code table 4.4)	
(28+5Np)–(31+5Np)	Forecast time in units defined by the previous octet (see Note 4)	
32+5Np	Type of first fixed surface (see Code table 4.5)	
33+5Np	Scale factor of first fixed surface	
(34+5Np)–(37+5Np)	Scaled value of first fixed surface	
38+5Np	Type of second fixed surface (see Code table 4.5)	
39+5Np	Scale factor of second fixed surface	
(40+5Np)–(43+5Np)	Scaled value of second fixed surface	
44+5Np	Type of ensemble forecast (see Code table 4.6)	
45+5Np	Perturbation number	
46+5Np	Number of forecasts in ensemble	
(47+5Np)–(48+5Np)	<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> Year Month Day Hour Minute Second </div> <div style="font-size: 3em; line-height: 1;">}</div> <div>Time of end of overall time interval</div> </div>	
(49+5Np)		
(50+5Np)		
(51+5Np)		
(52+5Np)		
(53+5Np)		
(54+5Np)	n – number of time range specifications describing the time intervals used to calculate the statistically processed field	
(55+5Np)–(58+5Np)	Total number of data values missing in statistical process	
	<i>(59+5Np)–(70+5Np) Specification of the outermost (or only) time range over which statistical processing is done</i>	
(59+5Np)	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)	
(60+5Np)	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)	
(61+5Np)	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)	
(62+5Np)–(65+5Np)	Length of the time range over which statistical processing is done, in units defined by the previous octet	
(66+5Np)	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)	
(67+5Np)–(70+5Np)	Time increment between successive fields, in units defined by the previous octet (see Notes 5 and 6)	
	<i>(71+5Np)–nn These octets are included only if n > 1, where nn = (58+5Np) + 12 × n</i>	
(71+5Np)–(82+5Np)	As octets (59+5Np) to (70+5Np), next innermost step of processing	
(83+5Np)–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets (59+5Np) to (70+5Np), repeated as necessary	

Notes:

- (1) If Number of modes (N) > 1, then between x N fields with mode number I = 1, ..., N define the distribution function. x is the number of variable parameters in the distribution function.
- (2) For more information, see Part B, GRIB Attachment III.
- (3) Hours greater than 65534 will be coded as 65534.
- (4) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (5) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (6) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment. For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.70 – post-processing analysis or forecast at a horizontal level or in a horizontal layer at a point in time

Product definition template 4.70	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Input process identifier (see Note 1)
14–15	Input originating centre (see Common Code table C-11 and Note 2)
16	Type of post-processing (see Note 3)
17	Type of generating process (see Code table 4.3)
18	Background generating process identifier (defined by originating centre)
19	Analysis or forecast generating process identifier (defined by originating centre)
20–21	Hours of observational data cut-off after reference time (see Note 4)
22	Minutes of observational data cut-off after reference time
23	Indicator of unit of time range (see Code table 4.4)
24–27	Forecast time in units defined by octet 23
28	Type of first fixed surface (see Code table 4.5)
29	Scale factor of first fixed surface
30–33	Scaled value of first fixed surface
34	Type of second fixed surface (see Code table 4.5)
35	Scale factor of second fixed surface
36–39	Scaled value of second fixed surface

Notes:

- (1) The input process identifier shall have the value of the "analysis or forecast process identifier" of the original GRIB message used as input of the post-processing.
- (2) The input originating centre shall have the value of the "originating centre" of the original GRIB message used as input of the post-processing.
- (3) This identifies which post-processing technique was used. This is defined by the originating centre.
- (4) Hours greater than 65534 will be coded as 65534.

Product definition template 4.71 – post-processing individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time

Product definition template 4.71	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Input process identifier (see Note 1)
14–15	Input originating centre (see Common Code table C–11 and Note 2)
16	Type of post-processing (see Note 3)
17	Type of generating process (see Code table 4.3)
18	Background generating process identifier (defined by originating centre)
19	Forecast generating process identifier (defined by originating centre)
20–21	Hours after reference time of data cut-off (see Note 4)
22	Minutes after reference time of data cut-off
23	Indicator of unit of time range (see Code table 4.4)
24–27	Forecast time in units defined by octet 23
28	Type of first fixed surface (see Code table 4.5)
29	Scale factor of first fixed surface
30–33	Scaled value of first fixed surface
34	Type of second fixed surface (see Code table 4.5)
35	Scale factor of second fixed surface
36–39	Scaled value of second fixed surface
40	Type of ensemble forecast (see Code table 4.6)
41	Perturbation number
42	Number of forecasts in ensemble

Notes:

- (1) The input process identifier shall have the value of the “analysis or forecast process identifier” of the original GRIB message used as input of the post-processing.
- (2) The input originating centre shall have the value of the “originating centre” of the original GRIB message used as input of the post-processing.
- (3) This identifies which post-processing technique was used. This is defined by the originating centre.
- (4) Hours greater than 65534 will be coded as 65534.

Product definition template 4.72 – post-processing average, accumulation, extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.72	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Input process identifier (see Note 1)
14–15	Input originating centre (see Common Code table C–11 and Note 2)
16	Type of post-processing (see Note 3)
17	Type of generating process (see Code table 4.3)
18	Background generating process identifier (defined by originating centre)
19	Analysis or forecast generating process identifier (defined by originating centre)
20–21	Hours after reference time of data cut-off (see Note 4)

Product definition template 4.72	
Octet No.	Contents
22	Minutes after reference time of data cut-off
23	Indicator of unit of time range (see Code table 4.4)
24–27	Forecast time in units defined by octet 23 (see Note 5)
28	Type of first fixed surface (see Code table 4.5)
29	Scale factor of first fixed surface
30–33	Scaled value of first fixed surface
34	Type of second fixed surface (see Code table 4.5)
35	Scale factor of second fixed surface
36–39	Scaled value of second fixed surface
40–41	Year
42	Month
43	Day
44	Hour
45	Minute
46	Second
47	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
48–51	Total number of data values missing in statistical process
	<i>52–63 Specification of the outermost (or only) time range over which statistical processing is done</i>
52	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
53	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
54	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
55–58	Length of the time range over which statistical processing is done, in units defined by the previous octet
59	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
60–63	Time increment between successive fields, in units defined by the previous octet (see Notes 6 and 7)
	<i>64–nn These octets are included only if $n > 1$, where $nn = 51 + 12 \times n$</i>
64–75	As octets 52 to 63, next innermost step of processing
76–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 52 to 63, repeated as necessary

Notes:

- (1) The input process identifier shall have the value of the "analysis or forecast process identifier" of the original GRIB message used as input of the post-processing.
- (2) The input originating centre shall have the value of the "originating centre" of the original GRIB message used as input of the post-processing.
- (3) This identifies which post-processing technique was used. This is defined by the originating centre.
- (4) Hours greater than 65534 will be coded as 65534.
- (5) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.

- (6) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (7) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 63, 65, 77, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.73 – post-processing individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous time interval

<i>Product definition template 4.73</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Input process identifier (see Note 1)
14–15	Input originating centre (see Common Code table C-11 and Note 2)
16	Type of post-processing (see Note 3)
17	Type of generating process (see Code table 4.3)
18	Background generating process identifier (defined by originating centre)
19	Forecast generating process identifier (defined by originating centre)
20–21	Hours after reference time of data cut-off (see Note 4)
22	Minutes after reference time of data cut-off
23	Indicator of unit of time range (see Code table 4.4)
24–27	Forecast time in units defined by octet 23 (see Note 5)
28	Type of first fixed surface (see Code table 4.5)
29	Scale factor of first fixed surface
30–33	Scaled value of first fixed surface
34	Type of second fixed surface (see Code table 4.5)
35	Scale factor of second fixed surface
36–39	Scaled value of second fixed surface
40	Type of ensemble forecast (see Code table 4.6)
41	Perturbation number
42	Number of forecasts in ensemble
43–44	Year of end of overall time interval
45	Month of end of overall time interval
46	Day of end of overall time interval
47	Hour of end of overall time interval
48	Minute of end of overall time interval
49	Second of end of overall time interval
50	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
51–54	Total number of data values missing in statistical process <i>55–66 Specification of the outermost (or only) time range over which statistical processing is done</i>
55	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
56	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
57	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)

<i>Product definition template 4.73</i>	
Octet No.	Contents
58–61	Length of the time range over which statistical processing is done, in units defined by the previous octet
62	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
63–66	Time increment between successive fields, in units defined by the previous octet (see Notes 6 and 7)
67–nn	<i>These octets are included only if $n > 1$, where $nn = 54 + 12 \times n$</i>
67–78	As octets 55 to 66, next innermost step of processing
79–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 55 to 66, repeated as necessary

Notes:

- (1) The input process identifier shall have the value of the "analysis or forecast process identifier" of the original GRIB message used as input of the post-processing.
- (2) The input originating centre shall have the value of the "originating centre" of the original GRIB message used as input of the post-processing.
- (3) This identifies which post-processing technique was used. This is defined by the originating centre.
- (4) Hours greater than 65534 will be coded as 65534.
- (5) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (6) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (7) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 56, 68, 80, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.76 – analysis or forecast at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents with source or sink

<i>Product definition template 4.76</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14	Source or sink (see Code table 4.238)
15	Type of generating process (see Code table 4.3)
16	Background generating process identifier (defined by originating centre)
17	Analysis or forecast generating process identifier (defined by originating centre)
18–19	Hours of observational data cut-off after reference time (see Note)
20	Minutes of observational data cut-off after reference time
21	Indicator of unit of time range (see Code table 4.4)
22–25	Forecast time in units defined by octet 20
26	Type of first fixed surface (see Code table 4.5)
27	Scale factor of first fixed surface

<i>Product definition template 4.76</i>	
Octet No.	Contents
28–31	Scaled value of first fixed surface
32	Type of second fixed surface (see Code table 4.5)
33	Scale factor of second fixed surface
34–37	Scaled value of second fixed surface

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.77 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents with source or sink

<i>Product definition template 4.77</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14	Source or sink (see Code table 4.238)
15	Type of generating process (see Code table 4.3)
16	Background generating process identifier (defined by originating centre)
17	Forecast generating process identifier (defined by originating centre)
18–19	Hours after reference time of data cut-off (see Note)
20	Minutes after reference time of data cut-off
21	Indicator of unit of time range (see Code table 4.4)
22–25	Forecast time in units defined by octet 20
26	Type of first fixed surface (see Code table 4.5)
27	Scale factor of first fixed surface
28–31	Scaled value of first fixed surface
32	Type of second fixed surface (see Code table 4.5)
33	Scale factor of second fixed surface
34–37	Scaled value of second fixed surface
38	Type of ensemble forecast (see Code table 4.6)
39	Perturbation number
40	Number of forecasts in ensemble

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.78 – average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents with source or sink

<i>Product definition template 4.78</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14	Source or sink (see Code table 4.238)
15	Type of generating process (see Code table 4.3)
16	Background generating process identifier (defined by originating centre)

Product definition template 4.78

Octet No.	Contents
17	Analysis or forecast generating process identifier (defined by originating centre)
18–19	Hours after reference time of data cut-off (see Note 1)
20	Minutes after reference time of data cut-off
21	Indicator of unit of time range (see Code table 4.4)
22–25	Forecast time in units defined by octet 20 (see Note 2)
26	Type of first fixed surface (see Code table 4.5)
27	Scale factor of first fixed surface
28–31	Scaled value of first fixed surface
32	Type of second fixed surface (see Code table 4.5)
33	Scale factor of second fixed surface
34–37	Scaled value of second fixed surface
38–39	Year
40	Month
41	Day
42	Hour
43	Minute
44	Second
45	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
46–49	Total number of data values missing in statistical process
50–61	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
50	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
51	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
52	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
53–56	Length of the time range over which statistical processing is done, in units defined by the previous octet
57	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
58–61	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
62–nn	<i>These octets are included only if $n > 1$, where $nn = 49 + 12 \times n$</i>
62–73	As octets 50 to 61, next innermost step of processing
74–nn	Additional time range specifications, included in accordance with the value of n . Contents as octets 50 to 61, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 51, 63, 75, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.79 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents with source or sink

Product definition template 4.79	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Atmospheric chemical constituent type (see Code table 4.230)
14	Source or sink (see Code table 4.238)
15	Type of generating process (see Code table 4.3)
16	Background generating process identifier (defined by originating centre)
17	Forecast generating process identifier (defined by originating centre)
18–19	Hours after reference time of data cut-off (see Note 1)
20	Minutes after reference time of data cut-off
21	Indicator of unit of time range (see Code table 4.4)
22–25	Forecast time in units defined by octet 20 (see Note 2)
26	Type of first fixed surface (see Code table 4.5)
27	Scale factor of first fixed surface
28–31	Scaled value of first fixed surface
32	Type of second fixed surface (see Code table 4.5)
33	Scale factor of second fixed surface
34–37	Scaled value of second fixed surface
38	Type of ensemble forecast (see Code table 4.6)
39	Perturbation number
40	Number of forecasts in ensemble
41–42	Year of end of overall time interval
43	Month of end of overall time interval
44	Day of end of overall time interval
45	Hour of end of overall time interval
46	Minute of end of overall time interval
47	Second of end of overall time interval
48	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
49–52	Total number of data values missing in statistical process
53–64	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
53	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
54	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
55	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
56–59	Length of the time range over which statistical processing is done, in units defined by the previous octet
60	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
61–64	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
65–nn	<i>These octets are included only if $n > 1$, where $nn = 52 + 12 \times n$</i>
65–76	As octets 53 to 64, next innermost step of processing
77–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 53 to 64, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 54, 66, 78, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.80 – analysis or forecast at a horizontal level or in a horizontal layer at a point in time for optical properties of aerosol with source or sink

Product definition template 4.80	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Common Code table C-14)
14	Source or sink (see Code table 4.238)
15	Type of interval for first and second size (see Code table 4.91)
16	Scale factor of first size
17–20	Scaled value of first size in metres
21	Scale factor of second size
22–25	Scaled value of second size in metres
26	Type of interval for first and second wavelength (see Code table 4.91)
27	Scale factor of first wavelength
28–31	Scaled value of first wavelength in metres
32	Scale factor of second wavelength
33–36	Scaled value of second wavelength in metres
37	Type of generating process (see Code table 4.3)
38	Background generating process identifier (defined by originating centre)
39	Analysis or forecast generating process identifier (defined by originating centre)
40–41	Hours of observational data cut-off after reference time (see Note)
42	Minutes of observational data cut-off after reference time
43	Indicator of unit of time range (see Code table 4.4)
44–47	Forecast time in units defined by octet 42
48	Type of first fixed surface (see Code table 4.5)
49	Scale factor of first fixed surface
50–53	Scaled value of first fixed surface
54	Type of second fixed surface (see Code table 4.5)
55	Scale factor of second fixed surface
56–59	Scaled value of second fixed surface

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.81 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for optical properties of aerosol with source or sink

Product definition template 4.81	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Common Code table C–14)
14	Source or sink (see Code table 4.238)
15	Type of interval for first and second size (see Code table 4.91)
16	Scale factor of first size
17–20	Scaled value of first size in metres
21	Scale factor of second size
22–25	Scaled value of second size in metres
26	Type of interval for first and second wavelength (see Code table 4.91)
27	Scale factor of first wavelength
28–31	Scaled value of first wavelength in metres
32	Scale factor of second wavelength
33–36	Scaled value of second wavelength in metres
37	Type of generating process (see Code table 4.3)
38	Background generating process identifier (defined by originating centre)
39	Analysis or forecast generating process identifier (defined by originating centre)
40–41	Hours of observational data cut-off after reference time (see Note)
42	Minutes of observational data cut-off after reference time
43	Indicator of unit of time range (see Code table 4.4)
44–47	Forecast time in units defined by octet 42
48	Type of first fixed surface (see Code table 4.5)
49	Scale factor of first fixed surface
50–53	Scaled value of first fixed surface
54	Type of second fixed surface (see Code table 4.5)
55	Scale factor of second fixed surface
56–59	Scaled value of second fixed surface
60	Type of ensemble forecast (see Code table 4.6)
61	Perturbation number
62	Number of forecasts in ensemble

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.82 – average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol with source or sink

Product definition template 4.82	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Code table 4.233)
14	Source or sink (see Code table 4.238)
15	Type of interval for first and second sizes (see Code table 4.91)
16	Scale factor of first size

Product definition template 4.82	
Octet No.	Contents
17–20	Scaled value of first size in metres
21	Scale factor of second size
22–25	Scaled value of second size in metres
26	Type of generating process (see Code table 4.3)
27	Background generating process identifier (defined by originating centre)
28	Analysis or forecast generating process identifier (defined by originating centre)
29–30	Hours after reference time of data cut-off (see Note 1)
31	Minutes after reference time of data cut-off
32	Indicator of unit of time range (see Code table 4.4)
33–36	Forecast time in units defined by octet 31 (see Note 2)
37	Type of first fixed surface (see Code table 4.5)
38	Scale factor of first fixed surface
39–42	Scaled value of first fixed surface
43	Type of second fixed surface (see Code table 4.5)
44	Scale factor of second fixed surface
45–48	Scaled value of second fixed surface
49–50	Year
51	Month
52	Day
53	Hour
54	Minute
55	Second
56	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
57–60	Total number of data values missing in statistical process
61–72	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
61	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
62	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
63	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
64–67	Length of the time range over which statistical processing is done, in units defined by the previous octet
68	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
69–72	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
73–nn	<i>These octets are included only if $n > 1$, where $nn = 60 + 12 \times n$</i>
73–84	As octets 61 to 72, next innermost step of processing
85–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 61 to 72, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.

- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 62, 74, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.83 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol with source or sink

<i>Product definition template 4.83</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Code table 4.233)
14	Source or sink (see Code table 4.238)
15	Type of interval for first and second sizes (see Code table 4.91)
16	Scale factor of first size
17–20	Scaled value of first size in metres
21	Scale factor of second size
22–25	Scaled value of second size in metres
26	Background generating process identifier (defined by originating centre)
27	Forecast generating process identifier (defined by originating centre)
28–29	Hours after reference time of data cut-off (see Note 1)
30	Minutes after reference time of data cut-off
31	Indicator of unit of time range (see Code table 4.4)
32–35	Forecast time in units defined by octet 31 (see Note 2)
36	Type of first fixed surface (see Code table 4.5)
37	Scale factor of first fixed surface
38–41	Scaled value of first fixed surface
42	Type of second fixed surface (see Code table 4.5)
43	Scale factor of second fixed surface
44–47	Scaled value of second fixed surface
48	Type of ensemble forecast (see Code table 4.6)
49	Perturbation number
50	Number of forecasts in ensemble
51–52	Year of end of overall time interval
53	Month of end of overall time interval
54	Day of end of overall time interval
55	Hour of end of overall time interval
56	Minute of end of overall time interval
57	Second of end of overall time interval
58	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
59–62	Total number of data values missing in statistical process <i>63–74 Specification of the outermost (or only) time range over which statistical processing is done</i>
63	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)

Product definition template 4.83	
Octet No.	Contents
64	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
65	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
66–69	Length of the time range over which statistical processing is done, in units defined by the previous octet
70	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
71–74	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)
75–nn	<i>These octets are included only if $n > 1$, where $nn = 62 + 12 \times n$</i>
75–86	As octets 63 to 74, next innermost step of processing
87–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 63 to 74, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 63, 75, ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.
- (5) It is recommended not to use this template. Product definition template 4.84 should be used instead because it contains an additional octet to specify the type of generating process.

Product definition template 4.84 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol with source or sink

Product definition template 4.84	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Code table 4.2)
14	Source or sink (see Code table 4.238)
15	Type of interval for first and second sizes (see Code table 4.91)
16	Scale factor of first size
17–20	Scaled value of first size in metres
21	Scale factor of second size
22–25	Scaled value of second size in metres
26	Type of generating process (see Code table 4.3)
27	Background generating process identifier (defined by originating centre)
28	Forecast generating process identifier (defined by originating centre)
29–30	Hours after reference time of data cut-off (see Note 1)
31	Minutes after reference time of data cut-off
32	Indicator of unit of time range (see Code table 4.4)
33–36	Forecast time in units defined by octet 32 (see Note 2)

Product definition template 4.84	
Octet No.	Contents
37	Type of first fixed surface (see Code table 4.5)
38	Scale factor of first fixed surface
39–42	Scaled value of first fixed surface
43	Type of second fixed surface (see Code table 4.5)
44	Scale factor of second fixed surface
45–48	Scaled value of second fixed surface
49	Type of ensemble forecast (see Code table 4.6)
50	Perturbation number
51	Number of forecasts in ensemble
52–53	Year of end of overall time interval
54	Month of end of overall time interval
55	Day of end of overall time interval
56	Hour of end of overall time interval
57	Minute of end of overall time interval
58	Second of end of overall time interval
59	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
60–63	Total number of data values missing in statistical process
	<i>64–75 Specification of the outermost (or only) time range over which statistical processing is done</i>
64	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
65	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
66	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
67–70	Length of the time range over which statistical processing is done in units defined by the previous octet
71	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
72–75	Time increment between successive fields in units defined by the previous octet (see Notes 3 and 4)
	<i>76–nn These octets are included only if $n > 1$, where $nn = 63 + 12 \times n$</i>
76–87	As octets 64 to 75, next innermost step of processing
88–nn	Additional time range specifications included in accordance with the value of n. Contents as octets 64 to 75, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment. For all but the innermost (last) time range, the next inner range is then processed using these references and forecast times as the initial reference and forecast times.

Product definition template 4.85 – individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol

Product definition template 4.85	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–13	Aerosol type (see Code table 4.233)
14	Type of interval for first and second sizes (see Code table 4.91)
15	Scale factor of first size
16–19	Scaled value of first size in metres
20	Scale factor of second size
21–24	Scaled value of second size in metres
25	Type of generating process (see Code table 4.3)
26	Background generating process identifier (defined by originating centre)
27	Forecast generating process identifier (defined by originating centre)
28–29	Hours after reference time of data cut-off (see Note 1)
30	Minutes after reference time of data cut-off
31	Indicator of unit of time range (see Code table 4.4)
32–35	Forecast time in units defined by octet 31 (see Note 2)
36	Type of first fixed surface (see Code table 4.5)
37	Scale factor of first fixed surface
38–41	Scaled value of first fixed surface
42	Type of second fixed surface (see Code table 4.5)
43	Scale factor of second fixed surface
44–47	Scaled value of second fixed surface
48	Type of ensemble forecast (see Code table 4.6)
49	Perturbation number
50	Number of forecasts in ensemble
51–52	Year of end of overall time interval
53	Month of end of overall time interval
54	Day of end of overall time interval
55	Hour of end of overall time interval
56	Minute of end of overall time interval
57	Second of end of overall time interval
58	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
59–62	Total number of data values missing in statistical process
63–74	<i>Specification of the outermost (or only) time range over which statistical processing is done</i>
63	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
64	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
65	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
66–69	Length of the time range over which statistical processing is done, in units defined by the previous octet
70	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
71–74	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)

<i>Product definition template 4.85</i>	
Octet No.	Contents
	<i>75–nn These octets are included only if $n > 1$, where $nn = 62 + 12 \times n$</i>
75–86	As octets 63 to 74, next innermost step of processing
87–nn	Additional time range specifications, included in accordance with the value of n. Contents as octets 63 to 74, repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets 63, 75, ...). For all but the innermost (last) time range, the next inner range is then processed using these references and forecast times as the initial reference and forecast times.

Product definition template 4.86 – quantile forecasts at a horizontal level or in a horizontal layer at a point in time

<i>Product definition template 4.86</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35–36	Total number of quantile q
37–38	Quantile value (between 0 and q)

Note: Hours greater than 65534 will be coded as 65534.

Product definition template 4.87 – quantile forecasts at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.87	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time for data cut-off
18	Indicator of unit of time range (Code table 4.4)
19–22	Forecast time in units defined by previous octet (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35–36	Total number of quantiles q
37–38	Quantile value (between 0 and q)
39–40	Year of end of overall time interval
41	Month of end of overall time interval
42	Day of end of overall time interval
43	Hour of end of overall time interval
44	Minute of end of overall time interval
45	Second of end of overall time interval
46	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
47–50	Total number of data values missing in the statistical process
51–62	Specification of the outermost (or only) time range over which statistical processing is done
51	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
52	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
53	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
54–57	Length of the time range over which statistical processing is done in units defined by the previous octet
58	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
59–62	Time increment between successive fields in units defined by the previous octet (see Note 3)
63– nn	<i>These octets are included only if $n > 1$, where $nn = 50 + 12 \times n$</i>
63–74	As octets 51–62, next innermost step of processing
75– nn	Additional time range specifications, included in accordance with the value of n . Contents as octets 51 to 62, repeated as necessary.

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs and the rainfall measured by a rain gauge.

Product definition template 4.88 – analysis or forecast at a horizontal level or in a horizontal layer at a local time

Product definition template 4.88	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15	Type of first fixed surface (see Code table 4.5)
16	Scale factor of first fixed surface
17–20	Scaled value of first fixed surface
21	Type of second fixed surface (see Code table 4.5)
22	Scale factor of second fixed surface
23–26	Scaled value of second fixed surface
27	Method used to derive the data field values at the local time specified in section 1 (see Code table 4.248)
28	n – number of analyses or forecasts used to create the composite data field at the local time specified in section 1 ($n \geq 1$) <i>Octets 29–46 Specification of the analysis or forecast used in the processing ($n = 1$)</i>
29–30	Year of the analysis or forecast used in the processing
31	Month of the analysis or forecast used in the processing
32	Day of the analysis or forecast used in the processing
33	Hour of the analysis or forecast used in the processing
34	Minute of the analysis or forecast used in the processing
35	Second of the analysis or forecast used in the processing
36	Indicator of units of forecast time (see Note and Code table 4.4)
37–40	Forecast time (see Note)
41	Number of time increments of the forecast used in the processing
42	Indicator of units of time for the time increments
43–46	Time increments between successive forecast times <i>Octets 47–nn are included only if $n > 1$ where $nn = 28 + 18 \times n$</i>
47–nn	(n–1) repetitions of sequence of octets 29–46 describing the next analyses or forecasts used in the processing

Note: Set to missing if analysis.

Product definition template 4.91 – categorical forecasts at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.91	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15–16	Hours after reference time of data cut-off (see Note 1)
17	Minutes after reference time of data cut-off
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35	NC – number of categories
	<i>36– Repeat the following 12 octets for each category (i = 1, NC)</i>
(36+12(i-1))	Code figure
(37+12(i-1))	Type of interval for first and second limits (see Code table 4.91)
(38+12(i-1))	Scale factor of first limit
(39+12(i-1))–(42+12(i-1))	Scaled value of first limit
(43+12(i-1))	Scale factor of second limit
(44+12(i-1))–(47+12(i-1))	Scaled value of second limit
(48+12(NC-1))–(49+12(NC-1))	Year of end of overall time interval
(50+12(NC-1))	Month of end of overall time interval
(51+12(NC-1))	Day of end of overall time interval
(52+12(NC-1))	Hour of end of overall time interval
(53+12(NC-1))	Minute of end of overall time interval
(54+12(NC-1))	Second of end of overall time interval
(55+12(NC-1))	n – number of time range specifications describing the time intervals used to calculate the statistically processed field
(56+12(NC-1))–(59+12(NC-1))	Total number of data values missing in statistical process
	<i>60–71 Specification of the outermost (or only) time range over which statistical processing is done</i>
(60+12(NC-1))	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
(61+12(NC-1))	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
(62+12(NC-1))	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
(63+12(NC-1))–(66+12(NC-1))	Length of the time range over which statistical processing is done, in units defined by the previous octet
(67+12(NC-1))	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
(68+12(NC-1))–(71+12(NC-1))	Time increment between successive fields, in units defined by the previous octet (see Notes 3 and 4)

Product definition template 4.91	
Octet No.	Contents
	<i>72–nn</i> These octets are included only if $n > 1$, where $nn = 7271 + 12(n-1) + 12(NC-1)$
(72+12(NC-1))–(83+12(NC-1))	As octets (60+12(NC-1)) to (71+12(NC-1)), next innermost step of processing
(84+12(NC-1))–nn	Additional time range specifications, included in accordance with the value of n . Contents as octets (60+12(NC-1)) to (71+12(NC-1)), repeated as necessary

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The reference time in section 1 and the forecast time together define the beginning of the overall time interval.
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) The reference and forecast times are successively set to their initial values plus or minus the increment, as defined by the type of time increment (one of octets (60+12(NC-1)), (73+12(NC-1)), (85+12(NC-1)), ...). For all but the innermost (last) time range, the next inner range is then processed using these reference and forecast times as the initial reference and forecast times.

Product definition template 4.92 – Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a specified local time

Product definition template 4.92	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15	Type of first fixed surface (see Code table 4.5)
16	Scale factor of first fixed surface
17–20	Scaled value of first fixed surface
21	Type of second fixed surface (see Code table 4.5)
22	Scale factor of second fixed surface
23–26	Scaled value of second fixed surface
27	Type of ensemble forecast (see Code table 4.6)
28	Perturbation number
29	Number of forecasts in ensemble
30	Method used to derive the data field values at the local time specified in section 1 (see Code table 4.248)
31	n – number of forecasts used to create the composite data field at the local time specified in section 1 ($n \geq 1$)
	<i>Octets 32–49 Specification of the forecast used in the processing ($n = 1$)</i>
32–33	Year of the forecast used in the processing
34	Month of the forecast used in the processing
35	Day of the forecast used in the processing
36	Hour of the forecast used in the processing
37	Minute of the forecast used in the processing
38	Second of the forecast used in the processing

Product definition template 4.92	
Octet No.	Contents
39	Indicator of units of forecast time (see Code table 4.4)
40–43	Forecast time (see Note)
44	Number of time increments of the forecast used in the processing
45	Indicator of units of time for the time increments (see Code table 4.4)
46–49	Time increments between successive forecast times <i>Octets 50–nn are included only if $n > 1$ where $nn = 31 + 18 \times n$</i>
50–nn	(n–1) repetitions of sequence of octets 32–49 describing the next analyses or forecasts used in the processing

Note: The reference time in octets 32–38 and the forecast time together define the beginning of the overall time interval.

Product definition template 4.93 – Post-processing analysis or forecast at a horizontal level or in a horizontal layer at a specified local time

Product definition template 4.93	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
44 54312-13	Input process identifier (see Note 1)
14–15	Input originating centre (see Note 2 and Common Code table C-11)
16	Type of post-processing (see Note 3)
17	Type of generating process (see Code table 4.3)
18	Background generating process identifier (defined by originating centre)
19	Analysis or forecast generating process identifier (defined by originating centre)
20	Type of first fixed surface (see Code table 4.5)
21	Scale factor of first fixed surface
22–25	Scaled value of first fixed surface
26	Type of second fixed surface (see Code table 4.5)
27	Scale factor of second fixed surface
28–31	Scaled value of second fixed surface
32	Method used to derive the data field values at the local time specified in section 1 (see Code table 4.248)
33	n – number of analyses or forecasts used to create the composite data field at the local time specified in section 1 ($n \geq 1$) <i>Octets 34–51 Specification of the analysis or forecast used in the processing ($n = 1$)</i>
34–35	Year of the analysis or forecast used in the processing
36	Month of the analysis or forecast used in the processing
37	Day of the analysis or forecast used in the processing
38	Hour of the analysis or forecast used in the processing
39	Minute of the analysis or forecast used in the processing
40	Second of the analysis or forecast used in the processing
41	Indicator of units of forecast time (see Note 5 and Code table 4.4)
42–45	Forecast time (see Note 4 and 5)
46	Number of time increments of the forecast used in the processing

Product definition template 4.93

Octet No.	Contents
47	Indicator of units of time for the time increments (see Code table 4.4)
48–51	Time increments between successive forecast times <i>Octets 52–nn are included only if $n > 1$ where $nn = 33 + 18 \times n$</i>
52–nn	(n–1) repetitions of sequence of octets 34–51 describing the next analyses or forecasts used in the processing

Notes:

- (1) The input process identifier shall have the value of the "analysis or forecast process identifier" of the original GRIB message used as input of the post-processing.
- (2) The input originating centre shall have the value of the "originating centre" of the original GRIB message used as input of the post-processing.
- (3) This identifies which post-processing technique was used. This is defined by the originating centre.
- (4) The reference time in octets 34–40 and the forecast time together define the beginning of the overall time interval.
- (5) Set code to missing if analysis.

Product definition template 4.94 – Post-processing individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a specified local time

Product definition template 4.94

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
4454312-13	Input process identifier (see Note 1)
14–15	Input originating centre (see Note 2 and Common Code table C–11)
16	Type of post-processing (see Note 3)
17	Type of generating process (see Code table 4.3)
18	Background generating process identifier (defined by originating centre)
19	Analysis or forecast generating process identifier (defined by originating centre)
20	Type of first fixed surface (see Code table 4.5)
21	Scale factor of first fixed surface
22–25	Scaled value of first fixed surface
26	Type of second fixed surface (see Code table 4.5)
27	Scale factor of second fixed surface
28–31	Scaled value of second fixed surface
32	Type of ensemble forecast (see Code table 4.6)
33	Perturbation number
34	Number of forecasts in ensemble
35	Method used to derive the data field values at the local time specified in section 1 (see Code table 4.248)
36	n – number of analyses or forecasts used to create the composite data field at the local time specified in section 1 ($n \geq 1$) <i>Octets 37–54 Specification of the analysis or forecast used in the processing ($n = 1$)</i>
37–38	Year of the analysis or forecast used in the processing
39	Month of the analysis or forecast used in the processing
40	Day of the analysis or forecast used in the processing
41	Hour of the analysis or forecast used in the processing
42	Minute of the analysis or forecast used in the processing

Product definition template 4.94	
Octet No.	Contents
43	Second of the analysis or forecast used in the processing
44	Indicator of units of forecast time (set to missing if analysis) (see Code table 4.4)
45–48	Forecast time (see Notes 4 and 5)
49	Number of time increments of the forecast used in the processing
50	Indicator of units of time for the time increments (see Code table 4.4)
51–54	Time increments between successive forecast times <i>Octets 55–nn are included only if $n > 1$ where $nn = 36 + 18 \times n$</i>
55–nn	(n–1) repetitions of sequence of octets 37–54 describing the next analyses or forecasts used in the processing

Notes:

- (1) The input process identifier shall have the value of the "analysis or forecast process identifier" of the original GRIB message used as input of the post-processing.
- (2) The input originating centre shall have the value of the "originating centre" of the original GRIB message used as input of the post-processing.
- (3) This identifies which post-processing technique was used. This is defined by the originating centre.
- (4) The reference time in octets 37–43 and the forecast time together define the beginning of the overall time interval.
- (5) Set code to missing if analysis.

Product definition template 4.95 – Average, accumulation, extreme values or other statistically processed value at a horizontal level or in a horizontal layer at a local time

Product definition template 4.95	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15	Type of first fixed surface (see Code table 4.5)
16	Scale factor of first fixed surface
17–20	Scaled value of first fixed surface
21	Type of second fixed surface (see Code table 4.5)
22	Scale factor of second fixed surface
23–26	Scaled value of second fixed surface
27	Statistical process used to calculate the fields that will be used in the local time processing (see Code table 4.10)
28	Indicator of unit of time range over which statistical processing is done (see Code table 4.4)
29–32	Length of the time range over which statistical processing is done in units defined by the previous octet (see Note 1)
33	Number of statistically processed fields used in the local time composite field (see Note 2)
34	Method used to derive the data field values at the local time specified in section 1 (see Code table 4.248)
35	n – number of analyses or forecasts used to create the composite data field at the local time specified in section 1 ($n \geq 1$) (see Note 3)

Product definition template 4.95

Octet No.	Contents
	<i>Octets 36–53 Specification of the analysis or forecast used in the processing ($n = 1$)</i>
36–37	Year of the analysis or forecast used in the processing
38	Month of the analysis or forecast used in the processing
39	Day of the analysis or forecast used in the processing
40	Hour of the analysis or forecast used in the processing
41	Minute of the analysis or forecast used in the processing
42	Second of the analysis or forecast used in the processing
43	Indicator of units of forecast time (see Note 6 and Code table 4.4)
44–47	Forecast time (see Notes 4 and 6)
48	Number of time increments of the forecast used in the processing
49	Indicator of units of time for the time increments (see Code table 4.4)
50–53	Time increments between successive forecast times (see Note 5)
	<i>Octets 54–nn are included only if $n > 1$ where $nn = 35 + 18 \times n$</i>
54–nn	($n-1$) repetitions of sequence of octets 36–53 describing the next analyses or forecasts used in the processing

Notes:

- (1) This represents the length of time over which the statistical processing was applied. The local time defined in section 1 represents the end of this processing. For instance, a value of 24 h corresponds to a statistical processing between the previous day at local time and this day at local time.
- (2) This represents the number of statistically processed fields (or stripes) used to create the composite local time field. For instance, a value of 8 means that 8 statistically processed fields have been used in the processing, each of them representing a section of 45 degrees of longitude ($360/8$) centred around the UTC time corresponding to the local time.
- (3) This is the number of forecasts and time steps used to create the statistically processed fields. These implicitly have the same statistical process as defined in octet 27. If a forecast has 2 time increments (3 hourly day 1 to 5 then 6 hourly), it should be encoded as 2 forecasts with the same reference time, using the appropriate starting forecast time and time increments.
- (4) The reference time in octets 36–42 and the forecast time together define the beginning of the overall time interval.
- (5) This also represents the length of time range of the statistically processed fields. For instance, to create a 24 h accumulation (encoded in octets 29–32), we could use several 3 h accumulations, or 6 h accumulations, a mixture of the two, etc.
- (6) Set code to missing if analysis.

Product definition template 4.96 – Average, accumulation, extreme values or other statistically processed values of an individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a local time

Product definition template 4.96

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Forecast generating process identifier (defined by originating centre)
15	Type of first fixed surface (see Code table 4.5)
16	Scale factor of first fixed surface
17–20	Scaled value of first fixed surface

Product definition template 4.96	
Octet No.	Contents
21	Type of second fixed surface (see Code table 4.5)
22	Scale factor of second fixed surface
23–26	Scaled value of second fixed surface
27	Type of ensemble forecast (see Code table 4.6)
28	Perturbation number
29	Number of forecasts in ensemble
30	Statistical process used to calculate the fields that will be used in the local time processing (see Code table 4.10)
31	Indicator of unit of time range over which statistical processing is done (see Code table 4.4)
32–35	Length of the time range over which statistical processing is done in units defined by the previous octet (see Note 1)
36	Number of statistically processed fields used in the local time composite field (see Note 2)
37	Method used to derive the data field values at the local time specified in section 1 (see Code table 4.248)
38	n – number of forecasts used to create the composite data field at the local time specified in section 1 ($n \geq 1$) (see Note 3) <i>Octets 39–56 Specification of the forecast used in the processing ($n = 1$)</i>
39–40	Year of the forecast used in the processing
41	Month of the forecast used in the processing
42	Day of the forecast used in the processing
43	Hour of the forecast used in the processing
44	Minute of the forecast used in the processing
45	Second of the forecast used in the processing
46	Indicator of units of forecast time (see Code table 4.4)
47–50	Forecast time (see Note 4)
51	Number of time increments of the forecast used in the processing
52	Indicator of units of time for the time increments (see Code table 4.4)
53–56	Time increments between successive forecast times (see Note 5) <i>Octets 57–nn are included only if $n > 1$ where $nn = 38 + 18 \times n$</i>
57–nn	$(n-1)$ repetitions of sequence of octets 39–56 describing the next analyses or forecasts used in the processing

Notes:

- (1) This represents the length of time over which the statistical processing was applied. The local time defined in section 1 represents the end of this processing. For instance, a value of 24 h corresponds to a statistical processing between the previous day at local time and this day at local time.
- (2) This represents the number of statistically processed fields (or stripes) used to create the composite local time field. For instance, a value of 8 means that 8 statistically processed fields have been used in the processing, each of them representing a section of 45 degrees of longitude ($360/8$) centred around the UTC time corresponding to the local time.
- (3) This is the number of forecasts and time steps used to create the statistically processed fields. These implicitly have the same statistical process as defined in octet 30. If a forecast has 2 time increments (3 hourly day 1 to 5 then 6 hourly), it should be encoded as 2 forecasts with the same reference time, using the appropriate starting forecast time and time increments.
- (4) The reference time in octets 39–45 and the forecast time together define the beginning of the overall time interval.
- (5) This also represents the length of time range of the statistically processed fields. For instance, to create a 24 h accumulations (encoded in octets 32–35), we could use several 3 h accumulations, or 6 h accumulations, a mixture of the two, etc.

Product definition template 4.97 – Average, accumulation, extreme values or other statistically processed values of post-processing analysis or forecast at a horizontal level or in a horizontal layer at a local time

Product definition template 4.97	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
4454312-13	Input process identifier (see Note 1)
14–15	Input originating centre (see Note 2 and Common Code table C-11)
16	Type of post-processing (see Note 3)
17	Type of generating process (see Code table 4.3)
18	Background generating process identifier (defined by originating centre)
19	Analysis or forecast generating process identifier (defined by originating centre)
20	Type of first fixed surface (see Code table 4.5)
21	Scale factor of first fixed surface
22–25	Scaled value of first fixed surface
26	Type of second fixed surface (see Code table 4.5)
27	Scale factor of second fixed surface
28–31	Scaled value of second fixed surface
32	Statistical process used to calculate the fields that will be used in the local time processing (see Code table 4.10)
33	Indicator of unit of time range over which statistical processing is done (see Code table 4.4)
34–37	Length of the time range over which statistical processing is done in units defined by the previous octet (see Note 4)
38	Number of statistically processed fields used in the local time composite field (see Note 5)
39	Method used to derive the data field values at the local time specified in section 1 (see Code table 4.248)
40	n – number of analyses or forecasts used to create the composite data field at the local time specified in section 1 ($n \geq 1$) (see Note 6)
<i>Octets 41–58 Specification of the analysis or forecast used in the processing ($n = 1$)</i>	
41–42	Year of the analysis or forecast used in the processing
43	Month of the analysis or forecast used in the processing
44	Day of the analysis or forecast used in the processing
45	Hour of the analysis or forecast used in the processing
46	Minute of the analysis or forecast used in the processing
47	Second of the analysis or forecast used in the processing
48	Indicator of units of forecast time (set to missing if analysis) (see Code table 4.4)
49–52	Forecast time (see Notes 7 and 9)
53	Number of time increments of the forecast used in the processing
54	Indicator of units of time for the time increments (see Code table 4.4)
55–58	Time increments between successive forecast times (see Note 8)
<i>Octets 59–nn are included only if $n > 1$ where $nn = 40 + 18 \times n$</i>	
59–nn	(n-1) repetitions of sequence of octets 41–58 describing the next analyses or forecasts used in the processing

Notes:

- (1) The input process identifier shall have the value of the "analysis or forecast process identifier" of the original GRIB message used as input of the post-processing.
- (2) The input originating centre shall have the value of the "originating centre" of the original GRIB message used as input of the post-processing.

- (3) This identifies which post-processing technique was used. This is defined by the originating centre.
- (4) This represents the length of time over which the statistical processing was applied. The local time defined in section 1 represents the end of this processing. For instance, a value of 24 h corresponds to a statistical processing between the previous day at local time and this day at local time.
- (5) This represents the number of statistically processed fields (or stripes) used to create the composite local time field. For instance, a value of 8 means that 8 statistically processed fields have been used in the processing, each of them representing a section of 45 degrees of longitude (360/8) centred around the UTC time corresponding to the local time.
- (6) This is the number of forecasts and time steps used to create the statistically processed fields. These implicitly have the same statistical process as defined in octet 32. If a forecast has 2 time increments (3 hourly day 1 to 5 then 6 hourly), it should be encoded as 2 forecasts with the same reference time, using the appropriate starting forecast time and time increments.
- (7) The reference time in octets 41–47 and the forecast time together define the beginning of the overall time interval.
- (8) This also represents the length of time range of the statistically processed fields. For instance, to create a 24 h accumulation (encoded in octets 34–37), we could use several 3 h accumulations, or 6 h accumulations, a mixture of the two, etc.
- (9) Set code to missing if analysis.

Product definition template 4.98 – Average, accumulation, extreme values or other statistically processed values of a post-processing individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a local time

Product definition template 4.98	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
4454312-13	Input process identifier (see Note 1)
14–15	Input originating centre (see Note 2 and Common Code table C-11)
16	Type of post-processing (see Note 3)
17	Type of generating process (see Code table 4.3)
18	Background generating process identifier (defined by originating centre)
19	Forecast generating process identifier (defined by originating centre)
20	Type of first fixed surface (see Code table 4.5)
21	Scale factor of first fixed surface
22–25	Scaled value of first fixed surface
26	Type of second fixed surface (see Code table 4.5)
27	Scale factor of second fixed surface
28–31	Scaled value of second fixed surface
32	Type of ensemble forecast (see Code table 4.6)
33	Perturbation number
34	Number of forecasts in ensemble
35	Statistical process used to calculate the fields that will be used in the local time processing (see Code table 4.10)
36	Indicator of unit of time range over which statistical processing is done (see Code table 4.4)
37–40	Length of the time range over which statistical processing is done in units defined by the previous octet (see Note 4)
41	Number of statistically processed fields used in the local time composite field (see Note 5)

Product definition template 4.98

Octet No.	Contents
42	Method used to derive the data field values at the local time specified in section 1 (see Code table 4.248)
43	n – number of forecasts used to create the composite data field at the local time specified in section 1 ($n \geq 1$) (see Note 6) <i>Octets 44–61 Specification of the forecast used in the processing ($n = 1$)</i>
44–45	Year of the forecast used in the processing
46	Month of the forecast used in the processing
47	Day of the forecast used in the processing
48	Hour of the forecast used in the processing
49	Minute of the forecast used in the processing
50	Second of the forecast used in the processing
51	Indicator of units of forecast time (see Code table 4.4)
52–55	Forecast time (see Notes 7 and 9)
56	Number of time increments of the forecast used in the processing
57	Indicator of units of time for the time increments (see Code table 4.4)
58–61	Time increments between successive forecast times (see Note 8) <i>Octet 62–nn are included only if $n > 1$ where $nn = 43 + 18 \times n$</i>
62–nn	(n–1) repetitions of sequence of octets 44–61 describing the next analyses or forecasts used in the processing

Notes:

- (1) The input process identifier shall have the value of the "analysis or forecast process identifier" of the original GRIB message used as input of the post-processing.
- (2) The input originating centre shall have the value of the "originating centre" of the original GRIB message used as input of the post-processing.
- (3) This identifies which post-processing technique was used. This is defined by the originating centre.
- (4) This represents the length of time over which the statistical processing was applied. The local time defined in section 1 represents the end of this processing. For instance, a value of 24 h corresponds to a statistical processing between the previous day at local time and this day at local time.
- (5) This represents the number of statistically processed fields (or stripes) used to create the composite local time field. For instance, a value of 8 means that 8 statistically processed fields have been used in the processing, each of them representing a section of 45 degrees of longitude ($360/8$) centred around the UTC time corresponding to the local time.
- (6) This is the number of forecasts and time steps used to create the statistically processed fields. These implicitly have the same statistical process as defined in octet 35. If a forecast has 2 time increments (3 hourly day 1 to 5 then 6 hourly), it should be encoded as 2 forecasts with the same reference time, using the appropriate starting forecast time and time increments.
- (7) The reference time in octets 44–50 and the forecast time together define the beginning of the overall time interval.
- (8) This also represents the length of time range of the statistically processed fields. For instance, to create a 24 h accumulation (encoded in octets 37–40), we could use several 3 h accumulations, or 6 h accumulations, a mixture of the two, etc.
- (9) Set code to missing if analysis.

Product definition template 4.99 – Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with explicit list of frequencies and directions

<i>Product definition template 4.99</i>	
Octet No.	Contents
<u>10</u>	<u>Parameter category (see Code table 4.1)</u>
<u>11</u>	<u>Parameter number (see Code table 4.2)</u>
<u>12-13</u>	<u>Wave direction number</u>
<u>14-15</u>	<u>Number of wave directions (ND)</u>
<u>16-17</u>	<u>Wave frequency number</u>
<u>18-19</u>	<u>Number of wave frequencies (NF)</u>
<u>20</u>	<u>Type of generating process (see Code table 4.3)</u>
<u>21</u>	<u>Background generating process identifier (defined by originating centre)</u>
<u>22</u>	<u>Analysis or forecast generating process identifier (defined by originating centre)</u>
<u>23-24</u>	<u>Hours of observational data cut-off after reference time (see Note 1)</u>
<u>25</u>	<u>Minutes of observational data cut-off after reference time</u>
<u>26</u>	<u>Indicator of unit of time range (see Code table 4.4)</u>
<u>27-30</u>	<u>Forecast time in units defined by previous octet</u>
<u>31</u>	<u>Scale factor of wave directions</u> <i>The following entry of 4 octets is repeated ND times. (ND is defined in octets 14-15)</i>
<u>32 + (ND-1)*4 -35 + (ND-1)*4</u>	<u>Scaled values of wave directions</u>
<u>36 + (ND-1)*4</u>	<u>Scale factor of wave frequencies (see Note 2)</u> <i>The following entry of 4 octets is repeated NF times. (NF is defined in octets 18-19)</i>
<u>37 + (ND-1)*4 + (NF-1)*4 -40 + (ND-1)*4 + (NF-1)*4</u>	<u>Scaled values of wave frequencies (see Note 3)</u>

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) The units of the wave directions are degree true.
- (3) The frequencies are defined as $1/T$ where T is the wave period in seconds.

Product definition template 4.100 – Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with explicit list of frequencies and directions

<i>Product definition template 4.100</i>	
Octet No.	Contents
<u>10</u>	<u>Parameter category (see Code table 4.1)</u>
<u>11</u>	<u>Parameter number (see Code table 4.2)</u>
<u>12-13</u>	<u>Wave direction number</u>
<u>14-15</u>	<u>Number of wave directions (ND)</u>
<u>16-17</u>	<u>Wave frequency number</u>
<u>18-19</u>	<u>Number of wave frequencies (NF)</u>
<u>20</u>	<u>Type of generating process (see Code table 4.3)</u>
<u>21</u>	<u>Background generating process identifier (defined by originating centre)</u>
<u>22</u>	<u>Analysis or forecast generating process identifier (defined by originating centre)</u>
<u>23-24</u>	<u>Hours of observational data cut-off after reference time (see Note 1)</u>
<u>25</u>	<u>Minutes of observational data cut-off after reference time</u>

Product definition template 4.100

Octet No.	Contents
26	Indicator of unit of time range (see Code table 4.4)
27-30	Forecast time in units defined by previous octet
31	Type of ensemble forecast (see Code table 4.6)
32	Perturbation number
33	Number of forecasts in ensemble
34	Scale factor of wave directions
<i>The following entry of 4 octets is repeated ND times. (ND is defined in octets 14-15)</i>	
35 + (ND-1)*4 - 38 + (ND-1)*4	Scaled values of wave directions (see Note 2)
39 + (ND-1)*4	Scale factor of wave frequencies
<i>The following entry of 4 octets is repeated NF times. (NF is defined in octets 18-19)</i>	
40 + (ND-1)*4 + (NF-1)*4 - 43 + (ND-1)*4 + (NF-1)*4	Scaled values of wave frequencies (see Note 3)

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
 (2) The units of the wave directions are degree true.
 (3) The frequencies are defined as 1/T where T is the wave period in seconds.

Product definition template 4.101 – Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with frequencies and directions defined by formulae

Product definition template 4.101

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12-13	Wave direction number
14-15	Number of wave directions (ND)
16-17	Wave frequency number
18-19	Number of wave frequencies (NF)
20	Type of generating process (see Code table 4.3)
21	Background generating process identifier (defined by originating centre)
22	Analysis or forecast generating process identifier (defined by originating centre)
23-24	Hours of observational data cut-off after reference time (see Note 1)
25	Minutes of observational data cut-off after reference time
26	Indicator of unit of time range (see Code table 4.4)
27-30	Forecast time in units defined by previous octet
31	Type of wave direction sequence (see Code table 4.251)
32	Number of wave direction sequence parameters (NDSP)
<i>The next two entries are repeated NDSP times to encode the scale factors and scaled values of the sequence parameters.</i>	
33 + (NDSP-1)*5	Scale factor of wave direction sequence parameter
34+(NDSP-1)*5 - 37+(NDSP-1)*5	Scaled value of wave direction sequence parameter (see Note 2)
33+NDSP*5	Type of wave frequency sequence (see Code table 4.251)
34+NDSP*5	Number of wave frequency sequence parameters (NFSP)

The next two entries are repeated NFSP times to encode the scale factors and scaled values of the sequence parameters.

$35 + \text{NDSP} * 5 + (\text{NFSP} - 1) * 5$	Scale factor of wave frequency sequence parameter
$36 + \text{NDSP} * 5 + (\text{NFSP} - 1) * 5 -$ $39 + \text{NDSP} * 5 + (\text{NFSP} - 1) * 5$	Scaled value of wave frequency sequence parameter (see Note 3)

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
 (2) The units of the wave directions are degree true.
 (3) The frequencies are defined as $1/T$ where T is the wave period in seconds.

Product definition template 4.102 – Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with frequencies and directions defined by formulae

<i>Product definition template 4.102</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12-13	Wave direction number
14-15	Number of wave directions (ND)
16-17	Wave frequency number
18-19	Number of wave frequencies (NF)
20	Type of generating process (see Code table 4.3)
21	Background generating process identifier (defined by originating centre)
22	Analysis or forecast generating process identifier (defined by originating centre)
23-24	Hours of observational data cut-off after reference time (see Note 1)
25	Minutes of observational data cut-off after reference time
26	Indicator of unit of time range (see Code table 4.4)
27-30	Forecast time in units defined by previous octet
31	Type of ensemble forecast (see Code table 4.6)
32	Perturbation number
33	Number of forecasts in ensemble
34	Type of wave direction sequence (see Code table 4.251)
35	Number of wave direction sequence parameters (NDSP)
<i>The next two entries are repeated NDSP times to encode the scale factors and scaled values of the sequence parameters.</i>	
$36 + (\text{NDSP} - 1) * 5$	Scale factor of wave direction sequence parameter
$37 + (\text{NDSP} - 1) * 5 -$ $40 + (\text{NDSP} - 1) * 5$	Scaled value of wave direction sequence parameter (see Note 2)
$36 + \text{NDSP} * 5$	Type of wave frequency sequence (see Code table 4.251)
$37 + \text{NDSP} * 5$	Number of wave frequency sequence parameters (NFSP)
<i>The next two entries are repeated NFSP times to encode the scale factors and scaled values of the sequence parameters.</i>	
$38 + \text{NDSP} * 5 + (\text{NFSP} - 1) * 5$	Scale factor of wave frequency sequence parameter
$39 + \text{NDSP} * 5 + (\text{NFSP} - 1) * 5 -$ $42 + \text{NDSP} * 5 + (\text{NFSP} - 1) * 5$	Scaled value of wave frequency sequence parameter (see Note 3)

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
 (2) The units of the wave directions are degree true.
 (3) The frequencies are defined as $1/T$ where T is the wave period in seconds.

Product definition template 4.103 – Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for waves selected by period range

<i>Product definition template 4.103</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of wave period interval (see Code table 4.91)
13	Scale factor of lower wave period limit
14-17	Scaled value of lower wave period limit (see Note 1)
18	Scale factor of upper wave period limit
19-22	Scaled value of upper wave period limit (see Note 1)
23	Type of generating process (see Code table 4.3)
24	Background generating process identifier (defined by originating centre)
25	Analysis or forecast generating process identifier (defined by originating centre)
26-27	Hours of observational data cut-off after reference time (see Note 2)
28	Minutes of observational data cut-off after reference time
29	Indicator of unit of time range (see Code table 4.4)
30-33	Forecast time in units defined by previous octet
34	Type of first fixed surface (see Code table 4.5)
35	Scale factor of first fixed surface
36-39	Scaled value of first fixed surface
40	Type of second fixed surface (see Code table 4.5)
41	Scale factor of second fixed surface
42-45	Scaled value of second fixed surface

Notes:

- (1) Wave periods should be specified in seconds.
 (2) Hours greater than 65534 will be coded as 65534.

Product definition template 4.104 – Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for waves selected by period range

<i>Product definition template 4.104</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of wave period interval (see Code table 4.91)
13	Scale factor of lower wave period limit
14-17	Scaled value of lower wave period limit (see Note 1)
18	Scale factor of upper wave period limit
19-22	Scaled value of upper wave period limit (see Note 1)
23	Type of generating process (see Code table 4.3)
24	Background generating process identifier (defined by originating centre)
25	Analysis or forecast generating process identifier (defined by originating centre)
26-27	Hours of observational data cut-off after reference time (see Note 2)

Product definition template 4.104

Octet No.	Contents
28	Minutes of observational data cut-off after reference time
29	Indicator of unit of time range (see Code table 4.4)
30-33	Forecast time in units defined by previous octet
34	Type of first fixed surface (see Code table 4.5)
35	Scale factor of first fixed surface
36-39	Scaled value of first fixed surface
40	Type of second fixed surface (see Code table 4.5)
41	Scale factor of second fixed surface
42-45	Scaled value of second fixed surface
46	Type of ensemble forecast (see Code table 4.6)
47	Perturbation number
48	Number of forecasts in ensemble

Notes:

- (1) Wave periods should be specified in seconds.
 (2) Hours greater than 65534 will be coded as 65534.

Product definition template 4.105 – Anomalies, significance and other derived products from an analysis or forecast in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.105

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15-16	Hours of observational data cut-off after reference time (see Note 1)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19-22	Forecast time in units defined by previous octet
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25-28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31-34	Scaled value of second fixed surface
35-36	Year of end of overall time interval
37	Month of end of overall time interval
38	Day of end of overall time interval
39	Hour of end of overall time interval
40	Minute of end of overall time interval
41	Second of end of overall time interval
42	Number of time range
43-46	Number of missing in statistical process
<i>The next six entries are repeated NT times nt=1:NT</i>	
47 + (nt-1)*12	Type of statistical processing
48 + (nt-1)*12	Type of time increment

<i>Product definition template 4.105</i>	
<u>Octet No.</u>	<u>Contents</u>
$49 + (nt-1)*12$	<u>Indicator of unit for time range</u>
$50 + (nt-1)*12 - 53 + (nt-1)*12$	<u>Length of time range</u>
$54 + (nt-1)*12$	<u>Indicator of unit for time increment (see Code table 4.4)</u>
$55 + (nt-1)*12 - 58 + (nt-1)*12$	<u>Time increment</u>
<i>End of sequence repeated NT times</i>	
$59 + (NT-1)*12$	<u>Type of reference dataset (see Code table 4.100)</u>
$60 + (NT-1)*12$	<u>Type of relation to reference dataset (see Code table 4.101)</u>
$61 + (NT-1)*12$	<u>Number of additional parameter for reference period - NA (see Note 2)</u> <i>The next two entries are repeated NA times na=0:NA - can be 0 times if no parameters are necessary</i>
$62 + (NT-1)*12 + (na-1)*5$	<u>Scale factor of additional parameter for reference period</u>
$63 + (NT-1)*12 + (na-1)*5 - 66 + (NT-1)*12 + (na-1)*5$	<u>Scaled value of additional parameter for reference period</u>
<i>end of repeated NA sequence</i>	
$62 + (NT-1)*12 + NA*5 - 63 + (NT-1)*12 + NA*5$	<u>Year of start of reference period</u>
$64 + (NT-1)*12 + NA*5$	<u>Month of start of reference period</u>
$65 + (NT-1)*12 + NA*5$	<u>Day of start of reference period</u>
$66 + (NT-1)*12 + NA*5$	<u>Hour of start of reference period</u>
$67 + (NT-1)*12 + NA*5$	<u>Minute of start of reference period</u>
$68 + (NT-1)*12 + NA*5$	<u>Second of start of reference period</u>
$69 + (NT-1)*12 + NA*5 - 72 + (NT-1)*12 + NA*5$	<u>Sample size of reference period</u>
$73 + (NT-1)*12 + NA*5$	<u>Number of reference period time range - NR (see Note 3)</u> <i>The next three entries are repeated NR times nr=1:NR</i>
$74 + (NT-1)*12 + NA*5 + (nr-1)*6$	<u>Type of statistical processing for time range for reference period (see Code table 4.102)</u>
$75 + (NT-1)*12 + NA*5 + (nr-1)*6$	<u>Indicator of unit of time range for reference period (see Code table 4.4)</u>
$76 + (NT-1)*12 + NA*5 + (nr-1)*6 - 79 + (NT-1)*12 + NA*5 + (nr-1)*6$	<u>Length of time range for reference period</u>
<i>end of repeated NR sequence</i>	

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) See notes under Code table 4.101 for details.
- (3) 'Number of reference period time range' is used to define an outer and, if needed, one or more inner loops. The outer loop gives the overall date and time range of the reference period and the inner loop(s) are used to specify a sub-period over all time instances defined in the outer loop in terms of the time unit defined by "Reference period indicator of unit for time increment". Typically the outer loop defines a number of years and inner loop defines the date and time range within each year: for instance 'every January for 30 years'.

Product definition template 4.106 – Anomalies, significance and other derived products from an individual ensemble forecast, control and perturbed in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

<i>Product definition template 4.106</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15-16	Hours of observational data cut-off after reference time (see Note 1)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19-22	Forecast time in units defined by previous octet
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25-28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31-34	Scaled value of second fixed surface
35-36	Year of end of overall time interval
37	Month of end of overall time interval
38	Day of end of overall time interval
39	Hour of end of overall time interval
40	Minute of end of overall time interval
41	Second of end of overall time interval
42	Number of time range
43-46	Number of missing in statistical process
<i>The next six entries are repeated NT times nt=1:NT</i>	
47 + (nt-1)*12	Type of statistical processing
48 + (nt-1)*12	Type of time increment
49 + (nt-1)*12	Indicator of unit for time range
50 + (nt-1)*12 - 53 + (nt-1)*12	Length of time range
54 + (nt-1)*12	Indicator of unit for time increment (see Code table 4.4)
55 + (nt-1)*12 - 58 + (nt-1)*12	Time increment
<i>End of sequence repeated NT times</i>	
59 + (NT-1)*12	Type of ensemble forecast (see Code table 4.6)
60 + (NT-1)*12	Perturbation number
61 + (NT-1)*12	Number of forecasts in ensemble
62 + (NT-1)*12	Type of reference dataset (see Code table 4.100)
63 + (NT-1)*12	Type of relation to reference dataset (see Code table 4.101)
64 + (NT-1)*12	Number of additional parameter for reference period - NA (see Note 2)
<i>The next two entries are repeated NA times na=0:NA - can be 0 times if no parameters are necessary</i>	
65 + (NT-1)*12 + (na-1)*5	Scale factor of additional parameter for reference period

Product definition template 4.106

<u>Octet No.</u>	<u>Contents</u>
<u>66 + (NT-1)*12 + (na-1)*5 ,Äi 69 + (NT-1)*12 + (na-1)*5</u>	<u>Scaled value of additional parameter for reference period</u>
	<u>end of repeated NA sequence</u>
<u>65 + (NT-1)*12 + NA*5 - 66 + (NT-1)*12 + NA*5</u>	<u>Year of start of reference period</u>
<u>67 + (NT-1)*12 + NA*5</u>	<u>Month of start of reference period</u>
<u>68 + (NT-1)*12 + NA*5</u>	<u>Day of start of reference period</u>
<u>69 + (NT-1)*12 + NA*5</u>	<u>Hour of start of reference period</u>
<u>70 + (NT-1)*12 + NA*5</u>	<u>Minute of start of reference period</u>
<u>71 + (NT-1)*12 + NA*5</u>	<u>Second of start of reference period</u>
<u>72 + (NT-1)*12 + NA*5 ,Äi 75 + (NT-1)*12 + NA*5</u>	<u>Sample size of reference period</u>
<u>76 + (NT-1)*12 + NA*5</u>	<u>Number of reference period time range - NR (see Note 3)</u>
	<u>The next three entries are repeated NR times nr=1:NR</u>
<u>77 + (NT-1)*12 + NA*5 + (nr-1)*6</u>	<u>Type of statistical processing for time range for reference period (see Code table 4.102)</u>
<u>78 + (NT-1)*12 + NA*5 + (nr-1)*6</u>	<u>Indicator of unit of time range for reference period (see Code table 4.4)</u>
<u>79 + (NT-1)*12 + NA*5 + (nr-1)*6 - 82 + (NT-1)*12 + NA*5 + (nr-1)*6</u>	<u>Length of time range for reference period</u>
	<u>end of repeated NR sequence</u>

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) See notes under Code table 4.101 for details.
- (3) 'Number of reference period time range' is used to define an outer and, if needed, one or more inner loops. The outer loop gives the overall date and time range of the reference period and the inner loop(s) are used to specify a sub-period over all time instances defined in the outer loop in terms of the time unit defined by "Reference period indicator of unit for time increment". Typically the outer loop defines a number of years and inner loop defines the date and time range within each year: for instance 'every January for 30 years'.

Product definition template 4.107 – Anomalies, significance and other derived products from derived forecasts based on all ensemble members in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

Product definition template 4.107

<u>Octet No.</u>	<u>Contents</u>
<u>10</u>	<u>Parameter category (see Code table 4.1)</u>
<u>11</u>	<u>Parameter number (see Code table 4.2)</u>

Product definition template 4.107

<u>Octet No.</u>	<u>Contents</u>
<u>12</u>	<u>Type of generating process (see Code table 4.3)</u>
<u>13</u>	<u>Background generating process identifier (defined by originating centre)</u>
<u>14</u>	<u>Analysis or forecast generating process identifier (defined by originating centre)</u>
<u>15-16</u>	<u>Hours of observational data cut-off after reference time (see Note 1)</u>
<u>17</u>	<u>Minutes of observational data cut-off after reference time</u>
<u>18</u>	<u>Indicator of unit of time range (see Code table 4.4)</u>
<u>19-22</u>	<u>Forecast time in units defined by previous octet</u>
<u>23</u>	<u>Type of first fixed surface (see Code table 4.5)</u>
<u>24</u>	<u>Scale factor of first fixed surface</u>
<u>25-28</u>	<u>Scaled value of first fixed surface</u>
<u>29</u>	<u>Type of second fixed surface (see Code table 4.5)</u>
<u>30</u>	<u>Scale factor of second fixed surface</u>
<u>31-34</u>	<u>Scaled value of second fixed surface</u>
<u>35-36</u>	<u>Year of end of overall time interval</u>
<u>37</u>	<u>Month of end of overall time interval</u>
<u>38</u>	<u>Day of end of overall time interval</u>
<u>39</u>	<u>Hour of end of overall time interval</u>
<u>40</u>	<u>Minute of end of overall time interval</u>
<u>41</u>	<u>Second of end of overall time interval</u>
<u>42</u>	<u>Number of time range</u>
<u>43-46</u>	<u>Number of missing in statistical process</u>
<i>The next six entries are repeated NT times nt=1:NT</i>	
<u>47 + (nt-1)*12</u>	<u>Type of statistical processing</u>
<u>48 + (nt-1)*12</u>	<u>Type of time increment</u>
<u>49 + (nt-1)*12</u>	<u>Indicator of unit for time range</u>
<u>50 + (nt-1)*12 - 53</u> <u>+ (nt-1)*12</u>	<u>Length of time range</u>
<u>54 + (nt-1)*12</u>	<u>Indicator of unit for time increment (see Code table 4.4)</u>
<u>55 + (nt-1)*12 - 58</u> <u>+ (nt-1)*12</u>	<u>Time increment</u>
<i>End of sequence repeated NT times</i>	
<u>59 + (NT-1)*12</u>	<u>Derived forecast (see Code table 4.7)</u>
<u>60 + (NT-1)*12</u>	<u>Number of forecasts in ensemble</u>
<u>61 + (NT-1)*12</u>	<u>Type of reference dataset (see Code table 4.100)</u>
<u>62 + (NT-1)*12</u>	<u>Type of relation to reference dataset (see Code table 4.101)</u>
<u>63 + (NT-1)*12</u>	<u>Number of additional parameter for reference period - NA (see Note 2)</u>
<i>The next two entries are repeated NA times na=0:NA - can be 0 times if no parameters are necessary</i>	
<u>64 + (NT-1)*12 +</u> <u>(na-1)*5</u>	<u>Scale factor of additional parameter for reference period</u>
<u>65 + (NT-1)*12 +</u> <u>(na-1)*5 - 68 +</u> <u>(NT-1)*12 + (na-</u> <u>1)*5</u>	<u>Scaled value of additional parameter for reference period</u>
<i>end of repeated NA sequence</i>	
<u>64 + (NT-1)*12 +</u> <u>NA*5 - 65 + (NT-</u> <u>1)*12 + NA*5</u>	<u>Year of start of reference period</u>
<u>66 + (NT-1)*12 +</u> <u>NA*5</u>	<u>Month of start of reference period</u>

Product definition template 4.107

Octet No.	Contents
67 + (NT-1)*12 + NA*5	Day of start of reference period
68 + (NT-1)*12 + NA*5	Hour of start of reference period
69 + (NT-1)*12 + NA*5	Minute of start of reference period
70 + (NT-1)*12 + NA*5	Second of start of reference period
71 + (NT-1)*12 + NA*5 - 74 + (NT-1)*12 + NA*5	Sample size of reference period
75 + (NT-1)*12 + NA*5	Number of reference period time range - NR (see Note 3)
<i>The next three entries are repeated NR times nr=1..NR</i>	
76 + (NT-1)*12 + NA*5 + (nr-1)*6	Type of statistical processing for time range for reference period (see Code table 4.102)
77 + (NT-1)*12 + NA*5 + (nr-1)*6	Indicator of unit of time range for reference period (see Code table 4.4)
78 + (NT-1)*12 + NA*5 + (nr-1)*6 - 81 + (NT-1)*12 + NA*5 + (nr-1)*6	Length of time range for reference period
<i>end of repeated NR sequence</i>	

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) See notes under Code table 4.101 for details.
- (3) 'Number of reference period time range' is used to define an outer and, if needed, one or more inner loops. The outer loop gives the overall date and time range of the reference period and the inner loop(s) are used to specify a sub-period over all time instances defined in the outer loop in terms of the time unit defined by "Reference period indicator of unit for time increment". Typically the outer loop defines a number of years and inner loop defines the date and time range within each year: for instance 'every January for 30 years'.

Product definition template 4.108 - Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for generic optical products*Product definition template 4.108*

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of interval (for wavelength) (see Code table 4.91)
13	Scale factor of first wavelength
14-17	Scaled value of first wavelength
18	Scale factor of second wavelength
19-22	Scaled value of second wavelength
23	Type of generating process (see Code table 4.3)
24	Background generating process identifier (defined by originating centre)
25	Forecast generating process identifier (defined by originating centre)
26-27	Hours after reference time of data cut-off
28	Minutes after reference time of data cut-off
29	Indicator of unit of time range (see Code table 4.4)

Product definition template 4.108

<u>Octet No.</u>	<u>Contents</u>
<u>30-33</u>	<u>Forecast time in units defined by octet 29</u>
<u>34</u>	<u>Type of first fixed surface (see Code table 4.5)</u>
<u>35</u>	<u>Scale factor of first fixed surface</u>
<u>36-39</u>	<u>Scaled value of first fixed surface</u>
<u>40</u>	<u>Type of second fixed surface (see Code table 4.5)</u>
<u>41</u>	<u>Scale factor of second fixed surface</u>
<u>42-45</u>	<u>Scaled value of second fixed surface</u>

Product definition template 4.109 - Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for generic optical products

Product definition template 4.109

<u>Octet No.</u>	<u>Contents</u>
<u>10</u>	<u>Parameter category (see Code table 4.1)</u>
<u>11</u>	<u>Parameter number (see Code table 4.2)</u>
<u>12</u>	<u>Type of interval (for wavelength) (see Code table 4.91)</u>
<u>13</u>	<u>Scale factor of first wavelength</u>
<u>14-17</u>	<u>Scaled value of first wavelength</u>
<u>18</u>	<u>Scale factor of second wavelength</u>
<u>19-22</u>	<u>Scaled value of second wavelength</u>
<u>23</u>	<u>Type of generating process (see Code table 4.3)</u>
<u>24</u>	<u>Background generating process identifier (defined by originating centre)</u>
<u>25</u>	<u>Forecast generating process identifier (defined by originating centre)</u>
<u>26-27</u>	<u>Hours after reference time of data cut-off</u>
<u>28</u>	<u>Minutes after reference time of data cut-off</u>
<u>29</u>	<u>Indicator of unit of time range (see Code table 4.4)</u>
<u>30-33</u>	<u>Forecast time in units defined by octet 29</u>
<u>34</u>	<u>Type of first fixed surface (see Code table 4.4)</u>
<u>35</u>	<u>Scale factor of first fixed surface</u>
<u>36-39</u>	<u>Scaled value of first fixed surface</u>
<u>40</u>	<u>Type of second fixed surface (see Code table 4.5)</u>
<u>41</u>	<u>Scale factor of second fixed surface</u>
<u>42-45</u>	<u>Scaled value of second fixed surface</u>
<u>46</u>	<u>Type of ensemble forecast (see Code table 4.6)</u>
<u>47</u>	<u>Perturbation number</u>
<u>48</u>	<u>Number of forecasts in ensemble</u>

Product definition template 4.110 - Average, accumulation, extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for generic optical products

Product definition template 4.110

<u>Octet No.</u>	<u>Contents</u>
<u>10</u>	<u>Parameter category (see Code table 4.1)</u>
<u>11</u>	<u>Parameter number (see Code table 4.2)</u>
<u>12</u>	<u>Type of interval (for wavelength) (see Code table 4.91)</u>
<u>13</u>	<u>Scale factor of first wavelength</u>

<i>Product definition template 4.110</i>	
Octet No.	Contents
<u>14-17</u>	<u>Scaled value of first wavelength</u>
<u>18</u>	<u>Scale factor of second wavelength</u>
<u>19-22</u>	<u>Scaled value of second wavelength</u>
<u>23</u>	<u>Type of generating process (see Code table 4.3)</u>
<u>24</u>	<u>Background generating process identifier (defined by originating centre)</u>
<u>25</u>	<u>Forecast generating process identifier (defined by originating centre)</u>
<u>26-27</u>	<u>Hours after reference time of data cut-off</u>
<u>28</u>	<u>Minutes after reference time of data cut-off</u>
<u>29</u>	<u>Indicator of unit of time range (see Code table 4.4)</u>
<u>30-33</u>	<u>Forecast time in units defined by octet 29</u>
<u>34</u>	<u>Type of first fixed surface (see Code table 4.5)</u>
<u>35</u>	<u>Scale factor of first fixed surface</u>
<u>36-39</u>	<u>Scaled value of first fixed surface</u>
<u>40</u>	<u>Type of second fixed surface (see Code table 4.5)</u>
<u>41</u>	<u>Scale factor of second fixed surface</u>
<u>42-45</u>	<u>Scaled value of second fixed surface</u>
<u>46-47</u>	<u>Year of end of overall time interval</u>
<u>48</u>	<u>Month of end of overall time interval</u>
<u>49</u>	<u>Day of end of overall time interval</u>
<u>50</u>	<u>Hour of end of overall time interval</u>
<u>51</u>	<u>Minute of end of overall time interval</u>
<u>52</u>	<u>Second of end of overall time interval</u>
<u>53</u>	<u>n - number of time range specifications describing the time intervals used to calculate the statistically processed field</u>
<u>54-57</u>	<u>Total number of data values missing in statistical process</u>
	<u>58-69 Specification of the outermost (or only) time range over which statistical processing is done</u>
<u>58</u>	<u>Statistical process used to calculate the processed field from the field at each time increment during the time range</u>
<u>59</u>	<u>Type of time increment between successive fields used in the statistical processing</u>
<u>60</u>	<u>Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)</u>
<u>61-64</u>	<u>Length of the time range over which statistical processing is done, in units defined by the previous octet</u>
<u>65</u>	<u>Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)</u>
<u>66-69</u>	<u>Time increment between successive fields, in units defined by the previous octet</u>
	<u>70-<i>nn</i> These octets are included only if $n > 1$, where $nn = 57 + 12 \times n$</u>
<u>70-71</u>	<u>As octets 58 to 69, next innermost step of processing</u>
<u>72-<i>nn</i></u>	<u>Additional time range specifications, included in accordance with the value of n. Contents as octets 58 to 69, repeated as necessary</u>

Product definition template 4.111 - Average, accumulation, extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for generic optical products

<i>Product definition template 4.111</i>	
Octet No.	Contents
<u>10</u>	<u>Parameter category (see Code table 4.1)</u>

<i>Product definition template 4.111</i>	
<u>Octet No.</u>	<u>Contents</u>
<u>11</u>	<u>Parameter number (see Code table 4.2)</u>
<u>12</u>	<u>Type of interval (for wavelength) (see Code table 4.91)</u>
<u>13</u>	<u>Scale factor of first wavelength</u>
<u>14-17</u>	<u>Scaled value of first wavelength</u>
<u>18</u>	<u>Scale factor of second wavelength</u>
<u>19-22</u>	<u>Scaled value of second wavelength</u>
<u>23</u>	<u>Type of generating process (see Code table 4.3)</u>
<u>24</u>	<u>Background generating process identifier (defined by originating centre)</u>
<u>25</u>	<u>Forecast generating process identifier (defined by originating centre)</u>
<u>26-27</u>	<u>Hours after reference time of data cut-off</u>
<u>28</u>	<u>Minutes after reference time of data cut-off</u>
<u>29</u>	<u>Indicator of unit of time range (see Code table 4.4)</u>
<u>30-33</u>	<u>Forecast time in units defined by octet 29</u>
<u>34</u>	<u>Type of first fixed surface (see Code table 4.5)</u>
<u>35</u>	<u>Scale factor of first fixed surface</u>
<u>36-39</u>	<u>Scaled value of first fixed surface</u>
<u>40</u>	<u>Type of second fixed surface (see Code table 4.5)</u>
<u>41</u>	<u>Scale factor of second fixed surface</u>
<u>42-45</u>	<u>Scaled value of second fixed surface</u>
<u>46</u>	<u>Type of ensemble forecast</u>
<u>47</u>	<u>Perturbation number</u>
<u>48</u>	<u>Number of forecasts in ensemble</u>
<u>49-50</u>	<u>Year of end of overall time interval</u>
<u>51</u>	<u>Month of end of overall time interval</u>
<u>52</u>	<u>Day of end of overall time interval</u>
<u>53</u>	<u>Hour of end of overall time interval</u>
<u>54</u>	<u>Minute of end of overall time interval</u>
<u>55</u>	<u>Second of end of overall time interval</u>
<u>56</u>	<u>n - number of time range specifications describing the time intervals used to calculate the statistically processed field</u>
<u>57-60</u>	<u>Total number of data values missing in statistical process</u>
	<u>61-72 Specification of the outermost (or only) time range over which statistical processing is done</u>
<u>61</u>	<u>Statistical process used to calculate the processed field from the field at each time increment during the time range</u>
<u>62</u>	<u>Type of time increment between successive fields used in the statistical processing</u>
<u>63</u>	<u>Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)</u>
<u>64-67</u>	<u>Length of the time range over which statistical processing is done, in units defined by the previous octet</u>
<u>68</u>	<u>Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)</u>
<u>69-72</u>	<u>Time increment between successive fields, in units defined by the previous octet</u>
	<u>73-<i>nn</i> These octets are included only if $n > 1$, where $nn = 60 + 12 \times n$</u>
<u>73-74</u>	<u>As octets 61 to 72, next innermost step of processing</u>
<u>75-<i>nn</i></u>	<u>Additional time range specifications, included in accordance with the value of n. Contents as octets 61 to 72, repeated as necessary</u>

Product definition template 4.112 – Anomalies, significance and other derived products as probability forecasts in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval

<i>Product definition template 4.112</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15-16	Hours of observational data cut-off after reference time (see Note 1)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19-22	Forecast time in units defined by previous octet
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25-28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31-34	Scaled value of second fixed surface
35-36	Year of end of overall time interval
37	Month of end of overall time interval
38	Day of end of overall time interval
39	Hour of end of overall time interval
40	Minute of end of overall time interval
41	Second of end of overall time interval
42	Number of time range
43-46	Number of missing in statistical process
<i>The next six entries are repeated NT times nt=1:NT</i>	
47 + (nt-1)*12	Type of statistical processing
48 + (nt-1)*12	Type of time increment
49 + (nt-1)*12	Indicator of unit for time range
50 + (nt-1)*12 - 53 + (nt-1)*12	Length of time range
54 + (nt-1)*12	Indicator of unit for time increment (see Code table 4.4)
55 + (nt-1)*12 - 58 + (nt-1)*12	Time increment
<i>End of sequence repeated NT times</i>	
59 + (NT-1)*12	Forecast probability number
60 + (NT-1)*12	Total number of forecast probabilities
61 + (NT-1)*12	Probability type (see Code table 4.9)
62 + (NT-1)*12	Scale factor of lower limit
63 + (NT-1)*12 - 66 + (NT-1)*12	Scaled value of lower limit
67 + (NT-1)*12	Scale factor of lower limit
68 + (NT-1)*12 - 71 + (NT-1)*12	Scaled value of lower limit
72 + (NT-1)*12	Type of reference dataset (see Code table 4.100)
73 + (NT-1)*12	Type of relation to reference dataset (see Code table 4.101)
74 + (NT-1)*12	Number of additional parameter for reference period - NA (see Note 2)
<i>The next two entries are repeated NA times na=0:NA - can be 0 times if no parameters are necessary</i>	

Product definition template 4.112

Octet No.	Contents
$75 + (NT-1)*12 + (na-1)*5$	<u>Scale factor of additional parameter for reference period</u>
$76 + (NT-1)*12 + (na-1)*5 - 79 + (NT-1)*12 + (na-1)*5$	<u>Scaled value of additional parameter for reference period</u>
	<u>end of repeated NA sequence</u>
$75 + (NT-1)*12 + NA*5 - 76 + (NT-1)*12 + NA*5$	<u>Year of start of reference period</u>
$77 + (NT-1)*12 + NA*5$	<u>Month of start of reference period</u>
$78 + (NT-1)*12 + NA*5$	<u>Day of start of reference period</u>
$79 + (NT-1)*12 + NA*5$	<u>Hour of start of reference period</u>
$80 + (NT-1)*12 + NA*5$	<u>Minute of start of reference period</u>
$81 + (NT-1)*12 + NA*5$	<u>Second of start of reference period</u>
$82 + (NT-1)*12 + NA*5 - 85 + (NT-1)*12 + NA*5$	<u>Sample size of reference period</u>
$86 + (NT-1)*12 + NA*5$	<u>Number of reference period time range - NR (see Note 3)</u>
	<u>The next three entries are repeated NR times nr=1:NR</u>
$87 + (NT-1)*12 + NA*5 + (nr-1)*6$	<u>Type of statistical processing for time range for reference period (see Code table 4.102)</u>
$88 + (NT-1)*12 + NA*5 + (nr-1)*6$	<u>Indicator of unit of time range for reference period (see Code table 4.4)</u>
$89 + (NT-1)*12 + NA*5 + (nr-1)*6 - 92 + (NT-1)*12 + NA*5 + (nr-1)*6$	<u>Length of time range for reference period</u>
	<u>end of repeated NR sequence</u>

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) See notes under Code table 4.101 for details.
- (3) 'Number of reference period time range' is used to define an outer and, if needed, one or more inner loops. The outer loop gives the overall date and time range of the reference period and the inner loop(s) are used to specify a sub-period over all time instances defined in the outer time loop in terms of the time unit defined by "Reference period indicator of unit for time increment". Typically the outer loop defines a number of years and inner loop defines the date and time range within each year: for instance 'every January for 30 years'.

Product definition template 4.254 – CCITT IA5 character string*Product definition template 4.254*

Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12–15	Number of characters

Product definition template 4.1000 – cross-section of analysis and forecast at a point in time

<i>Product definition template 4.1000</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours of observational data cut-off after reference time (see Note 2)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18

Notes:

- (1) This template is experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests.
- (2) Hours greater than 65534 will be coded as 65534.

Product definition template 4.1001 – cross-section of averaged or otherwise statistically processed analysis or forecast over a range of time

<i>Product definition template 4.1001</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours of observational data cut-off after reference time (see Note 1)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23–26	Total number of data values missing in the statistical process
27	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
28	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
29	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
30–33	Length of the time range over which statistical processing is done, in units defined by the previous octet
34	Indicator of unit of time for the increment between the successive fields used (see Code table 4.4)
35–38	Time increment between successive fields, in units defined by the previous octet (see Note 2)

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.

- (3) This template is experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests.

Product definition template 4.1002 – cross-section of analysis and forecast, averaged or otherwise statistically processed over latitude or longitude

<i>Product definition template 4.1002</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours of observational data cut-off after reference time (see Note 2)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Horizontal dimension processed (see Code table 4.220)
24	Treatment of missing data (e.g. below ground) (see Code table 4.221)
25	Type of statistical processing (see Code table 4.10)
26–29	Start of range
30–33	End of range
34–35	Number of values

Notes:

- (1) This template is experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests.
- (2) Hours greater than 65534 will be coded as 65534.

Product definition template 4.1100 – Hovmöller-type grid with no averaging or other statistical processing

<i>Product definition template 4.1100</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours of observational data cut-off after reference time (see Note 2)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface

Notes:

- (1) This template is experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests.
- (2) Hours greater than 65534 will be coded as 65534.

Product definition template 4.1101 – Hovmöller-type grid with averaging or other statistical processing

<i>Product definition template 4.1101</i>	
Octet No.	Contents
10	Parameter category (see Code table 4.1)
11	Parameter number (see Code table 4.2)
12	Type of generating process (see Code table 4.3)
13	Background generating process identifier (defined by originating centre)
14	Analysis or forecast generating process identifier (defined by originating centre)
15–16	Hours of observational data cut-off after reference time (see Note 1)
17	Minutes of observational data cut-off after reference time
18	Indicator of unit of time range (see Code table 4.4)
19–22	Forecast time in units defined by octet 18 (see Note 2)
23	Type of first fixed surface (see Code table 4.5)
24	Scale factor of first fixed surface
25–28	Scaled value of first fixed surface
29	Type of second fixed surface (see Code table 4.5)
30	Scale factor of second fixed surface
31–34	Scaled value of second fixed surface
35–38	Total number of data values missing in the statistical process
39	Statistical process used to calculate the processed field from the field at each time increment during the time range (see Code table 4.10)
40	Type of time increment between successive fields used in the statistical processing (see Code table 4.11)
41	Indicator of unit of time for time range over which statistical processing is done (see Code table 4.4)
42–45	Length of the time range over which statistical processing is done, in units defined by the previous octet
46	Indicator of unit of time for increment between the successive fields used (see Code table 4.4)
47–50	Time increment between successive fields, in units defined by the previous octet (see Note 3)

Notes:

- (1) Hours greater than 65534 will be coded as 65534.
- (2) Reference = reference time (section 1) + forecast range (PDT) + offset and increments from reference time (GDT).
- (3) An increment of zero means that the statistical processing is the result of a continuous (or near-continuous) process, not the processing of a number of discrete samples. Examples of such continuous processes are the temperatures measured by analogue maximum and minimum thermometers or thermographs, and the rainfall measured by a rain gauge.
- (4) This template is experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests. (Octets 35–50 are very similar to octets 43–58 of product definition template 4.8, but the meaning of some fields differs slightly.)

TEMPLATE DEFINITIONS USED IN SECTION 5***Data representation template 5.0 – Grid point data – simple packing***

<i>Data representation template 5.0</i>	
Octet No.	Contents
12–15	Reference value (R) (IEEE 32-bit floating-point value)
16–17	Binary scale factor (E)
18–19	Decimal scale factor (D)
20	Number of bits used for each packed value for simple packing, or for each group reference value for complex packing or spatial differencing
21	Type of original field values (see Code table 5.1)

Notes:

- (1) For most templates, details of the packing process are described in Regulation 92.9.4.
- (2) Negative values of E or D shall be represented according to Regulation 92.1.5.

Data representation template 5.1 – Matrix values at grid point – simple packing

<i>Data representation template 5.1</i>	
Octet No.	Contents
12–21	Same as data representation template 5.0
22	0, no matrix bit maps present; 1–matrix bit maps present
23–26	Number of data values encoded in Section 7
27–28	NR – first dimension (rows) of each matrix
29–30	NC – second dimension (columns) of each matrix
31	First dimension coordinate value definition (Code table 5.2)
32	NC1 – number of coefficients or values used to specify first dimension coordinate function
33	Second dimension coordinate value definition (Code table 5.2)
34	NC2 – number of coefficients or values used to specify second dimension coordinate function
35	First dimension physical significance (Code table 5.3)
36	Second dimension physical significance (Code table 5.3)
37–(36+NC1x4)	Coefficients to define first dimension coordinate values in functional form, or the explicit coordinate values (IEEE 32-bit floating-point value)
(37+NC1x4)–(36+4(NC1+NC2))	Coefficients to define second dimension coordinate values in functional form, or the explicit coordinate values (IEEE 32-bit floating-point value)

Notes:

- (1) This form of representation enables a matrix of values to be depicted at each grid point; the two dimensions of the matrix may represent coordinates expressed in terms of two elemental parameters (e.g. direction and frequency for wave spectra). The numeric values of these coordinates, beyond that of simple subscripts, can be given in a functional form, or as a collection of explicit numbers.
- (2) Some simple coordinate functional forms are tabulated in Code table 5.2. Where a more complex coordinate function applies, the coordinate values shall be explicitly denoted by the inclusion of the actual set of values rather than the coefficients. This shall be indicated by a code figure 0 from Code table 5.2; the number of explicit values coded shall be equal to the appropriate dimension of the matrix for which values are presented and they shall follow octet 36 in place of the coefficients.

- (3) Matrix bit maps will be present only if indicated by octet 22. If present, there shall be one bit map for each grid point with data values, as defined by the primary bit map in Section 6, each of length (NR x NC) bits: a bit set to 1 will indicate a data element at the corresponding location within the matrix. Bit maps shall be represented end-to-end, without regard for octet boundaries; the last bit map shall, if necessary, be followed by bits set to zero to fill any partially used octet.
- (4) Matrices restricted to scanning in the +i direction (left to right) and in the -j direction (top to bottom).
- (5) For most templates, details of the packing process are described in Regulation 92.9.4.
- (6) This template was not validated at the time of publication and should be used with caution. Please report any use to WMO Secretariat to assist with validation.

Data representation template 5.2 – Grid point data – complex packing

<i>Data representation template 5.2</i>	
Octet No.	Contents
12–21	Same as data representation template 5.0
22	Group splitting method used (see Code table 5.4)
23	Missing value management used (see Code table 5.5)
24–27	Primary missing value substitute
28–31	Secondary missing value substitute
32–35	NG – number of groups of data values into which field is split
36	Reference for group widths (see Note 12)
37	Number of bits used for the group widths (after the reference value in octet 36 has been removed)
38–41	Reference for group lengths (see Note 13)
42	Length increment for the group lengths (see Note 14)
43–46	True length of last group
47	Number of bits used for the scaled group lengths (after subtraction of the reference value given in octets 38–41 and division by the length increment given in octet 42)

Notes:

- (1) Group lengths have no meaning for row by row packing, where groups are coordinate lines (so the grid description section and possibly the bit-map section are enough); for consistency, associated field width and reference should then be encoded as 0.
- (2) For row by row packing with a bit-map, there should always be as many groups as rows. In case of rows with only missing values, all associated descriptors should be coded as zero.
- (3) Management of widths into a reference and increments, together with management of lengths as scaled incremental values, are intended to save descriptor size (which is an issue as far as compression gains are concerned).
- (4) Management of explicitly missing values is an alternative to bit-map use within Section 6; it is intended to reduce the whole GRIB message size.
- (5) There may be two types of missing value(s), such as to make a distinction between static misses (for instance, due to a land/sea mask) and occasional misses.
- (6) As an extra option, substitute value(s) for missing data may be specified. If not wished (or not applicable), all bits should be set to 1 for relevant substitute value(s).
- (7) If substitute value(s) are specified, type of content should be consistent with original field values (floating-point - and then IEEE 32-bit encoded-, or integer).
- (8) If primary missing values are used, such values are encoded within appropriate group with all bits set to 1 at packed data level.
- (9) If secondary missing values are used, such values are encoded within appropriate group with all bits set to 1, except the last one set to 0, at packed data level.

- (10) A group containing only missing values (of either type) will be encoded as a constant group (null width, no associated data) and the group reference will have all bits set to 1 for primary type, and all bits set to 1, except the last bit set to 0, for secondary type.
- (11) If necessary, group widths and/or field width of group references may be enlarged to avoid ambiguities between missing value indicator(s) and true data.
- (12) The group width is the number of bits used for every value in a group.
- (13) The group length (L) is the number of values in a group.
- (14) The essence of the complex packing method is to subdivide a field of values into NG groups, where the values in each group have similar sizes. In this procedure, it is necessary to retain enough information to recover the group lengths upon decoding. The NG group lengths for any given field can be described by $L_n = \text{ref} + K_n \times \text{len_inc}$, $n = 1, \text{NG}$, where ref is given by octets 38–41 and len_inc by octet 42. The NG values of K (the scaled group lengths) are stored in the data section, each with the number of bits specified by octet 47. Since the last group is a special case which may not be able to be specified by this relationship, the length of the last group is stored in octets 43–46.
- (15) See data template 7.2 and associated Notes for complementary information.
- (16) For most templates, details of the packing process are described in Regulation 92.9.4.

Data representation template 5.3 – Grid point data – complex packing and spatial differencing

<i>Data representation template 5.3</i>		
Octet No.	Contents	
12–47	Same as data representation template 5.2	
48	Order of spatial differencing (see Code table 5.6)	
49	Number of octets required in the data section to specify extra descriptors needed for spatial differencing (octets 6–ww in data template 7.3)	

Notes:

- (1) Spatial differencing is a pre-processing before group splitting at encoding time. It is intended to reduce the size of sufficiently smooth fields, when combined with a splitting scheme as described in data representation template 5.2. At order 1, an initial field of values f is replaced by a new field of values g , where $g_1 = f_1$, $g_2 = f_2 - f_1$, ..., $g_n = f_n - f_{n-1}$. At order 2, the field of values g is itself replaced by a new field of values h , where $h_1 = f_1$, $h_2 = f_2$, $h_3 = g_3 - g_2$, ..., $h_n = g_n - g_{n-1}$. To keep values positive, the overall minimum of the resulting field (either g_{\min} or h_y) is removed. At decoding time, after bit string unpacking, the original scaled values are recovered by adding the overall minimum and summing up recursively.
- (2) For differencing of order n , the first n values in the array that are not missing are set to zero in the packed array. These dummy values are not used in unpacking.
- (3) See data template 7.3 and associated Notes for complementary information.
- (4) For most templates, details of the packing process are described in Regulation 92.9.4.

Data representation template 5.4 – Grid point data – IEEE floating point data

<i>Data representation template 5.4</i>		
Octet No.	Contents	
12	Precision (see Code table 5.7)	

Data representation template 5.40 – Grid point data – JPEG 2000 code stream format

<i>Data representation template 5.40</i>	
Octet No.	Contents
12–15	Reference value (R) (IEEE 32-bit floating-point value)
16–17	Binary scale factor (E)
18–19	Decimal scale factor (D)
20	Number of bits required to hold the resulting scaled and referenced data values (i.e. depth of the greyscale image) (see Note 2)
21	Type of original field values (see Code table 5.1)
22	Type of compression used (see Code table 5.40)
23	Target compression ratio, M:1 (with respect to the bit-depth specified in octet 20), when octet 22 indicates lossy compression. Otherwise, set to missing (see Note 3)

Notes:

- (1) The purpose of this template is to scale the grid point data to obtain the desired precision, if appropriate, and then subtract out the reference value from the scaled field as is done using data representation template 5.0. After this, the resulting grid point field can be treated as a greyscale image and is then encoded into the JPEG 2000 code stream format. To unpack the data field, the JPEG 2000 code stream is decoded back into an image, and the original field is obtained from the image data as described in Regulation 92.9.4, Note 4.
- (2) The JPEG 2000 standard specifies that the bit-depth must be in the range of 1 to 38 bits.
- (3) The compression ratio M:1 (e.g. 20:1) specifies that the encoded stream should be less than $((1/M) \times \text{depth} \times \text{number of data points})$ bits, where depth is specified in octet 20 and the number of data points in octets 6–9 of the data representation section.
- (4) The order of the data points should remain as specified in the scanning mode flags (Flag table 3.4) set in the appropriate grid definition template, even though the JPEG 2000 standard specifies that an image is stored starting at the top left corner. Assuming that the encoding software is expecting the image data in raster order (left to right across rows for each row), users should set the image width to N_i (or N_x) and the height to N_j (or N_y) if bit 3 of the scanning mode flag equals 0 (adjacent points in i (x) order), when encoding the "image". If bit 3 of the scanning mode flags equals 1 (adjacent points in j (y) order), it may be advantageous to set the image width to N_j (or N_y) and the height to N_i (or N_x).
- (5) This template should not be used when the data points are not available on a rectangular grid, such as occurs if some data points are bit-mapped out or if section 3 describes a quasi-regular grid. If it is necessary to use this template on such a grid, the data field can be treated as a one-dimensional image where the height is set to 1 and the width is set to the total number of data points specified in octets 6–9.
- (6) Negative values of E or D shall be represented according to Regulation 92.1.5.
- (7) JPEG 2000 should not be used for bit-mapped or quasi-regular grid data.
- (8) For most templates, details of the packing process are described in Regulation 92.9.4.

Data representation template 5.41 – Grid point data – Portable Network Graphics (PNG) format

<i>Data representation template 5.41</i>	
Octet No.	Contents
12–15	Reference value (R) (IEEE 32-bit floating-point value)
16–17	Binary scale factor (E)
18–19	Decimal scale factor (D)
20	Number of bits required to hold the resulting scaled and referenced data values (i.e. depth of the image) (see Note 2)
21	Type of original field values (see Code table 5.1)

Notes:

- (1) The purpose of this template is to scale the grid point data to obtain the desired precision, if appropriate, and then subtract out the reference value from the scaled field, as is done using data representation template 5.0. After this, the resulting grid point field can be treated as an image and is then encoded into PNG format. To unpack the data field, the PNG stream is decoded back into an image, and the original field is obtained from the image data as described in Regulation 92.9.4, Note 4.
- (2) PNG does not support all bit-depths in an image, so it is necessary to define which depths can be used and how they are to be treated. For greyscale images, PNG supports depths of 1, 2, 4, 8 or 16 bits. Red-Green-Blue (RGB) colour images can have depths of 8 or 16 bits with an optional alpha sample. Valid values for octet 20 can be:
 - 1, 2, 4, 8, or 16 : Treat as greyscale image
 - 24 : Treat as RGB colour image (each component having 8-bit depth)
 - 32 : Treat as RGB w/ alpha sample colour image (each component having 8-bit depth)
- (3) The order of the data points should remain as specified in the scanning mode flags (Flag table 3.4) set in the appropriate grid definition template, even though the PNG standard specifies that an image is stored starting at the top left corner and scans each row from left to right, starting with the top row. Users should set the image width to N_i (or N_x) and the height to N_j (or N_y) if bit 3 of the scanning mode flag equals 0 (adjacent points in i (x) order), when encoding the "image". If bit 3 of the scanning mode flags equals 1 (adjacent points in j (y) order), it may be advantageous to set the image width to N_j (or N_y) and the height to N_i (or N_x).
- (4) This template should not be used when the data points are not available on a rectangular grid, such as occurs if some data points are bit-mapped out or if section 3 describes a quasi-regular grid. If it is necessary to use this template on such a grid, the data field can be treated as a one-dimensional image where the height is set to 1 and the width is set to the total number of data points specified in octets 6–9.
- (5) Negative values of E or D shall be represented according to Regulation 92.1.5.
- (6) For most templates, details of the packing process are described in Regulation 92.9.4.

Data representation template 5.42 – Grid point data – CCSDS recommended lossless compression

<i>Data representation template 5.42</i>	
Octet No.	Contents
12–15	Reference value (R) (IEEE 32-bit floating-point value)
16–17	Binary scale factor (E)
18–19	Decimal scale factor (D)
20	Number of bits required to hold the resulting scaled and referenced data values (see Note 1)
21	Type of original field values (see Code table 5.1)
22	CCSDS compression options mask (see Note 3)
23	Block size
24–25	Reference sample interval

Notes:

- (1) The intent of this template is to scale the grid point data to obtain the desired precision, if appropriate, and then subtract the reference value from the scaled field, as is done using data representation template 5.0. After this, the resulting grid point field can be treated as a greyscale image and encoded into the CCSDS recommended standard for lossless data compression code stream format. To unpack the data field, the CCSDS recommended standard for lossless data compression code stream is decoded back into an image, and the original field is obtained from the image data as described in regulation 92.9.4, Note 4.
- (2) The Consultative Committee for Space Data Systems (CCSDS) recommended standard for lossless data compression is the standard used by space agencies for the compression of scientific data transmitted from satellites and other space instruments. CCSDS recommended standard for lossless data compression is a very fast predictive compression algorithm based on the extended-Rice algorithm. It uses Golomb–Rice codes for entropy coding. The sequence of prediction errors is divided into blocks. Each block is compressed using a two-pass algorithm. In the first pass, the best coding method for the whole block is determined. In the second pass, the output of the marker of the selected coding method is encoded as ancillary information along with prediction errors.
The coding methods include:
 - Golomb–Rice codes of a chosen rank
 - Unary code for transformed pairs of prediction errors
 - Fixed-length natural binary code if the block is found to be incompressible
 - Signalling to the decoder empty block if all prediction errors are zeroes
- (3) Library flags governing data type, and storage and processing parameters. For further information, see Rosenhauer, Mathis. "Flags." libaec – Adaptive Entropy Coding library. German Climate Computing Centre (Deutsches Klimarechenzentrum, DKRZ), 12 May 2016. Web. 13 June 2016. <<http://gitlab.dkrz.de/k202009/libaec/blob/v0.3.3/README.md#flags>>.
- (4) For most templates, details of the packing process are described in regulation 92.9.4. This template is only valid for the Consultative Committee for Space Data Systems Recommendation for Space Data System Standards, Lossless Data Compression, CCSDS 121.0-B-2, Blue Book, May 2012.

Data representation template 5.50 – Spectral data – simple packing

<i>Data representation template 5.50</i>	
Octet No.	Contents
12–15	Reference value (R) (IEEE 32-bit floating-point value)
16–17	Binary scale factor (E)
18–19	Decimal scale factor (D)
20	Number of bits used for each packed value (field width)
21–24	Real part of (0.0) coefficient (IEEE 32-bit floating-point value)
12–15	Reference value (R) (IEEE 32-bit floating-point value)

Notes:

- (1) Removal of the real part of (0.0) coefficient from packed data is intended to reduce the variability of the coefficients, in order to improve packing accuracy.
- (2) For some spectral representations, the (0.0) coefficient represents the mean value of the parameter represented.
- (3) Negative values of E or D shall be represented according to Regulation 92.1.5.
- (4) For most templates, details of the packing process are described in Regulation 92.9.4.

Data representation template 5.51 – Spherical harmonics data – complex packing

<i>Data representation template 5.51</i>	
Octet No.	Contents
12–20	Same as data representation template 5.50
21–24	P – Laplacian scaling factor (expressed in 10^{-6} units)
25–26	J_S – pentagonal resolution parameter of the unpacked subset (see Note 1)
27–28	K_S – pentagonal resolution parameter of the unpacked subset (see Note 1)
29–30	M_S – pentagonal resolution parameter of the unpacked subset (see Note 1)
31–34	T_S – total number of values in the unpacked subset (see Note 1)
35	Precision of the unpacked subset (see Code table 5.7)

Notes:

- (1) The unpacked subset is a set of values defined in the same way as the full set of values (on a spectrum limited to J_S , K_S and M_S), but on which scaling and packing are not applied. Associated values are stored in octets 6 onwards of Section 7.
- (2) The remaining coefficients are multiplied by $(n \times (n+1))^P$, scaled and packed. The operator associated with this multiplication is derived from the Laplacian operator on the sphere.
- (3) The retrieval formula for a coefficient of wave number n is then:

$$Y = (R + X \times 2^E) \times 10^{-D} \times (n \times (n+1))^{-P}$$
 where X is the packed scaled value associated with the coefficient.
- (4) For most templates, details of the packing process are described in Regulation 92.9.4.

Data representation template 5.53 – spectral data for limited area models – complex packing

Data representation template 5.53	
Octet No.	Contents
12–15	Reference value (R) (IEEE 32-bit floating-point value)
16–17	Binary scale factor (E)
18–19	Decimal scale factor (D)
20	Number of bits used for each packed value (field width)
21	Type of bi-Fourier subtruncation (see Code table 5.25)
22	Packing mode for axes (see Code table 5.26)
23–26	P – Laplacian scaling factor (expressed in 10^{-6} units)
27–28	N_S – bi-Fourier resolution parameter of the unpacked subset (see Note 1)
29–30	M_S – bi-Fourier resolution parameter of the unpacked subset (see Note 1)
31–34	T_S – total number of values in the unpacked subset (see Note 1)
35	Precision of the unpacked subset (see Code table 5.7)

Notes:

- (1) The unpacked subset is a set of values defined in the same way as the full set of values (on a spectrum limited to N_S and M_S), but on which scaling and packing are not applied. Associated values are stored in octets 6 onwards of Section 7.
- (2) The remaining coefficients are multiplied by $(n^2+m^2)^P$, scaled and packed. The operator associated with this multiplication is derived from the Laplacian operator.
- (3) The retrieval formula for a coefficient of wave number n is then: $Y = (R + X \times 2^E) \times 10^{-D} \times (m^2+n^2)^{-P}$ where X is the packed scaled value associated with the coefficient.

Data representation template 5.61 – Grid point data – simple packing with logarithm pre-processing

Data representation template 5.61	
Octet No.	Contents
12–15	Reference value (R) (IEEE 32-bit floating-point value)
16–17	Binary scale factor (E)
18–19	Decimal scale factor (D)
20	Number of bits used for each packed value
21–24	Pre-processing parameter (B) (IEEE 32-bit floating-point value)

Notes:

- (1) This template is appropriately designed for data sets with all non-negative values and a wide variability range (more than 5 orders of magnitude). It must not be used for data sets with negative values or smaller variability range.
- (2) A logarithm pre-processing algorithm is used to fit the variability range into one or two order of magnitudes before using the simple packing algorithm. It requires a parameter (B) to assure that all values passed to the logarithm function are positive. Thus scaled values are $Z = \ln(Y+B)$, where Y are the original values, \ln is the natural logarithm (or Napierian) function and B is chosen so that $Y+B > 0$.
- (3) Best practice follows for choosing the B pre-processing parameter.
 - (a) If the data set minimum value is positive, B can be safely put to zero.
 - (b) If the data set minimum is zero, all values must be scaled to become greater than zero and B can be equal to the minimum positive value in the data set.
- (4) Data shall be packed using data template 7.
- (5) This template is experimental, was not validated at the time of publication and should be used only for bilateral previously agreed tests.

Data representation template 5.200 – Grid point data – run length packing with level values

<i>Data representation template 5.200</i>	
Octet No.	Contents
12	Number of bits used for each packed value in the run length packing with level value
13–14	MV – maximum value within the levels that are used in the packing
15–16	MVL – maximum value of level (predefined)
17	Decimal scale factor of representative value of each level
18–(19+2(lv–1))	List of MVL scaled representative values of each level from lv = 1 to MVL

Provisional Copy
2023

TEMPLATE DEFINITIONS USED IN SECTION 7***Data template 7.0 – Grid point data – simple packing***

<i>Data template 7.0</i>	
Octet No.	Contents
6–nn	Binary data values – binary string, with each (scaled) data value

Note: For most templates, details of the packing process are described in Regulation 92.9.4.

Data template 7.1 – Matrix values at grid point – simple packing

<i>Data template 7.1</i>	
Octet No.	Contents
6–nn	Binary data values – binary string, with each (scaled) data value

Notes:

- (1) This template was not validated at the time of publication and should be used with caution. Please report any use to WMO Secretariat to assist with validation.
- (2) For most templates, details of the packing process are described in Regulation 92.9.4.
- (3) Group descriptors mentioned above may not be physically present; if associated field width is 0.

Data template 7.2 – Grid point data – complex packing

<i>Data template 7.2</i>	
Octet No.	Contents
6–xx	NG group reference values (X1 in the decoding formula), each of which is encoded using the number of bits specified in octet 20 of data representation template 5.0. Bits set to zero shall be appended as necessary to ensure this sequence of numbers ends on an octet boundary
[xx+1]–yy	NG group widths, each of which is encoded using the number of bits specified in octet 37 of data representation template 5.2. Bits set to zero shall be appended as necessary to ensure this sequence of numbers ends on an octet boundary
[yy+1]–zz	NG scaled group lengths, each of which is encoded using the number of bits specified in octet 47 of data representation template 5.2. Bits set to zero shall be appended as necessary to ensure this sequence of numbers ends on an octet boundary (see Note 5)
[zz+1]–nn	Packed values (X2 in the decoding formula), where each value is a deviation from its respective group reference value

Notes:

- (1) Group descriptors mentioned above may not be physically present; if associated field width is 0.
- (2) Group lengths have no meaning for row by row packing; for consistency, associated field width should then be encoded as 0. So no specific test for row by row case is mandatory at decoding software level to handle encoding/decoding of group descriptors.
- (3) Scaled group lengths, if present, are encoded for each group. But the true last group length (unscaled) should be taken from data representation template.
- (4) For groups with a constant value, associated field width is 0, and no incremental data are physically present.

- (5) The essence of the complex packing method is to subdivide a field of values into NG groups, where the values in each group have similar sizes. In this procedure, it is necessary to retain enough information to recover the group lengths upon decoding. The NG group lengths for any given field can be described by $L_n = \text{ref} + K_n \times \text{len_inc}$, $n = 1, \text{NG}$, where ref is given by octets 38–41 and len_inc by octet 42. The NG values of K (the scaled group lengths) are stored in the data section, each with the number of bits specified by octet 47. Since the last group is a special case which may not be able to be specified by this relationship, the length of the last group is stored in octets 43–46.
- (6) For most templates, details of the packing process are described in Regulation 92.9.4.

Data template 7.3 – Grid point data – complex packing and spatial differencing

<i>Data template 7.3</i>	
Octet No.	Contents
6–ww	First value(s) of original (undifferenced) scaled data values, followed by the overall minimum of the differences. The number of values stored is 1 greater than the order of differentiation, and the field width is described at octet 49 of data representation template 5.3 (see Note 1)
[ww+1]–xx	NG group reference values (X_1 in the decoding formula), each of which is encoded using the number of bits specified in octet 20 of data representation template 5.0. Bits set to zero shall be appended where necessary to ensure this sequence of numbers ends on an octet boundary
[xx+1]–nn	Same as for data representation template 7.2

Notes:

- (1) Referring to the notation in Note 1 of data representation template 5.3, at order 1, the values stored in octets 6–ww are g_1 and g_{\min} . At order 2, the values stored are h_1 , h_2 , and h_{\min} .
- (2) Extra descriptors related to spatial differencing are added before the splitting descriptors, to reflect the separation between the two approaches. It enables to share software parts between cases with and without spatial differencing.
- (3) The position of overall minimum after initial data values is a choice that enables less software management.
- (4) Overall minimum will be negative in most cases. First bit should indicate the sign: 0 if positive, 1 if negative.
- (5) For most templates, details of the packing process are described in Regulation 92.9.4.

Data template 7.4 – Grid point data – IEEE floating point data

<i>Data template 7.4</i>	
Octet No.	Contents
6–nn	Binary data values

Data template 7.40 – Grid point data – JPEG 2000 code stream format

<i>Data template 7.40</i>	
Octet No.	Contents
6–nn	JPEG 2000 code stream as described in Part 1 of the JPEG 2000 standard (ISO/IEC 15444-1:2000)

Notes:

- (1) For simplicity, image data should be packed specifying a single component (i.e. greyscale image) instead of a multicomponent colour image.
- (2) For most templates, details of the packing process are described in Regulation 92.9.4.

Data template 7.41 – Grid point data – Portable Network Graphics (PNG) format

Data template 7.41	
Octet No.	Contents
6–nn	PNG encoded image

Notes:

- (1) If octet 20 of data representation template 5.41 specifies the data are packed into either 1, 2, 4, 8, or 16 bits, then encode the "image" as a greyscale image. If octet 20 specifies 24 bits, encode the "image" as a Red-Green-Blue (RGB) colour image with 8-bit depth for each colour component, and finally if octet 20 is 32, encode the "image" as an RGB colour image with an alpha sample using 8-bit depth for each of the four components.
- (2) For most templates, details of the packing process are described in Regulation 92.9.4.

Data template 7.42 – Grid point data – CCSDS recommended lossless compression

Data template 7.42	
Octet No.	Contents
6–nn	CCSDS recommended standard for lossless data compression code stream

Data template 7.50 – Spectral data – simple packing

Data template 7.50	
Octet No.	Contents
6–nn	Binary data values – binary string, with each (scaled) data value

Note: For most templates, details of the packing process are described in Regulation 92.9.4.

Data template 7.51 – Spherical harmonics – complex packing

Data template 7.51	
Octet No.	Contents
6–(5+IxTS)	Data values from the unpacked subset (IEEE floating-point values on I octets)
(6+IxTS)–nn	Binary data values – binary string, with each (scaled) data value out of the unpacked subse

Notes:

- (1) Values ordering within the unpacked subset is defined according to the source of grid definition associated with the data.
- (2) Number of octets associated with each value of the unpacked subset (I) is defined in Code table 5.7, according to the actual value in octet 35 of data representation template 5.51.
- (3) Values ordering within the packed data is done according to the source of grid definition, skipping the values processed in the unpacked subset.
- (4) For most templates, details of the packing process are described in Regulation 92.9.4.

Data template 7.53 – spectral data for limited area models – complex packing

<i>Data template 7.53</i>	
Octet No.	Contents
6–(5+IxTS)	Data values from the unpacked subset (IEEE floating-point values on I octets)
(6+IxTS)–nn	Binary data values – binary string, with each (scaled) data value out of the unpacked subset

Provisional Copy
2023

CODE TABLE USED IN SECTION 0***Code table 0.0 – Discipline of processed data in the GRIB message, number of GRIB Master table***

<i>Code table 0.0</i>	
Code figure	Meaning
0	Meteorological products
1	Hydrological products
2	Land surface products
3	Satellite remote sensing products (formerly "Space products")
4	Space weather products
5–9	Reserved
10	Oceanographic products
11–191	Reserved
192–254	Reserved for local use
255	Missing

Provisional Copy
2023

CODE TABLES USED IN SECTION 1**Code table 1.0 – GRIB master tables version number**

Code table 1.0	
Code figure	Meaning
0	Experimental
1	Version implemented on 7 November 2001
2	Version implemented on 4 November 2003
3	Version implemented on 2 November 2005
4	Version implemented on 7 November 2007
5	Version implemented on 4 November 2009
6	Version implemented on 15 September 2010
7	Version implemented on 4 May 2011
8	Version implemented on 2 November 2011
9	Version implemented on 2 May 2012
10	Version implemented on 7 November 2012
11	Version implemented on 8 May 2013
12	Version implemented on 14 November 2013
13	Version implemented on 7 May 2014
14	Version implemented on 5 November 2014
15	Version implemented on 6 May 2015
16	Version implemented on 11 November 2015
17	Version implemented on 4 May 2016
18	Version implemented on 2 November 2016
19	Version implemented on 3 May 2017
20	Version implemented on 8 November 2017
21	Version implemented on 2 May 2018
22	Version implemented on 7 November 2018
23	Pre-operational to be implemented by next amendment
24–254	Future versions (see Note)
255	Missing

Note: This code table is deprecated. See Common Code table C-0 instead.

Code table 1.1 – GRIB local tables version number

Code table 1.1	
Code figure	Meaning
0	Local tables not used. Only table entries and templates from the current master table are valid
1–254	Number of local tables version used
255	Missing

Code table 1.2 – Significance of reference time

Code table 1.2	
Code figure	Meaning
0	Analysis
1	Start of forecast
2	Verifying time of forecast
3	Observation time
4	Local time
5–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 1.3 – Production status of data

Code table 1.3	
Code figure	Meaning
0	Operational products
1	Operational test products
2	Research products
3	Re-analysis products
4	THORPEX Interactive Grand Global Ensemble (TIGGE)
5	THORPEX Interactive Grand Global Ensemble (TIGGE) test
6	S2S operational products
7	S2S test products
8	Uncertainties in Ensembles of Regional ReAnalyses project (UERRA)
9	Uncertainties in Ensembles of Regional ReAnalyses project (UERRA) test
10	Copernicus regional reanalysis
11	Copernicus regional reanalysis test
12–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 1.4 – Type of data

Code table 1.4	
Code figure	Meaning
0	Analysis products
1	Forecast products
2	Analysis and forecast products
3	Control forecast products
4	Perturbed forecast products
5	Control and perturbed forecast products
6	Processed satellite observations
7	Processed radar observations
8	Event probability
9–191	Reserved
192–254	Reserved for local use
255	Missing

Note: An initialized analysis is considered a zero-hour forecast.

Code table 1.5 – Identification template number

Code table 1.5	
Code figure	Meaning
0	Calendar definition
1	Paleontological offset
2	Calendar definition and paleontological offset
3–32767	Reserved
32768–65534	Reserved for local use
65535	Missing

Code table 1.6 – Type of calendar

Code table 1.6	
Code figure	Meaning
0	Gregorian
1	360-day
2	365-day (see Note 1)
3	Proleptic Gregorian (see Note 2)
4–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

(1) Essentially a non-leap year.

(2) Extends the Gregorian calendar indefinitely in the past.

CODE AND FLAG TABLES USED IN SECTION 3**Code table 3.0 – Source of grid definition**

Code table 3.0	
Code figure	Meaning
0	Specified in Code table 3.1
1	Predetermined grid definition (see Note)
2–191	Reserved
192–254	Reserved for local use
255	A grid definition does not apply to this product

Note: Defined by originating centre.

Code table 3.1 – Grid definition template number

Code table 3.1	
Code figure	Meaning
0	Latitude/longitude (see Note 1)
1	Rotated latitude/longitude
2	Stretched latitude/longitude
3	Stretched and rotated latitude/longitude
4	Variable resolution latitude/longitude
5	Variable resolution rotated latitude/longitude
6–9	Reserved
10	Mercator
11	Reserved
12	Transverse Mercator
13	Mercator with modelling subdomains definition
14–19	Reserved
20	Polar stereographic projection (see Note 2)
21–22	Reserved
23	Polar stereographic with modelling subdomains definition
24–29	Reserved
30	Lambert conformal (see Note 3)
31	Albers equal area
32	Reserved
33	Lambert conformal with modelling subdomains definition
34–39	Reserved
40	Gaussian latitude/longitude
41	Rotated Gaussian latitude/longitude
42	Stretched Gaussian latitude/longitude
43	Stretched and rotated Gaussian latitude/longitude
44–49	Reserved
50	Spherical harmonic coefficients
51	Rotated spherical harmonic coefficients
52	Stretched spherical harmonic coefficients
53	Stretched and rotated spherical harmonic coefficients
54–60	Reserved
61	Spectral Mercator with modelling subdomains definition

Code table 3.1

Code figure	Meaning
62	Spectral polar stereographic with modelling subdomains definition
63	Spectral Lambert conformal with modelling subdomains definition
64–89	Reserved
90	Space view perspective or orthographic
91–99	Reserved
100	Triangular grid based on an icosahedron
101	General unstructured grid
102–109	Reserved
110	Equatorial azimuthal equidistant projection
111–119	Reserved
120	Azimuth-range projection
121–139	Reserved
140	Lambert azimuthal equal area projection
141–999	Reserved
1000	Cross-section grid with points equally spaced on the horizontal
1001–1099	Reserved
1100	Hovmöller diagram grid with points equally spaced on the horizontal
1101–1199	Reserved
1200	Time section grid
1201–32767	Reserved
32768–65534	Reserved for local use
65535	Missing

Notes:

- (1) Also called equidistant cylindrical or Plate Carrée.
- (2) Polar stereographic projection can be south or north.
- (3) Lambert conformal can be secant, tangent, conical or bipolar.

Code table 3.2 – Shape of the reference system

Code table 3.2

Code figure	Meaning
0	Earth assumed spherical with radius = 6 367 470.0 m (see Note 2)
1	Earth assumed spherical with radius specified (in m) by data producer (see Note 2)
2	Earth assumed oblate spheroid with size as determined by IAU in 1965 (major axis = 6 378 160.0 m, minor axis = 6 356 775.0 m, $f = 1/297.0$)
3	Earth assumed oblate spheroid with major and minor axes specified (in km) by data producer (see Note 2)
4	Earth assumed oblate spheroid as defined in IAG-GRS80 model (major axis = 6 378 137.0 m, minor axis = 6 356 752.314 m, $f = 1/298.257\ 222\ 101$)
5	Earth assumed represented by WGS-84 (as used by ICAO since 1998) (see Note 1)
6	Earth assumed spherical with radius of 6 371 229.0 m (see Note 2)
7	Earth assumed oblate spheroid with major or minor axes specified (in m) by data producer (see Note 2)
8	Earth model assumed spherical with radius of 6 371 200 m, but the horizontal datum of the resulting latitude/longitude field is the WGS-84 reference frame

Code table 3.2

Code figure	Meaning
9	Earth represented by the Ordnance Survey Great Britain 1936 Datum, using the Airy 1830 Spheroid, the Greenwich meridian as 0 longitude, and the Newlyn datum as mean sea level, 0 height
10	Earth model assumed WGS84 with corrected geomagnetic coordinates (latitude and longitude) defined by Gustafsson et al., 1992 (see Note 1)
11	Sun assumed spherical with radius = 695 990 000 m (Allen, C.W., Astrophysical Quantities, 3rd ed.; Athlone: London, 1976) and Stonyhurst latitude and longitude system with origin at the intersection of the solar central meridian (as seen from Earth) and the solar equator (Thompson, W., Coordinate systems for solar image data, Astron. Astrophys. 2006, 449, 791–803)
12–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

- (1) WGS-84 is a geodetic system that uses IAG-GRS80 as a basis.
- (2) With respect to code figures 0, 1, 3, 6 and 7, coordinates can only be unambiguously interpreted, if the coordinate reference system in which they are embedded is known. Therefore, defining the shape of the Earth alone without coordinate system axis origins is ambiguous. Generally, the prime meridian defined in the geodetic system WGS-84 can be safely assumed to be the longitudinal origin. However, because these code figures do not specify the longitudinal origin explicitly, it is suggested to contact the originating centre if high precision coordinates are needed, in order to obtain the precise details of the coordinate system used (effective as from 16 November 2016).

Flag table 3.3 – Resolution and component flags

Flag table 3.3

Bit No.	Value	Meaning
1–2		Reserved
3	0	i direction increments not given
	1	i direction increments given
4	0	j direction increments not given
	1	j direction increments given
5	0	Resolved u- and v- components of vector quantities relative to easterly and northerly directions
	1	Resolved u- and v- components of vector quantities relative to the defined grid in the direction of increasing x and y (or i and j) coordinates, respectively
6–8		Reserved – set to zero

Flag table 3.4 – Scanning mode

Flag table 3.4		
Bit No.	Value	Meaning
1	0	Points of first row or column scan in the +i (+x) direction
	1	Points of first row or column scan in the -i (-x) direction
2	0	Points of first row or column scan in the -j (-y) direction
	1	Points of first row or column scan in the +j (+y) direction
3	0	Adjacent points in i (x) direction are consecutive
	1	Adjacent points in j (y) direction is consecutive
4	0	All rows scan in the same direction
	1	Adjacent rows scans in the opposite direction
5	0	Points within odd rows are not offset in i (x) direction
	1	Points within odd rows are offset by $D_i/2$ in i (x) direction
6	0	Points within even rows are not offset in i (x) direction
	1	Points within even rows are offset by $D_i/2$ in i (x) direction
7	0	Points are not offset in j (y) direction
	1	Points are offset by $D_j/2$ in j (y) direction
8	0	Rows have N_i grid points and columns have N_j grid points
	1	Rows have N_i grid points if points are not offset in i direction
		Rows have N_i-1 grid points if points are offset by $D_i/2$ in i direction
		Columns have N_j grid points if points are not offset in j direction
		Columns have N_j-1 grid points if points are offset by $D_j/2$ in j direction

Notes:

- (1) i direction: west to east along a parallel or left to right along an x-axis.
- (2) j direction: south to north along a meridian, or bottom to top along a y-axis.
- (3) If bit number 4 is set, the first row scan is as defined by previous flags.
- (4) La1 and Lo1 define the first row, which is an odd row.
- (5) D_i and D_j are assumed to be positive, with the direction of i and j being given by bits 1 and 2.
- (6) Bits 5 through 8 may be used to generate staggered grids, such as Arakawa grids (see Part B, GRIB Attachment II).
- (7) If any of bits 5, 6, 7 or 8 are set, D_i and D_j are not optional.

Flag table 3.5 – Projection centre

Flag table 3.5		
Bit No.	Value	Meaning
1	0	North Pole is on the projection plane
	1	South Pole is on the projection plane
2	0	Only one projection centre is used
	1	Projection is bipolar and symmetric

Code table 3.6 – Spectral data representation type

Code table 3.6	
Code figure	Meaning
1	<p>The associated Legendre functions of the first kind are defined by:</p> $P_n^m(\mu) = \sqrt{(2n+1) \frac{(n-m)!}{(n+m)!} \frac{1}{2^n n!}} (1-\mu^2)^{m/2} \frac{d^{n+m}}{d\mu^{n+m}} (\mu^2-1)^n, \quad m \geq 0$ $P_n^{-m}(\mu) = P_n^m(\mu)$ <p>A field $F(\lambda, \mu)$ is represented by:</p> $F(\lambda, \mu) = \sum_{m=-M}^M \sum_{n= m }^{N(m)} F_n^m P_n^m(\mu) e^{im\lambda}$ <p>where</p> <ul style="list-style-type: none"> λ is the longitude, μ the sine of latitude, and F_n^{-m} the complex conjugate of F_n^m
2	Bi-Fourier representation

Code table 3.7 – Spectral data representation mode

Code table 3.7	
Code figure	Meaning
0	Reserved
1	The complex numbers F_n^m (see code figure 1 in Code table 3.6) are stored for $m \geq 0$ as pairs of real numbers $\text{Re}(F_n^m)$, $\text{Im}(F_n^m)$ ordered with n increasing from m to $N(m)$, first for $m = 0$ and then for $m = 1, 2, \dots, M$ (see Note)
2–254	Reserved
255	Missing

Note: Values of $N(m)$ for common truncation cases:

Triangular:	$M = J = K,$	$N(m) = J$
Rhomboidal:	$K = J + M,$	$N(m) = J + m$
Trapezoidal:	$K = J, K > M,$	$N(m) = J$

Code table 3.8 – Grid point position

Code table 3.8	
Code figure	Meaning
0	Grid points at triangle vertices
1	Grid points at centres of triangles
2	Grid points at midpoints of triangle sides
3–191	Reserved
192–254	Reserved for local use
255	Missing

Flag table 3.9 – Numbering order of diamonds as seen from the corresponding pole

Flag table 3.9		
Bit No.	Value	Meaning
1	0	Clockwise orientation
	1	Anti-clockwise (i.e. counter-clockwise) orientation
2–8		Reserved

Flag table 3.10 – Scanning mode for one diamond

Flag table 3.10		
Bit No.	Value	Meaning
1	0	Points scan in +i direction, i.e. from pole to Equator
	1	Points scan in –i direction, i.e. from Equator to pole
2	0	Points scan in +j direction, i.e. from west to east
	1	Points scan in –j direction, i.e. from east to west
3	0	Adjacent points in i direction are consecutive
	1	Adjacent points in j direction are consecutive
4–8		Reserved

Code table 3.11 – Interpretation of list of numbers at end of section 3

Code table 3.11	
Code figure	Meaning
0	There is no appended list
1	Numbers define number of points corresponding to full coordinate circles (i.e. parallels), coordinate values on each circle are multiple of the circle mesh, and extreme coordinate values given in grid definition (i.e. extreme longitudes) may not be reached in all rows (see Note 1)
2	Numbers define number of points corresponding to coordinate lines delimited by extreme coordinate values given in grid definition (i.e. extreme longitudes) which are present in each row
3	Numbers define the actual latitudes for each row in the grid. The list of numbers are integer values of the valid latitudes in microdegrees (scaled by 10^{-6}) or in unit equal to the ratio of the basic angle and the subdivisions number for each row, in the same order as specified in the "scanning mode flag" (bit no. 2) (see Note 2)
4–254	Reserved
255	Missing

Notes:

- (1) It should be noted that depending on values of extreme (first/last) coordinates, and regardless of bit-map, effective number of points per row may be less than the number of points on the current circle.
- (2) The value for the constant direction increment D_i (or D_x) in the accompanying grid definition template should be set to all ones (missing).

Code table 3.15 – Physical meaning of vertical coordinate

Code table 3.15		
Code figure	Meaning	Unit
0–19	Reserved	
20	Temperature	K
21–99	Reserved	
100	Pressure	Pa
101	Pressure deviation from mean sea level	Pa
102	Altitude above mean sea level	m
103	Height above ground (see Note 1)	m
104	Sigma coordinate	
105	Hybrid coordinate	
106	Depth below land surface	m
107	Potential temperature (theta)	K
108	Pressure deviation from ground to level	Pa
109	Potential vorticity	$\text{K m}^2 \text{ kg}^{-1} \text{ s}^{-1}$
110	Geometrical height	m
111	Eta coordinate (see Note 2)	
112	Geopotential height	gpm
113	Logarithmic hybrid coordinate	
114–159	Reserved	
160	Depth below sea level	m
161–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Negative values associated to this coordinate will indicate depth below ground surface. If values are all below surface, use of entry 106 is recommended, with positive coordinate values instead.
- (2) The Eta vertical coordinate system involves normalizing the pressure at some point on a specific level by the mean sea-level pressure at that point.

Code table 3.20 – Type of horizontal line

Code table 3.20	
Code figure	Meaning
0	Rhumb
1	Great circle
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 3.21 – Vertical dimension coordinate values definition

Code table 3.21	
Code figure	Meaning
0	Explicit coordinate values set
1	Linear coordinates $f(1) = C1$ $f(n) = f(n-1) + C2$
2–10	Reserved
11	Geometric coordinates $f(1) = C1$ $f(n) = C2 \times f(n-1)$
12–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 3.25 – Type of bi-Fourier truncation

Code table 3.25	
Code figure	Meaning
0–76	Reserved
77	Rectangular
78–87	Reserved
88	Elliptic
89–98	Reserved
99	Diamond
100–191	Reserved
192–254	Reserved for local use
255	Missing

CODE TABLES USED IN SECTION 4

Code table 4.0 – Product definition template number

Code table 4.0	
Code figure	Meaning
0	Analysis or forecast at a horizontal level or in a horizontal layer at a point in time
1	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time
2	Derived forecasts based on all ensemble members at a horizontal level or in a horizontal layer at a point in time
3	Derived forecasts based on a cluster of ensemble members over a rectangular area at a horizontal level or in a horizontal layer at a point in time
4	Derived forecasts based on a cluster of ensemble members over a circular area at a horizontal level or in a horizontal layer at a point in time
5	Probability forecasts at a horizontal level or in a horizontal layer at a point in time
6	Percentile forecasts at a horizontal level or in a horizontal layer at a point in time
7	Analysis or forecast error at a horizontal level or in a horizontal layer at a point in time
8	Average, accumulation, extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval
9	Probability forecasts at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval
10	Percentile forecasts at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval
11	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous interval
12	Derived forecasts based on all ensemble members at a horizontal level or in a horizontal layer, in a continuous or non-continuous interval
13	Derived forecasts based on a cluster of ensemble members over a rectangular area, at a horizontal level or in a horizontal layer, in a continuous or non-continuous interval
14	Derived forecasts based on a cluster of ensemble members over a circular area, at a horizontal level or in a horizontal layer, in a continuous or non-continuous interval
15	Average, accumulation, extreme values or other statistically processed values over a spatial area at a horizontal level or in a horizontal layer at a point in time
16–19	Reserved
20	Radar product
21–29	Reserved
30	Satellite product (deprecated)
31	Satellite product
32	Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for simulated (synthetic) satellite data
33	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for simulated (synthetic) satellite data
34	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous interval for simulated (synthetic) satellite data
35–39	Reserved
40	Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents
41	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents

Code table 4.0

Code figure	Meaning
42	Average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents
43	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents
44	Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for aerosol
45	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for aerosol
46	Average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol
47	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol
48	Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for optical properties of aerosol
49	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for optical properties of aerosol
50	Reserved
51	Categorical forecasts at a horizontal level or in a horizontal layer at a point in time
52	Reserved
53	Partitioned parameters at a horizontal level or in a horizontal layer at a point in time
54	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for partitioned parameters
55	Spatio-temporal changing tiles at a horizontal level or horizontal layer at a point in time
56	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for spatio-temporal changing tile parameters (deprecated)
57	Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents based on a distribution function
58	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents based on a distribution function
59	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for spatio-temporal changing tile parameters (corrected version of template 4.56)
60	Individual ensemble reforecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time
61	Individual ensemble reforecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous time interval
62	Average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for spatio-temporal changing tiles at a horizontal level or horizontal layer at a point in time
63	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for spatio-temporal changing tiles
64–66	Reserved
67	Average, accumulation and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents based on a distribution function

Code table 4.0

Code figure	Meaning
68	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents based on a distribution function
69	Reserved
70	Post-processing analysis or forecast at a horizontal level or in a horizontal layer at a point in time
71	Post-processing individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time
72	Post-processing average, accumulation, extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval
73	Post-processing individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous time interval
74–75	Reserved
76	Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents with source or sink
77	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents with source or sink
78	Average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents with source or sink
79	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for atmospheric chemical constituents with source or sink
80	Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for optical properties of aerosol with source or sink
81	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for optical properties of aerosol with source or sink
82	Average, accumulation, and/or extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol with source or sink
83	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol with source or sink
84	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol with source or sink
85	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for aerosol
86	Quantile forecasts at a horizontal level or in a horizontal layer at a point in time
87	Quantile forecasts at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval
88	Analysis or forecast at a horizontal level or in a horizontal layer at a specified local time
89–90	Reserved
91	Categorical forecasts at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval
92	Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a specified local time
93	Post-processing analysis or forecast at a horizontal level or in a horizontal layer at a specified local time

Code table 4.0

Code figure	Meaning
94	Post-processing individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a specified local time
95	Average, accumulation, extreme values or other statistically processed value at a horizontal level or in a horizontal layer at a specified local time
96	Average, accumulation, extreme values or other statistically processed values of an individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a specified local time
97	Average, accumulation, extreme values or other statistically processed values of post-processing analysis or forecast at a horizontal level or in a horizontal layer at a specified local time
98	Average, accumulation, extreme values or other statistically processed values of a post-processing individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a specified local time
<u>99</u>	<u>Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with explicit list of frequencies and directions</u>
<u>100</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with explicit list of frequencies and directions</u>
<u>101</u>	<u>Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with frequencies and directions defined by formulae</u>
<u>102</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with frequencies and directions defined by formulae</u>
<u>103</u>	<u>Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for waves selected by period range</u>
<u>104</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for waves selected by period range</u>
<u>105</u>	<u>Anomalies, significance and other derived products from an analysis or forecast in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval</u>
<u>106</u>	<u>Anomalies, significance and other derived products from an individual ensemble forecast, control and perturbed in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval</u>
<u>107</u>	<u>Anomalies, significance and other derived products from derived forecasts based on all ensemble members in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval</u>
<u>108</u>	<u>Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for generic optical products</u>
<u>109</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for generic optical products</u>
<u>110</u>	<u>Average, accumulation, extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for generic optical products</u>
<u>111</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous interval for generic optical products</u>
<u>112</u>	<u>Anomalies, significance and other derived products as probability forecasts in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval</u>
<u>99</u>	<u>Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with explicit list of frequencies and directions</u>
<u>100</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with explicit list of frequencies and directions</u>
<u>101</u>	<u>Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with frequencies and directions defined by formulae</u>

Code table 4.0

Code figure	Meaning
<u>102</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for wave 2D spectra with frequencies and directions defined by formulae</u>
<u>103</u>	<u>Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for waves selected by period range</u>
<u>104</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for waves selected by period range</u>
<u>105</u>	<u>Anomalies, significance and other derived products from an analysis or forecast in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval</u>
<u>106</u>	<u>Anomalies, significance and other derived products from an individual ensemble forecast, control and perturbed in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval</u>
<u>107</u>	<u>Anomalies, significance and other derived products from derived forecasts based on all ensemble members in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval</u>
<u>108</u>	<u>Analysis or forecast at a horizontal level or in a horizontal layer at a point in time for generic optical products</u>
<u>109</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer at a point in time for generic optical products</u>
<u>110</u>	<u>Average, accumulation, extreme values or other statistically processed values at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval for generic optical products</u>
<u>111</u>	<u>Individual ensemble forecast, control and perturbed, at a horizontal level or in a horizontal layer, in a continuous or non-continuous interval for generic optical products</u>
<u>112</u>	<u>Anomalies, significance and other derived products as probability forecasts in relation to a reference period at a horizontal level or in a horizontal layer in a continuous or non-continuous time interval</u>
99 <u>113</u> –253	Reserved
254	CCITT IA5 character string
255–999	Reserved
1000	Cross-section of analysis and forecast at a point in time
1001	Cross-section of averaged or otherwise statistically processed analysis or forecast over a range of time
1002	Cross-section of analysis and forecast, averaged or otherwise statistically processed over latitude or longitude
1003–1099	Reserved
1100	Hovmöller-type grid with no averaging or other statistical processing
1101	Hovmöller-type grid with averaging or other statistical processing
1102–32767	Reserved
32768–65534	Reserved for local use
65535	Missing

Code table 4.1 – Parameter category by product discipline

Note: When a new category is to be added to Code table 4.1 and more than one discipline applies, the choice of discipline should be made based on the intended use of the product.

Product discipline 0 – Meteorological products

Code table 4.1
Product discipline 0 – Meteorological products

Category	Description
0	Temperature
1	Moisture
2	Momentum
3	Mass
4	Short-wave radiation
5	Long-wave radiation
6	Cloud
7	Thermodynamic stability indices
8	Kinematic stability indices (see Note)
9	Temperature probabilities (see Note)
10	Moisture probabilities (see Note)
11	Momentum probabilities (see Note)
12	Mass probabilities (see Note)
13	Aerosols
14	Trace gases (e.g. ozone, CO ₂)
15	Radar
16	Forecast radar imagery
17	Electrodynamics
18	Nuclear/radiology
19	Physical atmospheric properties
20	Atmospheric chemical constituents
21	Thermodynamic properties
21 22 –189	Reserved
190	CCITT IA5 string
191	Miscellaneous
192–254	Reserved for local use
255	Missing

Note: Entries ~~9~~, ~~10~~, ~~11~~ and ~~8~~ - 12 are deprecated.

Product discipline 1 – Hydrological products

Code table 4.1
Product discipline 1 – Hydrological products

Category	Description
0	Hydrology basic products
1	Hydrology probabilities
2	Inland water and sediment properties
3–191	Reserved
192–254	Reserved for local use
255	Missing

Product discipline 2 – Land surface products

<i>Code table 4.1</i> <i>Product discipline 2 – Land surface products</i>	
Category	Description
0	Vegetation/biomass
1	Agri-/aquacultural special products
2	Transportation-related products
3	Soil products
4	Fire weather products
5	<u>Glaciers and inland ice</u>
6	<u>Urban areas</u>
57–191	Reserved
192–254	Reserved for local use
255	Missing

Product discipline 3 – Satellite remote sensing products (formerly "Space products")

<i>Code table 4.1</i> <i>Product discipline 3 – Satellite remote sensing products</i>	
Category	Description
0	Image format products (see Note 1)
1	Quantitative products (see Note 2)
2	Cloud properties
3	Flight rule conditions
4	Volcanic ash
5	Sea-surface temperature
6	Solar radiation
7–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

- (1) Data are numeric without units, although they might be given quantitative meaning through a code table defined external to this document. The emphasis is on a displayable "picture" of some phenomenon, perhaps with certain enhanced features. Generally, each datum is an unsigned, one octet integer, but some image format products might have another datum size. The size of a datum is indicated in section 5.
- (2) Data are in specified physical units.

Product discipline 4 – Space weather products

<i>Code table 4.1</i> <i>Product discipline 4 – Space weather products</i>	
Category	Description
0	Temperature
1	Momentum
2	Charged particle mass and number
3	Electric and magnetic fields
4	Energetic particles
5	Waves

<i>Code table 4.1</i> <i>Product discipline 4 – Space weather products</i>	
Category	Description
6	Solar electromagnetic emissions
7	Terrestrial electromagnetic emissions
8	Imagery
9	Ion-neutral coupling
10	Space weather indices
11-191	Reserved
192-254	Reserved for local use
255	Missing

Product discipline 10 – Oceanographic products

<i>Code table 4.1</i> <i>Product discipline 10 – Oceanographic products</i>	
Category	Description
0	Waves
1	Currents
2	Ice
3	Surface properties
4	Subsurface properties
5-190	Reserved
191	Miscellaneous
192-254	Reserved for local use
255	Missing

Product discipline 20 – Health and socioeconomic impacts

<i>Code table 4.1</i> <i>Product discipline 20 – Health and socioeconomic impacts</i>	
Category	Description
0	Health indicators
1	Epidemiology
2	Socioeconomic indicators
3-191	Reserved
192-254	Reserved for local use
255	Missing

Code table 4.2 – Parameter number by product discipline and parameter category

Notes:

- (1) By convention, the flux sign is positive if downwards.

(2) When a new parameter is to be added to Code table 4.2 and more than one category applies, the choice of category should be made based on the intended use of the product. The discipline and category are an important part of any product definition, so it is possible to have the same parameter name in more than one category. For example, "water temperature" in discipline 10 (oceanographic products), category 4 (subsurface properties) is used for reporting water temperature in the ocean or open sea, and is not the same as "water temperature" in discipline 1 (hydrological products), category 2 (inland water and sediment properties), which is used for reporting water temperature in freshwater lakes and rivers.

Product discipline 0 – Meteorological products, parameter category 0: temperature

<i>Code table 4.2</i>		
<i>Product discipline 0 – Meteorological products, parameter category 0: temperature</i>		
Number	Parameter	Units
0	Temperature	K
1	Virtual temperature	K
2	Potential temperature	K
3	Pseudo-adiabatic potential temperature or equivalent potential temperature	K
4	Maximum temperature (see Note 1)	K
5	Minimum temperature (see Note 1)	K
6	Dewpoint temperature	K
7	Dewpoint depression (or deficit)	K
8	Lapse rate	K m ⁻¹
9	Temperature anomaly	K
10	Latent heat net flux	W m ⁻²
11	Sensible heat net flux	W m ⁻²
12	Heat index	K
13	Wind chill factor	K
14	Minimum dewpoint depression (see Note 1)	K
15	Virtual potential temperature	K
16	Snow phase change heat flux	W m ⁻²
17	Skin temperature	K
18	Snow temperature (top of snow)	K
19	Turbulent transfer coefficient for heat	Numeric
20	Turbulent diffusion coefficient for heat	m ² s ⁻¹
21	Apparent temperature (see Note 2)	K
22	Temperature tendency due to short-wave radiation	K s ⁻¹
23	Temperature tendency due to long-wave radiation	K s ⁻¹
24	Temperature tendency due to short-wave radiation, clear sky	K s ⁻¹
25	Temperature tendency due to long-wave radiation, clear sky	K s ⁻¹
26	Temperature tendency due to parameterization	K s ⁻¹
27	Wet-bulb temperature	K
28	Unbalanced component of temperature	K
29	Temperature advection	K s ⁻¹
30	Latent heat net flux due to evaporation	W m ⁻²
31	Latent heat net flux due to sublimation	W m ⁻²
32	Wet-bulb potential temperature	K
33–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Parameter deprecated. See Regulation 92.6.2 and use another parameter instead.
- (2) Apparent temperature is the perceived outdoor temperature, caused by a combination of phenomena, such as air temperature, relative humidity and wind speed.

Product discipline 0 – Meteorological products, parameter category 1: moisture

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 1: moisture

Number	Parameter	Units
0	Specific humidity	kg kg ⁻¹
1	Relative humidity	%
2	Humidity mixing ratio	kg kg ⁻¹
3	Precipitable water	kg m ⁻²
4	Vapour pressure	Pa
5	Saturation deficit	Pa
6	Evaporation	kg m ⁻²
7	Precipitation rate (see Note 1)	kg m ⁻² s ⁻¹
8	Total precipitation (see Note 3)	kg m ⁻²
9	Large-scale precipitation (non-convective) (see Note 3)	kg m ⁻²
10	Convective precipitation (see Note 3)	kg m ⁻²
11	Snow depth	m
12	Snowfall rate water equivalent (see Note 1)	kg m ⁻² s ⁻¹
13	Water equivalent of accumulated snow depth (see Note 3)	kg m ⁻²
14	Convective snow (see Note 3)	kg m ⁻²
15	Large-scale snow (see Note 3)	kg m ⁻²
16	Snow melt (see Note 7)	kg my
17	Snow age	d
18	Absolute humidity	kg m ⁻³
19	Precipitation type	(Code table 4.201)
20	Integrated liquid water	kg m ⁻²
21	Condensate	kg kg ⁻¹
22	Cloud mixing ratio	kg kg ⁻¹
23	Ice water mixing ratio	kg kg ⁻¹
24	Rain mixing ratio	kg kg ⁻¹
25	Snow mixing ratio	kg kg ⁻¹
26	Horizontal moisture convergence	kg kg ⁻¹ s ⁻¹
27	Maximum relative humidity (see Note 1)	%
28	Maximum absolute humidity (see Note 1)	kg m ⁻³
29	Total snowfall (see Note 3)	m
30	Precipitable water category	(Code table 4.202)
31	Hail	m
32	Graupel (snow pellets)	kg kg ⁻¹
33	Categorical rain	(Code table 4.222)
34	Categorical freezing rain	(Code table 4.222)
35	Categorical ice pellets	(Code table 4.222)
36	Categorical snow	(Code table 4.222)
37	Convective precipitation rate	kg m ⁻² s ⁻¹
38	Horizontal moisture divergence	kg kg ⁻¹ s ⁻¹

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 1: moisture

Number	Parameter	Units
39	Per cent frozen precipitation	%
40	Potential evaporation	kg m ⁻²
41	Potential evaporation rate (see Note 4)	W m ⁻²
42	Snow cover	%
43	Rain fraction of total cloud water	Proportion
44	Rime factor	Numeric
45	Total column integrated rain	kg m ⁻²
46	Total column integrated snow	kg m ⁻²
47	Large scale water precipitation (non-convective) (see Note 3)	kg m ⁻²
48	Convective water precipitation (see Note 3)	kg m ⁻²
49	Total water precipitation (see Note 3)	kg m ⁻²
50	Total snow precipitation (see Note 3)	kg my
51	Total column water (Vertically integrated total water (vapour + cloud water/ice))	kg my
52	Total precipitation rate (see Note 2)	kg m ⁻² s ⁻¹
53	Total snowfall rate water equivalent (see Note 2)	kg m ⁻² s ⁻¹
54	Large scale precipitation rate	kg m ⁻² s ⁻¹
55	Convective snowfall rate water equivalent	kg m ⁻² s ⁻¹
56	Large scale snowfall rate water equivalent	kg m ⁻² s ⁻¹
57	Total snowfall rate	m s ⁻¹
58	Convective snowfall rate	m s ⁻¹
59	Large scale snowfall rate	m s ⁻¹
60	Snow depth water equivalent	kg m ⁻²
61	Snow density	kg m ⁻³
62	Snow evaporation (see Note 8)	kg m ⁻²
63	Reserved	
64	Total column integrated water vapour	kg m ⁻²
65	Rain precipitation rate	kg m ⁻² s ⁻¹
66	Snow precipitation rate	kg m ⁻² s ⁻¹
67	Freezing rain precipitation rate	kg m ⁻² s ⁻¹
68	Ice pellets precipitation rate	kg m ⁻² s ⁻¹
69	Total column integrated cloud water	kg m ⁻²
70	Total column integrated cloud ice	kg m ⁻²
71	Hail mixing ratio	kg kg ⁻¹
72	Total column integrated hail	kg m ⁻²
73	Hail precipitation rate	kg m ⁻² s ⁻¹
74	Total column integrated graupel	kg m ⁻²
75	Graupel (snow pellets) precipitation rate	kg m ⁻² s ⁻¹
76	Convective rain rate	kg m ⁻² s ⁻¹
77	Large scale rain rate	kg m ⁻² s ⁻¹
78	Total column integrated water (all components including precipitation)	kg m ⁻²
79	Evaporation rate	kg m ⁻² s ⁻¹
80	Total condensate	kg kg ⁻¹
81	Total column-integrated condensate	kg m ⁻²
82	Cloud ice mixing-ratio	kg kg ⁻¹
83	Specific cloud liquid water content	kg kg ⁻¹

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 1: moisture

Number	Parameter	Units
84	Specific cloud ice water content	kg kg ⁻¹
85	Specific rainwater content	kg kg ⁻¹
86	Specific snow water content	kg kg ⁻¹
87	Stratiform precipitation rate	kg m ⁻² s ⁻¹
88	Categorical convective precipitation	(Code table 4.222)
89	Reserved	
90	Total kinematic moisture flux	kg kg ⁻¹ m s ⁻¹
91	u-component (zonal) kinematic moisture flux	kg kg ⁻¹ m s ⁻¹
92	v-component (meridional) kinematic moisture flux	kg kg ⁻¹ m s ⁻¹
93	Relative humidity with respect to water	%
94	Relative humidity with respect to ice	%
95	Freezing or frozen precipitation rate	kg m ⁻² s ⁻¹
96	Mass density of rain	kg m ⁻³
97	Mass density of snow	kg m ⁻³
98	Mass density of graupel	kg m ⁻³
99	Mass density of hail	kg m ⁻³
100	Specific number concentration of rain	kg ⁻¹
101	Specific number concentration of snow	kg ⁻¹
102	Specific number concentration of graupel	kg ⁻¹
103	Specific number concentration of hail	kg ⁻¹
104	Number density of rain	m ⁻³
105	Number density of snow	m ⁻³
106	Number density of graupel	m ⁻³
107	Number density of hail	m ⁻³
108	Specific humidity tendency due to parameterization	kg kg ⁻¹ s ⁻¹
109	Mass density of liquid water coating on hail expressed as mass of liquid water per unit volume of air	kg m ⁻³
110	Specific mass of liquid water coating on hail expressed as mass of liquid water per unit mass of moist air	kg kg ⁻¹
111	Mass mixing ratio of liquid water coating on hail expressed as mass of liquid water per unit mass of dry air	kg kg ⁻¹
112	Mass density of liquid water coating on graupel expressed as mass of liquid water per unit volume of air	kg m ⁻³
113	Specific mass of liquid water coating on graupel expressed as mass of liquid water per unit mass of moist air	kg kg ⁻¹
114	Mass mixing ratio of liquid water coating on graupel expressed as mass of liquid water per unit mass of dry air	kg kg ⁻¹
115	Mass density of liquid water coating on snow expressed as mass of liquid water per unit volume of air	kg m ⁻³
116	Specific mass of liquid water coating on snow expressed as mass of liquid water per unit mass of moist air	kg kg ⁻¹
117	Mass mixing ratio of liquid water coating on snow expressed as mass of liquid water per unit mass of dry air	kg kg ⁻¹

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 1: moisture

Number	Parameter	Units
118	Unbalanced component of specific humidity	kg kg ⁻¹
119	Unbalanced component of specific cloud liquid water content	kg kg ⁻¹
120	Unbalanced component of specific cloud ice water content	kg kg ⁻¹
121	Fraction of snow cover	Proportion
122	Precipitation intensity index	(Code table 4.247)
123	Dominant precipitation type	(Code table 4.201)
124	Presence of showers	(Code table 4.222)
125	Presence of blowing snow	(Code table 4.222)
126	Presence of blizzard	(Code table 4.222)
127	Ice pellets (non-water equivalent) precipitation rate	m/s
128	Total solid precipitation rate (see Note 5)	kg m ⁻² s ⁻¹
129	Effective radius of cloud water	m
130	Effective radius of rain	m
131	Effective radius of cloud ice	m
132	Effective radius of snow	m
133	Effective radius of graupel	m
134	Effective radius of hail	m
135	Effective radius of subgrid liquid clouds	m
136	Effective radius of subgrid ice clouds	m
137	Effective aspect ratio of rain	–
138	Effective aspect ratio of cloud ice	–
139	Effective aspect ratio of snow	–
140	Effective aspect ratio of graupel	–
141	Effective aspect ratio of hail	–
142	Effective aspect ratio of subgrid ice clouds	–
143	Potential evaporation rate	kg m ⁻² s ⁻¹
144	Specific rain water content (convective)	kg kg ⁻¹
145	Specific snow water content (convective)	kg kg ⁻¹
146	Cloud ice precipitation rate (see Note 6)	kg m ⁻² s ⁻¹
147	Character of precipitation	(Code table 4.249)
148	Snow evaporation rate (see Note 9)	kg m ⁻² s ⁻¹
149	Cloud water mixing ratio	kg kg ⁻¹
150	<u>Column integrated eastward water vapour mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
151	<u>Column integrated northward water vapour mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
152	<u>Column integrated eastward cloud liquid water mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
153	<u>Column integrated northward cloud liquid water mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
154	<u>Column integrated eastward cloud ice mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
155	<u>Column integrated northward cloud ice mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
156	<u>Column integrated eastward rain mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
157	<u>Column integrated northward rain mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
158	<u>Column integrated eastward snow mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
159	<u>Column integrated northward snow mass flux</u>	<u>kg m⁻¹ s⁻¹</u>
160	<u>Column integrated divergence of water vapour mass flux</u>	<u>kg m⁻² s⁻¹</u>

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 1: moisture

Number	Parameter	Units
<u>161</u>	<u>Column integrated divergence of cloud liquid water mass flux</u>	<u>kg m⁻² s⁻¹</u>
<u>162</u>	<u>Column integrated divergence of cloud ice mass flux</u>	<u>kg m⁻² s⁻¹</u>
<u>163</u>	<u>Column integrated divergence of rain mass flux</u>	<u>kg m⁻² s⁻¹</u>
<u>164</u>	<u>Column integrated divergence of snow mass flux</u>	<u>kg m⁻² s⁻¹</u>
<u>165</u>	<u>Column integrated divergence of total water mass flux</u>	<u>kg m⁻² s⁻¹</u>
<u>166</u>	<u>Column integrated water vapour flux</u>	<u>kg m⁻² s⁻¹</u>
<u>167</u>	<u>Total column supercooled liquid water</u>	<u>kg m⁻²</u>
150 168– 191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Parameter deprecated. See Regulation 92.6.2 and use another parameter instead.
- (2) Total precipitation/snowfall rate stands for the sum of convective and large-scale precipitation/snowfall rate.
- (3) Statistical process 1 (Accumulation) does not change units. It is recommended to use another parameter with “rate” in its name and accumulation in PDT.
- (4) The listed units for this parameter appear to be inappropriate for the potential evaporation rate. Instead, it is recommended to use parameter 143.
- (5) Total solid precipitation includes the sum of all types of solid water, e.g. graupel, snow and hail.
- (6) Assuming a cloud containing a bi-modal ice particle distribution, “cloud ice” refers to the small particle mode, whereas the large mode is usually called “snow”. (“Ice pellets”, in contrast, may refer to the precipitation of sleet, formed from freezing raindrops or refreezing (partially) melted snowflakes, or the precipitation of small hail.)
- (7) It is recommended to use Snow melt rate instead (discipline 2, category 0, number 41).
- (8) It is recommended to use parameter 148.
- (9) Snow evaporation is the accumulated amount of water that has evaporated from snow from within the snow covered area of a grid-box.

Product discipline 0 – Meteorological products, parameter category 2: momentum

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 2: momentum

Number	Parameter	Units
0	Wind direction (from which blowing)	degree true
1	Wind speed	m s ⁻¹
2	u-component of wind	m s ⁻¹
3	v-component of wind	m s ⁻¹
4	Stream function	m ² s ⁻¹
5	Velocity potential	m ² s ⁻¹
6	Montgomery stream function	m ² s ⁻²
7	Sigma coordinate vertical velocity	s ⁻¹
8	Vertical velocity (pressure)	Pa s ⁻¹
9	Vertical velocity (geometric)	m s ⁻¹
10	Absolute vorticity	s ⁻¹
11	Absolute divergence	s ⁻¹

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 2: momentum

Number	Parameter	Units
12	Relative vorticity	s^{-1}
13	Relative divergence	s^{-1}
14	Potential vorticity	$K\ m^2\ kg^{-1}\ s^{-1}$
15	Vertical u-component shear	s^{-1}
16	Vertical v-component shear	s^{-1}
17	Momentum flux, u-component	$N\ m^{-2}$
18	Momentum flux, v-component	$N\ m^{-2}$
19	Wind mixing energy	J
20	Boundary layer dissipation	$W\ m^{-2}$
21	Maximum wind speed (see Note 1)	$m\ s^{-1}$
22	Wind speed (gust)	$m\ s^{-1}$
23	u-component of wind (gust)	$m\ s^{-1}$
24	v-component of wind (gust)	$m\ s^{-1}$
25	Vertical speed shear	s^{-1}
26	Horizontal momentum flux	$N\ m^{-2}$
27	u-component storm motion	$m\ s^{-1}$
28	v-component storm motion	$m\ s^{-1}$
29	Drag coefficient	Numeric
30	Frictional velocity	$m\ s^{-1}$
31	Turbulent diffusion coefficient for momentum	$m^2\ s^{-1}$
32	Eta coordinate vertical velocity	s^{-1}
33	Wind fetch	m
34	Normal wind component (see Note 2)	$m\ s^{-1}$
35	Tangential wind component (see Note 2)	$m\ s^{-1}$
36	Amplitude function for Rossby wave envelope for meridional wind (see Note 3)	$m\ s^{-1}$
37	Northward turbulent surface stress (see Note 4)	$N\ m^{-2}\ s$
38	Eastward turbulent surface stress (see Note 4)	$N\ m^{-2}\ s$
39	Eastward wind tendency due to parameterization	$m\ s^{-2}$
40	Northward wind tendency due to parameterization	$m\ s^{-2}$
41	u-component of geostrophic wind	$m\ s^{-1}$
42	v-component of geostrophic wind	$m\ s^{-1}$
43	Geostrophic wind direction	degree true
44	Geostrophic wind speed	$m\ s^{-1}$
45	Unbalanced component of divergence	s^{-1}
46	Vorticity advection	s^{-2}
47	Surface roughness for heat (see Note 5)	m
48	Surface roughness for moisture (see Note 6)	m
49	<u>Wind stress</u>	<u>$N\ m^{-2}$</u>
50	<u>Eastward wind stress</u>	<u>$N\ m^{-2}$</u>
51	<u>Northward wind stress</u>	<u>$N\ m^{-2}$</u>
52	<u>u-component of wind stress</u>	<u>$N\ m^{-2}$</u>
53	<u>v-component of wind stress</u>	<u>$N\ m^{-2}$</u>
54	<u>Natural logarithm of surface roughness length for heat</u>	<u>Numeric</u>
55	<u>Natural logarithm of surface roughness length for moisture</u>	<u>Numeric</u>
56	<u>u-component of neutral wind</u>	<u>$m\ s^{-1}$</u>

FM 92 GRIB

Code table 4.2		
Product discipline 0 – Meteorological products, parameter category 2: momentum		
Number	Parameter	Units
57	<u>v-component of neutral wind</u>	<u>m s⁻¹</u>
58	<u>Magnitude of turbulent surface stress</u>	<u>N m⁻²</u>
4959–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Parameter deprecated. See Regulation 92.6.2 and use another parameter instead.
- (2) In relation to local coordinate axes at a cell edge.
- (3) This parameter is described in more detail by (a) Lee, S. and I.M. Held, 1993: Baroclinic wave packets in models and observations. *J. Atmos. Sci.*, 50:1413–1428, (b) Chang, E.K.M., 1993: Downstream development of baroclinic waves as inferred from regression analysis. *J. Atmos. Sci.*, 50:2038–2053, (c) Archambault, H.M., D. Keyser and L.F. Bosart, 2010: Relationships between large-scale regime transitions and major cool-season precipitation events in the northeastern United States. *Mon. Wea. Review*, 138:3454–3473, and (d) Zimin, A.V., I. Szunyogh, B.R. Hung and E. Orr, 2006: Extracting envelopes of nonzonally propagating Rossby wave packets. *Mon. Wea. Review*, 134:1329–1333.
- (4) Statistical process 1 (Accumulation) does not change units.
- (5) Surface roughness for heat is a measure of the surface resistance to heat transfer.
- (6) Surface roughness for moisture is a measure of the surface resistance to moisture transfer.

Product discipline 0 – Meteorological products, parameter category 3: mass

Code table 4.2		
Product discipline 0 – Meteorological products, parameter category 3: mass		
Number	Parameter	Units
0	Pressure	Pa
1	Pressure reduced to MSL	Pa
2	Pressure tendency	Pa s ⁻¹
3	ICAO Standard Atmosphere Reference Height	m
4	Geopotential	m ² s ⁻²
5	Geopotential height	gpm
6	Geometric height (see Note)	m
7	Standard deviation of height	m
8	Pressure anomaly	Pa
9	Geopotential height anomaly	gpm
10	Density	kg m ⁻³
11	Altimeter setting	Pa
12	Thickness	m
13	Pressure altitude	m
14	Density altitude	m
15	5-wave geopotential height	gpm
16	Zonal flux of gravity wave stress	N m ⁻²
17	Meridional flux of gravity wave stress	N m ⁻²
18	Planetary boundary layer height	m
19	5-wave geopotential height anomaly	gpm
20	Standard deviation of sub-grid scale orography	m
21	Angle of sub-gridscale orography	rad
22	Slope of sub-gridscale orography	Numeric

Code table 4.2		
Product discipline 0 – Meteorological products, parameter category 3: mass		
Number	Parameter	Units
23	Gravity wave dissipation	W m^{-2}
24	Anisotropy of sub-gridscale orography	Numeric
25	Natural logarithm of pressure in Pa	Numeric
26	Exner pressure	Numeric
27	Updraught mass flux	$\text{kg m}^{-2} \text{s}^{-1}$
28	Downdraught mass flux	$\text{kg m}^{-2} \text{s}^{-1}$
29	Updraught detrainment rate	$\text{kg m}^{-3} \text{s}^{-1}$
30	Downdraught detrainment rate	$\text{kg m}^{-3} \text{s}^{-1}$
31	Unbalanced component of logarithm of surface pressure	–
32	Saturation water vapour pressure	Pa
33	Geometric altitude above mean sea level	m
34	Geometric height above ground level	m
35	Column integrated divergence of total mass flux	$\text{kg m}^{-2} \text{s}^{-1}$
36	Column integrated eastward total mass flux	$\text{kg m}^{-1} \text{s}^{-1}$
37	Column integrated northward total mass flux	$\text{kg m}^{-1} \text{s}^{-1}$
38	Standard deviation of filtered subgrid orography	m
39	Column integrated mass of atmosphere	kg m^{-2}
40	Column integrated eastward geopotential flux	W m^{-1}
41	Column integrated northward geopotential flux	W m^{-1}
42	Column integrated divergence of water geopotential flux	W m^{-2}
43	Column integrated divergence of geopotential flux	W m^{-2}
44	Height of zero-degree wet-bulb temperature	m
45	Height of one-degree wet-bulb temperature	m
3546–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Note: Number 33 (Geometric altitude above mean sea level) or number 34 (Geometric height above ground level) should be used instead of number 6 (Geometric height), because it does not indicate whether this is referring to height above mean sea level or height above ground.

Product discipline 0 – Meteorological products, parameter category 4: short-wave radiation

Code table 4.2		
Product discipline 0 – Meteorological products, parameter category 4: short-wave radiation		
Number	Parameter	Units
0	Net short-wave radiation flux (surface) (see Note 1)	W m^{-2}
1	Net short-wave radiation flux (top of atmosphere) (see Note 1)	W m^{-2}
2	Short-wave radiation flux (see Note 1)	W m^{-2}
3	Global radiation flux	W m^{-2}
4	Brightness temperature	K
5	Radiance (with respect to wave number)	$\text{W m}^{-1} \text{sr}^{-1}$
6	Radiance (with respect to wavelength)	$\text{W m}^{-3} \text{sr}^{-1}$
7	Downward short-wave radiation flux	W m^{-2}
8	Upward short-wave radiation flux	W m^{-2}

Code table 4.2

Product discipline 0 – Meteorological products, parameter category 4: short-wave radiation

Number	Parameter	Units
9	Net short wave radiation flux	W m ⁻²
10	Photosynthetically active radiation	W m ⁻²
11	Net short-wave radiation flux, clear sky	W m ⁻²
12	Downward UV radiation	W m ⁻²
13	Direct short-wave radiation flux	W m ⁻²
14	Diffuse short-wave radiation flux	W m ⁻²
15	Upward UV radiation emitted/reflected from the Earth's surface	W m ⁻²
16–49	Reserved	
50	UV index (under clear sky) (see Note 2)	Numeric
51	UV index (see Note 2)	Numeric
52	Downward short-wave radiation flux, clear sky	W m ⁻²
53	Upward short-wave radiation flux, clear sky	W m ⁻²
54	Direct normal short-wave radiation flux (see Note 3)	W m ⁻²
55	<u>UV visible albedo for diffuse radiation</u>	%
56	<u>UV visible albedo for direct radiation</u>	%
57	<u>UV visible albedo for direct radiation, geometric component</u>	%
58	<u>UV visible albedo for direct radiation, isotropic component</u>	%
59	<u>UV visible albedo for direct radiation, volumetric component</u>	%
60	<u>Photosynthetically active radiation flux, clear sky</u>	W m ⁻²
61	<u>Direct short-wave radiation flux, clear sky</u>	W m ⁻²
5562–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Parameter deprecated. See Regulation 92.6.2 and use another parameter instead.
- (2) The Global Solar UVI is formulated using the International Commission on Illumination (CIE) reference action spectrum for UV-induced erythema on the human skin (ISO 17166:1999/CIE S 007/E-1998).

It is a measure of the UV radiation that is relevant to and defined for a horizontal surface. The UVI is a unitless quantity defined by the formula:

$$I_{UV} = k_{er} \cdot \int_{250nm}^{400nm} E_{\lambda} \cdot S_{er}(\lambda) d\lambda$$

where E_{λ} is the solar spectral irradiance expressed in W / (m²·nanometre) at wavelength λ and $d\lambda$ is the wave-length interval used in the summation. S_{er} λ is the erythema reference action spectrum, and k_{er} is a constant equal to 40 m² / W.

- (3) Normal flux is on a surface lifted to be normal to sun rays.

Product discipline 0 – Meteorological products, parameter category 5: long-wave radiation

Code table 4.2

Product discipline 0 – Meteorological products, parameter category 5: long-wave radiation

Number	Parameter	Units
0	Net long-wave radiation flux (surface) (see Note)	W m ⁻²
1	Net long-wave radiation flux (top of atmosphere) (see Note)	W m ⁻²

Code table 4.2		
Product discipline 0 – Meteorological products, parameter category 5: long-wave radiation		
Number	Parameter	Units
2	Long-wave radiation flux (see Note)	W m ⁻²
3	Downward long-wave radiation flux	W m ⁻²
4	Upward long-wave radiation flux	W m ⁻²
5	Net long-wave radiation flux	W m ⁻²
6	Net long-wave radiation flux, clear sky	W m ⁻²
7	Brightness temperature	K
8	Downward long-wave radiation flux, clear sky	W m ⁻²
9	<u>Near IR albedo for diffuse radiation</u>	%
10	<u>Near IR albedo for direct radiation</u>	%
11	<u>Near IR albedo for direct radiation, geometric component</u>	%
12	<u>Near IR albedo for direct radiation, isotropic component</u>	%
13	<u>Near IR albedo for direct radiation, volumetric component</u>	%
914–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Note: Parameter deprecated. See Regulation 92.6.2 and use another parameter instead.

Product discipline 0 – Meteorological products, parameter category 6: cloud

Code table 4.2		
Product discipline 0 – Meteorological products, parameter category 6: cloud		
Number	Parameter	Units
0	Cloud ice	kg m ⁻²
1	Total cloud cover	%
2	Convective cloud cover	%
3	Low cloud cover	%
4	Medium cloud cover	%
5	High cloud cover	%
6	Cloud water	kg m ⁻²
7	Cloud amount	%
8	Cloud type	(Code table 4.203)
9	Thunderstorm maximum tops	m
10	Thunderstorm coverage	(Code table 4.204)
11	Cloud base	m
12	Cloud top	m
13	Ceiling	m
14	Non-convective cloud cover	%
15	Cloud work function	J kg ⁻¹
16	Convective cloud efficiency	Proportion
17	Total condensate (see Note 1)	kg kg ⁻¹
18	Total column-integrated cloud water (see Note 1)	kg m ⁻²
19	Total column-integrated cloud ice (see Note 1)	kg m ⁻²
20	Total column-integrated condensate (see Note 1)	kg m ⁻²
21	Ice fraction of total condensate	Proportion

Code table 4.2		
Product discipline 0 – Meteorological products, parameter category 6: cloud		
Number	Parameter	Units
22	Cloud cover	%
23	Cloud ice mixing ratio (see Note 1)	kg kg ⁻¹
24	Sunshine	Numeric
25	Horizontal extent of cumulonimbus (CB)	%
26	Height of convective cloud base	m
27	Height of convective cloud top	m
28	Number of cloud droplets per unit mass of air	kg ⁻¹
29	Number of cloud ice particles per unit mass of air	kg ⁻¹
30	Number density of cloud droplets	m ⁻³
31	Number density of cloud ice particles	m ⁻³
32	Fraction of cloud cover	Numeric
33	Sunshine duration	s
34	Surface long-wave effective total cloudiness	Numeric
35	Surface short-wave effective total cloudiness	Numeric
36	Fraction of stratiform precipitation cover	Proportion
37	Fraction of convective precipitation cover	Proportion
38	Mass density of cloud droplets	kg m ⁻³
39	Mass density of cloud ice	kg m ⁻³
40	Mass density of convective cloud water droplets	kg m ⁻³
41–46	Reserved	
47	Volume fraction of cloud water droplets (see Note 2)	Numeric
48	Volume fraction of cloud ice particles (see Note 2)	Numeric
49	Volume fraction of cloud (ice and/or water) (see Note 2)	Numeric
50	Fog (see Note 3)	%
51	<u>Sunshine duration fraction (see Note 4)</u>	<u>Proportion</u>
51 52–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Note:

- (1) Parameter deprecated. Use another parameter in parameter category 1: moisture instead.
- (2) The sum of the water and ice fractions may exceed the total due to overlap between the volumes containing ice and those containing liquid water.
- (3) Fog is defined as cloud cover in the lowest model level.
- (4) This parameter is the amount of sunshine in seconds over a given length of time in seconds. Sunshine is defined as a radiation intensity above 120 W m⁻².

Product discipline 0 – Meteorological products, parameter category 7: thermodynamic stability indices

Code table 4.2		
Product discipline 0 – Meteorological products, parameter category 7: thermodynamic stability indices		
Number	Parameter	Units
0	Parcel lifted index (to 500 hPa)	K
1	Best lifted index (to 500 hPa)	K
2	K index	K

Code table 4.2

Product discipline 0 – Meteorological products, parameter category 7: thermodynamic stability indices

Number	Parameter	Units
3	KO index	K
4	Total totals index	K
5	Sweat index	Numeric
6	Convective available potential energy	J kg ⁻¹
7	Convective inhibition	J kg ⁻¹
8	Storm relative helicity	J kg ⁻¹
9	Energy helicity index	Numeric
10	Surface lifted index	K
11	Best (4-layer) lifted index	K
12	Richardson number	Numeric
13	Showalter index	K
14	Reserved	
15	Updraught helicity	m ² s ⁻²
16	Bulk Richardson number	Numeric
17	Gradient Richardson number	Numeric
18	Flux Richardson number	Numeric
19	Convective available potential energy – shear	m ² s ⁻²
20	Thunderstorm intensity index	(Code table 4.246)
21–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Product discipline 0 – Meteorological products, parameter category 13: aerosols

Note: This category is no longer populated. Please use “Product discipline 0 – Meteorological products, parameter category 20: atmospheric chemical constituents”.

Code table 4.2

Product discipline 0 – Meteorological products, parameter category 13: aerosols

Number	Parameter	Units
0	Aerosol type	(Code table 4.205)
1–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Product discipline 0 – Meteorological products, parameter category 14: trace gases

Code table 4.2

Product discipline 0 – Meteorological products, parameter category 14: trace gases

Number	Parameter	Units
0	Total ozone	DU
1	Ozone mixing ratio	kg kg ⁻¹
2	Total column integrated ozone	DU
3–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Product discipline 0 – Meteorological products, parameter category 15: radar

Code table 4.2 Product discipline 0 – Meteorological products, parameter category 15: radar		
Number	Parameter	Units
0	Base spectrum width	m s^{-1}
1	Base reflectivity	dB
2	Base radial velocity	m s^{-1}
3	Vertically integrated liquid water (VIL)	kg m^{-2}
4	Layer-maximum base reflectivity	dB
5	Precipitation	kg m^{-2}
6	Radar spectra (1)	–
7	Radar spectra (2)	–
8	Radar spectra (3)	–
9	Reflectivity of cloud droplets	dB
10	Reflectivity of cloud ice	dB
11	Reflectivity of snow	dB
12	Reflectivity of rain	dB
13	Reflectivity of graupel	dB
14	Reflectivity of hail	dB
15	Hybrid scan reflectivity	dB
16	Hybrid scan reflectivity height	m
17–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Product Discipline 0 – Meteorological products, parameter category 16: forecast radar imagery

Code table 4.2 Product Discipline 0 – Meteorological products, parameter category 16: forecast radar imagery		
Number	Parameter	Units
0	Equivalent radar reflectivity factor for rain	$\text{mm}^6 \text{m}^{-3}$
1	Equivalent radar reflectivity factor for snow	$\text{mm}^6 \text{m}^{-3}$
2	Equivalent radar reflectivity factor for parameterized convection	$\text{mm}^6 \text{m}^{-3}$
3	Echo top	m
4	Reflectivity	dB
5	Composite reflectivity	dB
6–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Note: Decibel (dB) is a logarithmic measure of the relative power, or of the relative values of two flux densities, especially of sound intensities and radio and radar power densities. In radar meteorology, the logarithmic scale (dBZ) is used for measuring radar reflectivity factor (obtained from the American Meteorological Society *Glossary of Meteorology*).

Product discipline 0 – Meteorological products, parameter category 17: electrodynamics

Code table 4.2 Product discipline 0 – Meteorological products, parameter category 17: electrodynamics		
Number	Parameter	Units
0	Lightning strike density	$\text{m}^{-2} \text{s}^{-1}$

Code table 4.2		
<i>Product discipline 0 – Meteorological products, parameter category 17: electrodynamics</i>		
Number	Parameter	Units
1	Lightning potential index (LPI) (see Note 1)	J kg ⁻¹
2	Cloud-to-ground lightning flash density	km ⁻² day ⁻¹
3	Cloud-to-cloud lightning flash density	km ⁻² day ⁻¹
4	Total lightning flash density (see Note 2)	km ⁻² day ⁻¹
5	Subgrid-scale lightning potential index (see Note 3)	J kg ⁻¹

Notes:

- (1) Definition of LPI after Lynn et al.: Lynn, B. and Y. Yair, 2010: Prediction of lightning flash density with the WRF model, *Adv. Geosci.*, 23:11–16; Yair, Y., B. Lynn, C. Price, V. Kotroni, K. Lagouvardos, E. Morin, A. Mugnai and M. Llasat, 2010: Predicting the potential for lightning activity in Mediterranean storms based on the Weather Research and Forecasting (WRF) model dynamic and microphysical fields, *Journal of Geophysical Research*, 115, D04205, doi:10.1029/2008JD010868.
- (2) The total lightning flash density is the sum of cloud-to-ground and cloud-to-cloud lightning flash densities (see Lopez, P., 2016: A lightning parameterization for the ECMWF Integrated Forecasting System, *Monthly Weather Review*, 144, 3057–3075).
- (3) The lightning potential index (LPI, Number 1), as defined by Lynn et al. 2010, is derived from grid scale (resolved) model information in convection permitting models. In contrast, the subgrid-scale lightning potential index is derived from subgrid-scale information (from parameterized convection) for models with coarser resolution.

**Product discipline 0 – Meteorological products, parameter category 18:
nuclear/radiology**

Code table 4.2		
<i>Product discipline 0 – Meteorological products, parameter category 18: nuclear/radiology</i>		
Number	Parameter	Units
0	Air concentration of caesium 137	Bq m ⁻³
1	Air concentration of iodine 131	Bq m ⁻³
2	Air concentration of radioactive pollutant	Bq m ⁻³
3	Ground deposition of caesium 137	Bq m ⁻²
4	Ground deposition of iodine 131	Bq m ⁻²
5	Ground deposition of radioactive pollutant	Bq m ⁻²
6	Time-integrated air concentration of caesium pollutant (see Note 1)	Bq s m ⁻³
7	Time-integrated air concentration of iodine pollutant (see Note 1)	Bq s m ⁻³
8	Time-integrated air concentration of radioactive pollutant (see Note 1)	Bq s m ⁻³
9	Reserved	
10	Air concentration (see Note 2)	Bq m ⁻³
11	Wet deposition	Bq m ⁻²
12	Dry deposition	Bq m ⁻²
13	Total deposition (wet + dry)	Bq m ⁻²
14	Specific activity concentration (see Note 2)	Bq kg ⁻¹
15	Maximum of air concentration in layer	Bq m ⁻³
16	Height of maximum air concentration	m
17	Column-integrated air concentration	Bq m ⁻²
18	Column-averaged air concentration in layer	Bq m ⁻³
19–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Statistical process 1 (Accumulation) does not change units. It is recommended to use another parameter without the word "time-integrated" in its name and accumulation in PDT.
- (2) Conversion factor between "Specific activity concentration" (14) and "Air concentration" (10) is "mass density" [kg m^{-3}].
- (3) Parameters from 10 onward may be used in combination with product definition templates 4.40– 4.43 and Common Code table C-14 (Code table 4.230) to represent any type of radioisotope.

Product discipline 0 – Meteorological products, parameter category 19: physical atmospheric properties

Code table 4.2 Product discipline 0 – Meteorological products, parameter category 19: physical atmospheric properties		
Number	Parameter	Units
0	Visibility	m
1	Albedo	%
2	Thunderstorm probability	%
3	Mixed layer depth	m
4	Volcanic ash	(Code table 4.206)
5	Icing top	m
6	Icing base	m
7	Icing	(Code table 4.207)
8	Turbulence top	m
9	Turbulence base	m
10	Turbulence	(Code table 4.208)
11	Turbulent kinetic energy	J kg^{-1}
12	Planetary boundary-layer regime	(Code table 4.209)
13	Contrail intensity	(Code table 4.210)
14	Contrail engine type	(Code table 4.211)
15	Contrail top	m
16	Contrail base	m
17	Maximum snow albedo (see Note 1)	%
18	Snow free albedo	%
19	Snow albedo	%
20	Icing	%
21	In-cloud turbulence	%
22	Clear air turbulence (CAT)	%
23	Supercooled large droplet probability (see Note 2)	%
24	Convective turbulent kinetic energy	J kg^{-1}
25	Weather	(Code table 4.225)
26	Convective outlook	(Code table 4.224)
27	Icing scenario	(Code table 4.227)
28	Mountain wave turbulence (eddy dissipation rate)	$\text{m}^{2/3} \text{ s}^{-1}$
29	Clear air turbulence (CAT)	$\text{m}^{2/3} \text{ s}^{-1}$
30	Eddy dissipation parameter (see Note 3)	$\text{m}^{2/3} \text{ s}^{-1}$
31	Maximum of eddy dissipation parameter in layer	$\text{m}^{2/3} \text{ s}^{-1}$
32	Highest freezing level	m
33	Visibility through liquid fog	m
34	Visibility through ice fog	m
35	Visibility through blowing snow	m
36	Presence of snow squalls	Code table 4.222
37	Icing severity	(Code table 4.228)
38	Sky transparency index (see Note 4)	(Code table 4.214)

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 19: physical atmospheric properties

Number	Parameter	Units
39	Seeing index (see Note 5)	(Code table 4.214)
40	Snow level	m
41	Duct base height (see Note 6)	m
42	Trapping layer base height (see Note 6)	m
43	Trapping layer top height (see Note 6)	m
44	Mean vertical gradient of refractivity inside trapping layer (see Note 6)	m ⁻¹
45	Minimum vertical gradient of refractivity inside trapping layer (see Note 6)	m ⁻¹
41 46–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Parameter deprecated. See Regulation 92.6.2 and use another parameter instead.
- (2) Supercooled large droplets (SLD) are defined as those with a diameter greater than 50 microns.
- (3) Eddy dissipation parameter is the third root of eddy dissipation rate [m² s⁻³].
- (4) In astronomy, sky transparency means the effect on the viewing experience caused by the scattering of light through atmospheric water vapour, aerosols or other constituents. Ideal transparency conditions produce a black night sky conducive to viewing faint astronomical objects, almost like being in outer space. In poor transparency conditions, which may occur even in cloud-free conditions, the deep sky background is greyish (not black), faint details are washed out and contrast is reduced.
- (5) Seeing means the steadiness or turbulence of the atmosphere in the context of astronomical observation. Turbulence causes rapid random fluctuations of the optical path through the atmosphere. The twinkling of stars, for example, occurs in poor seeing conditions.
- (6) A duct layer is an atmospheric layer with a refractivity which leads to a trapping of electromagnetic waves. In a trapping layer the refractivity leads to a bending of EM waves, which is stronger than the Earth's curvature.

Product discipline 0 – Meteorological products, parameter category 20: atmospheric chemical constituents

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 20: atmospheric chemical constituents

Number	Parameter	Units
0	Mass density (concentration)	kg m ⁻³
1	Column-integrated mass density (see Note 1)	kg m ⁻²
2	Mass mixing ratio (mass fraction in air)	kg kg ⁻¹
3	Atmosphere emission mass flux	kg m ⁻² s ⁻¹
4	Atmosphere net production mass flux	kg m ⁻² s ⁻¹
5	Atmosphere net production and emission mass flux	kg m ⁻² s ⁻¹
6	Surface dry deposition mass flux	kg m ⁻² s ⁻¹
7	Surface wet deposition mass flux	kg m ⁻² s ⁻¹
8	Atmosphere re-emission mass flux	kg m ⁻² s ⁻¹
9	Wet deposition by large-scale precipitation mass flux	kg m ⁻² s ⁻¹
10	Wet deposition by convective precipitation mass flux	kg m ⁻² s ⁻¹
11	Sedimentation mass flux	kg m ⁻² s ⁻¹

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 20: atmospheric
chemical constituents

Number	Parameter	Units
12	Dry deposition mass flux	$\text{kg m}^{-2} \text{s}^{-1}$
13	Transfer from hydrophobic to hydrophilic	$\text{kg kg}^{-1} \text{s}^{-1}$
14	Transfer from SO_2 (sulphur dioxide) to SO_4 (sulphate)	$\text{kg kg}^{-1} \text{s}^{-1}$
15	Dry deposition velocity	m s^{-1}
16	Mass mixing ratio with respect to dry air	kg kg^{-1}
17	Mass mixing ratio with respect to wet air	kg kg^{-1}
18	Potential of hydrogen (pH)	pH
18 19–49	Reserved	
50	Amount in atmosphere	mol
51	Concentration in air	mol m^{-3}
52	Volume mixing ratio (fraction in air)	mol mol^{-1}
53	Chemical gross production rate of concentration	$\text{mol m}^{-3} \text{s}^{-1}$
54	Chemical gross destruction rate of concentration	$\text{mol m}^{-3} \text{s}^{-1}$
55	Surface flux	$\text{mol m}^{-2} \text{s}^{-1}$
56	Changes of amount in atmosphere (see Note 1)	mol s^{-1}
57	Total yearly average burden of the atmosphere	mol
58	Total yearly averaged atmospheric loss (see Note 1)	mol s^{-1}
59	Aerosol number concentration (see Note 2)	m^{-3}
60	Aerosol specific number concentration (see Note 2)	kg^{-1}
61	Maximum of mass density in layer (see Note 1)	kg m^{-3}
62	Height of maximum mass density	m
63	Column-averaged mass density in layer	kg m^{-3}
64	Mole fraction with respect to dry air	mol mol^{-1}
65	Mole fraction with respect to wet air	mol mol^{-1}
66	Column-integrated in-cloud scavenging rate by precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
67	Column-integrated below-cloud scavenging rate by precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
68	Column-integrated release rate from evaporating precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
69	Column-integrated in-cloud scavenging rate by large-scale precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
70	Column-integrated below-cloud scavenging rate by large-scale precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
71	Column-integrated release rate from evaporating large-scale precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
72	Column-integrated in-cloud scavenging rate by convective precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
73	Column-integrated below-cloud scavenging rate by convective precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
74	Column-integrated release rate from evaporating convective precipitation	$\text{kg m}^{-2} \text{s}^{-1}$
75	Wildfire flux	$\text{kg m}^{-2} \text{s}^{-1}$
76	Emission rate	$\text{kg kg}^{-1} \text{s}^{-1}$
77	Surface emission flux	$\text{kg m}^{-2} \text{s}^{-1}$
78	Column integrated eastward mass flux	kg m⁻¹ s⁻¹
79	Column integrated northward mass flux	kg m⁻¹ s⁻¹
80	Column integrated divergence of mass flux	kg m⁻² s⁻¹
81	Column integrated net source (see Note 3)	kg m⁻² s⁻¹
78 82–99	Reserved	
100	Surface area density (aerosol)	m^{-1}
101	Vertical visual range	m
102	Aerosol optical thickness	Numeric
103	Single scattering albedo	Numeric

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 20: atmospheric chemical constituents

Number	Parameter	Units
104	Asymmetry factor	Numeric
105	Aerosol extinction coefficient	m^{-1}
106	Aerosol absorption coefficient	m^{-1}
107	Aerosol lidar backscatter from satellite	$\text{m}^{-1} \text{sr}^{-1}$
108	Aerosol lidar backscatter from the ground	$\text{m}^{-1} \text{sr}^{-1}$
109	Aerosol lidar extinction from satellite	m^{-1}
110	Aerosol lidar extinction from the ground	m^{-1}
111	Angstrom exponent	Numeric
112–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) FirstFixedSurface and SecondFixedSurface of Code table 4.5 (Fixed surface types and units) to define the vertical extent, i.e. FirstFixedSurface can be set to 1 (Ground or water surface) and SecondFixedSurface set to 7 (Tropopause) for a restriction to the troposphere.
- (2) The term “number density” is used as well for “number concentration” (code number 59); conversion factor between “number density” (59) and “specific number concentration” (60) is “mass density” [kg m^{-3}].
- (3) The net source is the sum of all the atmospheric (chemical) processes creating and destroying chemical constituents or aerosols in the column.

Product discipline 0 – Meteorological products, parameter category 21: thermodynamic properties

Code table 4.2
Product discipline 0 – Meteorological products, parameter category 21: thermodynamic properties

Number	Parameter	Units
0	<u>Column integrated potential + internal energy</u>	<u>J m^{-2}</u>
1	<u>Column integrated kinetic energy</u>	<u>J m^{-2}</u>
2	<u>Column integrated total energy (see Note 1)</u>	<u>J m^{-2}</u>
3	<u>Column integrated enthalpy</u>	<u>J m^{-2}</u>
4	<u>Column integrated water enthalpy (see Note 2)</u>	<u>J m^{-2}</u>
5	<u>Column integrated eastward enthalpy flux</u>	<u>W m^{-1}</u>
6	<u>Column integrated northward enthalpy flux</u>	<u>W m^{-1}</u>
7	<u>Column integrated eastward potential energy flux</u>	<u>W m^{-1}</u>
8	<u>Column integrated northward potential energy flux</u>	<u>W m^{-1}</u>
9	<u>Column integrated eastward kinetic energy flux</u>	<u>W m^{-1}</u>
10	<u>Column integrated northward kinetic energy flux</u>	<u>W m^{-1}</u>
11	<u>Column integrated eastward total energy flux</u>	<u>W m^{-1}</u>
12	<u>Column integrated northward total energy flux (see Note 1)</u>	<u>W m^{-1}</u>
13	<u>Divergence of column integrated enthalpy flux (see Note 1)</u>	<u>W m^{-2}</u>
14	<u>Divergence of column integrated potential energy flux</u>	<u>W m^{-2}</u>
15	<u>Divergence of column integrated water potential energy flux (see Note 3)</u>	<u>W m^{-2}</u>
16	<u>Divergence of column integrated kinetic energy flux</u>	<u>W m^{-2}</u>
17	<u>Divergence of column integrated total energy flux (see Note 1)</u>	<u>W m^{-2}</u>
18	<u>Divergence of column integrated water enthalpy flux (see Note 2)</u>	<u>W m^{-2}</u>
19	<u>Column integrated eastward heat flux</u>	<u>W m^{-1}</u>

Code table 4.2

Product discipline 0 - Meteorological products, parameter category 21: thermodynamic properties

Number	Parameter	Units
20	Column integrated northward heat flux	W m ⁻¹
21	Column integrated potential+internal+latent energy	J m ⁻²
22-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Notes:

- (1) Total (atmospheric) energy is the sum of internal energy, potential energy, kinetic energy and latent heat. Same applies to energy fluxes.
- (2) The water enthalpy (flux) is the enthalpy (flux) associated with the temperature of the water mass.
- (3) The water potential energy flux is the flux of potential energy associated with the water mass.

Product discipline 0 – Meteorological products, parameter category 190: CCITT IA5 string

Code table 4.2

Product discipline 0 – Meteorological products, parameter category 190: CCITT IA5 string

Number	Parameter	Units
0	Arbitrary text string	CCITT IA5
1-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 0 – Meteorological products, parameter category 191: miscellaneous

Code table 4.2

Product discipline 0 – Meteorological products, parameter category 191: miscellaneous

Number	Parameter	Units
0	Seconds prior to initial reference time(defined in Section 1)	s
1	Geographical latitude	°N
2	Geographical longitude	°E
3	Days since last observation	d
4-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 1 – Hydrological products, parameter category 0: hydrology basic products

Code table 4.2

Product discipline 1 – Hydrological products, parameter category 0: hydrology basic products

Number	Parameter	Units
0	Flash flood guidance (Encoded as an accumulation over a floating subinterval of time between the reference time and valid time)	kg m ⁻²
1	Flash flood runoff (Encoded as an accumulation over a floating subinterval of time)	kg m ⁻²

Code table 4.2		
Product discipline 1 – Hydrological products, parameter category 0: hydrology basic products		
Number	Parameter	Units
2	Remotely sensed snow cover (see Note 1)	(Code table 4.215)
3	Elevation of snow-covered terrain (see Note 2)	(Code table 4.216)
4	Snow water equivalent per cent of normal (see Note 3)	%
5	Baseflow-groundwater runoff	kg m ⁻²
6	Storm surface runoff	kg m ⁻²
7	Discharge from rivers or streams	m ³ s ⁻¹
8	Groundwater upper storage	kg m ⁻²
9	Groundwater lower storage	kg m ⁻²
10	Side flow into river channel	m ³ s ⁻¹ m ⁻¹
11	River storage of water	m ³
12	Floodplain storage of water	m ³
13	Depth of water on soil surface	kg m ⁻²
14	Upstream accumulated precipitation	kg m ⁻²
15	Upstream accumulated snow melt (see Note 4)	kg m ⁻²
16	Percolation rate	kg m ⁻² s ⁻¹
17–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Remotely sensed snow cover is expressed as a field of dimensionless, thematic values. The currently accepted values are for no-snow/no-cloud, 50, for clouds, 100, and for snow, 250 (see Code table 4.215).
- (2) A data field representing snow coverage by elevation portrays at which elevations there is a snow pack. The elevation values typically range from 0 to 90 in 100-metre increments. A value of 253 is used to represent a no-snow/no-cloud data point. A value of 254 is used to represent a data point at which snow elevation could not be estimated because of clouds obscuring the remote sensor (when using aircraft or satellite measurements).
- (3) Snow water equivalent per cent of normal is stored in per cent of normal units. For example, a value of 110 indicates 110 per cent of the normal snow water equivalent for a given depth of snow.
- (4) It is recommended to use Snow melt rate instead (discipline 2, category 0, number 41).

Product discipline 1 – Hydrological products, parameter category 1: hydrology probabilities

Code table 4.2		
Product discipline 1 – Hydrological products, parameter category 1: hydrology probabilities		
Number	Parameter	Units
0	Conditional per cent precipitation amount fractile for an overall period (Encoded as an accumulation)	kg m ⁻²
1	Per cent precipitation in a sub-period of an overall period (Encoded as per cent accumulation over the sub-period)	%
2	Probability of 0.01 inch of precipitation (POP)	%
3–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Product discipline 1 – Hydrological products, parameter category 2: inland water and sediment properties

Code table 4.2

Product discipline 1 – Hydrological products, parameter category 2: inland water and sediment properties

Number	Parameter	Units
1	Water temperature	K
2	Water fraction	Proportion
3	Sediment thickness	m
4	Sediment temperature	K
5	Ice thickness	m
6	Ice temperature	K
7	Ice cover	Proportion
8	Land cover (0 = water, 1 = land)	Proportion
9	Shape factor with respect to salinity profile	–
10	Shape factor with respect to temperature profile in thermocline	–
11	Attenuation coefficient of water with respect to solar radiation	m ⁻¹
12	Salinity	kg kg ⁻¹
13	Cross-sectional area of flow in channel	m ²
14	Snow temperature	K
15–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Product discipline 2 – Land surface products, parameter category 0: vegetation/biomass

Code table 4.2

Product discipline 2 – Land surface products, parameter category 0: vegetation/biomass

Number	Parameter	Units
0	Land cover (0 = sea, 1 = land)	Proportion
1	Surface roughness	m
2	Soil temperature (see Note 3)	K
3	Soil moisture content (see Note 1)	kg m ⁻²
4	Vegetation	%
5	Water runoff	kg m ⁻²
6	Evapotranspiration (see Note 6)	kg ⁻² s ⁻¹
7	Model terrain height	m
8	Land use	(Code table 4.212)
9	Volumetric soil moisture content (see Note 2)	Proportion
10	Ground heat flux (see Note 1)	W m ⁻²
11	Moisture availability	%
12	Exchange coefficient	kg m ⁻² s ⁻¹
13	Plant canopy surface water	kg m ⁻²
14	Blackadar's mixing length scale	m
15	Canopy conductance	m s ⁻¹
16	Minimal stomatal resistance	s m ⁻¹
17	Wilting point (see Note 1)	Proportion
18	Solar parameter in canopy conductance	Proportion
19	Temperature parameter in canopy	Proportion
20	Humidity parameter in canopy conductance	Proportion
21	Soil moisture parameter in canopy conductance	Proportion
22	Soil moisture (see Note 3)	kg m ⁻³

Code table 4.2		
Product discipline 2 – Land surface products, parameter category 0: vegetation/biomass		
Number	Parameter	Units
23	Column-integrated soil water (see Note 3)	kg m ⁻²
24	Heat flux	W m ⁻²
25	Volumetric soil moisture	m ³ m ⁻³
26	Wilting point	kg m ⁻³
27	Volumetric wilting point	m ³ m ⁻³
28	Leaf area index	Numeric
29	Evergreen forest cover	Proportion
30	Deciduous forest cover	Proportion
31	Normalized differential vegetation index (NDVI)	Numeric
32	Root depth of vegetation	m
33	Water runoff and drainage (see Note 4)	kg m ⁻²
34	Surface water runoff (see Note 4)	kg m ⁻²
35	Tile class	(Code table 4.243)
36	Tile fraction	Proportion
37	Tile percentage	%
38	Soil volumetric ice content (water equivalent) (see Note 5)	m ³ m ⁻³
39	Evapotranspiration rate	kg m ⁻² s ⁻¹
40	Potential evapotranspiration rate	kg m ⁻² s ⁻¹
41	Snow melt rate	kg m ⁻² s ⁻¹
42	Water runoff and drainage rate	kg m ⁻² s ⁻¹
43	Drainage direction	(Code table 4.250)
44	Upstream area	m ²
45	Wetland cover	Proportion
46	Wetland type	(Code table 4.239)
47	Irrigation cover	Proportion
48	C4 crop cover (see Note 7)	Proportion
49	C4 grass cover (see Note 7)	Proportion
50	Skin reservoir content	
51	Surface runoff rate	
52	Subsurface runoff rate	
53	Low-vegetation cover	
54	High-vegetation cover	
55	Leaf area index, low-vegetation	
56	Leaf area index, high-vegetation	
57	Type of low-vegetation	
58	Type of high-vegetation	
59	Net ecosystem exchange flux (see Note 8)	
60	Gross primary production flux (see Note 8)	
61	Ecosystem respiration flux (see Note 8)	
4562-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Notes:

- (1) Parameter deprecated. See Regulation 92.6.2 and use another parameter instead.
- (2) It is recommended not to use this parameter, but another one with a more descriptive unit.
- (3) Parameter deprecated. Use another parameter in parameter category 3: soil products instead.
- (4) Statistical process 1 (Accumulation) does not change units.
- (5) For parameter 38 (Parameter category 0), ice volume is expressed as if the ice content were melted to liquid water and then its volume measured in the liquid state. This may be understood in the same manner as water equivalent snow depth.

- (6) The listed units for this parameter appear not to be appropriate for evapotranspiration. Instead, it is recommended to use parameter 39 with statistical process 1 (accumulation) in order to report evapotranspiration in units of kg m^{-2} .
- (7) A C4 plant is a type of plant that uses a specific photosynthesis mechanism (C4 photosynthesis) in order to avoid photorespiration. Other types of plants are C3 and CAM.
- (8) This parameter can be used with templates for chemical constituents to specify a chemical species if needed, for instance: Net ecosystem CO₂ exchange flux or Net ecosystem CH₄ exchange flux.

Product discipline 2 – Land surface products, parameter category 3: soil products

Code table 4.2
Product discipline 2 – Land surface products, parameter category 3: soil products

Number	Parameter	Units
0	Soil type	(Code table 4.213)
1	Upper layer soil temperature (see Note 1)	K
2	Upper layer soil moisture (see Note 1)	kg m^{-3}
3	Lower layer soil moisture (see Note 1)	kg m^{-3}
4	Bottom layer soil temperature (see Note 1)	K
5	Liquid volumetric soil moisture (non-frozen) (see Note 2)	Proportion
6	Number of soil layers in root zone	Numeric
7	Transpiration stress-onset (soil moisture) (see Note 2)	Proportion
8	Direct evaporation cease (soil moisture) (see Note 2)	Proportion
9	Soil porosity (see Note 2)	Proportion
10	Liquid volumetric soil moisture (non-frozen)	$\text{m}^3 \text{m}^{-3}$
11	Volumetric transpiration stress-onset (soil moisture)	$\text{m}^3 \text{m}^{-3}$
12	Transpiration stress-onset (soil moisture)	kg m^{-3}
13	Volumetric direct evaporation cease (soil moisture)	$\text{m}^3 \text{m}^{-3}$
14	Direct evaporation cease (soil moisture)	kg m^{-3}
15	Soil porosity	$\text{m}^3 \text{m}^{-3}$
16	Volumetric saturation of soil moisture	$\text{m}^3 \text{m}^{-3}$
17	Saturation of soil moisture	kg m^{-3}
18	Soil temperature	K
19	Soil moisture	kg m^{-3}
20	Column-integrated soil moisture	kg m^{-2}
21	Soil ice	kg m^{-3}
22	Column-integrated soil ice	kg m^{-2}
23	Liquid water in snow pack	kg m^{-2}
24	Frost index	K day^{-1}
25	Snow depth at elevation bands	kg m^{-2}
26	Soil heat flux	W m^{-2}
27	Soil depth	m
28	Snow temperature	K
29	Ice temperature	K
30–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Parameter deprecated. See Regulation 92.6.2 and use another parameter instead.
- (2) It is recommended not to use this parameter, but another one with a more descriptive unit.

Product discipline 2 – Land surface products, parameter category 4: fire weather products

Code table 4.2		
Product discipline 2 – Land surface products, parameter category 4: fire weather products		
Number	Parameter	Units
0	Fire outlook	Code table 4.224
1	Fire outlook due to dry thunderstorm	Code table 4.224
2	Haines index	Numeric
3	Fire burned area	%
4	Fosberg index (see Note)	Numeric
5	Forest Fire Weather Index (Canadian Forest Service)	Numeric
6	Fine Fuel Moisture Code (Canadian Forest Service)	Numeric
7	Duff Moisture Code (Canadian Forest Service)	Numeric
8	Drought Code (Canadian Forest Service)	Numeric
9	Initial Fire Spread Index (Canadian Forest Service)	Numeric
10	Fire Buildup Index (Canadian Forest Service)	Numeric
11	Fire Daily Severity Rating (Canadian Forest Service)	Numeric
12	Keetch-Byram drought index	Numeric
13	Drought factor (as defined by the Australian Forest Service)	Numeric
14	Rate of spread (as defined by the Australian Forest Service)	m/s
15	Fire danger index (as defined by the Australian Forest Service)	Numeric
16	Spread component (as defined by the US Forest Service National Fire Danger Rating System)	Numeric
17	Burning index (as defined by the US Forest Service National Fire Danger Rating System)	Numeric
18	Ignition component (as defined by the US Forest Service National Fire Danger Rating System)	%
19	Energy release component (as defined by the US Forest Service National Fire Danger Rating System)	Joule/m ²
20	<u>Burning area</u>	<u>%</u>
21	<u>Burnable area</u>	<u>%</u>
22	<u>Unburnable area</u>	<u>%</u>
23	<u>Fuel load</u>	<u>kg m⁻²</u>
24	<u>Combustion completeness</u>	<u>%</u>
25	<u>Fuel moisture content</u>	<u>kg kg⁻¹</u>
26	<u>Wildfire potential (as defined by the US NOAA Global Systems Laboratory)</u>	<u>Numeric</u>
20–191	Reserved	
192 27–254	Reserved for local use	
255	Missing	

Note: The Fosberg index denotes the potential influence of weather on a wildland fire. It takes into account the combined effects of temperature, wind speed, relative humidity and precipitation. Higher values indicate a higher potential impact.

Product discipline 2 – Land surface products, parameter category 5: glaciers and inland ice

Code table 4.2		
Product discipline 2 – Land surface products, parameter category 5: glaciers and inland ice		
Number	Parameter	Units
0	Glacier cover (see Note)	Proportion
1	Glacier temperature	K
2–191	Reserved	
192–254	Reserved for local use	

Code table 4.2

Product discipline 2 – Land surface products, parameter category 5: glaciers and inland ice

Number	Parameter	Units
255	Missing	

Note: A value strictly above 0.5 is treated as glacier. A value equal or below 0.5 is treated as land without glacier.

Product discipline 2 - Land surface products, parameter category 6: urban areas

Code table 4.2

Product discipline 2 - Land surface products, parameter category 6: urban areas

Number	Parameter	Units
0	Urban cover	Proportion
1	Road cover	Proportion
2	Building cover	Proportion
3	Building height	m
4	Vertical-to-horizontal area fraction	m ² m ⁻²
5	Standard deviation of building height	m
6-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 3 – Space products, parameter category 0: image format products

Code table 4.2

Product discipline 3 – Space products, parameter category 0: image format products

Number	Parameter	Units
0	Scaled radiance	Numeric
1	Scaled albedo	Numeric
2	Scaled brightness temperature	Numeric
3	Scaled precipitable water	Numeric
4	Scaled lifted index	Numeric
5	Scaled cloud top pressure	Numeric
6	Scaled skin temperature	Numeric
7	Cloud mask	Code table 4.217
8	Pixel scene type	Code table 4.218
9	Fire detection indicator	Code table 4.223
10-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 3 – Space products, parameter category 1: quantitative products

Code table 4.2

Product discipline 3 – Space products, parameter category 1: quantitative products

Number	Parameter	Units
0	Estimated precipitation	kg m ⁻²
1	Instantaneous rain rate	kg m ⁻² s ⁻¹
2	Cloud top height	m

Code table 4.2
Product discipline 3 – Space products, parameter category 1: quantitative products

Number	Parameter	Units
3	Cloud top height quality indicator	Code table 4.219
4	Estimated u-component of wind	m s^{-1}
5	Estimated v-component of wind	m s^{-1}
6	Number of pixel used	Numeric
7	Solar zenith angle	°
8	Relative azimuth angle	°
9	Reflectance in 0.6 micron channel	%
10	Reflectance in 0.8 micron channel	%
11	Reflectance in 1.6 micron channel	%
12	Reflectance in 3.9 micron channel	%
13	Atmospheric divergence	s^{-1}
14	Cloudy brightness temperature	K
15	Clear-sky brightness temperature	K
16	Cloudy radiance (with respect to wave number)	$\text{W m}^{-1} \text{sr}^{-1}$
17	Clear-sky radiance (with respect to wave number)	$\text{W m}^{-1} \text{sr}^{-1}$
18	Reserved	
19	Wind speed	m s^{-1}
20	Aerosol optical thickness at 0.635 μm	
21	Aerosol optical thickness at 0.810 μm	
22	Aerosol optical thickness at 1.640 μm	
23	Angstrom coefficient	
24–26	Reserved	
27	Bidirectional reflectance factor (see Note 1)	Numeric
28	Brightness temperature	K
29	Scaled radiance (see Note 2)	Numeric
30	Reflectance in 0.4 micron channel	%
31–97	Reserved	
98	Correlation coefficient between MPE rain rates for the co-located IR data and the microwave data rain rates	Numeric
99	Standard deviation between MPE rain rates for the co-located IR data and the microwave data rain rates	$\text{kg m}^{-2} \text{s}^{-1}$
100–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) The ratio of the radiant flux reflected by a surface to that reflected into the same reflected-beam geometry and wavelength range by an ideal (lossless) and diffuse (Lambertian) standard surface, irradiated under the same conditions.
- (2) Top of atmosphere radiance observed by a sensor, multiplied by pi and divided by the in-band solar irradiance.

Product discipline 3 – Space products, parameter category 2: cloud properties

Code table 4.2
Product discipline 3 – Space products, parameter category 2: cloud properties

Number	Parameter	Units
0	Clear sky probability	%
1	Cloud top temperature	K
2	Cloud top pressure	Pa
3	Cloud type	Code table 4.218
4	Cloud phase	Code table 4.218

Code table 4.2		
<i>Product discipline 3 – Space products, parameter category 2: cloud properties</i>		
Number	Parameter	Units
5	Cloud optical depth	Numeric
6	Cloud particle effective radius	m
7	Cloud liquid water path	kg m ⁻²
8	Cloud ice water path	kg m ⁻²
9	Cloud albedo	Numeric
10	Cloud emissivity	Numeric
11	Effective absorption optical depth ratio	Numeric
30	Measurement cost	Numeric
31	Upper layer cloud optical depth (see Note)	Numeric
32	Upper layer cloud top pressure (see Note)	Pa
33	Upper layer cloud effective radius (see Note)	m
34	Error in upper layer cloud optical depth (see Note)	Numeric
35	Error in upper layer cloud top pressure (see Note)	Pa
36	Error in upper layer cloud effective radius (see Note)	m
37	Lower layer cloud optical depth (see Note)	Numeric
38	Lower layer cloud top pressure (see Note)	Pa
39	Error in lower layer cloud optical depth (see Note)	Numeric
40	Error in lower layer cloud top pressure (see Note)	Pa

Note: Numbers 31 to 40 are deprecated.

Product discipline 3 – Space products, parameter category 3: flight rule conditions

Code table 4.2		
<i>Product discipline 3 – Space products, parameter category 3: flight rule conditions</i>		
Number	Parameter	Units
0	Probability of encountering marginal visual flight rule conditions	%
1	Probability of encountering low instrument flight rule conditions	%
2	Probability of encountering instrument flight rule conditions	%

Product discipline 3 – Space products, parameter category 4: volcanic ash

Code table 4.2		
<i>Product discipline 3 – Space products, parameter category 4: volcanic ash</i>		
Number	Parameter	Units
0	Volcanic ash probability	%
1	Volcanic ash cloud top temperature	K
2	Volcanic ash cloud top pressure	Pa
3	Volcanic ash cloud top height	m
4	Volcanic ash cloud emissivity	Numeric
5	Volcanic ash effective absorption optical depth ratio	Numeric
6	Volcanic ash cloud optical depth	Numeric
7	Volcanic ash column density	kg m ⁻²
8	Volcanic ash particle effective radius	m

Product discipline 3 – Space products, parameter category 5: sea-surface temperature

Code table 4.2
Product discipline 3 – Space products, parameter category 5: sea-surface temperature

Number	Parameter	Units
0	Interface sea-surface temperature (see Note 1)	K
1	Skin sea-surface temperature (see Note 2)	K
2	Sub-skin sea-surface temperature (see Note 3)	K
3	Foundation sea-surface temperature (see Note 4)	K
4	Estimated bias between sea-surface temperature and standard	K
5	Estimated standard deviation between sea-surface temperature and standard	K

Notes:

- (1) Theoretical temperature at the precise air-sea interface.
- (2) Temperature of the water across a very small depth (approximately the upper 20 micrometers).
- (3) Temperature at the base of the thermal skin layer.
- (4) Temperature of the water column free of diurnal temperature variability or equal to the SST sub-skin in the absence of any diurnal signal.

Product discipline 3 – Space products, parameter category 6: solar radiation

Code table 4.2
Product discipline 3 – Space products, parameter category 6: solar radiation

Number	Parameter	Units
0	Global solar irradiance (see Note 1)	W m ⁻²
1	Global solar exposure (see Note 2)	J m ⁻²
2	Direct solar irradiance (see Note 3)	W m ⁻²
3	Direct solar exposure (see Note 4)	J m ⁻²
4	Diffuse solar irradiance (see Note 5)	W m ⁻²
5	Diffuse solar exposure (see Note 6)	J m ⁻²

Notes:

- (1) The solar flux per unit area received from a solid angle of 2π sr on a horizontal surface.
- (2) Time integral of global solar irradiance.
- (3) The solar flux per unit area received from the solid angle of the sun's disc on a surface normal to the sun direction.
- (4) Time integral of direct solar irradiance.
- (5) The solar flux per unit area received from a solid angle of 2π sr, except for the solid angle of the sun's disc, on a horizontal surface.
- (6) Time integral of diffuse solar irradiance.

Product discipline 4 – Space weather products, parameter category 0: temperature

Code table 4.2
Product discipline 4 – Space weather products, parameter category 0: temperature

Number	Parameter	Units
0	Temperature	K
1	Electron temperature	K
2	Proton temperature	K

Code table 4.2

Product discipline 4 – Space weather products, parameter category 0: temperature

Number	Parameter	Units
3	Ion temperature	K
4	Parallel temperature	K
5	Perpendicular temperature	K
6-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 1: momentum

Code table 4.2

Product discipline 4 – Space weather products, parameter category 1: momentum

Number	Parameter	Units
0	Velocity magnitude (speed)	m s-1
1	1st vector component of velocity (coordinate system dependent)	m s-1
2	2nd vector component of velocity (coordinate system dependent)	m s-1
3	3rd vector component of velocity (coordinate system dependent)	m s-1
4-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 2: charged particle mass and number

Code table 4.2

Product discipline 4 – Space weather products, parameter category 2: charged particle mass and number

Number	Parameter	Units
0	Particle number density	m-3
1	Electron density	m-3
2	Proton density	m-3
3	Ion density	m-3
4	Vertical total electron content	TECU
5	HF absorption frequency	Hz
6	HF absorption	dB
7	Spread F	m
8	h'F	m
9	Critical frequency	Hz
10	Maximal usable frequency (MUF)	Hz
11	Peak height (hm)	m
12	Peak density (Nm)	m-3
13	Equivalent slab thickness (tau)	km
14-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 3: electric and magnetic fields

Code table 4.2

Product discipline 4 – Space weather products, parameter category 3: electric and magnetic fields

Number	Parameter	Units
0	Magnetic field magnitude	T
1	1st vector component of magnetic field	T
2	2nd vector component of magnetic field	T
3	3rd vector component of magnetic field	T
4	Electric field magnitude	V m-1
5	1st vector component of electric field	V m-1
6	2nd vector component of electric field	V m-1
7	3rd vector component of electric field	V m-1
8-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 4: energetic particles

Code table 4.2

Product discipline 4 – Space weather products, parameter category 4: energetic particles

Number	Parameter	Units
0	Proton flux (differential)	(m2 s sr eV)-1
1	Proton flux (integral)	(m2 s sr)-1
2	Electron flux (differential)	(m2 s sr eV)-1
3	Electron flux (integral)	(m2 s sr)-1
4	Heavy ion flux (differential)	(m2 s sr eV/nuc)-1
5	Heavy ion flux (integral)	(m2 s sr)-1
6	Cosmic ray neutron flux	h^{-1}
7-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 5: waves

Code table 4.2

Product discipline 4 – Space weather products, parameter category 5: waves

Number	Parameter	Units
0	Amplitude	dB
1	Phase	rad
2	Frequency	Hz
3	Wavelength	m
4-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 6: solar electromagnetic emissions*Code table 4.2**Product discipline 4 – Space weather products, parameter category 6: solar electromagnetic emissions*

Number	Parameter	Units
0	Integrated solar irradiance	W m ⁻²
1	Solar X-ray flux (XRS long)	W m ⁻²
2	Solar X-ray flux (XRS short)	W m ⁻²
3	Solar EUV irradiance	W m ⁻²
4	Solar spectral irradiance	W m ⁻² nm ⁻¹
5	F10.7	W m ⁻² Hz ⁻¹
6	Solar radio emissions	W m ⁻² Hz ⁻¹
7-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 7: terrestrial electromagnetic emissions*Code table 4.2**Product discipline 4 – Space weather products, parameter category 7: terrestrial electromagnetic emissions*

Number	Parameter	Units
0	Limb intensity	J m ⁻² s ⁻¹
1	Disk intensity	J m ⁻² s ⁻¹
2	Disk intensity day	J m ⁻² s ⁻¹
3	Disk intensity night	J m ⁻² s ⁻¹
4-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 8: imagery*Code table 4.2**Product discipline 4 – Space weather products, parameter category 8: imagery*

Number	Parameter	Units
0	X-ray radiance	W sr ⁻¹ m ⁻²
1	EUV radiance	W sr ⁻¹ m ⁻²
2	H-alpha radiance	W sr ⁻¹ m ⁻²
3	White light radiance	W sr ⁻¹ m ⁻²
4	CaII-K radiance	W sr ⁻¹ m ⁻²
5	White light coronagraph radiance	W sr ⁻¹ m ⁻²
6	Heliospheric radiance	W sr ⁻¹ m ⁻²
7	Thematic mask	Numeric
8	Solar induced chlorophyll fluorescence	W sr ⁻¹ m ⁻²
9-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 9: ion-neutral coupling

Code table 4.2

Product discipline 4 – Space weather products, parameter category 9: ion-neutral coupling

Number	Parameter	Units
0	Pedersen conductivity	S m ⁻¹
1	Hall conductivity	S m ⁻¹
2	Parallel conductivity	S m ⁻¹
3-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 4 – Space weather products, parameter category 10: space weather indices

Code table 4.2

Product discipline 4 – Space weather products, parameter category 10: space weather indices

Number	Parameter	Units
0	Scintillation index (sigma phi)	rad
1	Scintillation index S4	Numeric
2	Rate of change of TEC index (ROTI)	TECU/min
3	Disturbance ionosphere index spatial gradient (DIXSG)	Numeric
4	Along arc TEC rate (AATR)	TECU/min
5	Kp	Numeric
6	Equatorial disturbance storm time index (Dst)	nT
7	Auroral electrojet (AE)	nT
8-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 10 – Oceanographic products, parameter category 0: waves

Code table 4.2

Product discipline 10 – Oceanographic products, parameter category 0: waves

Number	Parameter	Units
0	Wave spectra (1)	–
1	Wave spectra (2)	–
2	Wave spectra (3)	–
3	Significant height of combined wind waves and swell	m
4	Direction of wind waves	degree true
5	Significant height of wind waves	m
6	Mean period of wind waves	s
7	Direction of swell waves	degree true
8	Significant height of swell waves	m
9	Mean period of swell waves	s
10	Primary wave direction	degree true
11	Primary wave mean period	s
12	Secondary wave direction	degree true
13	Secondary wave mean period	s
14	Mean direction of combined wind waves and swell	degree true
15	Mean period of combined wind waves and swell	s
16	Coefficient of drag with waves	–
17	Friction velocity	m s ⁻¹

Code table 4.2
Product discipline 10 – Oceanographic products, parameter category 0: waves

Number	Parameter	Units
18	Wave stress	N m ⁻²
19	Normalized wave stress	–
20	Mean square slope of waves	–
21	u-component surface Stokes drift	m s ⁻¹
22	v-component surface Stokes drift	m s ⁻¹
23	Period of maximum individual wave height	s
24	Maximum individual wave height	m
25	Inverse mean wave frequency	s
26	Inverse mean frequency of wind waves	s
27	Inverse mean frequency of total swell	s
28	Mean zero-crossing wave period	s
29	Mean zero-crossing period of wind waves	s
30	Mean zero-crossing period of total swell	s
31	Wave directional width	–
32	Directional width of wind waves	–
33	Directional width of total swell	–
34	Peak wave period	s
35	Peak period of wind waves	s
36	Peak period of total swell	s
37	Altimeter wave height	m
38	Altimeter corrected wave height	m
39	Altimeter range relative correction	–
40	10-metre neutral wind speed over waves	m s ⁻¹
41	10-metre wind direction over waves	°
42	Wave energy spectrum	m ² s rad ⁻¹
43	Kurtosis of the sea-surface elevation due to waves	–
44	Benjamin–Feir index	–
45	Spectral peakedness factor	s ⁻¹
46	Peak wave direction	°
47	Significant wave height of first swell partition	m
48	Significant wave height of second swell partition	m
49	Significant wave height of third swell partition	m
50	Mean wave period of first swell partition	s
51	Mean wave period of second swell partition	s
52	Mean wave period of third swell partition	s
53	Mean wave direction of first swell partition	°
54	Mean wave direction of second swell partition	°
55	Mean wave direction of third swell partition	°
56	Wave directional width of first swell partition	–
57	Wave directional width of second swell partition	–
58	Wave directional width of third swell partition	–
59	Wave frequency width of first swell partition	–
60	Wave frequency width of second swell partition	–
61	Wave frequency width of third swell partition	–
62	Wave frequency width	–
63	Frequency width of wind waves	–
64	Frequency width of total swell	–
65	Peak wave period of first swell partition	s
66	Peak wave period of second swell partition	s
67	Peak wave period of third swell partition	s
68	Peak wave direction of first swell partition	degree true
69	Peak wave direction of second swell partition	degree true

Code table 4.2
Product discipline 10 – Oceanographic products, parameter category 0: waves

Number	Parameter	Units
70	Peak wave direction of third swell partition	degree true
71	Peak direction of wind waves	degree true
72	Peak direction of total swell	degree true
73	Whitecap fraction	fraction
74	<u>Mean direction of total swell</u>	<u>degree</u>
75	<u>Mean direction of wind waves</u>	<u>degree</u>
76	<u>Charnock (see Note 2)</u>	<u>Numeric</u>
77	<u>Wave Spectral Skewness</u>	<u>Numeric</u>
78	<u>Wave energy flux magnitude</u>	<u>W m⁻¹</u>
79	<u>Wave energy flux mean direction</u>	<u>degree true</u>
80	<u>Ratio of wave angular and frequency width</u>	<u>Numeric</u>
81	<u>Free convective velocity over the oceans</u>	<u>m s⁻¹</u>
82	<u>Air density over the oceans</u>	<u>kg m⁻³</u>
83	<u>Normalized energy flux into waves (see Note 3)</u>	<u>Numeric</u>
84	<u>Normalized stress into ocean (see Note 3)</u>	<u>Numeric</u>
85	<u>Normalized energy flux into ocean (see Note 3)</u>	<u>Numeric</u>
86	<u>Surface elevation variance due to waves (over all frequencies and directions)</u>	<u>m² s rad⁻¹</u>
87	<u>Wave induced mean sea level correction</u>	<u>m</u>
88	<u>Spectral width index</u>	<u>Numeric</u>
89	<u>Number of events in freak waves statistics</u>	<u>Numeric</u>
90	<u>u-component of surface momentum flux into ocean</u>	<u>N m⁻²</u>
91	<u>v-component of surface momentum flux into ocean</u>	<u>N m⁻²</u>
92	<u>Wave turbulent energy flux into ocean</u>	<u>W m⁻²</u>
93–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) Further information concerning the wave parameters can be found in the *Guide to Wave Analysis and Forecasting* (WMO-No. 702).
- (2) The Charnock parameter accounts for increased aerodynamic roughness as wave heights grow due to increasing surface stress. It depends on the wind speed, wave age and other aspects of the sea state and is used to calculate how much the waves slow down the wind.
- (3) Parameters are normalised by being divided by the product of air density and the square of the friction velocity.

Product discipline 10 – Oceanographic products, parameter category 1: currents

Code table 4.2
Product discipline 10 – Oceanographic products, parameter category 1: currents

Number	Parameter	Units
0	Current direction	degree true
1	Current speed	m s ⁻¹
2	u-component of current	m s ⁻¹
3	v-component of current	m s ⁻¹
4	Rip current occurrence probability	%
5	<u>Eastward current</u>	<u>m s⁻¹</u>
6	<u>Northward current</u>	<u>m s⁻¹</u>
7–191	Reserved	
192–254	Reserved for local use	

Code table 4.2		
Product discipline 10 – Oceanographic products, parameter category 1: currents		
Number	Parameter	Units
255	Missing	

Product discipline 10 – Oceanographic products, parameter category 2: ice

Code table 4.2		
Product discipline 10 – Oceanographic products, parameter category 2: ice		
Number	Parameter	Units
0	Ice cover	Proportion
1	Ice thickness	m
2	Direction of ice drift	degree true
3	Speed of ice drift	m s ⁻¹
4	u-component of ice drift	m s ⁻¹
5	v-component of ice drift	m s ⁻¹
6	Ice growth rate	m s ⁻¹
7	Ice divergence	s ⁻¹
8	Ice temperature	K
9	Module of ice internal pressure (see Note)	Pa m
10	Zonal vector component of vertically integrated ice internal pressure	Pa m
11	Meridional vector component of vertically integrated ice internal pressure	Pa m
12	Compressive ice strength	N m ⁻¹
13	Snow temperature (over sea ice)	K
14	Albedo	Numeric
15	<u>Sea ice volume per unit area</u>	<u>m³ m⁻²</u>
16	<u>Snow volume over sea ice per unit area</u>	<u>m³ m⁻²</u>
17	<u>Sea ice heat content</u>	<u>J m⁻²</u>
18	<u>Snow over sea ice heat content</u>	<u>J m⁻²</u>
19	<u>Ice freeboard thickness</u>	<u>m</u>
20	<u>Ice melt pond fraction</u>	<u>fraction</u>
21	<u>Ice melt pond depth</u>	<u>m</u>
22	<u>Ice melt pond volume per unit area</u>	<u>m³ m⁻²</u>
23	<u>Sea ice fraction tendency due to parameterization</u>	<u>s⁻¹</u>
15 24–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Note: Ice internal pressure or stress (Pa m) is the integrated pressure across the vertical thickness of a layer of ice. It is produced when concentrated ice reacts to external forces such as wind and ocean currents.

Product discipline 10 – Oceanographic products, parameter category 3: surface properties

Code table 4.2		
Product discipline 10 – Oceanographic products, parameter category 3: surface properties		
Number	Parameter	Units
0	Water temperature	K
1	Deviation of sea level from mean	m
2	Heat exchange coefficient	–
3	Practical salinity	Numeric
4	Downward heat flux	W m ⁻²

Code table 4.2		
Product discipline 10 – Oceanographic products, parameter category 3: surface properties		
Number	Parameter	Units
5	Eastward surface stress	N m^{-2}
6	Northward surface stress	N m^{-2}
7	x-component surface stress (see Note)	N m^{-2}
8	y-component surface stress (see Note)	N m^{-2}
9	Thermosteric change in sea-surface height	m
10	Halosteric change in sea-surface height	m
11	Steric change in sea-surface height	m
12	Sea salt flux	$\text{kg m}^{-2} \text{s}^{-1}$
13	Net upward water flux	$\text{kg m}^{-2} \text{s}^{-1}$
14	Eastward surface water velocity	m s^{-1}
15	Northward surface water velocity	m s^{-1}
16	x-component of surface water velocity	m s^{-1}
17	y-component of surface water velocity	m s^{-1}
18	Heat flux correction	W m^{-2}
19	Sea surface height tendency due to parameterization	m s^{-1}
20	Deviation of sea level from mean with inverse barometer correction	m
1921–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Note: The x- and y- components of surface stress are not necessarily equivalent to the u- and v- components (eastward/northward). The x- and y- components strictly follow the defined coordinate system which may or may not follow the eastward and northward directions.

Product discipline 10 – Oceanographic products, parameter category 4: subsurface properties

Code table 4.2		
Product discipline 10 – Oceanographic products, parameter category 4: subsurface properties		
Number	Parameter	Units
0	Main thermocline depth	m
1	Main thermocline anomaly	m
2	Transient thermocline depth	m
3	Salinity	kg kg^{-1}
4	Ocean vertical heat diffusivity	$\text{m}^2 \text{s}^{-1}$
5	Ocean vertical salt diffusivity	$\text{m}^2 \text{s}^{-1}$
6	Ocean vertical momentum diffusivity	$\text{m}^2 \text{s}^{-1}$
7	Bathymetry	m
8–10	Reserved	
11	Shape factor with respect to salinity profile	–
12	Shape factor with respect to temperature profile in thermocline	–
13	Attenuation coefficient of water with respect to solar radiation	m^{-1}
14	Water depth	m
15	Water temperature	K
16	Water density (rho)	kg m^{-3}
17	Water density anomaly (sigma) (see Note)	kg m^{-3}
18	Water potential temperature (theta)	K
19	Water potential density (rho theta)	kg m^{-3}
20	Water potential density anomaly (sigma theta) (see Note 1)	kg m^{-3}
21	Practical salinity	Numeric

Code table 4.2

Product discipline 10 – Oceanographic products, parameter category 4: subsurface properties

Number	Parameter	Units
22	Water column-integrated heat content	J m ⁻²
23	Eastward water velocity	m s ⁻¹
24	Northward water velocity	m s ⁻¹
25	x-component water velocity (see Note 2)	m s ⁻¹
26	y-component water velocity (see Note 2)	m s ⁻¹
27	Upward water velocity	m s ⁻¹
28	Vertical eddy diffusivity	m ² s ⁻¹
29	<u>Bottom pressure equivalent height</u>	<u>m</u>
30	<u>Fresh water flux into sea water from rivers</u>	<u>kg m⁻² s⁻¹</u>
31	<u>Fresh water flux correction</u>	<u>kg m⁻² s⁻¹</u>
32	<u>Virtual salt flux into sea water</u>	<u>g kg⁻¹ m⁻² s⁻¹</u>
33	<u>Virtual salt flux correction</u>	<u>g kg⁻¹ m⁻² s⁻¹</u>
34	<u>Sea water temperature tendency due to Newtonian relaxation</u>	<u>K s⁻¹</u>
35	<u>Sea water salinity tendency due to Newtonian relaxation</u>	<u>g kg⁻¹ s⁻¹</u>
36	<u>Sea water temperature tendency due to parameterization</u>	<u>K s⁻¹</u>
37	<u>Sea water salinity tendency due to parameterization</u>	<u>g kg⁻¹ s⁻¹</u>
38	<u>Eastward sea water velocity tendency due to parameterization</u>	<u>m s⁻²</u>
39	<u>Northward sea water velocity tendency due to parameterization</u>	<u>m s⁻²</u>
40	<u>Sea water temperature tendency due to direct bias correction</u>	<u>K s⁻¹</u>
41	<u>Sea water salinity tendency due to direct bias correction</u>	<u>g kg⁻¹ s⁻¹</u>
2942-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Notes:

- (1) Numbers 17 and 20 are deviations from the reference value of 1 000 kg m⁻³.
- (2) The x- and y- components of water velocity are not necessarily equivalent to the u- and v- components (eastward/northward). The x- and y- components strictly follow the defined coordinate system which may or may not follow the eastward and northward directions.

Product discipline 10 – Oceanographic products, parameter category 191: miscellaneous

Code table 4.2

Product discipline 10 – Oceanographic products, parameter category 191: miscellaneous

Number	Parameter	Units
0	Seconds prior to initial reference time(defined in Section 1)	s
1	Meridional overturning stream function	m ³ s ⁻¹
2	Reserved	
3	Days since last observation	d
4	Barotropic stream function	m ³ s ⁻¹
5-191	Reserved	
192-254	Reserved for local use	
255	Missing	

Product discipline 20 – Health and socioeconomic impacts, parameter category 0: health indicators

Code table 4.2
Product discipline 20 – Health and socioeconomic impacts, parameter category 0: health indicators

Number	Parameter	Units
0	Universal thermal climate index	K
1	Mean radiant temperature	K
2	Wet-bulb globe temperature (see Note)	K
3	Globe temperature	K
4	Humidex	K
5	Effective temperature	K
6	Normal effective temperature	K
7	Standard effective temperature	K
8	Physiological equivalent temperature	K
9–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Note: Higher values indicate that heat stress is important. Interpretation of values can vary among organizations and use. See example in the ISO certification (ISO 7243: 1989, 2017; Parsons, 2013).

Product discipline 20 – Health and socioeconomic impacts, parameter category 1: epidemiology

Code table 4.2
Product discipline 20 – Health and socioeconomic impacts, parameter category 1: epidemiology

Number	Parameter	Units
0	Malaria cases	Fraction
1	Malaria circumsporozoite protein rate	Fraction
2	Plasmodium falciparum entomological inoculation rate	Bites per day per person
3	Human bite rate by anopheles vectors	Bites per day per person
4	Malaria immunity	Fraction
5	Falciparum parasite rates	Fraction
6	Detectable falciparum parasite ratio (after day 10)	Fraction
7	Anopheles vector to host ratio	Fraction
8	Anopheles vector number	Number m-2
9	Fraction of malarial vector reproductive habitat	Fraction
10–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Product discipline 20 – Health and socioeconomic impacts, parameter category 2: socioeconomic indicators

Code table 4.2
Product discipline 20 – Health and socioeconomic impacts, parameter category 2: socioeconomic indicators

Number	Parameter	Units
0	Population density	Person m-2
1–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Code table 4.3 – Type of generating process

Code table 4.3	
Code figure	Meaning
0	Analysis
1	Initialization
2	Forecast
3	Bias corrected forecast
4	Ensemble forecast
5	Probability forecast
6	Forecast error
7	Analysis error
8	Observation
9	Climatological
10	Probability-weighted forecast
11	Bias-corrected ensemble forecast
12	Post-processed analysis (see Note 1)
13	Post-processed forecast (see Note 1)
14	Nowcast
15	Hindcast
16	Physical retrieval
17	Regression analysis
18	Difference between two forecasts
19	First guess
20	Analysis increment (see Note 2)
21	Initialization increment for analysis (see Note 3)
22–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

- (1) Code figures 12 and 13 are intended in cases where code figures 0 and 2 may not be sufficient to indicate that significant post-processing has taken place on an initial analysis or forecast output.
- (2) Analysis increment represents analysis minus first guess
- (3) Initialized analysis increment represents initialized analysis minus analysis

Code table 4.4 – Indicator of unit of time range

Code table 4.4	
Code figure	Meaning
0	Minute
1	Hour
2	Day
3	Month
4	Year
5	Decade (10 years)
6	Normal (30 years)
7	Century (100 years)
8–9	Reserved
10	3 hours
11	6 hours

Code table 4.4	
Code figure	Meaning
12	12 hours
13	Second
14–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.5 – Fixed surface types and units

Code table 4.5		
Code figure	Meaning	Unit
0	Reserved	
1	Ground or water surface	–
2	Cloud base level	–
3	Level of cloud tops	–
4	Level of 0 °C isotherm	–
5	Level of adiabatic condensation lifted from the surface	–
6	Maximum wind level	–
7	Tropopause	–
8	Nominal top of the atmosphere	–
9	Sea bottom	–
10	Entire atmosphere	–
11	Cumulonimbus (CB) base	m
12	Cumulonimbus (CB) top	m
13	Lowest level where vertically integrated cloud cover exceeds the specified percentage (cloud base for a given percentage cloud cover)	%
14	Level of free convection (LFC)	–
15	Convective condensation level (CCL)	–
16	Level of neutral buoyancy or equilibrium level (LNB)	–
17	Departure level of the most unstable parcel of air (MUDL)	–
18	Departure level of a mixed layer parcel of air with specified layer depth	Pa
19	Reserved	
20	Isothermal level	K
21	Lowest level where mass density exceeds the specified value (base for a given threshold of mass density)	kg m ⁻³
22	Highest level where mass density exceeds the specified value (top for a given threshold of mass density)	kg m ⁻³
23	Lowest level where air concentration exceeds the specified value (base for a given threshold of air concentration)	Bq m ⁻³
24	Highest level where air concentration exceeds the specified value (top for a given threshold of air concentration)	Bq m ⁻³
25	Highest level where radar reflectivity exceeds the specified value (echo top for a given threshold of reflectivity)	dBZ
26	Convective cloud layer base	m
27	Convective cloud layer top	m
28–29	Reserved	
30	Specified radius from the centre of the Sun	m
31	Solar photosphere	
32	Ionospheric D-region level	

Code table 4.5

Code figure	Meaning	Unit
33	Ionospheric E-region level	
34	Ionospheric F1-region level	
35	Ionospheric F2-region level	
36–99	Reserved	
100	Isobaric surface	Pa
101	Mean sea level	
102	Specific altitude above mean sea level	m
103	Specified height level above ground	m
104	Sigma level	"sigma" value
105	Hybrid level	–
106	Depth below land surface	m
107	Isentropic (theta) level	K
108	Level at specified pressure difference from ground to level	Pa
109	Potential vorticity surface	$\text{K m}^2 \text{ kg}^{-1} \text{ s}^{-1}$
110	Reserved	
111	Eta level (see Note 1)	–
112	Reserved	
113	Logarithmic hybrid level	
114	Snow level	Numeric
115	Sigma height level (see Note 4)	–
116	Reserved	
117	Mixed layer depth	m
118	Hybrid height level (see Note 2)	–
119	Hybrid pressure level (see Note 3)	–
120–149	Reserved	
150	Generalized vertical height coordinate (see Note 5)	–
151	Soil level (see Note 6)	Numeric
152	Sea-ice level (see Note 8)	Numeric
153–159	Reserved	
160	Depth below sea level	m
161	Depth below water surface	m
162	Lake or river bottom	–
163	Bottom of sediment layer	–
164	Bottom of thermally active sediment layer	–
165	Bottom of sediment layer penetrated by thermal wave	–
166	Mixing layer	–
167	Bottom of root zone	–
168	Ocean model level	Numeric
169	Ocean level defined by water density (sigma-theta) difference from near-surface to level (see Note 7)	kg m^{-3}
170	Ocean level defined by water potential temperature (theta) difference from near-surface to level (see Note 7)	K
171	Ocean level defined by vertical eddy diffusivity difference from near-surface to level (see Note 7)	$\text{m}^2 \text{ s}^{-1}$
172–173	Reserved	
174	Top surface of ice on sea, lake or river	–
175	Top surface of ice, under snow cover, on sea, lake or river	–
176	Bottom surface (underside) ice on sea, lake or river	–
177	Deep soil (of indefinite depth)	–

Code table 4.5

Code figure	Meaning	Unit
178	Reserved	
179	Top surface of glacier ice and inland ice	–
180	Deep inland or glacier ice (of indefinite depth)	–
181	Grid tile land fraction as a model surface	–
182	Grid tile water fraction as a model surface	–
183	Grid tile ice fraction on sea, lake or river as a model surface	–
184	Grid tile glacier ice and inland ice fraction as a model surface	–
185–191	Reserved	
192–254	Reserved for local use	
255	Missing	

Notes:

- (1) The Eta vertical coordinate system involves normalizing the pressure at some point on a specific level by the mean sea-level pressure at that point.
- (2) Hybrid height level (Code figure 118) can be defined as:

$$z(k) = A(k) + B(k) \times \text{orog}$$
(k = 1,...,NLevels; orog = orography; z(k) = height in metres at level k)
- (3) Hybrid pressure level, for which Code figure 119 shall be used instead of 105, can be defined as:

$$p(k) = A(k) + B(k) \times \text{sp}$$
(k = 1,...,NLevels; sp = surface pressure; p(k) = pressure at level k)
- (4) Sigma height level is the vertical model level of the height-based terrain-following coordinate (Gal-Chen and Somerville, 1975). The value of the level = (height of the level – height of the terrain) / (height of the top level – height of the terrain), which is ≥ 0 and ≤ 1 .
- (5) The definition of a generalized vertical height coordinate implies the absence of coordinate values in Section 4 but the presence of an external 3D-GRIB message that specifies the height of every model grid point in metres (see Notes to Section 4 in the section above entitled Specification of Octet Contents), i.e., this GRIB message will contain the field with discipline = 0, category = 3, parameter = 6 (Geometric height).
- (6) The soil level represents a model level for which the depth is not constant across the model domain. The depth in metres of the level is provided by another GRIB message with the parameter "soil depth" with discipline 2, category 3 and parameter number 27.
- (7) The level is defined by a water property difference from the near-surface to the level. The near-surface is typically chosen at 10 m depth. The physical quantity used to compute the difference can be water density (σ_θ) when using level type 169 or water potential temperature (θ) when using level type 170.
- (8) The sea-ice level represents a sea-ice model level for which the depth is not constant across the model domains. The depth in metres of the level is provided by another GRIB message with the parameter "sea-ice thickness" with discipline 10, category 2 and parameter number 1.

Code table 4.6 – Type of ensemble forecast

Code table 4.6

Code figure	Meaning
0	Unperturbed high-resolution control forecast
1	Unperturbed low-resolution control forecast
2	Negatively perturbed forecast
3	Positively perturbed forecast
4	Multi-model forecast

Code table 4.6	
Code figure	Meaning
5–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.7 – Derived forecast

Code table 4.7	
Code figure	Meaning
0	Unweighted mean of all members
1	Weighted mean of all members
2	Standard deviation with respect to cluster mean
3	Standard deviation with respect to cluster mean, normalized
4	Spread of all members
5	Large anomaly index of all members (see Note 1)
6	Unweighted mean of the cluster members
7	Interquartile range (range between the 25th and 75th quantile)
8	Minimum of all ensemble members (see Note 2)
9	Maximum of all ensemble members (see Note 2)
10–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

- (1) Large anomaly index is defined as $\{(\text{number of members whose anomaly is higher than } 0.5 \times \text{SD}) - (\text{number of members whose anomaly is lower than } -0.5 \times \text{SD})\} / (\text{number of members})$ at each grid point, where SD is defined as observed climatological standard deviation.
- (2) It should be noted that the reference for "minimum of all ensemble members" and "maximum of all ensemble members" is the set of ensemble members and not a time interval and should not be confused with the maximum and minimum described by PDT 4.8.

Code table 4.8 – Clustering method

Code table 4.8	
Code figure	Meaning
0	Anomaly correlation
1	Root mean square
2–191	Reserved
192–254	Reserved for local use
255	Missing
0	Anomaly correlation
1	Root mean square
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.9 – Probability type

3.0	
Code figure	Meaning
0	Probability of event below lower limit
1	Probability of event above upper limit
2	Probability of event between lower and upper limits (the range includes the lower limit but not the upper limit)
3	Probability of event above lower limit
4	Probability of event below upper limit
5	Probability of event equal to lower limit
6	Probability of event in above normal category (see Notes 1 and 2)
7	Probability of event in near normal category (see Notes 1 and 2)
8	Probability of event in below normal category (see Notes 1 and 2)
9–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

- (1) Above normal, near normal and below normal are defined as three equiprobable categories based on climatology at each point over the geographical area covered by the grid. The type and methodology of the reference climatology are unspecified and should be documented concurrently by the data producer.
- (2) Product definition templates that use Code Table 4.9 may contain octets to store the values of lower and upper limits. When categorical probability is used (such as below, near and above normal), these octets shall be set to “all ones” (missing).

Code table 4.10 – Type of statistical processing

Code table 4.10	
Code figure	Meaning
0	Average
1	Accumulation (see Note 1)
2	Maximum
3	Minimum
4	Difference (value at the end of time range minus value at the beginning)
5	Root mean square
6	Standard deviation
7	Covariance (temporal variance) (see Note 2)
8	Difference (value at the start of time range minus value at the end)
9	Ratio (see Note 3)
10	Standardized anomaly
11	Summation
12	Return period
13–99	Reserved
100	Severity
101	Mode
102–254	Reserved for local use
255	Missing

Notes:

- (1) The original data value (Y in the note 4 of Regulation 92.9.4) has units of Code table 4.2 multiplied by second, unless otherwise noted on Code table 4.2.

- (2) The original data value has squared units of Code table 4.2.
- (3) The original data value is non-dimensional number without units.

Code table 4.11 – Type of time intervals

Code table 4.11	
Code figure	Meaning
0	Reserved
1	Successive times processed have same forecast time, start time of forecast is incremented
2	Successive times processed have same start time of forecast, forecast time is incremented
3	Successive times processed have start time of forecast incremented and forecast time decremented so that valid time remains constant
4	Successive times processed have start time of forecast decremented and forecast time incremented so that valid time remains constant
5	Floating subinterval of time between forecast time and end of overall time interval (see Note)
6–191	Reserved
192–254	Reserved for local use
255	Missing

Note: Code figure 5 applies to instances where a single time subinterval was used to calculate the statistically processed field. The exact starting and ending times of the subinterval are not given, but it is known that it is contained inclusively between the beginning time and the ending time of the overall interval.

Code table 4.12 – Operating mode

Code table 4.12	
Code figure	Meaning
0	Maintenance mode
1	Clear air
2	Precipitation
3–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.13 – Quality control indicator

Code table 4.13	
Code figure	Meaning
0	No quality control applied
1	Quality control applied
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.14 – Clutter filter indicator

Code table 4.14	
Code figure	Meaning
0	No clutter filter used
1	Clutter filter used
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.15 – Type of spatial processing used to arrive at given data value from the source data

Code table 4.15	
Code figure	Meaning
0	Data is calculated directly from the source grid with no interpolation (see Note 1)
1	Bilinear interpolation using the 4 source grid grid-point values surrounding the nominal grid-point
2	Bicubic interpolation using the 4 source grid grid-point values surrounding the nominal grid-point
3	Using the value from the source grid grid-point which is nearest to the nominal grid-point
4	Budget interpolation using the 4 source grid grid-point values surrounding the nominal grid-point (see Note 2)
5	Spectral interpolation using the 4 source grid grid-point values surrounding the nominal grid-point
6	Neighbor-budget interpolation using the 4 source grid grid-point values surrounding the nominal grid-point (see Note 3)
7–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

- (1) This method assumes that each field really represents box averages/maxima/minima where each box extends halfway to its neighboring grid point in each direction to represent averages/maxima/minima of values from the source grid with no interpolation.
- (2) Budget interpolation means a low-order interpolation method that quasi-conserves area averages. It would be appropriate for interpolating budget fields such as precipitation. This method assumes that the field really represents box averages/maxima/minima where each box extends halfway to its neighboring grid point in each direction. The method actually averages bilinearly interpolated values in a square array of points distributed within each output grid box.
- (3) Performs a budget interpolation at the grid point nearest to the nominal grid point.

Code table 4.16 – Quality value associated with parameter

Code table 4.16	
Code figure	Meaning
0	Confidence index (see Note 2)
1	Quality indicator (see Note 3 and Code table 4.244)
2	Correlation of product with used calibration product (see Note 4)
3	Standard deviation (see Note 5)
4	Random error (see Note 5)
5	Probability

Code table 4.16

Code figure	Meaning
6–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

- (1) When a non-missing value is used from this code table, the original data value is a quality value associated with the parameter defined by octets 10 and 11 of the product definition template.
- (2) The original data value is a non-dimensional number from 0 to 1, where 0 indicates no confidence and 1 indicates maximal confidence.
- (3) The original data value is defined by Code table 4.244
- (4) The original data value is a non-dimensional number without units.
- (5) The original data value is in the same units as the parameter defined by octets 10 and 11 of the product definition template.

Code table 4.91 – Type of Interval

Code table 4.91

Code figure	Meaning
0	Smaller than first limit
1	Greater than second limit
2	Between first and second limit. The range includes the first limit but not the second limit
3	Greater than first limit
4	Smaller than second limit
5	Smaller or equal first limit
6	Greater or equal second limit
7	Between first and second. The range includes the first limit and the second limit
8	Greater or equal first limit
9	Smaller or equal second limit
10	Between first and second limit. The range includes the second limit but not the first limit
11	Equal to first limit
12–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.100 – Type of reference dataset

Code table 4.100

Code figure	Meaning
<u>0</u>	<u>Analysis</u>
<u>1</u>	<u>Forecast</u>
<u>2</u>	<u>Reforecast (Hindcast)</u>
<u>3</u>	<u>Reanalysis</u>
<u>4</u>	<u>Climate projection</u>
<u>5</u>	<u>Gridded observations</u>
<u>6–191</u>	<u>Reserved</u>
<u>192–254</u>	<u>Reserved for local use</u>
<u>255</u>	<u>Missing</u>

Code table 4.101 – Type of relationship to reference dataset

<i>Code table 4.101</i>	
<u>Code figure</u>	<u>Meaning</u>
<u>0</u>	<u>Anomaly (see Note 1)</u>
<u>1</u>	<u>Standardized anomaly (see Note 1)</u>
<u>2</u>	<u>Significance (Wilcoxon-Mann-Whitney) (see Note)</u>
<u>3-19</u>	<u>Reserved</u>
<u>20</u>	<u>Extreme Forecast Index (EFI) (see Note 3)</u>
<u>21</u>	<u>Shift of Tails (SOT) (see Note 4)</u>
<u>22-191</u>	<u>Reserved</u>
<u>192-254</u>	<u>Reserved for local use</u>
<u>255</u>	<u>Missing</u>

Notes:

(1) No additional parameter needed, NA in templates 4.105, 4.106 and 4.107 should be set to 0.

(2) Confidence interval for the significance test is needed (NA=1).

(3) EFI is defined in <https://doi.org/10.1256/qj.02.152>. No additional parameter needed (NA=0).

(4) SOT is defined in <https://doi.org/10.1256/qj.02.152>. Lower and upper quantile used for the SOT need to be defined (NA=2) in this order: start of the tail (10 or 90 usually) then end of tail (1 or 99 respectively).

Code table 4.102 – Statistical processing of reference period

<i>Code table 4.102</i>	
<u>Code figure</u>	<u>Meaning</u>
<u>0</u>	<u>Average</u>
<u>1</u>	<u>Accumulation</u>
<u>2</u>	<u>Maximum</u>
<u>3</u>	<u>Minimum</u>
<u>4</u>	<u>Median</u>
<u>5-19</u>	<u>Reserved</u>
<u>20</u>	<u>Model Climate</u>
<u>21-191</u>	<u>Reserved</u>
<u>192-254</u>	<u>Reserved for local use</u>
<u>255</u>	<u>Missing</u>

Code table 4.201 – Precipitation type

<i>Code table 4.201</i>	
<u>Code figure</u>	<u>Meaning</u>
<u>0</u>	<u>No precipitation</u>
<u>1</u>	<u>Rain</u>
<u>2</u>	<u>Thunderstorm</u>
<u>3</u>	<u>Freezing rain</u>
<u>4</u>	<u>Mixed/ice</u>
<u>5</u>	<u>Snow</u>
<u>6</u>	<u>Wet snow</u>

Code table 4.201

Code figure	Meaning
7	Mixture of rain and snow
8	Ice pellets
9	Graupel
10	Hail
11	Drizzle
12	Freezing drizzle
13–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.202 – Precipitable water category

Code table 4.202

Code figure	Meaning
0–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.203 – Cloud type

Code table 4.203

Code figure	Meaning
0	Clear
1	Cumulonimbus
2	Stratus
3	Stratocumulus
4	Cumulus
5	Altostratus
6	Nimbostratus
7	Altostratus
8	Cirrostratus
9	Cirrocumulus
10	Cirrus
11	Cumulonimbus – ground-based fog beneath the lowest layer
12	Stratus – ground-based fog beneath the lowest layer
13	Stratocumulus – ground-based fog beneath the lowest layer
14	Cumulus – ground-based fog beneath the lowest layer
15	Altostratus – ground-based fog beneath the lowest layer
16	Nimbostratus – ground-based fog beneath the lowest layer
17	Altostratus – ground-based fog beneath the lowest layer
18	Cirrostratus – ground-based fog beneath the lowest layer
19	Cirrocumulus – ground-based fog beneath the lowest layer
20	Cirrus – ground-based fog beneath the lowest layer
21–190	Reserved
191	Unknown
192–254	Reserved for local use
255	Missing

Note: Code figures 11–20 indicate all four layers were used and ground-based fog is beneath the lowest layer.

Code table 4.204 – Thunderstorm coverage

Code table 4.204	
Code figure	Meaning
0	None
1	Isolated (1–2%)
2	Few (3–5%)
3	Scattered (6–45%)
4	Numerous (> 45%)
5–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.205 – Presence of aerosol

Code table 4.205	
Code figure	Meaning
0	Aerosol not present
1	Aerosol present
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.206 – Volcanic ash

Code table 4.206	
Code figure	Meaning
0	Not present
1	Present
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.207 – Icing

Code table 4.207	
Code figure	Meaning
0	None
1	Light
2	Moderate
3	Severe
4	Trace
5	Heavy
6–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.208 – Turbulence

Code table 4.208	
Code figure	Meaning
0	None (smooth)
1	Light
2	Moderate
3	Severe
4	Extreme
5–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.209 – Planetary boundary-layer regime

Code table 4.209	
Code figure	Meaning
0	Reserved
1	Stable
2	Mechanically driven turbulence
3	Forced convection
4	Free convection
5–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.210 – Contrail intensity

Code table 4.210	
Code figure	Meaning
0	Contrail not present
1	Contrail present
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.211 – Contrail engine type

Code table 4.211	
Code figure	Meaning
0	Low bypass
1	High bypass
2	Non-bypass
3–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.212 – Land use

Code table 4.212	
Code figure	Meaning
0	Reserved
1	Urban land
2	Agriculture
3	Range land
4	Deciduous forest
5	Coniferous forest
6	Forest/wetland
7	Water
8	Wetlands
9	Desert
10	Tundra
11	Ice
12	Tropical forest
13	Savannah
14–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.213 – Soil type

Code table 4.213	
Code figure	Meaning
0	Reserved
1	Sand
2	Loamy sand
3	Sandy loam
4	Silt loam
5	Organic (redefined)
6	Sandy clay loam
7	Silt clay loam
8	Clay loam
9	Sandy clay
10	Silty clay
11	Clay
12–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.214 – Environmental Factor Qualifier

Code table 4.214	
Code figure	Meaning
0	Worst
1	Very poor
2	Poor
3	Average
4	Good

Code table 4.214	
Code figure	Meaning
5	Excellent
6–190	Reserved
191	Unknown
192–254	Reserved for local use
255	Missing

Code table 4.215 – Remotely sensed snow coverage

Code table 4.215	
Code figure	Meaning
0–49	Reserved
50	No-snow/no-cloud
51–99	Reserved
100	Clouds
101–249	Reserved
250	Snow
251–254	Reserved for local use
255	Missing

Code table 4.216 – Elevation of snow-covered terrain

Code table 4.216	
Code figure	Meaning
0–90	Elevation in increments of 100 m
91–253	Reserved
254	Clouds
255	Missing

Code table 4.217 – Cloud mask type

Code table 4.217	
Code figure	Meaning
0	Clear over water
1	Clear over land
2	Cloud
3	No data
4–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.218 – Pixel scene type

Code table 4.218	
Code figure	Meaning
0	No scene identified

Code table 4.218

Code figure	Meaning
1	Green needle-leaved forest
2	Green broad-leaved forest
3	Deciduous needle-leaved forest
4	Deciduous broad-leaved forest
5	Deciduous mixed forest
6	Closed shrub-land
7	Open shrub-land
8	Woody savannah
9	Savannah
10	Grassland
11	Permanent wetland
12	Cropland
13	Urban
14	Vegetation/crops
15	Permanent snow/ice
16	Barren desert
17	Water bodies
18	Tundra
19	Warm liquid water cloud
20	Supercooled liquid water cloud
21	Mixed-phase cloud
22	Optically thin ice cloud
23	Optically thick ice cloud
24	Multilayered cloud
25–96	Reserved
97	Snow/ice on land
98	Snow/ice on water
99	Sun-glint
100	General cloud
101	Low cloud/fog/stratus
102	Low cloud/stratocumulus
103	Low cloud/unknown type
104	Medium cloud/nimbostratus
105	Medium cloud/altostratus
106	Medium cloud/unknown type
107	High cloud/cumulus
108	High cloud/cirrus
109	High cloud/unknown
110	Unknown cloud type
111	Single Layer Water Cloud
112	Single Layer Ice Cloud
113–191	Reserved
192–254	Reserved for local use
255	Missing
99	Sun-glint
100	General cloud
101	Low cloud/fog/stratus
102	Low cloud/stratocumulus
103	Low cloud/unknown type

Code table 4.218

Code figure	Meaning
104	Medium cloud/nimbostratus
105	Medium cloud/altostratus
106	Medium cloud/unknown type
107	High cloud/cumulus
108	High cloud/cirrus
109	High cloud/unknown
110	Unknown cloud type
111	Single Layer Water Cloud
112	Single Layer Ice Cloud
113–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.219 – Cloud top height quality indicator

Code table 4.219

Code figure	Meaning
0	Nominal cloud top height quality
1	Fog in segment
2	Poor quality height estimation
3	Fog in segment and poor quality height estimation
4–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.220 – Horizontal dimension processed

Code table 4.220

Code figure	Meaning
0	Latitude
1	Longitude
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.221 – Treatment of missing data

Code table 4.221

Code figure	Meaning
0	Not included
1	Extrapolated
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.222 – Categorical result

Code table 4.222	
Code figure	Meaning
0	No
1	Yes
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.223 – Fire detection indicator

Code table 4.223	
Code figure	Meaning
0	No fire detected
1	Possible fire detected
2	Probable fire detected
3	Missing

Code table 4.224 – Categorical outlook

Code table 4.224	
Code figure	Meaning
0	No risk area
1	Reserved
2	General thunderstorm risk area
3	Reserved
4	Slight risk area
5	Reserved
6	Moderate risk area
7	Reserved
8	High risk area
9–10	Reserved
11	Dry thunderstorm (dry lightning) risk area
12–13	Reserved
14	Critical risk area
15–17	Reserved
18	Extremely critical risk area
19–254	Reserved
255	Missing

Code table 4.225 – Weather

(see FM 94 BUFR/FM 95 CREX Code table 0 20 003 – Present weather)

Code table 4.227 – Icing scenario (weather/cloud classification)

Code table 4.227	
Code figure	Meaning
0	None

Code table 4.227	
Code figure	Meaning
1	General
2	Convective
3	Stratiform
4	Freezing
5–191	Reserved
192–254	Reserved for local use
255	Missing value

Code table 4.228 – Icing severity

Code table 4.228	
Code figure	Meaning
0	None
1	Trace
2	Light
3	Moderate
4	Severe
5–254	Reserved
255	Missing value

Code table 4.230 – Atmospheric chemical constituent type

(See Common Code table C–14)

Code table 4.233 – Aerosol type

(See Common Code table C–14)

Code table 4.234 – Canopy cover fraction (to be used as partitioned parameter in product definition template 4.53 or 4.54)

Code table 4.234	
Code figure	Meaning
1	Crops, mixed farming
2	Short grass
3	Evergreen needleleaf trees
4	Deciduous needleleaf trees
5	Deciduous broadleaf trees
6	Evergreen broadleaf trees
7	Tall grass
8	Desert
9	Tundra
10	Irrigated crops
11	Semidesert
12	Ice caps and glaciers
13	Bogs and marshes
14	Inland water

Code table 4.234	
Code figure	Meaning
15	Ocean
16	Evergreen shrubs
17	Deciduous shrubs
18	Mixed forest
19	Interrupted forest
20	Water and land mixtures

Code table 4.236 – Soil texture fraction (to be used as partitioned parameter in product definition template 4.53 or 4.54)

Code table 4.236	
Code figure	Meaning
1	Coarse
2	Medium
3	Medium-fine
4	Fine
5	Very-fine
6	Organic
7	Tropical-organic

Code table 4.238 – Source or sink

Code table 4.238	
Code figure	Meaning
0	Other
1	Aviation
2	Lightning
3	Biogenic sources
4	Anthropogenic sources
5	Wild fires
6	Natural sources
7	Volcanoes
8	Biofuel
9	Fossil fuel
10	Wetlands
11	Oceans
12	Elevated anthropogenic sources
13	Surface anthropogenic sources
14	Agriculture livestock
15	Agriculture soils
16	Agriculture waste burning
17	Agriculture (all)
18	Residential, commercial and other combustion
19	Power generation
20	Super power stations
21	Fugitives
22	Industrial process
23	Solvents

Code table 4.238

Code figure	Meaning
24	Ships
25	Wastes (solid and water)
26	Road transportation
27	Off-road transportation
28–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.239 – Wetland type

Code table 4.239

Code figure	Meaning
<u>0</u>	<u>Reserved</u>
<u>1</u>	<u>Bog</u>
<u>2</u>	<u>Drained</u>
<u>3</u>	<u>Fen</u>
<u>4</u>	<u>Floodplain</u>
<u>5</u>	<u>Mangrove</u>
<u>6</u>	<u>Marsh</u>
<u>7</u>	<u>Rice</u>
<u>8</u>	<u>Riverine</u>
<u>9</u>	<u>Salt marsh</u>
<u>10</u>	<u>Swamp</u>
<u>11</u>	<u>Upland</u>
<u>12</u>	<u>Wet tundra</u>
<u>13–191</u>	<u>Reserved</u>
<u>192–254</u>	<u>Reserved for local use</u>
<u>255</u>	<u>Missing</u>

Code table 4.240 – Type of distribution function

Code table 4.240

Code figure	Meaning
0	No specific distribution function given
1	Delta functions with spatially variable concentration and fixed diameters D_l ($p1$) in metre (see Note 1)
2	Delta functions with spatially variable concentration and fixed masses D_l ($p1$) in kg (see Note 2)
3	Gaussian (normal) distribution with spatially variable concentration and fixed mean diameter D_l ($p1$) and variance σ ($p2$) (see Note 3)
4	Gaussian (normal) distribution with spatially variable concentration, mean diameter and variance (see Note 4)
5	Log-normal distribution with spatially variable number density, mean diameter and variance (see Note 5)
6	Log-normal distribution with spatially variable number density, mean diameter and fixed variance σ ($p1$) (see Note 6)
7	Log-normal distribution with spatially variable number density and mass density and fixed variance σ ($p1$) and fixed particle density ρ ($p2$) (see Note 7)

Code table 4.240

Code figure	Meaning
8	No distribution function. The encoded variable is derived from variables characterized by type of distribution function of type No. 7 (see above) with fixed variance σ (p1) and fixed particle density ρ (p2)
9-49151	Reserved
49152-65534	Reserved for local use
65535	Missing value

Notes:

(1) Bin model or delta function with N concentrations $c_l(r)$ in class (or mode) l .

Concentration-density function:

$$f(r; d) = \sum_{l=1}^N c_l(r) \delta(d - D_l)$$

where

N – number of modes in the distribution

δ – delta function

d – diameter

D_l – diameter of mode l (p1)

(2) Bin model or delta function with N concentrations $c_l(r)$ in class (or mode) l .

Concentration-density function:

$$f(r; m) = \sum_{l=1}^N c_l(r) \delta(m - M_l)$$

where

N – number of modes in the distribution

δ – delta function

m – mass

M_l – mass of mode l (p1)

(3) N-modal concentration-density function consisting of Gaussian functions:

$$f(r; d) = \sum_{l=1}^N c_l(r) \frac{1}{\sqrt{2\pi\sigma_l}} e^{-\frac{1}{2}\left(\frac{d-D_l}{\sigma_l}\right)^2} \quad f(r; d) = \sum_{l=1}^N c_l(r) \frac{1}{\sqrt{2\pi\sigma_l}} e^{-\frac{(d-D_l)^2}{\sigma_l^2}}$$

where

N – number of modes in the distribution

d – diameter

D_l – mean diameter of mode l (p1)

σ_l – variance of mode l (p2)

with N fields of concentration $c_l(r)$.

(4) N-modal concentration-density function consisting of Gaussian functions:

$$f(r; d) = \sum_{l=1}^N c_l(r) \frac{1}{\sqrt{2\pi\sigma_l(r)}} e^{-\frac{1}{2}\left(\frac{d-D_l(r)}{\sigma_l(r)}\right)^2} \quad f(r; d) = \sum_{l=1}^N c_l(r) \frac{1}{\sqrt{2\pi\sigma_l(r)}} e^{-\frac{(d-D_l(r))^2}{\sigma_l^2(r)}}$$

with $3N$ fields of concentration $c_l(r)$, variance $\sigma_l(r)$ and mean diameter $D_l(r)$.

(5) N-modal log-normal-distribution for the number density:

$$f(r; d) = \sum_{l=1}^N \frac{n_l(r)}{\sqrt{2\pi \log \sigma_l(r)}} e^{\frac{\log^2 \frac{d}{D_l(r)}}{2 \log^2 \sigma_l(r)}}$$

where

d – diameter

with $3N$ fields of number density $n_l(r)$, variance $\sigma_l(r)$ and mean diameter $D_l(r)$.

- (6) N -modal log-normal-distribution for the number density:

$$f(r; d) = \sum_{l=1}^N \frac{n_l(r)}{\sqrt{2\pi} \log \sigma_l} e^{\frac{\log^2 \frac{d}{D_l(r)}}{2 \log^2 \sigma_l}}$$

where

σ_l – variance of mode l ($p1$)

with $2N$ fields of number density $n_l(r)$ and mean diameter $D_l(r)$.

- (7) N -modal log-normal-distribution for the number density as in Note 6, but with a prescribed mass density $m_l(r)$, from which the diameter $D_l(r)$ is calculated by:

$$D_l = \left(\frac{m_l(r)}{n_l(r) \frac{\pi}{6} \rho_{p,l} e^{\frac{9}{2} \log^2 \sigma_l}} \right)^{1/3}$$

where

σ_l – variance of mode l ($p1$)

$\rho_{p,l}$ – particle density ($p2$)

with $2N$ fields of number density $n_l(r)$ and mass density $m_l(r)$.

Code table 4.241 – Coverage attributes

Code table 4.241	
Code figure	Meaning
0	Undefined
1	Unmodified
2	Snow covered
3	Flooded
4	Ice covered
5–191	Reserved
192–254	Reserved for local use
255	Missing value

Code table 4.242 – Tile classification

Code table 4.242	
Code figure	Meaning
0	Reserved
1	Land use classes according to ESA-GlobCover GCV2009
2	Land use classes according to European Commission–Global Land Cover Project GLC2000
3–191	Reserved
192–254	Reserved for local use
255	Missing value

Code table 4.243 – Tile class

Code table 4.243	
Code figure	Meaning
0	Reserved

Code table 4.243

Code figure	Meaning
1	Evergreen broadleaved forest
2	Deciduous broadleaved closed forest
3	Deciduous broadleaved open forest
4	Evergreen needle-leaf forest
5	Deciduous needle-leaf forest
6	Mixed leaf trees
7	Freshwater flooded trees
8	Saline water flooded trees
9	Mosaic tree/natural vegetation
10	Burnt tree cover
11	Evergreen shrubs closed-open
12	Deciduous shrubs closed-open
13	Herbaceous vegetation closed-open
14	Sparse herbaceous or grass
15	Flooded shrubs or herbaceous
16	Cultivated and managed areas
17	Mosaic crop/tree/natural vegetation
18	Mosaic crop/shrub/grass
19	Bare areas
20	Water
21	Snow and ice
22	Artificial surface
23	Ocean
24	Irrigated croplands
25	Rainfed croplands
26	Mosaic cropland (50–70%) – vegetation (20–50%)
27	Mosaic vegetation (50–70%) – cropland (20–50%)
28	Closed broadleaved evergreen forest
29	Closed needle-leaved evergreen forest
30	Open needle-leaved deciduous forest
31	Mixed broadleaved and needle-leaved forest
32	Mosaic shrubland (50–70%) – grassland (20–50%)
33	Mosaic grassland (50–70%) – shrubland (20–50%)
34	Closed to open shrubland
35	Sparse vegetation
36	Closed to open forest regularly flooded
37	Closed forest or shrubland permanently flooded
38	Closed to open grassland regularly flooded
39	Undefined
40–32767	Reserved
32768–	Reserved for local use

Code table 4.244 – Quality indicator

Code table 4.244

Code figure	Meaning
0	No quality information available
1	Failed
2	Passed

Code table 4.244

Code figure	Meaning
3-191	Reserved
192-254	Reserved for local use
255	Missing

Code table 4.246 – Thunderstorm Intensity

Code table 4.246

Code figure	Meaning
0	No thunderstorm occurrence
1	Weak thunderstorm
2	Moderate thunderstorm
3	Severe thunderstorm
4-254	Reserved
255	Missing

Code table 4.247 – Precipitation Intensity

Code table 4.247

Code figure	Meaning
0	No precipitation occurrence
1	Light precipitation
2	Moderate precipitation
3	Heavy precipitation
4-254	Reserved
255	Missing

Code table 4.248 – Method used to derive data values for a given local time

Code table 4.248

Code figure	Meaning
0	Nearest forecast or analysis time to specified local time
1	Interpolated to be valid at the specified local time
2-191	Reserved
192-254	Reserved for local use
255	Missing

Code table 4.249 – Character of precipitation

Code table 4.249

Code figure	Meaning
0	None
1	Showers
2	Intermittent
3	Continuous
4-254	Reserved
255	Missing

Code table 4.250 – Drainage direction

Code table 4.250	
Code figure	Meaning
0	Reserved
1	South-west
2	South
3	South-east
4	West
5	No direction
6	East
7	North-west
8	North
9	North-east
10–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 4.251 – Wave direction and frequency formulae

Code table 4.251	
Code figure	Meaning
0	Undefined sequence
1	Geometric sequence (see Note 1)
2	Arithmetic sequence (see Note 2)
3–191	Reserved
192–254	Reserved for local use
255	Missing

Notes:

- (1) Geometric sequence: $x_n = x_0 * r^{(n-1)}$ with 'x₀' first parameter and 'r' second parameter.
- (2) Arithmetic sequence: $a_n = a_1 + (n-1) d$ with 'a₁' first parameter and 'd' second parameter.

CODE TABLES USED IN SECTION 5**Code table 5.0 – Data representation template number**

<i>Code table 5.0</i>	
Code figure	Meaning
0	Grid point data – simple packing
1	Matrix value at grid point – simple packing
2	Grid point data – complex packing
3	Grid point data – complex packing and spatial differencing
4	Grid point data – IEEE floating point data
5–39	Reserved
40	Grid point data – JPEG 2000 code stream format
41	Grid point data – Portable Network Graphics (PNG)
42	Grid point data – CCSDS recommended lossless compression
43–49	Reserved
50	Spectral data – simple packing
51	Spherical harmonics data – complex packing
52	Reserved
53	Spectral data for limited area models – complex packing
54–60	Reserved
61	Grid point data – simple packing with logarithm pre-processing
62–199	Reserved
200	Run length packing with level values
201–49151	Reserved
49152–65534	Reserved for local use
65535	Missing

Code table 5.1 – Type of original field values

<i>Code table 5.1</i>	
Code figure	Meaning
0	Floating point
1	Integer
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 5.2 – Matrix coordinate value function definition

Code table 5.2	
Code figure	Meaning
0	Explicit coordinate values set
1	Linear coordinates $f(1) = C1$ $f(n) = f(n-1) + C2$
2–10	Reserved
11	Geometric coordinates $f(1) = C1$ $f(n) = C2 \times f(n-1)$
12–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 5.3 – Matrix coordinate parameter

Code table 5.3	
Code figure	Meaning
1	Direction degrees true
2	Frequency (s^{-1})
3	Radial number ($2\pi/\lambda$) (m^{-1})
4–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 5.4 – Group splitting method

Code table 5.4	
Code figure	Meaning
0	Row by row splitting
1	General group splitting
2–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 5.5 – Missing value management for complex packing

Code table 5.5	
Code figure	Meaning
0	No explicit missing values included within data values
1	Primary missing values included within data values
2	Primary and secondary missing values included within data values
3–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 5.6 – Order of spatial differencing

Code table 5.6	
Code figure	Meaning
0	Reserved
1	First-order spatial differencing
2	Second-order spatial differencing
3–191	Reserved
192–254	Reserved for local use
255	Missing

Code table 5.7 – Precision of floating-point numbers

Code table 5.7	
Code figure	Meaning
0	Reserved
1	IEEE 32-bit (I=4 in section 7)
2	IEEE 64-bit (I=8 in section 7)
3	IEEE 128-bit (I=16 in section 7)
4–254	Reserved
255	Missing

Code table 5.25 – Type of bi-Fourier subtruncation

Code table 5.25	
Code figure	Meaning
0–76	Reserved
77	Rectangular
78–87	Reserved
88	Elliptic
89–98	Reserved
99	Diamond
100–254	Reserved
255	Missing

Code table 5.26 – Packing mode for axes

Code table 5.26	
Code figure	Meaning
0	Spectral coefficients for axes are packed
1	Spectral coefficients for axes included in the unpacked subset
2–254	Reserved
255	Missing

Code table 5.40 – Type of compression

Code table 5.40	
Code figure	Meaning
0	Lossless
1	Lossy
2–254	Reserved
255	Missing

Provisional Copy
2023

CODE TABLES USED IN SECTION 6***Code table 6.0 – Bit map indicator***

<i>Code table 6.0</i>	
Code figure	Meaning
0	A bit map applies to this product and is specified in this Section
1–253	A bit map predetermined by the originating/generating centre applies to this product and is not specified in this Section
254	A bit map defined previously in the same “GRIB” message applies to this product
255	A bit map does not apply to this product

Provisional Copy
2023

ATTACHMENT I

DEFINITION OF A TRIANGULAR GRID BASED ON AN ICOSAHDREDON

A triangular grid based on an icosahedron was first introduced in a meteorological model by Sadourny and others (1968) and Williamson (1969). The approach outlined here, especially the code implementation, is based on the work of Baumgardner (1995).

To construct the triangular grid based on an icosahedron, the unit-sphere, i.e. a sphere with radius 1, is divided into 20 spherical triangles of equal size by placing a plane icosahedron into the sphere (Figure 1). The 12 vertices of the icosahedron touch the sphere, one vertex coincides with the north pole (NP), the opposite one with the south pole (SP), for simplicity.

The 12 vertices are connected by great circles to form 20 main spherical triangles. Since each of the 12 vertices is surrounded by five main spherical triangles (Figure 2), the angles between two sides of the main triangles are $2\pi/5$ or 72° .




Figure 1. Plane icosahedron consisting of 20 plane triangles.




Figure 2. The five main spherical triangles at the north pole.




Figure 3. One main spherical triangle at the North Pole.

The length w of a main triangle side follows from Figure 3 and equation (1):

$$\cos \frac{1}{2} w = \frac{\cos \frac{\pi}{5}}{\sin 2 \frac{\pi}{5}} = \frac{1}{2 \sin \frac{\pi}{5}} \quad (1)$$

Thus $w \approx 1.107149$. On the unit-sphere, w is identical to $\pi/2$ minus φ with the latitude φ of the lower corner of the triangle. Thus w is a measure of the latitude of the lower vertices of the triangle in Figure 3.

Two adjacent main spherical triangles are combined to form a "diamond", i.e. a logical square block. Five of the diamonds originate from the north pole and five from the south pole. The numbering and order of the diamonds are outlined in Figure 4.




Figure 4. The 20 main spherical triangles combined to 10 diamonds.

ATTACHMENT I

Diamonds 1 to 5 are the “northern” ones, i.e. they start at the north pole, while diamonds 6 to 10 start at the south pole. The so-called home vertex of each diamond (in the order 1, 6, 2, 7, 3, 8, 4, 9, 5, 10) is shifted by $\pi/5$ to the east starting at $-\pi/5$ for the first diamond. Thus the 10 home vertices have the geographical coordinates (λ and φ) on the unit-sphere as presented in Table 1.

Table 1
Geographical coordinates (λ and φ) of the home vertices of the 10 diamonds

Diamond #	1	2	3	4	5	6	7	8	9	10
λ	$-\pi/5$	$\pi/5$	$3\pi/5$	$5\pi/5$	$-3\pi/5$	0	$2\pi/5$	$4\pi/5$	$-4\pi/5$	$-2\pi/5$
φ	$\pi/2-w$	$\pi/2-w$	$\pi/2-w$	$\pi/2-w$	$\pi/2-w$	$w-\pi/2$	$w-\pi/2$	$w-\pi/2$	$w-\pi/2$	$w-\pi/2$

A Cartesian coordinate system is placed into the unit-sphere with the origin in the centre of the sphere, the z-axis towards the north pole and the x-axis in the direction of the Greenwich meridian. The Cartesian coordinates (x , y , z) of a point on the unit-sphere follow from equation (2):

$$\begin{aligned} x &= \cos \lambda \cos \varphi = \cos \lambda \sin w \\ y &= \sin \lambda \cos \varphi = \sin \lambda \sin w \\ z &= \sin \varphi = \cos w \end{aligned} \quad (2)$$

Thus the two pole vertices have the Cartesian coordinates (0, 0, 1) and (0, 0, -1), respectively.

The geographical coordinates (λ , φ) of a point on the unit-sphere with the Cartesian coordinates (x , y , z) follow from equation (3) which may be derived from equation (2):

$$\begin{aligned} \lambda &= \arctan \frac{y}{x} \\ \varphi &= \arcsin z \end{aligned} \quad (3)$$

For the grid generation, the sides (w) of the 20 main triangles are iteratively subdivided into n_i equal parts to form sub-triangles. Each point in a main triangle is now surrounded by six triangles (Figure 5) and is, therefore, in the centre of a hexagon (see also Figure 6). However, the points which form the vertices of the icosahedron




Figure 5. Spherical triangular grids for different values n_i of the subdivision of the main spherical triangles.




Figure 6. Polygons which represent the area of representativeness of a triangular grid-point.

are surrounded by only five triangles and therefore these 12 special points are the centres of pentagons. For the first subdivision, w may be divided into three parts, later on, only bisections are allowed. This restriction is due to the use of a multi-grid (MG) solver for the Helmholtz equations in the semi-implicit time stepping. MG solvers work efficiently with such mesh refinements. Thus the number (n_i) of subdivisions of w is factorized according to equation (4):

$$n_i = 3^{n_3} 2^{n_2} \quad (4)$$

with $n_3 = 0$ or 1 and $n_2 \geq 0$. Figure 5 shows the resulting grids for $n_i = 1, 2, 4$ and 8 , i.e. $n_2 = 0, 1, 2, 3$ with $n_3 = 0$.

The model grid-points (nodes) are located at the vertices of the triangles; thus there are $(n_i+1)^2$ grid-points within one diamond. Of these $(n_i+1)^2$ grid-points, $n_i \times n_i$ are "uniquely" identified with each diamond; one extra row and column is shared between neighbouring diamonds.

On Earth with a mean radius $R_E = 637\,122.9$ m, the length (L) of a side of a main triangle is $L = wR_E = 705\,389.8$ m. The mesh size (Δ) of the triangular grid with n_i equal intervals on the side of a main triangle is not constant within a diamond but varies by 20 per cent at most on the sphere and is approximately given by using equation (5). For example, for $n_i = 32$, Δ varies between 220 and 263 km, for $n_i = 64$, Δ varies between 110 and 132 km and for $n_i = 128$, Δ varies between 55 and 66 km:

$$\Delta \approx \frac{wR_E}{n_i} \quad (5)$$

The number N of grid-points, not counting the common edges of the diamond, is given by equation (6):

$$N = 10 n_i^2 + 2 \quad (6)$$

Table 2a gives the mesh size, the number (N) of grid-points and the time step (Δt) for different values of n_i , if only bisections are performed, i.e. $n_i = 2^{n_2}$. The time step (Δt) is calculated under the assumption that an air parcel does not leave the region of the six surrounding triangles during the period of twice the time step, i.e. $2 \Delta t < h/v_{Max}$, with the height (h) of the spherical triangle (which is the shortest distance for leaving a triangle) and v_{Max} , the maximum wind speed (≈ 125 m s⁻¹) assuming that the fast gravity waves are treated semi-implicitly. The height (h) of a spherical triangle approximately follows from equation (7) and is about 5 per cent smaller than the mesh size (Δ):

$$h \approx \arcsin \left(\sin \frac{w}{n_i} \sin \frac{2\pi}{5} \right) R_E \quad (7)$$

ATTACHMENT I

Table 2a
Mesh size (Δ), height (h), number (N) of grid-points and time step (Δt) for the spherical triangular mesh using only bisections

n_i	16	32	64	128	256
Δ (km)	441	220	110	55	28
h (km)	420	210	105	52	26
N	2 562	10 242	40 962	163 842	655 362
Δt (s)	1 600	800	400	200	100

Table 2b
Mesh size (Δ), height (h), number (N) of grid-points and time step (Δt) for the spherical triangular mesh using first a trisection followed by bisections

n_i	12	24	48	96	192
Δ (km)	588	294	147	73	37
h (km)	559	279	140	69	35
N	1 442	5 762	23 042	92 162	368 642
Δt (s)	2 200	1 100	550	275	138

Each grid-point is representative for a spherical polygon with six vertices (Figure 6) except the 12 vertices of the icosahedron which are surrounded by five triangles only. The grid-point indices are defined as presented in Figure 7.

The start address (0, 1) reflects the philosophy that the $n_i \times n_i$ grid-points which are "uniquely" identified within each diamond have the indices 1 to n_i for rows and columns. The extra row and column needed for communication between neighbouring diamonds is lying in one case at the beginning of the first coordinate and in the other case at the end of the second. Thus points outside the range (1: n_i , 1: n_i) belong to the neighbouring diamonds and have to be communicated during each time step. Grid-point (0, 1), respectively, is the north pole for diamonds 1 to 5, and the south pole for diamonds 6 to 10.

The calculation of the subdivision of the great circle between two points P_1 (with location vector x_1) and P_2 (with location vector x_2) can be derived from Figure 8.

Since x_1 and x_2 define the great circle plane through P_1 and P_2 , all points (P) with the location vector (x) on the great circle may be written as a linear combination of x_1 and x_2 :

$$x = \alpha x_1 + \beta x_2 \quad (8)$$




Figure 7. Grid-point indices for a northern (left) and southern (right) diamond.




Figure 8. Calculation of the subdivision of the great circle through the points P_1 and P_2 on the unit-sphere.

The coefficients α and β are derived from the condition that x is a vector on the unit-sphere and the angle between x and x_1 is given by $\gamma\theta$ with γ between 0 and 1 and θ being the angle between x_1 and x_2 , i.e. the length of the great circle between P_1 and P_2 :

$$\begin{aligned} x \cdot x &= 1 = \alpha^2 + \beta^2 + 2\alpha\beta \cos \theta \\ x \cdot x_1 &= \cos(\gamma\theta) = \alpha + \beta \cos \theta \end{aligned} \quad (9)$$

Substituting α from the second equation into the first one, the coefficients follow from equation (10):

$$\begin{aligned} \alpha &= \frac{\sin((1 \pm \gamma)\theta)}{\sin \theta} \\ \beta &= \frac{\sin(\gamma\theta)}{\sin \theta} \end{aligned} \quad (10)$$

The angle θ between x_1 and x_2 follows from the scalar product $x_1 \cdot x_2$ or by calculating the distance (d) between x_1 and x_2 and observing that $\sin \theta/2 = d/2$.

The grid-point coordinates (x, y, z) of all triangle vertices on the unit-sphere are derived from equation (8) using the coefficients of equation (10). The $(n+1)^2$ grid-points in a diamond form the vertices of $2n^2$ triangles (Figure 9) and half of those point northward and half southward.

To calculate the coordinates (x_c, y_c, z_c) of the triangle centres P_c , the coordinates of the three triangle vertices P_1, P_2 and P_3 are summed and normalized as in equation (11):

$$\begin{aligned} x_c &= (x_1 + x_2 + x_3) \cdot x_N \\ y_c &= (y_1 + y_2 + y_3) \cdot x_N \\ z_c &= (z_1 + z_2 + z_3) \cdot x_N \end{aligned} \quad (11)$$

with

$$x_N = \frac{1}{\sqrt{(x_1 + x_2 + x_3)^2 + (y_1 + y_2 + y_3)^2 + (z_1 + z_2 + z_3)^2}}$$




Figure 9. The 2 ni^2 triangles in a diamond defined by the $(ni+1)^2$ vertices for $ni = 4$.

The area of the 2 ni^2 triangles in a diamond can be calculated by using equation (12) which is due to Huilier. The triangle sides are denoted by a , b and c . On the unit-sphere, the excess angle is equal to the area of the spherical triangle:

$$\tan \frac{\varepsilon}{4} = \sqrt{\tan \frac{s}{2} \tan \frac{s-a}{2} \tan \frac{s-b}{2} \tan \frac{s-c}{2}} \quad (12)$$

with:

$$s = \frac{1}{2} (a + b + c)$$

Since each grid-point is surrounded by six triangles (five triangles at the 12 special points), the grid-point is the centre of a hexagon (pentagon at the 12 special points) as is illustrated in Figure 10. The coordinates of




Figure 10. Hexagon connected to a grid-point of the triangular mesh.

the vertices of the hexagon, i.e. points Q_1, Q_2, \dots, Q_6 , are in a good approximation given by averaging the Cartesian coordinates of the three surrounding triangles vertices and normalizing to unit length, thus they follow from equation (11).

The grid-point in the centre of the hexagon is denoted by 0, the six surrounding triangles (and their vertices) by 1 to 6 counting counter-clockwise. We define point Q_i , i.e. a vertex of the hexagon, equidistant from the three vertices P_0, P_i , and P_{i+1} such that Q_i and Q_{i+1} is the perpendicular bisection of the great circle P_0P_{i+1} (Figure 10). The coordinates of Q_i are needed for the calculation of the topographical fields like orography, land fraction, roughness length as mean values over the area of the hexagons. Here, high-resolution datasets are averaged over the hexagon area.

Provisional Copy
2023

ATTACHMENT II


ARAKAWA GRIDS

Arakawa grids were first described in Arakawa and Lamb (1977).¹ There are several different grids with unique staggers labelled as A, B, C, D and E. The following examples show how many of these grids can be defined in GRIB2 using grid definition template 3.1 along with bits 5 through 8 of Flag table 3.4. The relevant bit settings are noted where applicable.


Provisional Copy
2023



¹ Arakawa, A. and V.R. Lamb, 1977: Computational design of the basic dynamical processes of the UCLA general circulation model. *Methods of Computational Physics* 17, New York: Academic Press, pp. 173–265.

B – grid (full)




B – grid (mass)







C – grid (full)




C – grid (mass)




C – grid (wind-u)




C – grid (wind-v)




E – grid (full)




E – grid (mass) full array




E – grid (mass) jagged array



E – grid (wind) full array





ATTACHMENT III

DISTRIBUTION FUNCTIONS IN GRIB

Goal: representation of fields, which depends not only on space and time, but also on an additional continuous parameter, for example, diameter d or particle mass m . Such fields at the end are (density) distribution functions $f(x, y, z, t, d) \equiv f(\mathbf{r}, t, d)$. They describe, for example, the distribution of particles with different particle sizes in the air. For simplicity, the time variable t is omitted in the following; in GRIB this would be superfluous, because times are noted in the product definition section (PDS).

Furthermore, this is an attempt to describe unimodal and multimodal distribution functions in a common GRIB2 framework.

A GRIB file contains one or several fields, which describe the distribution function (concentrations, number densities, ...). The purpose of the GRIB template 4.57 analysis or forecast at a horizontal level or in a horizontal layer at a point in time for atmospheric chemical constituents based on a distribution function is to enable the user to calculate additional interesting variables (mostly integrals) from these fields, if the user knows the underlying distribution function. Examples are the mass density of cloud droplets:

$$\rho(\mathbf{r}) = \int_0^\infty \frac{1}{6} \pi d^3 \rho_w f(\mathbf{r}, d) dd \quad (1.1)$$

(with the density of water $\rho_w = 1\,000 \text{ kg/m}^3$) or the radar reflectivity of rain droplet distributions:

$$Z(\mathbf{r}) = \text{const.} \int_0^\infty d^6 f(\mathbf{r}, d) dd \quad (1.2)$$

These are examples of distribution functions:

1. Bin model with concentrations $c_l(\mathbf{r})$ in the class (or mode) l . A concentration distribution function is described by:

$$f(\mathbf{r}; d) = \sum_{l=1}^N c_l(\mathbf{r}) \delta(d - D_l) \quad (1.3)$$

In this model, the numbers D_l for the diameter in these N classes are fixed and prescribed ($p1 = D_l$). Area of application: bin models in the cloud microphysics, volcanic ash, ...

2. N-modal concentration distribution function, composed by a Gaussian function:

$$f(\mathbf{r}; d) = \sum_{l=1}^N c_l(\mathbf{r}) \frac{1}{\sqrt{2\pi}\sigma_l} e^{-\frac{1}{2}\left(\frac{d-D_l}{\sigma_l}\right)^2} \quad (1.4)$$

Again, N concentrations $c_l(\mathbf{r})$ must be stored. The N modes are defined by fixed values for diameter D_l and width σ_l (therefore, $p1 = D_l$ and $p2 = \sigma_l$).

3. N-modal concentration distribution function, composed by Gaussian function, in which diameter and width can vary from grid point to grid point:

$$f(\mathbf{r}; d) = \sum_{l=1}^N c_l(\mathbf{r}) \frac{1}{\sqrt{2\pi}\sigma_l(\mathbf{r})} e^{-\frac{1}{2}\left(\frac{d-D_l(\mathbf{r})}{\sigma_l(\mathbf{r})}\right)^2} \quad (1.5)$$

Now, $3N$ fields $c_l(\mathbf{r})$, $D_l(\mathbf{r})$ and $\sigma_l(\mathbf{r})$ must be stored.

4. N-modal log-normal distribution for the number density:

$$f(\mathbf{r}; d) = \sum_{l=1}^N \frac{n_l(\mathbf{r})}{\sqrt{2\pi} \log \sigma_l(\mathbf{r})} e^{-\frac{\log^2 \frac{d}{D_l(\mathbf{r})}}{2 \log^2 \sigma_l(\mathbf{r})}} \quad (1.6)$$

5. N-modal log-normal distribution for the number density at fixed variance:

$$f(\mathbf{r}; d) = \sum_{l=1}^N \frac{n_l(\mathbf{r})}{\sqrt{2\pi} \log \sigma_l} e^{-\frac{\log^2 \frac{d}{D_l(\mathbf{r})}}{2 \log^2 \sigma_l}} \quad (1.7)$$

It is described by $2N$ fields $n_l(\mathbf{r})$, $D_l(\mathbf{r})$ and N fixed numbers σ_l (therefore, $p1 = \sigma_l$).

6. N-modal log-normal distribution for the number density at fixed variance and the prescription of number density and mass density. Again, equation 1.7 is used. However, the field $D_l(\mathbf{r})$ is not stored, but is expressed via:

$$D_l = \left(\frac{m_l(\mathbf{r})}{n_l(\mathbf{r}) \frac{\pi}{6} \rho_{p,l} e^{\frac{9}{2} \log^2 \sigma_l}} \right)^{1/3} \quad (1.8)$$

by the mass density $m_l(\mathbf{r})$.

It is described by $2N$ fields number density $n_l(\mathbf{r})$ and mass density $m_l(\mathbf{r})$, N values σ_l and N values for the particle densities $\rho_{p,l}$ ($p1 = \sigma_l$ and $p2 = \rho_{p,l}$).

(C. Hoose, 2004: master thesis, Univ. Karlsruhe)

Application area: aerosol fields

7. N-modal exponential distribution function with prescribed specific mass $q(\mathbf{r})$:

$$f(\mathbf{r}; d) = \sum_{l=1}^N N_{0,l} e^{-\lambda_l(\mathbf{r})d} \quad (1.9)$$

with a fixed intercept-parameter $N_{0,l}$ for the mode l .

For the case of spherical particles and $N = 1$ (cloud droplets, rain droplets), the inverse length $\lambda(\mathbf{r})$ depends on the specific mass $q(\mathbf{r})$ and the air density $\rho(\mathbf{r})$ by:

$$\lambda_l(\mathbf{r}) = \sqrt[4]{\frac{\pi \rho_{w,l} N_{0,l}}{\rho(\mathbf{r}) q(\mathbf{r})}} \quad (1.10)$$

This formula also contains the density $\rho_{w,l}$ (for example, density of liquid water. In general this value is the same for all modes l) ($p1 = N_{0,l}$ and $p2 = \rho_{w,l}$).

Application area: for $N = 1$, an exponential distribution is assumed for most cloud physics particles (cloud ice, graupel, ...).

8. Skew Gaussian function (for example, for temperature distributions):

$$f(\mathbf{r}; T) = \begin{cases} c_r e^{-\frac{(T-T_0(\mathbf{r}))^2}{\sigma_r^2(\mathbf{r})}}, & T > T_0(\mathbf{r}) \\ c_l e^{-\frac{(T-T_0(\mathbf{r}))^2}{\sigma_l^2(\mathbf{r})}}, & T \leq T_0(\mathbf{r}) \end{cases} \quad (1.11)$$

with three fields $T_0(\mathbf{r})$, $\sigma_r(\mathbf{r})$, $\sigma_l(\mathbf{r})$. The “left-sided” and “right-sided” variances $\sigma_{l,r}$ have the same physical dimension (temperature). To distinguish them, it is recommended to define two different GRIB elements; c_l and c_r are appropriate norms (not given here).

9. ...

Though there is an extremely large amount of possible functional forms of distribution functions, in practice, only a few are used. However, the examples shown indicate that even for the same underlying distribution function, the parameters and fields that are prescribed or derived by others, as well as the independent variable, can differ significantly. In these examples, this was the diameter d ; the particle mass m could be another. Consequently, this list can become quite large during the lifetime of GRIB2. In the end, this GRIB template is an attempt to deliver a minimum of order together with complete information for users of GRIB data.

ATTACHMENT IV

DEFINITION OF “TILES” WITH TIME-DEPENDENT ATTRIBUTES

How to code “tiles” with Product definition templates 4.55 and 4.56

The land surface model is evolving and growing more complex. More complex descriptive capabilities are needed to properly describe the representation of land cover types in state-of-the-art weather and climate models.

This includes the sub-grid scale tiling to represent surface heterogeneity. Each grid box with sub-grid variability is divided into a number of tiles, each representing a single surface type.

The use of PDT 4.53 and 4.54 for partitioned parameters implies that for every chosen partition $PN(1)$, $PN(2)$, ..., $PN(NP)$ a GRIB message exists. All NP partitions are linked by the normalization formula.

The GRIB code representation of this tile approach takes into account the possibility to encode:

- (1) Only the dominating tiles, which could differ from grid box to grid box;
- (2) Tile attributes, considering that tile fractions can be modified according to Code table 4.241 (for example, snow-covered).

Point (1) implies that every grid box has its own subset of tile classes from the land-use table.

Point (2) allows for the differentiation of tile attributes, the temporal component of this approach.

The fractions f_i of these N (dominant) classes and their attributes are subject to a normalization formula:

$$\sum_{i=1}^N f_i = 1$$

In detail, the model grid box is regarded as consisting of a prescribed number of surface types (tiles).

The fractional area of each tile is either given by the geospatial surface data or by one or more prescribed tile attributes (for example, snow-free and snow-covered). It is important to note that in contrast to the geospatial surface data, the tile attributes according to Code table 4.241 could be time dependent.




Figure 1. Generation of the dominating tile structure for $NUT=3$ of a heterogeneous land surface. The outer circle shows the fractional areas covered by the respective land cover classes for a given grid cell. The inner circle shows the selected dominating tiles. Please note the rescaling of the fractional areas performed in the inner circle.

Given the number of land-use surface types from the geospatial land-use data table in a particular grid box, the approach recognizes the most dominant land-use surface types above a prescribed threshold fraction (for example, 5%) up to the number of used tiles (NUT). Two model grid boxes always use the same number of tiles but could differ in the most dominant land-use surface types (see Figure 1, outer circles). The fraction of the resulting NUT is always rescaled to the total grid box area (see Figure 1, inner circles).

For grid boxes with nearly homogeneous land surface types, the approach recognizes only the single dominant type and the fractional area of the other used tiles is considered as zero (see Figure 2).




Figure 2. Generation of the dominating tile structure for NUT=3 of a nearly homogeneous land surface of a coastal region. In this example, area fractions smaller than 5% are not considered when selecting the dominating tiles.

The tile attributes considered in this approach allow for a modification of the tile fractions, for example, by a temporal evolution of the snow cover (see Code table 4.241– Coverage attributes). Therefore, a subset of the land-use classes from the geospatial land-use data table can be considered for tile attributes.




Figure 3. Generation of the dominating tile structure for NUT=3 with tile attribute "snow-covered" of a heterogeneous land surface, partly covered with snow. Dominating tiles are equipped with two attributes where applicable: "snow-covered" and "unmodified". Shaded areas show the snow-covered tile fractions.

The tiles used in a particular grid box that belong to the attribute are then divided into fractions of the attribute and fractions of the originating dominating tile (see Figure 3).

REPRESENTATION FORM :

SECTION 0	Indicator section
SECTION 1	Identification section
SECTION 2	(Optional section)
SECTION 3	Data description section
SECTION 4	Data section
SECTION 5	7777

Notes:

- (1) BUFR is the name of a binary code for the exchange and storage of data.
- (2) The BUFR message consists of a continuous bit-stream made of a sequence of octets (1 octet = 8 bits).
- (3) The terms "BUFR message" and "section" describe logical entities to assist BUFR definition.
- (4) A BUFR message consists of one or more subsets of related meteorological data defined, described and represented by a single BUFR entity. For observational data, each data subset usually corresponds to one observation.
- (5) The octets of a BUFR message are grouped in sections:

<i>Section number</i>	<i>Name</i>	<i>Contents</i>
0	Indicator section	"BUFR", length of message, BUFR edition number
1	Identification section	Length of section, identification of the message
2	Optional section	Length of section and additional items for local use by automatic data processing centres
3	Data description section	Length of section, number of data subsets, data category flag, data compression flag and a collection of descriptors which define the form and content of individual data elements
4	Data section	Length of section and binary data
5	End section	7777

- (6) It will be noted that the BUFR representation is not suitable for visual data recognition without computer interpretation.
- (7) The representation of data by means of a series of bits is independent of any particular machine representation.
- (8) Message and section lengths are expressed in octets. Section 0 has a fixed length of 8 octets; Section 5 has a fixed length of 4 octets. Sections 1, 2, 3 and 4 have a variable length which is included in the first three octets of each section.
- (9) In the BUFR message, the bit length for "International Alphabet No. 5" is regarded as 8-bit, adding one bit "0" to the 7-bit of IA5 as the most significant bit.

- (10) Position can only be interpreted unambiguously if the coordinate reference system and, if required, the fixed reference mean sea level to which it is attributed, is known. If these are not specified, it is assumed that the position shall be interpreted with respect to the WGS84 geodetic system and the Earth Gravitational Model EGM96.

Provisional Copy
2023

REGULATIONS:**94.1 General**

94.1.1 The BUFR form shall be used for the binary representation of meteorological data for exchange and storage. BUFR is particularly suitable for meteorological data that cannot be represented using FM 92 GRIB.

94.1.2 The beginning and the end of the code form shall be identified by 4 octets coded according to the International Alphabet No. 5 to represent, respectively, the indicators BUFR and 7777 in Indicator section 0 and End section 5. All other octets included in the code shall represent data in binary form.

94.1.3 Each section included in the code form shall always contain an integer multiple of 8 bits (octet). This rule shall be applied by appending bits set to zero to the section where necessary.

94.1.4 By convention, reserved values in sections 1 to 4 shall be set to zero.

94.1.5 Missing values shall be expressed by all bits set to 1 within the data width of the element. This shall apply to all Table B elements, including elements defined as CCITT IA5, code tables and flag tables, with the exception of data description operator qualifiers in Class 31.

Note: Flag tables are always augmented to contain an additional bit as the least significant bit of the table. All bits, including this additional bit, shall be set to 1 to express a missing value, but in all other cases this additional bit shall be set to 0. This note does not apply to data present indicator 0 31 031.

94.1.6 The convention for representing missing data for compressed data within the binary data section shall be to set the corresponding increments to fields so that all bits are set to 1.

94.1.7 When a local reference value for a set of element values for compressed data is represented as all bits set to 1, this shall imply that all values in the set are missing.

94.2 Section 0 – Indicator section

Section 0 shall be 8 octets long. Octets 1 to 4 shall be character coded according to the International Alphabet No. 5 as BUFR. The remainder of the section shall contain the length of the entire BUFR message (including the Indicator section) expressed in binary form over octets 5 to 7 (i.e. 24 bits), followed by the BUFR edition number, in binary, in octet 8.

94.3 Section 1 – Identification section

94.3.1 The length of the section, in units of octets, shall be expressed in binary form over the group of the first three octets of the section.

94.3.2 Octet 8 of the section shall be used to indicate the inclusion or the omission of section 2.

94.4 Section 2 – Optional section

94.4.1 Regulation 94.3.1 shall apply.

94.4.2 Octet 5 and subsequent octets shall contain additional items as may be defined within each centre for its own use.

94.5 Section 3 – Data description section

94.5.1 Regulation 94.3.1 shall apply.

94.5.2 Octets 5 and 6 of the section shall be used as a 16-bit number to indicate the number of data subsets within the BUFR message. Octet 7 shall be used to indicate whether observed data or other data are reported, and whether data are compressed or not. Octet 8 and subsequent octets shall contain a collection of descriptors which define the form and content of individual data elements in the Data section. A “data subset” shall be defined as the subset of data described by one single application of this collection of descriptors.

94.5.3 *Data description syntax for BUFR*

94.5.3.1 Data description shall consist of one or more descriptors. Each descriptor shall occupy 2 octets and contain 3 parts: F (2 bits), X (6 bits) and Y (8 bits).

94.5.3.2 If F = 0, the descriptor shall be called an “element descriptor”. An element descriptor shall define a single data item by reference to Table B.

Notes:

- (1) X denotes the Table B class, Y denotes the element within that class. The corresponding data item is depicted according to the definition contained in Table B, unless otherwise modified.
- (2) The definition(s) of one or more data item(s) may be modified by means of data description operators.

94.5.3.3 Element descriptors corresponding to the following classes in Table B shall remain in effect until superseded by redefinition:

Class

01	Identification
02	Instrumentation
03	Instrumentation
04	Location (time)
05	Location (horizontal – 1)
06	Location (horizontal – 2)
07	Location (vertical)
08	Significance qualifiers
09	Reserved

Note: Redefinition is effected by the occurrence of element descriptors which contradict the preceding element descriptors from these classes. If two or more elements from the same class do not contradict one another, they all apply.

94.5.3.4 The consecutive occurrence of two identical element descriptors or identical sets of element descriptors from Classes 04 to 07 inclusive shall denote a range of values bounded by the corresponding element values. This enables the definition of layers and simple time periods.

94.5.3.5 The definition of line, areas, volumes and more complex time attributes shall be accomplished using descriptors from Classes 04 to 07 in association with suitable descriptors from Class 08.

94.5.3.6 The consecutive occurrence of two or more non-identical element descriptors from Classes 04 to 07 inclusive shall infer that all such elements remain in effect until redefined, unless such elements define an increment.

94.5.3.7 Data items defined by element descriptors in Class 10 or above shall not behave as coordinates with respect to subsequent data.

94.5.3.8 Increments: Any occurrence of an element descriptor from Classes 04 to 07 which defines an increment shall indicate that the location corresponding to that class shall be incremented by the corresponding data value. In the case of successive increments from the same class, this means that each increment shall apply in a cumulative manner, with all preceding increments remaining in effect.

Displacements: In contrast, any displacement descriptor from Classes 04 to 07 does not redefine the location corresponding to that class, but shall define only a transient displaced location from the location corresponding to that class. In the case of successive displacements from the same class, this means that each displacement shall apply independently and in a non-cumulative manner to the location corresponding to that class.

94.5.3.9 If a BUFR message is made up of more than one subset, each subset shall be treated as though it was the first subset encountered.

94.5.4 ***The replication operation***

94.5.4.1 If $F = 1$, the descriptor shall be called a "replication descriptor". For this case, X shall indicate the number of descriptors to be repeated, and Y the total number of occurrences (replications) of the repeated subsequence.

Note: Where a replication operation includes delayed replication(s) within the scope of its replication, the replication (or repetition) factor descriptor(s) from Class 31 shall be counted for X , except the one (if any) located immediately after the replication description for which X is being calculated, as in the following example:

106000 031001 008002 103000 031001 005002 006002 010002.

94.5.4.2 A value of $Y = 0$ associated with the replication descriptor shall indicate delayed replication. In this case, the replication data description operator shall be completed by the next element descriptor, which shall define a data item indicating the number of replications. This descriptor may also indicate (by its value of Y) that the following datum is to be replicated together with the following descriptor.

94.5.4.3 Time or location increment descriptors, from Classes 04 to 07 inclusive, may be associated with replication descriptors in the following way: when an increment descriptor immediately precedes a replication descriptor, or is separated from it by one or more operator descriptors from Table C, this shall infer that all such increments be applied for each replication; the application of the increments shall have effect from the beginning of each defined replication, including the first.

94.5.5 ***Further operations on element and sequence descriptors***

94.5.5.1 If $F = 2$, the descriptor shall be called an "operator descriptor". An operator descriptor shall define an operation by reference to Table C.

Notes:

- (1) X denotes the value corresponding to an operator defined within Table C.
- (2) Y contains a value to be used as an operand in completing the defined operation.

94.5.5.2 When the Y operand of any operator descriptor, or a count associated with it, refers to a specific number of descriptors preceding the operator, this shall infer that those preceding descriptors are all from Table B or C, i.e. all references to Table D descriptors shall have been completely resolved. Any forward reference to descriptors shall infer that the descriptors are enumerated as they are found in the original record, i.e. Table D descriptors are not expanded.

- 94.5.5.3 A data present bit-map shall be defined as a set of N one bit values corresponding to N data entities described by N element descriptors (including element descriptors for delayed replication, if present); the data description of a data present bit-map is comprised of a replication operator followed by the element descriptor for the data present indicator.

Notes:

- (1) Where an operator descriptor requires a data present bit-map of length N to complete the operator definition, the N consecutive element descriptors which correspond to the N data entities to which the N bit values refer shall end with the element descriptor which immediately precedes the first such operator, or with the element descriptor which immediately precedes the first occurrence of such an operator following the occurrence of a cancel backward reference operator.
- (2) All references to previously defined element descriptors effected through the application of operators which are qualified by data present bit-maps shall refer to the element descriptors concerned including any modifications resulting from change data width, change reference value, and change scale factor.
- (3) The define data present bit-map for re-use operator enables a data present bit-map to be defined and later re-used; the definition of a data present bit-map shall remain defined until the occurrence of a cancel defined data present bit-map operator or a cancel backward data reference operator.
- (4) Where an operator descriptor is qualified by a data present bit-map of length N there shall be defined a number of values of the type indicated by that operator together with subsequent appropriate element descriptors; the number of values defined shall correspond to the number of bits set to zero in the data present bit-map; the description of each data item shall be obtained by substituting the appropriate element descriptors, modified by the operator, at each subsequent occurrence of a marker operator.

94.5.6 **Indirect reference to descriptors**

- 94.5.6.1 If $F = 3$, the descriptor shall be called a "sequence descriptor". A sequence descriptor shall define a list of element descriptors, replication descriptors, operator descriptors and/or sequence descriptors by reference to Table D.

Note: X denotes the Table D category, Y denotes the entry within the category. Table D entries contain lists of commonly associated descriptors for convenience.

- 94.5.6.2 A sequence descriptor shall be equivalent to the corresponding list of descriptors in Table D.

Note: If a sequence descriptor is included within the scope of a replication descriptor 1 X Y, the number of descriptors to be repeated shall be modified if the sequence descriptor is replaced by the corresponding list of descriptors from Table D.

94.5.7 **Unit rules**

- 94.5.7.1 The unit of an element descriptor, when not defined as a code table, flag table or CCITT5, should be based on the International System of Units (SI), established by the eleventh General Conference on Weights and Measures in 1960, and extended at the 1980 Conference. Alternatively, in exceptional cases, consideration may be given to other standard common units used by the data producer and the users, where a convincing case can be made that those units are more appropriate for the intended purpose of the descriptor. In such cases, priority shall be given to units contained in WMO Common Table C-6 or, in the case of descriptors for aviation products, ICAO Annex 5.

- 94.5.7.2 In cases where an element descriptor is defined as a code table that references values requiring units, Regulation 94.5.7.1 shall apply.

94.6 **Section 4 – Data section**

- 94.6.1 Regulation 94.3.1 shall apply.

- 94.6.2 Reported values shall be coded using the number of bits for each parameter indicated by reference to the sequence descriptors, replication descriptors, operator descriptors, element descriptors and associated tables.

94.6.3

Values shall be coded in the order indicated by the sequence descriptors, replication descriptors, operator descriptors and element descriptors.

Notes:

- (1) Where more than one data subset is included in a single BUFR message without data compression:
 - (i) The first set of data values shall be in the order defined by the data description, and shall represent the first data subset;
 - (ii) Subsequent sets of data values shall also be in the order defined by the data description, representing subsequent data subsets.
- (2) Where more than one data subset is included in a single BUFR message, data compression may be used as follows:
 - (i) Values for each data element are grouped into sets, and the sets shall be in the order defined by the data description; the first value in each set shall represent a minimum value for the set; for character data the first value in the set shall be set to all bits zero; however, if the character data values in all subsets are identical, the first value shall represent the character string; this value is termed a "local reference value", R^0 , with respect to the subsequent set of data;
 - (ii) Local reference values shall be coded according to Regulation 94.6.2;
 - (iii) If all values of an element are missing, R^0 shall be coded with all bits set to 1;
 - (iv) The local reference value shall be followed by a 6-bit quantity specifying the number of bits for each increment or for character data, specifying the number of octets needed for representing the character string in the data subsets. However, if the character data values in all subsets are identical, sub-note vii shall apply;
 - (v) Integer values (V), other than character values and missing values, will then be obtained as:

$$V = R + R^0 + I$$
 where R = table reference value
 R^0 = local reference value
 I = increment;
 Actual data values (V_a) will be then obtained by:

$$V_a = V \times 10^{-S}$$
 where S = table scale value
 - (vi) Missing values will be denoted by setting all bits of the corresponding I to 1;
 - (vii) Data elements all having the same value throughout a set shall be signified by coding the number of bits required for storing I as zero; in such cases, the increments shall be omitted;
 - (viii) When operators qualified by a data present bit-map are present, it is required that the length and contents of the bit-map shall be identical for each data subset if data compression is to be used;
 - (ix) When delayed replication is present, it is required that the number of replications shall be identical for each data subset if data compression is to be used. In such cases, sub-note vii shall apply when coding the number of replications.

94.7

Section 5 – End section

The End section shall always be 4 octets long, character coded according to the International Alphabet No. 5 as 7777.

SPECIFICATIONS OF OCTET CONTENTS

Notes:

- (1) Octets are numbered 1, 2, 3, etc., starting at the beginning of each section.
- (2) In the following, bit positions within octets are referred to as bit 1 to bit 8, where bit 1 is the most significant and bit 8 is the least significant bit. Thus, an octet with only bit 8 set to 1 would have the integer value 1.
- (3) Specific features for different editions, when different, will be clearly indicated below in sequence.

Section 0 – Indicator section

Octet No.	Contents
1–4	BUFR (coded according to the CCITT International Alphabet No. 5)
5–7	Total length of BUFR message (including Section 0)
8	BUFR edition number (4)

Section 1 – Identification section

Octet No.	Contents
1–3	Length of section
4	BUFR master table (zero if standard WMO FM 94 BUFR tables are used – see Note 2)
5–6	Identification of originating/generating centre (see Common Code table C–11)
7–8	Identification of originating/generating sub-centre (allocated by originating/generating centre – see Common Code table C–12)
9	Update sequence number (zero for original messages and for messages containing only delayed reports; incremented for the other updates)
10	<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> Bit 1 = 0 = 1 Bits 2-8 </div> <div> No optional section Optional section follows Set to zero (reserved) </div> </div>
11	Data category (Table A)
12	International data sub-category (see Common Code table C–13 and Note 3)
13	Local data sub-category (defined locally by automatic data-processing (ADP) centres – see Note 3)
14	BUFR master table version number (see Common Code table C–0 and Note 2)
15	Version number of local tables used to augment master table in use – see Note 2
16–17	<div style="display: flex; align-items: center;"> <div style="margin-right: 10px;"> Year (4 digits) Month Day Hour Minute Second </div> <div style="font-size: 4em; line-height: 1;">}</div> <div> Most typical time for the BUFR message contents – see Note 4 </div> </div>
18	
19	
20	
21	
22	Second
23–	Optional – for local use by ADP centres

Notes:

- (1) If a BUFR message is corrected, the corrected message shall be produced at least as a complete subset, containing all data items. Operator 2 04 YYY qualified by descriptor 0 31 021 may be used to indicate which data item or items were corrected.
- (2) A BUFR master table may be defined for a scientific discipline other than meteorology. This shall be indicated by non-zero numeric values in octet 4. Such a table will be developed when a recognized organization exists with the necessary expertise to maintain such a master table, and when at least one of the following situations also exists:

- Requirements cannot be met using Master Table 0.
- There is expected to be a minimal amount of overlap with respect to the entries in Master Table 0.

The current list of master tables, along with their associated values in octet 4, is as follows:

- 0 Meteorology maintained by the World Meteorological Organization (WMO)
- 10 Oceanography maintained by the Intergovernmental Oceanographic Commission (IOC) of UNESCO

Whenever a new master table is developed, the following criteria shall apply:

- Table C may not be changed, nor may Classes 00 and 31 of Table B. These would remain identical for any of the master tables.
- For Classes 01 through 09 (coordinate classes) and Class 33 of Table B, and for Categories 00 and 01 of Table D, these classes and categories must have the same name and be used for the same types of descriptors as in Master Table 0; however, individual descriptors within these classes and categories would be left to the discretion of the Organization defining the particular master table in question.
- For Table A and all remaining classes of Table B and categories of Table D, these would be left to the discretion of the Organization defining the particular master table in question.

For all master tables (including Master Table 0):

- Each revision of the master tables shall be given a new version number.
 - Local tables shall define those parts of the master table which are reserved for local use, thus version numbers of local tables may be changed at will by the originating centre. If no local table is used, the version number of the local table shall be encoded as 0.
- (3) The local data sub-category is maintained for backwards-compatibility with BUFR editions 0-3, since many ADP centres have made extensive use of such values in the past. The international data sub-category introduced with BUFR edition 4 is intended to provide a mechanism for better understanding of the overall nature and intent of messages exchanged between ADP centres. These two values (i.e. local sub-category and international sub-category) are intended to be supplementary to one another, so both may be used within a particular BUFR message.
- (4) When accuracy of the time does not define a time unit, then the value for this unit shall be set to zero (e.g. for a SYNOP observation at 09 UTC, minute = 0, second = 0).

Section 2 – Optional section

Octet No.	Contents
1–3	Length of section
4	Set to zero (reserved)
5–	Reserved for local use by ADP centres

Section 3 – Data description section

Octet No.	Contents
1–3	Length of section
4	Set to zero (reserved)
5–6	Number of data subsets
7	Bit 1 = 1 Observed data = 0 Other data Bit 2 = 1 Compressed data = 0 Non-compressed data Bits 3–8 Set to zero (reserved)
8–	A collection of element descriptors, replication descriptors, operator descriptors and sequence descriptors, which define the form and contents of individual data elements comprising one data subset in the Data section

Notes:

- (1) The collection of descriptors, beginning at octet 8, is called the “data description”.

- (2) Each descriptor occupies 2 octets and contains 3 parts:

F	X	Y
2 bits	6 bits	8 bits

- (3) If $F = 0$, the descriptor is an element descriptor. The values of X and Y refer directly to a single entry in Table B, X indicating the class and Y the entry within that class.
- (4) If $F = 1$, the descriptor is a replication descriptor defining the replication data description operator according to Regulations 94.5.4.1 and 94.5.4.2. The values of X and Y define the scope of the operator and the number of replications, respectively. If $Y = 0$, delayed replication is defined; the next element descriptor will define a data item giving the number of replications; this descriptor may also indicate (by its value of Y) that the following datum is to be replicated together with the following descriptor.
- (5) If $F = 2$, the descriptor is an operator descriptor. The value of X indicates an operation in Table C. The meaning of Y depends on the operation.
- (6) If $F = 3$, the descriptor is a sequence descriptor. The values of X and Y refer directly to a single entry in Table D. Each entry in Table D contains a list of element descriptors, data description operators, and/or sequence descriptors. A sequence descriptor is defined to be equivalent to the corresponding list of descriptors at the Table D entry.
- (7) "Other data", as identified in octet 7, could, for example, be forecast information generated from a numerical model.

Section 4 – Data section

Octet No.	Contents
1–3	Length of Data section (octets)
4	Set to zero (reserved)
5–	Binary data as defined by sequence descriptors

Notes:

- (1) The binary data in non-compressed form may be described as follows:

$$R_{11}, R_{12}, R_{13}, \dots, R_{1s}$$

$$R_{21}, R_{22}, R_{23}, \dots, R_{2s}$$

$$\dots$$

$$\dots$$

$$\dots$$

$$R_{n1}, R_{n2}, R_{n3}, \dots, R_{ns}$$

where R_{ij} is the j^{th} value of the i^{th} data subset, s is the number of values per data subset, and n is the number of data subsets in the BUFR message; the data subsets each occupy an identical number of bits, unless delayed replication is used, and are *not* necessarily aligned on octet boundaries.

- (2) The binary data in compressed form may be described as follows:

$$R_1^0, \text{NBINC}_1, I_{11}, I_{12}, \dots, I_{1n}$$

$$R_2^0, \text{NBINC}_2, I_{21}, I_{22}, \dots, I_{2n}$$

$$\dots$$

$$\dots$$

$$\dots$$

$$R_s^0, \text{NBINC}_s, I_{s1}, I_{s2}, \dots, I_{sn}$$

where $R_1^0, R_2^0, \dots, R_s^0$ are local reference values for the set of values for each data element (number of bits as Table B).

$\text{NBINC}_1, \dots, \text{NBINC}_s$ contain, as 6-bit quantities, the number of bits occupied by the increments $(I_{11} \dots I_{1n}) \dots (I_{s1} \dots I_{sn})$. s is the number of data elements per data subset and n is the number of data subsets per BUFR message. If $\text{NBINC}_1 = 0$, all values of element I are equal to R_1^0 ; in such cases, the increments shall be omitted. For character data, NBINC shall contain the number of octets occupied by the character element. However, if the character data in all subsets are identical $\text{NBINC}=0$.

- (3) Associated fields are treated as separate data items and precede the data;

e.g.

ASSOCIATED FIELDS	DATA
N bits	M bits

Binary data with associated fields may be described as follows:

$$A_{11}, R_{11}, A_{12}, R_{12}, \dots, A_{1s}, R_{1s}$$

$$A_{21}, R_{21}, A_{22}, R_{22}, \dots, A_{2s}, R_{2s}$$

$$\dots$$

$$\dots$$

$$\dots$$

$$A_{n1}, R_{n1}, A_{n2}, R_{n2}, \dots, A_{ns}, R_{ns}$$

where A_{ij} R_{ij} is the j^{th} combined associated field value and data value of the i^{th} data subset, s is the number of values per data subset, and n is the number of data subsets in the BUFR message.

- (4) Binary data in compressed form with associated fields may be described as follows:

$$A_1^0, \text{NBINC}_{A1}, I_{A11}, I_{A12}, \dots, I_{A1n}$$

$$R_1^0, \text{NBINC}_{R1}, I_{R11}, I_{R12}, \dots, I_{R1n}$$

$$\dots$$

$$\dots$$

$$\dots$$

$$A_s^0, \text{NBINC}_{As}, I_{As1}, I_{As2}, \dots, I_{Asn}$$

$$R_s^0, \text{NBINC}_{Rs}, I_{Rs1}, I_{Rs2}, \dots, I_{Rsn}$$

where $A_1^0, R_1^0, \dots, A_s^0, R_s^0$ are local reference values for the set of associated field values and the set of values for each data element.

R^0 uses bit length from Table B. A^0 uses bit length from descriptor 2 04 YYY.

Section 5 – End section

Octet No.	Contents
1–4	7777 (coded according to the CCITT International Alphabet No. 5)

BUFR TABLES, CODE TABLES AND FLAG TABLES

FM 94 BUFR refers to three types of tables: BUFR tables, code tables and flag tables.

BUFR tables

Tables containing information used to describe, classify and define the contents of a BUFR message are called BUFR tables. Four BUFR tables are defined: Tables A, B, C and D. Entry numbering shall be the same in BUFR tables and CREX tables (see definition of FM 95 CREX in Part C, Common Features to Binary and Alphanumeric Codes) for the same entity represented. Table B entries shall be listed in the common BUFR/CREX Table B. Table D common sequences shall not be defined in both BUFR Table D and CREX Table D, unless otherwise a conversion between both Tables D is not simple, that is, the conversion is not completed by simple replacement of part "F" of each descriptor. A new BUFR Table D sequence shall be assigned a number not used by any CREX Table D sequence. Similarly, if a CREX Table D sequence is not defined in BUFR Table D, it shall be assigned a number not used by any BUFR sequence.

Code tables and flag tables

BUFR Table B defines some elements by means of code tables or flag tables. Within this general description are included code tables referenced by code figures, and flag tables where each bit is set to 0 or 1 to indicate a false or true value with respect to a specific criterion. The concept of a flag table is especially useful where combinations of criteria are represented. Within BUFR, all code tables and flag tables refer to elements defined within BUFR Table B; they are numbered according to the X and Y values of the corresponding Table B reference.

BUFR TABLE RELATIVE TO SECTION 1**BUFR Table A – Data category**

<i>BUFR Table A – Data category</i>	
Code figure	Meaning
0	Surface data – land
1	Surface data – sea
2	Vertical soundings (other than satellite)
3	Vertical soundings (satellite)
4	Single level upper-air data (other than satellite)
5	Single level upper-air data (satellite)
6	Radar data
7	Synoptic features
8	Physical/chemical constituents
9	Dispersal and transport
10	Radiological data
11	BUFR tables, complete replacement or update
12	Surface data (satellite)
13	Forecasts
14	Warnings
15–19	Reserved
20	Status information
21	Radiances (satellite measured)
22	Radar (satellite) but not altimeter and scatterometer
23	Lidar (satellite)
24	Scatterometry (satellite)
25	Altimetry (satellite)
26	Spectrometry (satellite)
27	Gravity measurement (satellite)
28	Precision orbit (satellite)
29	Space environment (satellite)
30	Calibration datasets (satellite)
31	Oceanographic data
32	Lidar (ground-based)
33–100	Reserved
101	Image data (satellite)
102–239	Reserved
240–254	For experimental use
255	Other category

BUFR TABLES RELATIVE TO SECTION 3

BUFR/CREX Table B – Classification of elements

F	X	CLASS	COMMENTS
0	00	BUFR/CREX table entries	
0	01	Identification	Identifies origin and type of data
0	02	Instrumentation	Defines instrument types used
0	03	Instrumentation	Defines instrument types used
0	04	Location (time)	Defines time and time derivatives
0	05	Location (horizontal – 1)	Defines geographical position, including horizontal derivatives, in association with Class 06 (first dimension of horizontal space)
0	06	Location (horizontal – 2)	Defines geographical position, including horizontal derivatives, in association with Class 05 (second dimension of horizontal space)
0	07	Location (vertical)	Defines height, altitude, pressure level, including vertical derivatives of position
0	08	Significance qualifiers	Defines special character of data
0	09	Reserved	
0	10	Non-coordinate location (vertical)	Height, altitude, pressure and derivatives observed or measured, not defined as a vertical location
0	11	Wind and turbulence	Wind speed, direction, etc.
0	12	Temperature	
0	13	Hydrographic and hydrological	Humidity, rainfall, snowfall, etc. elements
0	14	Radiation and radiance	
0	15	Physical/chemical constituents	
0	19	Synoptic features	
0	20	Observed phenomena	Defines present/past weather, special phenomena, etc.
0	21	Radar data	
0	22	Oceanographic elements	
0	23	Dispersal and transport	
0	24	Radiological elements	
0	25	Processing information	
0	26	Non-coordinate location (time)	Defines time and time derivatives that are not coordinates
0	27	Non-coordinate location (horizontal – 1)	Defines geographical positions, in conjunction with Class 28, that are not coordinates
0	28	Non-coordinate location (horizontal – 2)	Defines geographical positions, in conjunction with Class 27, that are not coordinates
0	29	Map data	
0	30	Image	
0	31 ¹	Data description operator qualifiers	Elements used in conjunction with data description operators
0	33	Quality information	
0	35	Data monitoring information	

¹ This class does not exist in CREX.

FM 94 BUFR, FM 95 CREX

F	X	CLASS	COMMENTS
0	40	Satellite data	
0	41	Oceanographic/biogeochemical parameters	
0	42	Oceanographic elements	

Notes:

- (1) Where a code table or flag table is appropriate, "code table" or "flag table", respectively is entered in the UNITS column.
- (2) The code tables and flag tables associated with Table B are numbered to correspond with the F, X and Y part of the table reference.
- (3) To encode values into BUFR, the data (with units as specified in the UNIT column) must be multiplied by 10 to the power SCALE. Then subtract the REFERENCE VALUE to give the coded value found in Section 4 of the BUFR message. For example, a measured latitude is – 45.76 degrees. The coarse accuracy descriptor is 0 05 002 and the encoded value is – $45.76 \times 102 - (-9000) = 4424$.
- (4) Where UNITS are given as CCITT IA5, data shall be coded as character data left justified within the field width indicated using CCITT International Alphabet No. 5, and blank filled to the full field width indicated.
- (5) Classes 48 to 63 are reserved for local use; all other classes are reserved for future development.
- (6) Entries 192 to 255 within all classes are reserved for local use.
- (7) The use of local descriptors, as defined in Notes 5 and 6, in messages intended for non-local or international exchange is strongly discouraged. They should be kept to the barest minimum possible and must also be by-passed by the use of descriptor 2 06 YYY.
- (8) First-order statistics are included in Table B only when they are produced, as such, by the observing system.
- (9) In all flag tables within the BUFR specification, bits are numbered from 1 to N from the most significant to least significant within a data of N bits, i.e. bit No.1 is the leftmost and bit No. N is the rightmost bit within the data width. The bit No. N (least significant bit) is set to 1 only if all the bits are set to 1 within the data width of the flag table to represent a missing value.

Class 00 – BUFR/CREX table entries

Class 00								
TABLE REFERENCE F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
0 00 001	Table A: entry	CCITT IA5	0	0	24	Character	0	3
0 00 002	Table A: data category description, line 1	CCITT IA5	0	0	256	Character	0	32
0 00 003	Table A: data category description, line 2	CCITT IA5	0	0	256	Character	0	32
0 00 004	BUFR/CREX Master table (see Note 1)	CCITT IA5	0	0	16	Character	0	2
0 00 005	BUFR/CREX edition number	CCITT IA5	0	0	24	Character	0	3
0 00 006	BUFR Master table version number (see Note 2)	CCITT IA5	0	0	16	Character	0	2
0 00 007	CREX Master table version number (see Note 3)	CCITT IA5	0	0	16	Character	0	2
0 00 008	BUFR Local table version number (see Note 4)	CCITT IA5	0	0	16	Character	0	2
0 00 010	F descriptor to be added or defined	CCITT IA5	0	0	8	Character	0	1
0 00 011	X descriptor to be added or defined	CCITT IA5	0	0	16	Character	0	2
0 00 012	Y descriptor to be added or defined	CCITT IA5	0	0	24	Character	0	3
0 00 013	Element name, line 1	CCITT IA5	0	0	256	Character	0	32
0 00 014	Element name, line 2	CCITT IA5	0	0	256	Character	0	32
0 00 015	Units name	CCITT IA5	0	0	192	Character	0	24
0 00 016	Units scale sign	CCITT IA5	0	0	8	Character	0	1
0 00 017	Units scale	CCITT IA5	0	0	24	Character	0	3
0 00 018	Units reference sign	CCITT IA5	0	0	8	Character	0	1
0 00 019	Units reference value	CCITT IA5	0	0	80	Character	0	10
0 00 020	Element data width	CCITT IA5	0	0	24	Character	0	3

FM 94 BUFR, FM 95 CREX

Class 00								
TABLE REFERENCE F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
0 00 024	Code figure	CCITT IA5	0	0	64	Character	0	8
0 00 025	Code figure meaning	CCITT IA5	0	0	496	Character	0	62
0 00 026	Bit number	CCITT IA5	0	0	48	Character	0	6
0 00 027	Bit number meaning	CCITT IA5	0	0	496	Character	0	62
0 00 030	Descriptor defining sequence	CCITT IA5	0	0	48	Character	0	6

Notes:

- (1) Master tables are described in Note 2 to Section 1 of the BUFR regulations (part of the regulation entitled "Specifications of octet contents").
- (2) BUFR master table version numbers are described in Common Code table C-0 and Note 2 to Section 1 of BUFR regulations.
- (3) CREX master table version numbers are described in Common Code table C-0.
- (4) For local table version number, see last part of Note 2 to Section 1 of BUFR regulations.
- (5) For CREX descriptors F = B, not 0.

Class 01 –BUFR/CREX Identification

Class 01								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTER S)
F X Y								
0 01 001	WMO block number	Numeric	0	0	7	Numeric	0	2
0 01 002	WMO station number	Numeric	0	0	10	Numeric	0	3
0 01 003	WMO Region number/geographical area	Code table	0	0	3	Code table	0	1
0 01 004	WMO Region sub-area (see Note 9)	Numeric	0	0	3	Numeric	0	1
0 01 005	Buoy/platform identifier	Numeric	0	0	17	Numeric	0	5
0 01 006	Aircraft flight number	CCITT IA5	0	0	64	Character	0	8
0 01 007	Satellite identifier	Code table	0	0	10	Code table	0	4
0 01 008	Aircraft registration number or other identification	CCITT IA5	0	0	64	Character	0	8
0 01 009	Type of commercial aircraft	CCITT IA5	0	0	64	Character	0	8
0 01 010	Stationary buoy platform identifier; e.g. C-MAN buoys	CCITT IA5	0	0	64	Character	0	8
0 01 011	Ship or mobile land station identifier	CCITT IA5	0	0	72	Character	0	9
0 01 012	Direction of motion of moving observing platform (see Notes 14 and 15)	degree true	0	0	9	degree true	0	3
0 01 013	Speed of motion of moving observing platform (see Notes 14 and 15)	m s ⁻¹	0	0	10	m s ⁻¹	0	3
0 01 014	Platform drift speed (high precision)	m s ⁻¹	2	0	10	m s ⁻¹	2	4
0 01 015	Station or site name	CCITT IA5	0	0	160	Character	0	20
<u>0 01 016</u>	<u>Satellite sub-identifier</u>	<u>Numeric</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Numeric</u>	<u>0</u>	<u>5</u>
0 01 018	Short station or site name	CCITT IA5	0	0	40	Character	0	5
0 01 019	Long station or site name	CCITT IA5	0	0	256	Character	0	32
0 01 020	WMO Region sub-area	Numeric	0	0	4	Numeric	0	2
0 01 021	Synoptic feature identifier	Numeric	0	0	14	Numeric	0	4
0 01 022	Name of feature (see Note 11)	CCITT IA5	0	0	224	Character	0	28

FM 94 BUFR, FM 95 CREX

Class 01								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTER S)
F X Y								
0 01 023	Observation sequence number	Numeric	0	0	9	Numeric	0	3
0 01 024	Wind speed source	Code table	0	0	5	Code table	0	2
0 01 025	Storm identifier (see Note 1)	CCITT IA5	0	0	24	Character	0	3
0 01 026	WMO storm name (see Note 16)	CCITT IA5	0	0	64	Character	0	8
0 01 027	WMO long storm name (see Note 2)	CCITT IA5	0	0	80	Character	0	10
0 01 028	Aerosol optical depth (AOD) source	Code table	0	0	5	Code table	0	2
0 01 029	SSI source	Code table	0	0	5	Code table	0	2
0 01 030	Numerical model identifier (see Note 13)	CCITT IA5	0	0	128	Character	0	16
0 01 031	Identification of originating/ generating centre (see Note 10)	Code table	0	0	16	Code table	0	5
0 01 032	Generating application (see Notes 3, 4 and 5)	Code table defined by originating/ generating centre	0	0	8	Code table	0	3
0 01 033	Identification of originating/ generating centre	Common Code table C-1	0	0	8	Common Code table C-1	0	3
0 01 034	Identification of originating/ generating sub-centre	Common Code table C-12	0	0	8	Common Code table C-12	0	3
0 01 035	Originating/generating centre	Common Code table C-11	0	0	16	Common Code table C-11	0	5
0 01 036	Agency in charge of operating the observing platform	Code table	0	0	20	Code table	0	7
0 01 037	SIGMET sequence identifier	CCITT IA5	0	0	24	Character	0	3
0 01 038	Source of sea-ice fraction	Code table	0	0	5	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 01								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTER S)
0 01 039	Graphical Area Forecast (GFA) sequence identifier	CCITT IA5	0	0	40	Character	0	5
0 01 040	Processing centre ID code	CCITT IA5	0	0	48	Character	0	6
0 01 041	Absolute platform velocity – first component (see Notes 6, 7 and 8)	m s ⁻¹	5	– 1073741824	31	m s ⁻¹	5	10
0 01 042	Absolute platform velocity – second component (see Notes 6, 7 and 8)	m s ⁻¹	5	– 1073741824	31	m s ⁻¹	5	10
0 01 043	Absolute platform velocity – third component (see Notes 6, 7 and 8)	m s ⁻¹	5	– 1073741824	31	m s ⁻¹	5	10
0 01 044	Standard generating application	Code table	0	0	8	Code table	0	3
0 01 050	Platform transmitter ID number	Numeric	0	0	17	Numeric	0	6
0 01 051	Platform transmitter ID number	CCITT IA5	0	0	96	Character	0	12
0 01 052	Platform transmitter ID	Code table	0	0	3	Code table	0	1
0 01 053	Tsunami report sequence number triggered by a tsunami event	Numeric	0	0	7	Numeric	0	2
0 01 060	Aircraft reporting point (Beacon identifier)	CCITT IA5	0	0	64	Character	0	8
0 01 062	Short ICAO location indicator	CCITT IA5	0	0	32	Character	0	4
0 01 063	ICAO location indicator	CCITT IA5	0	0	64	Character	0	8
0 01 064	Runway designator	CCITT IA5	0	0	32	Character	0	4
0 01 065	ICAO region identifier	CCITT IA5	0	0	256	Character	0	32
0 01 075	Tide station identification	CCITT IA5	0	0	40	Character	0	5
0 01 079	Unique identifier for the profile	CCITT IA5	0	0	64	Character	0	8
0 01 080	Ship line number according to SOOP	CCITT IA5	0	0	32	Character	0	4
0 01 081	Radiosonde serial number	CCITT IA5	0	0	160	Character	0	20
0 01 082	Radiosonde ascension number (see Note 12)	Numeric	0	0	14	Numeric	0	4
0 01 083	Radiosonde release number (see Note 12)	Numeric	0	0	3	Numeric	0	1

FM 94 BUFR, FM 95 CREX

Class 01								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTER S)
F X Y								
0 01 085	Observing platform manufacturer's model	CCITT IA5	0	0	160	Character	0	20
0 01 086	Observing platform manufacturer's serial number	CCITT IA5	0	0	256	Character	0	32
0 01 087	WMO marine observing platform extended identifier	Numeric	0	0	23	Numeric	0	7
0 01 090	Technique for making up initial perturbations	Code table	0	0	8	Code table	0	3
0 01 091	Ensemble member number	Numeric	0	0	10	Numeric	0	4
0 01 092	Type of ensemble forecast	Code table	0	0	8	Code table	0	3
0 01 093	Balloon lot number	CCITT IA5	0	0	96	Character	0	12
0 01 094	WBAN number	Numeric	0	0	17	Numeric	0	5
0 01 095	Observer identification	CCITT IA5	0	0	32	Character	0	4
0 01 096	Station acquisition	CCITT IA5	0	0	160	Character	0	20
0 01 099	Unique product definition	CCITT IA5	0	0	248	Character	0	31
0 01 101	State identifier	Code table	0	0	10	Code table	0	3
0 01 102	National station number	Numeric	0	0	30	Numeric	0	9
0 01 103	IMO Number. Unique Lloyd's register	Numeric	0	0	24	Numeric	0	7
0 01 104	State/federal state identifier	CCITT IA5	0	0	32	Character	0	4
0 01 105	Highway designator	CCITT IA5	0	0	40	Character	0	5
0 01 106	Location along highway as indicated by position markers	m	-2	0	14	m	-2	5
0 01 110	Aircraft tail number	CCITT IA5	0	0	48	Character	0	6
0 01 111	Origination airport	CCITT IA5	0	0	24	Character	0	3
0 01 112	Destination airport	CCITT IA5	0	0	24	Character	0	3
0 01 113	Template version number defined by originating centre	Numeric	1	0	9	Numeric	1	3
0 01 114	Encrypted ship or mobile land station identifier (base64 encoding)	CCITT IA5	0	0	352	Character	0	44

FM 94 BUFR, FM 95 CREX

Class 01								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTER S)
0 01 115	Identifier of the cruise or mission under which the data were collected	CCITT IA5	0	0	160	Character	0	20
0 01 124	Grid point identifier	Numeric	0	0	24	Numeric	0	8
0 01 125	WIGOS identifier series	Numeric	0	0	4	Numeric	0	2
0 01 126	WIGOS issuer of identifier	Numeric	0	0	16	Numeric	0	5
0 01 127	WIGOS issue number	Numeric	0	0	16	Numeric	0	5
0 01 128	WIGOS local identifier (character)	CCITT IA5	0	0	128	Character	0	16
0 01 144	Snapshot identifier	Numeric	0	0	31	Numeric	0	10
0 01 145	<u>Light source identifier (see Note 17)</u>	<u>Numeric</u>	<u>0</u>	<u>-8</u>	<u>20</u>	<u>Numeric</u>	<u>0</u>	<u>7</u>
0 01 150	Coordinate reference system	Code table	0	0	16	Code table	0	5
0 01 151	Fixed mean sea-level reference datum	Code table	0	0	12	Code table	0	4
0 01 152	Semi-major axis of rotation ellipsoid	m	2	0	31	m	2	11
0 01 153	Semi-minor axis of rotation ellipsoid	m	2	0	31	m	2	11
0 01 154	Sensor identifier	Numeric	0	0	12	Numeric	0	4
0 01 155	Retrieval identifier	Code table	0	0	8	Code table	0	3

Notes:

- (1) The storm identifier (descriptor 0 01 025) has the following meaning: the first two characters shall be a numeric sequence number assigned by the originator of the message; the third character is a letter indicating the ocean basin where the storm is located, as follows:

W NW Pacific Ocean
 E NE Pacific Ocean to 140°W
 C NE Pacific Ocean 140°W – 180°W
 L N Atlantic Ocean, including Caribbean and Gulf of Mexico
 A N Arabian Sea
 B Bay of Bengal
 S S Indian Ocean
 P S Pacific Ocean
 F RSMC Nadi's zone in South Pacific

U Australia
O South China Sea
T East China Sea

There is no requirement that differing observers coordinate sequence numbers even though they both may be reporting the same storm.

- (2) WMO long storm name (descriptor 0 01 027): the storm name "Nameless" shall be used in those cases where an identifiable tropical disturbance has not reached tropical storm strength and has not been assigned an official name.
- (3) Where a centre other than the originating centre generates quality information, replacement or substitute values, and/or statistical information, the centre may be indicated by using 0 01 033.
- (4) A generating centre may wish to indicate a reference to the application that generated quality information, etc.; it may use descriptor 0 01 032 for this purpose. However, the corresponding code tables will vary from centre to centre.
- (5) Code table 0 01 032 is to be generated by each centre.
- (6) The components of absolute platform velocity (0 01 041, 0 01 042, 0 01 043) are defined as follows:
 - First component: From the Earth's centre to 0 degree longitude at the Equator: velocity of the platform along this line relative to the Earth's centre.
 - Second component: From the Earth's centre to 90 degrees East longitude at the Equator: velocity of the platform along this line relative to the Earth's centre.
 - Third component: From the Earth's centre to the north pole: velocity of the platform along this line relative to the Earth's centre.
- (7) The values for descriptors 0 01 041, 0 01 042 and 0 01 043 have been chosen to be suitable for polar orbiting satellites in approximately Sun-synchronous orbits. Geostationary orbits would require greater data widths for distance and slightly less for speed.
- (8) Left handed x, y and z axes have been chosen for descriptors 0 01 041, 0 01 042 and 0 01 043.
- (9) Descriptor 0 01 020 should be used instead of 0 01 004 for encoding this element.
- (10) Descriptor 0 01 033 shall be used instead of descriptor 0 01 031 for encoding originating/generating centre. Code table 0 01 034 is to be established by the associated originating/generating centre identified by descriptor 0 01 033 and provided to the Secretariat for publication.
- (11) For 0 01 022, the character string representing the "Name of feature" should be of the form: "Type of phenomenon" – "Location or geographical name" e.g. "volcano – Popocatepetl", "oil fire – Kuwait").
- (12) Descriptor 0 01 082 is to be used for reporting the sequential number of the current radiosonde reporting period (e.g. synoptic cycle) within a given year or other similar locally defined length of time. Descriptor 0 01 083 is to be used in the case of multiple sequential radiosonde releases during a single reporting period (e.g. synoptic cycle), in order to indicate which particular release generated the corresponding data values.
- (13) The value of this feature could be a string of characters, which contain the name of the model and other useful elements such as the model mesh.
- (14) Stationary position of ship shall be reported by 0 01 012 set to 0 and 0 01 013 set to 0. Course of ship unknown ($D_s = 9$) shall be reported by 0 01 012 set to 509.
- (15) Descriptors 0 01 012 and 0 01 013 may relate to parameters of various meanings and the corresponding values may be integrated on different periods.
- (16) Descriptor 0 01 027 should be used instead of 0 01 026 to encode this element.

(17) Positive value of descriptor 0 01 145 corresponds to Hipparcos identifier; 0 is Sun, -2 is Venus, -4 is Mars, -5 is Jupiter, -6 is Saturn, -7 is Earth's moon, and -8 is Bright limb.

Provisional Copy
2023

Class 02 – BUFR/CREX Instrumentation

Class 02								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 02 001	Type of station	Code table	0	0	2	Code table	0	1
0 02 002	Type of instrumentation for wind measurement	Flag table	0	0	4	Flag table	0	2
0 02 003	Type of measuring equipment used	Code table	0	0	4	Code table	0	2
0 02 004	Type of instrumentation for evaporation measurement or type of crop for which evapotranspiration is reported	Code table	0	0	4	Code table	0	2
0 02 005	Precision of temperature observation	K	2	0	7	K	2	3
0 02 006	Upper air remote sensing instrument type	Code table	0	0	6	Code table	0	0
0 02 007	Type of sensor for water level measuring instrument	Code table	0	0	6	Code table	0	2
0 02 008	Type of offshore platform	Code table	0	0	4	Code table	0	2
0 02 011	Radiosonde type	Code table	0	0	8	Code table	0	3
0 02 012	Radiosonde computational method	Code table	0	0	4	Code table	0	2
0 02 013	Solar and infrared radiation correction	Code table	0	0	4	Code table	0	2
0 02 014	Tracking technique/status of system used	Code table	0	0	7	Code table	0	3
0 02 015	Radiosonde completeness	Code table	0	0	4	Code table	0	2
0 02 016	Radiosonde configuration	Flag table	0	0	5	Flag table	0	2
0 02 017	Correction algorithms for humidity measurements	Code table	0	0	5	Code table	0	2
0 02 019	Satellite instruments	Code table	0	0	11	Code table	0	4
0 02 020	Satellite classification	Code table	0	0	9	Code table	0	3

FM 94 BUFR, FM 95 CREX

Class 02								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 02 021	Satellite instrument data used in processing (see Note 8)	Flag table	0	0	9	Flag table	0	3
0 02 022	Satellite data-processing technique used	Flag table	0	0	8	Flag table	0	3
0 02 023	Satellite-derived wind computation method	Code table	0	0	4	Code table	0	2
0 02 024	Integrated mean humidity computational method	Code table	0	0	4	Code table	0	2
0 02 025	Satellite channel(s) used in computation	Flag table	0	0	25	Flag table	0	9
0 02 026	Cross-track resolution	m	2	0	12	m	2	4
0 02 027	Along-track resolution	m	2	0	12	m	2	4
0 02 028	Segment size at nadir in x-direction	m	0	0	18	m	0	6
0 02 029	Segment size at nadir in y-direction	m	0	0	18	m	0	6
0 02 030	Method of current measurement	Code table	0	0	3	Code table	0	1
0 02 031	Duration and time of current measurement	Code table	0	0	5	Code table	0	2
0 02 032	Indicator for digitization	Code table	0	0	2	Code table	0	1
0 02 033	Method of salinity/depth measurement	Code table	0	0	3	Code table	0	1
0 02 034	Drogue type	Code table	0	0	5	Code table	0	2
0 02 035	Cable length	m	0	0	9	m	0	3
0 02 036	Buoy type	Code table	0	0	2	Code table	0	1
0 02 037	Method of tidal observation	Code table	0	0	3	Code table	0	1
0 02 038	Method of water temperature and/or salinity measurement	Code table	0	0	4	Code table	0	2
0 02 039	Method of wet-bulb temperature measurement	Code table	0	0	3	Code table	0	1

FM 94 BUFR, FM 95 CREX

Class 02								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 02 040	Method of removing velocity and motion of platform from current	Code table	0	0	4	Code table	0	2
0 02 041	Method for estimating reports related to synoptic features	Code table	0	0	6	Code table	0	2
0 02 042	Indicator for sea-surface current speed	Code table	0	0	2	Code table	0	1
0 02 044	Indicator for method of calculating spectral wave data	Code table	0	0	4	Code table	0	2
0 02 045	Indicator for type of platform	Code table	0	0	4	Code table	0	2
0 02 046	Wave measurement instrumentation	Code table	0	0	4	Code table	0	2
0 02 047	Deep-ocean tsunameter type	Code table	0	0	7	Code table	0	2
0 02 048	Satellite sensor indicator	Code table	0	0	4	Code table	0	2
0 02 049	Geostationary satellite data-processing technique used	Flag table	0	0	8	Flag table	0	3
0 02 050	Geostationary sounder satellite channels used	Flag table	0	0	20	Flag table	0	7
0 02 051	Indicator to specify observing method for extreme temperatures	Code table	0	0	4	Code table	0	2
0 02 052	Geostationary imager satellite channels used	Flag table	0	0	6	Flag table	0	2
0 02 053	GOES-I/M brightness temperature characteristics	Code table	0	0	4	Code table	0	2
0 02 054	GOES-I/M soundings parameter characteristics	Code table	0	0	4	Code table	0	2
0 02 055	Geostationary soundings statistical parameters	Code table	0	0	4	Code table	0	2
0 02 056	Geostationary soundings accuracy statistics	Code table	0	0	4	Code table	0	2
0 02 057	Origin of first-guess information for GOES-I/M soundings	Code table	0	0	4	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 02								
TABLE REFERENCE F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
0 02 058	Valid times of first-guess information for GOES-I/M soundings	Code table	0	0	4	Code table	0	2
0 02 059	Origin of analysis information for GOES-I/M soundings	Code table	0	0	4	Code table	0	2
0 02 060	Origin of surface information for GOES-I/M soundings	Code table	0	0	4	Code table	0	2
0 02 061	Aircraft navigational system	Code table	0	0	3	Code table	0	1
0 02 062	Type of aircraft data relay system	Code table	0	0	4	Code table	0	2
0 02 063	Aircraft roll angle	°	2	-18000	16	°	2	5
0 02 064	Aircraft roll angle quality	Code table	0	0	2	Code table	0	1
0 02 065	ACARS ground-receiving station	CCITT IA5	0	0	40	Character	0	5
0 02 066	Radiosonde ground receiving system	Code table	0	0	6	Code table	0	2
0 02 067	Radiosonde operating frequency	Hz	-5	0	15	Hz	-5	5
0 02 070	Original specification of latitude/longitude	Code table	0	0	4	Code table	0	2
0 02 071	Spectrographic wavelength	m	13	0	30	m	13	10
0 02 072	Spectrographic width	m	13	0	30	m	13	10
0 02 080	Balloon manufacturer	Code table	0	0	6	Code table	0	2
0 02 081	Type of balloon	Code table	0	0	5	Code table	0	2
0 02 082	Weight of balloon	kg	3	0	12	kg	3	4
0 02 083	Type of balloon shelter	Code table	0	0	4	Code table	0	2
0 02 084	Type of gas used in balloon	Code table	0	0	4	Code table	0	2
0 02 085	Amount of gas used in balloon	kg	3	0	13	kg	3	4
0 02 086	Balloon flight train length	m	1	0	10	m	1	4
0 02 087	Parachute surface area	m ²	4	0	15	m ²	4	5
0 02 088	Volume of gas used in balloon	m ³	3	0	13	m ³	3	4
0 02 090	Instrument wavelength	m	9	0	16	m	9	5

FM 94 BUFR, FM 95 CREX

Class 02								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 02 091	Entry sensor 4/20 mA	A	4	0	10	A	4	3
0 02 092	Ozone profile computation method	Code table	0	0	3	Code table	0	1
0 02 095	Type of pressure sensor	Code table	0	0	5	Code table	0	2
0 02 096	Type of temperature sensor	Code table	0	0	5	Code table	0	2
0 02 097	Type of humidity sensor	Code table	0	0	5	Code table	0	2
0 02 099	Polarization	Code table	0	0	3	Code table	0	1
0 02 100	Radar constant (see Note 9)	dB	1	0	12	dB	1	4
0 02 101	Type of antenna	Code table	0	0	4	Code table	0	2
0 02 102	Antenna height above tower base	m	0	0	8	m	0	3
0 02 103	Radome	Flag table	0	0	2	Flag table	0	1
0 02 104	Antenna polarization	Code table	0	0	4	Code table	0	2
0 02 105	Maximum antenna gain	dB	0	0	6	dB	0	2
0 02 106	3-dB beamwidth	°	1	0	6	°	1	2
0 02 107	Sidelobe suppression	dB	0	0	6	dB	0	2
0 02 108	Crosspol discrimination (on axis)	dB	0	0	6	dB	0	2
0 02 109	Antenna speed (azimuth)	degree/s	2	0	12	degree/s	2	4
0 02 110	Antenna speed (elevation)	degree/s	2	0	12	degree/s	2	4
0 02 111	Radar incidence angle	°	1	0	10	°	1	4
0 02 112	Radar look angle	°	1	0	12	°	1	4
0 02 113	Number of azimuth looks	Numeric	0	0	4	Numeric	0	2
0 02 114	Antenna effective surface area	m ²	0	0	15	m ²	0	5
0 02 115	Type of surface observing equipment	Code table	0	0	5	Code table	0	2
0 02 116	Percentage of 320 MHz band processed	%	0	0	7	%	0	3
0 02 117	Percentage of 80 MHz band processed	%	0	0	7	%	0	3
0 02 118	Percentage of 20 MHz band processed	%	0	0	7	%	0	3

FM 94 BUFR, FM 95 CREX

Class 02								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 02 119	RA-2 instrument operations	Code table	0	0	3	Code table	0	1
0 02 120	Ocean wave frequency	Hz	3	0	10	Hz	3	4
0 02 121	Mean frequency	Hz	-8	0	7	Hz	-8	3
0 02 122	Frequency agility range	Hz	-6	-128	8	Hz	-6	3
0 02 123	Peak power	W	-4	0	7	W	-4	3
0 02 124	Average power	W	-1	0	7	W	-1	3
0 02 125	Pulse repetition frequency	Hz	-1	0	8	Hz	-1	3
0 02 126	Pulse width	s	7	0	6	s	7	2
0 02 127	Receiver intermediate frequency	Hz	-6	0	7	Hz	-6	3
0 02 128	Intermediate frequency bandwidth	Hz	-5	0	6	Hz	-5	2
0 02 129	Minimum detectable signal	dB	0	-150	5	dB	0	3
0 02 130	Dynamic range	dB	0	0	7	dB	0	3
0 02 131	Sensitivity time control (STC)	Flag table	0	0	2	Flag table	0	1
0 02 132	Azimuth pointing accuracy	°	2	0	6	°	2	2
0 02 133	Elevation pointing accuracy	°	2	0	6	°	2	2
0 02 134	Antenna beam azimuth	°	2	0	16	°	2	5
0 02 135	Antenna elevation	°	2	-9000	15	°	2	5
0 02 136	Range processed by range attenuation correction	m	-3	0	16	m	-3	5
0 02 137	Radar dual PRF ratio	Code table	0	0	4	Code table	0	2
0 02 138	Antenna rotation direction	Code table	0	0	2	Code table	0	1
0 02 139	SIRAL instrument configuration	Code table	0	0	2	Code table	0	1
0 02 140	Satellite radar beam azimuth angle (see Note 4)	°	0	0	9	°	0	3
0 02 141	Measurement type	CCITT IA5	0	0	24	Character	0	3
0 02 142	Ozone instrument serial number/ identification (see Note 5)	CCITT IA5	0	0	32	Character	0	4
0 02 143	Ozone instrument type	Code table	0	0	7	Code table	0	3

FM 94 BUFR, FM 95 CREX

Class 02								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 02 144	Light source type for Brewer spectrophotometer	Code table	0	0	4	Code table	0	2
0 02 145	Wavelength setting for Dobson instruments	Code table	0	0	4	Code table	0	2
0 02 146	Source conditions for Dobson instruments	Code table	0	0	4	Code table	0	2
0 02 147	Method of transmission to collection centre	Code table	0	0	6	Code table	0	2
0 02 148	Data collection and/or location system	Code table	0	0	5	Code table	0	2
0 02 149	Type of data buoy	Code table	0	0	6	Code table	0	2
0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	Code table	0	0	6	Code table	0	2
0 02 151	Radiometer identifier	Code table	0	0	11	Code table	0	4
0 02 152	Satellite instrument used in data processing (see Note 6)	Flag table	0	0	31	Flag table	0	10
0 02 153	Satellite channel centre frequency	Hz	-8	0	26	Hz	-8	8
0 02 154	Satellite channel band width	Hz	-8	0	26	Hz	-8	8
0 02 155	Satellite channel wavelength	m	9	0	16	m	9	5
0 02 156	Percentage of valid KU ocean retracker measurements	%	0	0	7	%	0	3
0 02 157	Percentage of valid S ocean retracker measurements	%	0	0	7	%	0	3
0 02 158	RA-2 instrument	Flag table	0	0	9	Flag table	0	3
0 02 159	MWR instrument	Flag table	0	0	8	Flag table	0	3
0 02 160	Wavelength of the radar	Code table	0	0	4	Code table	0	2
0 02 161	Wind processing method	Flag table	0	0	16	Flag table	0	6
0 02 162	Extended height assignment method	Code table	0	0	6	Code table	0	2
0 02 163	Height assignment method	Code table	0	0	4	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 02								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 02 164	Tracer correlation method	Code table	0	0	3	Code table	0	1
0 02 165	Radiance type flags	Flag table	0	0	15	Flag table	0	5
0 02 166	Radiance type	Code table	0	0	4	Code table	0	2
0 02 167	Radiance computational method	Code table	0	0	4	Code table	0	2
0 02 168	Hydrostatic pressure of lower end of cable (thermistor string)	Pa	-3	0	16	kPa	0	5
0 02 169	Anemometer type	Code table	0	0	4	Code table	0	2
0 02 170	Aircraft humidity sensors	Code table	0	0	6	Code table	0	2
0 02 171	Instrument serial number for water temperature profile measurement	CCITT IA5	0	0	64	Character	0	8
0 02 172	Product type for retrieved atmospheric gases	Code table	0	0	8	Code table	0	3
0 02 173	Square of the off-nadir angle (see Note 7)	degree ²	4	0	10	degree ²	4	4
0 02 174	Mean across track pixel number	Numeric	0	0	9	Numeric	0	3
0 02 175	Method of precipitation measurement	Code table	0	0	4	Code table	0	2
0 02 176	Method of state of ground measurement	Code table	0	0	4	Code table	0	2
0 02 177	Method of snow depth measurement	Code table	0	0	4	Code table	0	2
0 02 178	Method of liquid content measurement of precipitation	Code table	0	0	4	Code table	0	2
0 02 179	Type of sky condition algorithm	Code table	0	0	4	Code table	0	2
0 02 180	Main present weather detecting system	Code table	0	0	4	Code table	0	2
0 02 181	Supplementary present weather sensor	Flag table	0	0	21	Flag table	0	7
0 02 182	Visibility measurement system	Code table	0	0	4	Code table	0	2
0 02 183	Cloud detection system	Code table	0	0	4	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 02								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 02 184	Type of lightning detection sensor	Code table	0	0	4	Code table	0	2
0 02 185	Method of evaporation measurement	Code table	0	0	4	Code table	0	2
0 02 186	Capability to detect precipitation phenomena	Flag table	0	0	30	Flag table	0	10
0 02 187	Capability to detect other weather phenomena	Flag table	0	0	18	Flag table	0	6
0 02 188	Capability to detect obscuration	Flag table	0	0	21	Flag table	0	7
0 02 189	Capability to discriminate lightning strikes	Flag table	0	0	12	Flag table	0	4
0 02 190	Lagrangian drifter submergence (% time submerged)	%	0	0	7	%	0	3
0 02 191	Geopotential height calculation	Code table	0	0	4	Code table	0	2

Notes:

- (1) This class shall contain elements to describe the instrumentation used to obtain the meteorological elements reported.
- (2) This class may also contain elements relating to observational procedures.
- (3) Some indication of expected accuracy may be implied in conjunction with certain elements in this class.
- (4) Note that descriptor 0 02 140 is the azimuth angle measured anticlockwise from satellite heading vector.
- (5) In descriptor 0 02 142: Ozone instrument serial number/identification is four characters long. For Japanese Dobson instruments, omit the leading digit(s).
- (6) Descriptor 0 02 019 should be used instead of descriptor 0 02 152 for single satellite instrument identification.
- (7) Square of off-nadir angle computed from Ku waveform-derived parameters, Unit 10^{-4} deg², Common minimum value 0, Common maximum value 900.
- (8) Descriptor 0 02 152 should be used instead of 0 02 021 for encoding this element.
- (9) This constant is defined as follows: $Z = P + \text{radar constant}$, where Z = the reflectivity of target in beam direction (dBZ) and P = the input receiver power above 1 mW (dBm). This constant is used to normalize the signal to the equivalent 100 km range.

Class 03 – BUFR/CREX Instrumentation

Class 03								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 03 001	Surface station type	Code table	0	0	5	Code table	0	2
0 03 003	Thermometer/hygrometer housing	Code table	0	0	4	Code table	0	2
0 03 004	Type of screen/shelter/radiation shield	Code table	0	0	4	Code table	0	2
0 03 005	Horizontal width of screen or shield (x)	m	3	0	16	m	3	5
0 03 006	Horizontal depth of screen or shield (y)	m	3	0	16	m	3	5
0 03 007	Vertical height of screen or shield (z)	m	3	0	16	m	3	5
0 03 008	Artificially ventilated screen or shield	Code table	0	0	3	Code table	0	1
0 03 009	Amount of forced ventilation at time of reading	m s ⁻¹	1	0	9	m s ⁻¹	1	3
0 03 010	Method of sea/water current measurement	Code table	0	0	4	Code table	0	2
0 03 011	Method of depth calculation	Code table	0	0	2	Code table	0	1
0 03 012	Instrument type/sensor for dissolved oxygen measurement	Code table	0	0	4	Code table	0	2
0 03 016	Position of road sensors	Code table	0	0	4	Code table	0	2
0 03 017	Extended type of station	Flag table	0	0	6	Flag table	0	2
0 03 018	Type of road	Code table	0	0	5	Code table	0	2
0 03 019	Type of construction	Code table	0	0	4	Code table	0	2
0 03 020	Material for thermometer/hygrometer housing	Code table	0	0	3	Code table	0	1
0 03 021	Hygrometer heating	Code table	0	0	2	Code table	0	1
0 03 022	Instrument owner	Code table	0	0	3	Code table	0	1

FM 94 BUFR, FM 95 CREX

Class 03								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 03 023	Configuration of louvers for thermometer/hygrometer screen	Code table	0	0	3	Code table	0	1
0 03 024	Psychrometric coefficient	K ⁻¹	6	0	10	K ⁻¹	6	3
0 03 025	Cross-track estimation area size	m	0	5000	16	m	0	5
0 03 026	Along-track estimation area size	m	0	5000	16	m	0	5
0 03 027	Type of flight rig	Code table	0	0	4	Code table	0	2
0 03 028	Method of snow water equivalent measurement	Code table	0	0	6	Code table	0	2
<u>0 03 029</u>	<u>Swath</u>	<u>Code table</u>	<u>0</u>	<u>0</u>	<u>3</u>	<u>Code table</u>	<u>0</u>	<u>1</u>
<u>0 03 030</u>	<u>Antenna status</u>	<u>Code table</u>	<u>0</u>	<u>0</u>	<u>3</u>	<u>Code table</u>	<u>0</u>	<u>1</u>

Class 04 – BUFR/CREX Location (time)

Class 04								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 04 001	Year	a	0	0	12	a	0	4
0 04 002	Month	mon	0	0	4	mon	0	2
0 04 003	Day	d	0	0	6	d	0	2
0 04 004	Hour	h	0	0	5	h	0	2
0 04 005	Minute	min	0	0	6	min	0	2
0 04 006	Second	s	0	0	6	s	0	2
0 04 007	Seconds within a minute (microsecond accuracy)	s	6	0	26	s	6	8
0 04 011	Time increment	a	0	-1024	11	a	0	4
0 04 012	Time increment	mon	0	-1024	11	mon	0	4
0 04 013	Time increment	d	0	-1024	11	d	0	4
0 04 014	Time increment	h	0	-1024	11	h	0	4
0 04 015	Time increment	min	0	-2048	12	min	0	4
0 04 016	Time increment	s	0	-4096	13	s	0	4
0 04 017	Reference time period for accumulated or extreme data	min	0	-1440	12	min	0	4
0 04 021	Time period or displacement	a	0	-1024	11	a	0	4
0 04 022	Time period or displacement	mon	0	-1024	11	mon	0	4
0 04 023	Time period or displacement	d	0	-1024	11	d	0	4
0 04 024	Time period or displacement	h	0	-2048	12	h	0	4
0 04 025	Time period or displacement	min	0	-2048	12	min	0	4
0 04 026	Time period or displacement	s	0	-4096	13	s	0	4
0 04 031	Duration of time relating to following value	h	0	0	8	h	0	3
0 04 032	Duration of time relating to following value	min	0	0	6	min	0	2

FM 94 BUFR, FM 95 CREX

Class 04								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 04 041	Time difference, UTC – LMT (see Note 6)	min	0	–1440	12	min	0	4
0 04 043	Day of the year	d	0	0	9	d	0	3
0 04 051	Principal time of daily reading of maximum temperature	h	0	0	5	h	0	2
0 04 052	Principal time of daily reading of minimum temperature	h	0	0	5	h	0	2
0 04 053	Number of days with precipitation equal to or more than 1 mm	Numeric	0	0	6	Numeric	0	2
0 04 059	Times of observation used to compute the reported mean values	Flag table	0	0	6	Flag table	0	2
0 04 065	Short time increment	min	0	–128	8	min	0	2
0 04 066	Short time increment	s	0	–128	8	s	0	2
0 04 073	Short time period or displacement	d	0	–128	8	d	0	2
0 04 074	Short time period or displacement	h	0	–128	8	h	0	2
0 04 075	Short time period or displacement	min	0	–128	8	min	0	2
0 04 080	Averaging period for following value	Code table	0	0	4	Code table	0	2
0 04 086	Long time period or displacement	s	0	–8192	15	s	0	5

Notes:

- (1) The significance of time periods or displacements may be indicated using the time significance code corresponding to table reference 0 08 021.
- (2) Where more than one time period or displacement is required to define complex time structures, they shall be defined in immediate succession, and the following ordering shall apply: ensemble period (if required), followed by forecast period (if required), followed by period for averaging or accumulation (if required).
- (3) Time periods or displacements and time increments require an initial time location to be defined prior to their use, followed where appropriate by a time significance definition.

FM 94 BUFR, FM 95 CREX

- (4) The time location, when used with forecast values, shall indicate the time of the initial state for the forecast, or the beginning of the forecast period; when used with ensemble means of forecast values, the time location shall indicate the initial state or the beginning of the first forecast over which ensemble means are derived.
 - (5) Negative time periods or displacements shall be used to indicate time periods or displacements preceding the currently defined time.
 - (6) Descriptor 0 04 041 has been replaced by the combination of 0 08 025 and 0 26 003 and should not be used for encoding this element.
 - (7) All times are Universal Time Coordinated (UTC) unless otherwise noted.
-

Provisional Copy
2023

Class 05 – BUFR/CREX Location (horizontal – 1)

Class 05								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 05 001	Latitude (high accuracy)	°	5	–9000000	25	°	5	7
0 05 002	Latitude (coarse accuracy)	°	2	–9000	15	°	2	4
0 05 011	Latitude increment (high accuracy)	°	5	–9000000	25	°	5	7
0 05 012	Latitude increment (coarse accuracy)	°	2	–9000	15	°	2	4
0 05 015	Latitude displacement (high accuracy)	°	5	–9000000	25	°	5	7
0 05 016	Latitude displacement (coarse accuracy)	°	2	–9000	15	°	2	4
0 05 021	Bearing or azimuth	degree true	2	0	16	degree true	2	5
0 05 022	Solar azimuth	degree true	2	0	16	degree true	2	5
0 05 023	Sun to satellite azimuth difference	°	1	–1800	12	°	1	4
0 05 030	Direction (spectral)	°	0	0	12	°	0	4
0 05 031	Row number	Numeric	0	0	12	Numeric	0	4
0 05 032	Y offset (see Note 6)	m	2	–1073741824	31	m	2	11
0 05 033	Pixel size on horizontal – 1	m	–1	0	16	m	–1	5
0 05 034	Along track row number	Numeric	0	0	11	Numeric	0	4
0 05 035	Maximum size of x-dimension	Numeric	0	0	12	Numeric	0	4
0 05 036	Ship transect number according to SOOP	Numeric	0	0	7	Numeric	0	2
0 05 040	Orbit number	Numeric	0	0	24	Numeric	0	8
0 05 041	Scan line number	Numeric	0	0	8	Numeric	0	3
0 05 042	Channel number	Numeric	0	0	6	Numeric	0	2
0 05 043	Field of view number	Numeric	0	0	8	Numeric	0	3
0 05 044	Satellite cycle number	Numeric	0	0	11	Numeric	0	4
0 05 045	Field of regard number	Numeric	0	0	8	Numeric	0	3
0 05 052	Channel number increment	Numeric	0	0	5	Numeric	0	2

FM 94 BUFR, FM 95 CREX


Class 05								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 05 053	Field of view number increment	Numeric	0	0	5	Numeric	0	2
0 05 060	Y angular position from centre of gravity	°	6	-8000000	24	°	6	8
0 05 061	Z angular position from centre of gravity	°	6	-8000000	24	°	6	8
0 05 063	Spacecraft roll	°	2	0	16	°	2	5
0 05 064	Spacecraft pitch	°	2	0	16	°	2	5
0 05 066	Spacecraft yaw	°	2	0	16	°	2	5
0 05 067	Number of scan lines	Numeric	0	0	8	Numeric	0	3
0 05 068	Profile number	Numeric	0	0	16	Numeric	0	5
0 05 069	Receiver channel	Code table	0	0	2	Code table	0	1
0 05 070	Observation identifier	Numeric	0	0	30	Numeric	0	10
0 05 071	Stripmap identifier	Numeric	0	0	16	Numeric	0	5
0 05 072	Number of spectra in range direction	Numeric	0	0	8	Numeric	0	3
0 05 073	Number of spectra in azimuthal direction	Numeric	0	0	8	Numeric	0	3
0 05 074	Index in range direction	Numeric	0	0	8	Numeric	0	3
0 05 075	Index in azimuthal direction	Numeric	0	0	8	Numeric	0	3
<u>0 05 076</u>	<u>Solar azimuth in instrument reference frame</u>	<u>deg</u>	<u>2</u>	<u>0</u>	<u>16</u>	<u>deg</u>	<u>2</u>	<u>6</u>
<u>0 05 077</u>	<u>Sub-satellite point latitude</u>	<u>deg</u>	<u>4</u>	<u>-900000</u>	<u>21</u>	<u>deg</u>	<u>4</u>	<u>7</u>
<u>0 05 078</u>	<u>Horn number</u>	<u>Numeric</u>	<u>0</u>	<u>0</u>	<u>4</u>	<u>Numeric</u>	<u>0</u>	<u>2</u>
<u>0 05 079</u>	<u>Band number</u>	<u>Numeric</u>	<u>0</u>	<u>0</u>	<u>6</u>	<u>Numeric</u>	<u>0</u>	<u>2</u>
<u>0 05 080</u>	<u>Resolution radius</u>	<u>m</u>	<u>-3</u>	<u>0</u>	<u>6</u>	<u>m</u>	<u>-3</u>	<u>2</u>

Notes:

- (1) Values of latitude and latitude increments are limited to the range -90 degrees to +90 degrees.
- (2) South latitude shall be assigned negative values.

FM 94 BUFR, FM 95 CREX

- (3) North to south increments shall be assigned negative values.
- (4) Bearing or azimuth shall only be used with respect to a stated location, and shall not redefine that location.
- (5) The pixel size on horizontal – 1 is given at location where map scale factor is unity.
- (6) Y offset is the distance between the projection origin and the upper left corner of the upper left pixel in a map, as shown in the following diagram:



Class 06 – BUFR/CREX Location (horizontal – 2)


Class 06								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 06 001	Longitude (high accuracy)	°	5	-18000000	26	°	5	8
0 06 002	Longitude (coarse accuracy)	°	2	-18000	16	°	2	5
0 06 011	Longitude increment (high accuracy)	°	5	-18000000	26	°	5	8
0 06 012	Longitude increment (coarse accuracy)	°	2	-18000	16	°	2	5
0 06 015	Longitude displacement (high accuracy)	°	5	-18000000	26	°	5	8
0 06 016	Longitude displacement (coarse accuracy)	°	2	-18000	16	°	2	5
0 06 021	Distance	m	-1	0	13	m	-1	4
0 06 029	Wave number	m ⁻¹	1	0	22	m ⁻¹	1	7
0 06 030	Wave number (spectral)	rad m ⁻¹	5	0	13	rad m ⁻¹	5	4
0 06 031	Column number	Numeric	0	0	12	Numeric	0	4
0 06 032	X offset (see Note 6)	m	2	-1073741824	31	m	2	11
0 06 033	Pixel size on horizontal – 2	m	-1	0	16	m	-1	5
0 06 034	Cross-track cell number	Numeric	0	0	7	Numeric	0	3
0 06 035	Maximum size of y-dimension	Numeric	0	0	12	Numeric	0	4
0 06 040	Radius of confidence	m	0	0	13	m	0	4
<u>0 06 041</u>	<u>Earth scan sample number</u>	<u>Numeric</u>	<u>0</u>	<u>0</u>	<u>11</u>	<u>Numeric</u>	<u>0</u>	<u>4</u>
<u>0 06 042</u>	<u>Space/moon scan sample number</u>	<u>Numeric</u>	<u>0</u>	<u>0</u>	<u>6</u>	<u>Numeric</u>	<u>0</u>	<u>2</u>
<u>0 06 043</u>	<u>Sub-satellite point longitude</u>	<u>deg</u>	<u>4</u>	<u>-1800000</u>	<u>22</u>	<u>deg</u>	<u>4</u>	<u>8</u>

Notes:

- (1) Values of longitude are limited to the range -180 degrees to +180 degrees.
- (2) West longitude shall be assigned negative values.
- (3) East to west increments shall be assigned negative values.

FM 94 BUFR, FM 95 CREX

- (4) Distance shall only be used with respect to a stated location and a bearing, azimuth or elevation; it shall not redefine that location.
- (5) The pixel size on horizontal – 2 is given at location where map scale factor is unity.
- (6) X offset is the distance between the projection origin and the upper left corner of the upper left pixel in a map, as shown in the following diagram:



Class 07 – BUFR/CREX Location (vertical)

Class 07								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 07 001	Height of station (see Note 1)	m	0	-400	15	m	0	5
0 07 002	Height or altitude	m	-1	-40	16	m	-1	5
0 07 003	Geopotential	m ² s ⁻²	-1	-400	17	m ² s ⁻²	-1	6
0 07 004	Pressure	Pa	-1	0	14	Pa	-1	5
0 07 005	Height increment	m	0	-400	12	m	0	4
0 07 006	Height above station	m	0	0	15	m	0	5
0 07 007	Height	m	0	-1000	17	m	0	6
0 07 008	Geopotential	m ² s ⁻²	0	-10000	20	m ² s ⁻²	0	7
0 07 009	Geopotential height	gpm	0	-1000	17	gpm	0	5
0 07 010	Flight level	m	0	-1024	16	ft	-1	5
0 07 012	Grid point altitude	m	2	-50000	20	m	2	7
0 07 021	Elevation (see Note 2)	°	2	-9000	15	°	2	5
0 07 022	Solar elevation	°	2	-9000	15	°	2	5
0 07 024	Satellite zenith angle	°	2	-9000	15	°	2	5
0 07 025	Solar zenith angle	°	2	-9000	15	°	2	5
0 07 026	Satellite zenith angle	°	4	-900000	21	°	4	7
0 07 030	Height of station ground above mean sea level (see Note 3)	m	1	-4000	17	m	1	5
0 07 031	Height of barometer above mean sea level (see Note 4)	m	1	-4000	17	m	1	5
0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 5)	m	2	0	16	m	2	5
0 07 033	Height of sensor above water surface (see Note 6)	m	1	0	12	m	1	4
0 07 035	Maximum size of z-dimension	Numeric	0	0	12	Numeric	0	4
0 07 036	Level index of z	Numeric	0	0	12	Numeric	0	4

FM 94 BUFR, FM 95 CREX

Class 07								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 07 040	Impact parameter (see Note 7)	m	1	62000000	22	m	1	8
0 07 061	Depth below land surface	m	2	0	14	m	2	5
0 07 062	Depth below sea/water surface	m	1	0	17	m	1	6
0 07 063	Depth below sea/water surface (cm)	m	2	0	20	m	2	7
0 07 064	Representative height of sensor above station (see Note 8)	m	0	0	4	m	0	2
0 07 065	Water pressure	Pa	-3	0	17	Pa	-3	6
0 07 070	Drogue depth	m	0	0	10	m	0	4
0 07 071	Height (high resolution)	m	3	-10000000	26	m	3	8
0 07 072	Scan angle	deg	2	-9000	15	deg	2	6
<u>0 07 073</u>	<u>Angle between moon and space view</u>	<u>deg</u>	<u>2</u>	<u>0</u>	<u>15</u>	<u>deg</u>	<u>2</u>	<u>5</u>
<u>0 07 074</u>	<u>Solar elevation angle in instrument reference frame</u>	<u>deg</u>	<u>2</u>	<u>-9000</u>	<u>15</u>	<u>deg</u>	<u>2</u>	<u>5</u>
<u>0 07 075</u>	<u>Scattering angle</u>	<u>deg</u>	<u>0</u>	<u>0</u>	<u>8</u>	<u>deg</u>	<u>0</u>	<u>3</u>
<u>0 07 076</u>	<u>Relative azimuth angle</u>	<u>deg</u>	<u>0</u>	<u>0</u>	<u>8</u>	<u>deg</u>	<u>0</u>	<u>3</u>

Notes:

- (1) Regarding data from ground-based stations, this descriptor should be used for archived data only. Descriptors 0 07 030 and 0 07 031 should be used and preferred to represent ground elevation and elevation of barometer, respectively, as defined in *Weather Reporting* (WMO-No. 9), Volume A – Observing Stations. Regarding marine stations, this descriptor refers to the height above mean sea level of the deck of marine platform where the instruments stand.
- (2) Elevation shall only be used with respect to a stated location and a bearing, azimuth or distance; it shall not redefine that location.
- (3) Height of station ground above mean sea level is defined as the height above mean sea level of the ground on which the raingauge stands or, if there is no raingauge, the ground beneath the thermometer screen. If there is neither raingauge nor screen, it is the average level of terrain in the vicinity of the station (Reference: *Guide to Meteorological Instruments and Methods of Observation* (WMO-No. 8), 1996).
- (4) Height of barometer above mean sea level, referring to the location of barometer of a station, does not redefine the descriptor 0 07 030.

- (5) Height of sensor above local ground (or deck of marine platform) is the actual height of sensor above ground (or deck of marine platform) at the point where the sensor is located. This descriptor does not redefine the descriptors 0 07 030 or 0 07 033. Previously defined value of 0 07 032 may be cancelled by setting 0 07 032 to a "missing value".
 - (6) Height of sensor above water surface is the height of sensor above water surface of sea or lake. This descriptor does not redefine descriptors 0 07 030 or 0 07 032. Previously defined value 0 07 033 may be cancelled by setting 0 07 033 to a "missing value".
 - (7) For an atmospheric limb sounder, the "impact parameter" is the distance between the ray asymptote and the centre of curvature of the Earth's surface at the tangent point.
 - (8) Representative height of sensor above station is the standard height of a sensor required by WMO documentation. The value of the following meteorological element should be adjusted using a formula. For example, standard height recommended in WMO documentation for surface wind sensors is 10 metres. If the sensor is placed at a different height, the wind speed may be adjusted using a formula.
-

Class 08 – BUFR/CREX Significance qualifiers

Class 08								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 08 001	Vertical sounding significance	Flag table	0	0	7	Flag table	0	3
0 08 002	Vertical significance (surface observations)	Code table	0	0	6	Code table	0	2
0 08 003	Vertical significance (satellite observations)	Code table	0	0	6	Code table	0	2
0 08 004	Phase of aircraft flight	Code table	0	0	3	Code table	0	1
0 08 005	Meteorological attribute significance	Code table	0	0	4	Code table	0	2
0 08 006	Ozone vertical sounding significance	Flag table	0	0	9	Flag table	0	3
0 08 007	Dimensional significance	Code table	0	0	4	Code table	0	2
0 08 008	Radiation vertical sounding significance	Flag table	0	0	9	Flag table	0	3
0 08 009	Detailed phase of flight	Code table	0	0	4	Code table	0	2
0 08 010	Surface qualifier (temperature data)	Code table	0	0	5	Code table	0	2
0 08 011	Meteorological feature	Code table	0	0	6	Code table	0	2
0 08 012	Land/sea qualifier	Code table	0	0	2	Code table	0	1
0 08 013	Day/night qualifier	Code table	0	0	2	Code table	0	1
0 08 014	Qualifier for runway visual range	Code table	0	0	4	Code table	0	2
0 08 015	Significant qualifier for sensor	Code table	0	0	3	Code table	0	1
0 08 016	Change qualifier of a trend-type forecast or an aerodrome forecast	Code table	0	0	3	Code table	0	1
0 08 017	Qualifier of the time when the forecast change is expected	Code table	0	0	2	Code table	0	1
0 08 018	SEAWINDS land/ice surface type	Flag table	0	0	17	Flag table	0	6
0 08 019	Qualifier for following centre identifier	Code table	0	0	4	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 08								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 08 020	Total number of missing entities (with respect to accumulation or average)	Numeric	0	0	16	Numeric	0	5
0 08 021	Time significance	Code table	0	0	5	Code table	0	2
0 08 022	Total number (with respect to accumulation or average)	Numeric	0	0	16	Numeric	0	5
0 08 023	First-order statistics (see Note 3)	Code table	0	0	6	Code table	0	2
0 08 024	Difference statistics (see Note 4)	Code table	0	0	6	Code table	0	2
0 08 025	Time difference qualifier (see Note 5)	Code table	0	0	4	Code table	0	2
0 08 026	Matrix significance	Code table	0	0	6	Code table	0	2
0 08 029	Surface type	Code table	0	0	8	Code table	0	3
0 08 030	<i>Manual on Codes</i> (Volume I.1, Section C) Code table from which data are derived	Numeric	0	0	13	Numeric	0	4
0 08 031	Data category – CREX table A	Numeric	0	0	8	Numeric	0	3
0 08 032	Status of operation	Code table	0	0	4	Code table	0	2
0 08 033	Method of derivation of percentage confidence (see Note 6)	Code table	0	0	7	Code table	0	3
0 08 034	Temperature/salinity measurement qualifier	Code table	0	0	4	Code table	0	2
0 08 035	Type of monitoring exercise	Code table	0	0	3	Code table	0	1
0 08 036	Type of centre or station performing monitoring	Code table	0	0	3	Code table	0	1
0 08 037	Baseline check significance	Code table	0	0	5	Code table	0	2
0 08 038	Instrument data significance	Code table	0	0	8	Code table	0	3
0 08 039	Time significance (Aviation forecast)	Code table	0	0	6	Code table	0	2
0 08 040	Flight level significance	Code table	0	0	6	Code table	0	2
0 08 041	Data significance	Code table	0	0	5	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 08								
TABLE REFERENCE F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
0 08 042	Extended vertical sounding significance	Flag table	0	0	18	Flag table	0	6
0 08 043	Atmospheric chemical or physical constituent type (see Note 7)	Code table	0	0	8	Code table	0	3
0 08 044	CAS registry number	CCITT IA5	0	0	88	Character	0	11
0 08 046	Atmospheric chemical or physical constituent type	Common Code table C-14	0	0	16	Common Code table C-14	0	5
0 08 049	Number of observations	Numeric	0	0	8	Numeric	0	3
0 08 050	Qualifier for number of missing values in calculation of statistic	Code table	0	0	4	Code table	0	2
0 08 051	Qualifier for number of missing values in calculation of statistic	Code table	0	0	3	Code table	0	1
0 08 052	Condition for which number of days of occurrence follows	Code table	0	0	5	Code table	0	2
0 08 053	Day of occurrence qualifier	Code table	0	0	2	Code table	0	1
0 08 054	Qualifier for wind speed or wind gusts	Code table	0	0	3	Code table	0	1
0 08 060	Sample scanning mode significance	Code table	0	0	4	Code table	0	2
0 08 065	Sun-glint indicator	Code table	0	0	2	Code table	0	1
0 08 066	Semi-transparency indicator	Code table	0	0	2	Code table	0	1
0 08 070	Vertical sounding product qualifier	Code table	0	0	4	Code table	0	2
0 08 072	Pixel(s) type	Code table	0	0	3	Code table	0	1
0 08 074	Altimeter echo type	Code table	0	0	2	Code table	0	1
0 08 075	Ascending/descending orbit qualifier	Code table	0	0	2	Code table	0	1
0 08 076	Type of band	Code table	0	0	6	Code table	0	2
0 08 077	Radiometer sensed surface type	Code table	0	0	7	Code table	0	3
0 08 079	Product status	Code table	0	0	4	Code table	0	2
0 08 080	Qualifier for GTSP quality flag	Code table	0	0	6	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 08								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 08 087	Corner position of observation	Code table	0	0	3	Code table	0	1
0 08 088	Map significance	Code table	0	0	6	Code table	0	2
0 08 090	Decimal scale of following significands (see Note 8)	Numeric	0	-127	8	Numeric	0	3
0 08 091	Coordinates significance	Code table	0	0	8	Code table	0	3
0 08 092	Measurement uncertainty expression	Code table	0	0	5	Code table	0	2
0 08 093	Measurement uncertainty significance	Code table	0	0	5	Code table	0	2
0 08 094	Method used to calculate the average daily temperature	Code table	0	0	8	Code table	0	3
0 08 095	Siting and measurement quality classification for temperature	Code table	0	0	8	Code table	0	3
0 08 096	Siting and measurement quality classification for precipitation	Code table	0	0	8	Code table	0	3
<u>0 08 097</u>	<u>Method used to calculate the average instrument temperature</u>	<u>Code table</u>	<u>0</u>	<u>0</u>	<u>7</u>	<u>Code table</u>	<u>0</u>	<u>3</u>
<u>0 08 098</u>	<u>Source of temperature measurement</u>	<u>Code table</u>	<u>0</u>	<u>0</u>	<u>4</u>	<u>Code table</u>	<u>0</u>	<u>2</u>
<u>0 08 099</u>	<u>Sensing direction</u>	<u>Code table</u>	<u>0</u>	<u>0</u>	<u>4</u>	<u>Code table</u>	<u>0</u>	<u>2</u>

Notes:

- (1) Where values are accumulated or averaged (for example over a time period), the total number of values from which the accumulated or averaged values are obtained may be represented using reference 0 08 022.
- (2) A previously defined significance may be cancelled by transmitting a "missing" from the appropriate code or flag table.
- (3) First-order statistics have values with a similar range and the same dimensions as the corresponding reported values (e.g., maxima, minima, means).
- (4) Difference statistics are difference values; they have dimensions similar to the corresponding reported values with respect to units, but assume a range centred on zero (e.g. the difference between reported and analysed values, the difference between reported and forecast values).
- (5) Descriptor 0 08 025 is to be used with 0 26 003 (time difference).
- (6) Descriptor 0 08 033 is to be used by preceding the element 0 33 007 as part of quality control information in order to specify the method used to calculate the percentage confidence.

- (7) When descriptor 0 08 043 is used to specify particulate matter (PM) under a given size threshold, descriptor 0 08 044 or 0 08 046 may also be used to further specify a subset of the PM population on the basis of ion composition.
 - (8) Descriptor 0 08 090 is to be used to establish the decimal scale of one or more subsequent numerical element descriptors requiring a large dynamic range of values. The numerical element descriptor(s) will contain the scaled value of the measurement(s) with the required number of significant digits. The actual value will be obtained, at the application level, by multiplying the scaled value by the given decimal scale: (scaled value $\times 10^{\text{decimal scale}}$).
-

Provisional Copy
2023

Class 10 – BUFR/CREX Non-coordinate location (vertical)

Class 010								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 10 001	Height of land surface	m	0	-400	15	m	0	5
0 10 002	Height	m	-1	-40	16	m	-1	5
0 10 003	Geopotential	m ² s ⁻²	-1	-400	17	m ² s ⁻²	-1	6
0 10 004	Pressure	Pa	-1	0	14	Pa	-1	5
0 10 007	Height	m	0	-1000	17	m	0	6
0 10 008	Geopotential	m ² s ⁻²	0	-10000	20	m ² s ⁻²	0	7
0 10 009	Geopotential height	gpm	0	-1000	17	gpm	0	5
0 10 010	Minimum pressure reduced to mean sea level	Pa	-1	0	14	Pa	-1	5
0 10 011	Maximum pressure reduced to mean sea level	Pa	-1	0	14	Pa	-1	5
0 10 031	In direction of the North Pole, distance from the Earth's centre (see Notes 2 and 3)	m	2	-1073741824	31	m	2	10
0 10 032	Satellite distance to Earth's centre	m	1	0	27	m	2	9
0 10 033	Altitude (platform to ellipsoid)	m	1	0	27	m	2	9
0 10 034	Earth's radius	m	1	0	27	m	2	9
0 10 035	Earth's local radius of curvature	m	1	62000000	22	m	1	8
0 10 036	Geoid undulation (see Note 4)	m	2	-15000	15	m	2	6
0 10 038	Maximum height of deck cargo above summer load line	m	0	0	6	m	0	2
0 10 039	Departure of reference level (summer maximum load line) from actual sea level	m	0	-32	6	m	0	3
0 10 040	Number of retrieved layers	Numeric	0	0	10	Numeric	0	4
0 10 050	Standard deviation altitude	m	2	0	16	m	2	5
0 10 051	Pressure reduced to mean sea level	Pa	-1	0	14	Pa	-1	5
0 10 052	Altimeter setting (QNH)	Pa	-1	0	14	Pa	-1	5

FM 94 BUFR, FM 95 CREX

Class 010								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 10 053	Global navigation satellite system altitude	m	0	-1000	17	m	0	5
0 10 060	Pressure change	Pa	-1	-1024	11	Pa	-1	4
0 10 061	3-hour pressure change	Pa	-1	-500	10	Pa	-1	4
0 10 062	24-hour pressure change	Pa	-1	-1000	11	Pa	-1	4
0 10 063	Characteristic of pressure tendency	Code table	0	0	4	Code table	0	2
0 10 064	SIGMET cruising level	Code table	0	0	3	Code table	0	1
0 10 070	Indicated aircraft altitude	m	0	-400	16	m	0	5
0 10 071	Vertical resolution	m	0	0	14	m	0	5
0 10 079	Off-nadir angle of the satellite from platform data	°	4	0	16	°	4	5
0 10 080	Viewing zenith angle	°	2	-9000	15	°	2	5
0 10 081	Altitude of COG above reference ellipsoid	m	3	0	31	m	3	10
0 10 082	Instantaneous altitude rate	m s ⁻¹	3	-65536	17	m s ⁻¹	3	6
0 10 083	Squared off-nadir angle of the satellite from platform data	degree ²	2	0	16	degree ²	2	5
0 10 084	Squared off-nadir angle of the satellite from waveform data	degree ²	2	0	16	degree ²	2	5
0 10 085	Mean sea-surface height	m	3	-131072	18	m	3	6
0 10 086	Geoid's height	m	3	-131072	18	m	3	6
0 10 087	Ocean depth/land elevation	m	1	-131072	18	m	1	6
0 10 088	Total geocentric ocean tide height (solution 1)	m	3	-32768	16	m	3	5
0 10 089	Total geocentric ocean tide height (solution 2)	m	3	-32768	16	m	3	5
0 10 090	Long period tide height	m	3	-32768	16	m	3	5
0 10 091	Tidal loading height	m	3	-32768	16	m	3	5
0 10 092	Solid Earth tide height	m	3	-32768	16	m	3	5

FM 94 BUFR, FM 95 CREX

Class 010								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 10 093	Geocentric pole tide height	m	3	-32768	16	m	3	5
0 10 095	Height of atmosphere used	m	0	0	16	m	0	5
0 10 096	Mean dynamic topography	m	3	-131072	18	m	3	6
0 10 097	Mean sea-surface height from altimeter only	m	3	-131072	18	m	3	6
0 10 098	Loading tide height geocentric ocean tide solution 1	m	4	-2000	12	m	4	4
0 10 099	Loading tide height geocentric ocean tide solution 2	m	4	-2000	12	m	4	4
0 10 100	Non-equilibrium long period tide height	m	4	-2000	12	m	4	4
0 10 101	Squared off-nadir angle of the satellite from waveform data	degree ²	2	-32768	16	degree ²	2	5
0 10 102	Sea-surface height anomaly	m	3	-32768	16	m	3	5
0 10 103	Mean dynamic topography accuracy	m	3	-131072	18	m	3	6

Notes:

- (1) Vertical elements and pressure shall be used to define values of these elements independent of the element or variable denoting the vertical coordinate.
- (2) The value for descriptor 0 10 031 has been chosen to be suitable for polar orbiting satellites in approximately Sun-synchronous orbits. Geostationary orbits would require greater data widths for distance and slightly less for speed.
- (3) Left handed x, y and z axes have been chosen for descriptor 0 10 031.
- (4) The "geoid undulation" is the difference between the reference ellipsoid (WGS-84) and the geoid height (EGM96) at the geographic location of the observation, both referenced to the centre of mass of the Earth.

Class 11 – BUFR/CREX Wind and turbulence

Class 11								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 11 001	Wind direction	degree true	0	0	9	degree true	0	3
0 11 002	Wind speed	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 003	u-component	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4
0 11 004	v-component	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4
0 11 005	w-component	Pa s ⁻¹	1	-512	10	Pa s ⁻¹	1	4
0 11 006	w-component	m s ⁻¹	2	-4096	13	m s ⁻¹	2	4
0 11 007	Relative wind direction (in degrees off bow)	°	0	0	9	°	0	3
0 11 008	Relative wind speed	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 010	Wind direction associated with wind speed which follows	degree true	0	0	9	degree true	0	3
0 11 011	Wind direction at 10 m	degree true	0	0	9	degree true	0	3
0 11 012	Wind speed at 10 m	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 013	Wind direction at 5 m	degree true	0	0	9	degree true	0	3
0 11 014	Wind speed at 5 m	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 016	Extreme counterclockwise wind direction of a variable wind	degree true	0	0	9	degree true	0	3
0 11 017	Extreme clockwise wind direction of a variable wind	degree true	0	0	9	degree true	0	3
0 11 019	Steadiness of wind (see Note 6)	%	0	0	7	%	0	3
0 11 021	Relative vorticity	s ⁻¹	9	-65536	17	s ⁻¹	9	6
0 11 022	Divergence	s ⁻¹	9	-65536	17	s ⁻¹	9	6
0 11 023	Velocity potential	m ² s ⁻¹	-2	-65536	17	m ² s ⁻¹	-2	6
0 11 030	Extended degree of turbulence	Code table	0	0	6	Code table	0	2
0 11 031	Degree of turbulence	Code table	0	0	4	Code table	0	2
0 11 032	Height of base of turbulence	m	-1	-40	16	m	-1	5
0 11 033	Height of top of turbulence	m	-1	-40	16	m	-1	5

FM 94 BUFR, FM 95 CREX

Class 11								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 11 034	Vertical gust velocity	m s ⁻¹	1	-1024	11	m s ⁻¹	1	4
0 11 035	Vertical gust acceleration	m s ⁻²	2	-8192	14	m s ⁻²	2	5
0 11 036	Maximum derived equivalent vertical gust speed	m s ⁻¹	1	0	10	m s ⁻¹	1	4
0 11 037	Turbulence index	Code table	0	0	6	Code table	0	2
0 11 038	Time of occurrence of peak eddy dissipation rate	Code table	0	0	5	Code table	0	2
0 11 039	Extended time of occurrence of peak eddy dissipation rate	Code table	0	0	6	Code table	0	2
0 11 040	Maximum wind speed (mean wind)	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 041	Maximum wind gust speed	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 042	Maximum wind speed (10-minute mean wind)	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 043	Maximum wind gust direction	degree true	0	0	9	degree true	0	3
0 11 044	Mean wind direction for surface – 1 500 m (5 000 feet)	degree true	0	0	9	degree true	0	3
0 11 045	Mean wind speed for surface – 1 500 m (5 000 feet)	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 046	Maximum instantaneous wind speed	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 047	Maximum instantaneous wind speed over 10 minutes	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 049	Standard deviation of wind direction	degree true	0	0	9	degree true	0	3
0 11 050	Standard deviation of horizontal wind speed	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 051	Standard deviation of vertical wind speed	m s ⁻¹	1	0	8	m s ⁻¹	1	3
0 11 052	Formal uncertainty in wind speed	m s ⁻¹	2	0	13	m s ⁻¹	2	5

FM 94 BUFR, FM 95 CREX

Class 11								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 11 053	Formal uncertainty in wind direction	degree true	2	0	15	degree true	2	5
0 11 054	Mean wind direction for 1 500 – 3 000 m	degree true	0	0	9	degree true	0	3
0 11 055	Mean wind speed for 1 500 – 3 000 m	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 061	Absolute wind shear in 1 km layer below	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 062	Absolute wind shear in 1 km layer above	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 070	Designator of the runway affected by wind shear (including ALL)	CCITT IA5	0	0	32	Character	0	4
0 11 071	Turbulent vertical momentum flux	m ² s ⁻²	3	-128	14	m ² s ⁻²	3	5
0 11 072	Turbulent vertical buoyancy flux	K m s ⁻¹	3	-128	11	K m s ⁻¹	3	4
0 11 073	Turbulent kinetic energy	m ² s ⁻²	2	-1024	13	m ² s ⁻²	2	4
0 11 074	Dissipation energy	m ² s ⁻²	2	-1024	10	m ² s ⁻²	2	4
0 11 075	Mean turbulence intensity (eddy dissipation rate)	m ^{2/3} s ⁻¹	2	0	8	m ^{2/3} s ⁻¹	2	3
0 11 076	Peak turbulence intensity (eddy dissipation rate)	m ^{2/3} s ⁻¹	2	0	8	m ^{2/3} s ⁻¹	2	3
0 11 077	Reporting interval or averaging time for eddy dissipation rate	s	0	0	12	s	0	4
0 11 081	Model wind direction at 10 m	degree true	2	0	16	degree true	2	5
0 11 082	Model wind speed at 10 m	m s ⁻¹	2	0	14	m s ⁻¹	2	4
0 11 083	Wind speed	km h ⁻¹	0	0	9	km h ⁻¹	0	3
0 11 084	Wind speed	kt	0	0	8	kt	0	3
0 11 085	Maximum wind gust speed	km h ⁻¹	0	0	9	km h ⁻¹	0	3
0 11 086	Maximum wind gust speed	kt	0	0	8	kt	0	3
0 11 095	u-component of the model wind vector	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4

FM 94 BUFR, FM 95 CREX

Class 11								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 11 096	v-component of the model wind vector	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4
0 11 097	Wind speed from altimeter	m s ⁻¹	2	0	12	m s ⁻¹	2	4
0 11 098	Wind speed from radiometer	m s ⁻¹	2	0	12	m s ⁻¹	2	4
0 11 100	Aircraft true airspeed	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 11 101	Aircraft ground speed u-component	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4
0 11 102	Aircraft ground speed v-component	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4
0 11 103	Aircraft ground speed w-component	m s ⁻¹	1	-512	10	m s ⁻¹	1	3
0 11 104	True heading of aircraft, ship or other mobile platform	degree true	0	0	9	degree true	0	3
0 11 105	EDR algorithm version	Numeric	0	0	6	Numeric	0	2
0 11 106	Running minimum confidence	Numeric	1	0	4	Numeric	1	2
0 11 107	Maximum number bad inputs	Numeric	0	0	5	Numeric	0	2
0 11 108	Peak location	Numeric	1	0	4	Numeric	1	2
0 11 109	Number of good EDR	Numeric	0	0	4	Numeric	0	2
0 11 110	Uncertainty in u-component	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4
0 11 111	Uncertainty in v-component	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4
0 11 112	Uncertainty in w-component	m s ⁻¹	2	-4096	13	m s ⁻¹	2	4
0 11 113	Tracking correlation of vector	Numeric	3	-1000	12	Numeric	3	4

Notes:

- (1) West to east u-components shall be assigned positive values.
- (2) South to north v-components shall be assigned positive values.
- (3) Upward w-components shall be assigned positive values where units are m s⁻¹.
- (4) Downward w-components shall be assigned positive values where units are Pa s⁻¹.

(5) Wind reporting standards:

	<i>Speed</i>	<i>Direction</i>
No observation	Missing	Missing
Calm	0	0
Normal observation	> 0	1°–360°
Speed only	> 0	Missing
Direction only	Missing	1°–360°
"Light and variable"	> 0	0

- (6) The steadiness factor (descriptor 0 11 019) is the ratio of speed of the monthly mean vector wind to the speed of the monthly mean scalar wind expressed as a percentage. It is reported to the nearest one per cent.
- (7) Surface wind direction measured at a station within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian.

Class 12 – BUFR/CREX Temperature

Class 12								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 12 001	Temperature/air temperature	K	1	0	12	°C	1	3
0 12 002	Wet-bulb temperature	K	1	0	12	°C	1	3
0 12 003	Dewpoint temperature	K	1	0	12	°C	1	3
0 12 004	Air temperature at 2 m	K	1	0	12	°C	1	3
0 12 005	Wet-bulb temperature at 2 m	K	1	0	12	°C	1	3
0 12 006	Dewpoint temperature at 2 m	K	1	0	12	°C	1	3
0 12 007	Virtual temperature	K	1	0	12	°C	1	3
0 12 008	Uncertainty in virtual temperature	K	1	0	12	°C	1	4
0 12 011	Maximum temperature, at height and over period specified	K	1	0	12	°C	1	3
0 12 012	Minimum temperature, at height and over period specified	K	1	0	12	°C	1	3
0 12 013	Ground minimum temperature, past 12 hours	K	1	0	12	°C	1	3
0 12 014	Maximum temperature at 2 m, past 12 hours	K	1	0	12	°C	1	3
0 12 015	Minimum temperature at 2 m, past 12 hours	K	1	0	12	°C	1	3
0 12 016	Maximum temperature at 2 m, past 24 hours	K	1	0	12	°C	1	3
0 12 017	Minimum temperature at 2 m, past 24 hours	K	1	0	12	°C	1	3
0 12 021	Maximum temperature at 2 m	K	2	0	16	°C	2	4
0 12 022	Minimum temperature at 2 m	K	2	0	16	°C	2	4
0 12 023	Temperature	°C	0	–99	8	°C	0	2
0 12 024	Dewpoint temperature	°C	0	–99	8	°C	0	2
0 12 030	Soil temperature	K	1	0	12	°C	1	3

FM 94 BUFR, FM 95 CREX

Class 12								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 12 049	Temperature change over specified period	K	0	-30	6	°C	0	2
0 12 051	Standard deviation temperature	K	1	0	10	°C	1	3
0 12 052	Highest daily mean temperature	K	1	0	12	°C	1	3
0 12 053	Lowest daily mean temperature	K	1	0	12	°C	1	3
0 12 060	AWS enclosure internal temperature	K	1	0	12	°C	1	3
0 12 061	Skin temperature	K	1	0	12	°C	1	3
0 12 062	Equivalent black body temperature	K	1	0	12	°C	1	3
0 12 063	Brightness temperature	K	1	0	12	°C	1	3
0 12 064	Instrument temperature	K	1	0	12	K	1	4
0 12 065	Standard deviation brightness temperature	K	1	0	12	K	1	4
0 12 066	Antenna temperature	K	2	0	16	°C	2	5
0 12 070	Warm load temperature	K	2	0	16	K	2	5
0 12 071	Coldest cluster temperature	K	1	0	12	K	1	4
0 12 072	Radiance	W m ⁻² sr ⁻¹	6	0	31	W m ⁻² sr ⁻¹	6	9
0 12 075	Spectral radiance	W m ⁻³ sr ⁻¹	-3	0	16	W m ⁻³ sr ⁻¹	-3	5
0 12 076	Radiance (see Note 2)	W m ⁻² sr ⁻¹	3	0	16	W m ⁻² sr ⁻¹	3	5
0 12 080	Brightness temperature real part	K	2	-10000	16	K	2	5
0 12 081	Brightness temperature imaginary part	K	2	-10000	16	K	2	5
0 12 082	Pixel radiometric accuracy	K	2	0	12	K	2	4
0 12 101	Temperature/air temperature	K	2	0	16	°C	2	4
0 12 102	Wet-bulb temperature	K	2	0	16	°C	2	4
0 12 103	Dewpoint temperature	K	2	0	16	°C	2	4
0 12 104	Air temperature at 2 m	K	2	0	16	°C	2	4
0 12 105	Web-bulb temperature at 2 m	K	2	0	16	°C	2	4
0 12 106	Dewpoint temperature at 2 m	K	2	0	16	°C	2	4

FM 94 BUFR, FM 95 CREX

Class 12								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 12 107	Virtual temperature	K	2	0	16	°C	2	4
0 12 111	Maximum temperature, at height and over period specified (see Note 1)	K	2	0	16	°C	2	4
0 12 112	Minimum temperature, at height and over period specified (see Note 1)	K	2	0	16	°C	2	4
0 12 113	Ground minimum temperature, past 12 hours	K	2	0	16	°C	2	4
0 12 114	Maximum temperature at 2 m, past 12 hours	K	2	0	16	°C	2	4
0 12 115	Minimum temperature at 2 m, past 12 hours	K	2	0	16	°C	2	4
0 12 116	Maximum temperature at 2 m, past 24 hours	K	2	0	16	°C	2	4
0 12 117	Minimum temperature at 2 m, past 24 hours	K	2	0	16	°C	2	4
0 12 118	Maximum temperature at height specified, past 24 hours	K	2	0	16	°C	2	4
0 12 119	Minimum temperature at height specified, past 24 hours	K	2	0	16	°C	2	4
0 12 120	Ground temperature	K	2	0	16	°C	2	4
0 12 121	Ground minimum temperature	K	2	0	16	°C	2	4
0 12 122	Ground minimum temperature of the preceding night	K	2	0	16	°C	2	4
0 12 128	Road surface temperature	K	2	0	16	°C	2	5
0 12 129	Road subsurface temperature	K	2	0	16	°C	2	5
0 12 130	Soil temperature	K	2	0	16	°C	2	4
0 12 131	Snow temperature	K	2	0	16	°C	2	4
0 12 132	Ice surface temperature	K	2	0	16	°C	2	4

FM 94 BUFR, FM 95 CREX

Class 12								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 12 151	Standard deviation of daily mean temperature	K	2	0	12	°C	2	4
0 12 152	Highest daily mean temperature	K	2	0	16	°C	2	4
0 12 153	Lowest daily mean temperature	K	2	0	16	°C	2	4
0 12 158	Noise-equivalent delta temperature while viewing cold target	K	2	0	12	°C	2	4
0 12 159	Noise-equivalent delta temperature while viewing warm target	K	2	0	12	°C	2	4
0 12 161	Skin temperature	K	2	0	16	°C	2	4
0 12 162	Equivalent black body temperature	K	2	0	16	°C	2	4
0 12 163	Brightness temperature	K	2	0	16	°C	2	4
0 12 164	Instrument temperature	K	2	0	16	K	2	5
0 12 165	Direct sun brightness temperature	K	0	0	23	K	0	7
0 12 166	Snapshot accuracy	K	1	-4000	13	K	1	4
0 12 167	Radiometric accuracy (pure polarization)	K	1	0	9	K	1	3
0 12 168	Radiometric accuracy (cross polarization)	K	1	0	9	K	1	3
0 12 171	Coldest cluster temperature	K	2	0	16	K	2	5
0 12 180	Averaged 12 micron BT for all clear pixels at nadir	K	2	0	16	K	2	5
0 12 181	Averaged 11 micron BT for all clear pixels at nadir	K	2	0	16	K	2	5
0 12 182	Averaged 3.7 micron BT for all clear pixels at nadir	K	2	0	16	K	2	5
0 12 183	Averaged 12 micron BT for all clear pixels, forward view	K	2	0	16	K	2	5
0 12 184	Averaged 11 micron BT for all clear pixels, forward view	K	2	0	16	K	2	5

FM 94 BUFR, FM 95 CREX

Class 12								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 12 185	Averaged 3.7 micron BT for all clear pixels, forward view	K	2	0	16	K	2	5
0 12 186	Mean nadir sea-surface temperature	K	2	0	16	K	2	5
0 12 187	Mean dual view sea-surface temperature	K	2	0	16	K	2	5
0 12 188	Interpolated 23.8 GHz brightness T from MWR	K	2	0	16	K	2	5
0 12 189	Interpolated 36.5 GHz brightness T from MWR	K	2	0	16	K	2	5

Notes:

- (1) Where the expression "at height and over period specified" is entered under element name, an appropriate vertical location shall be specified using descriptors from Class 07, together with an appropriate period using descriptors from Class 04.
- (2) Descriptor 0 12 076 should be used instead of descriptor 0 12 072 to encode radiance.

Class 13 – BUFR/CREX Hydrographic and hydrological elements

Class 13								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 13 001	Specific humidity	kg kg ⁻¹	5	0	14	kg kg ⁻¹	5	5
0 13 002	Mixing ratio	kg kg ⁻¹	5	0	14	kg kg ⁻¹	5	5
0 13 003	Relative humidity	%	0	0	7	%	0	3
0 13 004	Vapour pressure	Pa	-1	0	10	Pa	-1	4
0 13 005	Vapour density	kg m ⁻³	3	0	7	kg m ⁻³	3	3
0 13 006	Mixing heights	m	-1	-40	16	m	-1	5
0 13 007	Minimum relative humidity	%	0	0	7	%	0	3
0 13 008	Maximum relative humidity	%	0	0	7	%	0	3
0 13 009	Relative humidity (see Note 6)	%	1	-1000	12	%	1	4
0 13 011	Total precipitation/total water equivalent	kg m ⁻²	1	-1	14	kg m ⁻²	1	5
0 13 012	Depth of fresh snow (see Note 2)	m	2	-2	12	m	2	4
0 13 013	Total snow depth (see Note 2)	m	2	-2	16	m	2	5
0 13 014	Rainfall/water equivalent of snow (averaged rate)	kg m ⁻² s ⁻¹	4	0	12	kg m ⁻² s ⁻¹	4	4
0 13 015	Snowfall (averaged rate)	m s ⁻¹	7	0	12	m s ⁻¹	7	4
0 13 016	Precipitable water	kg m ⁻²	0	0	7	kg m ⁻²	0	3
0 13 019	Total precipitation past 1 hour	kg m ⁻²	1	-1	14	kg m ⁻²	1	4
0 13 020	Total precipitation past 3 hours	kg m ⁻²	1	-1	14	kg m ⁻²	1	5
0 13 021	Total precipitation past 6 hours	kg m ⁻²	1	-1	14	kg m ⁻²	1	5
0 13 022	Total precipitation past 12 hours	kg m ⁻²	1	-1	14	kg m ⁻²	1	5
0 13 023	Total precipitation past 24 hours	kg m ⁻²	1	-1	14	kg m ⁻²	1	5
0 13 031	Evapotranspiration	kg m ⁻²	0	0	7	kg m ⁻²	0	3
0 13 032	Evaporation/evapotranspiration (see Note 5)	kg m ⁻²	1	0	8	kg m ⁻²	1	3
0 13 033	Evaporation/evapotranspiration	kg m ⁻²	1	0	10	kg m ⁻²	1	4
0 13 038	Superadiabatic indicator	Code table	0	0	2	Code table	0	1

FM 94 BUFR, FM 95 CREX

Class 13								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 13 039	Terrain type (ice/snow)	Code table	0	0	3	Code table	0	1
0 13 040	Surface flag	Code table	0	0	4	Code table	0	2
0 13 041	Pasquill-Gifford stability category	Code table	0	0	4	Code table	0	2
0 13 042	Parcel lifted index (to 500 hPa) (see Notes 3 and 4)	K	0	-20	6	K	0	2
0 13 043	Best lifted index (to 500 hPa) (see Notes 3 and 4)	K	0	-20	6	K	0	2
0 13 044	K index	K	0	-30	8	K	0	3
0 13 045	KO index	K	0	-30	8	K	0	3
0 13 046	Maximum buoyancy	K	0	-30	8	K	0	3
0 13 047	Modified Showalter stability index (see Note 7)	K	0	-60	6	°C	0	2
0 13 048	Water fraction	%	1	0	10	%	1	4
0 13 051	Frequency group, precipitation	Code table	0	0	4	Code table	0	2
0 13 052	Highest daily amount of precipitation	kg m ⁻²	1	-1	14	kg m ⁻²	1	5
0 13 055	Intensity of precipitation	kg m ⁻² s ⁻¹	4	0	8	mm h ⁻¹	1	4
0 13 056	Character and intensity of precipitation	Code table	0	0	4	Code table	0	2
0 13 057	Time of beginning or end of precipitation	Code table	0	0	4	Code table	0	2
0 13 058	Size of precipitating element	m	4	0	7	mm	1	3
0 13 059	Number of flashes (thunderstorm)	Numeric	0	0	7	Numeric	0	3
0 13 060	Total accumulated precipitation	kg m ⁻²	1	-1	17	kg m ⁻²	1	5
0 13 071	Upstream water level	m	2	0	14	m	2	4
0 13 072	Downstream water level	m	2	0	14	m	2	4
0 13 073	Maximum water level	m	2	0	14	m	2	4
0 13 074	Ground water level	m	2	0	18	m	2	6
0 13 080	Water pH	pH unit	1	0	10	pH unit	1	3

FM 94 BUFR, FM 95 CREX

Class 13								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 13 081	Water conductivity	S m ⁻¹	3	0	14	S m ⁻¹	3	4
0 13 082	Water temperature	K	1	0	12	K	1	4
0 13 083	Dissolved oxygen	kg m ⁻³	6	0	15	kg m ⁻³	6	5
0 13 084	Turbidity	lm	0	0	14	lm	0	4
0 13 085	Oxidation Reduction Potential (ORP)	V	3	0	14	V	3	4
0 13 090	Radiometer water vapour content	kg m ⁻²	1	0	10	kg m ⁻²	1	4
0 13 091	Radiometer liquid content	kg m ⁻²	2	0	8	kg m ⁻²	2	3
0 13 093	Cloud optical thickness	Numeric	0	0	8	Numeric	0	3
0 13 095	Total column water vapour	kg m ⁻²	4	0	19	kg m ⁻²	4	6
0 13 096	MWR water vapour content	kg m ⁻²	2	0	14	kg m ⁻²	2	5
0 13 097	MWR liquid water content	kg m ⁻²	2	0	14	kg m ⁻²	2	5
0 13 098	Integrated water vapour density	kg m ⁻²	8	0	30	kg m ⁻²	8	10
0 13 099	Log ₁₀ of integrated cloud particle density	log(m ⁻²)	1	0	7	log(m ⁻²)	1	3
0 13 100	Log ₁₀ of integrated cloud particle area	log(m ² m ⁻²)	1	-70	7	log(m ² m ⁻²)	1	2
0 13 101	Log ₁₀ of integrated cloud particle volume	log(m ³ m ⁻²)	1	-140	7	log(m ³ m ⁻²)	1	3
0 13 109	Ice/liquid water path	kg m ⁻²	3	0	10	kg m ⁻²	3	4
0 13 110	Mass mixing ratio	%	0	0	7	%	0	3
0 13 111	Soil moisture	g kg ⁻¹	0	0	10	g kg ⁻¹	0	4
0 13 112	Object wetness duration	s	0	0	17	s	0	5
0 13 114	Rate of ice accretion	kg m ⁻² h ⁻¹	1	0	11	kg m ⁻² h ⁻¹	1	4
0 13 115	Ice thickness (see Note 9)	m	2	0	19	m	2	6
0 13 116	Water film thickness	m	4	0	10	m	3	2
0 13 117	Snow density (liquid water content)	kg m ⁻³	0	0	10	kg m ⁻³	0	3

FM 94 BUFR, FM 95 CREX

Class 13								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 13 118	Depth of fresh snow (high accuracy) (see Note 10)	m	3	-2	14	m	3	5
0 13 155	Intensity of precipitation (high accuracy) (see Note 8)	kg m ⁻² s ⁻¹	5	-1	16	mm h ⁻¹	2	5
0 13 160	Radiometer liquid content	kg m ⁻²	2	-350	10	kg m ⁻²	2	3
0 13 162	Cloud liquid water	kg m ⁻²	2	0	8	kg m ⁻²	2	3
0 13 163	Snow water equivalent	kg m ⁻²	0	0	16	kg m ⁻²	0	5
0 13 164	Sea-ice freeboard	m	3	-131072	18	m	3	6

Notes:

- (1) A precipitation value of -0.1 kg m⁻² before scaling (-1 after scaling or in CREX) shall indicate a "trace" (non-measurable, less than 0.05 kg m⁻²).
- (2) A snow depth value of -0.01 m before scaling (-1 after scaling or in CREX) shall indicate a little (less than 0.005 m) snow. A value of -0.02 m (-2 after scaling or in CREX) shall indicate "snow cover not continuous".
- (3) The "parcel lifted index" (as defined in the *International Meteorological Vocabulary* (WMO-No. 182) under the listing "lifted index") is defined as the temperature difference between the ambient 500-hPa temperature (T500) and that of a parcel of air lifted from the surface (Tparcel) following the dry and moist adiabatic process. Negative values of (T500 - Tparcel) suggest instability. The "best lifted index" is defined as the most unstable of a collection of parcel lifted indices, with parcel initial conditions defined for a collection of 30-hPa thick layers stacked one upon the other with the lowest resting on the ground. Commonly four to six such layers are used in the calculation.
- (4) Since the two lifted indices (0 13 042 and 0 13 043) are defined as temperature differences, they may take on negative values, even though the units are kelvin; hence the non-zero reference value.
- (5) Descriptor 0 13 033 should be used instead of descriptor 0 13 032 to encode evaporation/evapotranspiration.
- (6) Concerning descriptor 0 13 009, the originators of these data want to be able to retain the raw (i.e. unprocessed) relative humidity value reported by the sensor in order to be able to track, among other things, when a sensor begins to malfunction. The latter case is when a negative value might occur. For worldwide exchange with other countries, it is possible that only the processed data would ever be sent.
- (7) The "Modified Showalter stability index" is defined as the temperature difference between the ambient 500-hPa temperature and the temperature a parcel of air, initially at a selected base level, would have if brought from its condensation level to the 500-hPa surface by a moist adiabatic process. Positive values denote stable conditions, while negative values denote unstable conditions. The base level is 850 hPa, 800 hPa or 750 hPa if the station elevation is less than 1000, 1000 to 1400 or 1401 to 2000 gpm above mean sea level, respectively.

FM 94 BUFR, FM 95 CREX

- (8) An intensity of precipitation value of $-0.00001 \text{ kg m}^{-2} \text{ s}^{-1}$ before scaling (-1 after scaling) and of -0.01 mm h^{-1} before scaling (-1 after scaling) shall indicate a "trace" in BUFR and in CREX, respectively.
- (9) Ice thickness (0 13 115) shall be preceded by Surface type (0 08 029) set to 11, 12, 13 or 14 to specify river, lake, sea or glacier, respectively.
- (10) Depth of fresh snow (0 13 118) set to -0.001 before scaling (-1 after scaling or in CREX) shall indicate a little snow (less than 0.0005 m). Depth of fresh snow (0 13 118) set to -0.002 before scaling (-2 after scaling or in CREX) shall indicate "snow cover not continuous".

Provisional Copy
2023

Class 14 – BUFR/CREX Radiation and radiance

Class 14								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 14 001	Long-wave radiation, integrated over 24 hours	J m ⁻²	-3	-65536	17	J m ⁻²	-3	5
0 14 002	Long-wave radiation, integrated over period specified	J m ⁻²	-3	-65536	17	J m ⁻²	-3	5
0 14 003	Short-wave radiation, integrated over 24 hours	J m ⁻²	-3	-65536	17	J m ⁻²	-3	5
0 14 004	Short-wave radiation, integrated over period specified	J m ⁻²	-3	-65536	17	J m ⁻²	-3	5
0 14 011	Net long-wave radiation, integrated over 24 hours	J m ⁻²	-3	-65536	17	J m ⁻²	-3	5
0 14 012	Net long-wave radiation, integrated over period specified	J m ⁻²	-3	-65536	17	J m ⁻²	-3	5
0 14 013	Net short-wave radiation, integrated over 24 hours	J m ⁻²	-3	-65536	17	J m ⁻²	-3	5
0 14 014	Net short-wave radiation, integrated over period specified	J m ⁻²	-3	-65536	17	J m ⁻²	-3	5
0 14 015	Net radiation, integrated over 24 hours	J m ⁻²	-4	-16384	15	J m ⁻²	-4	5
0 14 016	Net radiation, integrated over period specified	J m ⁻²	-4	-16384	15	J m ⁻²	-4	5
0 14 017	Instantaneous long-wave radiation	W m ⁻²	0	-512	10	W m ⁻²	0	4
0 14 018	Instantaneous short-wave radiation	W m ⁻²	0	-2048	12	W m ⁻²	0	4
0 14 019	Surface albedo	%	0	0	7	%	0	3
0 14 020	Global solar radiation, integrated over 24 hours	J m ⁻²	-4	0	15	J m ⁻²	-4	5
0 14 021	Global solar radiation, integrated over period specified	J m ⁻²	-4	0	15	J m ⁻²	-4	5

FM 94 BUFR, FM 95 CREX

Class 14								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 14 022	Diffuse solar radiation, integrated over 24 hours	J m ⁻²	-4	0	15	J m ⁻²	-4	5
0 14 023	Diffuse solar radiation, integrated over period specified	J m ⁻²	-4	0	15	J m ⁻²	-4	5
0 14 024	Direct solar radiation, integrated over 24 hours	J m ⁻²	-4	0	15	J m ⁻²	-4	5
0 14 025	Direct solar radiation, integrated over period specified	J m ⁻²	-4	0	15	J m ⁻²	-4	5
0 14 026	Albedo at the top of clouds	%	0	0	7	%	0	3
0 14 027	Albedo	%	0	0	7	%	0	3
0 14 028	Global solar radiation (high accuracy), integrated over period specified	J m ⁻²	-2	0	20	J m ⁻²	-2	6
0 14 029	Diffuse solar radiation (high accuracy), integrated over period specified	J m ⁻²	-2	0	20	J m ⁻²	-2	6
0 14 030	Direct solar radiation (high accuracy), integrated over period specified	J m ⁻²	-2	0	20	J m ⁻²	-2	6
0 14 031	Total sunshine	min	0	0	11	min	0	4
0 14 032	Total sunshine	h	0	0	10	h	0	4
0 14 033	Total sunshine	%	0	0	9	%	0	3
0 14 034	Sunshine over period specified	min	0	0	11	min	0	4
0 14 035	Solar radiation flux	W m ⁻²	1	0	14	W m ⁻²	1	5
0 14 042	Bidirectional reflectance	%	0	0	7	%	0	3
0 14 043	Channel radiance (see Note 7)	W m ⁻² sr ⁻¹ μm ⁻¹	4	0	23	W m ⁻² sr ⁻¹ μm ⁻¹	4	7
0 14 044	Channel radiance	W m ⁻² sr ⁻¹ cm	7	-100000	22	W m ⁻² sr ⁻¹ cm	7	7
0 14 045	Channel radiance (see Note 4)	W m ⁻² sr ⁻¹ cm	0	0	11	W m ⁻² sr ⁻¹ cm	0	4
0 14 046	Scaled radiance (see Note 6)	W m ⁻² sr ⁻¹ m	0	-5000	16	W m ⁻² sr ⁻¹ m	0	5
0 14 047	Scaled mean AVHRR radiance	W m ⁻² sr ⁻¹ m	0	0	31	W m ⁻² sr ⁻¹ m	0	10

FM 94 BUFR, FM 95 CREX

Class 14								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 14 048	Scaled standard deviation AVHRR radiance	W m ⁻² sr ⁻¹ m	0	0	31	W m ⁻² sr ⁻¹ m	0	10
0 14 049	Noise equivalent delta radiance	W m ⁻² sr ⁻¹ cm	7	0	22	W m ⁻² sr ⁻¹ cm	0	0
0 14 050	Emissivity (see Note 5)	%	1	0	10	%	1	4
0 14 051	Direct solar radiation integrated over last hour	J m ⁻²	-3	0	14	J m ⁻²	-3	4
0 14 052	Global upward solar radiation, integrated over period specified	J m ⁻²	-2	-1048574	20	J m ⁻²	-2	7
0 14 053	Net radiation (high accuracy), integrated over period specified	J m ⁻²	-2	-1048574	21	J m ⁻²	-2	7
0 14 054	Photosynthetically active radiation, integrated over period specified	J m ⁻²	-3	0	16	J m ⁻²	-3	5
0 14 055	Solar activity index	Numeric	0	-32768	16	Numeric	0	5
0 14 056	Background luminance	Cd m ⁻²	0	0	18	Cd m ⁻²	0	6
0 14 057	Soil heat flux	J m ⁻²	-2	-1048574	21	J m ⁻²	-2	7
<u>0 14 058</u>	<u>Corrected cross-pole backscatter</u>	<u>dB</u>	<u>2</u>	<u>-5000</u>	<u>13</u>	<u>dB</u>	<u>2</u>	<u>5</u>
0 14 072	Global UV irradiation (see Note 8)	J m ⁻²	0	-4000000	23	J m ⁻²	0	7

Notes:

- (1) Downward radiation shall be assigned positive values.
- (2) Upward radiation shall be assigned negative values.
- (3) Where the expression "period specified" is entered under element name, an appropriate period shall be specified using descriptors from Class 04.
- (4) Channel radiance (0 14 045) uses cm to represent the wave number.
- (5) Emissivity is the ratio of the amount of energy emitted from a particular object compared to the amount that would be emitted by a blackbody at the same temperature (i.e. the Planck function). Multiplying by 100 gives a per cent (and provides 2 digits of precision at the same time).
- (6) An offset has been introduced for the scaled radiances (0 14 046). This is to accommodate the negative radiances which can be measured at some wave numbers, either due to effects of noise or remaining after apodization. The offset is an order of magnitude larger than the expected maximum negative excursion based on instrument noise, and so would leave sufficient margin. At the same time the dynamic range is not significantly degraded.

- (7) Channel radiance (0 14 043) uses μm to represent the wave number.
 - (8) Global UV irradiation (0 14 072) is UV energy integrated over period specified for spectral band specified. 0 14 072 shall be preceded by a time period descriptor and by Spectrographic wavelength (0 02 071) and Spectrographic width (0 02 072). For example, if 0 14 072 is used for global UV-B irradiation, 0 02 071 and 0 02 072 shall specify spectral band 280 to 315 nm.
-

Provisional Copy
2023

Class 15 – BUFR/CREX Physical/chemical constituents

Class 15								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 15 001	Total ozone	DU	0	0	10	DU	0	4
0 15 002	Air mass (slant path at 22 km)	Numeric	2	0	10	Numeric	2	3
0 15 003	Measured ozone partial pressure (sounding) (see Note 1)	Pa	4	0	9	nbar	0	3
0 15 004	Ozone sounding correction factor (CF) (see Note 2)	Numeric	3	0	11	Numeric	3	4
0 15 005	Ozone p (see Note 3)	DU	0	0	10	DU	0	3
0 15 006	Log ₁₀ of number density of atmosphere	log (m ⁻³)	5	1800000	20	log (m ⁻³)	5	7
0 15 008	Significand of volumetric mixing ratio	Numeric	0	0	10	Numeric	0	4
0 15 009	Log ₁₀ of number density of ozone	log (m ⁻³)	5	1200000	20	log (m ⁻³)	5	7
0 15 011	Log ₁₀ of integrated electron density	log (m ⁻²)	3	14000	13	log (m ⁻²)	3	4
0 15 012	Total electron count per square metre	m ⁻²	-16	0	6	m ⁻²	-16	2
0 15 015	Maximum image spectral component before normalization	Numeric	0	0	31	Numeric	0	10
0 15 020	Integrated ozone density	kg m ⁻²	8	0	21	kg m ⁻²	8	7
0 15 021	Integrated mass density	kg m ⁻²	11	0	31	kg m ⁻²	11	10
0 15 022	Extended integrated mass density	kg m ⁻²	1	-100000000	31	kg m ⁻²	1	10
0 15 024	Optical depth	Numeric	4	0	24	Numeric	4	8
0 15 025	Type of pollutant	Code table	0	0	4	Code table	0	2
0 15 026	Concentration of pollutant (mol mol ⁻¹)	mol mol ⁻¹	9	0	9	mol mol ⁻¹	9	3
0 15 027	Concentration of pollutant (kg m ⁻³)	kg m ⁻³	9	0	10	kg m ⁻³	9	4

FM 94 BUFR, FM 95 CREX

Class 15								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 15 028	Mole fraction of atmospheric constituent/pollutant in dry air	‰	5	0	16	‰	5	5
0 15 029	Extinction coefficient	m ⁻¹	9	0	30	m ⁻¹	9	10
0 15 030	Aerosol contamination index (see Note 6)	Numeric	2	-1000	12	Numeric	2	4
0 15 031	Atmospheric path delay in satellite signal	m	4	10000	15	m	4	5
0 15 032	Estimated error in atmospheric path delay	m	4	0	10	m	4	4
0 15 033	Difference in path delays for limb views at extremes of scan	m	5	-10000	15	m	5	5
0 15 034	Estimated error in path delay difference	m	5	0	14	m	5	5
0 15 035	Component of zenith path delay due to water vapour	m	4	0	14	m	4	5
0 15 036	Atmospheric refractivity (see Note 5)	N units	3	0	19	N units	3	6
0 15 037	Bending angle	rad	8	-100000	23	rad	8	7
0 15 038	Path delay due to neutral atmosphere (see Note 10)	m	4	0	20	m		
0 15 039	Estimated error in neutral atmosphere path delay	m	4	0	14	m		
0 15 041	Sulphur dioxide index (see Note 7)	Numeric	2	-1200	14	Numeric	2	4
0 15 042	Reflectance	%	2	0	14	%	2	5
0 15 045	Sulphur dioxide (see Note 8)	DU	2	-2000	15	DU	2	5
0 15 046	Volcano contamination index (see Note 9)	Numeric	2	-1000	11	Numeric	2	4
0 15 049	Aerosol Angstrom wavelength exponent	Numeric	3	-2000	14	Numeric	3	5
0 15 051	Meteorological optical range	m	0	0	18	m	0	6

FM 94 BUFR, FM 95 CREX

Class 15								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 15 052	Log ₁₀ of number density of aerosol particles with diameter greater than 5 nm	log(m ⁻³)	1	60	6	log(m ⁻³)	1	3
0 15 053	Log ₁₀ of number density of aerosol particles with diameter greater than 14 nm	log(m ⁻³)	2	600	9	log(m ⁻³)	2	4
0 15 054	Log ₁₀ of number density of aerosol particles with diameter between 0.25 and 2.5 µm	log(m ⁻³)	2	550	9	log(m ⁻³)	2	4
0 15 055	Non-volatile aerosol ratio	Numeric	2	0	7	Numeric	2	3
0 15 062	Aerosol optical thickness	Numeric	3	-1000	14	Numeric	3	5
0 15 063	Attenuated backscatter	m ⁻¹ sr ⁻¹	8	0	20	m ⁻¹ sr ⁻¹	8	7
0 15 064	Uncertainty in attenuated backscatter	m ⁻¹ sr ⁻¹	8	0	20	m ⁻¹ sr ⁻¹	8	7
0 15 065	Particle backscatter coefficient	m ⁻¹ sr ⁻¹	8	0	20	m ⁻¹ sr ⁻¹	8	7
0 15 066	Uncertainty in particle backscatter coefficient	m ⁻¹ sr ⁻¹	8	0	20	m ⁻¹ sr ⁻¹	8	7
0 15 067	Particle extinction coefficient	m ⁻¹	8	0	20	m ⁻¹	8	7
0 15 068	Uncertainty in particle extinction coefficient	m ⁻¹	8	0	20	m ⁻¹	8	7
0 15 069	Particle lidar ratio	sr	2	0	14	sr	2	5
0 15 070	Uncertainty in lidar ratio	sr	2	0	14	sr	2	5
0 15 071	Particle depolarization ratio	%	2	0	14	%	2	5
0 15 072	Uncertainty in depolarization ratio	%	2	0	14	%	2	5
0 15 073	Attenuated backscatter	m ⁻¹ sr ⁻¹	8	-524288	20	m ⁻¹ sr ⁻¹	8	7
0 15 074	Particle backscatter coefficient	m ⁻¹ sr ⁻¹	8	-524288	20	m ⁻¹ sr ⁻¹	8	7
0 15 075	Particle extinction coefficient	m ⁻¹	8	-524288	20	m ⁻¹	8	7
0 15 076	Particle lidar Ratio	sr	1	-2048	13	sr	1	5
0 15 077	Uncertainty in lidar Ratio	sr	1	0	12	sr	1	5
0 15 078	Particle depolarization ratio	%	2	-8192	15	%	2	5

FM 94 BUFR, FM 95 CREX

Class 15								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 15 079	Zenith path delay due to neutral atmosphere (see Note 11)	m	4	0	15	m	4	9
0 15 080	Estimated error in neutral atmosphere zenith path delay	m	4	0	12	m	4	8
0 15 081	Wet path delay due to neutral atmosphere (see Note 12)	m	4	0	18	m	4	10
0 15 082	Path integrated water vapour (see Note 16)	kg m ⁻²	1	0	16	kg m ⁻²	1	10
0 15 083	GNSS-derived neutral atmosphere gradient (see Note 17)	m	5	-8192	14	m	5	9
0 15 084	GNSS least squares residual (see Note 18)	m	4	0	14	m	4	9
0 15 085	GNSS multi-path delay (see Note 15)	m	4	0	14	m	4	9
0 15 086	GNSS hydrostatic mapping function (see Note 19)	Numeric	3	0	16	Numeric	3	10
0 15 087	GNSS wet mapping function (see Note 19)	Numeric	3	0	16	Numeric	3	10
0 15 088	GNSS gradient mapping function (see Note 19)	Numeric	3	0	16	Numeric	3	10
0 15 089	Zenith path delay due to neutral hydrostatic atmosphere (see Note 13)	m	4	0	15	m	4	9
0 15 090	Path delay due to neutral hydrostatic atmosphere (see Note 14)	m	4	0	20	m	4	11

Notes:

- (1) 0 15 003 is the partial pressure of ozone, measured at the pressure level identified by 0 07 004.
- (2) 0 15 004 (CF) is defined as:
 $CF = TOI/TOS$ where TOI is the integrated ozone value obtained "simultaneously to a sounding" from a Dobson or Brewer spectrophotometer at the site or "nearby" and TOS is the total ozone obtained from the sounding. TOS is the sum of the integrated ozone below the lowest pressure level reached by the sounding and the estimate of the amount above. In the absence of any spectrophotometer measurement, CF = Missing value.
- (3) 0 15 005 is the value obtained as the result of the vertical integration of the sounding values (0 15 003) measured below the lowest pressure level reached by the sonde, multiplied by 0 15 004.
- (4) DU = Dobson unit.
- (5) The refractivity, N , is related to the refractive index, n , by the formula $N = 10^6 (n - 1)$. N is therefore dimensionless but values computed by the formula are by convention described as being in "N units".
- (6) For this descriptor, numbers less than -1 indicate a predominance of scattering aerosols, increasing in concentration as the number becomes more negative. Numbers greater than $+1$ indicate a predominance of absorptive aerosols, increasing in concentration as the number becomes more positive. Numbers between -1 and $+1$ indicate clouds or noise.
- (7) For this descriptor, numbers greater than $+6$ indicate sulphur dioxide contamination, increasing in intensity as the number becomes more positive. The number is computed from a measurement in Dobson Units, but for a specific temperature and assumed concentration profile that may not be close to the true state of the atmosphere. Because of these deficiencies, it is reported as a numeric index.
- (8) For this descriptor, negative values indicate noise, poor calibration or presence of absorbing aerosols. Preserving these values allows for better subsequent estimates of calibration bias.
- (9) For this descriptor, the units represent the climatological standard deviation of the tropospheric ozone value for a given latitude. For example, a value of 5.0 indicates a profile with a tropospheric ozone value 5.0 standard deviations larger than the climatological average.
- (10) 0 15 038 is the delay of an electromagnetic wave in the neutral atmosphere as compared to undisturbed propagation in a vacuum. The delay due to ionized gases in the ionosphere is not covered, hence "neutral atmosphere". The delay in metres is the time delay multiplied by the vacuum speed of light.
- (11) 0 15 079 is the hypothetical path delay with the transmitter, e.g. GNSS satellite, in the zenith of the receiver.
- (12) 0 15 081 is the contribution of atmospheric water vapour to the path delay.
- (13) 0 15 089 is the contribution of the (almost) dry atmosphere to the zenith path delay as expressed by the hydrostatic equation.
- (14) 0 15 090 is the zenith path delay due to the neutral hydrostatic atmosphere mapped onto the signal path.
- (15) 0 15 085 is the excess delay due to multi-path effects which needs to be removed from the estimated path delay.
- (16) 0 15 082 is the amount of atmospheric water vapour integrated along the signal path.

- (17) 0 15 083 is the gradient (east–west or north–south) of the neutral atmosphere estimated by the GNSS processing.
- (18) 0 15 084 Non-modelled contribution to the path delay estimated by the least squares adjustment of GNSS path delays.
- (19) A mapping function is an empirical projection of the zenith delay onto the path delay: $\text{Path delay} = \text{mapping function} * \text{zenith delay}$. It is a dimensionless real number greater than or equal to one. Different mapping functions are used for the wet and hydrostatic contributions to the delay and for the GNSS gradients.

Provisional Copy
2023

Class 19 – BUFR/CREX Synoptic features

Class 19								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 19 001	Type of synoptic feature	Code table	0	0	6	Code table	0	2
0 19 002	Effective radius of feature (see Note 1)	m	-2	0	12	m	-2	4
0 19 003	Wind speed threshold (see Note 2)	m s ⁻¹	0	0	8	m s ⁻¹	0	3
0 19 004	Effective radius with respect to wind speeds above threshold (see Note 2)	m	-2	0	12	m	-2	4
0 19 005	Direction of motion of feature (see Note 3)	degree true	0	0	9	degree true	0	3
0 19 006	Speed of motion of feature (see Note 3)	m s ⁻¹	2	0	14	m s ⁻¹	2	5
0 19 007	Effective radius of feature	m	-3	0	12	m	-3	4
0 19 008	Vertical extent of circulation	Code table	0	0	3	Code table	0	1
0 19 009	Effective radius with respect to wind speeds above threshold (large storms)	m	-3	0	12	m	-3	4
0 19 010	Method for tracking the centre of synoptic feature	Code table	0	0	4	Code table	0	2
0 19 100	Time interval to calculate the movement of the tropical cyclone	Code table	0	0	4	Code table	0	2
0 19 101	Accuracy of the position of the centre of the tropical cyclone	Code table	0	0	4	Code table	0	2
0 19 102	Shape and definition of the eye of the tropical cyclone	Code table	0	0	3	Code table	0	1
0 19 103	Diameter of major axis of the eye of the tropical cyclone	Code table	0	0	4	Code table	0	2
0 19 104	Change in character of the eye during the 30 minutes	Code table	0	0	4	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 19								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 19 105	Distance between the end of spiral band and the centre	Code table	0	0	4	Code table	0	2
0 19 106	Identification number of tropical cyclone	Numeric	0	0	7	Numeric	0	3
0 19 107	Time interval over which the movement of the tropical cyclone has been calculated	Code table	0	0	4	Code table	0	2
0 19 108	Accuracy of geographical position of the tropical cyclone	Code table	0	0	3	Code table	0	1
0 19 109	Mean diameter of the overcast cloud of the tropical cyclone	Code table	0	0	4	Code table	0	2
0 19 110	Apparent 24-hour change in intensity of the tropical cyclone	Code table	0	0	4	Code table	0	2
0 19 111	Current Intensity (CI) number of the tropical cyclone	Numeric	1	0	7	Numeric	1	3
0 19 112	Data Tropical (DT) number of the tropical cyclone	Numeric	1	0	7	Numeric	1	3
0 19 113	Cloud pattern type of the DT-number	Code table	0	0	4	Code table	0	2
0 19 114	Model Expected Tropical (MET) number of the tropical cyclone	Numeric	1	0	7	Numeric	1	3
0 19 115	Trend of the past 24-hour change (+: Developed, -: Weakened)	Numeric	1	-30	6	Numeric	1	2
0 19 116	Pattern Tropical (PT) number of the tropical cyclone	Numeric	1	0	7	Numeric	1	3
0 19 117	Cloud picture type of the PT-number	Code table	0	0	3	Code table	0	1

FM 94 BUFR, FM 95 CREX

Class 19								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 19 118	Final Tropical (T) number of the tropical cyclone	Numeric	1	0	7	Numeric	1	3
0 19 119	Type of the final T-number	Code table	0	0	3	Code table	0	1
0 19 150	Typhoon International Common Number (Typhoon Committee)	CCITT IA5	0	0	32	Character	0	4

Notes:

- (1) The effective radius of feature shall be defined with respect to the radius of the 1000-hPa isobars at mean sea level.
- (2) Maximum wind and effective radius of maximum wind shall be indicated by means of the 0 19 003 and 0 19 004 entries.
- (3) For a stationary feature, both Direction of motion of feature (0 19 005) and Speed of motion of feature (0 19 006) shall be reported as 0.

Class 20 – BUFR/CREX Observed phenomena

Class 20								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 20 001	Horizontal visibility	m	–1	0	13	m	–1	4
0 20 002	Vertical visibility	m	–1	0	7	m	–1	3
0 20 003	Present weather (see Note 1)	Code table	0	0	9	Code table	0	3
0 20 004	Past weather (1) (see Note 2)	Code table	0	0	5	Code table	0	2
0 20 005	Past weather (2) (see Note 2)	Code table	0	0	5	Code table	0	2
0 20 006	Flight rules	Code table	0	0	3	Code table	0	1
0 20 008	Cloud distribution for aviation	Code table	0	0	5	Code table	0	2
0 20 009	General weather indicator (TAF/METAR)	Code table	0	0	4	Code table	0	2
0 20 010	Cloud cover (total) (see Note 5)	%	0	0	7	%	0	3
0 20 011	Cloud amount	Code table	0	0	4	Code table	0	2
0 20 012	Cloud type	Code table	0	0	6	Code table	0	2
0 20 013	Height of base of cloud (see Note 6)	m	–1	–40	11	m	–1	4
0 20 014	Height of top of cloud	m	–1	–40	11	m	–1	4
0 20 015	Pressure at base of cloud	Pa	–1	0	14	Pa	–1	5
0 20 016	Pressure at top of cloud	Pa	–1	0	14	Pa	–1	5
0 20 017	Cloud top description	Code table	0	0	4	Code table	0	2
0 20 018	Tendency of runway visual range	Code table	0	0	2	Code table	0	1
0 20 019	Significant present or forecast weather (see Note 15)	CCITT IA5	0	0	72	Character	0	9
0 20 020	Significant recent weather phenomena (see Note 15)	CCITT IA5	0	0	32	Character	0	4
0 20 021	Type of precipitation	Flag table	0	0	30	Flag table	0	10
0 20 022	Character of precipitation	Code table	0	0	4	Code table	0	2
0 20 023	Other weather phenomena	Flag table	0	0	18	Flag table	0	6
0 20 024	Intensity of phenomena	Code table	0	0	3	Code table	0	1

FM 94 BUFR, FM 95 CREX

Class 20								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 20 025	Obscuration	Flag table	0	0	21	Flag table	0	7
0 20 026	Character of obscuration	Code table	0	0	4	Code table	0	2
0 20 027	Phenomena occurrence	Flag table	0	0	9	Flag table	0	3
0 20 028	Expected change in intensity	Code table	0	0	3	Code table	0	1
0 20 029	Rain flag	Code table	0	0	2	Code table	0	1
0 20 031	Ice deposit (thickness)	m	2	0	7	m	2	3
0 20 032	Rate of ice accretion (estimated)	Code table	0	0	3	Code table	0	1
0 20 033	Cause of ice accretion	Flag table	0	0	4	Flag table	0	2
0 20 034	Sea-ice concentration	Code table	0	0	5	Code table	0	2
0 20 035	Amount and type of ice	Code table	0	0	4	Code table	0	2
0 20 036	Ice situation	Code table	0	0	5	Code table	0	2
0 20 037	Ice development	Code table	0	0	5	Code table	0	2
0 20 038	Bearing of ice edge (see Note 3)	degree true	0	0	12	degree true	0	3
0 20 039	Ice distance	m	-1	0	13	m	-1	4
0 20 040	Evolution of drift snow	Code table	0	0	4	Code table	0	2
0 20 041	Airframe icing	Code table	0	0	4	Code table	0	2
0 20 042	Airframe icing present	Code table	0	0	2	Code table	0	1
0 20 043	Peak liquid water content	kg m ⁻³	4	0	7	kg m ⁻³	4	2
0 20 044	Average liquid water content	kg m ⁻³	4	0	7	kg m ⁻³	4	2
0 20 045	Supercooled large droplet (SLD) conditions	Code table	0	0	2	Code table	0	1
0 20 048	Evolution of feature	Code table	0	0	4	Code table	0	2
0 20 050	Cloud index	Code table	0	0	8	Code table	0	3
0 20 051	Amount of low clouds	%	0	0	7	%	0	3
0 20 052	Amount of middle clouds	%	0	0	7	%	0	3
0 20 053	Amount of high clouds	%	0	0	7	%	0	3

FM 94 BUFR, FM 95 CREX

Class 20								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed (see Note 17)	degree true	0	0	9	degree true	0	3
0 20 055	State of sky in the tropics	Code table	0	0	4	Code table	0	2
0 20 056	Cloud phase	Code table	0	0	3	Code table	0	1
0 20 058	Visibility seawards from a coastal station	m	-1	0	13	m	-1	4
0 20 059	Minimum horizontal visibility	m	-1	0	9	m	-1	3
0 20 060	Prevailing horizontal visibility (see Note 7)	m	-1	0	10	m	-1	4
0 20 061	Runway visual range (RVR)	m	0	0	12	m	0	4
0 20 062	State of the ground (with or without snow)	Code table	0	0	5	Code table	0	2
0 20 063	Special phenomena	Code table	0	0	10	Code table	0	4
0 20 065	Snow cover (see Note 4)	%	0	0	7	%	0	3
0 20 066	Maximum diameter of hailstones	m	3	0	8	m	3	3
0 20 067	Diameter of deposit	m	3	0	9	m	3	3
0 20 070	Minimum number of atmospherics	Numeric	0	0	7	Numeric	0	3
0 20 071	Accuracy of fix and rate of atmospherics	Code table	0	0	4	Code table	0	2
0 20 081	Cloud amount in segment	%	0	0	7	%	0	3
0 20 082	Amount segment cloud free	%	0	0	7	%	0	3
0 20 083	Amount of segment covered by scene	%	0	0	7	%	0	3
0 20 085	General condition of runway	Code table	0	0	4	Code table	0	1
0 20 086	Runway deposits	Code table	0	0	4	Code table	0	1
0 20 087	Runway contamination	Code table	0	0	4	Code table	0	1
0 20 088	Depth of runway deposits	m	3	0	12	m	0	4
0 20 089	Runway friction coefficient	Code table	0	0	7	Code table	0	2

FM 94 BUFR, FM 95 CREX

Class 20								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 20 090	Special clouds	Code table	0	0	4	Code table	0	2
0 20 091	Vertical visibility	ft	-2	0	10	ft	-2	3
0 20 092	Height of base of cloud	ft	-2	0	10	ft	-2	3
0 20 093	Height of inversion	m	-1	0	8	m	-1	3
0 20 095	Ice probability	Numeric	3	0	10	Numeric	3	4
0 20 096	Ice age ("A" parameter)	dB	2	-4096	13	dB	2	4
0 20 101	Locust (acridian) name	Code table	0	0	4	Code table	0	2
0 20 102	Locust (maturity) colour	Code table	0	0	4	Code table	0	2
0 20 103	Stage of development of locusts	Code table	0	0	4	Code table	0	2
0 20 104	Organization state of swarm or band of locusts	Code table	0	0	4	Code table	0	2
0 20 105	Size of swarm or band of locusts and duration of passage of swarm	Code table	0	0	4	Code table	0	2
0 20 106	Locust population density	Code table	0	0	4	Code table	0	2
0 20 107	Direction of movements of locust swarm	Code table	0	0	4	Code table	0	2
0 20 108	Extent of vegetation	Code table	0	0	4	Code table	0	2
0 20 111	x-axis error ellipse major component (see Notes 8 and 9)	m	-1	0	17	m	-1	6
0 20 112	y-axis error ellipse minor component (see Notes 8 and 9)	m	-1	0	17	m	-1	6
0 20 113	z-axis error ellipse component (see Note 9)	m	-1	0	17	m	-1	6
0 20 114	Angle of x-axis in error ellipse (see Note 10)	°	2	-18000	16	°	2	5
0 20 115	Angle of z-axis in error ellipse (see Note 11)	°	2	-18000	16	°	2	5
0 20 116	Emission height of cloud stroke	m	0	0	16	m	0	5
0 20 117	Amplitude of lightning strike	A	-1	-32000	16	A	-1	5
0 20 118	Lightning detection error	m	0	0	19	m	0	6

FM 94 BUFR, FM 95 CREX

Class 20								
TABLE REFERENCE F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
0 20 119	Lightning discharge polarity	Code table	0	0	2	Code table	0	1
0 20 121	Threshold value for polarity decision (see Note 12)	V	3	0	16	V	3	5
0 20 122	Threshold value for polarity decision (see Note 13)	A	0	0	16	A	0	5
0 20 123	Minimum threshold for detection (see Note 14)	V m ⁻¹	3	0	16	V m ⁻¹	3	5
0 20 124	Lightning stroke or flash	Code table	0	0	2	Code table	0	1
0 20 126	Lightning rate of discharge	h ⁻¹	0	0	23	h ⁻¹	0	7
0 20 127	Lightning – distance from station	m	-3	0	8	m	-3	3
0 20 128	Lightning – direction from station	degree true	1	0	12	degree true	1	4
0 20 129	Lightning density (stroke, flash or event)	m ⁻²	6	0	10	m ⁻²	6	4
0 20 130	Cloud hydrometeor concentration (see Note 16)	Numeric	0	0	10	Numeric	0	3
0 20 131	Effective radius of cloud hydrometeors	m	5	0	6	m	5	2
0 20 132	Cloud liquid water content	kg m ⁻³	5	0	11	kg m ⁻³	5	4
0 20 133	Hydrometeor radius	m	5	0	6	m	5	2
0 20 135	Ice mass (on a rod)	kg m ⁻¹	1	0	10	kg m ⁻¹	1	3
0 20 136	Supplementary cloud type	Code table	0	0	9	Code table	0	3
0 20 137	Evolution of clouds	Code table	0	0	4	Code table	0	2
0 20 138	Road surface condition	Code table	0	0	4	Code table	0	2

Notes:

- (1) When encoding present weather reported from an automatic weather station, the appropriate combination of descriptors 0 20 021, 0 20 022, 0 20 023, 0 20 024, 0 20 025, 0 20 026 and 0 20 027 should be used and preferred. Descriptor 0 20 003 should be used only when descriptors mentioned above are not applicable.

- (2) When encoding past weather reported from an automatic weather station, the appropriate combination of descriptors 0 20 021, 0 20 022, 0 20 023, 0 20 024, 0 20 025, 0 20 026 and 0 20 027 should be used and preferred. Descriptors 0 20 004 or 0 20 005 should be used only when descriptors mentioned above are not applicable.
 - (3) The data width for descriptor 0 20 038 originally defined to be 12 is wrong. 9 bits are sufficient as for all the other "degree true" quantities. However, the 12-bit width is maintained for historical consistency. Also: A bearing of ice edge value 0 shall indicate "Ship in shore or flaw lead".
 - (4) Snow cover will be reported for each satellite pixel as a percentage of coverage of the pixel. It does not seem feasible to try to use existing descriptor 0 20 062 for such a purpose because the use of that descriptor additionally implies details on, e.g. snow drifts, wet compared to dry snow that a satellite obviously cannot accurately detect.
 - (5) A cloud cover (total) value 113 shall indicate "Sky obscured by fog and/or other meteorological phenomena".
 - (6) When encoding height of cloud base between 20 050 and 21 000 m, 0 20 013 shall be set to 20 050; when encoding height of cloud base above 21 000 m, 0 20 013 shall be set to 20 060.
 - (7) A prevailing visibility value of 10 000 m before scaling (after scaling 1000) shall be used to report prevailing visibility 10 km or more.
 - (8) If $x = y$ then it is a radial error, and the angle (see 0 20 114) will be zero.
 - (9) If $x = y = z$ then it is a spherical error, and the angle (see 0 20 115) will be zero.
 - (10) Angle of the error defined by 0 20 113 and 0 20 114. Cartesian with sign bit.
 - (11) Angle of the error defined by 0 20 112, 0 20 113 and 0 20 114. Cartesian with sign bit.
 - (12) 0 20 121 used in combination with 0 25 035, or all zero if not defined. Typically +1.000 V.
 - (13) 0 20 122 used in combination with 0 25 035, or all zero if not defined. Typically +2000 A.
 - (14) Minimum signal level acceptable for processing, e.g. 0.005 V or 5 mV, or typically just above the noise floor of the detector.
 - (15) Significant present or forecast weather (0 20 019) and Significant recent weather phenomena (0 20 020) shall be used in accordance with Code table 4678 (Reference: *Manual on Codes* (WMO-No. 306), Volume I.1).
 - (16) Cloud hydrometeor concentration (0 20 130) represents the number of hydrometeors in 1 dm³.
 - (17) True direction of a phenomenon or clouds (0 20 054) shall be used to indicate true direction from which a phenomenon or clouds are moving or in which they are observed. 0 20 054 value 0 shall indicate "stationary or no clouds" or "observed at the station", whereas value 500 shall indicate "observed in all directions" and value 501 shall indicate "unknown or clouds invisible".
-

Class 21 – BUFR/CREX Radar data

Class 21								
TABLE REFERENC E	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 21 001	Horizontal reflectivity	dB	0	-64	7	dB	0	3
0 21 002	Vertical reflectivity	dB	0	-64	7	dB	0	3
0 21 003	Differential reflectivity	dB	1	-5	7	dB	1	3
0 21 004	Differential reflectivity	dB	2	-800	11	dB	2	4
0 21 005	Linear depolarization ratio	dB	0	-65	6	dB	0	2
0 21 006	Circular depolarization ratio	dB	0	-65	6	dB	0	2
0 21 007	Radar reflectivity factor	dB	2	-9000	15	dB	0	0
0 21 008	Uncertainty in radar reflectivity factor	dB	2	0	13	dB	0	0
0 21 009	Vertical Doppler velocity	m/s	2	-10000	15	m/s	0	0
0 21 010	Uncertainty in vertical Doppler velocity	m/s	2	-10000	15	m/s	0	0
0 21 011	Doppler mean velocity in x-direction	m s ⁻¹	0	-128	8	m s ⁻¹	0	3
0 21 012	Doppler mean velocity in y-direction	m s ⁻¹	0	-128	8	m s ⁻¹	0	3
0 21 013	Doppler mean velocity in z-direction	m s ⁻¹	0	-128	8	m s ⁻¹	0	3
0 21 014	Doppler mean velocity (radial)	m s ⁻¹	1	-4096	13	m s ⁻¹	1	4
0 21 017	Doppler velocity spectral width	m s ⁻¹	1	0	8	m s ⁻¹	1	3
0 21 018	Extended NYQUIST velocity	m s ⁻¹	1	0	10	m s ⁻¹	1	4
0 21 019	High NYQUIST velocity	m s ⁻¹	1	0	10	m s ⁻¹	1	3
0 21 021	Echo tops	m	-3	0	4	m	-3	2
0 21 022	Range bin offset	m	1	0	14	m	1	5
0 21 023	Range bin size	m	0	0	14	m	0	5
0 21 024	Azimuth offset	°	1	0	12	°	1	4
0 21 025	Azimuthal resolution	°	1	0	8	°	1	3
<u>0 21 026</u>	<u>ASCAT sigma-0 usability</u>	<u>Code table</u>	<u>0</u>	<u>0</u>	<u>3</u>	<u>Code table</u>	<u>0</u>	<u>1</u>
<u>0 21 027</u>	<u>Land contribution ratio</u>	<u>Numeric</u>	<u>4</u>	<u>0</u>	<u>14</u>	<u>Numeric</u>	<u>4</u>	<u>5</u>
0 21 028	Differential phase	°	1	0	12	°	1	4

FM 94 BUFR, FM 95 CREX

Class 21								
TABLE REFERENC E F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 21 029	Cross-polarization correlation coefficient	Numeric	2	-100	8	Numeric	2	3
0 21 030	Signal to noise ratio	dB	0	-32	8	dB	0	3
0 21 031	Vertically integrated liquid-water content	kg m ⁻²	0	0	7	kg m ⁻²	0	3
0 21 036	Radar rainfall intensity	m s ⁻¹	7	0	12	m s ⁻¹	7	4
0 21 041	Bright-band height	m	-2	0	8	m	-2	3
0 21 051	Signal power above 1 mW	dB	0	-256	8	dB	0	3
0 21 062	Backscatter	dB	2	-5000	13	dB	2	4
0 21 063	Radiometric resolution (noise value)	%	1	0	10	%	1	4
0 21 064	Clutter noise estimate	Numeric	0	0	8	Numeric	0	3
0 21 065	Missing packet counter	Numeric	0	-127	8	Numeric	0	3
0 21 066	Wave scatterometer product confidence data	Flag table	0	0	12	Flag table	0	4
0 21 067	Wind product confidence data	Flag table	0	0	13	Flag table	0	5
0 21 068	Radar altimeter product confidence data	Flag table	0	0	8	Flag table	0	3
0 21 069	SST product confidence data	Flag table	0	0	10	Flag table	0	4
0 21 070	SST product confidence data (SADIST-2)	Flag table	0	0	23	Flag table	0	6
0 21 071	Peakiness	Numeric	0	0	16	Numeric	0	5
0 21 072	Satellite altimeter calibration status	Flag table	0	0	4	Flag table	0	2
0 21 073	Satellite altimeter instrument mode	Flag table	0	0	9	Flag table	0	3
0 21 075	Image spectrum intensity	Numeric	0	0	8	Numeric	0	3
0 21 076	Representation of intensities	Code table	0	0	3	Code table	0	1
0 21 077	Altitude correction (ionosphere)	m	3	0	14	m	3	5
0 21 078	Altitude correction (dry troposphere)	m	3	0	9	m	3	3
0 21 079	Altitude correction (wet troposphere)	m	3	2000	10	m	3	4
0 21 080	Altitude correction (calibration constant)	m	3	0	11	m	3	4
0 21 081	Open loop correction (height-time loop)	m	3	0	10	m	3	4
0 21 082	Open loop correction (auto gain control)	dB	3	-3000	14	dB	3	5
0 21 083	Warm target calibration	Numeric	0	0	16	Numeric	0	5

FM 94 BUFR, FM 95 CREX

Class 21								
TABLE REFERENC E	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 21 084	Cold target calibration	Numeric	0	0	16	Numeric	0	5
0 21 085	ATSR sea-surface temperature across-track band number	Numeric	0	0	4	Numeric	0	2
0 21 086	Number of pixels in nadir only, average	Numeric	0	0	9	Numeric	0	3
0 21 087	Number of pixels in dual view, average	Numeric	0	0	9	Numeric	0	3
0 21 088	Wet backscatter	dB	2	-5000	13	dB	2	4
0 21 091	Radar signal Doppler spectrum 0th moment	dB	0	-100	8	dB	0	3
0 21 092	RASS signal Doppler spectrum 0th moment, referring to RASS signal	dB	0	-100	8	dB	0	3
0 21 093	Ku band peakiness	Numeric	3	0	16	Numeric	3	5
0 21 094	S band peakiness	Numeric	3	0	16	Numeric	3	5
0 21 095	Kp coefficient A	Numeric	6	0	20	Numeric	6	7
0 21 096	Kp coefficient B	Numeric	6	0	20	Numeric	6	7
0 21 097	Kp coefficient C	Numeric	6	0	20	Numeric	6	7
0 21 101	Number of vector ambiguities	Numeric	0	0	3	Numeric	0	1
0 21 102	Index of selected wind vector	Numeric	0	0	3	Numeric	0	1
0 21 103	Total number of sigma-0 measurements	Numeric	0	0	5	Numeric	0	2
0 21 104	Likelihood computed for solution	Numeric	3	-30000	15	Numeric	3	5
0 21 105	Normalized radar cross-section	dB	2	-10000	14	dB	2	5
0 21 106	Kp variance coefficient (alpha)	Numeric	3	0	14	Numeric	3	5
0 21 107	Kp variance coefficient (beta)	Numeric	8	0	16	Numeric	8	5
0 21 109	SEAWINDS wind vector cell quality	Flag table	0	0	17	Flag table	0	6
0 21 110	Number of inner-beam sigma-0 (forward of satellite)	Numeric	0	0	6	Numeric	0	2
0 21 111	Number of outer-beam sigma-0 (forward of satellite)	Numeric	0	0	6	Numeric	0	2
0 21 112	Number of inner-beam sigma-0 (aft of satellite)	Numeric	0	0	6	Numeric	0	2

FM 94 BUFR, FM 95 CREX

Class 21								
TABLE REFERENC E F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 21 113	Number of outer-beam sigma-0 (aft of satellite)	Numeric	0	0	6	Numeric	0	2
0 21 114	Kp variance coefficient (gamma)	dB	3	-140000	18	dB	3	6
0 21 115	SEAWINDS sigma-0 quality	Flag table	0	0	17	Flag table	0	6
0 21 116	SEAWINDS sigma-0 mode	Flag table	0	0	17	Flag table	0	6
0 21 117	Sigma-0 variance quality control	Numeric	2	0	16	Numeric	2	5
0 21 118	Attenuation correction on sigma-0	dB	2	-10000	14	dB	2	5
0 21 119	Wind scatterometer geophysical model function	Code table	0	0	6	Code table	0	2
0 21 120	Probability of rain	Numeric	3	0	10	Numeric	3	4
0 21 121	SEAWINDS NOF rain index	Numeric	0	0	8	Numeric	0	3
0 21 122	Attenuation correction on sigma-0 (from tB)	dB	2	-10000	14	dB	2	5
0 21 123	SEAWINDS normalized radar cross-section	dB	2	-30000	15	dB	2	5
0 21 128	Number of valid points per second used to derive previous parameters	Numeric	0	0	8	Numeric	0	3
0 21 130	Spectrum total energy	Numeric	6	0	28	Numeric	6	9
0 21 131	Spectrum max energy	Numeric	6	0	28	Numeric	6	9
0 21 132	Direction of spectrum max on higher resolution grid	°	3	0	19	°	3	6
0 21 133	Wavelength of spectrum max on higher resolution grid	m	3	0	29	m	3	9
0 21 134	Range resolution of cress covariance spectrum	rad m ⁻¹	3	0	19	rad m ⁻¹	3	6
0 21 135	Real part of cross spectra polar grid number of bins	Numeric	3	-524288	20	Numeric	3	7
0 21 136	Imaginary part of cross spectra polar grid number of bins	Numeric	3	-524288	20	Numeric	3	7
0 21 137	Ku band corrected ocean backscatter coefficient	dB	2	-32768	16	dB	2	5

FM 94 BUFR, FM 95 CREX

Class 21								
TABLE REFERENC E	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 21 138	Std Ku band corrected ocean backscatter coefficient	dB	2	-32768	16	dB	2	5
0 21 139	Ku band net instrumental correction for AGC	dB	2	-2048	12	dB	2	4
0 21 140	S band corrected ocean backscatter coefficient	dB	2	-32768	16	dB	2	5
0 21 141	Std S band corrected ocean backscatter coefficient	dB	2	-32768	16	dB	2	5
0 21 142	S band net instrumental correction for AGC	dB	2	-1024	11	dB	2	4
0 21 143	Ku band rain attenuation	dB	2	-1073741824	31	dB	2	10
0 21 144	Altimeter rain flag	Flag table	0	0	2	Flag table	0	1
0 21 145	Ku band automatic gain control	dB	2	0	13	dB	2	4
0 21 146	RMS Ku band automatic gain control	dB	2	0	8	dB	2	3
0 21 147	Number of valid points for Ku band automatic gain control	Numeric	0	0	5	Numeric	0	2
0 21 148	Trailing edge variation flag	Flag table	0	0	9	Flag table	0	3
0 21 150	Beam co-location	Code table	0	0	2	Code table	0	1
0 21 151	Estimated error in sigma-0 at 40 degrees incidence angle	dB	2	0	9	dB	2	3
0 21 152	Slope at 40 degrees incidence angle	dB degree ⁻¹	2	-80	7	dB degree ⁻¹	2	2
0 21 153	Estimated error in slope at 40 degrees incidence angle	dB degree ⁻¹	2	-40	6	dB degree ⁻¹	2	2
0 21 154	Soil moisture sensitivity	dB	2	0	12	dB	2	4
0 21 155	Wind vector cell quality	Flag table	0	0	24	Flag table	0	8
0 21 156	Backscatter distance	Numeric	1	-4096	13	Numeric	1	4
0 21 157	Loss per unit length of atmosphere used	dB m ⁻¹	10	0	22	dB m ⁻¹	10	7
0 21 158	ASCAT Kp estimate quality	Code table	0	0	2	Code table	0	1

FM 94 BUFR, FM 95 CREX

Class 21								
TABLE REFERENC E	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 21 159	ASCAT sigma-0 usability	Code table	0	0	2	Code table	0	1
0 21 160	ASCAT use of synthetic data	Numeric	3	0	10	Numeric	3	4
0 21 161	ASCAT synthetic data quantity	Numeric	3	0	10	Numeric	3	4
0 21 162	ASCAT satellite orbit and attitude quality	Numeric	3	0	10	Numeric	3	4
0 21 163	ASCAT solar array reflection contamination	Numeric	3	0	10	Numeric	3	4
0 21 164	ASCAT telemetry presence and quality	Numeric	3	0	10	Numeric	3	4
0 21 165	ASCAT extrapolated reference function presence	Numeric	3	0	10	Numeric	3	4
0 21 166	Land fraction	Numeric	3	0	10	Numeric	3	4
0 21 169	Ice presence indicator	Code table	0	0	2	Code table	0	1
0 21 170	C band corrected ocean backscatter coefficient	dB	2	-32768	16	dB	2	5
0 21 171	RMS C band corrected ocean backscatter coefficient	dB	2	-32768	16	dB	2	5
0 21 172	C band net instrumental correction for AGC	dB	2	-2048	12	dB	2	4
0 21 173	C band automatic gain control	dB	2	0	13	dB	2	4
0 21 174	RMS C band automatic gain control	dB	2	0	9	dB	2	3
0 21 175	Number of valid points for C band automatic gain control	Numeric	0	0	10	Numeric	0	4
0 21 176	High frequency variability correction	m	3	0	16	m	3	5
0 21 177	Corrected OCOG backscatter coefficient	dB	2	0	16	dB	2	5
0 21 178	STD of 20 Hz OCOG backscatter coefficient	dB	2	0	16	dB	2	5
0 21 179	Number of 20 Hz valid points for OCOG backscatter coefficient	Numeric	0	0	16	Numeric	0	5
0 21 180	Number of 20 Hz valid points for ocean backscatter coefficient	Numeric	0	0	8	Numeric	0	3
0 21 181	20 Hz ocean backscatter coefficient	dB	2	0	16	dB	2	5

FM 94 BUFR, FM 95 CREX

Class 21								
TABLE REFERENC E F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 21 182	20 Hz Ku band peakiness	Numeric	3	0	16	Numeric	3	5
0 21 183	Specific band corrected ocean backscatter coefficient	dB	2	-32768	16	dB	2	5
0 21 184	STD specific band corrected ocean backscatter coefficient	dB	2	-32768	16	dB	2	5
0 21 185	Specific band net instrumental correction for AGC	dB	2	-2048	12	dB	2	4
0 21 186	Specific band automatic gain control	dB	2	0	13	dB	2	4
0 21 187	RMS specific band automatic gain control	dB	2	0	8	dB	2	3
0 21 188	Number of valid points for specific band automatic gain control	Numeric	0	0	7	Numeric	0	3
0 21 189	Corrected OCOG backscatter coefficient (negative reference) (see Note)	dB	2	-32768	16	dB	2	6

Note: 0 21 189 is similar to 0 21 177, but with a negative reference value

Class 22 – BUFR/CREX Oceanographic elements

Class 22								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 22 001	Direction of waves (see Note 6)	degree true	0	0	9	degree true	0	3
0 22 002	Direction of wind waves (see Note 6)	degree true	0	0	9	degree true	0	3
0 22 003	Direction of swell waves (see Note 6)	degree true	0	0	9	degree true	0	3
0 22 004	Direction of current (see Note 7)	degree true	0	0	9	degree true	0	3
0 22 005	Direction of sea-surface current	degree true	0	0	9	degree true	0	3
0 22 011	Period of waves	s	0	0	6	s	0	2
0 22 012	Period of wind waves	s	0	0	6	s	0	2
0 22 013	Period of swell waves	s	0	0	6	s	0	2
0 22 021	Height of waves	m	1	0	10	m	1	4
0 22 022	Height of wind waves	m	1	0	10	m	1	4
0 22 023	Height of swell waves	m	1	0	10	m	1	4
0 22 025	Standard deviation wave height	m	2	0	10	m	2	4
0 22 026	Standard deviation of significant wave height	m	2	0	10	m	2	4
0 22 031	Speed of current	m s ⁻¹	2	0	13	m s ⁻¹	2	4
0 22 032	Speed of sea-surface current	m s ⁻¹	2	0	13	m s ⁻¹	2	4
0 22 035	Tidal elevation with respect to local chart datum	m	2	0	14	m	2	4
0 22 036	Meteorological residual tidal elevation (surge or offset)	m	2	0	14	m	2	4
0 22 037	Tidal elevation with respect to national land datum	m	3	-10000	15	m	3	5
0 22 038	Tidal elevation with respect to local chart datum	m	3	-10000	15	m	3	5

FM 94 BUFR, FM 95 CREX

Class 22								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 22 039	Meteorological residual tidal elevation (surge or offset) (see Note 4)	m	3	-5000	13	m	3	4
0 22 040	Meteorological residual tidal elevation (surge or offset) (see Note 4)	m	3	-5000	14	m	3	5
0 22 041	Sea-surface temperature (15-day running mean)	K	1	0	12	K	1	4
0 22 042	Sea/water temperature	K	1	0	12	K	1	4
0 22 043	Sea/water temperature	K	2	0	15	K	2	5
0 22 044	Sound velocity	m s ⁻¹	1	0	14	m s ⁻¹	1	5
0 22 045	Sea/water temperature	K	3	0	19	K	3	6
0 22 046	Sea-ice fraction	Numeric	2	0	7	Numeric	2	3
0 22 049	Sea-surface temperature	K	2	0	15	K	2	5
0 22 050	Standard deviation sea-surface temperature	K	2	0	8	K	2	3
0 22 055	Float cycle number	Numeric	0	0	10	Numeric	0	3
0 22 056	Direction of profile	Code table	0	0	2	Code table	0	1
0 22 059	Sea-surface salinity	‰	2	0	14	‰	2	5
0 22 060	Lagrangian drifter drogue status	Code table	0	0	3	Code table	0	1
0 22 061	State of the sea	Code table	0	0	4	Code table	0	2
0 22 062	Salinity	‰	2	0	14	‰	2	5
0 22 063	Total water depth	m	0	0	14	m	0	5
0 22 064	Salinity	‰	3	0	17	‰	3	6
0 22 065	Water pressure	Pa	-3	0	17	Pa	-3	6
0 22 066	Water conductivity	S m ⁻¹	6	0	26	S m ⁻¹	6	8
0 22 067	Instrument type for water temperature/ salinity profile measurement	Code table	0	0	10	Code table	0	4

FM 94 BUFR, FM 95 CREX

Class 22								
TABLE REFERENCE F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
0 22 068	Water temperature profile recorder types	Code table	0	0	7	Code table	0	3
0 22 069	Spectral wave density	m ² Hz ⁻¹	3	0	22	m ² Hz ⁻¹	3	7
0 22 070	Significant wave height (see Note 1)	m	2	0	13	m	2	4
0 22 071	Spectral peak wave period	s	1	0	9	s	1	3
0 22 072	Spectral peak wavelength	m	0	0	13	m	0	4
0 22 073	Maximum wave height	m	2	0	13	m	2	4
0 22 074	Average wave period	s	1	0	9	s	1	3
0 22 075	Average wavelength	m	0	0	13	m	0	4
0 22 076	Direction from which dominant waves are coming (see Note 2)	degree true	0	0	9	degree true	0	3
0 22 077	Directional spread of dominant wave (see Note 2)	°	0	0	9	°	0	3
0 22 078	Duration of wave record	s	0	0	12	s	0	4
0 22 080	Waveband central frequency	Hz	3	0	10	Hz	3	4
0 22 081	Waveband central wave number	m ⁻¹	5	0	13	m ⁻¹	5	4
0 22 082	Maximum non-directional spectral wave density	m ² s	2	0	20	m ² s	2	7
0 22 083	Maximum non-directional spectral wave number	m ³	2	0	20	m ³	2	7
0 22 084	Band containing maximum non-directional spectral wave density	Numeric	0	0	7	Numeric	0	3
0 22 085	Spectral wave density ratio	Numeric	0	0	7	Numeric	0	3
0 22 086	Mean direction from which waves are coming (see Note 3)	degree true	0	0	9	degree true	0	3
0 22 087	Principal direction from which waves are coming	degree true	0	0	9	degree true	0	3
0 22 088	First normalized polar coordinate from Fourier coefficients	Numeric	2	0	7	Numeric	2	3

FM 94 BUFR, FM 95 CREX

Class 22								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 22 089	Second normalized polar coordinate from Fourier coefficients	Numeric	2	0	7	Numeric	2	3
0 22 090	Non-directional spectral estimate by wave frequency	m ² s	2	0	20	m ² s	2	7
0 22 091	Non-directional spectral estimate by wave number	m ³	2	0	20	m ³	2	7
0 22 092	Directional spectral estimate by wave frequency	m ² rad ⁻¹ s	2	0	20	m ² rad ⁻¹ s	2	7
0 22 093	Directional spectral estimate by wave number	m ⁴	2	0	20	m ⁴	2	7
0 22 094	Total number of wave bands	Numeric	0	0	7	Numeric	0	3
0 22 095	Directional spread of individual waves	°	0	0	8	°	0	3
0 22 096	Spectral band width	s ⁻¹	3	0	4	s ⁻¹	3	2
0 22 097	Mean wavelength > 731 m of image spectrum at low wave numbers (see Note 5)	m	0	0	14	m	0	5
0 22 098	Wavelength spread (wavelength > 731 m) at low wave numbers (see Note 5)	m	0	0	14	m	0	5
0 22 099	Mean direction at low wave numbers (wavelength > 731 m) (see Note 5)	degree true	0	0	9	degree true	0	3
0 22 100	Direction spread at low wave numbers (wavelength > 731 m) (see Note 5)	°	0	0	9	°	0	3
0 22 101	Total energy (wavelength > 731m) at low wave numbers (see Note 5)	Numeric	0	0	31	Numeric	0	10
0 22 102	Scaled maximum non-directional spectral wave density by frequency (see Note 10)	m ² s	0	0	14	m ² s	0	5

FM 94 BUFR, FM 95 CREX

Class 22								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
F X Y		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
0 22 103	Scaled maximum non-directional spectral wave density by wave number (see Note 10)	m ³	0	0	14	m ³	0	5
0 22 104	Scaled non-directional spectral wave density by frequency (see Note 10)	m ² s	0	0	14	m ² s	0	5
0 22 105	Scaled non-directional spectral wave density by wave number (see Note 10)	m ³	0	0	14	m ³	0	5
0 22 106	Scaled directional spectral wave density by frequency (see Note 10)	m ² s rad ⁻¹	0	0	14	m ² s rad ⁻¹	0	5
0 22 107	Scaled directional spectral wave density by wave number (see Note 10)	m ⁴	0	0	14	m ⁴	0	5
0 22 108	Spectral wave density ratio	%	0	0	7	%	0	3
0 22 120	Tide station automated water level check	Code table	0	0	5	Code table	0	2
0 22 121	Tide station manual water level check	Code table	0	0	5	Code table	0	2
0 22 122	Tide station automated meteorological data check	Code table	0	0	5	Code table	0	2
0 22 123	Tide station manual meteorological data check	Code table	0	0	5	Code table	0	2
0 22 130	Number of valid points for specific band	Numeric	0	0	10	Numeric	0	4
0 22 131	RMS specific band significant wave height	m	3	0	16	m	3	5
0 22 132	Number of valid points for specific band significant wave height	Numeric	0	0	10	Numeric	0	4
0 22 133	Specific band net instrument correction for significant wave height	m	3	-1000	11	m	3	4

FM 94 BUFR, FM 95 CREX

Class 22								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 22 134	Number of valid points for specific band backscatter	Numeric	0	0	10	Numeric	0	4
0 22 141	Sea-surface temperature (15-day running mean)	K	2	0	15	K	2	5
0 22 142	Square of significant wave height	m ²	3	-33554432	26	m ²	3	8
0 22 143	STD of 20 Hz SWH squared	m ²	3	-8388608	24	m ²	3	8
0 22 144	Number of 20 Hz valid points for SWH squared	Numeric	0	0	9	Numeric	0	3
0 22 145	STD of 20 Hz ocean range	m	3	-33554432	31	m	3	10
0 22 146	OCOG range	m	3	0	31	m	3	10
0 22 147	STD of 20 Hz OCOG range	m	3	-8388608	31	m	3	10
0 22 148	Number of 20 Hz valid points for ocean range	Numeric	0	0	9	Numeric	0	3
0 22 149	20 Hz significant wave height squared	m ²	3	-33554432	26	m ²	3	8
0 22 150	Number of 18 Hz valid points for Ku band	Numeric	0	0	10	Numeric	0	4
0 22 151	Ku band ocean range	m	3	0	31	m	3	10
0 22 152	STD of 18 Hz Ku band ocean range	m	3	0	16	m	3	5
0 22 153	Number of 18 Hz valid points for S band	Numeric	0	0	10	Numeric	0	4
0 22 154	S band ocean range	m	3	0	31	m	3	10
0 22 155	STD of 18 Hz S band ocean range	m	3	0	16	m	3	5
0 22 156	Ku band significant wave height	m	3	0	16	m	3	5
0 22 157	STD of 18 Hz Ku band ocean range	m	3	0	16	m	3	5
0 22 158	S band significant wave height	m	3	0	16	m	3	5
0 22 159	STD of 18 Hz S band significant wave height	m	3	0	16	m	3	5
0 22 160	Normalized inverse wave age	Numeric	6	0	21	Numeric	6	7
0 22 161	Wave spectra	m ⁴	4	0	27	m ⁴	4	9

FM 94 BUFR, FM 95 CREX

Class 22								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 22 162	RMS of 20 Hz Ku band ocean range	m	3	0	16	m	3	5
0 22 163	Number of 20 Hz valid points for Ku band	Numeric	0	0	10	Numeric	0	4
0 22 164	RMS 20 Hz Ku band significant wave height	m	3	0	16	m	3	5
0 22 165	Number of 20 Hz valid points for Ku band significant wave height	Numeric	0	0	10	Numeric	0	4
0 22 166	Ku band net instrumental correction for significant wave height	m	3	-1000	11	m	3	4
0 22 167	Number of valid points for Ku band backscatter	Numeric	0	0	10	Numeric	0	4
0 22 168	C band ocean range	m	3	0	31	m	3	10
0 22 169	RMS of C band ocean range	m	3	0	16	m	3	5
0 22 170	Number of 20 Hz valid points for C band	Numeric	0	0	10	Numeric	0	4
0 22 171	C band significant wave height	m	3	0	16	m	3	5
0 22 172	RMS 20 Hz C band significant wave height	m	3	0	16	m	3	5
0 22 173	Number of 20 Hz valid points for C band significant wave height	Numeric	0	0	10	Numeric	0	4
0 22 174	C band net instrumental correction for significant wave height	m	3	-1000	11	m	3	4
0 22 175	Number of valid points for C band backscatter	Numeric	0	0	10	Numeric	0	4
0 22 177	Height of XBT/XCTD launcher	m	0	0	6	m	0	3
0 22 178	XBT/XCTD launcher type	Code table	0	0	8	Code table	0	3
0 22 179	Specific band significant wave height (negative reference) (see Note 13)	m	3	-500	16	m	3	6

FM 94 BUFR, FM 95 CREX

Class 22								
TABLE REFERENCE F X Y	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
0 22 182	Water column height (see Note 9)	m	3	0	23	m	3	7
0 22 184	Water column height deviation from the reference value	m	3	-2000	12	m	3	4
0 22 185	BPR transmission count	Numeric	0	0	10	Numeric	0	3
0 22 186	Direction from which waves are coming (see Note 11)	degree true	0	0	9	degree true	0	3
0 22 187	Directional spread of wave (see Note 12)	°	0	0	9	°	0	3
0 22 188	Dissolved oxygen	μmol kg ⁻¹	3	0	19	μmol kg ⁻¹	3	6
0 22 189	Specific band ocean range	m	3	0	31	m	3	10
0 22 190	Specific band significant wave height	m	3	0	16	m	3	5
0 22 191	RMS of specific band ocean range	m	4	0	16	m	4	5

Notes:

- (1) The significant wave height is defined as four times the square root of the energy spectrum integrated over direction and frequency. It corresponds to about the height that one third of all waves exceed.
- (2) The dominant wave is the one that has the maximum energy in the energy spectrum.
- (3) Mean wave direction is the angle alpha 1 and principal wave direction is the angle alpha 2, in the expression $S(f, \alpha)$ approximately equals:

$$c_{11} \times (0.5 + r_1 \times \cos(\alpha - \alpha_1) + r_2 \times \cos(2(\alpha - \alpha_2))) / \pi$$
in which $S(f, \alpha)$ is the wave directional spectrum and c_{11} is the non-directional spectrum, and the right hand side of this expression is the first two terms of the Fourier series expansion of $S(f, \alpha)$. If the mean and principal directions differ significantly (e.g. more than 15 degrees) for a given frequency, crossing seas are indicated.
- (4) Descriptor 0 22 040 should be used instead of 0 22 039 for encoding meteorological residual tidal elevation (surge or offset).

- (5) Additional information:
 0 22 097 nominal input range 0 – 10000
 0 22 098 nominal input range 0 – 10000
 0 22 099 nominal input range 0 – 359
 0 22 100 nominal input range 0 – 359
 0 22 101 nominal input range 0 – 2×10^6 , but may be greater because of uncertainty.
- (6) Descriptors 0 22 001, 0 22 002, 0 22 003: the direction given in these entries is the direction which waves are coming from.
- (7) Descriptor 0 22 004: the direction given in this entry is the direction towards which current is flowing.
- (8) Wind waves and waves reporting standards:

<i>Observation</i>	<i>Speed</i>	<i>Direction</i>
No observation	Missing	Missing
Calm	0	0
Normal observation	> 0	1°–360°
Speed only	> 0	Missing
Direction only	Missing	1°–360°
"Light and variable"	> 0	0

- (9) The maximum deployment depth of deep-ocean tsunameters such as the PMEL Deep-Ocean Assessment and Reporting of Tsunamis (DART II) is about 6 000 m.
- (10) Must be preceded by 0 08 090, possibly with intervening operators. The value is 10^x multiplied by the encoded value, where x is the value associated with the preceding 0 08 090 descriptor. The encoded value is the actual value multiplied by 10^{-x} .
- (11) 0 22 186 is introduced to express the direction of "any wave", as opposed to the direction of "dominant wave" (0 22 076), "mean direction"
- (12) 0 22 187 is introduced to express the directional spread of "any wave", as opposed to the directional spread of "dominant wave" (0 22 077).
- (13) 0 22 179 is similar to 0 22 190, but with a negative reference value.

Class 23 – BUFR/CREX Dispersal and transport

Class 23								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 23 001	Accident early notification – article applicable	Code table	0	0	3	Code table	0	1
0 23 002	Activity or facility involved in incident	Code table	0	0	5	Code table	0	2
0 23 003	Type of release	Code table	0	0	3	Code table	0	1
0 23 004	Countermeasures taken near border	Code table	0	0	3	Code table	0	1
0 23 005	Cause of incident	Code table	0	0	2	Code table	0	1
0 23 006	Incident situation	Code table	0	0	3	Code table	0	1
0 23 007	Characteristics of release	Code table	0	0	3	Code table	0	1
0 23 008	State of current release	Code table	0	0	2	Code table	0	1
0 23 009	State of expected release	Code table	0	0	2	Code table	0	1
0 23 016	Possibility of significant chemical toxic health effect	Code table	0	0	2	Code table	0	1
0 23 017	Flow discharge of major recipient	m ³ s ⁻¹	6	0	20	m ³ s ⁻¹	6	7
0 23 018	Release behaviour over time	Code table	0	0	3	Code table	0	1
0 23 019	Actual release height	m	0	-15000	17	m	0	6
0 23 021	Effective release height	m	0	-15000	17	m	0	6
0 23 022	Distance of release point or site of incident	m	0	0	24	m	0	8
0 23 023	Main transport speed in the atmosphere	m s ⁻¹	1	0	12	m s ⁻¹	1	4
0 23 024	Main transport speed in water	m s ⁻¹	2	0	13	m s ⁻¹	2	4
0 23 025	Main transport speed in ground water	m s ⁻¹	2	0	13	m s ⁻¹	2	4
0 23 027	Main transport direction in the atmosphere	degree true	0	0	9	degree true	0	3
0 23 028	Main transport direction in water	degree true	0	0	9	degree true	0	3

FM 94 BUFR, FM 95 CREX

Class 23								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 23 029	Main transport direction in ground water	degree true	0	0	9	degree true	0	3
0 23 031	Possibility that plume will encounter precipitation in State in which incident occurred	Code table	0	0	2	Code table	0	1
0 23 032	Plume will encounter change in wind direction and/or speed flag	Code table	0	0	2	Code table	0	1
0 23 040	Flow discharge – river	m ³ s ⁻¹	1	0	22	m ³ s ⁻¹	1	7
0 23 041	Flow discharge – well	m ³ s ⁻¹	3	0	16	m ³ s ⁻¹	3	5

Class 24 – BUFR/CREX Radiological elements

Class 24								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 24 001	Estimate of amount of radioactivity released up to specified time	Bq	-11	0	28	Bq	-11	9
0 24 002	Estimated maximum potential release	Bq	-11	0	28	Bq	-11	9
0 24 003	Composition of release	Code table	0	0	5	Code table	0	2
0 24 004	Element name	CCITT IA5	0	0	16	Character	0	2
0 24 005	Isotope mass	Numeric	0	0	9	Numeric	0	3
0 24 011	Dose	mSv	2	0	32	mSv	2	10
0 24 012	Trajectory dose (defined location and expected time of arrival)	mSv	2	0	32	mSv	2	10
0 24 013	Gamma dose in air along the main transport path (defined location and time period)	mSv	2	0	32	mSv	2	10
0 24 014	Gamma radiation dose rate (see Note 2)	nSv h ⁻¹	1	0	14	nSv h ⁻¹	1	4
0 24 021	Air concentration (of named isotope type including gross beta)	Bq m ⁻³	2	0	32	Bq m ⁻³	2	10
0 24 022	Concentration in precipitation (of named isotope type)	Bq l ⁻¹	2	0	32	Bq l ⁻¹	2	10
0 24 023	Pulse rate of beta radiation	s ⁻¹	1	0	14	s ⁻¹	1	4
0 24 024	Pulse rate of gamma radiation	s ⁻¹	1	0	14	s ⁻¹	1	4

Notes:

- (1) Useful ranges used above:
10¹¹ Bq to 10¹⁹ Bq for releases;
10⁻² Bq to 10⁷ Bq and 10⁻² mSv to 10⁷ mSv for concentration and doses.
 - (2) Gamma radiation dose rate 0 24 014 is intended to be used for reporting of this element under normal conditions, nuclear accidents excluded.
-

Provisional Copy
2023

Class 25 – BUFR/CREX Processing information

Class 25								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 25 001	Range-gate length	m	-1	0	6	m	-1	2
0 25 002	Number of gates averaged	Numeric	0	0	4	Numeric	0	2
0 25 003	Number of integrated pulses	Numeric	0	0	8	Numeric	0	3
0 25 004	Echo processing	Code table	0	0	2	Code table	0	1
0 25 005	Echo integration	Code table	0	0	2	Code table	0	1
0 25 006	Z to R conversion	Code table	0	0	3	Code table	0	1
0 25 007	Z to R conversion factor	Numeric	0	0	12	Numeric	0	4
0 25 008	Z to R conversion exponent	Numeric	2	0	9	Numeric	2	3
0 25 009	Calibration method (see Note 3)	Flag table	0	0	4	Flag table	0	2
0 25 010	Clutter treatment	Code table	0	0	4	Code table	0	2
0 25 011	Ground occultation correction (screening)	Code table	0	0	2	Code table	0	1
0 25 012	Range attenuation correction	Code table	0	0	2	Code table	0	1
0 25 013	Bright-band correction	Flag table	0	0	2	Flag table	0	1
0 25 014	Azimuth clutter cut-off (see Note 1)	Numeric	0	0	12	Numeric	0	4
0 25 015	Radome attenuation correction	Flag table	0	0	2	Flag table	0	1
0 25 016	Clear-air attenuation correction	dB m ⁻¹	5	0	6	dB m ⁻¹	5	2
0 25 017	Precipitation attenuation correction	Flag table	0	0	2	Flag table	0	1
0 25 018	A to Z law for attenuation factor	Numeric	7	0	6	Numeric	7	2
0 25 019	A to Z law for attenuation exponent	Numeric	2	0	7	Numeric	2	3
0 25 020	Mean speed estimation	Code table	0	0	2	Code table	0	1
0 25 021	Wind computation enhancement	Flag table	0	0	8	Flag table	0	3
0 25 022	GHRSSST rejection flag	Flag table	0	0	9	Flag table	0	3
0 25 023	GHRSSST confidence flag	Flag table	0	0	9	Flag table	0	3

FM 94 BUFR, FM 95 CREX

Class 25								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 25 024	GHRST data quality	Code table	0	0	4	Code table	0	2
0 25 025	Battery voltage	V	1	0	9	V	1	3
0 25 026	Battery voltage (large range)	V	1	0	12	V	1	4
0 25 028	Operator or manufacturer defined parameter	Numeric	1	-16384	15	Numeric	1	5
0 25 029	Calibration method (see Note 3)	Flag table	0	0	6	Flag table	0	2
0 25 030	Running mean sea-surface temperature usage	Code table	0	0	2	Code table	0	1
0 25 031	NWP-generated vertical profile thinning method	Code table	0	0	3	Code table	0	1
0 25 032	Wind profiler mode information (see Note 2)	Code table	0	0	2	Code table	0	1
0 25 033	Wind profiler submode information (see Note 2)	Code table	0	0	2	Code table	0	1
0 25 034	Wind profiler quality control test results (see Note 2)	Flag table	0	0	4	Flag table	0	2
0 25 035	Decision method for polarity (see Note 5)	Code table	0	0	3	Code table	0	1
0 25 036	Atmospherics location method	Code table	0	0	4	Code table	0	2
0 25 037	SST bias	K	2	-127	8	K	2	3
0 25 038	Difference between SST and analysis	K	1	-127	8	K	1	3
0 25 040	CO ₂ wind product derivation	Code table	0	0	4	Code table	0	2
0 25 041	Moving platform direction reporting method	Code table	0	0	2	Code table	0	1
0 25 042	Moving platform speed reporting method	Code table	0	0	2	Code table	0	1
0 25 043	Wave sampling interval (time)	s	4	0	15	s	4	5
0 25 044	Wave sampling interval (space)	m	2	0	14	m	2	5
0 25 045	HIRS channel combination	Flag table	0	0	21	Flag table	0	7

FM 94 BUFR, FM 95 CREX

Class 25								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 25 046	MSU channel combination	Flag table	0	0	5	Flag table	0	2
0 25 047	SSU channel combination	Flag table	0	0	4	Flag table	0	2
0 25 048	AMSU-A channel combination	Flag table	0	0	16	Flag table	0	6
0 25 049	AMSU-B channel combination	Flag table	0	0	6	Flag table	0	2
0 25 050	Principal component score	Numeric	4	-131072	18	Numeric	4	6
0 25 051	AVHRR channel combination	Flag table	0	0	7	Flag table	0	3
0 25 052	Log ₁₀ of principal components normalized fit to data	Numeric	4	0	15	Numeric	4	5
0 25 053	Observation quality	Flag table	0	0	12	Flag table	0	4
0 25 054	SSMIS subframe ID number	Numeric	0	0	5	Numeric	0	2
0 25 055	Multiplexer housekeeping	K	2	0	16	K	2	5
<u>0 25 056</u>	<u>Normalized error estimate in backscatter measurement (Kp)</u>	<u>Numeric</u>	<u>4</u>	<u>0</u>	<u>14</u>	<u>Numeric</u>	<u>4</u>	<u>5</u>
0 25 060	Software identification (see Note 2)	Numeric	0	0	14	Numeric	0	5
0 25 061	Software identification and version number	CCITT IA5	0	0	96	Character	0	12
0 25 062	Database identification	Numeric	0	0	14	Numeric	0	5
0 25 063	Central processor or system identifier (see Note 6)	Code table	0	0	8	Code table	0	3
0 25 065	Orientation correction (azimuth)	°	2	-1000	11	°	2	4
0 25 066	Orientation correction (elevation)	°	2	-1000	11	°	2	4
0 25 067	Radiosonde release point pressure correction	Pa	0	-8000	14	Pa	0	4
0 25 068	Number of archive recomputes	Numeric	0	0	7	Numeric	0	3
0 25 069	Flight level pressure corrections	Flag table	0	0	8	Flag table	0	3
0 25 070	Major frame count	Numeric	0	0	4	Numeric	0	2
0 25 071	Frame count	Numeric	0	0	5	Numeric	0	2
0 25 075	Satellite antenna corrections version number	Numeric	0	0	5	Numeric	0	2

FM 94 BUFR, FM 95 CREX

Class 25								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 25 076	Log ₁₀ of (temperature-radiance central wave number) for ATOVS	log (m ⁻¹)	8	0	30	log (m ⁻¹)	8	10
0 25 077	Bandwidth correction coefficient 1	Numeric	5	-100000	18	Numeric	5	7
0 25 078	Bandwidth correction coefficient 2	Numeric	5	0	17	Numeric	5	6
0 25 079	Albedo-radiance solar filtered irradiance for ATOVS	W m ⁻²	4	0	24	W m ⁻²	4	8
0 25 080	Albedo-radiance equivalent filter width for ATOVS	m	10	0	14	m	10	5
0 25 081	Incidence angle	°	3	0	17	°	3	6
0 25 082	Azimuth angle	°	3	0	19	°	3	6
0 25 083	Faraday rotational angle	°	3	0	19	°	3	6
0 25 084	Geometric rotational angle	°	5	0	26	°	5	8
0 25 085	Fraction of clear pixels in HIRS FOV	Numeric	0	0	7	Numeric	0	3
0 25 086	Depth correction indicator	Code table	0	0	2	Code table	0	1
0 25 090	Orbit state flag	Code table	0	0	4	Code table	0	2
0 25 091	Structure constant of the refraction index (C _n ²)	dB	3	-18192	13	dB	3	5
0 25 092	Acoustic propagation velocity	m s ⁻¹	2	28000	14	m s ⁻¹	2	5
0 25 093	RASS computation correction	Flag table	0	0	8	Flag table	0	3
0 25 095	Altimeter state flag	Flag table	0	0	2	Flag table	0	1
0 25 096	Radiometer state flag	Flag table	0	0	5	Flag table	0	2
0 25 097	Three-dimensional error estimate of the navigator orbit	Code table	0	0	4	Code table	0	2
0 25 098	Altimeter data quality flag	Flag table	0	0	9	Flag table	0	3
0 25 099	Altimeter correction quality flag	Flag table	0	0	9	Flag table	0	3
0 25 100	XBT/XCTD fall rate equation coefficient a	Numeric	5	0	20	Numeric	5	6
0 25 101	XBT/XCTD fall rate equation coefficient b	Numeric	5	-500000	21	Numeric	5	6

FM 94 BUFR, FM 95 CREX

Class 25								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 25 102	Number of missing lines excluding data gaps	Numeric	0	0	8	Numeric	0	3
0 25 103	Number of directional bins	Numeric	0	0	8	Numeric	0	3
0 25 104	Number of wavelength bins	Numeric	0	0	8	Numeric	0	3
0 25 105	First directional bin	°	3	0	19	°	3	6
0 25 106	Directional bin step	°	3	0	19	°	3	6
0 25 107	First wavelength bin	m	3	0	29	m	3	9
0 25 108	Last wavelength bin	m	3	0	29	m	3	9
0 25 110	Image processing summary	Flag table	0	0	10	Flag table	0	4
0 25 111	Number of input data gaps	Numeric	0	0	8	Numeric	0	3
0 25 112	Band specific altimeter data quality flag	Flag table	0	0	9	Flag table	0	3
0 25 113	Band specific altimeter correction quality flag	Flag table	0	0	9	Flag table	0	3
0 25 120	RA2-L2-processing flag	Code table	0	0	2	Code table	0	1
0 25 121	RA2-L2-processing quality	%	0	0	7	%	0	3
0 25 122	Hardware configuration for RF	Code table	0	0	2	Code table	0	1
0 25 123	Hardware configuration for HPA	Code table	0	0	2	Code table	0	1
0 25 124	MWR-L2-processing flag	Code table	0	0	2	Code table	0	1
0 25 125	MWR-L2-processing quality	%	0	0	7	%	0	3
0 25 126	Model dry tropospheric correction	m	3	-32768	16	m	3	5
0 25 127	Inverted barometer correction	m	3	-32768	16	m	3	5
0 25 128	Model wet tropospheric correction	m	3	-32768	16	m	3	5
0 25 129	MWR derived wet tropospheric correction	m	3	-32768	16	m	3	5
0 25 130	RA2 ionospheric correction on Ku band	m	3	-32768	16	m	3	5
0 25 131	Ionospheric correction from Doris on Ku band	m	3	-32768	16	m	3	5

FM 94 BUFR, FM 95 CREX

Class 25								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 25 132	Ionospheric correction from model on Ku band	m	3	-32768	16	m	3	5
0 25 133	Sea-state bias correction on Ku band	m	3	-32768	16	m	3	5
0 25 134	RA2 ionospheric correction on S band	m	3	-32768	16	m	3	5
0 25 135	Ionospheric correction from Doris on S band	m	3	-32768	16	m	3	5
0 25 136	Ionospheric correction from model on S band	m	3	-32768	16	m	3	5
0 25 137	Sea-state bias correction on S band	m	3	-32768	16	m	3	5
0 25 138	Average signal-to-noise ratio	Numeric	0	-2048	12	Numeric	0	4
0 25 139	Processing level	Numeric	0	0	5	Numeric	0	4
0 25 140	Start channel	Numeric	0	0	14	Numeric	0	5
0 25 141	End channel	Numeric	0	0	14	Numeric	0	5
0 25 142	Channel scale factor	Numeric	0	0	6	Numeric	0	2
0 25 143	Linear coefficient (see Note 4)	Numeric	6	-5000000	24	Numeric	6	8
0 25 148	Coefficient of variation	Numeric	2	-10000	15	Numeric	2	5
0 25 149	Optimal estimation cost	Numeric	0	0	8	Numeric	0	3
0 25 150	Method of tropical cyclone intensity analysis using satellite data	Code table	0	0	4	Code table	0	2
0 25 160	Ku band net instrumental correction	m	4	-120000	18	m	4	6
0 25 161	C band net instrumental correction	m	4	-120000	18	m	4	6
0 25 162	Sea-state bias correction on C band	m	4	-6000	13	m	4	4
0 25 163	Altimeter ionospheric correction on Ku band	m	3	-32768	16	m	3	5

FM 94 BUFR, FM 95 CREX

Class 25								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 25 164	Radiometer wet tropospheric correction	m	4	−5000	13	m	4	4
0 25 165	Ionospheric correction from model on specific band	m	4	−32768	16	m	4	5
0 25 166	Sea-state bias correction on specific band	m	4	−32768	16	m	4	5
0 25 167	Specific band net instrumental correction	m	4	−120000	18	m	4	6
0 25 170	Sampling interval (time)	s	0	0	10	s	0	4
0 25 171	Sample averaging period	s	0	0	10	s	0	4
0 25 172	Number of samples	Numeric	0	0	10	Numeric	0	4
0 25 174	SMOS information flag	Flag table	0	0	14	Flag table	0	5
0 25 175	Modified residual (see Note 7)	Numeric	2	0	13	Numeric	2	4
0 25 180	LRM per cent	%	2	0	16	%	2	5
0 25 181	L2 processing flag	Code table	0	0	2	Code table	0	1
0 25 182	L1 processing flag	Code table	0	0	2	Code table	0	1
0 25 183	L1 processing quality	%	2	0	14	%	2	5
0 25 184	L2 product status	Code table	0	0	2	Code table	0	1
0 25 185	Encryption method	Code table	0	0	8	Code table	0	3
0 25 186	Encryption key version	CCITT IA5	0	0	96	Character	0	12
0 25 187	Confidence flag	Code table	0	0	4	Code table	0	2
0 25 188	Method for reducing pressure to sea level	Code table	0	0	5	Code table	0	2
0 25 189	Range cut-off wavelength	m	0	1	9	m	0	3
0 25 190	Altimeter echo processing mode	Code table	0	0	8	Code table	0	3
0 25 191	Altimeter tracking mode	Code table	0	0	8	Code table	0	3

Notes:

- (1) 0 25 014 nominal input range 0 – 2300.
 - (2) The actual meaning of this quantity may be obtained from the originator of the data.
 - (3) Descriptor 0 25 009 is deprecated. 0 25 029 should be used instead.
 - (4) Descriptor 0 25 143 is intended for numerical, non-dimensional values to be used as coefficients in statistical or linear processing. Each instance of 0 25 143 should be characterized by using an appropriate significance qualifier, such as 0 08 026.
 - (5) Certain sensors use a current decision above a threshold, others directly measure the voltage deflection.
 - (6) Flash Location Processor or system identity so as to identify where the event location was developed in multi-integrated system. Typically, a value of 1.
 - (7) Modified residual calculated from the loci of the sensors and signal to noise ratios for the flash.
-

Class 26 – BUFR/CREX Non-coordinate location (time)

Class 26								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 26 001	Principal time of daily reading in UTC of maximum temperature	h	1	0	12	h	1	3
0 26 002	Principal time of daily reading in UTC of minimum temperature	h	1	0	12	h	1	3
0 26 003	Time difference (see Note)	min	0	-1440	12	min	0	4
0 26 010	Hours included	Flag table	0	0	26	Flag table	0	9
0 26 020	Duration of precipitation	min	0	0	11	min	0	4
0 26 021	Year	a	0	0	12	a	0	4
0 26 022	Month	mon	0	0	4	mon	0	2
0 26 023	Day	d	0	0	6	d	0	2
0 26 030	Measurement integration time	s	2	0	8	s	2	3

Note: Descriptor 0 26 003 is to be used with 0 08 025 (time difference qualifier).

Class 27 – BUFR/CREX Non-coordinate location (horizontal – 1)

Class 27								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 27 001	Latitude (high accuracy)	°	5	–9000000	25	°	5	7
0 27 002	Latitude (coarse accuracy)	°	2	–9000	15	°	2	4
0 27 003	Alternate latitude (coarse accuracy) (see Note 1)	°	2	–9000	15	°	2	4
0 27 004	Alternate latitude (high accuracy) (see Note 1)	°	5	–9000000	25	°	5	7
0 27 010	Footprint axis 1	m	–1	0	14	m	–1	5
0 27 020	Satellite location counter (see Note 2)	Numeric	0	0	16	Numeric	0	5
0 27 021	Satellite sublocation dimension (see Note 3)	Numeric	0	0	16	Numeric	0	5
0 27 031	In direction of 0 degrees longitude, distance from the Earth's centre (see Notes 4 and 5)	m	2	–1073741824	31	m	2	10
0 27 079	Horizontal width of sampled volume	m	0	0	18	m	0	6
0 27 080	Viewing azimuth angle	degree true	2	0	16	degree true	0	5

Notes:

- (1) The alternate latitude may be used when the computation of the position yields multiple solutions and there is no a priori way to distinguish between them.
- (2) The satellite location counter is calculated as:

$$\text{counter} = \text{superswath No.} \times 1000 + \text{box No.} \times 10 + \text{minibox No.}$$
- (3) The satellite sublocation dimension is calculated as:

$$\text{dimension} = \text{minibox dimension} + \text{box dimension}$$

where: minibox dimension = lines \times 1000 + spots \times 100
 box dimension = lines \times 10 + spots

- (4) The value for descriptor 0 27 031 has been chosen to be suitable for polar orbiting satellites in approximately Sun-synchronous orbits. Geostationary orbits would require greater data widths for distance and slightly less for speed.
- (5) Left-handed x, y and z axes have been chosen for descriptor 0 27 031.

Provisional Copy
2023

Class 28 – BUFR/CREX Non-coordinate location (horizontal – 2)

Class 28								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 28 001	Longitude (high accuracy)	°	5	-18000000	26	°	5	8
0 28 002	Longitude (coarse accuracy)	°	2	-18000	16	°	2	5
0 28 003	Alternate longitude (coarse accuracy) (see Note 1)	°	2	-18000	16	°	2	5
0 28 004	Alternate longitude (high accuracy) (see Note 1)	°	5	-18000000	26	°	5	8
0 28 010	Footprint axis 2	m	-1	0	14	m	-1	5
0 28 031	In direction 90 degrees East, distance from the Earth's centre (see Notes 2 and 3)	m	2	-1073741824	31	m	2	10

- (1) The alternate longitude may be used when the computation of the position yields multiple solutions and there is no a priori way to distinguish between them.
- (2) The value for descriptor 0 28 031 has been chosen to be suitable for polar orbiting satellites in approximately Sun-synchronous orbits. Geostationary orbits would require greater data widths for distance and slightly less for speed.
- (3) Left handed x, y and z axes have been chosen for descriptor 0 28 031.

Class 29 – BUFR/CREX Map data

Class 29								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 29 001	Projection type	Code table	0	0	3	Code table	0	1
0 29 002	Coordinate grid type	Code table	0	0	3	Code table	0	1
0 29 014	Optional list of parameters for an external map projection library	CCITT IA5	0	0	504	Character	0	63

Class 30 – BUFR/CREX Image

Class 30								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 30 001	Pixel value (4 bits)	Numeric	0	0	4	Numeric	0	2
0 30 002	Pixel value (8 bits)	Numeric	0	0	8	Numeric	0	3
0 30 004	Pixel value (16 bits)	Numeric	0	0	16	Numeric	0	5
0 30 010	Number of grid points	Numeric	0	0	13	Numeric	0	4
0 30 021	Number of pixels per row	Numeric	0	0	12	Numeric	0	4
0 30 022	Number of pixels per column	Numeric	0	0	12	Numeric	0	4
0 30 031	Picture type	Code table	0	0	4	Code table	0	2
0 30 032	Combination with other data	Flag table	0	0	16	Flag table	0	6
0 30 033	Number of bins along the radial	Numeric	0	0	12	Numeric	0	4
0 30 034	Number of azimuths	Numeric	0	0	12	Numeric	0	4

Notes:

- (1) Pixel data width can be changed with descriptor 2 01 YYY.
- (2) In order to distinguish unambiguously the cases of missing data and saturated pixels, n-bit image data should be encoded using a data width of n+1. Where such a descriptor is not already available in Class 30, operator descriptor 2 01 YYY should be used to modify the data width of the existing entry as required.

Class 31 – BUFR Data description operator qualifiers

Class 31								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 31 000	Short delayed descriptor replication factor	Numeric	0	0	1	Non-existent in CREX		
0 31 001	Delayed descriptor replication factor	Numeric	0	0	8			
0 31 002	Extended delayed descriptor replication factor	Numeric	0	0	16			
0 31 011	Delayed descriptor and data repetition factor (see Note 1)	Numeric	0	0	8			
0 31 012	Extended delayed descriptor and data repetition factor	Numeric	0	0	16			
0 31 021	Associated field significance	Code table	0	0	6			
0 31 031	Data present indicator (see Notes 2 and 3)	Flag table	0	0	1			

Notes:

- (1) The “delayed descriptor and data repetition factor” is intended for run-length encoding (e.g. scanning an image). It specifies a count N which applies to both descriptor and data, i.e. the value of the single element defined by the following descriptor is repeated N times (at intervals already specified).
- (2) Descriptor 0 31 031, used in conjunction with quality control or statistics operators 2 22 YYY through 2 32 YYY, shall indicate the presence of quality control information when the indicator value is set to zero. It may be used in conjunction with the replication operator 1 01 YYY to construct a table of data present/not present indicators, forming a data present bit-map as defined in Regulation 94.5.5.3. This makes it possible to present quality control information and statistical information for selected data corresponding to element descriptors which precede the 2 22 YYY to 2 32 YYY operators.
- (3) Other applications of the data present indicator may be developed.

Class 33 – BUFR/CREX Quality information

Class 33								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 33 002	Quality information	Code table	0	0	2	Code table	0	1
0 33 003	Quality information	Code table	0	0	3	Code table	0	1
0 33 005	Quality information (AWS data)	Flag table	0	0	30	Flag table	0	10
0 33 006	Internal measurement status information (AWS)	Code table	0	0	3	Code table	0	1
0 33 007	Per cent confidence	%	0	0	7	%	0	3
0 33 015	Data quality check indicator	Code table	0	0	6	Code table	0	2
0 33 020	Quality control indication of following value	Code table	0	0	3	Code table	0	1
0 33 021	Quality of following value	Code table	0	0	2	Code table	0	1
0 33 022	Quality of buoy satellite transmission	Code table	0	0	2	Code table	0	1
0 33 023	Quality of buoy location	Code table	0	0	2	Code table	0	1
0 33 024	Station elevation quality mark (for mobile stations)	Code table	0	0	4	Code table	0	2
0 33 025	ACARS interpolated values indicator	Code table	0	0	3	Code table	0	1
0 33 026	Moisture quality	Code table	0	0	6	Code table	0	2
0 33 027	Location quality class (range of radius of 66 % confidence)	Code table	0	0	3	Code table	0	1
0 33 028	Snapshot overall quality	Code table	0	0	3	Code table	0	1
0 33 030	Scan line status flags for ATOVS	Flag table	0	0	24	Flag table	0	8
0 33 031	Scan line quality flags for ATOVS	Flag table	0	0	24	Flag table	0	8
0 33 032	Channel quality flags for ATOVS	Flag table	0	0	24	Flag table	0	8
0 33 033	Field of view quality flags for ATOVS	Flag table	0	0	24	Flag table	0	8
0 33 035	Manual/automatic quality control	Code table	0	0	4	Code table	0	2
0 33 036	Nominal confidence threshold	%	0	0	7	%	0	3

FM 94 BUFR, FM 95 CREX

Class 33								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 33 037	Wind correlation error	Flag table	0	0	20	Flag table	0	7
0 33 038	Quality flags for ground-based GNSS data	Flag table	0	0	10	Flag table	0	4
0 33 039	Quality flags for radio occultation data	Flag table	0	0	16	Flag table	0	6
0 33 040	Confidence interval	%	0	0	7	%	0	3
0 33 041	Attribute of following value	Code table	0	0	2	Code table	0	1
0 33 042	Type of limit represented by following value	Code table	0	0	3	Code table	0	1
0 33 043	AST confidence	Flag table	0	0	8	Flag table	0	3
0 33 044	ASAR quality information	Flag table	0	0	15	Flag table	0	5
0 33 045	Probability of following event (see Notes 1 and 3)	%	0	0	7	%	0	3
0 33 046	Conditional probability of following event with respect to specified conditioning event (see Notes 1, 2 and 3)	%	0	0	7	%	0	3
0 33 047	Measurement confidence data	Flag table	0	0	31	Flag table	0	11
0 33 048	Confidence measure of SAR inversion	Code table	0	0	2	Code table	0	1
0 33 049	Confidence measure of wind retrieval	Code table	0	0	2	Code table	0	1
0 33 050	Global GTSP quality flag	Code table	0	0	4	Code table	0	2
0 33 052	S band ocean retracking quality	Flag table	0	0	21	Flag table	0	7
0 33 053	Ku band ocean retracking quality	Flag table	0	0	21	Flag table	0	7
0 33 055	Wind vector quality flag	Flag table	0	0	24	Flag table	0	8
0 33 056	Sigma-0 quality flag	Flag table	0	0	24	Flag table	0	8
0 33 060	GqisFlagQual – individual IASI- System quality flag	Code table	0	0	2	Code table	0	1

FM 94 BUFR, FM 95 CREX

Class 33								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 33 061	GqisQualIndex – indicator for instrument noise performance (contributions from spectral and radiometric calibration)	%	0	0	7	%	0	3
0 33 062	GqisQualIndexLoc – indicator for geometric quality index	%	0	0	7	%	0	3
0 33 063	GqisQualIndexRad – indicator for instrument noise performance (contributions from radiometric calibration)	%	0	0	7	%	0	3
0 33 064	GqisQualIndexSpect – indicator for instrument noise performance (contributions from spectral calibration)	%	0	0	7	%	0	3
0 33 065	GqisSysTecSondQual – output of system TEC (Technical Expertise Centre) quality function	Numeric	0	0	24	Numeric	0	8
0 33 066	AMV quality flag	Flag table	0	0	24	Flag table	0	8
0 33 070	Total ozone quality	Code table	0	0	4	Code table	0	2
0 33 071	Profile ozone quality	Code table	0	0	4	Code table	0	2
0 33 072	Ozone error	Code table	0	0	5	Code table	0	2
0 33 075	Scan-level quality flags	Flag table	0	0	13	Flag table	0	5
0 33 076	Calibration quality flags	Flag table	0	0	9	Flag table	0	3
0 33 077	Field-of-view quality flags	Flag table	0	0	19	Flag table	0	7
0 33 078	Geolocation quality	Code table	0	0	4	Code table	0	2
0 33 079	Granule level quality flags	Flag table	0	0	16	Flag table	0	6
0 33 080	Scan level quality flags	Flag table	0	0	20	Flag table	0	7
0 33 081	Channel data quality flags	Flag table	0	0	12	Flag table	0	4
0 33 082	Geolocation quality flags	Flag table	0	0	16	Flag table	0	6
0 33 083	Radiance data quality flags	Flag table	0	0	16	Flag table	0	6

FM 94 BUFR, FM 95 CREX

Class 33								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
0 33 075	Scan-level quality flags	Flag table	0	0	13	Flag table	0	5
0 33 076	Calibration quality flags	Flag table	0	0	9	Flag table	0	3
0 33 077	Field-of-view quality flags	Flag table	0	0	19	Flag table	0	7
0 33 078	Geolocation quality	Code table	0	0	4	Code table	0	2
0 33 079	Granule level quality flags	Flag table	0	0	16	Flag table	0	6
0 33 080	Scan level quality flags	Flag table	0	0	20	Flag table	0	7
0 33 081	Channel data quality flags	Flag table	0	0	12	Flag table	0	4
0 33 082	Geolocation quality flags	Flag table	0	0	16	Flag table	0	6
0 33 083	Radiance data quality flags	Flag table	0	0	16	Flag table	0	6
0 33 084	Pixel level quality flags	Flag table	0	0	16	Flag table	0	6
0 33 085	Aerosol optical thickness quality flags	Flag table	0	0	18	Flag table	0	6
0 33 086	Quality of pixel level retrieval	Code table	0	0	3	Code table	0	1
0 33 087	Extent of satellite within South Atlantic anomaly (based on climatological data)	Code table	0	0	4	Code table	0	1
0 33 088	Ozone total column quality flag	Flag table	0	0	18	Flag table	0	6
0 33 089	Noise equivalent delta temperature (NEdT) quality indicators for warm target calibration	K	2	0	12	K	2	4
0 33 090	NEdT quality indicators for cold target calibration	K	2	0	12	K	2	4
0 33 091	NEdT quality indicators for overall calibration	K	2	0	12	K	2	4
0 33 092	Band-specific ocean quality flag	Flag table	0	0	9	Flag table	0	3
0 33 093	Extended quality flags for ground- based GNSS data	Flag table	0	0	31	Flag table	0	31
0 33 094	<u>Calibration quality control flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>24</u>	<u>Flag table</u>	<u>0</u>	<u>24</u>
0 33 095	<u>MWI temperatures flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>8</u>	<u>Flag table</u>	<u>0</u>	<u>3</u>

FM 94 BUFR, FM 95 CREX

Class 33								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACT ERS)
<u>0 33 096</u>	<u>MWI calibration flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 097</u>	<u>MWI scan quality flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 098</u>	<u>MWI data quality flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>9</u>	<u>Flag table</u>	<u>0</u>	<u>3</u>
<u>0 33 099</u>	<u>MWI navigation status flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 100</u>	<u>ICI temperatures flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>8</u>	<u>Flag table</u>	<u>0</u>	<u>3</u>
<u>0 33 101</u>	<u>ICI calibration flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 102</u>	<u>ICI scan quality flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 103</u>	<u>ICI data quality flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>9</u>	<u>Flag table</u>	<u>0</u>	<u>3</u>
<u>0 33 104</u>	<u>ICI navigation status flag</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 105</u>	<u>ICI processing flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 106</u>	<u>MWI processing flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 107</u>	<u>MWS scan line processing flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 108</u>	<u>MWS navigation status flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 109</u>	<u>MWS overall quality flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 110</u>	<u>MWS channel processing flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>9</u>	<u>Flag table</u>	<u>0</u>	<u>3</u>
<u>0 33 111</u>	<u>SCA quality flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>32</u>	<u>Flag table</u>	<u>0</u>	<u>11</u>
<u>0 33 112</u>	<u>Faraday rotation angle (one way)</u>	<u>deg</u>	<u>2</u>	<u>-18000</u>	<u>16</u>	<u>deg</u>	<u>2</u>	<u>6</u>
<u>0 33 113</u>	<u>IASI-NG general quality flags</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>16</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 114</u>	<u>Out of bounds check</u>	<u>Flag table</u>	<u>0</u>	<u>0</u>	<u>17</u>	<u>Flag table</u>	<u>0</u>	<u>6</u>
<u>0 33 115</u>	<u>Aerosol optical depth quality information</u>	<u>Code table</u>	<u>0</u>	<u>0</u>	<u>5</u>	<u>Code table</u>	<u>0</u>	<u>2</u>

Notes:

- (1) When using descriptor 0 33 045 or 0 33 046, operator 2 41 000 shall be used in order to define the following event to which the reported probability value applies.
- (2) When using descriptor 0 33 046, operator 2 42 000 shall precede the occurrence of this descriptor in order to define the event upon which the reported probability value is conditioned.

- (3) When defining an event for use with descriptor 0 33 045 or 0 33 046, descriptor 0 33 042 may be employed in order to indicate that the following value is actually a bound for a range of values.

Provisional Copy
2023

Class 35 – BUFR/CREX Data monitoring information

Class 35								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 35 000	FM and regional code number	Code table	0	0	10	Code table	0	3
0 35 001	Time frame for monitoring	Code table	0	0	3	Code table	0	1
0 35 011	Number of reports actually received	Numeric	0	0	14	Numeric	0	4
0 35 021	Bulletin being monitored (TTAAii)	CCITT IA5	0	0	48	Character	0	6
0 35 022	Bulletin being monitored (YGGGgg)	CCITT IA5	0	0	48	Character	0	6
0 35 023	Bulletin being monitored (CCCC)	CCITT IA5	0	0	32	Character	0	4
0 35 024	Bulletin being monitored (BBB)	CCITT IA5	0	0	24	Character	0	3
0 35 030	Discrepancies in the availability of expected data	Code table	0	0	4	Code table	0	1
0 35 031	Qualifier on monitoring results	Code table	0	0	7	Code table	0	2
0 35 032	Cause of missing data	Code table	0	0	4	Code table	0	1
0 35 033	Observation and collection deficiencies	Code table	0	0	7	Code table	0	2
0 35 034	Statistical trends for availability of data (during the survey period(s))	Code table	0	0	3	Code table	0	1
0 35 035	Reason for termination	Code table	0	0	5	Code table	0	2

Class 40 – BUFR/CREX Satellite data

Class 40								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 40 001	Surface soil moisture (ms)	%	1	0	10	%	1	4
0 40 002	Estimated error in surface soil moisture	%	1	0	10	%	1	4
0 40 003	Mean surface soil moisture	Numeric	3	0	10	Numeric	3	4
0 40 004	Rain fall detection	Numeric	3	0	10	Numeric	3	4
0 40 005	Soil moisture correction flag	Flag table	0	0	8	Flag table	0	3
0 40 006	Soil moisture processing flag	Flag table	0	0	16	Flag table	0	6
0 40 007	Soil moisture quality	%	1	0	10	%	1	4
0 40 008	Frozen land surface fraction	%	1	0	10	%	1	4
0 40 009	Inundation and wetland fraction	%	1	0	10	%	1	4
0 40 010	Topographic complexity	%	1	0	10	%	1	4
0 40 011	Interpolation flag	Flag table	0	0	8	Flag table	0	3
0 40 012	Radiometer data quality flag	Flag table	0	0	8	Flag table	0	3
0 40 013	Radiometer brightness temperature interpretation flag	Code table	0	0	3	Code table	0	1
0 40 014	High-frequency fluctuations of the sea-surface topography correction	m	4	−3000	13	m	4	4
0 40 015	Normalized differential vegetation index (NDVI)	Numeric	2	−100	8	Numeric	2	3
0 40 016	Residual RMS in band	Numeric	3	0	14	Numeric	3	5
0 40 017	Non-normalized principal component score	Numeric	0	−1073741824	31	Numeric	0	10
0 40 018	GIacAvgImagIIS – average of imager measurements	W m ^{−2} sr ^{−1} m	6	0	24	W m ^{−2} sr ^{−1} m	6	8
0 40 019	GIacVarImagIIS – variance of imager measurements	W m ^{−2} sr ^{−1} m	6	0	24	W m ^{−2} sr ^{−1} m	6	8

FM 94 BUFR, FM 95 CREX

Class 40								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 40 020	GqisFlagQualDetailed – quality flag for the system	Flag table	0	0	17	Flag table	0	6
0 40 021	Fraction of weighted AVHRR pixel in IASI FOV covered with snow/ice	%	0	0	7	%	0	3
0 40 022	Number of missing, bad or failed AVHRR pixels	Numeric	0	0	7	Numeric	0	3
0 40 023	Auxiliary altimeter state flags	Flag table	0	0	5	Flag table	0	2
0 40 024	Meteorological map availability	Code table	0	0	3	Code table	0	1
0 40 025	Interpolation flag for mean diurnal tide	Code table	0	0	2	Code table	0	1
0 40 026	Score quantization factor	Numeric	2	0	16	Numeric	2	5
0 40 027	Sun glint angle	°	2	-18000	16	°	2	5
0 40 028	GMI quality flag	Code table	0	0	4	Code table	0	2
0 40 029	Horizontal observation integration length	m	0	0	26	m	0	8
0 40 030	Horizontal line of sight wind	m s ⁻¹	2	-32767	16	m s ⁻¹	2	5
0 40 031	Error estimate of horizontal line of sight wind	m s ⁻¹	2	0	15	m s ⁻¹	2	5
0 40 032	Derivative wind to pressure	m s ⁻¹ Pa ⁻¹	3	-100000	18	m s ⁻¹ Pa ⁻¹	3	6
0 40 033	Derivative wind to temperature	m s ⁻¹ K ⁻¹	3	-100000	18	m s ⁻¹ K ⁻¹	3	6
0 40 034	Derivative wind to backscatter ratio	m s ⁻¹	3	-200000	19	m s ⁻¹	3	6
0 40 035	Satellite range	m	0	380000	18	m	0	6
0 40 036	Lidar L2b classification type	Code table	0	0	4	Code table	0	2
0 40 037	Backscatter ratio	Numeric	3	500	20	Numeric	3	7
0 40 038	Cloud particle size	m	7	0	28	m	7	6
0 40 039	Single look complex image intensity	Numeric	0	-25	5	Numeric	0	3
0 40 040	Single look complex image skewness	Numeric	2	1	13	Numeric	0	4

FM 94 BUFR, FM 95 CREX

Class 40								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 40 041	Single look complex image kurtosis	Numeric	2	1	13	Numeric	0	4
0 40 042	Single look complex image variance	Numeric	2	1	13	Numeric	0	4
0 40 043	Satellite manoeuvre indicator	Code table	0	0	3	Code table	0	1
0 40 044	Dust index	Numeric	1	0	8	Numeric	1	3
0 40 045	Cloud formation and height assignment	Flag table	0	0	5	Flag table	0	2
0 40 046	Cloudiness summary	Code table	0	0	3	Code table	0	1
0 40 047	Validation flag for IASI or IASI-NG level 1 product	Code table	0	0	3	Code table	0	1
0 40 048	Validation flag of AMSU-A level 1 data flow	Code table	0	0	3	Code table	0	1
0 40 049	Cloud tests executed and results	Flag table	0	0	16	Flag table	0	5
0 40 050	Retrieval initialisation	Flag table	0	0	8	Flag table	0	3
0 40 051	Convergence of the iterative retrieval	Code table	0	0	3	Code table	0	1
0 40 052	Indication of super-adiabatic and super-saturation in final retrieval	Flag table	0	0	8	Flag table	0	3
0 40 053	Number of iterations used for retrieval	Numeric	0	0	8	Numeric	0	3
0 40 054	Potential processing and inputs errors	Flag table	0	0	13	Flag table	0	4
0 40 055	Diagnostics on the retrieval	Flag table	0	0	21	Flag table	0	7
0 40 056	General retrieval quality	Code table	0	0	3	Code table	0	1
0 40 057	IASI level 2 retrieval flags	Flag table	0	0	31	Flag table	0	10
0 40 058	Number of vectors describing the characterization matrices	Numeric	0	0	8	Numeric	0	3

FM 94 BUFR, FM 95 CREX

Class 40								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 40 059	Number of layers actually retrieved	Numeric	0	0	8	Numeric	0	3
0 40 060	Number of profiles retrieved in scanline	Numeric	0	0	8	Numeric	0	3
0 40 061	Air partial columns on each retrieved layer	mol cm ⁻²	3	0	16	mol cm ⁻²	3	5
0 40 062	A priori partial columns on each retrieved layer	mol cm ⁻²	10	0	16	mol cm ⁻²	10	5
0 40 063	Scaling vector multiplying the a priori vector in order to define the retrieved vector	Numeric	5	0	26	Numeric	5	8
0 40 064	Main eigenvalues of the sensitivity matrix	Numeric	6	0	31	Numeric	6	10
0 40 065	Main eigenvectors of the sensitivity matrix	Numeric	6	-1000000000	31	Numeric	6	10
0 40 066	Quality indicator for atmospheric water vapour	Numeric	1	0	8	Numeric	1	3
0 40 067	Quality indicator for atmospheric temperature	Numeric	1	0	8	Numeric	1	3
0 40 068	General retrieval quality flag for SO ₂	Code table	0	0	4	Code table	0	2
0 40 069	PWLR estimated retrieval error for surface air temperature (see Note)	K	4	-1000000	21	K	4	7
0 40 070	PWLR estimated retrieval error of surface dew point	K	4	-1000000	21	K	4	7
0 40 071	Retrieval error covariance matrix for ozone in principal component domain	Numeric	4	-1000000	21	Numeric	4	7

FM 94 BUFR, FM 95 CREX

Class 40								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F X Y								
0 40 072	PWLR estimated retrieval quality indicator of atmospheric ozone	Numeric	1	0	8	Numeric	1	3
0 40 073	PWLR estimated retrieval error of surface skin temperature	K	1	0	8	K	1	3
0 40 074	General interferometry quality flags	Flag table	0	0	16			

Note: Piece-wise linear regression cube is a first-guess optimal estimation method.

Class 41 – BUFR/CREX Oceanographic/biogeochemical parameters

Class 41								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 41 001	pCO ₂	Pa	3	0	18	Pa	3	6
0 41 002	Fluorescence	kg l ⁻¹	12	0	16	kg l ⁻¹	12	5
0 41 003	Dissolved nitrates	μmol kg ⁻¹	3	0	17	μmol kg ⁻¹	3	5
0 41 005	Turbidity	NTU	2	0	12	NTU	2	4

Class 42 – BUFR/CREX Oceanographic elements

Class 42								
TABLE REFERENCE	ELEMENT NAME	BUFR				CREX		
		UNIT	SCALE	REFERENCE VALUE	DATA WIDTH (BITS)	UNIT	SCALE	DATA WIDTH (CHARACTERS)
F* X Y								
0 42 001	Dominant swell wave direction of spectral partition	°	0	0	9	°	0	3
0 42 002	Significant swell wave height of spectral partition	m	1	0	9	m	1	3
0 42 003	Dominant swell wavelength of spectral partition	m	2	100	17	m	2	6
0 42 004	Confidence of inversion for each partition of swell wave spectra	Code table	0	0	4	Code table	0	2
0 42 005	Ambiguity removal factor for swell wave partition	Numeric	5	-100000	18	Numeric	5	6
0 42 006	Wave age	Numeric	2	1	8	Numeric	2	3
0 42 007	Shortest ocean wavelength on spectral resolution	m	2	0	16	m	2	5
0 42 008	Nonlinear inverse spectral width	m	2	0	16	m	2	5
0 42 009	Bin partition reference	Numeric	0	0	8	Numeric	0	3
0 42 010	Partition number	Numeric	0	1	4	Numeric	0	2
0 42 011	a1 coefficient of the directional Fourier series	Numeric	4	-20000	15	Numeric	4	6
0 42 012	b1 coefficient of the directional Fourier series	Numeric	4	-20000	15	Numeric	4	6
0 42 013	a2 coefficient of the directional Fourier series	Numeric	4	-20000	15	Numeric	4	6
0 42 014	b2 coefficient of the directional Fourier series	Numeric	4	-20000	15	Numeric	4	6
0 42 015	Check factor K	Numeric	2	0	12	Numeric	2	4
<u>0 42 016</u>	<u>Sea water potential density referenced to sea surface</u>	<u>kg m⁻³</u>	<u>5</u>	<u>-10000000</u>	<u>24</u>	<u>kg m⁻³</u>	<u>5</u>	<u>9</u>

Provisional Copy
2023

BUFR Table C – Data description operators

BUFR TABLE C – DATA DESCRIPTION OPERATORS			
TABLE REFERENCE	OPERAND	OPERATOR NAME	OPERATION DEFINITION
F X			
2 01	YYY	Change data width	Add (YYY-128) bits to the data width given for each data element in Table B, other than CCITT IA5 (character) data, code or flag tables (see Note 1).
2 02	YYY	Change scale	Add YYY-128 to the scale for each data element in Table B, other than CCITT IA5 (character) data, code or flag tables (see Notes 1 and 2).
2 03	YYY	Change reference values	Subsequent element descriptors define new reference values for corresponding Table B entries. Each new reference value is represented by YYY bits in the Data section. Definition of new reference values is concluded by coding this operator with YYY = 255. Negative reference values shall be represented by a positive integer with the left-most bit (bit 1) set to 1 (see Note 1).
2 04	YYY	Add associated field	Precede each data element with YYY bits of information. This operation associates a data field (e.g. quality control information) of YYY bits with each data element (see Notes 1, 5, 6, 7, and 9).
2 05	YYY	Signify character	YYY characters (CCITT International Alphabet No. 5) are inserted as a data field of YYY x 8 bits in length (see Note 11).
2 06	YYY	Signify data width for the immediately following local descriptor	YYY bits of data are described by the immediately following descriptor (see Note 12).
2 07	YYY	Increase scale, reference value and data width	For Table B elements, which are not CCITT IA5 (character data), code tables, or flag tables: 1. Add YYY to the existing scale factor 2. Multiply the existing reference value by $10^{**}YYY$ 3. Calculate $((10 \times YYY) + 2) \div 3$, disregard any fractional remainder and add the result to the existing bit width (see Notes 1 and 4).
2 08	YYY	Change width of CCITT IA5 field	YYY characters from CCITT International Alphabet No. 5 (representing YYY x 8 bits in length) replace the specified data width given for each CCITT IA5 element in Table B (see Note 1).
2 21	YYY	Data not present	Data values present in Section 4 (Data section) corresponding to the following YYY descriptors shall be limited to data from Classes 01-09, and Class 31 (see Note 15).
2 22	000	Quality information follows	The values of Class 33 elements which follow relate to the data defined by the data present bit-map.
2 23	000	Substituted values operator	The substituted values which follow relate to the data defined by the data present bit-map (see Note 14).

FM 94 BUFR

BUFR TABLE C – DATA DESCRIPTION OPERATORS			
TABLE REFERENCE	OPERAND	OPERATOR NAME	OPERATION DEFINITION
F X			
2 23	255	Substituted values marker operator	This operator shall signify a data item containing a substituted value; the element descriptor for the substituted value is obtained by the application of the data present bit-map associated with the substituted values operator (see Note 14).
2 24	000	First-order statistical values follow	The statistical values which follow relate to the data defined by the data present bit-map (see Note 16).
2 24	255	First-order statistical values marker operator	This operator shall signify a data item containing a first-order statistical value of the type indicated by the preceding 0 08 023 element descriptor; the element descriptor to which the first-order statistic relates is obtained by the application of the data present bit-map associated with the first-order statistical values follow operator; first-order statistical values shall be represented as defined by this element descriptor (see Note 17).
2 25	000	Difference statistical values follow	The statistical values which follow relate to the data defined by the data present bit-map.
2 25	255	Difference statistical values marker operator	This operator shall signify a data item containing a difference statistical value of the type indicated by the preceding 0 08 024 element descriptor; the element descriptor to which the difference statistical value relates is obtained by the application of the data present bit-map associated with the difference statistical values follow operator; difference statistical values shall be represented as defined by this element descriptor, but with a reference value of -2^{*n} and a data width of $(n+1)$, where n is the data width given by the original descriptor. This special reference value allows the statistical difference values to be centred around zero.
2 32	000	Replaced/retained values follow	The replaced/retained values which follow relate to the data defined by the data present bit-map (see Note 13).
2 32	255	Replaced/retained value marker operator	This operator shall signify a data item containing the original of an element which has been replaced by a substituted value. The element descriptor for the retained value is obtained by the application of the data present bit-map associated with the substituted values operator (see Note 13).
2 35	000	Cancel backward data reference	This operator terminates all previously defined back-ward reference and cancels any previously defined data present bit-map; it causes the next data present bit-map to refer to the data descriptors which immediately precede the operator to which it relates.

BUFR TABLE C – DATA DESCRIPTION OPERATORS			
TABLE REFERENCE	OPERAND	OPERATOR NAME	OPERATION DEFINITION
F X			
2 36	000	Define data present bit-map	This operator defines the data present bit-map which follows for possible re-use; only one data present bit-map may be defined between this operator and the cancel use defined data present bit-map operator.
2 37	000	Use defined data present bit-map	This operator causes the defined data present bit-map to be used again.
2 37	255	Cancel use defined data present bit-map	This operator cancels the re-use of the defined data present bit-map.
2 41	000	Define event	This operator denotes the beginning of the definition of an event (see Note 19).
2 41	255	Cancel define event	This operator denotes the conclusion of the event definition that was begun via the previous 2 41 000 operator.
2 42	000	Define conditioning event	This operator denotes the beginning of the definition of a conditioning event (see Note 19).
2 42	255	Cancel define conditioning event	This operator denotes the conclusion of the conditioning event definition that was begun via the previous 2 42 000 operator.
2 43	000	Categorical forecast values follow	The values which follow are categorical forecast values (see Note 20).
2 43	255	Cancel categorical forecast values follow	This operator denotes the conclusion of the definition of categorical forecast values that was begun via the previous 2 43 000 operator.

Notes:

- (1) The operations specified by operator descriptors 2 01, 2 02, 2 03, 2 04, 2 07 and 2 08 remain defined until cancelled or until the end of the data subset.
- (2) If change scale is used, then it may be necessary for the originator of the message to supply an appropriately rescaled reference value and data width.
- (3) Cancellation of the use of the redefined value shall be effected by the inclusion of the appropriate operand with Y set to 0. The value shall then revert to the original Table B value.
- (4) Nesting of operator descriptors must guarantee unambiguous interpretation. In particular, operators defined within a set of replicated descriptors must be cancelled or completed within that set, and the 2 07 operator may neither be nested within any of the 2 01, 2 02, and 2 03 operators, nor vice-versa.
- (5) Nesting of the operator descriptor 2 04 is defined such that:
 - (a) Each new definition adds to the currently defined associated field. The order of the included associated information shall correspond with the order in which the associated fields have been defined.
 - (b) Each cancellation (2 04 000) cancels only the most recently defined addition to the associated field.
- (6) When the descriptor 2 04 YYY is to be used, it shall precede the first of the data descriptors to which it applies.
- (7) The data description operator 2 04 YYY, other than 2 04 000, shall be followed immediately by the descriptor 0 31 021 to indicate the meaning of the associated field.
- (8) In the data stream, the 6 bits described by 0 31 021 shall precede the YYY bits.
- (9) Once an associated field has been established and given meaning, the meaning may be changed by a re-application of descriptor 0 31 021. The associated field needs not to be cancelled in order to change the meaning. Further, if an associated field is cancelled, and then re-established, it must be given a meaning by a proper application of the 0 31 021

descriptor, as described in Notes 5 to 8, i.e. a previous assignment of meaning does not remain in force when the associated field is cancelled.

- (10) Data description operators shall not be applied to Table B, Class 31 entries.
 - (11) The operation 2 05 permits the inclusion of plain language.
 - (12) The operator 2 06 YYY allows for the inclusion of local descriptors in a message, with their associated data, which can then be by-passed by a receiver of the message. It can be applied to element descriptors (F = 0) only.
 - (13) If "replaced/retained" values are indicated, this shall imply that the data element in the original part of the message has been replaced with a (presumably) better value; the original value has been retained in the message following the replaced/retained operator. If multiple replacements for the same data element are to be included, they shall be ordered such that the original datum shall be last, the first replacement shall precede it, the next precede that, etc. Each (set of) replaced/retained data values shall be indicated by the inclusion of the 2 32 000 operator.
 - (14) If "substituted values" are indicated, this shall imply that the data element in the original part of the message is thought to be of poor quality. However, it has been left in the original message as received; an improved value has been placed within the message following the substituted values operator. If multiple substitutions for the same data element are to be included, they shall be ordered such that the first substitution shall be first, the next substitution shall follow it, the next follow that, etc. Thus, the (presumed) "best" value will be found at the end of the collection of substituted values. Each (set of) substituted data values shall be indicated by the inclusion of the 2 23 000 operator.
 - (15) Operator 2 21 YYY allows for the construction of a BUFR message containing only coordinate (Classes 01–09), delayed replication (Class 31) and quality control information. The message could be linked back to the original data-containing message by comparison of the coordinate information in the two messages, or, in a local context, through "database" information in Section 2.
 - (16) First-order statistics have values with a similar range and the same dimensions as the corresponding reported values (e.g. maxima, minima, means).
 - (17) Difference statistics are difference values; they have dimensions the same as the corresponding reported values with respect to units, but assume a range centred on zero (e.g. the difference between reported and analysed values, the difference between reported and forecast values).
 - (18) No operator descriptors are reserved for local use.
 - (19) An event, as defined for use with operators 2 41 000 and 2 42 000, is a set of one or more circumstances described using appropriate Table B descriptors along with their corresponding data values. The grouping of such descriptors together as a single "event" allows them to be collectively assigned as the target of a separate descriptor such as 0 33 045 or 0 33 046. When defining a circumstance within an event, descriptor 0 33 042 may be employed preceding the appropriate Table B descriptor in order to indicate that the corresponding value is actually a bound for a range of values.
 - (20) A categorical forecast value represents a "best guess" from among a set of related, and often mutually exclusive, data values or categories. Operator 2 43 000 may be used to designate one or more values as categorical forecast values, and descriptor 0 33 042 may be employed preceding any such value in order to indicate that that value is actually a bound for a range of values.
-

BUFR Table D – List of common sequences

F	X	CATEGORY OF SEQUENCES
3	00	BUFR table entries sequences
3	01	Location and identification sequences
3	02	Meteorological sequences common to surface data
3	03	Meteorological sequences common to vertical soundings data
3	04	Meteorological sequences common to satellite observations
3	05	Meteorological or hydrological sequences common to hydrological observations
3	06	Meteorological or oceanographic sequences common to oceanographic observations
3	07	Surface report sequences (land)
3	08	Surface report sequences (sea)
3	09	Vertical sounding sequences (conventional data)
3	10	Vertical sounding sequences (satellite data)
3	11	Single level report sequences (conventional data)
3	12	Single level report sequences (satellite data)
3	13	Sequences common to image data
3	14	Reserved
3	15	Oceanographic report sequences
3	16	Synoptic feature sequences
3	18	Radiological report sequences
3	21	Radar report sequences
3	22	Chemical and aerosol sequences
3	40	Additional satellite report sequences

Notes:

- (1) From a conceptual point of view, Table D is *not* necessary:
 - (a) The Data description section can fully and completely describe the data using only element descriptors, operator descriptors and the rules of description;
 - (b) Such a means of defining the data would involve considerable overheads in terms of the length of the Data description section. Table D is a device to reduce these overheads;
 - (c) Each entry within Table D contains a list of descriptors. Each sequence descriptor that references to Table D may be "expanded" by replacing it with the list corresponding to that entry. The process of "expansion" is well defined, provided it results in a set of element descriptors and operator descriptors;
 - (d) Descriptors listed in entries to Table D may themselves refer to Table D, provided no circularity results on repeated expansion;
 - (e) The initial Table D has been limited to lists of descriptors likely to be used frequently. Every attempt has been made not to produce initial tables that are too comprehensive. *Minor differences of reporting practice can be accommodated by not endeavouring to reduce each observation type to a single descriptor.* Indeed, much more flexibility is retained if the Data description section is envisaged as containing three or four descriptors.
- (2) It should be noted that, initially, effort has been concentrated on the requirements for observational data. Extensions to forecast data, time series data, products, etc., follow logically, and can be added at an appropriate future date.
- (3) Category 01 contains common sequences of non-meteorological descriptors; categories 02 to 06 contain common sequences of meteorological descriptors; categories 07 to 21 contain sequences which define reports, or major subsets of reports.
- (4) Underwater soundings are included, with some minor omissions, to illustrate the facility to describe data of slightly different contents.
- (5) Satellite data have been split to maximize the benefits of data compression. Compound combinations may easily be defined using the descriptors available.

- (6) Satellite observation data benefit enormously from being split into fragments (1, 2, 3 . . . 7), then applying data compression to many locations within each fragment. Again, BUFR flexibility enables compound forms to be defined if desired.
 - (7) Categories 48 to 63 are reserved for local use; all other categories are reserved for future development.
 - (8) Entries 192 to 255 within all categories are reserved for local use.
-

Provisional Copy
2023

Category 00 – BUFR table entries sequences

		Category 00	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 00 002	0 00 002	Table A: data category description, line 1	
	0 00 003	Table A: data category description, line 2	
3 00 003		(F, X, Y of descriptor to be added or defined)	
	0 00 010	F descriptor to be added or defined	
	0 00 011	X descriptor to be added or defined	
	0 00 012	Y descriptor to be added or defined	
3 00 004	3 00 003	F, X, Y of descriptor to be added or defined	
	0 00 013	Element name, line 1	
	0 00 014	Element name, line 2	
	0 00 015	Units name	
	0 00 016	Units scale sign	
	0 00 017	Units scale	
	0 00 018	Units reference sign	
	0 00 019	Units reference value	
	0 00 020	Element data width	
3 00 010	3 00 003	F, X, Y of descriptor to be added or defined	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 00 030	Descriptor defining sequence	
3 00 015		(Code table definition)	
	0 00 030	Descriptor defining sequence	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 00 024	Code figure	
3 00 016	0 00 025	Code figure meaning	
		(Flag table definition)	
	0 00 030	Descriptor defining sequence	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 00 026	Bit number	
	0 00 027	Bit number meaning	

Notes:

- (1) These entries include the facility to update the Table A code figure and data description.
- (2) It is better to use different Class 00 descriptors for the defining and defined elements, in the same way as different descriptors correspond to pressure considered as a coordinate and pressure measured at a given point; otherwise special rules would be needed to interpret such message.

FM 94 BUFR

Entries 0 00 010 to 0 00 012 define F, X and Y for Tables B and D; entry 0 00 030 is a descriptor used as data and provides the F, X and Y values defining a sequence for Table D entries.

- (3) It could be argued that, as only additions are possible, only complete lines should be allowed; but it is conceivable that local areas will require changes as well as additions, so it is better and in any case clearer to provide descriptions for all the fields.

Provisional Copy
2023

Category 01 – Location and identification sequences

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 001	0 01 001	(WMO block and station numbers) WMO block number	Ship's call sign
	0 01 002	WMO station number	
3 01 002 (see Note 1)	0 01 003	WMO Region number/geographical area	
	0 01 004	WMO Region sub-area	
	0 01 005	Buoy/platform identifier	
3 01 003		(Ship's call sign and motion)	
	0 01 011	Ship or mobile land station identifier	
	0 01 012	Direction of motion of moving observing platform	
	0 01 013	Speed of motion of moving observing platform	
3 01 004		(Surface station identification)	
	0 01 001	WMO block number	
	0 01 002	WMO station number	
	0 01 015	Station or site name	
	0 02 001	Type of station	
3 01 005		(Originating centre/sub-centre)	
	0 01 035	Originating centre	
	0 01 034	Identification of originating/generating sub-centre	
3 01 011		(Year, month, day)	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
3 01 012		(Hour, minute)	
	0 04 004	Hour	
	0 04 005	Minute	
3 01 013		(Hour, minute, second)	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
3 01 014		(Time period)	
	1 02 002	Replicate 2 descriptors 2 times	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 018	0 01 114	(Encrypted ship's call sign and encryption method) (see Notes 2, and 3 and 4)	
		Encrypted ship or mobile land station identifier (base64 encoding)	
	0 25 185	Encryption method	
	0 25 186	Encryption key version	
3 01 021		(Latitude/longitude (high accuracy))	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
3 01 022		(Latitude/longitude (high accuracy), height of station)	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 001	Height of station	
3 01 023		(Latitude/longitude (coarse accuracy))	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
3 01 024		(Latitude/longitude (coarse accuracy), height of station)	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 07 001	Height of station	
3 01 025		(Latitude/longitude (coarse accuracy), day/time)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 04 003	Day	
	3 01 012	Hour, minute	
3 01 026		(Latitude/longitude (high accuracy), time period (day, hour, minute))	
	3 01 021	Latitude/longitude (high accuracy)	
	0 04 003	Day }	Time period in days
	0 04 003	Day }	
	0 04 004	Hour }	Time period in hours
	0 04 004	Hour }	
	0 04 005	Minute }	Time period in minutes
	0 04 005	Minute }	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 027	0 08 007	(Description of a feature in 3-D or 2-D) Dimensional significance	= 0 Point, = 1 Line, = 2 Area, = 3 Volume
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor (see Note 54)	
	3 01 028	Horizontal section of a feature described as a polygon, circle, line or point	
	0 08 007	Dimensional significance	
3 01 028		(Horizontal section of a feature described as a polygon, circle, line or point)	Set to missing (cancel)
	0 08 040	Flight level significance	
	0 33 042	Type of limit represented by following value	
	0 07 010	Flight level	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor (see Note 65)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 19 007	Effective radius of feature (see Note 76)	
3 01 029	0 08 040	Flight level significance	Set to missing (cancel)
		(Identification)	
	0 01 018	Short station or site name	
	0 02 001	Type of station	
3 01 030	3 01 011	Year, month, day	
		(Identification – with physical location)	
	0 01 018	Short station or site name	
	0 02 001	Type of station	
3 01 031	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 022	Latitude/longitude (coarse accuracy), height of station	
		(Identification and type of station, date/time, location (high accuracy), height of station)	
	3 01 001	WMO block and station numbers	
	0 02 001	Type of station	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 032	3 01 001	(Identification and type of station, date/time, location (coarse accuracy), height of station)	
	0 02 001	WMO block and station numbers	
	3 01 011	Type of station	
	3 01 012	Year, month, day	
	3 01 024	Hour, minute	
3 01 033	0 01 005	Latitude/longitude (coarse accuracy), height of station	
	0 02 001	(Buoy/platform – fixed)	
	3 01 011	Buoy/platform identifier	
	3 01 012	Type of station	
	3 01 021	Year, month, day	
3 01 034	0 01 005	Hour, minute	
	0 02 001	Latitude/longitude (high accuracy)	
	3 01 011	(Buoy/platform – fixed)	
	3 01 012	Buoy/platform identifier	
	3 01 023	Type of station	
3 01 035	0 01 005	Year, month, day	
	0 01 012	Hour, minute	
3 01 035	0 01 013	Latitude/longitude (coarse accuracy)	
	0 02 001	(Buoy/platform – moving) (see Note 8Z)	
	3 01 011	Buoy/platform identifier	
	3 01 012	Direction of motion of moving observing platform	
	3 01 023	Speed of motion of moving observing platform	
3 01 036	0 02 001	Type of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 023	Latitude/longitude (coarse accuracy)	
		(Ship)	
3 01 037	3 01 003	Ship's call sign and motion	
	0 02 001	Type of station	
	0 02 011	Year, month, day	
	0 02 012	Hour, minute	
		Latitude/longitude (coarse accuracy)	
		(Land station for vertical soundings)	
		WMO block and station numbers	
		Radiosonde type	
		Radiosonde computational method	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 037 (continued)	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 022	Latitude/longitude (high accuracy), height of station	
3 01 038		(Land station for vertical soundings)	
	3 01 001	WMO block and station numbers	
	0 02 011	Radiosonde type	
	0 02 012	Radiosonde computational method	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 024	Latitude/longitude (coarse accuracy), height of station	
3 01 039		(Ship for vertical soundings)	
	3 01 003	Ship's call sign and motion	
	0 02 011	Radiosonde type	
	0 02 012	Radiosonde computational method	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 023	Latitude/longitude (coarse accuracy)	
3 01 040		(Ship for vertical soundings)	
	3 01 003	Ship's call sign and motion	
	0 02 011	Radiosonde type	
	0 02 012	Radiosonde computational method	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 024	Latitude/longitude (coarse accuracy), height of station	
3 01 041		(Satellite identifier, instrument, data-processing technique, date/time)	
	0 01 007	Satellite identifier	
	0 02 021	Satellite instrument data used in processing	
	0 02 022	Satellite data-processing technique used	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
3 01 042		(Satellite identifier, instrument, data-processing technique, date/time, location)	
	3 01 041	Satellite identifier, instrument, data-processing technique, date/time	
	3 01 021	Latitude/longitude (high accuracy)	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 043	0 01 007	(Satellite identifier, wind computation method, date/time, location) Satellite identifier	
	0 02 023	Satellite-derived wind computation method	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
3 01 044	0 01 007	(Satellite identifier, humidity computation method, date/time, location) Satellite identifier	
	0 02 024	Integrated mean humidity computational method	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
3 01 045	3 01 011	(Satellite location and velocity) Year, month, day	
	3 01 012	Hour, minute	
	2 01 138	Change data width	16 bits long
	2 02 131	Change scale	Scale: 3
	0 04 006	Second	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	3 04 030	Location of platform	Relative to the Earth's centre
	3 04 031	Speed of platform	Relative to the Earth's centre
3 01 046	0 01 007	(Satellite identifier, direction of motion, sensor, model function, software, resolution) Satellite identifier	
	0 01 012	Direction of motion of moving observing platform	
	0 02 048	Satellite sensor indicator	
	0 21 119	Wind scatterometer geophysical model function	
	0 25 060	Software identification	
	2 02 124	Change scale	
	0 02 026	Cross-track resolution	
	0 02 027	Along-track resolution	
	2 02 000	Change scale	Cancel
	0 05 040	Orbit number	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 047	0 01 007	(ERS product header) Satellite identifier	
	0 25 060	Software identification	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 01 012	Direction of motion of moving observing platform	
	3 01 045	Satellite location and velocity	
	0 02 021	Satellite instrument data used in processing	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 01 138	Change data width	16 bits long
	2 02 131	Change scale	Scale: 3
	0 04 006	Second	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	3 01 023	Latitude/longitude (coarse accuracy)	
3 01 048		(Radar parameters)	
	0 02 104	Antenna polarization	
	0 02 121	Mean frequency	
	0 02 113	Number of azimuth looks	
	0 02 026	Cross-track resolution	
	0 02 027	Along-track resolution	
	0 02 111	Radar incidence angle	
	0 02 140	Satellite radar beam azimuth angle	
	2 02 127	Change scale	Scale: -1
	0 01 013	Speed of motion of moving observing platform	Radar platform velocity
	2 02 126	Change scale	Scale: -2
	0 07 001	Height of station	Radar platform altitude
	2 02 000	Change scale	Cancel
	0 25 010	Clutter treatment	
	0 21 064	Clutter noise estimate	
3 01 049		(Radar beam data)	
	0 02 111	Radar incidence angle	
	0 02 112	Radar look angle	
	0 21 062	Backscatter	
	0 21 063	Radiometric resolution (noise value)	
	0 21 065	Missing packet counter	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 051	0 01 006	(Flight number, navigational system, date/time, location, phase of flight) Aircraft flight number	
	0 02 061	Aircraft navigational system	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 08 004	Phase of aircraft flight	
3 01 055	0 01 005	(Identification and type of station, date/time, location (high accuracy), movement) Buoy/platform identifier	
	0 02 001	Type of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 01 012	Direction of motion of moving observing platform	
	0 01 014	Platform drift speed (high precision)	
3 01 056	0 01 087	(Sequence for platform identification, type, time and location of the observation report) WMO marine observing platform extended identifier	WMO number (extended 7-digit identifier) Call sign (where allocated) Platform name
	0 01 011	Ship or mobile land station identifier	
	0 01 015	Station or site name	
	0 02 008	Type of offshore platform	
	0 02 001	Type of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 07 031	Height of barometer above mean sea level	
		(Universal lightning event) <i>Date/time of lightning event</i>	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 01 152	Change data width	
	2 02 135	Change scale	
3 01 058	0 04 006	Second	Height of station platform above mean sea level
	2 02 000	Change scale	
	2 01 000	Change data width	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 058 (continued)		<i>Horizontal and vertical coordinates of lightning event</i>	
	3 01 021	Latitude/longitude (high accuracy)	
	0 20 111	x-axis error ellipse major component	
	0 20 112	y-axis error ellipse minor component	
	0 20 113	z-axis error ellipse component	
	0 20 114	Angle of x-axis in error ellipse	
	0 20 115	Angle of z-axis in error ellipse	
	0 20 116	Emission height of cloud stroke	
		<i>Emission information</i>	
	0 20 117	Amplitude of lightning strike	
	0 20 118	Lightning detection error	
	0 20 119	Lightning discharge polarity	
	0 25 035	Decision method for polarity	V or A
	0 20 121	Threshold value for polarity decision	
	0 20 122	Threshold value for polarity decision	
	0 20 123	Minimum threshold for detection	
	0 20 124	Lightning stroke or flash	
	0 25 175	Modified residual	
	0 20 023	Other weather phenomena	Cloud to ground or cloud to cloud identification
		<i>Sensor processing</i>	
	0 25 063	Central processor or system identifier	
	2 02 136	Change scale	
	2 01 136	Change data width	
	0 02 121	Mean frequency	Define centre frequency, if used
	2 01 000	Change data width	
	2 02 000	Change scale	
	0 25 061	Software identification and version number	
	0 02 184	Type of lightning detection sensor	
	0 02 189	Capability to discriminate lightning strikes	
	0 25 036	Atmospherics location method	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	Number of sensors contributing
	3 01 059	Identification of sensor site and instrumentation	
		(Identification of sensor site and instrumentation)	
3 01 059	3 01 021	Latitude/longitude (high accuracy)	Sensor
	0 07 030	Height of station ground above mean sea level	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Sensor for lightning

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 062	1 01 000	(Radar location(s))	
	0 31 001	Delayed replication of 1 descriptor	
	3 01 001	Delayed descriptor replication factor	
3 01 065	3 01 001	WMO block and station numbers	
		(ACARS identification)	
	0 01 006	Aircraft flight number (see Note 109)	
	0 01 008	Aircraft registration number or other identification (see Note 109)	
	0 02 001	Type of station	
	0 02 002	Type of instrumentation for wind measurement	
	0 02 005	Precision of temperature observation	
	0 02 062	Type of aircraft data relay system	
	0 02 070	Original specification of latitude/longitude	
3 01 066	0 02 065	ACARS ground-receiving station	
		(ACARS location)	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 07 004	Pressure	
	0 02 064	Aircraft roll angle quality	
3 01 070	0 08 004	Phase of aircraft flight	
		(Ozone instrumentation – Brewer spectrophotometer)	
	0 02 143	Ozone instrument type	
	0 02 142	Ozone instrument serial number/identification	
3 01 071	0 02 144	Light source type for Brewer spectrophotometer	
		(Satellite identifier/Generating resolution)	
	0 01 007	Satellite identifier	
	0 01 031	Identification of originating/generating centre	
	0 02 020	Satellite classification	
	0 02 028	Segment size at nadir in x-direction	
3 01 072	0 02 029	Segment size at nadir in y-direction	
		(Satellite identification)	
	3 01 071	Satellite identifier/Generating resolution	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 074	0 02 143	(Ozone instrumentation – Dobson spectrophotometer)	= 18 Launch time
	0 02 142	Ozone instrument type	
	0 02 145	Ozone instrument serial number/identification	
	0 02 146	Wavelength setting for Dobson instruments	
3 01 075		Source conditions for Dobson instruments	
		(Sounding identification)	
	3 01 001	WMO block and station numbers	
	0 01 015	Station or site name	
	3 01 024	Latitude/longitude (coarse accuracy), height of station	
	0 08 021	Time significance	
3 01 076	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
		(Ozone sounding instrumentation)	
3 01 089	0 02 011	Radiosonde type	
	0 02 143	Ozone instrument type	
	0 02 142	Ozone instrument serial number/identification	
3 01 090		(National station identification)	
	0 01 101	State identifier	
	0 01 102	National station number	
3 01 091		(Surface station identification; time, horizontal and vertical coordinates)	
	3 01 004	Surface station identification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
3 01 091	0 07 031	Height of barometer above mean sea level	
		(Surface station instrumentation)	
	0 02 180	Main present weather detecting system	
	0 02 181	Supplementary present weather sensor	
	0 02 182	Visibility measurement system	
	0 02 183	Cloud detection system	
	0 02 184	Type of lightning detection sensor	
	0 02 179	Type of sky condition algorithm	
	0 02 186	Capability to detect precipitation phenomena	
	0 02 187	Capability to detect other weather phenomena	
3 01 091	0 02 188	Capability to detect obscuration	
	0 02 189	Capability to discriminate lightning strikes	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 092	0 01 011	(Mobile surface station identification, date/time, horizontal and vertical coordinates) Ship or mobile land station identifier	Ship identification
	0 01 003	WMO Region number/geographical area	
	0 02 001	Type of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 07 031	Height of barometer above mean sea level	
	0 33 024	Station elevation quality mark (for mobile stations)	
3 01 093	3 01 036	(Ship identification, movement, date/time, horizontal and vertical coordinates) Ship	Ship identification
	0 07 030	Height of station ground above mean sea level	
	0 07 031	Height of barometer above mean sea level	
3 01 110	3 01 001	(Identification of launch site and instrumentation for wind measurements) WMO block and station numbers	
	0 01 011	Ship or mobile land station identifier	
	0 02 011	Radiosonde type	
	0 02 014	Tracking technique/status of system used	
	0 02 003	Type of measuring equipment used	
3 01 111	3 01 001	(Identification of launch site and instrumentation for P, T, U and wind measurements) WMO block and station numbers	
	0 01 011	Ship or mobile land station identifier	
	0 02 011	Radiosonde type	
	0 02 013	Solar and infrared radiation correction	
	0 02 014	Tracking technique/status of system used	
	0 02 003	Type of measuring equipment used	
3 01 112	0 01 006	(Identification of launch point and instrumentation of dropsonde) Aircraft flight number	
	0 02 011	Radiosonde type	
	0 02 013	Solar and infrared radiation correction	
	0 02 014	Tracking technique/status of system used	
	0 02 003	Type of measuring equipment used	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 113	0 08 021	(Date/time of launch) (see Note 11 10)	
	3 01 011	Time significance	= 18 Launch time
	3 01 013	Year, month, day	Launch time
3 01 114		Hour, minute, second	Launch time
		(Horizontal and vertical coordinates of launch site)	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 07 031	Height of barometer above mean sea level	
	0 07 007	Height	Release of sonde above mean sea level
	0 33 024	Station elevation quality mark (for mobile stations)	
		(Radiosonde abbreviated header and launch information)	
3 01 120	3 01 001	WMO block and station numbers	
	0 01 094	WBAN number	
	0 02 011	Radiosonde type	
	3 01 121	Radiosonde launch point location	
3 01 121		(Radiosonde launch point location)	
	0 08 041	Data significance	= 3 Balloon launch point
	3 01 122	Date/time (to hundredths of second)	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 031	Height of barometer above mean sea level	
3 01 122	0 07 007	Height	Release of radiosonde above mean sea level
		(Date/time (to hundredths of second)) (see Note 11 10)	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 01 135	Change data width	
	2 02 130	Change scale	
	0 04 006	Second	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 123	1 02 002	(Radiosonde full header information)	= 0 Parent site, = 1 Observation site
	0 08 041	Replicate 2 descriptors 2 times Data significance	
	0 01 062	Short ICAO location indicator	
	3 01 001	WMO block and station numbers	
	0 01 094	WBAN number	
	0 02 011	Radiosonde type	
	0 01 018	Short station or site name	
	0 01 095	Observer identification	
	0 25 061	Software identification and version number	
	0 25 068	Number of archive recomputes	
	0 01 082	Radiosonde ascension number	
	0 01 083	Radiosonde release number	
	0 01 081	Radiosonde serial number	
	0 02 067	Radiosonde operating frequency	
	0 02 066	Radiosonde ground receiving system	
	0 02 014	Tracking technique/status of system used	
	0 25 067	Radiosonde release point pressure correction	
	0 25 065	Orientation correction (azimuth)	
	0 25 066	Orientation correction (elevation)	
	0 02 095	Type of pressure sensor	
	0 02 096	Type of temperature sensor	
	0 02 097	Type of humidity sensor	
	0 02 016	Radiosonde configuration	
	0 02 083	Type of balloon shelter	
	0 02 080	Balloon manufacturer	
	0 02 081	Type of balloon	
	0 01 093	Balloon lot number	
	0 02 084	Type of gas used in balloon	
	0 02 085	Amount of gas used in balloon	
	0 02 086	Balloon flight train length	
	0 02 082	Weight of balloon	
	0 08 041	Data significance	
	3 01 011	Year, month, day	
		(ASCAT header information)	= 2 Balloon manufacture date
3 01 125	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub- centre	
	0 25 060	Software identification	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 012	Direction of motion of moving observing platform	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 126	0 01 087	(Sequence for representation of moored buoy identification)	
		WMO marine observing platform extended identifier	
	0 01 015	Station or site name	
	0 02 149	Type of data buoy	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
3 01 128	3 01 021	Latitude/longitude (high accuracy)	
		(Additional information on radiosonde ascent)	
	0 01 081	Radiosonde serial number	
	0 01 082	Radiosonde ascension number	
	0 01 083	Radiosonde release number	
	0 01 095	Observer identification	
	0 02 015	Radiosonde completeness	
	0 02 016	Radiosonde configuration	
	0 02 017	Correction algorithms for humidity measurements	
	0 02 066	Radiosonde ground receiving system	
	0 02 067	Radiosonde operating frequency	
	0 02 080	Balloon manufacturer	
	0 02 081	Type of balloon	
	0 02 082	Weight of balloon	
	0 02 083	Type of balloon shelter	
	0 02 084	Type of gas used in balloon	
	0 02 085	Amount of gas used in balloon	
	0 02 086	Balloon flight train length	
	0 02 095	Type of pressure sensor	
	0 02 096	Type of temperature sensor	
	0 02 097	Type of humidity sensor	
	0 02 103	Radome	
	0 02 191	Geopotential height calculation	
	0 25 061	Software identification and version number	
	0 35 035	Reason for termination	Reason for ascent termination
3 01 129		(Observing satellite and instruments)	
	0 01 007	Satellite identifier	
	0 01 031	Identification of originating/generating centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	

FM 94 BUFR

Category 01			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 01 130	3 01 011	(High precision timestamp) Year, month, day	Add 3 to scale Add 10 to width Cancel Cancel
	3 01 012	Hour, minute	
	2 02 131	Change scale	
	2 01 138	Change data width	
	0 04 006	Second	
	2 01 000	Change data width	
	2 02 000	Change scale	
3 01 131	3 01 021	(Pixel geolocation) Latitude/longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
3 01 132	3 01 150	(Common header sequence) WIGOS identifiers	Sensor
	3 01 001	WMO block and station numbers	
	3 01 021	Latitude/longitude (high accuracy) (see Note 1.2.1)	
	0 07 030	Height of station ground above mean sea level	
	0 08 021	Time significance	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	0 02 006	Upper air remote sensing instrument type	
	0 01 079	Unique identifier for the profile	
	0 01 085	Observing platform manufacturer's mode	
3 01 150	0 01 125	(WIGOS identifier) WIGOS identifier series	= 29 End of scan or time of ending
	0 01 126	WIGOS issuer of identifier	
	0 01 127	WIGOS issue number	
	0 01 128	WIGOS local identifier (character)	

Notes:

- (1) Descriptor 3 01 002 should not be used.
- (2) The ship's call sign or WMO identifier should be reported using descriptor 0 01 011.
- (3) However, if required by shipping companies when voluntary observing ships (VOS) are recruited or if subsequently requested, for ship reports using template 3 08 014 the ship call sign or other identifier can be encrypted in BUFR reports using sequence 3 01 018 according to the following method:
 - The normal call sign (i.e. descriptor 0 01 011) shall be encoded with missing value;
 - The encryption method shall be indicated using the method indicated by 0 25 185;
 - The version of the encryption key that is used shall be indicated by 0 25 186.

~~(4)~~ The encryption keys will be managed by the Joint WMO/IOC Technical Commission for Oceanography and Marine Meteorology Focal Point on Ship Masking.

- (54) This replication factor shall have a value of "1" when a 2-D feature is being described, whereas 3-D features may be described via any one of the following methods:
- (a) Via two or more horizontal sections in successive ascending flight levels. In this case, each section shall be described by an identical number of latitude/longitude points listed in identical order (i.e. where each point x of section n is to be joined via a straight line to point x of section n+1), in order to ensure that the overall shape of the 3-D feature is unambiguously described. In this case, all values reported for 0 33 042 shall be "missing".
 - (b) Via a single horizontal section with an appropriate value reported for 0 33 042, as follows. In all such cases, the corresponding horizontal section description applies throughout the entire region.
 - (i) A value of "0" to indicate a region above (but not including) the reported flight level and with unspecified upper bound.
 - (ii) A value of "1" to indicate a region above (and including) the reported flight level and with unspecified upper bound.
 - (iii) A value of "2" to indicate a region below (but not including) the reported flight level and extending to the surface.
 - (iv) A value of "3" to indicate a region below (and including) the reported flight level and extending to the surface.
 - (c) Via two replications of the same horizontal section at the same reported flight level, in order to indicate a region extending both below and above (and including!) the reported flight level. In this case, the values reported for the two replications of 0 33 042 shall be as follows:
 - (i) Values of "3" and "1", respectively, to indicate a region beginning from below a reported flight level, but continuing through that level upward to some unspecified point above (e.g. TOP ABV FL100).
 - (ii) Values of "1" and "3", respectively, to indicate a region beginning from above a reported flight level, but continuing through that level downward to some unspecified point below (e.g. CIGS BLW FL010).
- (65) This replication factor shall have a value of "1" when a circle or point is being described, and it shall have a value of "2" when a line is being described. A polygon, on the other hand, shall be described via a sequence of three or more contiguous points in accordance with the note to code table 0 08 007.
- (76) The value reported for 0 19 007 shall be "missing" unless the horizontal section being described is a circle.
- (87) Descriptor 3 01 055 should be used instead of 3 01 035 to encode moving buoy/platform information.
- (98) Descriptors from 3 01 041 to 3 01 049 and 3 01 062, 3 01 071 and 3 01 072 should not be used in CREX for transmission.
- (109) As supplied by originating sub-centre ARINC, this value is a pseudo-value rather than the actual value. The relationship between this pseudo-value and the true value is known only by ARINC.
- (1110) Time of launch shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry for seconds shall be set to zero.
- (1211) The latitude and longitude descriptors 0 05 001 and 0 06 001 indicate the position of the instrument and not the measurement itself (which is separately encoded in the associated data sequence).

Category 02 – Meteorological sequences common to surface data

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 001	0 10 004	(Pressure and 3-hour pressure change) Pressure	Station level
	0 10 051	Pressure reduced to mean sea level	
	0 10 061	3-hour pressure change	
	0 10 063	Characteristic of pressure tendency	
3 02 002		(High altitude station)	Station level Pressure level Pressure level
	0 10 004	Pressure	
	0 07 004	Pressure	
	0 10 003	Geopotential	
	0 10 061	3-hour pressure change	
3 02 003	0 10 063	Characteristic of pressure tendency	
		(Wind, temperature, humidity, visibility, weather)	
	0 11 011	Wind direction at 10 m	
	0 11 012	Wind speed at 10 m	
	0 12 004	Air temperature at 2 m	
	0 12 006	Dewpoint temperature at 2 m	
	0 13 003	Relative humidity	
	0 20 001	Horizontal visibility	
	0 20 003	Present weather	
	0 20 004	Past weather (1)	
3 02 004	0 20 005	Past weather (2)	
		(General cloud information)	
	0 20 010	Cloud cover (total)	
	0 08 002	Vertical significance (surface observations)	
	0 20 011	Cloud amount	
	0 20 013	Height of base of cloud	
	0 20 012	Cloud type	
	0 20 012	Cloud type	
3 02 005	0 20 012	Cloud type	
	0 20 012	Cloud type	
	0 20 012	Cloud type	
	0 20 013	Height of base of cloud	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 006	0 10 004	(Pressure and 24-hour pressure change) Pressure	Station level
	0 10 051	Pressure reduced to mean sea level	
	0 10 062	24-hour pressure change	
	0 10 063	Characteristic of pressure tendency	
3 02 011	3 02 001	(Low altitude station) Pressure and 3-hour pressure change	Significant cloud layer
	3 02 003	Wind, temperature, humidity, visibility, weather	
	3 02 004	General cloud information	
3 02 012	3 02 002	(High altitude station) High altitude station	Pressure and pressure change
	3 02 003	Wind, temperature, humidity, visibility, weather	
	3 02 004	General cloud information	Significant cloud layer
3 02 013	3 02 006	(Basic surface report) Pressure and 24-hour pressure change	
	3 02 003	Wind, temperature, humidity, visibility, weather	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 005	Cloud layer	
3 02 021	0 22 001	(Waves) Direction of waves	
	0 22 011	Period of waves	
	0 22 021	Height of waves	
3 02 022	0 22 002	(Wind waves) Direction of wind waves	
	0 22 012	Period of wind waves	
	0 22 022	Height of wind waves	
3 02 023	0 22 003	(Swell waves) Direction of swell waves	
	0 22 013	Period of swell waves	
	0 22 023	Height of swell waves	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 024	3 02 022	(Wind and swell waves) Wind waves	2 systems of swell
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 023	Swell waves	
3 02 031		(Pressure information)	Standard level
	3 02 001	Pressure and 3-hour pressure change	
	0 10 062	24-hour pressure change	
	0 07 004	Pressure	
3 02 032	0 10 009	Geopotential height	Temperature and humidity measurement Scale: 2 Scale: 2
		(Temperature and humidity data)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 12 101	Temperature/air temperature	
	0 12 103	Dewpoint temperature	
3 02 033	0 13 003	Relative humidity	Visibility measurement
		(Visibility data)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
3 02 034	0 20 001	Horizontal visibility	Precipitation measurement
		(Precipitation past 24 hours)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
3 02 035	0 13 023	Total precipitation past 24 hours	Set to missing (cancel)
		(Basic synoptic "instantaneous" data)	
	3 02 032	Temperature and humidity data	
	3 02 033	Visibility data	
	3 02 034	Precipitation past 24 hours	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	3 02 004	General cloud information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 005	Cloud layer	Individual cloud layer or mass

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 036	1 05 000	(Clouds with bases below station level)	
	0 31 001	Delayed replication of 5 descriptors	
	0 08 002	Delayed descriptor replication factor	
	0 20 011	Vertical significance (surface observations)	
	0 20 012	Cloud amount	
	0 20 012	Cloud type	
	0 20 014	Height of top of cloud	
	0 20 017	Cloud top description	
3 02 037	0 20 062	(State of ground, snow depth, ground minimum temperature)	
	0 13 013	State of the ground (with or without snow)	
	0 12 113	Total snow depth	
	0 12 113	Ground minimum temperature, past 12 hours	Scale: 2
3 02 038	0 20 003	(Present and past weather)	
	0 04 024	Present weather	
	0 20 004	Time period or displacement	Hours
	0 20 004	Past weather (1)	
	0 20 005	Past weather (2)	
3 02 039	0 04 024	(Sunshine data (from 1 hour and 24-hour period))	
	0 14 031	Time period or displacement	Hours
	0 14 031	Total sunshine	
3 02 040	0 07 032	(Precipitation measurement)	
	1 02 002	Height of sensor above local ground (or deck of marine platform)	Precipitation measurement
	1 02 002	Replicate 2 descriptors 2 times	
	0 04 024	Time period or displacement	Hours
	0 13 011	Total precipitation/total water equivalent	
3 02 041	0 07 032	(Extreme temperature data)	
	0 04 024	Height of sensor above local ground (or deck of marine platform)	Temperature measurement
	0 04 024	Time period or displacement	
	0 04 024	Time period or displacement (see Notes 1 and 2)	
	0 12 111	Maximum temperature, at height and over period specified	Scale: 2
	0 04 024	Time period or displacement	
	0 04 024	Time period or displacement (see Note 2)	
	0 12 112	Minimum temperature, at height and over period specified	Scale: 2

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 042	0 07 032	(Wind data) Height of sensor above local ground (or deck of marine platform)	Wind measurement
	0 02 002	Type of instrumentation for wind measurement	= 2 Time averaged = -10 minutes, or number of minutes after a significant change of wind
	0 08 021	Time significance	
	0 04 025	Time period or displacement	
	0 11 001	Wind direction	Set to missing
	0 11 002	Wind speed	
	0 08 021	Time significance	
	1 03 002	Replicate 3 descriptors 2 times	
	0 04 025	Time period or displacement	Minutes
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
		(Basic synoptic "period" data)	Set to missing (cancel)
	3 02 038	Present and past weather	
	1 01 002	Replicate 1 descriptor 2 times	
3 02 043	3 02 039	Sunshine data (from 1 hour and 24-hour period)	
	3 02 040	Precipitation measurement	
	3 02 041	Extreme temperature data	
	3 02 042	Wind data	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
		(Evaporation data)	Hours
	0 04 024	Time period or displacement	
	0 02 004	Type of instrumentation for evaporation measurement or type of crop for which evapotranspiration is reported	
3 02 044	0 13 033	Evaporation/evapotranspiration	
		(Radiation data (from 1 hour and 24-hour period))	Hours
	0 04 024	Time period or displacement	
	0 14 002	Long-wave radiation, integrated over period specified	
	0 14 004	Short-wave radiation, integrated over period specified	
	0 14 016	Net radiation, integrated over period specified	
	0 14 028	Global solar radiation (high accuracy), integrated over period specified	
	0 14 029	Diffuse solar radiation (high accuracy), integrated over period specified	
3 02 045	0 14 030	Direct solar radiation (high accuracy), integrated over period specified	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 046	0 04 024	(Temperature change) Time period or displacement	
	0 04 024	Time period or displacement (see Note 3)	
	0 12 049	Temperature change over specified period	
3 02 047		(Direction of cloud drift)	
	1 02 003	Replicate 2 descriptors 3 times	
	0 08 002	Vertical significance (surface observations)	
3 02 048	0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed	
		(Direction and elevation of cloud)	
	0 05 021	Bearing or azimuth	Elevation angle
3 02 049	0 07 021	Elevation	
	0 20 012	Cloud type	
	0 05 021	Bearing or azimuth	Set to missing (cancel)
3 02 050	0 07 021	Elevation	Set to missing (cancel)
		(Cloud information reported with vertical soundings)	
	0 08 002	Vertical significance (surface observations)	
3 02 049	0 20 011	Cloud amount	Low or middle clouds N _h
	0 20 013	Height of base of cloud	h
	0 20 012	Cloud type	Low clouds C _L
3 02 049	0 20 012	Cloud type	Middle clouds C _M
	0 20 012	Cloud type	High clouds C _H
	0 08 002	Vertical significance (surface observations)	Set to missing
3 02 050		(Radiosonde surface observation)	
	0 08 041	Data significance	= 5 Surface observation displacement from launch point
	0 05 021	Bearing or azimuth	
3 02 050	0 07 005	Height increment	
	2 02 130	Change scale	
	0 06 021	Distance	
3 02 050	2 02 000	Change scale	Cancel
	0 08 041	Data significance	= 4 Surface observation
3 02 050	2 01 131	Change data width	
	2 02 129	Change scale	
	0 02 115	Type of surface observing equipment	
3 02 050	0 10 004	Pressure	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 050 (continued)	0 02 115	Type of surface observing equipment	Cancel
	0 13 003	Relative humidity	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 02 115	Type of surface observing equipment	Hours
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 02 115	Type of surface observing equipment	
	1 02 002	Replicate 2 descriptors 2 times	
	0 12 101	Temperature/air temperature	
	0 04 024	Time period or displacement	
	0 02 115	Type of surface observing equipment	
	0 12 103	Dewpoint temperature	
	0 12 102	Wet-bulb temperature	
	1 01 003	Replicate 1 descriptor 3 times	
	0 20 012	Cloud type	
	0 20 011	Cloud amount	
	0 20 013	Height of base of cloud	
	1 01 002	Replicate 1 descriptor 2 times	
	0 20 003	Present weather	
3 02 051	0 10 004	Pressure	Vertical location
	0 10 051	Pressure reduced to mean sea level	
	0 07 004	Pressure	
	0 10 003	Geopotential	
	0 12 004	Air temperature at 2 m	
	0 12 051	Standard deviation temperature	
	0 12 016	Maximum temperature at 2 m, past 24 hours	
	0 12 017	Minimum temperature at 2 m, past 24 hours	
	0 13 004	Vapour pressure	
	1 02 004	Replicate 2 descriptors 4 times	
	0 08 051	Qualifier for number of missing values in calculation of statistic	
	0 08 020	Total number of missing entities (with respect to accumulation or average)	
3 02 052		(Ship temperature and humidity data)	Temperature and humidity measurement
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 12 101	Temperature/air temperature	
	0 02 039	Method of wet-bulb temperature measurement	
	0 12 102	Wet-bulb temperature	
	0 12 103	Dewpoint temperature	
	0 13 003	Relative humidity	Scale: 2

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 053	0 07 032	(Ship visibility data) Height of sensor above local ground (or deck of marine platform)	Visibility measurement
	0 07 033	Height of sensor above water surface	Visibility measurement
	0 20 001	Horizontal visibility	
3 02 054		(Ship "instantaneous" data)	
	3 02 052	Ship temperature and humidity data	
	3 02 053	Ship visibility data	
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	3 02 034	Precipitation past 24 hours	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	3 02 004	General cloud information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
3 02 055	3 02 005	Cloud layer	
		(Icing and ice)	
	0 20 031	Ice deposit (thickness)	
	0 20 032	Rate of ice accretion (estimated)	
	0 20 033	Cause of ice accretion	
	0 20 034	Sea-ice concentration	
	0 20 035	Amount and type of ice	
	0 20 036	Ice situation	
	0 20 037	Ice development	
3 02 056	0 20 038	Bearing of ice edge	
		(Sea/water temperature)	
	0 02 038	Method of water temperature and/or salinity measurement	
	0 07 063	Depth below sea/water surface (cm)	Sea-surface temperature measurement
	0 22 043	Sea/water temperature	
3 02 057	0 07 063	Depth below sea/water surface (cm)	Set to missing (cancel)
		(Ship marine data)	
	3 02 056	Sea/water temperature	Sea-surface temperature, method of measurement, and depth below sea surface
	3 02 021	Waves	
	3 02 024	Wind and swell waves	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 058	0 07 032	(Ship extreme temperature data) Height of sensor above local ground (or deck of marine platform)	Temperature measurement
	0 07 033	Height of sensor above water surface	Temperature measurement
	0 04 024	Time period or displacement	
	0 04 024	Time period or displacement (see Notes 1 and 2)	
	0 12 111	Maximum temperature, at height and over period specified	Scale: 2
	0 04 024	Time period or displacement	
	0 04 024	Time period or displacement (see Note 2)	
	0 12 112	Minimum temperature, at height and over period specified	Scale: 2
3 02 059		(Ship wind data)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Wind measurement
	0 07 033	Height of sensor above water surface	Wind measurement
	0 02 002	Type of instrumentation for wind measurement	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	= -10 minutes, or number of minutes after a significant change of wind
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 08 021	Time significance	Set to missing
	1 03 002	Replicate 3 descriptors 2 times	
	0 04 025	Time period or displacement	Minutes
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
3 02 060		(Ship "period" data)	
	3 02 038	Present and past weather	
	3 02 040	Precipitation measurement	
	3 02 058	Ship extreme temperature data	
3 02 062	3 02 059	Ship wind data	
		(Ship "instantaneous" data)	
	0 25 188	Method for reducing pressure to sea level	
	3 02 001	Pressure and 3-hour pressure change	
	3 02 093	Extended ship temperature and humidity data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 053	Ship visibility data	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 062 (continued)	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 004	General cloud information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 005	Cloud layer	
	0 08 002	Vertical significance (surface observations)	Set to missing (cancel)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 055	Icing and ice	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 056	Sea/water temperature	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 021	Waves	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 024	Wind and swell waves	
		(Ship "period" data)	
3 02 063	3 02 038	Present and past weather	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 040	Precipitation measurement	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 034	Precipitation past 24 hours	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 058	Ship extreme temperature data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 064	Ship or other marine platform wind data	
3 02 064		(Ship or other marine platform wind data)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 02 002	Type of instrumentation for wind measurement	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	
	0 11 001	Wind direction	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 064 (continued)	0 11 002	Wind speed	Set to missing (cancel)
	0 08 021	Time significance	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 04 025	Time period or displacement	
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
3 02 066		(Dangerous weather phenomena)	
	0 20 023	Other weather phenomena	
	0 20 024	Intensity of phenomena	
	0 20 027	Phenomena occurrence	
	0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed	
	0 20 023	Other weather phenomena	
	0 20 027	Phenomena occurrence	
	0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed	
	0 20 025	Obscuration	
	0 20 026	Character of obscuration	
	0 20 027	Phenomena occurrence	
	0 20 040	Evolution of drift snow	
	0 20 066	Maximum diameter of hailstones	
	0 20 027	Phenomena occurrence	
	0 20 021	Type of precipitation	
	0 20 067	Diameter of deposit	
	0 20 027	Phenomena occurrence	
3 02 067		(Additional synoptical parameters)	
	0 01 023	Observation sequence number <i>Additional "instantaneous" data</i>	
	0 04 025	Time period or displacement	
	0 02 177	Method of snow depth measurement = 0 Manual observation, = 1 Ultrasonic method, = 2 Video camera method, = 3 Laser method, 4–13 Reserved, = 14 Others, = 15 Missing value	
		<i>Additional present weather</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 20 003	Present weather <i>Visibility in different directions</i>	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 067 (continued)	0 05 021	Bearing or azimuth	981VV-988VV
	0 20 001	Horizontal visibility	VV
	0 05 021	Bearing or azimuth	Set to missing (cancel)
		<i>Sea data (observations from a coastal station)</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 056	Sea/water temperature	Sea-surface temperature, method of measurement, and depth below sea surface
	1 03 000	Delayed replication of 3 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 33 041	Attribute of following value	
	0 20 058	Visibility seawards from a coastal station	980V _s V _s
	0 22 061	State of the sea	924SV _s
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 022	Wind waves	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 023	Swell waves	
		<i>Clouds</i>	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed	D _a , D _p
	0 20 137	Evolution of clouds	940Cn ₃
	0 20 012	Cloud type	941CD _p , 943CLD _p
	0 20 090	Special clouds	993C _s D _a
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed	
	0 20 137	Evolution of clouds	
	0 20 136	Supplementary cloud type	948C ₀ D _a , 949C _a D _a , 950N _{mn3} , 951N _{vn4}
		<i>Additional "period" data</i>	
	0 04 025	Time period or displacement	Reference period of fresh fallen snow
	0 13 012	Depth of fresh snow	
		<i>Additional wind data</i>	
	0 04 025	Time period or displacement	= -60 minutes
	0 11 042	Maximum wind speed (10-minute mean wind)	912ff 902tt 912ff .. mandatory ff ≥ 18

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 067 (continued)	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 021	Time significance	= 30 Time of occurrence, = 17 Start of phenomenon
			= -xx 902tt
	0 04 025	Time period or displacement	912ff
	0 11 042	Maximum wind speed (10-minute mean wind)	Set to missing (cancel)
	0 08 021	Time significance	
		<i>Significant change in wind speed and/or direction</i>	
	1 15 000	Delayed replication of 15 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 021	Time significance	= 30 Time of occurrence, = 17 Start of phenomenon
			= -xx1
	0 04 015	Time increment	= 2 Time averaged
	0 08 021	Time significance	= -10 minutes, or number of minutes after a significant change of wind
	0 04 025	Time period or displacement	915dd
			913ff
	0 11 001	Wind direction	= 22 Time of occurrence of wind shift
	0 11 002	Wind speed	= +xx2
	0 08 021	Time significance	= 2 Time averaged
			= -10 minutes, or number of minutes after a significant change of wind
	0 04 015	Time increment	915dd
	0 08 021	Time significance	913ff
	0 04 025	Time period or displacement	Set to missing (cancel)
			= 0 minutes
	0 11 001	Wind direction	= +(xx1-xx2)
	0 11 002	Wind speed	Non negative to reset the time to the actual time
	0 08 021	Time significance	
	0 04 025	Time period or displacement	
	0 04 015	Time increment	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 067 (continued)	1 03 000	<i>Additional weather</i> Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -xx, i.e. from
	0 04 025	Time period or displacement	= -xx, i.e. to
	0 20 003	Present weather	962ww, 963w ₁ w ₁ , 964ww, 965w ₁ w ₁ , 966ww, 967w ₁ w ₁
		<i>Additional 9S_pS_pS_pS_p groups</i>	
	1 10 000	Delayed replication of 10 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -xx, i.e. from
	0 04 025	Time period or displacement	= -xx, i.e. to
	0 05 021	Bearing or azimuth	D _a , D _p
	0 05 021	Bearing or azimuth	D _a , D _p
	0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed	D _a , D _p
	0 20 024	Intensity of phenomena	= 1 Light, = 2 Moderate, = 3 Heavy, = 4 Violent, = 5 Severe
	0 20 025	Obscuration	
	0 20 026	Character of obscuration	
	0 20 027	Phenomena occurrence	
	0 20 063	Special phenomena	
		(Visibility data)	
3 02 069	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 33 041	Attribute of following value	
	0 20 001	Horizontal visibility	
		(Wind data)	
3 02 070	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
	0 11 016	Extreme counterclockwise wind direction of a variable wind	
	0 11 017	Extreme clockwise wind direction of a variable wind	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 071	0 07 032	(Wind data from one-hour period) Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	= -10 minutes, or number of minutes after a significant change of wind, if any
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 08 021	Time significance	Set to missing
	1 03 002	Replicate 3 descriptors 2 times	
	0 04 025	Time period or displacement	= -10 minutes in the first replication, = -60 minutes in the second replication
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
	0 04 025	Time period or displacement	= -10 minutes
	0 11 016	Extreme counterclockwise wind direction of a variable wind	
	0 11 017	Extreme clockwise wind direction of a variable wind	
3 02 072		(Temperature and humidity data)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 12 101	Temperature/air temperature	Scale: 2
	0 12 103	Dewpoint temperature	Scale: 2
	0 13 003	Relative humidity	
3 02 073		(Cloud data)	
	0 20 010	Cloud cover (total)	
	1 05 004	Replicate 5 descriptors 4 times	
	0 08 002	Vertical significance (surface observations)	
	0 20 011	Cloud amount	
	0 20 012	Cloud type	
	0 33 041	Attribute of following value	
	0 20 013	Height of base of cloud	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 074	0 20 003	(Present and past weather) Present weather	
	0 04 025	Time period or displacement	
	0 20 004	Past weather (1)	
	0 20 005	Past weather (2)	
3 02 075		(Intensity of precipitation, size of precipitation element)	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	= -10 minutes
	0 13 055	Intensity of precipitation	
	0 13 058	Size of precipitating element	
3 02 076	0 08 021	Time significance	Set to missing
		(Precipitation, obscuration and other phenomena)	
	0 20 021	Type of precipitation	
	0 20 022	Character of precipitation	
	0 26 020	Duration of precipitation	
	0 20 023	Other weather phenomena	
	0 20 024	Intensity of phenomena	
	0 20 025	Obscuration	
3 02 077	0 20 026	Character of obscuration	
		(Extreme temperature data)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 04 025	Time period or displacement	
	0 12 111	Maximum temperature, at height and over period specified	Scale: 2
	0 12 112	Minimum temperature, at height and over period specified	Scale: 2
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Ground temperature
	0 04 025	Time period or displacement	
3 02 078	0 12 112	Minimum temperature, at height and over period specified	Scale: 2 Ground temperature
		(State of ground and snow depth measurement)	
	0 02 176	Method of state of ground measurement	
	0 20 062	State of the ground (with or without snow)	
	0 02 177	Method of snow depth measurement	
	0 13 013	Total snow depth	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 079	0 07 032	(Precipitation measurement) Height of sensor above local ground (or deck of marine platform)	
	0 02 175	Method of precipitation measurement	
	0 02 178	Method of liquid content measurement of precipitation	
	0 04 025	Time period or displacement	
	0 13 011	Total precipitation/total water equivalent	
3 02 080	0 02 185	(Evaporation measurement) Method of evaporation measurement	
	0 04 025	Time period or displacement	
	0 13 033	Evaporation/evapotranspiration	
3 02 081	0 04 025	(Total sunshine data) Time period or displacement	
	0 14 031	Total sunshine	
3 02 082	0 04 025	(Radiation data) Time period or displacement	
	0 14 002	Long-wave radiation, integrated over period specified	
	0 14 004	Short-wave radiation, integrated over period specified	
	0 14 016	Net radiation, integrated over period specified	
	0 14 028	Global solar radiation (high accuracy), integrated over period specified	
	0 14 029	Diffuse solar radiation (high accuracy), integrated over period specified	
	0 14 030	Direct solar radiation (high accuracy), integrated over period specified	
3 02 083	0 04 025	(First-order statistics of P, W, T, U data) Time period or displacement	
	0 08 023	First-order statistics	
	0 10 004	Pressure	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 12 101	Temperature/air temperature	
	0 13 003	Relative humidity	
	0 08 023	First-order statistics	
3 02 084	3 02 031	(“Instantaneous” data of sequence 3 07 096) Pressure information	
	3 02 072	Temperature and humidity data	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 000	Short delayed descriptor replication factor	

Scale: 2

Set to missing

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 084 (continued)	1 01 005	Replicate 1 descriptor 5 times	
	3 07 063	Depth below land surface and soil temperature	
	0 07 061	Depth below land surface	Set to missing (cancel)
		<i>Visibility data</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 069	Visibility data	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
		<i>Marine data</i>	
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 20 031	Ice deposit (thickness)	
	0 20 032	Rate of ice accretion (estimated)	
	0 02 038	Method of water temperature and/or salinity measurement	
	0 22 043	Sea/water temperature	Scale: 2
	3 02 021	Waves	
		<i>State of ground and snow depth measurement</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 078	State of ground and snow depth measurement	
	0 12 113	Ground minimum temperature, past 12 hours	Scale: 2
		<i>Cloud data</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 004	General cloud information	
	1 05 000	Delayed replication of 5 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 002	Vertical significance (surface observations)	
	0 20 011	Cloud amount	
	0 20 012	Cloud type	
	0 33 041	Attribute of following value	
	0 20 013	Height of base of cloud	
	3 02 036	Clouds with bases below station level	
		<i>Direction of cloud drift 6D_LD_MD_H</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 047	Direction of cloud drift	
	0 08 002	Vertical significance (surface observations)	Set to missing (cancel)

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 084 (continued)	1 01 000	Direction and elevation of cloud 57CD _{aec} Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 048	Direction and elevation of cloud	
		("Period" data of sequence 3 07 096)	
		<i>Present and past weather data</i>	
3 02 085	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 20 003	Present weather	
	1 03 002	Replicate 3 descriptors 2 times	
	0 04 024	Time period or displacement = -1 hour in the first replication, = -x hours in the second replication, x corresponding to the time period of W ₁ W ₂ in the SYNOP report	/see left column
	0 20 004	Past weather (1)	
	0 20 005	Past weather (2)	
		<i>Intensity of precipitation, size of precipitation element</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 175	Intensity of precipitation, size of precipitation element	
		<i>Precipitation, obscuration and other phenomena</i>	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -10 minutes
	3 02 076	Precipitation, obscuration and other phenomena	
		<i>Lightning data</i>	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -10 minutes
	0 13 059	Number of flashes (thunderstorm)	
		<i>Wind data</i>	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	= -10 minutes, or number of minutes after a significant change of wind
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 08 021	Time significance	Set to missing
	1 03 003	Replicate 3 descriptors 3 times	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 085 (continued)	0 04 025	Time period or displacement = -10 minutes in the first replication, = -60 minutes in the second replication, = -60x3 or 60x6 minutes in the third replication	/see left column
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
	0 04 025	Time period or displacement	= -10 minutes
	0 11 016	Extreme counterclockwise wind direction of a variable wind	
	0 11 017	Extreme clockwise wind direction of a variable wind	
		<i>Extreme temperature data</i>	
	3 02 077	Extreme temperature data	
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	3 02 041	Extreme temperature data	
		<i>Precipitation measurement</i>	
	1 06 000	Delayed replication of 6 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 02 175	Method of precipitation measurement	
	0 02 178	Method of liquid content measurement of precipitation	
	1 02 005	Replicate 2 descriptors 5 times	
	0 04 024	Time period or displacement	= -1 hour in the first replication, = - 3, -6, -12 and -24 hours in the other replications
	0 13 011	Total precipitation/total water equivalent	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		<i>Evaporation data</i>	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 02 185	Method of evaporation measurement	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 044	Evaporation data	
		<i>Total sunshine data</i>	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 039	Sunshine data (from 1 hour and 24-hour period)	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 085 (continued)		<i>Radiation data</i>	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
		<i>Temperature change group 54g₀s_nd_T</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 046	Temperature change	
		<i>First-order statistics of P, W, T, U data</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 083	First-order statistics of P, W, T, U data	
3 02 089		(Locust information)	
	0 20 101	Locust (acridian) name	L _n
	0 20 102	Locust (maturity) colour	L _c
	0 20 103	Stage of development of locusts	L _d
	0 20 104	Organization state of swarm or band of locusts	L _g
	0 20 105	Size of swarm or band of locusts and duration of passage of swarm	S _L
	0 20 106	Locust population density	d _L
	0 20 107	Direction of movements of locust swarm	D _L
3 02 090	0 20 108	Extent of vegetation	V _e
		(Sea/water temperature high precision)	
	0 02 038	Method of water temperature and/or salinity measurement	
	0 07 063	Depth below sea/water surface (cm)	Sea-surface temperature measurement
3 02 091	0 22 045	Sea/water temperature	
		(Sequence for representation of ancillary meteorological observations)	
	0 20 001	Horizontal visibility	
	0 04 024	Time period or displacement	
3 02 092	0 13 011	Total precipitation/total water equivalent	
		(VOSCLim data elements)	
	0 11 104	True heading of aircraft, ship or other mobile platform	Ship's true heading
	0 01 012	Direction of motion of moving observing platform	Ship's course over ground
	0 01 013	Speed of motion of moving observing platform	Ship's speed over ground
	0 10 038	Maximum height of deck cargo above summer load line	

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 092 (continued)	0 10 039	Departure of reference level (summer maximum load line) from actual sea level	
	0 11 007	Relative wind direction (in degrees off bow)	
	0 11 008	Relative wind speed	
3 02 093		(Extended ship temperature and humidity data)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	3 03 099	Metadata common to temperature/humidity sensors	
	0 12 101	Temperature/air temperature	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 000	Short delayed descriptor replication factor	Set to 0 if no change from previous values, 1 if changes
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	3 03 099	Metadata common to temperature/humidity sensors	
	0 02 039	Method of wet-bulb temperature measurement	
	0 02 097	Type of humidity sensor	
	0 03 024	Psychrometric coefficient	Set to missing if type of humidity sensor is not psychrometer
	0 03 021	Hygrometer heating	
	0 12 102	Wet-bulb temperature	
	0 12 103	Dewpoint temperature	
	0 13 003	Relative humidity	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	3 03 099	Metadata common to temperature/humidity sensors	Set all elements in sequence to missing (cancel)
	0 02 039	Method of wet-bulb temperature measurement	Set to missing (cancel)
	0 02 097	Type of humidity sensor	Set to missing (cancel)
	0 03 021	Hygrometer heating	Set to missing (cancel)
	0 03 024	Psychrometric coefficient	Set to missing (cancel)

FM 94 BUFR

Category 02			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 02 175		(Intensity of precipitation, size of precipitation element)	
	0 08 021	Time significance	
	0 04 025	Time period or displacement	
	0 13 155	Intensity of precipitation (high accuracy)	
	0 13 058	Size of precipitating element	
	0 08 021	Time significance	

Notes:

- (1) Within RA IV, the maximum temperature at 1200 UTC is reported for the previous calendar day (i.e. the ending time of the period is not equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (2) Within RA III, the maximum daytime temperature and the minimum night-time temperature is reported (i.e. the ending time of the period may not be equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (3) To construct the required time range, descriptor 0 04 024 has to be included two times.

**Category 03 – Meteorological sequences common
to vertical soundings data**

Category 03			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 03 001	0 07 003	Geopotential	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
		(Wind at pressure level)	
3 03 002	0 07 004	Pressure	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
3 03 003	0 07 004	Pressure	
	0 10 003	Geopotential	
	0 12 001	Temperature/air temperature	
	0 12 003	Dewpoint temperature	
3 03 004	0 07 004	Pressure	
	0 10 003	Geopotential	
	0 12 001	Temperature/air temperature	
	0 12 003	Dewpoint temperature	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
		(Wind at height)	
3 03 011	0 07 003	Geopotential	
	0 08 001	Vertical sounding significance	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
		(Wind at pressure level)	
3 03 012	0 07 004	Pressure	
	0 08 001	Vertical sounding significance	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
		(Geopotential, temperature, humidity, wind at pressure level)	
3 03 013	0 07 004	Pressure	
	0 08 001	Vertical sounding significance	
	0 10 003	Geopotential	
	0 12 001	Temperature/air temperature	
	0 13 003	Relative humidity	
	0 11 001	Wind direction	
	0 11 002	Wind speed	

FM 94 BUFR

Category 03			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 03 014		(Geopotential, temperature, dewpoint temperature, wind at pressure level)	
	0 07 004	Pressure	
	0 08 001	Vertical sounding significance	
	0 10 003	Geopotential	
	0 12 001	Temperature/air temperature	
	0 12 003	Dewpoint temperature	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
3 03 021		(Layer, quality)	
	0 07 004	Pressure }	Define layer
	0 07 004	Pressure }	
	2 04 007	Add associated field	7 bits long
	0 31 021	Associated field significance	
3 03 022	3 03 021	Layer, quality	
	0 10 003	Geopotential	Layer mean thickness
	2 04 000	Add associated field	Cancel
3 03 023		(Layer mean temperature)	
	3 03 021	Layer, quality	
	0 12 001	Temperature/air temperature	Layer mean
	2 04 000	Add associated field	Cancel
3 03 024		(Precipitable water)	
	3 03 021	Layer, quality	
	0 13 016	Precipitable water	
	2 04 000	Add associated field	Cancel
3 03 025		(Satellite channel and brightness temperature)	
	0 02 025	Satellite channel(s) used in computation	
	2 04 007	Add associated field	7 bits long
	0 31 021	Associated field significance	
	0 12 063	Brightness temperature	
	2 04 000	Add associated field	Cancel
3 03 026	0 07 004	Pressure	
	0 08 003	Vertical significance (satellite observations)	
	2 04 007	Add associated field	7 bits long
	0 31 021	Associated field significance	
	0 12 001	Temperature/air temperature	
	2 04 000	Add associated field	Cancel

FM 94 BUFR

Category 03			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 03 027	0 07 004	Pressure	7 bits long
	2 04 007	Add associated field	
	0 31 021	Associated field significance	
	0 10 003	Geopotential	
	2 04 000	Add associated field	
			Cancel
3 03 031		(Significance data, land/sea, skin temperature)	Base of sounding Local zenith Solar zenith
	0 07 004	Pressure	
	0 08 003	Vertical significance (satellite observations)	
	0 07 021	Elevation	
	0 07 022	Solar elevation	
	0 08 012	Land/sea qualifier	
	0 12 061	Skin temperature	
3 03 032		(Cloud)	
	0 20 011	Cloud amount	
	0 20 016	Pressure at top of cloud	
3 03 033		(Cloud)	
	0 20 010	Cloud cover (total)	
	0 20 016	Pressure at top of cloud	
3 03 040		(Radiosonde duration of flight and termination information)	= 7 Flight level termination point Minutes Seconds
	0 08 041	Data significance	
	0 04 025	Time period or displacement	
	0 04 026	Time period or displacement	
	3 01 021	Latitude/longitude (high accuracy)	
	3 01 122	Date/time (to hundredths of second)	
	2 01 131	Change data width	
	2 02 129	Change scale	
	0 25 069	Flight level pressure corrections	
	0 07 004	Pressure	
	0 13 003	Relative humidity	
	2 02 000	Change scale	
	2 01 000	Change data width	
	0 02 013	Solar and infrared radiation correction	
	0 12 101	Temperature/air temperature	
	0 10 009	Geopotential height	
	1 02 002	Replicate 2 descriptors 2 times	
	0 08 040	Flight level significance	
	0 35 035	Reason for termination	
			Cancel

FM 94 BUFR

Category 03			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 03 041	0 02 152	(Wind sequence)	
	0 02 023	Satellite instrument used in data processing	
	0 07 004	Satellite-derived wind computation method	
	0 11 001	Pressure	
	0 11 002	Wind direction	
	0 11 002	Wind speed	
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	0 12 071	Coldest cluster temperature	
3 03 050		(Wind data at a pressure level with radiosonde position)	
	0 04 086	Long time period or displacement	Since launch time
	0 08 042	Extended vertical sounding significance	
	0 07 004	Pressure	
	0 05 015	Latitude displacement (high accuracy)	Since launch site
	0 06 015	Longitude displacement (high accuracy)	Since launch site
	0 11 001	Wind direction	
	0 11 002	Wind speed	
3 03 051		(Wind shear data at a pressure level with radiosonde position)	
	0 04 086	Long time period or displacement	Since launch time
	0 08 042	Extended vertical sounding significance	
	0 07 004	Pressure	
	0 05 015	Latitude displacement (high accuracy)	Since launch site
	0 06 015	Longitude displacement (high accuracy)	Since launch site
	0 11 061	Absolute wind shear in 1 km layer below	
	0 11 062	Absolute wind shear in 1 km layer above	
3 03 052		(Wind data at a height level with radiosonde position)	
	0 04 086	Long time period or displacement	Since launch time
	0 08 042	Extended vertical sounding significance	
	0 07 009	Geopotential height	
	0 05 015	Latitude displacement (high accuracy)	Since launch site
	0 06 015	Longitude displacement (high accuracy)	Since launch site
	0 11 001	Wind direction	
	0 11 002	Wind speed	
3 03 053		(Wind shear data at a height level with radiosonde position)	
	0 04 086	Long time period or displacement	Since launch time
	0 08 042	Extended vertical sounding significance	
	0 07 009	Geopotential height	

FM 94 BUFR

Category 03			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 03 053 (continued)	0 05 015	Latitude displacement (high accuracy)	Since launch site
	0 06 015	Longitude displacement (high accuracy)	Since launch site
	0 11 061	Absolute wind shear in 1 km layer below	
	0 11 062	Absolute wind shear in 1 km layer above	
3 03 054		(Temperature, dewpoint and wind data at a pressure level with radiosonde position)	
	0 04 086	Long time period or displacement	Since launch time
	0 08 042	Extended vertical sounding significance	
	0 07 004	Pressure	
	0 10 009	Geopotential height	
	0 05 015	Latitude displacement (high accuracy)	Since launch site
	0 06 015	Longitude displacement (high accuracy)	Since launch site
	0 12 101	Temperature/air temperature	Scale: 2
	0 12 103	Dewpoint temperature	Scale: 2
	0 11 001	Wind direction	
	0 11 002	Wind speed	
3 03 055		(Temperature, dewpoint, relative humidity and wind data at a height level with radiosonde position)	
	0 04 086	Long time period or displacement	Since launch time
	0 08 042	Extended vertical sounding significance	
	0 07 009	Geopotential height	
	0 05 015	Latitude displacement (high accuracy)	Since launch site
	0 06 015	Longitude displacement (high accuracy)	Since launch site
	0 12 101	Temperature/air temperature	Scale: 2
	0 13 009	Relative humidity	
	0 12 103	Dewpoint temperature	Scale: 2
	0 11 001	Wind direction	
	0 11 002	Wind speed	
3 03 056		(Temperature, dewpoint and wind data at a pressure level with radiosonde position and higher precision of pressure and geopotential height)	
	0 04 086	Long time period or displacement	Since launch time
	0 08 042	Extended vertical sounding significance	
	2 07 001	Increase scale, reference value and data width	
	0 07 004	Pressure	Scale: 0
	0 10 009	Geopotential height	Scale: 1
	2 07 000	Increase scale, reference value and data width	Cancel
	0 05 015	Latitude displacement (high accuracy)	Since launch site
	0 06 015	Longitude displacement (high accuracy)	Since launch site
	0 12 101	Temperature/air temperature	Scale: 2
	0 12 103	Dewpoint temperature	Scale: 2
	0 11 001	Wind direction	
	0 11 002	Wind speed	

FM 94 BUFR

Category 03			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 03 099		(Metadata common to temperature/humidity sensors)	
	0 03 005	Horizontal width of screen or shield (x)	
	0 03 006	Horizontal depth of screen or shield (y)	
	0 03 007	Vertical height of screen or shield (z)	
	0 02 096	Type of temperature sensor	
	0 03 022	Instrument owner	
	0 03 003	Thermometer/hygrometer housing	
	0 03 020	Material for thermometer/hygrometer housing	
	0 03 004	Type of screen/shelter/radiation shield	
	0 03 023	Configuration of louvres for thermometer/hygrometer screen	
	0 03 008	Artificially ventilated screen or shield	
	0 03 009	Amount of forced ventilation at time of reading	

Notes:

- (1) Descriptors 3 03 021 to 3 03 027 are not available in CREX.
- (2) Long time displacement 0 04 086 represents the time offset from the launch time 3 01 013 (in seconds).
- (3) Latitude displacement 0 05 015 represents the latitude offset from the latitude of the launch site. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site.

**Category 04 – Meteorological sequences common
to satellite observations**

Category 04			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 04 001	0 08 003	(Cloud top pressure, temperature, wind)	
	0 10 004	Vertical significance (satellite observations)	
	0 12 001	Pressure	
	0 11 001	Temperature/air temperature	
	0 11 002	Wind direction	
3 04 002	0 08 003	Wind speed	
	0 10 004	(Cloud top pressure, wind)	
	0 11 001	Vertical significance (satellite observations)	
	0 11 002	Pressure	
3 04 003	0 08 003	Wind direction	
	0 12 001	Wind speed	
3 04 004	0 08 003	(Surface temperature)	
	0 10 004	Vertical significance (satellite observations)	
	0 20 010	Temperature/air temperature	
	0 12 001		
3 04 005	0 08 003	(Cloud top pressure, cloud cover, temperature)	
	0 10 004	Vertical significance (satellite observations)	
	0 20 010	Pressure	
	0 12 001	Cloud cover (total)	
	0 12 001	Temperature/air temperature	
3 04 006	0 02 024	(Layer mean relative humidity)	
	0 07 004	Integrated mean humidity computational method	
	0 07 004	Pressure }	
	0 13 003	Pressure }	
3 04 011	0 14 001	Relative humidity	Define layer
	0 14 001	(Radiation)	
	0 14 003	Long-wave radiation, integrated over 24 hours	Outgoing long-wave radiation
3 04 011	0 14 001	Long-wave radiation, integrated over 24 hours	Incoming long-wave radiation
	0 14 003	Short-wave radiation, integrated over 24 hours	Outgoing short-wave radiation
	0 02 163	(GOES-I/M info)	
	0 02 164	Height assignment method	
3 04 011	0 08 012	Tracer correlation method	
	0 07 024	Land/sea qualifier	
	0 07 024	Satellite zenith angle	

FM 94 BUFR

Category 04			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 04 011 (continued)	0 02 057	Origin of first-guess information for GOES-I/M soundings	
	0 08 021	Time significance	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 08 021	Time significance	
	0 04 024	Time period or displacement	
	1 10 004	Replicate 10 descriptors 4 times	
	0 08 021	Time significance	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	0 08 021	Time significance	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	1 03 010	Replicate 3 descriptors 10 times	
	0 02 163	Height assignment method	
	0 07 004	Pressure	
	0 12 001	Temperature/air temperature	
		(Location of platform)	
3 04 030	0 27 031	In direction of 0 degrees longitude, distance from the Earth's centre	
	0 28 031	In direction 90 degrees East, distance from the Earth's centre	
	0 10 031	In direction of the North Pole, distance from the Earth's centre	
3 04 031		(Speed of platform)	
	0 01 041	Absolute platform velocity – first component	
	0 01 042	Absolute platform velocity – second component	
3 04 032	0 01 043	Absolute platform velocity – third component	
		(Cloud fraction)	
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	0 20 081	Cloud amount in segment	
	0 20 082	Amount segment cloud free	
	0 20 012	Cloud type	

FM 94 BUFR

Category 04			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 04 033	0 02 152	(Clear sky radiance)	
	0 02 166	Satellite instrument used in data processing	
	0 02 167	Radiance type	
	0 02 167	Radiance computational method	
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	0 12 075	Spectral radiance	
	0 12 076	Radiance	
3 04 034	0 12 063	Brightness temperature	
		(Latitude/longitude, solar elevation, number of layers)	
	1 02 004	Replicate 2 descriptors 4 times	
	0 27 001	Latitude (high accuracy)	
	0 28 001	Longitude (high accuracy)	
	0 07 022	Solar elevation	
	0 05 043	Field of view number	
	0 20 010	Cloud cover (total)	
	0 20 016	Pressure at top of cloud	
	0 33 003	Quality information	
3 04 035 (see Note)	0 10 040	Number of retrieved layers	
		(All sky radiance data)	
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	0 12 063	Brightness temperature	
	0 08 001	Meteorological feature	Pixel type: clear
	0 12 063	Brightness temperature	Clear
	0 08 001	Meteorological feature	Pixel type: cloudy
	0 12 063	Brightness temperature	Cloudy
	0 08 001	Meteorological feature	Cancel
	0 08 003	Vertical significance (satellite observations)	Low cloud
	0 12 063	Brightness temperature	Low cloud
	0 08 003	Vertical significance (satellite observations)	Mid cloud
	0 12 063	Brightness temperature	Mid cloud
	0 08 003	Vertical significance (satellite observations)	High cloud
	0 12 063	Brightness temperature	High cloud
	0 08 003	Vertical significance (satellite observations)	Cancel
3 04 036		(Cloud coverage)	
	0 20 082	Amount segment cloud free	
	0 08 012	Land/sea qualifier	Sea
	0 20 082	Amount segment cloud free	Sea
	0 08 012	Land/sea qualifier	Cancel
	0 20 081	Cloud amount in segment	
	0 08 003	Vertical significance (satellite observations)	Low cloud
	0 20 081	Cloud amount in segment	Low cloud

FM 94 BUFR

Category 04			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 04 036 (continued)	0 08 003	Vertical significance (satellite observations)	Mid cloud
	0 20 081	Cloud amount in segment	Mid cloud
	0 08 003	Vertical significance (satellite observations)	High cloud
	0 20 081	Cloud amount in segment	High cloud
	0 08 003	Vertical significance (satellite observations)	Cancel
3 04 037		(All sky radiance data)	
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	0 12 063	Brightness temperature	
	0 08 011	Meteorological feature	Pixel type: clear
	0 12 063	Brightness temperature	Clear
	0 08 011	Meteorological feature	Pixel type: cloudy
	0 12 063	Brightness temperature	Cloudy
	0 08 011	Meteorological feature	Cancel
	0 08 003	Vertical significance (satellite observations)	Low cloud
	0 12 063	Brightness temperature	Low cloud
	0 08 003	Vertical significance (satellite observations)	Mid cloud
	0 12 063	Brightness temperature	Mid cloud
	0 08 003	Vertical significance (satellite observations)	High cloud
	0 12 063	Brightness temperature	High cloud
3 04 039		(Radiance in channel)	
	2 01 136	Change data width	Add 8 to width
	0 05 042	Channel number	
	2 01 000	Change data width	Cancel
	0 14 046	Scaled radiance	
3 04 040		(Principal component score in band)	
	0 25 140	Start channel	
	0 25 141	End channel	
	0 40 026	Score quantization factor	
	0 40 016	Residual RMS in band	
	0 25 062	Database identification	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	0 40 017	Non-normalized principal component score	

Note: 3 04 035 is deprecated.

**Category 05 – Meteorological or hydrological sequences common
to hydrological observations**

Category 05			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 05 001	0 11 001	(SADC-HYCOS single measurement) Wind direction	First single measurement minus increment Time interval between measurements
	0 11 002	Wind speed	
	0 13 060	Total accumulated precipitation	
	0 13 071	Upstream water level	
3 05 002		(SADC-HYCOS environmental measurement)	
	3 01 012	Hour, minute	
	0 12 001	Temperature/air temperature	
	0 13 003	Relative humidity	
	0 14 051	Direct solar radiation integrated over last hour	
	0 13 060	Total accumulated precipitation	
	0 13 072	Downstream water level	
	0 13 080	Water pH	
	0 13 081	Water conductivity	
	0 13 082	Water temperature	
	0 13 083	Dissolved oxygen	
	0 13 084	Turbidity	
3 05 003		(SADC-HYCOS measurement array definition)	
	3 01 012	Hour, minute	
	0 04 065	Short time increment	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 05 001	SADC-HYCOS single measurement	
3 05 004		(SADC-HYCOS report)	
	3 01 030	Identification – with physical location	
	3 05 002	SADC-HYCOS environmental measurement	
	3 05 003	SADC-HYCOS measurement array definition	
3 05 006		(MEDHYCOS measurement)	
	0 13 072	Downstream water level	
	0 13 082	Water temperature	
	0 13 019	Total precipitation past 1 hour	
	0 12 001	Temperature/air temperature	
	0 13 073	Maximum water level	
	0 13 060	Total accumulated precipitation	

FM 94 BUFR

Category 05			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 05 007	3 01 029	(MEDHYCOS report) Identification	Time of first measurement
	3 01 012	Hour, minute	
	0 04 065	Short time increment	
	1 01 000	Delayed replication of 1 descriptor	Time interval between measurements
	0 31 001	Delayed descriptor replication factor	
	3 05 006	MEDHYCOS measurement	
3 05 008	3 05 006	(AOCHYCOS – Chad measurement) MEDHYCOS measurement	Single measurement
	0 12 030	Soil temperature	
3 05 009	3 01 029	(AOCHYCOS – Chad report) Identification	Same as MEDHYCOS type measurement
	3 01 012	Hour, minute	
	0 04 065	Short time increment	
	1 01 000	Delayed replication of 1 descriptor	At -50 cm
	0 31 001	Delayed descriptor replication factor	
	3 05 008	AOCHYCOS – Chad measurement	
3 05 010	3 05 008	(MEDHYCOS-Measurement type 2) AOCHYCOS-Chad measurement	Time of first measurement
	0 02 091	Entry sensor 4/20 mA	
	0 02 091	Entry sensor 4/20 mA	Time interval between measurements
3 05 011	3 01 029	(MEDHYCOS report type 2) Identification	Single measurement
	3 01 012	Hour, minute	
	0 04 065	Short time increment	
	1 01 000	Delayed replication of 1 descriptor	Same as AOCHYCOS type measurement
	0 31 001	Delayed descriptor replication factor	
	3 05 010	MEDHYCOS-Measurement type 2	

FM 94 BUFR

Category 05			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 05 016	0 14 021	(Meteorological parameters associated with hydrological data) Global solar radiation, integrated over period specified	Atmospheric pressure
	0 07 004	Pressure	
	0 13 003	Relative humidity	
	0 11 002	Wind speed	
	0 11 001	Wind direction	
	0 11 041	Maximum wind gust speed	
	0 11 043	Maximum wind gust direction	
3 05 017	0 13 080	(Water quality measurement) Water pH	
	0 13 081	Water conductivity	
	0 13 083	Dissolved oxygen	
	0 13 085	Oxidation reduction potential (ORP)	
	0 13 084	Turbidity	
3 05 018	3 01 029	(MEDHYCOS report with meteorology and water quality data) Identification	Time of first measurement
	3 01 012	Hour, minute	
	0 04 065	Short time increment	
	1 03 000	Delayed replication of 3 descriptors	Hour increment
	0 31 001	Delayed descriptor replication factor	
	3 05 008	AOCHYCOS-Chad measurement	
	3 05 016	Meteorological parameters associated with hydrological data	Same as AOCHYCOS type measurement
	3 05 017	Water quality measurement	

**Category 06 – Meteorological or oceanographic sequences common
to oceanographic observations**

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 001	0 02 032	(Depth, temperature) Indicator for digitization	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 062	Depth below sea/water surface	
	0 22 042	Sea/water temperature	
3 06 002		(Current)	
	0 02 031	Duration and time of current measurement	
	0 22 004	Direction of current	
3 06 003	0 22 031	Speed of current	
		(Surface wind and temperature)	
	0 02 002	Type of instrumentation for wind measurement	
	0 11 011	Wind direction at 10 m	
3 06 004	0 11 012	Wind speed at 10 m	
	0 12 004	Air temperature at 2 m	
		(Depth, temperature, salinity)	
	0 02 032	Indicator for digitization	
3 06 005	0 02 033	Method of salinity/depth measurement	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 062	Depth below sea/water surface	
	0 22 043	Sea/water temperature	
	0 22 062	Salinity	
3 06 006	0 02 031	Duration and time of current measurement	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 062	Depth below sea/water surface	
	0 22 004	Direction of current	
	0 22 031	Speed of current	
3 06 006		(Under water sounding (optional) parameters)	
	3 06 003	Surface wind and temperature	
	3 06 002	Current	
	0 22 063	Total water depth	

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 007	0 01 012	(Buoy spare block parameters) Direction of motion of moving observing platform	Alphanumeric ID (5 characters)
	0 01 014	Platform drift speed (high precision)	
	3 06 008	Buoy instrumentation parameters	
	0 04 024	Time period or displacement	
	0 27 003	Alternate latitude (coarse accuracy)	
	0 28 003	Alternate longitude (coarse accuracy)	
3 06 008		(Buoy instrumentation parameters)	
	0 02 034	Drogue type	
	0 02 035	Cable length	
3 06 011	0 02 036	Buoy type	
		(Sequence for representation of tide station identification, method of transmission, time the message is transmitted and reference time for reports in a time series)	
	3 01 021	Latitude/longitude (high accuracy)	
	0 01 075	Tide station identification	
	0 02 147	Method of transmission to collection centre	
	3 01 011	Year, month, day	
3 06 012	3 01 013	Hour, minute, second	
		(Sequence for representation of sensor type, significant qualifier for sensor and status of operation)	
	0 02 007	Type of sensor for water level measuring instrument	
	0 08 015	Significant qualifier for sensor	
	0 08 032	Status of operation	
3 06 013	3 06 029	Sequence for representation of tsunameter sampling information for water column heights in the time series report	
		(Sequence for representation of water level and residual in the time series)	
	3 06 012	Sequence for representation of sensor type, significant qualifier for sensor and status of operation	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	0 22 120	Tide station automated water level check	
	0 22 121	Tide station manual water level check	
	0 04 015	Time increment	
			Reference date for the time series
			Reference time for the time series
			Added to reset the reference time

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 013 (continued)	0 04 065	Short time increment	Added to each data value in the time series
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 22 038	Tidal elevation with respect to local chart datum	
	0 22 040	Meteorological residual tidal elevation (surge or offset)	
3 06 014		(Sequence for representation of water level in the time series, similar to 3 06 013 but with no residual)	
	3 06 012	Sequence for representation of sensor type, significant qualifier for sensor and status of operation	
	3 01 011	Year, month, day	Reference date for the time series
	3 01 013	Hour, minute, second	Reference time for the time series
	0 22 120	Tide station automated water level check	
	0 22 121	Tide station manual water level check	
	0 04 015	Time increment	Added to reset the reference time
	0 04 065	Short time increment	Added to each data value in the time series
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
3 06 016	0 22 038	Tidal elevation with respect to local chart datum	
		(Sequence for representation of ancillary meteorological data associated with water level data)	
	3 01 011	Year, month, day	Reference date for the time series
	3 01 013	Hour, minute, second	Reference time for the time series
	0 10 004	Pressure	Station level
	0 10 051	Pressure reduced to mean sea level	
	3 02 032	Temperature and humidity data	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 02 002	Type of instrumentation for wind measurement	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	E.g. = 1 for 1 minute, = 10 for 10 minutes
	0 11 001	Wind direction	

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 016 (continued)	0 11 002	Wind speed	
	0 04 025	Time period or displacement	In minutes
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
	0 25 026	Battery voltage (large range)	AWS battery voltage
	0 12 060	AWS enclosure internal temperature	
		(Subsurface temperature profile (high accuracy/precision) with quality flags)	
3 06 017	0 02 032	Indicator for digitization	= 0 Fixed sensor depths
	0 08 034	Temperature/salinity measurement qualifier	
	1 06 000	Delayed replication of 6 descriptors	
	0 31 002	Extended delayed descriptor replication factor	Number of depths
	0 07 065	Water pressure	In Pa
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 045	Sea/water temperature	In K to 3 decimal places
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 08 034	Temperature/salinity measurement qualifier	Set to missing (cancel)
		(Subsurface temperature profile (high accuracy/precision) with quality flags)	
3 06 018	0 02 032	Indicator for digitization	= 0 Fixed sensor depths
	0 08 034	Temperature/salinity measurement qualifier	
	1 09 000	Delayed replication of 9 descriptors	
	0 31 002	Extended delayed descriptor replication factor	Number of depths
	0 07 065	Water pressure	In Pa
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 045	Sea/water temperature	In K to 3 decimal places
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 064	Salinity	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 08 034	Temperature/salinity measurement qualifier	Set to missing (cancel)

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 019	0 01 075	(Tide report identification, water level checks, time increments)	Alphanumeric
	3 01 011	Tide station identification	
	3 01 012	Year, month, day	
	0 22 042	Hour, minute	
	0 22 120	Sea/water temperature	
	0 22 121	Tide station automated water level check	
	0 04 015	Tide station manual water level check	
	0 04 065	Time increment (see Note 1)	
		Short time increment	
3 06 020	0 01 075	(Tide report identification, water level checks, time period or displacement, time increment) (see Note 2)	Alphanumeric
	3 01 011	Tide station identification	
	3 01 012	Year, month, day	
	0 22 042	Hour, minute	
	0 22 120	Sea/water temperature	
	0 22 121	Tide station automated water level check	
	0 04 075	Tide station manual water level check	
	0 04 065	Short time period or displacement	
		Short time increment	
3 06 021	0 01 075	(Meteorological parameters in tide station)	Alphanumeric
	3 01 011	Tide station identification	
	3 01 012	Year, month, day	
	0 22 122	Hour, minute	
	0 22 123	Tide station automated meteorological data check	
	0 12 001	Tide station manual meteorological data check	
	3 03 002	Temperature/air temperature	
3 06 022	0 01 075	Wind at pressure level	Alphanumeric
	3 01 011	(Tidal elevation)	
	3 01 012	Tide station identification	
	0 22 038	Year, month, day	
	0 22 039	Hour, minute	
		Tidal elevation with respect to local chart datum	
		Meteorological residual tidal elevation (surge or offset)	

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 023	0 01 015	Station or site name	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	0 22 038	Tidal elevation with respect to local chart datum	
	0 22 039	Meteorological residual tidal elevation (surge or offset)	
	0 22 120	Tide station automated water level check	
	0 22 121	Tide station manual water level check	
3 06 024		(Tide elevation series) (see Note 3)	
	3 06 020	Tide report identification, water level checks, time period or displacement, time increment	
	1 02 006	Replicate 2 descriptors 6 times	
	0 22 038	Tidal elevation with respect to local chart datum	
	0 22 039	Meteorological residual tidal elevation (surge or offset)	
3 06 025		(Tide elevation series)	
	3 06 019	Tide report identification, water level checks, time increments	
	1 02 006	Replicate 2 descriptors 6 times	
	0 22 038	Tidal elevation with respect to local chart datum	
	0 22 039	Meteorological residual tidal elevation (surge or offset)	
3 06 027		(Sequence for representation of DART buoy identification, transmitter ID, type of tsunameter and the time the message is transmitted to the ground system)	
	0 01 005	Buoy/platform identifier	
	0 01 052	Platform transmitter ID	
	0 02 047	Deep-ocean tsunameter type	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
			Time the message is transmitted to the ground system

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 028	3 06 027	(Sequence for representation of time of observation and DART buoy position daily report) Sequence for representation of DART buoy identification, transmitter ID, type of tsunameter and the time the message is transmitted to the ground system	Observation time
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
3 06 029		(Sequence for representation of tsunameter sampling information for water column heights in the time series report)	Seconds Seconds
	0 25 170	Sampling interval (time)	
	0 25 171	Sample averaging period	
	0 25 172	Number of samples	
3 06 030		(Sequence for representation of DART buoy standard hourly report)	Message status Reference date/time for the time series BPR CPU Acoustic modem DSP Acoustic modem Added to reset the reference time Added to each data value in the time series
	3 06 027	Sequence for representation of DART buoy identification, transmitter ID, type of tsunameter and the time the message is transmitted to the ground system	
	3 06 029	Sequence for representation of tsunameter sampling information for water column heights in the time series report	
	1 11 000	Delayed replication of 11 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 33 002	Quality information	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	0 25 025	Battery voltage	
	0 25 025	Battery voltage	
	0 25 026	Battery voltage (large range)	
	0 22 185	BPR transmission count	
	0 04 015	Time increment	
	0 04 065	Short time increment	
	1 01 004	Replicate 1 descriptor 4 times	
	0 22 182	Water column height	

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 031	3 06 027	(Sequence for representation of DART buoy tsunami event reports and extended tsunami event reports) Sequence for representation of DART buoy identification, transmitter ID, type of tsunameter and the time the message is transmitted to the ground system	<p>Message status Time when tsunami is detected</p> <p>Reference date/time for the time series</p> <p>Determination of actual value reported in the time series Added to reset the reference time Added to each data value in the time series</p>
	3 06 029	Sequence for representation of tsunameter sampling information for water column heights in the time series report	
	0 01 053	Tsunameter report sequence number triggered by a tsunami event	
	0 33 002	Quality information	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	0 22 185	BPR transmission count	
	0 22 182	Water column height	
	0 04 016	Time increment	
	0 04 066	Short time increment	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 22 184	Water column height deviation from the reference value	
3 06 033	0 02 033	(Surface salinity) Method of salinity/depth measurement	
	0 07 063	Depth below sea/water surface (cm)	
	0 22 064	Salinity	
3 06 034	0 02 031	(Surface current) Duration and time of current measurement	
	0 03 010	Method of sea/water current measurement	
	0 02 040	Method of removing velocity and motion of platform from current	
	0 22 005	Direction of sea-surface current	
	0 22 032	Speed of sea-surface current	

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 035	1 12 000	(Temperature and salinity profile) Delayed replication of 12 descriptors	In metres = 13 Depth at a level = 10 Pressure at a level = 11 Temperature at a level = 12 Salinity at a level
	0 31 002	Extended delayed descriptor replication factor	
	0 07 062	Depth below sea/water surface	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 07 065	Water pressure	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 043	Sea/water temperature	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 064	Salinity	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
3 06 036	1 12 000	(Current profile) Delayed replication of 12 descriptors	In metres = 13 Depth at a level = 10 Pressure at a level = 14 Current speed at a level = 15 Current direction at a level
	0 31 002	Extended delayed descriptor replication factor	
	0 07 062	Depth below sea/water surface	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 07 065	Water pressure	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 031	Speed of current	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 004	Direction of current	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
3 06 037	1 09 000	(Dissolved oxygen profile data) Delayed replication of 9 descriptors	= 13 Depth at a level
	0 31 002	Extended delayed descriptor replication factor	
	0 07 062	Depth below sea / water surface	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 07 065	Water pressure	

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 037 (continued)	0 08 080	Qualifier for GTSP quality flag	= 10 Pressure at a level
	0 33 050	Global GTSP quality flag	
	0 22 188	Dissolved oxygen	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
3 06 038		(Sequence for representation of standard surface marine meteorological observations from moored buoys)	= 16 Dissolved oxygen at a level
	0 10 004	Pressure	
	0 10 051	Pressure reduced to mean sea level	
	0 07 033	Height of sensor above water surface	
	0 12 101	Temperature/air temperature	
	0 12 103	Dewpoint temperature	
	0 13 003	Relative humidity	
	0 07 033	Height of sensor above water surface	
	0 08 021	Time significance	
	0 04 025	Time period or displacement	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 08 021	Time significance	
	0 04 025	Time period or displacement	
	0 11 041	Maximum wind gust speed	
	0 04 025	Time period or displacement	
	0 07 033	Height of sensor above water surface	
	0 02 005	Precision of temperature observation	
	0 07 063	Depth below sea/water surface (cm)	
	0 22 049	Sea-surface temperature	
3 06 039		(Sequence for representation of basic wave measurements)	Height of air temperature/humidity sensor At observation height At observation height With respect to water at all temperatures Height of wind speed sensor = 2 Time averaged Period over which winds are averaged At observation height At observation height Set to missing (cancel) Time period over which maximum gust observed Set to missing (cancel) Set to missing (cancel)
	0 22 078	Duration of wave record	
	0 22 070	Significant wave height	
	0 22 073	Maximum wave height	

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 039 (continued)	0 22 074	Average wave period	
	0 22 071	Spectral peak wave period	
	0 22 076	Direction from which dominant waves are coming	
	0 22 077	Directional spread of dominant wave	
3 06 040		(Sequence for representation of detailed spectral wave measurements)	
	0 22 078	Duration of wave record	
	0 22 082	Maximum non-directional spectral wave density	
	1 06 000	Delayed replication of 6 descriptors	
	0 31 001	Delayed descriptor replication factor	Number of frequency bins
	0 22 080	Waveband central frequency	
	0 22 069	Spectral wave density	
	0 22 086	Mean direction from which waves are coming	
	0 22 087	Principal direction from which waves are coming	
	0 22 088	First normalized polar coordinate from Fourier coefficients	
3 06 041	0 22 089	Second normalized polar coordinate from Fourier coefficients	
		(Depth and temperature profile (high accuracy/precision))	
	0 02 032	Indicator for digitization	= 0 Fixed sensor depths
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	Number of depths
	0 07 062	Depth below sea/water surface	
3 06 042	0 22 043	Sea/water temperature	
		(Wind measurement from drifting buoy)	
	0 02 169	Anemometer type	E.g. = 2 WOTAN, = 3 Sonic anemometer
	0 07 033	Height of sensor above water surface	Height of anemometer above water surface or effective height for WOTAN
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	Averaging period in minutes
	0 11 001	Wind direction	At measurement height
	0 11 002	Wind speed	At measurement height

FM 94 BUFR

Category 06			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 06 043	0 41 001	(Marine biogeochemical and radiation observations) pCO ₂	Set to 3 (carbon dioxide)
	0 08 043	Atmospheric chemical or physical constituent type	
	0 15 028	Mole fraction of atmospheric constituent/pollutant in dry air	
	0 08 043	Atmospheric chemical or physical constituent type	Cancel
	0 13 080	Water pH	Set to -1 (preceding hour) Downwelling long-wave radiation Upwelling long-wave radiation
	0 41 005	Turbidity	
	0 41 003	Dissolved nitrates	
	0 22 188	Dissolved oxygen	
	0 41 002	Fluorescence	
	1 06 000	Delayed replication of 6 descriptors	
	0 31 000	Short delayed replication factor	
	0 04 024	Time period or displacement (hours)	
	0 14 002	Long-wave radiation, integrated over period specified	
	0 14 002	Long-wave radiation, integrated over period specified	
	0 14 012	Net long-wave radiation, integrated over period specified	
	0 14 004	Short-wave radiation, integrated over period specified	
	0 04 024	Time period or displacement (hours)	Cancel

Notes:

- (1) Range of value for parameter 0 04 015 limited from -99 to 99; CREX common sequence D 06 019 being the original sequence with 2 characters only for the corresponding descriptor.
- (2) This sequence is deprecated because of incorrect usage of descriptor 0 04 075; sequence 3 06 019 should be used instead.
- (3) This sequence is deprecated because of incorrect usage of descriptor 0 04 075 in sequence 3 06 020; sequence 3 06 025 should be used instead.

Category 07 – Surface report sequences (land)

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 001	3 01 031	(Low altitude station) Identification and type of station, date/time, location (high accuracy), height of station	Basic surface report
	3 02 011	Low altitude station	
3 07 002	3 01 032	(Low altitude station) Identification and type of station, date/time, location (coarse accuracy), height of station	Basic surface report
	3 02 011	Low altitude station	
3 07 003	3 07 001	(Low altitude station) Low altitude station	Location (high accuracy) and basic report
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 005	Cloud layer	
3 07 004	3 07 002	(Low altitude station) Low altitude station	Location (coarse accuracy) and basic report
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 005	Cloud layer	
3 07 005	3 07 001	(Low altitude station) Low altitude station	Location (high accuracy) and basic report
	1 01 004	Replicate 1 descriptor 4 times	
	3 02 005	Cloud layer	4 layers
3 07 006	3 07 002	(Low altitude station) Low altitude station	Location (coarse accuracy) and basic report
	1 01 004	Replicate 1 descriptor 4 times	
	3 02 005	Cloud layer	4 layers
3 07 007	3 01 031	(High altitude station) Identification and type of station, date/time, location (high accuracy), height of station	Basic surface report
	3 02 012	High altitude station	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 008	3 01 032	(High altitude station) Identification and type of station, date/time, location (coarse accuracy), height of station	Basic surface report
	3 02 012	High altitude station	
3 07 009	3 01 031	Identification and type of station, date/time, location (high accuracy), height of station	
	3 02 013	Basic surface report	
3 07 011	0 01 063	(Main part of data for representation of METAR/SPECI code in BUFR) ICAO location indicator	YY GG, gg
	0 02 001	Type of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 024	Latitude/longitude (coarse accuracy), height of station	Height of an anemometer
	0 07 006	Height above station	
	0 11 001	Wind direction	
	0 11 016	Extreme counterclockwise wind direction of a variable wind	
	0 11 017	Extreme clockwise wind direction of a variable wind	Height of a thermometer
	0 11 002	Wind speed	
	0 11 041	Maximum wind gust speed	
	0 07 006	Height above station	
	0 12 001	Temperature/air temperature	Up to 3
	0 12 003	Dewpoint temperature	
	0 10 052	Altimeter setting (QNH)	
	0 20 009	General weather indicator (TAF/METAR)	
3 07 012	1 03 000	(Horizontal visibility) Delayed replication of 3 descriptors	Direction of visibility observed
	0 31 001	Delayed descriptor replication factor	
	0 08 023	First-order statistics	
	0 05 021	Bearing or azimuth	
	0 20 001	Horizontal visibility	Up to 4
3 07 013	1 06 000	(Runway visual range) Delayed replication of 6 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 01 064	Runway designator	
	0 08 014	Qualifier for runway visual range	
	0 20 061	Runway visual range (RVR)	
	0 08 014	Qualifier for runway visual range	
	0 20 061	Runway visual range (RVR)	
	0 20 018	Tendency of runway visual range	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 014	1 01 000	(Significant present or forecast weather) Delayed replication of 1 descriptor	Up to 3
	0 31 001	Delayed descriptor replication factor	
	0 20 019	Significant present or forecast weather	
3 07 015		(Clouds group(s))	N _s N _s N _s , CC, h _s h _s h _s
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 005	Cloud layer	
3 07 016	0 20 002	Vertical visibility	Up to 3
		(Significant recent weather phenomena)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
3 07 017	0 20 020	Significant recent weather phenomena	Up to 3
		(Wind shear on runway(s))	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
3 07 018	0 11 070	Designator of the runway affected by wind shear (including ALL)	Up to 2 FM, TL, AT GG, gg Up to 1 Up to 1 w'w'
		(Trend-type landing forecast)	
	0 08 016	Change qualifier of a trend-type forecast or an aerodrome forecast	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 017	Qualifier of the time when the forecast change is expected	
	3 01 012	Hour, minute	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 006	Height above station	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 11 041	Maximum wind gust speed	
	0 20 009	General weather indicator (TAF/METAR)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 20 001	Horizontal visibility	
	3 07 014	Significant present or forecast weather	
3 07 020		(Short METAR/SPECI)	w'w' REw'w'
	3 07 011	Main part of data for representation of METAR/SPECI code in BUFR	
	3 07 014	Significant present or forecast weather	
	3 07 016	Significant recent weather phenomena	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 021	3 07 011	(Total sequence for representation of METAR/SPECI code in BUFR)	
	3 07 012	Main part of data for representation of METAR/SPECI code in BUFR	
	3 07 013	Horizontal visibility	D _V VVVV
	3 07 014	Runway visual range	D _R D _R /V _R V _R V _R V _R
	3 07 015	Significant present or forecast weather	w'w'
	3 07 016	Clouds group(s)	
	3 07 017	Significant recent weather phenomena	REw'w'
	3 07 018	Wind shear on runway(s)	
	3 07 019	Trend-type landing forecast	
3 07 022	3 07 015	Clouds group(s)	
		(Ground-based GNSS data)	
	0 01 015	Station or site name	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 022	Latitude/longitude (high accuracy), height of station	
	0 08 021	Time significance	= 23 Monitoring period
	0 04 025	Time period or displacement	
	0 10 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 13 003	Relative humidity	
	0 33 038	Quality flags for ground-based GNSS data	
	0 08 022	Total number (with respect to accumulation or average)	Number of GNSS satellites used
	1 06 025	Replicate 6 descriptors 25 times	
	0 02 020	Satellite classification	
	0 01 050	Platform transmitter ID number	
	0 05 021	Bearing or azimuth	
	0 07 021	Elevation	
	0 15 031	Atmospheric path delay in satellite signal	
	0 15 032	Estimated error in atmospheric path delay	
	0 08 060	Sample scanning mode significance	= 5 North/South
	0 15 033	Difference in path delays for limb views at extremes of scan	
	0 15 034	Estimated error in path delay difference	
	0 08 060	Sample scanning mode significance	= 6 East/West
	0 15 033	Difference in path delays for limb views at extremes of scan	
	0 15 034	Estimated error in path delay difference	
	0 15 035	Component of zenith path delay due to water vapour	
	2 01 131	Change data width	
	2 02 129	Change scale	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 022 (continued)	0 13 016	Precipitable water	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 15 011	Log ₁₀ of integrated electron density	
3 07 024		(Ground-based GNSS data – slant total delay)	
	3 01 150	WIGOS identifier	
	0 01 015	Station or site name	
	0 01 040	Processing centre ID code	GNSS processing centre
	0 08 021	Time significance	= 30 Time of occurrence
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 022	Latitude/longitude (high accuracy), height of station	
	0 10 036	Geoid undulation	Geoid height above WGS-84 ellipsoid, ±150 m to 1 cm
	0 25 061	Software identification and version number	GNSS processing software, software version
	0 10 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 13 003	Relative humidity	
		<i>Zenith total delay</i>	
	1 20 000	Delayed replication of 20 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 25 060	Software identification	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	
	1 15 000	Delayed replication of 15 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 15 079	Zenith path delay due to neutral atmosphere	
	0 15 080	Estimated error in neutral atmosphere zenith path delay	
	0 08 022	Total number (with respect to accumulation or average)	
	0 33 093	Extended quality flags for ground-based GNSS data	
	0 15 089	Zenith path delay due to neutral hydrostatic atmosphere	
	0 15 035	Component of zenith path delay due to water vapour	
	1 02 002	Replicate 2 descriptors 2 times	
	0 08 060	Sample scanning mode significance	= 5 north/south or =6 east/west
	0 15 083	GNSS-derived neutral atmosphere gradient	
	2 01 131	Change data width	
	2 02 129	Change scale	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 024 (continued)	0 13 016	Precipitable water	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 15 011	Log ₁₀ of integrated electron density <i>Slant total delay</i>	
	1 31 000	Delayed replication of 31 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 25 060	Software identification	
	0 08 021	Time significance	Set to missing
	0 04 025	Time period or displacement	= 0
	0 33 093	Extended quality flags for ground-based GNSS data	
	1 25 000	Delayed replication of 25 descriptors	
	0 31 001	Delayed descriptor replication factor	Number of GNSS satellites used
	0 02 020	Satellite classification	
	0 01 050	Platform transmitter ID number	
	0 01 150	Coordinate reference system	= 5 ECF coordinate system
	2 02 127	Change scale	
	3 04 030	Location of platform	
	2 02 000	Change scale	
	0 05 021	Bearing or azimuth	
	0 07 021	Elevation	
	0 15 038	Path delay due to neutral atmosphere	
	0 15 039	Estimated error in neutral atmosphere path delay	
	0 15 090	Path delay due to neutral hydrostatic atmosphere	
	0 15 081	Wet path delay due to neutral atmosphere	
	0 15 082	Path-integrated water vapour	
	0 15 079	Zenith path delay due to neutral atmosphere	
	0 15 089	Zenith path delay due to neutral hydrostatic atmosphere	
	0 15 035	Component of zenith path delay due to water vapour	
	1 02 002	Replicate 2 descriptors 2 times	
	0 08 060	Sample scanning mode significance	= 5 north/south or = 6 east/west
	0 15 083	GNSS-derived neutral atmosphere gradient	
	0 15 084	GNSS least squares residual	
	0 15 085	GNSS multi-path delay	
	0 15 086	GNSS hydrostatic mapping function	
	0 15 087	GNSS wet mapping function	
	0 15 088	GNSS gradient mapping function	
	0 15 011	Log ₁₀ of integrated electron density	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 030	0 15 001	(Ozone data – single observation) Total ozone	
	0 15 002	Air mass (slant path at 22 km)	
3 07 031	0 08 022	(Ozone data – averaged observations) Total number (with respect to accumulation or average)	Number of measurements
	0 08 023	First-order statistics	= 4 Mean value
	0 15 001	Total ozone	Average value of ozone measurement
	0 08 023	First-order statistics	= 9 Best estimate of standard deviation
	0 15 001	Total ozone	Best estimate of standard deviation of the ozone measurement
	0 08 023	First-order statistics	= 11 Harmonic mean
	0 15 002	Air mass (slant path at 22 km)	Harmonic mean value of the air- mass
3 07 041	3 01 001	(Total ozone measurement from a Brewer ground-based spectrophotometer obtained from a single observation) WMO block and station numbers	
	0 01 015	Station or site name	
	3 01 024	Latitude/longitude (coarse accuracy), height of station	
	3 01 011	Year, month, day	Ozone measurement
	3 01 012	Hour, minute	Ozone measurement
	3 01 070	Ozone instrumentation – Brewer spectrophotometer	
	3 07 030	Ozone data – single observation	
3 07 042	3 01 001	(Total ozone measurement from a Brewer ground-based spectrophotometer obtained from averaged observations) WMO block and station numbers	
	0 01 015	Station or site name	
	3 01 024	Latitude/longitude (coarse accuracy), height of station	
	3 01 011	Year, month, day	Ozone measurement
	3 01 012	Hour, minute	Ozone measurement
	0 08 021	Time significance	= 8 Ensemble mean

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 042 (continued)	0 04 025	Time period or displacement	Time period (minutes) for the computation of the average
	3 01 070	Ozone instrumentation – Brewer spectrophotometer	
	3 07 031	Ozone data – averaged observations	
3 07 043		(Total ozone measurement from a Dobson ground-based spectrophotometer obtained from a single observation)	Ozone measurement Ozone measurement
	3 01 001	WMO block and station numbers	
	0 01 015	Station or site name	
	3 01 024	Latitude/longitude (coarse accuracy), height of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 074	Ozone instrumentation – Dobson spectrophotometer	
	3 07 030	Ozone data – single observation	
3 07 044		(Total ozone measurement from a Dobson ground-based spectrophotometer obtained from averaged observations)	Ozone measurement Ozone measurement = 8 Ensemble mean Time period (minutes) for the computation of the average
	3 01 001	WMO block and station numbers	
	0 01 015	Station or site name	
	3 01 024	Latitude/longitude (coarse accuracy), height of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	0 08 021	Time significance	
	0 04 025	Time period or displacement	
	3 01 074	Ozone instrumentation – Dobson spectrophotometer	
	3 07 031	Ozone data – averaged observations	
3 07 045		(Main part of METAR/SPECI), replacing 3 07 011	CCCC METAR SPECI COR AUTO YY GGgg
	0 01 063	ICAO location indicator	
	0 08 079	Product status	
	0 02 001	Type of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 023	Latitude/longitude (coarse accuracy)	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 045 (continued)	0 07 030	Height of station ground above mean sea level	
	0 07 031	Height of barometer above mean sea level	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	= 10 m (if the actual value is not available)
	0 11 001	Wind direction	ddd
	0 11 016	Extreme counterclockwise wind direction of a variable wind	d _n d _n d _n
	0 11 017	Extreme clockwise wind direction of a variable wind	d _x d _x d _x
	0 08 054	Qualifier for wind speed or wind gusts	P
	0 11 083	Wind speed (see Note 1)	ff – km/h
	0 11 084	Wind speed (see Note 1)	ff – kt
	0 11 002	Wind speed (see Note 1)	ff – m/s
	0 08 054	Qualifier for wind speed or wind gusts	P
	0 11 085	Maximum wind gust speed (see Note 2)	f _m f _m – km/h
	0 11 086	Maximum wind gust speed (see Note 2)	f _m f _m – kt
	0 11 041	Maximum wind gust speed (see Note 2)	f _m f _m – m/s
	0 08 054	Qualifier for wind speed or wind gusts	Set to missing (cancel)
	0 07 032	Height of sensor above local ground (or deck of marine platform)	= 2 m (if the actual value is not available)
	0 12 023	Temperature	T'T' – Celsius
	0 12 024	Dewpoint temperature	T' _d T' _d – Celsius
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 10 052	Altimeter setting (QNH)	QP _H PHPH _H
	0 20 009	General weather indicator (TAF/METAR)	CAVOK
		(METAR/SPECI visibility)	
3 07 046	0 20 060	Prevailing horizontal visibility	VVVV or VVVVNDV
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	Up to 2
	0 05 021	Bearing or azimuth	Direction of minimum visibility observed D _v
	0 20 059	Minimum horizontal visibility	V _N V _N V _N V _N
3 07 047		(METAR/SPECI/TAF clouds), replacing 3 07 015	
	1 05 000	Delayed replication of 5 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 002	Vertical significance (surface observations)	
	0 20 011	Cloud amount	N _s N _s N _s
	0 20 012	Cloud type	CC

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 047 (continued)	0 20 013	Height of base of cloud	$h_s h_s h_s - m$
	0 20 092	Height of base of cloud	$h_s h_s h_s - ft$
	0 20 002	Vertical visibility	$VV h_s h_s h_s - m$
	0 20 091	Vertical visibility	$VV h_s h_s h_s - ft$
3 07 048		(Trend type forecast), replacing 3 07 018	
	0 08 016	Change qualifier of a trend-type forecast or an aerodrome forecast	TTTTT NOSIG
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	= 0, 1 or 2
	0 08 017	Qualifier of the time when the forecast change is expected	TT
	3 01 012	Hour, minute	GGgg
	1 12 000	Delayed replication of 12 descriptors	
	0 31 000	Short delayed descriptor replication factor	= 0 or 1
	0 07 032	Height of sensor above local ground (or deck of marine platform)	= 10 m (if the actual value is not available)
	0 11 001	Wind direction	ddd
	0 08 054	Qualifier for wind speed or wind gusts	P
	0 11 083	Wind speed (see Note 1)	ff – km/h
	0 11 084	Wind speed (see Note 1)	ff – kt
	0 11 002	Wind speed (see Note 1)	ff – m/s
	0 08 054	Qualifier for wind speed or wind gusts	P
	0 11 085	Maximum wind gust speed (see Note 2)	$f_m f_m - km/h$
	0 11 086	Maximum wind gust speed (see Note 2)	$f_m f_m - kt$
	0 11 041	Maximum wind gust speed (see Note 2)	$f_m f_m - m/s$
	0 08 054	Qualifier for wind speed or wind gusts	Set to missing (cancel)
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 20 009	General weather indicator (TAF/METAR)	CAVOK NSW NSC
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	= 0 or 1
	0 20 060	Prevailing horizontal visibility	VVVV
	3 07 014	Significant present and forecast weather	Weather intensity and phenomena $w'w'$
3 07 049	3 07 047	METAR/SPECI/TAF clouds, replacing 3 07 015	$N_s N_s N_s h_s h_s h_s$
		(Sea conditions)	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	= 0 or 1
	0 22 043	Sea/water temperature	$T_s T_s$
	0 22 021	Height of waves	S'

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 050	1 01 000	(Runway state) Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	= 0 or 1
	0 20 085	General condition of runway	SNOCLO
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 01 064	Runway designator	D _R D _R
	0 20 085	General condition of runway	CLRD//
	1 05 000	Delayed replication of 5 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 01 064	Runway designator	D _R D _R
	0 20 086	Runway deposits	E _R
	0 20 087	Runway contamination	C _R
	0 20 088	Depth of runway deposits	e _R e _R
	0 20 089	Runway friction coefficient	B _R B _R
		(Full METAR/SPECI), replacing 3 07 021	
3 07 051	3 07 045	Main part of METAR/SPECI, replacing 3 07 011	
	3 07 046	METAR/SPECI visibility	VVVV or VVVVNDV V _N V _N V _N V _N D _V
	3 07 013	Runway visual range	RD _R D _R /V _R V _R V _R V _R
	3 07 014	Significant present and forecast weather	Weather intensity and phenomena w'w'
	3 07 047	METAR/SPECI/TAF clouds, replacing 3 07 015	N _s N _s N _s h _s h _s h _s
	3 07 016	Significant recent weather phenomena	REw'w'
	3 07 017	Wind shear on runway(s)	WS RD _R D _R
	3 07 049	Sea conditions	WT _s T _s /SS'
	3 07 050	Runway state	RD _R D _R / E _R C _R e _R e _R B _R B _R
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	= 0 to 3 normally
	3 07 048	Trend type forecast, replacing 3 07 018	
		(Aerodrome forecast identification and time interval)	
	0 01 063	ICAO location indicator	CCCC
3 07 052	0 08 039	Time significance (aviation forecast)	= 0 Issue time of forecast
	3 01 011	Year, month, day	YY
	3 01 012	Hour, minute	GGgg
	0 08 079	Product status	COR CNL AMD NIL
	0 08 039	Time significance (aviation forecast)	= 1 Time of commencement of period of the forecast

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 052 (continued)	3 01 011	Year, month, day	Y ₁ Y ₁
	3 01 012	Hour, minute	G ₁ G ₁
	0 08 039	Time significance (aviation forecast)	= 2 Time of ending of period of the forecast
	3 01 011	Year, month, day	Y ₂ Y ₂
	3 01 012	Hour, minute	G ₂ G ₂
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 07 030	Height of station ground above mean sea level	
3 07 053	0 07 031	Height of barometer above mean sea level	
		(Forecast weather at an aerodrome)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	= 10 m (if the actual value is not available)
	0 11 001	Wind direction	ddd
	0 08 054	Qualifier for wind speed or wind gusts	P
	0 11 083	Wind speed (see Note 1)	ff – km/h
	0 11 084	Wind speed (see Note 1)	ff – kt
	0 11 002	Wind speed (see Note 1)	ff – m/s
	0 08 054	Qualifier for wind speed or wind gusts	P
	0 11 085	Maximum wind gust speed (see Note 2)	f _m f _m – km/h
	0 11 086	Maximum wind gust speed (see Note 2)	f _m f _m – kt
	0 11 041	Maximum wind gust speed (see Note 2)	f _m f _m – m/s
	0 08 054	Qualifier for wind speed or wind gusts	Set to missing (cancel)
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 20 009	General weather indicator (TAF/METAR)	CAVOK NSW NSC
	0 20 060	Prevailing horizontal visibility	VVVV
	3 07 014	Significant present and forecast weather	w'w'
	3 07 047	METAR/SPECI/TAF clouds, replacing 3 07 015	N _s N _s N _s h _s h _s h _s
		(Forecast of extreme temperatures)	
3 07 054	0 07 032	Height of sensor above local ground (or deck of marine platform)	= 2 m (if the actual value is not available)
	0 08 039	Time significance (aviation forecast)	= 3 Forecast time of maximum temperature
	0 04 003	Day	
	0 04 004	Hour	G _F G _F
	0 08 023	First-order statistics	= 3 Minimum
	0 12 023	Temperature	T _F T _F – Celsius
	0 08 039	Time significance (aviation forecast)	= 4 Forecast time of minimum temperature

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 054 (continued)	0 04 003	Day	
	0 04 004	Hour	G _F G _F
	0 08 023	First-order statistics	= 2 Maximum
	0 12 023	Temperature	T _F T _F – Celsius
	0 08 023	First-order statistics	Set to missing (cancel)
3 07 055	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		(Change indicator and forecast changes)	
	0 33 045	Probability of following event	C ₂ C ₂
	0 08 016	Change qualifier of a trend-type forecast or an aerodrome forecast	TTTTTT
	0 08 039	Time significance (aviation forecast)	= 5 Time of beginning of the forecast change
	0 04 003	Day	
	3 01 012	Hour, minute	GGgg
	0 08 039	Time significance (aviation forecast)	= 6 Time of ending of the forecast change
	0 04 003	Day	
	3 01 012	Hour, minute	G _e G _e
3 07 056	3 07 053	Forecast weather at an aerodrome	During or after change
		(Aerodrome forecast – full TAF)	
	3 07 052	Aerodrome forecast identification and time interval	
	3 07 053	Forecast weather at an aerodrome	
	3 07 054	Forecast of extreme temperatures	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 07 055	Change indicator and forecast changes	
3 07 060		(Soil temperature below land surface)	
	0 07 061	Depth below land surface	
	0 12 030	Soil temperature	
3 07 061		(Soil temperature data at number of depths not exceeding five – high accuracy position)	
	3 01 031	Identification and type of station, date/time, location (high accuracy), height of station	
	1 01 005	Replicate 1 descriptor 5 times	
	3 07 060	Soil temperature below land surface	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 062	3 01 032	(Soil temperature data at number of depths not exceeding five – coarse accuracy position)	
	1 01 005	Identification and type of station, date/time, location (coarse accuracy), height of station	
	3 07 060	Replicate 1 descriptor 5 times	
3 07 063		Soil temperature below land surface	
		(Depth below land surface and soil temperature)	
	0 07 061	Depth below land surface	Scale: 2
3 07 071	0 12 130	Soil temperature	
		(Monthly values of a land station)	
	3 01 090	Surface station identification; time, horizontal and vertical coordinates (see Note 3)	
	0 04 074	Short time period or displacement (see Note 3)	= UTC – LT
	0 04 023	Time period or displacement	Number of days in the month
		<i>Monthly mean values of pressure, temperature, extreme temperatures and vapour pressure</i>	
	0 08 023	First-order statistics	= 4 Mean value
	0 10 004	Pressure	
	0 10 051	Pressure reduced to mean sea level	
	0 07 004	Pressure	Standard level Set to missing for lowland stations
	0 10 009	Geopotential height	Standard level Set to missing for lowland stations
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 4)	
	0 12 101	Temperature/air temperature	
	0 02 051	Indicator to specify observing method for extreme temperatures	
	0 04 051	Principal time of daily reading of maximum temperature	
	0 12 118	Maximum temperature at height specified, past 24 hours	
	0 04 052	Principal time of daily reading of minimum temperature	
	0 12 119	Minimum temperature at height specified, past 24 hours	
	0 13 004	Vapour pressure	
	0 08 023	First-order statistics	Set to missing
	0 12 151	Standard deviation of daily mean temperature	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	1 02 005	Replicate 2 descriptors 5 times	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 071 (continued)	0 08 050	Qualifier for number of missing values in calculation of statistic = 1 Pressure, = 2 Temperature, = 4 Vapour pressure, = 7 Maximum temperature, = 8 Minimum temperature	/see left column
	0 08 020	Total number of missing entities (with respect to accumulation or average) <i>Sunshine duration</i>	Days
	0 14 032	Total sunshine	
	0 14 033	Total sunshine	
	0 08 050	Qualifier for number of missing values in calculation of statistic	= 6 Sunshine duration
	0 08 020	Total number of missing entities (with respect to accumulation or average) <i>Number of days of occurrence</i>	Days
	1 02 018	Replicate 2 descriptors 18 times	
	0 08 052	Condition for which number of days of occurrence follows	
	0 08 022	Total number (with respect to accumulation or average) <i>Occurrence of extreme values of temperature and wind speed</i>	Days
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 4)	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 12 152	Highest daily mean temperature	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 12 153	Lowest daily mean temperature	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 08 023	First-order statistics	= 2 Maximum value
	0 12 101	Temperature/air temperature	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 08 023	First-order statistics	= 3 Minimum value
	0 12 101	Temperature/air temperature	
	0 08 023	First-order statistics	Set to missing
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 4)	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 071 (continued)	0 02 002	Type of instrumentation for wind measurement	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 11 046	Maximum instantaneous wind speed	
	0 08 053	Day of occurrence qualifier	Set to missing (cancel)
		<i>Precipitation</i>	
	0 04 003	Day (see Note 5)	= 1
	0 04 004	Hour (see Note 5)	= 6
	0 04 023	Time period or displacement (see Note 5)	Number of days in the month
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 4)	
	0 13 060	Total accumulated precipitation	
	0 13 051	Frequency group, precipitation	
	0 04 053	Number of days with precipitation equal to or more than 1 mm	
	0 08 050	Qualifier for number of missing values in calculation of statistic	= 5 Precipitation
	0 08 020	Total number of missing entities (with respect to accumulation or average)	Days
		<i>Number of days of occurrence</i>	
	1 02 006	Replicate 2 descriptors 6 times	
	0 08 052	Condition for which number of days of occurrence follows	
	0 08 022	Total number (with respect to accumulation or average)	Days
		<i>Occurrence of extreme precipitation</i>	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 13 052	Highest daily amount of precipitation	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		(Monthly normals for a land station)	
3 07 072	0 04 001	Year	Beginning of the reference period
	0 04 001	Year	Ending of the reference period
	0 04 002	Month	
	0 04 003	Day (see Note 3)	= 1
	0 04 004	Hour (see Note 3)	= 0
	0 04 074	Short time period or displacement (see Note 3)	= UTC - LT
	0 04 022	Time period or displacement	= 1

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 072 (continued)		<i>Normals of monthly mean pressure, temperature, vapour pressure and of standard deviation</i>	
	0 08 023	First-order statistics	= 4 Mean value
	0 10 004	Pressure	
	0 10 051	Pressure reduced to mean sea level	
	0 07 004	Pressure	Standard level
	0 10 009	Geopotential height	Standard level
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 4)	
	0 12 101	Temperature/air temperature	
	0 02 051	Indicator to specify observing method for extreme temperatures	= 2
	0 04 051	Principal time of daily reading of maximum temperature	
	0 12 118	Maximum temperature at height specified, past 24 hours	
	0 04 052	Principal time of daily reading of minimum temperature	
	0 12 119	Minimum temperature at height specified, past 24 hours	
	0 13 004	Vapour pressure	
	0 12 151	Standard deviation of daily mean temperature	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		<i>Normal of sunshine duration</i>	
	0 14 032	Total sunshine	
	0 08 023	First-order statistics	Set to missing
		<i>Normals of precipitation</i>	
	0 04 001	Year	Beginning of the reference period
	0 04 001	Year	Ending of the reference period
	0 04 002	Month	
	0 04 003	Day (see Note 5)	= 1
	0 04 004	Hour (see Note 5)	= 6
	0 04 022	Time period or displacement	= 1
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 4)	
	0 08 023	First-order statistics	= 4 Mean value
	0 13 060	Total accumulated precipitation	
	0 04 053	Number of days with precipitation equal to or more than 1 mm	
	0 08 023	First-order statistics	Set to missing
	1 02 008	Replicate 2 descriptors 8 times	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 072 (continued)	0 08 050	Qualifier for number of missing values in calculation of statistic (see Note 6) = 1 Pressure, = 2 Temperature, = 3 Extreme temperature, = 4 Vapour pressure, = 5 Precipitation, = 6 Sunshine duration, = 7 Maximum temperature, = 8 Minimum temperature	/see left column
	0 08 020	Total number of missing entities (with respect to accumulation or average) (see Note 6)	Years
3 07 073	3 07 071	(Representation of CLIMAT data of the actual month and for monthly normals) Monthly values of a land station	
	3 07 072	Monthly normals for a land station	
3 07 074		(Supplemental daily temperature and precipitation values for monthly climate report)	
	3 01 001	WMO block and station numbers	
	0 04 001	Year	
	0 04 002	Month	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	1 12 000	Delayed replication of 12 descriptors	
	0 31 001	Delayed descriptor replication factor	Set to the number of days in the particular month for which data are being reported
	0 04 003	Day	
	0 04 004	Hour	
	0 04 024	Time period or displacement	Typically set to -24 to denote the time period beginning 24 hours prior to and ending at the specified time
	1 02 003	Replicate 2 descriptors 3 times	
	0 08 023	First-order statistics = 2 Daily maximum temperature, = 3 Daily minimum temperature, = 4 Daily mean temperature	/see left column
	0 12 101	Temperature/air temperature	
	0 08 023	First-order statistics	Set to missing (cancel)
	0 04 004	Hour	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 074 (continued)	0 04 024	Time period or displacement	
	0 13 060	Total accumulated precipitation	
	0 13 012	Depth of fresh snow	
	0 13 013	Total snow depth	
3 07 075		(Supplemental daily temperature and precipitation values with the time of occurrence for monthly climate report)	
	3 01 150	WIGOS identifier	
	3 01 001	WMO block and station number	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 08 095	Siting and measurement quality classification for temperature	
	0 08 096	Siting and measurement quality classification for precipitation	
	0 08 094	Method used to calculate the average daily temperature	
	3 01 011	Year, month, day	
		<i>Total accumulated precipitation</i>	
	0 04 023	Time period or displacement	= 0 when beginning time of the period is on the same day as reference date = -1 when beginning time of the period is on the day before reference date
	3 01 013	Hour, minute, second	Beginning time of the period
	2 04 008	Add associated field	8 bits long
	0 31 021	Associated field significance	Set as 5 for 8-bit indicator of quality control
	0 13 060	Total accumulated precipitation	
	2 04 000	Add associated field	Cancel
		<i>Depth of fresh snow</i>	
	0 04 023	Time period or displacement	= 0 when beginning time of the period is on the same day as reference date = -1 when beginning time of the period is on the day before reference date
	3 01 013	Hour, minute, second	Beginning time of the period
	2 04 008	Add associated field	8 bits long

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 075 (continued)	0 31 021	Associated field significance	Set as 5 for 8-bit indicator of quality control
	0 13 012	Depth of fresh snow	
	2 04 000	Add associated field	Cancel
		<i>Total snow depth</i>	
	0 04 023	Time period or displacement	= 0 when beginning time of the period is on the same day as reference date = -1 when beginning time of the period is on the day before reference date
	3 01 013	Hour, minute, second	Beginning time of the period
	2 04 008	Add associated field	8 bits long
	0 31 021	Associated field significance	Set as 5 for 8-bit indicator of quality control
	0 13 013	Total snow depth	
	2 04 000	Add associated field	Cancel
		<i>Max, min, mean temperature</i>	
	0 07 032	Height of sensor above local ground	For temperature measurement
	1 07 003	Replicate 7 descriptors 3 times	
	0 04 023	Time period or displacement	= 0 when beginning time of the period is on the same day as reference date = -1 when beginning time of the period is on the day before reference date
	3 01 013	Hour, minute, second	Beginning time of the period
	0 08 023	First-order statistics	2 – maximum; 3 – minimum; 4 – mean
	2 04 008	Add associated field	8 bits long
	0 31 021	Associated field significance	Set as 5 for 8-bit indicator of quality control
	0 12 101	Temperature/air temperature	
	2 04 000	Add associated field	Cancel
	0 08 023	First-order statistics	Set as missing value

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 076	3 01 090	(Monthly values from a land station in compliance with regional or national reporting practices)	
	0 04 074	Surface station identification; time, horizontal and vertical coordinates	
	0 04 023	Short time period or displacement	Number of days in the month
		Time period or displacement	
		<i>Monthly mean values of pressure, temperature, extreme temperatures and vapour pressure</i>	
	0 08 023	First-order statistics	= 4 Mean value
	0 10 004	Pressure	
	0 10 051	Pressure reduced to mean sea level	
	0 07 004	Pressure	Standard level Set to missing for lowland stations
	0 10 009	Geopotential height	Standard level Set to missing for lowland stations
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 12 101	Temperature/air temperature	
	0 02 051	Indicator to specify observing method for extreme temperatures	
	0 04 051	Principal time of daily reading of maximum temperature	
	0 12 118	Maximum temperature at height specified, past 24 hours	
	0 04 052	Principal time of daily reading of minimum temperature	
	0 12 119	Minimum temperature at height specified, past 24 hours	
	0 13 004	Vapour pressure	
	0 08 023	First-order statistics	Set to missing (cancel)
	0 12 151	Standard deviation of daily mean temperature	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		<i>Number of days for which values are missing</i>	
	1 02 005	Replicate 2 descriptors 5 times	
	0 08 050	Qualifier for number of missing values in calculation of statistic = 1 Pressure, = 2 Temperature, = 4 Vapour pressure, = 7 Maximum temperature, = 8 Minimum temperature	/see left column
	0 08 020	Total number of missing entities (with respect to accumulation or average)	Days

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 076 (continued)		<i>Sunshine duration</i>	
	0 14 032	Total sunshine	
	0 14 033	Total sunshine	
	0 08 050	Qualifier for number of missing values in calculation of statistic	= 6 Sunshine duration
	0 08 020	Total number of missing entities (with respect to accumulation or average)	Days
		<i>Number of days of occurrence</i>	
	1 02 018	Replicate 2 descriptors 18 times	
	0 08 052	Condition for which number of days of occurrence follows Wind ≥ 10 m/s, wind ≥ 20 m/s, wind ≥ 30 m/s, maximum temperature < 273.15 K, maximum temperature ≥ 298.15 K, maximum temperature ≥ 303.15 K, maximum temperature ≥ 308.15 K, maximum temperature ≥ 313.15 K, minimum temperature < 273.15 K, sss > 0.00 m, sss > 0.01 m, sss > 0.10 m, sss > 0.50 m, horizontal visibility < 50 m, horizontal visibility < 100 m, horizontal visibility $< 1\ 000$ m, hail, thunderstorm	/see left column
	0 08 022	Total number (with respect to accumulation or average) <i>Occurrence of extreme values of temperature and wind speed</i>	Days
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 12 152	Highest daily mean temperature	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 12 153	Lowest daily mean temperature	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 08 023	First-order statistics	= 2 Maximum value
	0 12 101	Temperature/air temperature	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 08 023	First-order statistics	= 3 Minimum value
	0 12 101	Temperature/air temperature	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 076 (continued)	0 08 023	First-order statistics	Set to missing (cancel)
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 02 002	Type of instrumentation for wind measurement	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 11 046	Maximum instantaneous wind speed	
	0 08 053	Day of occurrence qualifier	Set to missing (cancel)
		<i>Precipitation</i>	
	0 04 003	Day	= 1
	0 04 004	Hour	= 0
	0 04 074	Short time period or displacement	
	0 04 023	Time period or displacement	Number of days in the month
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 13 060	Total accumulated precipitation	
	0 13 051	Frequency group, precipitation	
	0 04 053	Number of days with precipitation equal to or more than 1 mm	
	0 08 050	Qualifier for number of missing values in calculation of statistic	= 5 Precipitation
	0 08 020	Total number of missing entities (with respect to accumulation or average)	Days
		<i>Number of days of occurrence</i>	
	1 02 006	Replicate 2 descriptors 6 times	
	0 08 052	Condition for which number of days of occurrence follows	
	0 08 022	Total number (with respect to accumulation or average)	Days
		<i>Occurrence of extreme precipitation</i>	
	0 08 053	Day of occurrence qualifier	= 0 On 1 day only, = 1 On 2 or more days
	0 04 003	Day	
	0 13 052	Highest daily amount of precipitation	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		(Monthly normals for a land station in compliance with regional or national reporting practices)	
3 07 077	0 04 001	Year	Beginning of the reference period
	0 04 001	Year	Ending of the reference period

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 077 (continued)	0 04 002	Month	
	0 04 003	Day	= 1
	0 04 004	Hour	= 0
	0 04 074	Short time period or displacement	
	0 04 022	Time period or displacement	= 1
	0 08 023	First-order statistics	= 4 Mean value
	0 10 004	Pressure	
	0 10 051	Pressure reduced to mean sea level	
	0 07 004	Pressure	Standard level
	0 10 009	Geopotential height	Standard level
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 12 101	Temperature/air temperature	
	0 02 051	Indicator to specify observing method for extreme temperatures	
	0 04 051	Principal time of daily reading of maximum temperature	
	0 12 118	Maximum temperature at height specified, past 24 hours	
	0 04 052	Principal time of daily reading of minimum temperature	
	0 12 119	Minimum temperature at height specified, past 24 hours	
	0 13 004	Vapour pressure	
	0 12 151	Standard deviation of daily mean temperature	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 14 032	Total sunshine	
	0 08 023	First-order statistics	Set to missing (cancel)
		<i>Normals of precipitation</i>	
	0 04 001	Year	Beginning of the reference period
	0 04 001	Year	Ending of the reference period
	0 04 002	Month	
	0 04 003	Day	= 1
	0 04 004	Hour	= 0
	0 04 074	Short time period or displacement	
	0 04 022	Time period or displacement	= 1
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 08 023	First-order statistics	= 4 Mean value
	0 13 060	Total accumulated precipitation	
	0 04 053	Number of days with precipitation equal to or more than 1 mm	
	0 08 023	First-order statistics	Set to missing (cancel)
	1 02 008	Replicate 2 descriptors 8 times	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 077 (continued)	0 08 050	Qualifier for number of missing values in calculation of statistic Pressure, temperature, extreme temperatures, vapour pressure, precipitation, sunshine duration, maximum temperature, minimum temperature	/see left column
	0 08 020	Total number of missing entities (with respect to accumulation or average)	Years
3 07 078	3 07 076	(Sequence for representation of monthly values suitable for CLIMAT data in compliance with regional or national reporting practices) Monthly values from a land station in compliance with regional or national reporting practices	
	3 07 077	Monthly normals for a land station in compliance with regional or national reporting practices (Sequence for representation of synoptic reports from fixed land stations suitable for SYNOP data and for maritime data from coastal stations)	
3 07 079	3 01 090	Surface station identification; time, horizontal and vertical coordinates	
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 047	Direction of cloud drift	
	0 08 002	Vertical significance (surface observations)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 048	Direction and elevation of cloud	
	3 02 037	State of ground, snow depth, ground minimum temperature	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 22 061	State of the sea	
	0 20 058	Visibility seawards from a coastal station	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 056	Sea/water temperature	Sea/water surface temperature, method of measurement, depth below water surface
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 079 (continued)	3 02 055	Icing and ice	
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 046	Temperature change	
3 07 080		(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data)	
	3 01 090	Surface station identification; time, horizontal and vertical coordinates	
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	3 02 047	Direction of cloud drift	
	0 08 002	Vertical significance (surface observations)	
	3 02 048	Direction and elevation of cloud	
	3 02 037	State of ground, snow depth, ground minimum temperature	
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
	3 02 046	Temperature change	
		(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data in compliance with reporting practices in RA I)	
3 07 081	3 01 090	Surface station identification; time, horizontal and vertical coordinates	
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	3 02 047	Direction of cloud drift	
	0 08 002	Vertical significance (surface observations)	Set to missing (cancel)
	3 02 048	Direction and elevation of cloud	
	3 02 037	State of ground, snow depth, ground minimum temperature	
	0 12 122	Ground minimum temperature of the preceding night	
	0 13 056	Character and intensity of precipitation	
	0 13 057	Time of beginning or end of precipitation	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 081 (continued)	0 20 101	Locust (acridian) name	
	0 20 102	Locust (maturity) colour	
	0 20 103	Stage of development of locusts	
	0 20 104	Organization state of swarm or band of locusts	
	0 20 105	Size of swarm or band of locusts and duration of passage of swarm	
	0 20 106	Locust population density	
	0 20 107	Direction of movements of locust swarm	
	0 20 108	Extent of vegetation	
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
	3 02 046	Temperature change	
		(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data in compliance with reporting practices in RA II) (see Note 7)	
3 07 082	3 01 090	Surface station identification; time, horizontal and vertical coordinates	
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	3 02 047	Direction of cloud drift	
	0 08 002	Vertical significance (surface observations)	Set to missing (cancel)
	3 02 048	Direction and elevation of cloud	
	3 02 037	State of ground, snow depth, ground minimum temperature	
	0 12 121	Ground minimum temperature	At the time of observation
	0 12 122	Ground minimum temperature of the preceding night	
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
	3 02 046	Temperature change	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 083	3 01 090	(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data in compliance with reporting practices in RA III) Surface station identification; time, horizontal and vertical coordinates	Set to missing (cancel)
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	3 02 047	Direction of cloud drift	
	0 08 002	Vertical significance (surface observations)	
	3 02 048	Direction and elevation of cloud	
	3 02 037	State of ground, snow depth, ground minimum temperature	
	0 12 122	Ground minimum temperature of the preceding night	
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
	3 02 046	Temperature change	
		(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data in compliance with reporting practices in RA IV)	
3 07 084	3 01 090	Surface station identification; time, horizontal and vertical coordinates	Set to missing (cancel)
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	3 02 047	Direction of cloud drift	
	0 08 002	Vertical significance (surface observations)	
	3 02 048	Direction and elevation of cloud	
	3 02 037	State of ground, snow depth, ground minimum temperature	
	0 20 055	State of sky in the tropics	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	2 05 001	Signify character	Character field of 1 character
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
	3 02 046	Temperature change	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 086	3 01 090	(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data in compliance with reporting practices in RA VI) Surface station identification; time, horizontal and vertical coordinates	Set to missing (cancel)
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	0 08 002	Vertical significance (surface observations)	
	3 02 037	State of ground, snow depth, ground minimum temperature	
	3 02 066	Dangerous weather phenomena	
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
		("Instantaneous" parameters of sequence 3 07 089) <i>Surface station identification, time, horizontal and vertical coordinates</i>	
	3 01 001	WMO block and station numbers	
	0 02 001	Type of station	
3 07 087	3 01 011	Year, month, day	IIiii i _x YY GG, gg
	3 01 012	Hour, minute	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 07 031	Height of barometer above mean sea level <i>Pressure data</i>	
	3 02 001	Pressure and 3-hour pressure change	
	0 10 062	24-hour pressure change	
	0 07 004	Pressure	
	0 10 009	Geopotential height	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 087 (continued)		<i>Temperature and humidity</i>	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Temperature measurement
	0 12 101	Temperature/air temperature	$s_n TTT$ Scale: 2
	0 12 103	Dewpoint temperature	$s_n T_d T_d T_d$ Scale: 2
	0 13 003	Relative humidity	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		<i>Visibility</i>	
	0 20 001	Horizontal visibility	VV
		<i>Cloud data</i>	
	3 02 004	General cloud information	/see left column
		Cloud cover (total) N: If N = 9, then 0 20 010 = 113, if N = /, then 0 20 010 = missing Vertical significance: If C_L are observed, then 0 08 002 = 7 Low cloud: If C_L are not observed and C_M are observed, then 0 08 002 = 8 Middle cloud: If only C_H are observed, 0 08 002 = 0, if N = 9, then 0 08 002 = 5, if N = 0, then 0 08 002 = 62, if N = /, then 0 08 002 = missing Cloud amount (of low or middle clouds) N_h : If N = 0, then 0 20 011 = 0, if N = 9, then 0 20 011 = 9, if N = /, then 0 20 011 = missing Height of base of cloud h: If N = 0 or /, then 0 20 013 = missing Cloud type (low clouds) C_L : 0 20 012 = $C_L + 30$, if N = 0, then 0 20 012 = 30, if N = 9 or /, then 0 20 012 = 62 Cloud type (middle clouds) C_M : 0 20 012 = $C_M + 20$, if N = 0, then 0 20 012 = 20, if N = 9 or / or $C_M = /$, then 0 20 012 = 61 Cloud type (high clouds) C_H : 0 20 012 = $C_H + 10$, if N = 0, then 0 20 012 = 10, if N = 9 or / or $C_H = /$, then 0 20 012 = 60	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 02 005	Cloud layer	/see left column
		Vertical significance: In any C_b layer, 0 08 002 = 4, else in the first replication, if N = 9, then 0 08 002 = 5, if N = /, then 0 08 002 = missing, else 0 08 002 = 1, in the other replications 0 08 002 = 2, 3, 4 Cloud amount N_s : In the first replication, if N = /, then 0 20 011 = missing, else 0 20 011 = N_s , in the other replications 0 20 011 = N_s Cloud type C: If N = 9 or /, then 0 20 012 = missing, else 0 20 012 = C Height of base of cloud $h_s h_s$	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 088		("Period" parameters of sequence 3 07 089) <i>Present and past weather</i>	
	0 20 003	Present weather	ww
	0 04 024	Time period or displacement	= -6 at 00, 06, 12, 18 UTC, = -3 at 03, 09, 15, 21 UTC
	0 20 004	Past weather (1)	W ₁
	0 20 005	Past weather (2)	W ₂
		<i>Evaporation</i>	
	0 04 024	Time period or displacement	= -24 (hours)
	0 02 004	Type of instrumentation for evaporation measurement or type of crop for which evapotranspiration is reported	i _E
	0 13 033	Evaporation/evapotranspiration	EEE
		<i>Sunshine</i>	
	1 02 002	Replicate 2 descriptors 2 times	
	0 04 024	Time period or displacement	= -24 (hours) in the first replication, = -1 (hour) in the second replication
	0 14 031	Total sunshine	SSS in the first replication, SS in the second replication
		<i>Precipitation</i>	
	1 02 002	Replicate 2 descriptors 2 times	
	0 04 024	Time period or displacement	t _R
	0 13 011	Total precipitation/total water equivalent	RRR = 0 No precipitation, = -0.1 Trace
		<i>Extreme temperatures</i>	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Temperature measurement
	0 04 024	Time period or displacement	= -12 (hours)
	0 12 111	Maximum temperature, at height and over period specified	s _n T _x T _x T _x
	0 04 024	Time period or displacement	= -12 (hours)
	0 12 112	Minimum temperature, at height and over period specified	s _n T _n T _n T _n
		<i>Wind data</i>	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Wind measurement
	0 02 002	Type of instrumentation for wind measurement	i _w
	0 08 021	Time significance	= 2 Time averaged

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 088 (continued)	0 04 025	Time period or displacement	= -10 (minutes) or number of minutes after a significant change of wind, if any
	0 11 001	Wind direction	dd If dd = 00 Calm or dd = 99 Variable, 0 11 001 = 0
	0 11 002	Wind speed	ff
	0 08 021	Time significance	Set to missing (cancel)
3 07 089		(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data manually encoded in CREX)	
	3 07 087	"Instantaneous" parameters of sequence 3 07 089	
	3 07 088	"Period" parameters of sequence 3 07 089	
3 07 090		(Sequence for representation of synoptic reports from a mobile land station suitable for SYNOP MOBIL data)	
	3 01 092	Mobile surface station identification, date/time, horizontal and vertical coordinates	
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	3 02 047	Direction of cloud drift	
	0 08 002	Vertical significance (surface observations)	
	3 02 048	Direction and elevation of cloud	
	3 02 037	State of ground, snow depth, ground minimum temperature	
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
	3 02 046	Temperature change	
3 07 091		(BUFR template for surface observations from one-hour period with national and WMO station identification)	
	3 01 089	National station identification	
	3 01 090	Surface station identification; time, horizontal and vertical co-ordinates	
	0 08 010	Surface qualifier (temperature data)	
	3 01 091	Surface station instrumentation	
	3 02 001	Pressure and 3-hour pressure change	
	0 07 004	Pressure	Standard level
	0 10 009	Geopotential height	Standard level

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 091 (continued)	3 02 072	Temperature and humidity data	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	1 01 005	Replicate 1 descriptor 5 times	
	3 07 063	Depth below land surface and soil temperature	
	0 07 061	Depth below land surface	Set to missing (cancel)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 069	Visibility data	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 20 031	Ice deposit (thickness)	
	0 20 032	Rate of ice accretion (estimated)	
	0 02 038	Method of water temperature and/or salinity measurement	
	0 22 043	Sea/water temperature	Scale: 2
	3 02 021	Waves	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 078	State of ground and snow depth measurement	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 073	Cloud data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 074	Present and past weather	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 175	Intensity of precipitation, size of precipitation element	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -10 (minutes)
	3 02 076	Precipitation, obscuration and other phenomena	
	3 02 071	Wind data from one-hour period	
	3 02 077	Extreme temperature data	
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 079	Precipitation measurement	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 091 (continued)	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 080	Evaporation measurement	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 081	Total sunshine data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 082	Radiation data	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -10 (minutes)
	0 13 059	Number of flashes (thunderstorm)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 083	First-order statistics of P, W, T, U data	
	0 33 005	Quality information (AWS data)	
	0 33 006	Internal measurement status information (AWS)	
		(BUFR template for surface observations from n-minute period)	
3 07 092	3 01 150	WIGOS identifier	
	3 01 001	WMO block and station numbers	
	2 08 040	Change width of CCITT IA5 field	
	0 01 019	Long station or site name	40 characters
	2 08 000	Change width of CCITT IA5 field	
	3 01 011	Year, month, day	The time identification refers to the end of the n-minute period.
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 01 023	Observation sequence number	
	1 08 000	Delayed replication of 8 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 07 031	Height of barometer above mean sea level	
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 10 004	Pressure	Measured value of the air pressure at the sensor location and sensor height
	0 10 051	Pressure reduced to mean sea level	
	0 07 004	Pressure	Standard level

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 092 (continued)	0 10 009	Geopotential height	Standard level
	2 04 000	Add associated field	Cancel
	1 15 000	Delayed replication of 15 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 08 010	Surface qualifier (temperature data)	
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 12 101	Temperature/air-temperature	Scale: 2
	0 12 103	Dewpoint temperature	Scale: 2
	2 02 129	Change scale	
	2 01 132	Change data width	
	0 13 003	Relative humidity	Mandatory to report (presuming a humidity sensor is installed), data width 11 bits
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	0 13 009	Relative humidity	Original measured value
	2 04 000	Add associated field	Cancel
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 08 010	Surface qualifier (temperature data)	Set to missing (cancel)
	1 07 000	Delayed replication of 7 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 061	Depth below land surface	
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 12 130	Soil temperature	
	0 13 111	Soil moisture	
	2 04 000	Add associated field	Cancel
	0 07 061	Depth below land surface	Set to missing (cancel)
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 33 041	Attribute of following value	
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 20 001	Horizontal visibility	
	2 04 000	Add associated field	Cancel
	1 13 000	Delayed replication of 13 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 20 010	Cloud cover (total)	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 092 (continued)	2 04 000	Add associated field	Cancel
	1 07 000	Delayed replication of 7 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 002	Vertical significance (surface observations)	
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 20 011	Cloud amount	
	0 20 013	Height of base of cloud	
	2 04 000	Add associated field	Cancel
	0 08 002	Vertical significance (surface observations)	Set to missing (cancel)
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 20 062	State of ground (with or without snow)	
	0 13 013	Total snow depth	
	2 04 000	Add associated field	Cancel
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -n minutes
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 20 003	Present weather	
	2 04 000	Add associated field	Cancel
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -n minutes
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 13 011	Total precipitation/total water equivalent	Snow
	2 04 000	Add associated field	Cancel
	1 15 000	Delayed replication of 15 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	= -10 minutes, or number of minutes after a significant change of wind
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	2 04 000	Add associated field	Cancel
	0 08 021	Time significance	Set to missing (cancel)

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 092 (continued)	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
	2 04 000	Add associated field	Cancel
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -n minutes (default n = 10)
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 14 031	Total sunshine	
	2 04 000	Add associated field	Cancel
	1 10 000	Delayed replication of 10 descriptors	
	0 31 000	Short delayed descriptor replication factor	Open or close (1/0)
	0 04 025	Time period or displacement	= -n minutes (default n = 10)
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 14 002	Long-wave radiation, integrated over period specified	Upward long-wave radiation according to BUFR Table B, under Class 14, Note 2: negative values
	0 14 002	Long-wave radiation, integrated over period specified	Downward long-wave radiation according to BUFR Table B, under Class 14, Note 1: positive values
	0 14 004	Short-wave radiation, integrated over period specified	Upward short-wave radiation according to BUFR Table B, under Class 14, Note 2: negative values
	0 14 028	Global solar radiation (high accuracy), integrated over period specified	
	0 14 029	Diffuse solar radiation (high accuracy), integrated over period specified	
	0 14 030	Direct solar radiation (high accuracy), integrated over period specified	
	2 04 000	Add associated field	Cancel
	1 13 000	Delayed replication of 13 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 04 025	Time period or displacement	= -n minutes (default n = 10)
	0 02 071	Spectrographic wavelength	UV-A: 315 nm

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 092 (continued)	0 02 072	Spectrographic width	UV-A: 85 nm
	2 04 018	Add associated field	
	0 31 021	Associated field significance	
	0 14 072	Global UV irradiation	Integrated over period specified UV-A irradiation according to BUFR Table B under Class 14, Note 8 (ISO 21348: UV-A wave length range $315 \leq \lambda \leq 400 \text{ nm}$)
	2 04 000	Add associated field	Cancel
	0 02 071	Spectrographic wavelength	UV-B: 280 nm
	0 02 072	Spectrographic width	UV-B: 35 nm
	2 04 018	Add associated field	
	0 31 021	Associated field significance	Quality flag
	0 14 072	Global UV irradiation	Integrated over period specified UV-B irradiation according to BUFR Table B under Class 14, Note 8 (ISO 21348 UV-B wave length range $280 \leq \lambda \leq 315 \text{ nm}$)
	2 04 000	Add associated field	Cancel
		(Sequence for representation of SYNOP with supplementary information on one-hour observations)	
	3 01 090	Surface station identification; time, horizontal and vertical coordinates	
	3 01 089	National station identification	
3 07 096	0 08 010	Surface qualifier (temperature data)	
	3 01 091	Surface station instrumentation	
	3 02 084	"Instantaneous" data of sequence 3 07 096	
	3 02 085	"Period" data of sequence 3 07 096	
	0 33 005	Quality information (AWS data)	
	0 33 006	Internal measurement status information (AWS)	
		(Snow observation)	
	3 01 089	National station identification	
3 07 101	0 01 019	Long station or site name	
	0 02 001	Type of station	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 101 (continued)	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 12 101	Temperature/air temperature	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 02 177	Method of snow depth measurement	
	0 20 062	State of the ground (with or without snow)	
	0 13 013	Total snow depth	
		(Road weather information)	
3 07 102		<i>Station identification</i>	For identification of the road weather monitoring site
	3 01 089	National station identification	
	0 01 018	Short station or site name	
	0 01 015	Station or site name	
	0 01 104	State/federal state identifier	
	0 01 105	Highway designator	
	0 01 106	Location along highway as indicated by position markers	
	0 03 017	Extended type of station	
	0 03 018	Type of road	
	0 03 019	Type of construction	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
		<i>Temperature, humidity and visibility data</i>	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 12 101	Temperature/air temperature	
	0 12 103	Dewpoint temperature	
	0 13 003	Relative humidity	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 20 001	Horizontal visibility	
		<i>Road temperature and other data</i>	
	1 09 000	Delayed replication of 9 descriptors	Set to missing (cancel)
	0 31 001	Delayed descriptor replication factor	
	0 03 016	Position of road sensors (see Note 11)	
	0 12 128	Road surface temperature	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 061	Depth below land surface	
			= 0.30 m in the first replication, = e.g. 0.15 or 0.07 m in the second replication

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 102 (continued)	0 12 129	Road subsurface temperature	
	0 07 061	Depth below land surface	Set to missing (cancel)
	0 13 116	Water film thickness	
	0 20 138	Road surface condition (see Note 12)	
		<i>Precipitation data</i>	
	0 04 025	Time period or displacement	= -15 minutes
	0 20 024	Intensity of phenomena (see Note 8)	Intensity (light, moderate, heavy) of precipitation
	0 13 055	Intensity of precipitation (see Note 8)	
	0 20 021	Type of precipitation (see Note 8)	
	0 13 011	Total precipitation/total water equivalent	
		<i>Wind data</i>	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement	= -10 minutes
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 08 021	Time significance	Set to missing (cancel)
		<i>Maximum wind gust</i>	
	0 04 025	Time period or displacement	In minutes
	0 11 043	Maximum wind gust direction	
	0 11 041	Maximum wind gust speed	
		<i>State of functionality</i>	
	0 33 005	Quality information (AWS data)	
		(Snow observation, snow density, snow water equivalent)	
3 07 103	3 01 150	WIGOS identifier	
	3 07 101	Snow observation	
	0 13 117	Snow density (liquid water content)	
	0 03 028	Method of snow water equivalent measurement	
	0 13 163	Snow water equivalent	
		(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data in compliance with reporting practices in RA II)	
3 07 182	3 01 090	Surface station identification; time, horizontal and vertical coordinates	
	3 02 031	Pressure information	
	3 02 035	Basic synoptic "instantaneous" data	
	3 02 036	Clouds with bases below station level	
	3 02 047	Direction of cloud drift	

FM 94 BUFR

Category 07			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 07 182 (continued)	0 08 002	Vertical significance (surface observations)	Set to missing (cancel)
	3 02 048	Direction and elevation of cloud	
	3 02 037	State of ground, snow depth, ground minimum temperature	Past 12 hours
	0 12 120	Ground temperature	$s_n T'_g T'_g$
	0 12 122	Ground minimum temperature of the preceding night	$s_n T_g T_g$
	3 02 043	Basic synoptic "period" data	
	3 02 044	Evaporation data	
	1 01 002	Replicate 1 descriptor 2 times	
	3 02 045	Radiation data (from 1 hour and 24-hour period)	
	3 02 046	Temperature change	

Notes:

- (1) Within 3 07 045, 3 07 048 and 3 07 053, wind speed shall be reported in the same units as in the original TAC data and:
0 11 083 shall be set to missing, if wind speed is reported in knots or $m\ s^{-1}$ in TAC data,
0 11 084 shall be set to missing, if wind speed is reported in $km\ h^{-1}$ or $m\ s^{-1}$ in TAC data.
- (2) Within 3 07 045, 3 07 048 and 3 07 053, maximum wind speed (gusts) shall be reported in the same units as in the original TAC data and:
0 11 085 shall be set to missing, if maximum wind speed is reported in knots or $m\ s^{-1}$ in TAC data,
0 11 086 shall be set to missing, if maximum wind speed is reported in $km\ h^{-1}$ or $m\ s^{-1}$ in TAC data.
- (3) The time identification refers to the beginning of the one-month period.
- (4) If the height of the sensor was changed during the period specified, the value shall be that which existed for the greater part of the period.
- (5) In case of precipitation measurements, the one-month period begins at 06 UTC on the first day of the month and ends at 06 UTC on the first day of the following month.
- (6) The number of missing years within the reference period from the calculation of normal for mean extreme air temperature should be given, if available, for both the calculation of normal maximum temperature and for the calculation of normal minimum temperature in addition to the number of missing years for the extreme air temperatures reported under 0 08 020 preceded by 0 08 050 in which figure 3 is used.
- (7) 3 07 082 is deprecated.
- (8) To represent Intensity of precipitation, type of precipitation and state of functionality, 0 20 024 (Code table), 0 20 021 (Flag table) and 0 33 005 (Flag table) are used, respectively.
- (9) Additional descriptors are required to reduce the workload with respect to the station database, e.g. for identification of the federal state and identification of the highway.
- (10) The majority of stations has only one position on the road and one subsurface temperature sensor. Delayed replications have been introduced to increase flexibility and volume efficiency.

- (11) Each position of road sensors includes the measurements of:
- Road surface temperature
 - Road subsurface temperatures
 - Water film thickness
 - Road surface condition
- (12) Some types of stations do not have the ability to identify the surface condition accurately. They can only report conditions such as "not dry" or "glazed". The code table for road surface conditions has been adjusted accordingly.
-

Provisional Copy
2023

Category 08 – Surface report sequences (sea)

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 001	3 01 033	(Buoy/platform – fixed) Buoy/platform – fixed	Identification, type, date/time, position (high accuracy) Basic surface report
	3 02 011	Low altitude station	
	0 22 042	Sea/water temperature	
3 08 002	3 01 034	(Buoy/platform – fixed) Buoy/platform – fixed	Identification, type, date/time, position (coarse accuracy) Basic surface report
	3 02 011	Low altitude station	
	0 22 042	Sea/water temperature	
3 08 003	3 01 035	(Buoy/platform – moving) (see Note 1) Buoy/platform – moving	Identification, movement, type, date/time, position (coarse accuracy) Basic surface report
	3 02 011	Low altitude station	
	0 22 042	Sea/water temperature	
3 08 004	3 01 036	(Ship) Ship	Identification, movement, type, date/time, position (coarse accuracy) Basic surface report
	3 02 011	Low altitude station	
	0 22 042	Sea/water temperature	
3 08 005	3 08 004	Ship	Basic ship report
	3 02 024	Wind and swell waves	
3 08 006		(Buoy Section 1 optional parameters)	
	0 10 004	Pressure	
	0 10 061	3-hour pressure change	
	0 10 063	Characteristic of pressure tendency	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 12 004	Air temperature at 2 m	
	0 13 003	Relative humidity	
	0 22 042	Sea/water temperature	

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 007	3 01 055	Identification and type of station, date/time, location (high accuracy), movement	Basic surface report
	3 02 011	Low altitude station	
	0 07 062	Depth below sea/water surface	
	0 22 042	Sea/water temperature	
3 08 009		(Sequence for representation of synoptic reports from a sea station suitable for SHIP data)	
	3 01 093	Ship identification, movement, date/time, horizontal and vertical coordinates	
	3 02 001	Pressure and 3-hour pressure change	
	3 02 054	Ship "instantaneous" data	
	0 08 002	Vertical significance (surface observations)	
	3 02 055	Icing and ice	
	3 02 057	Ship marine data	
	3 02 060	Ship "period" data	
3 08 010		(TRACKOB template)	
	0 01 011	Ship or mobile land station identifier	
	1 13 000	Delayed replication of 13 descriptors	
	0 31 001	Delayed descriptor replication factor	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 04 080	Averaging period for following value	
	0 22 049	Sea-surface temperature	
	0 04 080	Averaging period for following value	
	0 22 059	Sea-surface salinity	
	0 04 080	Averaging period for following value	
	0 22 005	Direction of sea-surface current	
	0 02 042	Indicator for sea-surface current speed	
	0 22 032	Speed of sea-surface current	
	0 02 042	Indicator for sea-surface current speed	Cancel
	0 04 080	Averaging period for following value	Cancel
3 08 011		(Monthly values from an ocean weather station – CLIMAT SHIP)	Ship's call sign
	0 01 011	Ship or mobile land station identifier	
	0 02 001	Type of station	
	3 01 011	Year, month, day (see Note 2)	
	3 01 012	Hour, minute (see Note 2)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 07 030	Height of station ground above mean sea level (see Note 3)	
	0 07 031	Height of barometer above mean sea level (see Note 3)	

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 011 (continued)		<i>Monthly mean values of pressure, temperature, vapour pressure and sea/water temperature</i>	
	0 04 074	Short time period or displacement (see Note 2)	= UTC – LT
	0 04 023	Time period or displacement	= Number of days in the month
	0 08 023	First-order statistics	= 4 Mean value
	0 10 051	Pressure reduced to mean sea level	
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 3)	Temperature measurement
	0 07 033	Height of sensor above water surface (see Note 3)	Temperature measurement
	0 12 101	Temperature/air temperature	
	0 13 004	Vapour pressure	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	3 02 056	Sea/water temperature	Sea-surface temperature, method of measurement, and depth below sea surface
	0 08 023	First-order statistics	Set to missing
		<i>Precipitation</i>	
	0 04 003	Day (see Note 4)	= 1
	0 04 004	Hour (see Note 4)	= 6
	0 04 023	Time period or displacement (see Note 4)	= Number of days in the month
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 3)	
	0 13 060	Total accumulated precipitation	
	0 13 051	Frequency group, precipitation	
	0 04 053	Number of days with precipitation equal to or more than 1 mm	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		(Monthly normals for an ocean weather station)	
3 08 012	0 04 001	Year	Beginning of the reference period
	0 04 001	Year	Ending of the reference period
	0 04 002	Month	
	0 04 003	Day (see Note 2)	= 1
	0 04 004	Hour (see Note 2)	= 0
	0 04 074	Short time period or displacement (see Note 2)	= UTC – LT
	0 04 022	Time period or displacement	= 1

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 012 (continued)		<i>Normals of monthly mean pressure, temperature, vapour pressure and sea/water temperature</i>	
	0 08 023	First-order statistics	= 4 Mean value
	0 10 051	Pressure reduced to mean sea level	
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 3)	Temperature measurement
	0 07 033	Height of sensor above water surface (see Note 3)	Temperature measurement
	0 12 101	Temperature/air temperature	
	0 13 004	Vapour pressure	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	3 02 056	Sea/water temperature	Sea-surface temperature, method of measurement, and depth below sea surface
	0 08 023	First-order statistics	Set to missing
	0 04 001	Year	Beginning of the reference period
	0 04 001	Year	Ending of the reference period
	0 04 002	Month	
	0 04 003	Day (see Note 4)	= 1
	0 04 004	Hour (see Note 4)	= 6
	0 04 022	Time period or displacement	= 1
		<i>Normals of precipitation</i>	
	0 07 032	Height of sensor above local ground (or deck of marine platform) (see Note 3)	Precipitation measurement
	0 08 023	First-order statistics	= 4 Mean value
	0 13 060	Total accumulated precipitation	
	0 04 053	Number of days with precipitation equal to or more than 1 mm	
	0 08 023	First-order statistics	Set to missing
		(Representation of CLIMAT SHIP data of the actual month and for monthly normals)	
3 08 013	3 08 011	Monthly values from an ocean weather station – CLIMAT SHIP	
	3 08 012	Monthly normals for an ocean weather station	
		(Synoptic reports from sea stations suitable for VOS observation data)	
3 08 014	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 01 018	Encrypted ship's call sign and encryption method	

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 014 (continued)	0 03 001	Surface station type	32 characters Unique ID for report Cancel
	3 01 093	Ship identification, movement, date/time, horizontal and vertical coordinates	
	2 08 032	Change width of CCITT IA5 field	
	0 01 079	Unique identifier for the profile	
	2 08 000	Change width of CCITT IA5 field	
	3 02 062	Ship "instantaneous" data	
	3 02 063	Ship "period" data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 092	VOSClm data elements	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 033	Surface salinity	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 034	Surface current	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 043	Marine biogeochemical and radiation observations	
		(Template for WAVEOB data expressed as frequency ($I_a = 0$ in FM-65 WAVEOB)) <i>Identification (WAVEOB Section 0)</i>	
3 08 015	0 01 003	WMO Region number/geographical area	A ₁ – First digit of WMO number (e.g. 62024 → 6)
	0 01 020	WMO Region sub-area	b _w – Second digit of WMO number (e.g. 62024 → 2)
	0 01 005	Buoy/platform identifier	n _b n _b n _b – Last 3 digits of WMO number (e.g. 62024 → 024)
	0 01 011	Ship or mobile land station identifier	D....D
	0 01 007	Satellite identifier	I6I6I6
	0 01 001	WMO block number	II
	0 01 002	WMO station number	iii – IIiii only apply to fixed sea stations
	0 02 044	Indicator for method of calculating spectral wave data	I _m – Code table 1744 (WAVEOB), 0 02 044 (BUFR)
	0 02 045	Indicator for type of platform	I _p – Code table 1747 (WAVEOB), 0 02 045 (BUFR)
	3 01 011	Year, month, day	YYMMJ – Date of observation

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 015 (continued)	3 01 012	Hour, minute	GGgg – Time of observation
	3 01 021	Latitude/longitude (high accuracy)	Q _c L _a L _a L _a L _o L _o L _o L _o
		<i>Basic data (WAVEOB Section 0)</i>	
	0 22 063	Total water depth	1hhhh
	0 22 076	Direction from which dominant waves are coming	9d _d d _d – Section 0
	0 22 077	Directional spread of dominant wave	d _s d _s – section 0
	0 22 094	Total number of wave bands	111B _T B _T – Section 1
	0 25 043	Wave sampling interval (time)	SSSS – Section 1
	0 22 078	Duration of wave record	D'D'D'D' – Section 1
	1 05 002	Replicate 5 descriptors 2 times	Replicate over sensor type
	0 02 046	Wave measurement instrumentation	= 1 Heave sensor, = 2 Slope sensor
	0 22 070	Significant wave height	2H _s H _s H _s H _s or 6H _{se} H _{se} H _{se} H _{se} – Section 0
	0 22 071	Spectral peak wave period	3P _p P _p P _p P _p or 7P _{sp} P _{sp} P _{sp} P _{sp} – Section 0
	0 22 073	Maximum wave height	4H _m H _m H _m H _m
	0 22 074	Average wave period	5P _a P _a P _a P _a or 8P _{sa} P _{sa} P _{sa} P _{sa} – Section 0
		<i>Spectral data (WAVEOB Sections 1–5)</i>	
	1 27 000	Delayed replication of 27 descriptors	Replication over sensor type
	0 31 001	Delayed descriptor replication factor (see Note 5)	(0,1,2) normally 1
	0 02 046	Wave measurement instrumentation	= 1 Heave sensor, = 2 Slope sensor
	0 08 090	Decimal scale of following significands	x – Scale to be applied to following element descriptors
	0 22 102	Scaled maximum non-directional spectral wave density by frequency	C _m C _m C _m – Section 2 or C _{sm} C _{sm} C _{sm} – Section 3
	0 08 090	Decimal scale of following significands	Set to missing
	0 22 084	Band containing maximum non-directional spectral wave density	n _m n _m – Section 2 or n _{sm} n _{sm} – Section 3
	1 20 000	Delayed replication of 20 descriptors	Replication over bands
	0 31 001	Delayed descriptor replication factor	111B _T B _T – Section 1 (number of band)
	0 22 080	Waveband central frequency	1f ₁ f ₁ f ₁ f ₁ x ... – Section 1
	0 22 108	Spectral wave density ratio	1c ₁ c ₁ c ₂ c ₂ ... – Section 2 or 1c _{s1} c _{s1} c _{s2} c _{s2} ... – Section 3

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 015 (continued)	0 22 086	Mean direction from which waves are coming	1d _{a1} d _{a1} – Section 4
	0 22 087	Principal direction from which waves are coming	d _{a2} d _{a2} – Section 4
	0 22 088	First normalized polar coordinate from Fourier coefficients	r ₁ r ₁ – Section 4
	0 22 089	Second normalized polar coordinate from Fourier coefficients	r ₂ r ₂ – Section 4
	1 05 000	Delayed replication of 5 descriptors (see Note 6)	
	0 31 001	Delayed descriptor replication factor	n – Section 5 (number of directions counted); = 0 if I _b = 1 (directional)
	0 08 090	Decimal scale of following significands	x – Scale to be applied to following element descriptors
	0 22 104	Scaled non-directional spectral wave density by frequency	1A ₁ A ₁ A ₁ x ... – Section 5
	0 08 090	Decimal scale of following significands	Set to missing
	0 22 186	Direction from which waves are coming (see Note 7)	1d ₁ d ₁ – Section 5
	0 22 187	Directional spread of wave (see Note 7)	d _s d _s – Section 5
	1 05 000	Delayed replication of 5 descriptors (see Note 8)	
	0 31 001	Delayed descriptor replication factor	n – Section 5 (number of directions counted); = 0 if I _b = 0 (non-directional)
	0 08 090	Decimal scale of following significands	x – Scale to be applied to following element descriptors
	0 22 106	Scaled directional spectral wave density by frequency	1A ₁ A ₁ A ₁ x ... – Section 5
	0 08 090	Decimal scale of following significands	Set to missing
	0 22 186	Direction from which waves are coming	1d ₁ d ₁ – Section 5
	0 22 187	Directional spread of wave	d _s d _s – Section 5
		(Template for WAVEOB data expressed as the wave number (I _a = 1 in FM-65 WAVEOB)) <i>Identification (WAVEOB Section 0)</i>	
3 08 016	0 01 003	WMO Region number/geographical area	A ₁ – First digit of WMO number (e.g. 62024 → 6)
	0 01 020	WMO Region sub-area	b _w – Second digit of WMO number (e.g. 62024 → 2)
	0 01 005	Buoy/platform identifier	n _b n _b n _b – Last 3 digits of WMO number (e.g. 62024 → 024)
	0 01 011	Ship or mobile land station identifier	D D

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 016 (continued)	0 01 007	Satellite identifier	I ₆ I ₆ I ₆
	0 01 001	WMO block number	II
	0 01 002	WMO station number	iii – IIiii only apply to fixed sea stations
	0 02 044	Indicator for method of calculating spectral wave data	I _m – Code table 1744 (WAVEOB), 0 02 044 (BUFR)
	0 02 045	Indicator for type of platform	I _p – Code table 1747 (WAVEOB), 0 02 045 (BUFR)
	3 01 011	Year, month, day	YYMMJ – Date of observation
	3 01 012	Hour, minute	GGgg – Time of observation
	3 01 021	Latitude/longitude (high accuracy)	Q _c L _a L _a L _a L _a , L _o L _o L _o L _o L _o
		<i>Basic data (WAVEOB Section 0)</i>	
	0 22 063	Total water depth	1hhhh
	0 22 076	Direction from which dominant waves are coming	9d _d d _d – Section 0
	0 22 077	Directional spread of dominant wave	d _s d _s – Section 0
	0 22 094	Total number of wave bands	111B _T B _T – Section 1
	0 25 044	Wave sampling interval (space)	SSSS – Section 1
	0 22 079	Length of wave record	D'D'D'D' – Section 1
	1 05 002	Replicate 5 descriptors 2 times	Replication over sensor type
	0 02 046	Wave measurement instrumentation	= 1 Heave sensor, = 2 Slope sensor
	0 22 070	Significant wave height	2H _s H _s H _s H _s or 6H _{se} H _{se} H _{se} H _{se} – Section 0
	0 22 072	Spectral peak wavelength	3P _p P _p P _p P _p – Section 0
	0 22 073	Maximum wave height	4H _m H _m H _m H _m
	0 22 075	Average wavelength	5P _a P _a P _a P _a – Section 0
		<i>Spectral data (WAVEOB Sections 1–5)</i>	
	1 27 000	Delayed replication of 27 descriptors	Replication over sensor type
	0 31 001	Delayed descriptor replication factor (see Note 5)	(0,1,2) normally 1
	0 02 046	Wave measurement instrumentation	= 1 Heave sensor, = 2 Slope sensor
	0 08 090	Decimal scale of following significands	x – Scale to be applied to following element descriptors
	0 22 103	Scaled maximum non-directional spectral wave density by wave number	C _m C _m C _m – Section 2 or C _{sm} C _{sm} C _{sm} – Section 3
	0 08 090	Decimal scale of following significands	Set to missing
	0 22 084	Band containing maximum non-directional spectral wave density	n _m n _m – Section 2 or n _{sm} n _{sm} – Section 3

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 016 (continued)	1 20 000	Delayed replication of 20 descriptors	Replication over bands
	0 31 001	Delayed descriptor replication factor	111B _T B _T – Section 1 (number of band)
	0 22 081	Waveband central wave number	1f ₁ f ₁ f ₁ f ₁ x ... – Section 1
	0 22 108	Spectral wave density ratio	1C ₁ C ₁ C ₂ C ₂ ... – Section 2 or 1C _{s1} C _{s1} C _{s2} C _{s2} ... – Section 3
	0 22 086	Mean direction from which waves are coming	1d _{a1} d _{a1} – Section 4
	0 22 087	Principal direction from which waves are coming	d _{a2} d _{a2} – Section 4
	0 22 088	First normalized polar coordinate from Fourier coefficients	r ₁ r ₁ – Section 4
	0 22 089	Second normalized polar coordinate from Fourier coefficients	r ₂ r ₂ – Section 4
	1 05 000	Delayed replication of 5 descriptors (see Note 6)	
	0 31 001	Delayed descriptor replication factor	n – Section 5 (number of directions counted); = 0 if I _b = 1 (directional)
	0 08 090	Decimal scale of following significands	x – Scale to be applied to following element descriptors
	0 22 105	Scaled non-directional spectral wave density by wave number	1A ₁ A ₁ A ₁ x ... – Section 5
	0 08 090	Decimal scale of following significands	Set to missing
	0 22 186	Direction from which waves are coming (see Note 7)	1d ₁ d ₁ – Section 5
	0 22 187	Directional spread of wave (see Note 7)	d _s d _s – Section 5
	1 05 000	Delayed replication of 5 descriptors (see Note 8)	
	0 31 001	Delayed descriptor replication factor	n – Section 5 (number of directions counted); = 0 if I _b = 0 (non- directional)
	0 08 090	Decimal scale of following significands	x – Scale to be applied to following element descriptors
	0 22 107	Scaled directional spectral wave density by wave number	1A ₁ A ₁ A ₁ x ... – Section 5
	0 08 090	Decimal scale of following significands	Set to missing
	0 22 186	Direction from which waves are coming	1d ₁ d ₁ – Section 5
	0 22 187	Directional spread of wave	d _s d _s – Section 5

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 017	3 01 056	(Sequence for reporting observations from offshore platforms) Sequence for platform identification, type, time and location of the observation report	Optional
	3 02 001	Pressure and 3-hour pressure change	
	3 02 052	Ship temperature and humidity data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 056	Sea/water temperature	
	3 02 064	Ship or other marine platform wind data	
	3 02 053	Ship visibility data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 004	General cloud information	Optional
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	Optional
	3 02 005	Cloud layer	
	1 01 000	Delayed replication of 1 descriptor	Optional
	0 31 000	Short delayed descriptor replication factor	
	3 02 038	Present and past weather	Optional
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	Optional
	3 06 039	Sequence for representation of basic wave measurements	
3 08 018	3 01 150	(Sequence for reporting of basic ship AWS observations) WIGOS Identifier	
	3 01 093	Ship identification, movement, date/time, horizontal and vertical coordinates	
	3 02 001	Pressure and 3-hour pressure change	
	3 02 072	Temperature and humidity data	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 056	Sea/water temperature	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 064	Ship or other marine platform wind data	
3 08 021	0 01 011	(Monthly values from an ocean weather station in compliance with regional or national reporting practices) <i>Station identification, date/time, horizontal and vertical coordinates</i> Ship or mobile land station identifier	Ship's call sign
	0 02 001	Type of station	
	3 01 011	Year, month, day	

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 021 (continued)	3 01 012	Hour, minute	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 07 031	Height of barometer above mean sea level	
		<i>Monthly mean values of pressure, temperature, vapour pressure and sea/water temperature</i>	
	0 04 074	Short time period or displacement	
	0 04 023	Time period or displacement	Number of days in the month = 4 Mean value
	0 08 023	First-order statistics	
	0 10 051	Pressure reduced to mean sea level	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Temperature measurement
	0 07 033	Height of sensor above water surface	Temperature measurement
	0 12 101	Temperature/air temperature	
	0 13 004	Vapour pressure	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	3 02 056	Sea/water temperature	Sea-surface temperature, method of measurement and depth below sea surface
	0 08 023	First-order statistics	Set to missing (cancel)
		<i>Precipitation</i>	
	0 04 003	Day	= 1
	0 04 004	Hour	= 0
	0 04 074	Short time period or displacement	
	0 04 023	Time period or displacement	Number of days in the month
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 13 060	Total accumulated precipitation	
	0 13 051	Frequency group, precipitation	
	0 04 053	Number of days with precipitation equal to or more than 1 mm	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 022		(Monthly normals for an ocean weather station in compliance with regional or national reporting practices) <i>Normals of pressure, temperature, vapour pressure and sea/water temperature</i>	
	0 04 001	Year	Beginning of the reference period
	0 04 001	Year	Ending of the reference period
	0 04 002	Month	
	0 04 003	Day	= 1
	0 04 004	Hour	= 0
	0 04 074	Short time period or displacement	
	0 04 022	Time period or displacement	= 1
	0 08 023	First-order statistics	= 4 Mean value
	0 10 051	Pressure reduced to mean sea level	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Temperature measurement
	0 07 033	Height of sensor above water surface	Temperature measurement
	0 12 101	Temperature/air temperature	
	0 13 004	Vapour pressure	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	3 02 056	Sea/water temperature	Sea-surface temperature, method of measurement and depth below sea surface
	0 08 023	First-order statistics	Set to missing (cancel)
		<i>Normals of precipitation</i>	
	0 04 001	Year	Beginning of the reference period
	0 04 001	Year	Ending of the reference period
	0 04 002	Month	
	0 04 003	Day	= 1
	0 04 004	Hour	= 0
	0 04 074	Short time period or displacement	
	0 04 022	Time period or displacement	= 1
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Precipitation measurement

FM 94 BUFR

Category 08			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 08 022 (continued)	0 08 023	First-order statistics	= 4 Mean value
	0 13 060	Total accumulated precipitation	
	0 04 053	Number of days with precipitation equal to or more than 1 mm	
	0 08 023	First-order statistics	
3 08 023		(Sequence for representation of monthly values suitable for CLIMAT SHIP data in compliance with regional or national reporting practices)	Set to missing (cancel)
	3 08 021	Monthly values from an ocean weather station in compliance with regional or national reporting practices	
	3 08 022	Monthly normals for an ocean weather station in compliance with regional or national reporting practices	

Notes:

- (1) Descriptor 3 08 007 should be used instead of 3 08 003 to encode moving buoy/platform information.
- (2) The time identification refers to the beginning of the one-month period.
- (3) If the height of the sensor was changed during the period specified, the value shall be that which existed for the greater part of the period.
- (4) In case of precipitation measurements, the one-month period begins at 06 UTC on the first day of the month and ends at 06 UTC on the first day of the following month.
- (5) Normally 1, may be 2 if both heave and slope sensors are in use, or 0 if no spectral data.
- (6) Non-directional spectra ($I_b = 0$ in WAVEOB) or partial directional spectra ($I_b = 1$ in WAVEOB with one direction per wave number). Count = 0 (full directional spectra) or 1 (non-directional spectra or partial directional spectra). Partial directional spectra have only one direction per wave number band.
- (7) Missing for non-directional spectra.
- (8) Full directional spectra ($I_b = 1$ in WAVEOB with more than one direction per wave number band). The replication count is the number of directions per wave number band that should normally cover the full circle.

Category 09 – Vertical sounding sequences (conventional data)

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 001	3 01 037	(Vertical wind profile) Land station for vertical soundings	Identification, etc. (land station, high accuracy position)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 011	Wind at height	
3 09 002	3 01 038	(Vertical wind profile) Land station for vertical soundings	Identification, etc. (land station, coarse accuracy position)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 011	Wind at height	
3 09 003	3 01 037	(Vertical wind profile) Land station for vertical soundings	Identification, etc. (land station, high accuracy position)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 012	Wind at pressure level	
3 09 004	3 01 038	(Vertical wind profile) Land station for vertical soundings	Identification, etc. (land station, coarse accuracy position)
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 012	Wind at pressure level	
3 09 005	3 01 037	(Vertical sounding with relative humidity) Land station for vertical soundings	Identification, etc. (land station, high accuracy position) Significant cloud layer
	3 02 004	General cloud information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 013	Geopotential, temperature, humidity, wind at pressure level	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 006	3 01 038	(Vertical sounding with relative humidity) Land station for vertical soundings	Identification, etc. (land station, coarse accuracy position)
	3 02 004	General cloud information	Significant cloud layer
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 013	Geopotential, temperature, humidity, wind at pressure level	
3 09 007	3 01 037	(Vertical sounding with dewpoint data) Land station for vertical soundings	Identification, etc. (land station, high accuracy position)
	3 02 004	General cloud information	Significant cloud layer
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 014	Geopotential, temperature, dewpoint temperature, wind at pressure level	
3 09 008	3 01 038	(Vertical sounding with dewpoint data) Land station for vertical soundings	Identification, etc. (land station, coarse accuracy position)
	3 02 004	General cloud information	Significant cloud layer
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 014	Geopotential, temperature, dewpoint temperature, wind at pressure level	
3 09 011	3 01 039	(Vertical wind profile) Ship for vertical soundings	Ship's identification, etc.
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 011	Wind at height	
3 09 012	3 01 039	(Vertical wind profile) Ship for vertical soundings	Ship's identification, etc.
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 012	Wind at pressure level	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 013	3 01 039	(Vertical sounding with relative humidity) Ship for vertical soundings	Ship's identification, etc. Significant cloud layer
	3 02 004	General cloud information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 013	Geopotential, temperature, humidity, wind at pressure level	
3 09 014	3 01 039	(Vertical sounding with dewpoint data) Ship for vertical soundings	Ship's identification, etc. Significant cloud layer
	3 02 004	General cloud information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 014	Geopotential, temperature, dewpoint temperature, wind at pressure level	
3 09 015	3 01 040	(Vertical wind profile) Ship for vertical soundings	Ship's identification, etc.
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 011	Wind at height	
3 09 016	3 01 040	(Vertical wind profile) Ship for vertical soundings	Ship's identification, etc.
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 012	Wind at pressure level	
3 09 017	3 01 040	(Vertical sounding with relative humidity) Ship for vertical soundings	Ship's identification, etc. Significant cloud layer
	3 02 004	General cloud information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 013	Geopotential, temperature, humidity, wind at pressure level	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 018	3 01 040	(Vertical sounding with dewpoint data) Ship for vertical soundings	Ship's identification, etc. Significant cloud layer
	3 02 004	General cloud information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 014	Geopotential, temperature, dewpoint temperature, wind at pressure level	
3 09 019	3 01 031	(Wind profiler – wind data sounding) Identification and type of station, date/time, location (high accuracy), height of station	
	0 02 003	Type of measuring equipment used	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 011	Wind at height	
3 09 020	3 01 031	(Wind profiler – Cartesian coordinates) Identification and type of station, date/time, location (high accuracy), height of station	
	0 02 003	Type of measuring equipment used	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 003	Geopotential	
	0 11 003	u-component	
	0 11 004	v-component	
	0 11 005	w-component	
3 09 021	3 01 001	(Single wavelength wind profiler wind data (product data)) (see Note 20) WMO block and station numbers	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	3 01 014	Time period	
	0 02 003	Type of measuring equipment used	
	0 02 121	Mean frequency	
	1 12 000	Delayed replication of 12 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 007	Height	
	3 01 021	Latitude/longitude (high accuracy)	
	0 11 003	u-component	
	0 11 110	Uncertainty in u-component	
	0 11 004	v-component	
	0 11 111	Uncertainty in v-component	
	0 33 002	Quality information	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 021 (continued)	0 11 006	w-component	
	0 11 112	Uncertainty in w-component	
	0 33 002	Quality information	
	0 10 071	Vertical resolution	
	0 27 079	Horizontal width of sampled volume	
3 09 022		(RASS virtual temperature (product data)) (see Note 20)	
	3 01 001	WMO block and station numbers	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	3 01 014	Time period	
	0 02 003	Type of measuring equipment used	
	0 02 121	Mean frequency	
	1 10 000	Delayed replication of 10 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 007	Height	
	3 01 021	Latitude/longitude (high accuracy)	
	0 12 007	Virtual temperature	
	0 12 008	Uncertainty in virtual temperature	
	0 33 002	Quality information	
	0 11 006	w-component	
	0 11 112	Uncertainty in w-component	
	0 33 002	Quality information	
	0 10 071	Vertical resolution	
	0 27 079	Horizontal width of sampled volume	
3 09 023		(Single wavelength elastic backscatter lidar sequence) (see Note 20)	
		<i>Header section</i>	
	3 01 001	WMO block and station numbers	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	3 01 014	Time period	
	0 02 003	Type of measuring equipment used	
		<i>Cloud data section</i>	
	3 02 004	General cloud information	
	3 02 005	Cloud layer	
		<i>Backscatter data section</i>	
	1 14 000	Delayed replication of 14 descriptors	
	0 31 001	Delayed descriptor replication factor	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 023 (continued)	0 07 007	Height	Number of wavelength measurements present in the data
	3 01 021	Latitude/longitude (high accuracy)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 02 121	Mean frequency	
	0 15 063	Attenuated backscatter	
	0 15 064	Uncertainty in attenuated backscatter	
	0 15 065	Particle backscatter coefficient	
	0 15 066	Uncertainty in particle backscatter coefficient	
	0 15 067	Particle extinction coefficient	
	0 15 068	Uncertainty in particle extinction coefficient	
	0 15 069	Particle lidar ratio	
	0 15 070	Uncertainty in lidar ratio	
	0 15 071	Particle depolarization ratio	
	0 15 072	Uncertainty in depolarization ratio	
	0 33 002	Quality information	
	0 10 071	Vertical resolution	
	0 27 079	Horizontal width of sampled volume	
		(Single wavelength wind profiler wind data sequence (product data))	
3 09 024	3 01 132	Common header sequence	= 2 Time averaged
	2 01 151	Change data width (by YYY-128 bit places)	
	2 02 130	Change scale (by YYY-128 places)	
	0 02 121	Mean frequency	
	2 02 000	Cancel scale change	
	2 01 000	Cancel data width change	
	0 08 021	Time significance	
	0 04 025	Time period or displacement (see Note 13)	
	1 09 000	Delayed replication of 9 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 07 007	Height (see Note 14)	
	3 01 021	Latitude/longitude (high accuracy) (see Note 15)	
	0 11 003	u-component	
	0 11 004	v-component	
	0 33 002	Quality information (see Note 16)	
	0 11 006	w-component	
	0 33 002	Quality information	
	0 10 071	Vertical resolution	
	0 27 079	Horizontal width of sampled volume	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 025	3 01 132	(RASS virtual temperature sequence (product data))	
	2 01 151	Common header sequence	
	2 02 130	Change data width	
	0 02 121	Change scale	
	2 02 000	Mean frequency	
	2 01 000	Cancel scale change	
	0 08 021	Cancel data width change	
	0 04 025	Time significance	= 2 Time averaged
	1 06 000	Time period or displacement (see Note 13)	
	0 31 002	Delayed replication of 6 descriptors	
	0 07 007	Extended delayed descriptor replication factor	
	3 01 021	Height (see Note 15)	
	0 12 007	Latitude/longitude (high accuracy) (see Note 15)	
	0 33 002	Virtual temperature	
	0 10 071	Quality information (see Note 17)	
	0 27 079	Vertical resolution	
		Horizontal width of sampled volume	
3 09 026		(Single wavelength elastic backscatter lidar sequence)	
	3 01 132	Common header sequence	
	3 02 004	General cloud information	
	3 02 005	Cloud layer	
	0 08 092	Measurement uncertainty expression (see Note 18)	
	0 08 093	Measurement uncertainty significance (see Note 15)	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement (see Note 13)	
	2 01 138	Change data width	
	2 02 126	Change scale	
	0 02 121	Mean frequency	
	2 02 000	Cancel scale change	
	2 01 000	Cancel data width change	
	1 15 000	Delayed replication of 15 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 07 007	Height (see Note 15)	
	3 01 021	Latitude/longitude (high accuracy)	= 2 Time averaged
	0 15 073	Attenuated backscatter	
	0 15 064	Uncertainty in attenuated backscatter	
	0 15 074	Particle backscatter coefficient	
	0 15 066	Uncertainty in particle backscatter coefficient	
	0 15 075	Particle extinction coefficient	
	0 15 068	Uncertainty in particle extinction coefficient	
	0 15 076	Particle lidar ratio	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 026 (continued)	0 15 077	Uncertainty in lidar ratio	
	0 15 078	Particle depolarization ratio	
	0 15 072	Uncertainty in depolarization ratio	
	0 33 002	Quality information (see Note 19)	
	0 10 071	Vertical resolution	
	0 27 079	Horizontal width of sampled volume	
3 09 027		(Multi wavelength ground-based lidar sequence)	
	3 01 132	Common header sequence	
	0 08 043	Atmospheric chemical or physical constituent type	
	0 25 061	Software version number	
	3 02 004	General cloud information	
	3 02 005	Cloud layer	
	0 08 092	Measurement uncertainty expression (see Note 18)	
	0 08 093	Measurement uncertainty significance (see Note 15)	
	0 08 021	Time significance	= 2 Time averaged
	0 04 025	Time period or displacement (see Note 13)	
	1 18 000	Delayed replication of 18 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 02 090	Instrument wavelength	
	1 15 000	Delayed replication of 15 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 07 007	Height (see Note 15)	
	3 01 021	Latitude/longitude (high accuracy)	= 2 Time averaged
	0 15 073	Attenuated backscatter	
	0 15 064	Uncertainty in attenuated backscatter	
	0 15 074	Particle backscatter coefficient	
	0 15 066	Uncertainty in particle backscatter coefficient	
	0 15 075	Particle extinction coefficient	
	0 15 068	Uncertainty in particle extinction coefficient	
	0 15 076	Particle lidar ratio	
	0 15 077	Uncertainty in lidar ratio	
	0 15 078	Particle depolarization ratio	
	0 15 072	Uncertainty in depolarization ratio	
	0 33 002	Quality information (see Note 19)	
	0 10 071	Vertical resolution	
	0 27 079	Horizontal width of sampled volume	
3 09 030		(Ozone sonde flight data) (see Note 1)	
	0 15 004	Ozone sounding correction factor (CF)	
	0 15 005	Ozone p	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 030 (continued)	0 04 015	Time increment	Since launch time, if needed, in minutes
	0 08 006	Ozone vertical sounding significance	
	0 07 004	Pressure	
	0 15 003	Measured ozone partial pressure (sounding)	
3 09 031		(Ozone sonde flight data)	Since launch time in minutes
	0 15 004	Ozone sounding correction factor (CF)	
	0 15 005	Ozone p	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 04 025	Time period or displacement	
3 09 040	0 08 006	Ozone vertical sounding significance	
	0 07 004	Pressure	
	0 15 003	Measured ozone partial pressure (sounding)	
		(Ozone sounding not coupled to a ground-based spectrophotometer) (see Note 2)	
	3 01 075	Sounding identification	
	3 01 076	Ozone sounding instrumentation	
3 09 041	3 09 030	Ozone sonde flight data	
		(Ozone sounding coupled to measurements from a Brewer ground-based spectrophotometer; the total ozone obtained from the Brewer is a single value) (see Note 2)	
	3 07 041	Total ozone measurement from a Brewer ground-based spectrophotometer obtained from a single observation	Description of the ground-based part
	3 01 075	Sounding identification	Identification of the ozone sounding part
	3 01 076	Ozone sounding instrumentation	
	3 09 030	Ozone sonde flight data	
3 09 042		(Ozone sounding coupled to measurements from a Brewer ground-based spectrophotometer; the total ozone obtained from the Brewer is an averaged value) (see Note 2)	Description of the ground-based part Identification of the ozone sounding part
	3 07 042	Total ozone measurement from a Brewer ground-based spectrophotometer obtained from averaged observations	
	3 01 075	Sounding identification	
	3 01 076	Ozone sounding instrumentation	
	3 09 030	Ozone sonde flight data	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 043	3 07 043	(Ozone sounding coupled to measurements from a Dobson ground-based spectrophotometer; the total ozone obtained from the Dobson is a single value) (see Note 2)	
		Total ozone measurement from a Dobson ground-based spectrophotometer obtained from a single observation	Description of the ground-based part
		Sounding identification	Identification of the ozone sounding part
		Ozone sounding instrumentation	
3 09 044	3 07 044	Ozone sonde flight data	
		(Ozone sounding coupled to measurements from a Dobson ground-based spectrophotometer; the total ozone obtained from the Dobson is an averaged value) (see Note 2)	
		Total ozone measurement from a Dobson ground-based spectrophotometer obtained from averaged observations	Description of the ground-based part
		Sounding identification	Identification of the ozone sounding part
3 09 045	3 01 075	Ozone sounding instrumentation	
		Ozone sonde flight data	
		(Ozone sounding not coupled to a ground-based spectrophotometer)	
		Sounding identification	
3 09 046	3 01 076	Ozone sounding instrumentation	
		Ozone sonde flight data	
		(Ozone sounding coupled to measurements from a Brewer ground-based spectrophotometer; the total ozone obtained from the Brewer is a single value)	
		Total ozone measurement from a Brewer ground-based spectrophotometer obtained from a single observation	Description of the ground-based part
3 09 046	3 01 075	Sounding identification	Identification of the ozone sounding part
		Ozone sounding instrumentation	
		Ozone sonde flight data	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 047	3 07 042	(Ozone sounding coupled to measurements from a Brewer ground-based spectrophotometer; the total ozone obtained from the Brewer is an averaged value)	Description of the ground-based part
		Total ozone measurement from a Brewer ground-based spectrophotometer obtained from averaged observations	
		Sounding identification	
		Ozone sounding instrumentation	
3 09 048	3 07 043	(Ozone sounding coupled to measurements from a Dobson ground-based spectrophotometer; the total ozone obtained from the Dobson is a single value)	Description of the ground-based part
		Total ozone measurement from a Dobson ground-based spectrophotometer obtained from a single observation	
		Sounding identification	
		Ozone sounding instrumentation	
3 09 049	3 07 044	(Ozone sounding coupled to measurements from a Dobson ground-based spectrophotometer; the total ozone obtained from the Dobson is an averaged value)	Description of the ground-based part
		Total ozone measurement from a Dobson ground-based spectrophotometer obtained from averaged observations	
		Sounding identification	
		Ozone sounding instrumentation	
3 09 050	3 01 110	(Sequence for representation of PILOT, PILOT SHIP and PILOT MOBIL observation type data with pressure as the vertical coordinate)	Identification of the ozone sounding part
		Identification of launch site and instrumentation for wind measurements	
		Date/time of launch	
		Horizontal and vertical coordinates of launch site	
		Delayed replication of 1 descriptor	
		Extended delayed descriptor replication factor	
		Wind data at a pressure level with radiosonde position	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 050 (continued)	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 051	Wind shear data at a pressure level with radiosonde position	
3 09 051		(Sequence for representation of PILOT, PILOT SHIP and PILOT MOBIL observation type data with height as the vertical coordinate)	
	3 01 110	Identification of launch site and instrumentation for wind measurements	
	3 01 113	Date/time of launch	
	3 01 114	Horizontal and vertical coordinates of launch site	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 03 052	Wind data at a height level with radiosonde position	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 053	Wind shear data at a height level with radiosonde position	
3 09 052		(Sequence for representation of TEMP, TEMP SHIP and TEMP MOBIL observation type data)	
	3 01 111	Identification of launch site and instrumentation for P, T, U and wind measurements	
	3 01 113	Date/time of launch	
	3 01 114	Horizontal and vertical coordinates of launch site	
	3 02 049	Cloud information reported with vertical soundings	
	0 22 043	Sea/water temperature	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 03 054	Temperature, dewpoint and wind data at a pressure level with radiosonde position	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 051	Wind shear data at a pressure level with radiosonde position	
3 09 053		(Sequence for representation of TEMP DROP observation type data)	
	3 01 112	Identification of launch point and instrumentation of dropsonde	
	3 01 113	Date/time of launch	
	3 01 114	Horizontal and vertical coordinates of launch site	
	1 01 000	Delayed replication of 1 descriptor	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 053 (continued)	0 31 002	Extended delayed descriptor replication factor	
	3 03 054	Temperature, dewpoint and wind data at a pressure level with radiosonde position	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 051	Wind shear data at a pressure level with radiosonde position	
3 09 054		(Sequence for representation of CLIMAT TEMP and CLIMAT TEMP SHIP data)	
	3 01 001	WMO block and station numbers	Identification of launch site
	0 01 011	Ship or mobile land station identifier	Ship's call sign
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 07 031	Height of barometer above mean sea level	
	0 07 007	Height	Release of sonde above mean sea level
		Monthly mean data	
	0 04 023	Time period or displacement	Number of days in the month
	0 04 059	Times of observation used to compute the reported mean values	
	1 15 000	Delayed replication of 15 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 001	Vertical sounding significance	
	0 08 023	First-order statistics	= 4 Mean value
	0 07 004	Pressure	
	0 10 009	Geopotential height	
	0 12 101	Temperature/air temperature	
	0 12 103	Dewpoint temperature	
	0 08 023	First-order statistics	= 32 Vector mean
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 08 023	First-order statistics	Set to missing
	0 11 019	Steadiness of wind	
	0 08 050	Qualifier for number of missing values in calculation of statistic	= 2 Temperature
	0 08 020	Total number of missing entities (with respect to accumulation or average)	Days
	0 08 050	Qualifier for number of missing values in calculation of statistic	= 9 Wind
	0 08 020	Total number of missing entities (with respect to accumulation or average)	Days

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 055	3 01 111	(Template for the representation of high resolution radiosonde data with geopotential height as the vertical coordinate) Identification of launch site and instrumentation for P, T, U and wind measurements	
	0 25 061	Software identification and version number	
	0 01 081	Radiosonde serial number	
	0 01 082	Radiosonde ascension number	
	0 02 067	Radiosonde operating frequency	
	0 02 095	Type of pressure sensor	
	0 02 096	Type of temperature sensor	
	0 02 097	Type of humidity sensor	
	0 02 081	Type of balloon	
	0 02 082	Weight of balloon	
	0 02 084	Type of gas used in balloon	
	0 02 191	Geopotential height calculation	
	3 01 113	Date/time of launch (see Note 3)	
	3 01 114	Horizontal and vertical coordinates of launch site	
	0 10 004	Pressure	
	3 02 032	Temperature and humidity data	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 02 002	Type of instrumentation for wind measurement	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 20 003	Present weather	
	3 02 049	Cloud information reported with vertical soundings	
	0 22 043	Sea/water temperature	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 03 055	Temperature, dewpoint, relative humidity and wind data at a height level with radiosonde position (see Notes 4, 5 and 6)	
3 09 056		(Sequence for representation of radiosonde descent data)	
	3 01 150	WIGOS identifier	
	3 01 111	Identification of launch site and instrumentation for P, T, U and wind measurements	
	3 01 128	Additional information on radiosonde ascent	Valid also for decent
	3 01 113	Date/time of launch (see Note 10)	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 056 (continued)	0 08 091	Coordinates significance	= 2 Start of observation Begin of descending of radiosonde above mean sea level Set to missing (cancel)
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 007	Height	
	0 08 091	Coordinates significance	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 03 056	Temperature, dewpoint and wind data at a pressure level with radiosonde position and higher precision of pressure and geopotential height (see Notes 11 and 12)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 051	Wind shear data at a pressure level with radiosonde position	
		(Sequence for representation of TEMP, TEMP SHIP and TEMP MOBIL observation type data with higher precision of pressure and geopotential height)	
	3 01 150	WIGOS identifier	
	3 01 111	Identification of launch site and instrumentation for P, T, U and wind measurements	
	3 01 128	Additional information on radiosonde ascent	
	3 01 113	Date/time of launch	
3 09 057	3 01 114	Horizontal and vertical coordinates of launch site	
	3 02 049	Cloud information reported with vertical soundings	
	0 22 043	Sea/water temperature	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 03 056	Temperature, dewpoint and wind data at a pressure level with radiosonde position and higher precision of pressure and geopotential height	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 051	Wind shear data at a pressure level with radiosonde position	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 060	3 01 123	(Radiosonde complete registration and surface observation)	
	3 01 121	Radiosonde full header information	
	3 02 050	Radiosonde launch point location	
	3 03 040	Radiosonde surface observation	
3 09 061	3 03 040	Radiosonde duration of flight and termination information	
		(Raw PTU)	
	3 01 120	Radiosonde abbreviated header and launch information	
	0 08 041	Data significance	= 6 Flight level observation
	3 01 122	Date/time (to hundredths of second)	
	2 01 131	Change data width	
	2 02 129	Change scale	
	0 25 069	Flight level pressure corrections	
	0 07 004	Pressure	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 33 007	Per cent confidence	Pressure
	0 33 035	Manual/automatic quality control	Pressure
	0 33 015	Data quality check indicator	Pressure
	0 13 009	Relative humidity	
	0 33 007	Per cent confidence	Relative humidity
	0 33 035	Manual/automatic quality control	Relative humidity
	0 33 015	Data quality check indicator	Relative humidity
	0 02 013	Solar and infrared radiation correction	
	0 12 101	Temperature/air temperature	
3 09 062	0 33 007	Per cent confidence	Temperature
	0 33 035	Manual/automatic quality control	Temperature
	0 33 015	Data quality check indicator	Temperature
		(Raw GPS unsmoothed wind)	
	3 01 120	Radiosonde abbreviated header and launch information	
	0 08 041	Data significance	= 6 Flight level observation
	3 01 122	Date/time (to hundredths of second)	
	0 05 001	Latitude (high accuracy)	
	0 33 035	Manual/automatic quality control	Latitude
	0 33 015	Data quality check indicator	Latitude
	0 06 001	Longitude (high accuracy)	
	0 33 035	Manual/automatic quality control	Longitude
	0 33 015	Data quality check indicator	Longitude
	0 07 007	Height	
	0 33 035	Manual/automatic quality control	Height

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 062 (continued)	0 33 015	Data quality check indicator	Height
	0 11 003	u-component	
	0 33 035	Manual/automatic quality control	u-component
	0 33 015	Data quality check indicator	u-component
	0 11 004	v-component	
	0 33 035	Manual/automatic quality control	v-component
	0 33 015	Data quality check indicator	v-component
	0 33 007	Per cent confidence	Raw GPS unsmoothed wind
3 09 063		(Raw GPS smoothed wind)	
	3 01 120	Radiosonde abbreviated header and launch information	
	0 08 041	Data significance	= 6 Flight level observation
	3 01 122	Date/time (to hundredths of second)	
	0 05 001	Latitude (high accuracy)	
	0 33 035	Manual/automatic quality control	Latitude
	0 33 015	Data quality check indicator	Latitude
	0 06 001	Longitude (high accuracy)	
	0 33 035	Manual/automatic quality control	Longitude
	0 33 015	Data quality check indicator	Longitude
	0 07 007	Height	
	0 33 035	Manual/automatic quality control	Height
	0 33 015	Data quality check indicator	Height
	0 11 003	u-component	
	0 33 035	Manual/automatic quality control	u-component
	0 33 015	Data quality check indicator	u-component
	0 11 004	v-component	
	0 33 035	Manual/automatic quality control	v-component
	0 33 015	Data quality check indicator	v-component
	0 33 007	Per cent confidence	Raw GPS smoothed wind
3 09 064		(Processed PTU)	
	3 01 120	Radiosonde abbreviated header and launch information	
	0 08 041	Data significance	= 6 Flight level observation
	3 01 122	Date/time (to hundredths of second)	
	2 01 131	Change data width	
	2 02 129	Change scale	
	1 04 002	Replicate 4 descriptors 2 times	
	0 25 069	Flight level pressure corrections	
	0 07 004	Pressure	
	0 33 035	Manual/automatic quality control	Pressure
	0 33 015	Data quality check indicator	Pressure
	0 13 003	Relative humidity	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 064 (continued)	0 33 035	Manual/automatic quality control	Relative humidity
	0 33 015	Data quality check indicator	Relative humidity
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	1 04 002	Replicate 4 descriptors 2 times	
	0 02 013	Solar and infrared radiation correction	
	0 12 101	Temperature/air temperature	
	0 33 035	Manual/automatic quality control	Temperature
	0 33 015	Data quality check indicator	Temperature
	0 12 103	Dewpoint temperature	
	0 33 035	Manual/automatic quality control	Dewpoint temperature
	0 33 015	Data quality check indicator	Dewpoint temperature
	0 10 009	Geopotential height	
	0 33 035	Manual/automatic quality control	Geopotential height
	0 33 015	Data quality check indicator	Geopotential height
3 09 065		(Processed GPS)	
	3 01 120	Radiosonde abbreviated header and launch information	
	0 08 041	Data significance	= 6 Flight level observation
	3 01 122	Date/time (to hundredths of second)	
	0 05 001	Latitude (high accuracy)	
	0 33 035	Manual/automatic quality control	Latitude
	0 33 015	Data quality check indicator	Latitude
	0 06 001	Longitude (high accuracy)	
	0 33 035	Manual/automatic quality control	Longitude
	0 33 015	Data quality check indicator	Longitude
	0 07 007	Height	
	0 33 035	Manual/automatic quality control	Height
	0 33 015	Data quality check indicator	Height
	0 11 003	u-component	
	0 33 035	Manual/automatic quality control	u-component
	0 33 015	Data quality check indicator	u-component
	0 11 004	v-component	
3 09 066	0 33 035	Manual/automatic quality control	v-component
	0 33 015	Data quality check indicator	v-component
		(Standard and significant levels)	
	3 01 120	Radiosonde abbreviated header and launch information	
	0 08 041	Data significance	= 6 Flight level observation
	3 01 122	Date/time (to hundredths of second)	
	0 08 040	Flight level significance	
	2 01 131	Change data width	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 066 (continued)	2 02 129	Change scale	
	0 25 069	Flight level pressure corrections	
	0 07 004	Pressure	
	0 13 003	Relative humidity	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 02 013	Solar and infrared radiation correction	
	0 12 101	Temperature/air temperature	
	0 12 103	Dewpoint temperature	
	0 10 009	Geopotential height	
	0 10 007	Height	
	0 11 002	Wind speed	
	0 11 001	Wind direction	
		(Vertical profile for numerical weather prediction data)	
		<i>Identification</i>	
3 09 070	0 01 035	Originating centre	
	0 01 032	Generating application	
	0 01 015	Station or site name	
	0 01 063	ICAO location indicator	
	3 01 001	WMO block and station numbers	
		<i>Location and reference time</i>	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	Reference time of the forecast (T-zero)
	3 01 021	Latitude/longitude (high accuracy)	
	2 07 001	Increase scale, reference value and data width	Increase scale factor by 1; reference value and data width are recalculated in accordance with the Table C specification of operator 2 07 YYY
			Station elevation (non coordinate)
	0 10 001	Height of land surface (see Note 7)	Cancel
	2 07 000	Increase scale, reference value and data width	Bit 9 set to 1 Virtual station height
	0 08 086	Vertical significance for NWP	Elevation of model terrain at the latitude/longitude of station. As qualified by 0 08 086, this value is both station and model specific.
	0 07 030	Height of station ground above mean sea level	

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 070 (continued)	0 25 031	<i>Vertical profile metadata</i> NWP-generated vertical profile thinning method (see Note 8)	= 4 Forecast, = 16 Analysis, = 27 First guess Validity time of the forecast expressed as a Delta T from reference time. In the case of an analysis or 00 hour forecast, the value is set to zero.
	0 08 021	Time significance	
	0 04 014	Time increment	
		<i>Point data at station height (including column- integrated data)</i>	
	0 10 004	Pressure	
	0 10 051	Pressure reduced to mean sea level	
	0 10 009	Geopotential height	
	0 20 010	Cloud cover (total)	
	0 13 095	Total column water vapour	
		<i>Replication loop for levels</i>	
	1 28 000	Delayed replication of 28 descriptors	The number of levels used in the vertical profile is determined by this replication. The number of levels is discretionary and comprises all agl levels and pressure levels.
	0 31 002	Extended delayed descriptor replication factor	
		<i>Data on pressure coordinates</i>	
	1 13 000	Delayed replication of 13 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 08 086	Vertical significance for NWP	
	0 07 004	Pressure (see Note 9)	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 12 101	Temperature/air temperature	
	0 12 102	Wet-bulb temperature	
	0 12 103	Dewpoint temperature	
	0 10 009	Geopotential height	
	1 03 000	Delayed replication of 3 descriptors	
			= 1 Vertical coordinate is pressure, = 0 Otherwise Bit 1 set to 0 and other bits as appropriate Degrees true m/s

FM 94 BUFR

Category 09			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 09 070 (continued)	0 31 000	Short delayed descriptor replication factor	= 1 Optional enhanced model data is to be included Vertical motion = 1 Vertical coordinate is 10 metres above ground level, = 0 Otherwise Bit 1 set to 1, bit 8 set to 1 = 10 m Degrees true m/s = 1 Vertical coordinate is 2 metres above ground level, = 0 Otherwise = 2 m
	0 11 021	Relative vorticity	
	0 11 022	Divergence	
	0 11 005	w-component <i>Data at 10 metres above ground level</i>	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 08 086	Vertical significance for NWP	
	0 07 006	Height above station	
	0 11 001	Wind direction	
	0 11 002	Wind speed <i>Data at 2 metres above ground level</i>	
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 08 086	Vertical significance for NWP	
	0 07 006	Height above station	
	0 12 101	Temperature/air temperature	
	0 12 102	Wet-bulb temperature	
	0 12 103	Dewpoint temperature	
		(Sequence for representation of PILOT in the area of ASECNA)	
3 09 071	3 01 001	WMO block and station numbers	Release of balloon
	0 02 014	Tracking technique/status of system used	
	0 02 003	Type of measuring equipment used	
	3 01 113	Date/time of launch	
	3 01 114	Horizontal and vertical coordinates of launch site	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 07 030	Height of station ground above mean sea level	
	0 07 007	Height	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 009	Geopotential height	
	0 11 001	Wind direction	
	0 11 002	Wind speed	

Notes:

- (1) Sequence 3 09 030 is deprecated because of incorrect usage of descriptor 0 04 015; sequence 3 09 031 should be used instead.
- (2) This sequence is deprecated because it includes deprecated sequence 3 09 030; sequence 3 09 045, 3 09 046, 3 09 047, 3 09 048 and 3 09 049 should be used instead of 3 09 040, 3 09 041, 3 09 042, 3 09 043 and 3 09 044, respectively.
- (3) Time of launch 3 01 013 in the sequence shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry for seconds shall be put to zero.
- (4) Long time displacement 0 04 086 in the sequence represents the time offset from the launch time 3 01 013 (in seconds).
- (5) Latitude displacement 0 05 015 in the sequence represents the latitude offset from the latitude of the launch site. Longitude displacement 0 06 015 in the sequence represents the longitude offset from the longitude of the launch site.
- (6) If the radiosonde is equipped with a relative humidity sensor, 0 13 009 in the sequence shall be reported as mandatory and dewpoint temperature may be included as a derived value. If the radiosonde is equipped with a dewpoint temperature sensor, 0 12 103 in the sequence shall be reported and 0 13 009 shall be set to a missing value.
- (7) This value is the official or best estimate of the actual elevation of the station. It is provided for comparison with the model's virtual terrain elevation. The two can be substantially different in rugged terrain. The scale factor is increased to make the value directly comparable with 0 07 030 below.
- (8) In this instance, the term "thinning" refers to a method that may be applied to select a subset of levels from a model that may have many native vertical levels. Selecting only a subset reduces the size of the pseudo-sounding, at the possible cost of information loss and extra processing.
- (9) Non-surface levels on the model's native vertical coordinate are transposed to pressure coordinate. This makes the levels more readily intelligible for human interpretation and easier to use by generic display applications. The levels may correspond exactly to native model levels, or be interpolated between model levels to pressure levels chosen by the generating centre.
- (10) Date/time of launch indicates date/time of start of descent measurement.
- (11) In this sequence for representation of radiosonde descent data, indication of standard levels using the extended vertical sounding significance (0 08 042) is not mandatory.
- (12) Data represented by this sequence should be sorted in descending order with respect to pressure.
- (13) The time period indicates the duration in minutes over which the measurements have been averaged. The end of the time period is marked by the end of scan (see above).
- (14) The Quality information descriptor 0 33 002 at this point relates to both u-component 0 11 003 and v-component 0 11 004. It is given for each respective gate of the profile measurement.
- (15) The Height descriptor 0 07 007 and the Latitude/longitude descriptor 3 01 021 indicate the altitude above sea level and the horizontal position of each vertical bin of the profile measurement and not the location of the instrument itself (which is encoded in the preceding Common header sequence 3 01 132).
- (16) The Quality information descriptor 0 33 002 at this point relates to the w-component 0 11 006. It is given for each respective gate of the profile measurement.
- (17) The Quality information descriptor 0 33 002 relates to the Virtual temperature 0 12 007. It is given for each respective gate of the profile measurement.
- (18) The Measurement uncertainty expression and significance descriptors 0 08 092 and 0 08 093 relate to all parameter uncertainties provided in the Backscatter data section.

- (19) The Quality information descriptor 0 33 002 relates to all parameters provided in the Backscatter data section and is given for each respective vertical bin of the profile measurement.
 - (20) The sequences 3 09 021, 3 09 022, and 3 09 023 should not be used because they are outdated. The sequences 3 09 024, 3 09 025 and 3 09 026, respectively, should be used instead.
-

Provisional Copy
2023

Category 10 – Vertical sounding sequences (satellite data)

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 001	3 01 042	(Satellite – brightness temperature) Satellite identifier, instrument, data- processing technique, date/time, location	
	3 03 031	Significance data, land/sea, skin temperature	
	3 03 032	Cloud	
	1 01 026	Replicate 1 descriptor 26 times	
	3 03 025	Satellite channel and brightness temperature	
3 10 002	3 01 042	(Satellite – low level) Satellite identifier, instrument, data- processing technique, date/time, location	
	3 03 031	Significance data, land/sea, skin temperature	
	3 03 032	Cloud	
	1 01 009	Replicate 1 descriptor 9 times	
	3 03 023	Layer mean temperature	
3 10 003	3 01 042	(Satellite – high level) Satellite identifier, instrument, data- processing technique, date/time, location	
	3 03 031	Significance data, land/sea, skin temperature	
	3 03 032	Cloud	
	1 01 006	Replicate 1 descriptor 6 times	
	3 03 023	Layer mean temperature	
3 10 004	3 01 042	(Satellite – precipitable water) Satellite identifier, instrument, data- processing technique, date/time, location	
	3 03 031	Significance data, land/sea, skin temperature	
	3 03 032	Cloud	
	1 01 003	Replicate 1 descriptor 3 times	
	3 03 024	Precipitable water	
3 10 005	3 01 042	Satellite identifier, instrument, data- processing technique, date/time, location	
	3 03 031	Significance data, land/sea, skin temperature	
	3 03 033	Cloud	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 025	Satellite channel and brightness temperature	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 006	3 01 042	Satellite identifier, instrument, data-processing technique, date/time, location	
	3 03 031	Significance data, land/sea, skin temperature	
	3 03 033	Cloud	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 023	Layer mean temperature	
3 10 007	3 01 042	Satellite identifier, instrument, data-processing technique, date/time, location	
	3 03 031	Significance data, land/sea, skin temperature	
	3 03 033	Cloud	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 03 024	Precipitable water	
3 10 008		(ATOVS HIRS report)	
	3 10 011	ATOVS field of view variables	
	1 01 019	Replicate 1 descriptor 19 times	
	3 10 012	ATOVS channel variables	
	0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	
	0 25 079	Albedo-radiance solar filtered irradiance for ATOVS	
	0 25 080	Albedo-radiance equivalent filter width for ATOVS	
	0 33 032	Channel quality flags for ATOVS	
3 10 009	0 14 045	Channel radiance	
		(ATOVS AMSU-A report)	
	3 10 011	ATOVS field of view variables	
	1 01 015	Replicate 1 descriptor 15 times	
3 10 010	3 10 012	ATOVS channel variables	
		(ATOVS AMSU-B/MHS report)	
	3 10 011	ATOVS field of view variables	
	1 01 005	Replicate 1 descriptor 5 times	
3 10 011	3 10 012	ATOVS channel variables	
		(ATOVS field of view variables)	
	0 08 070	Vertical sounding product qualifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 08 070	Vertical sounding product qualifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 011 (continued)	0 01 007	Satellite identifier	Satellite azimuth
	0 02 048	Satellite sensor indicator	
	0 05 040	Orbit number	
	0 25 075	Satellite antenna corrections version number	
	2 01 133	Change data width	
	0 05 041	Scan line number	
	2 01 000	Change data width	
	0 05 043	Field of view number	
	0 25 070	Major frame count	
	0 33 030	Scan line status flags for ATOVS	
	0 33 031	Scan line quality flags for ATOVS	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	2 02 131	Change scale	
	2 01 138	Change data width	
	0 04 006	Second	
	2 01 000	Change data width	
	2 02 000	Change scale	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	2 02 126	Change scale	
	0 07 001	Height of station	
	2 02 000	Change scale	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 33 033	Field of view quality flags for ATOVS	
	0 02 151	Radiometer identifier	
	0 12 064	Instrument temperature	
	0 02 151	Radiometer identifier	
	0 12 064	Instrument temperature	
	0 02 151	Radiometer identifier	
	0 12 064	Instrument temperature	
	0 02 151	Radiometer identifier	
	0 12 064	Instrument temperature	
		(ATOVS channel variables)	
3 10 012	0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	
	0 25 076	Log ₁₀ of (temperature-radiance central wave number) for ATOVS	
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 012 (continued)	0 33 032	Channel quality flags for ATOVS	
	2 01 132	Change data width	
	2 02 129	Change scale	
	0 12 063	Brightness temperature	
	2 02 000	Change scale	
	2 01 000	Change data width	
3 10 013		(AVHRR (GAC) report)	
	0 01 007	Satellite identifier	
	0 05 040	Orbit number	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 025	Solar zenith angle	
	0 05 043	Field of view number	
	0 25 085	Fraction of clear pixels in HIRS FOV	
	2 01 131	Change data width	
	2 02 129	Change scale	
	0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	
	0 08 023	First-order statistics	
	0 08 072	Pixel(s) type	
	0 14 027	Albedo	
	0 08 072	Pixel(s) type	
	0 14 027	Albedo	
	0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	
	0 08 023	First-order statistics	
	0 08 072	Pixel(s) type	
	0 14 027	Albedo	
	0 08 072	Pixel(s) type	
	0 14 027	Albedo	
	0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	
	0 08 023	First-order statistics	
	0 08 072	Pixel(s) type	
	0 14 027	Albedo	
	0 08 072	Pixel(s) type	
	0 14 027	Albedo	
	2 02 000	Change scale	
	2 01 000	Change data width	
	2 01 132	Change data width	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 013 (continued)	2 02 129	Change scale	
	0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	
	0 08 023	First-order statistics	
	0 08 072	Pixel(s) type	
	0 12 063	Brightness temperature	
	0 08 072	Pixel(s) type	
	0 12 063	Brightness temperature	
	0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	
	0 08 023	First-order statistics	
	0 08 072	Pixel(s) type	
	0 12 063	Brightness temperature	
	0 08 072	Pixel(s) type	
	0 12 063	Brightness temperature	
	0 08 023	First-order statistics	
	0 08 072	Pixel(s) type	
	0 12 063	Brightness temperature	
	0 08 072	Pixel(s) type	
	0 12 063	Brightness temperature	
	0 02 150	TOVS/ATOVS/AVHRR instrumentation channel number	
	0 08 023	First-order statistics	
	0 08 072	Pixel(s) type	
	0 12 063	Brightness temperature	
	0 08 072	Pixel(s) type	
	0 12 063	Brightness temperature	
	2 02 000	Change scale	
	2 01 000	Change data width	
		(Satellite – geostationary wind data)	
3 10 014	3 01 072	Satellite identification	Satellite identification, date/time, latitude/longitude
	3 03 041	Wind sequence	
	3 04 011	GOES-I/M info	
3 10 015		(Meteosat radiance data)	
	3 01 072	Satellite identification	
	0 07 024	Satellite zenith angle	
	0 10 002	Height	
	3 03 041	Wind sequence	
	1 01 003	Replicate 1 descriptor 3 times	
	3 04 032	Cloud fraction	
	0 02 152	Satellite instrument used in data processing	
	0 02 024	Integrated mean humidity computational method	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 015 (continued)	0 07 004	Pressure	
	0 07 004	Pressure	
	0 13 003	Relative humidity	
	1 01 003	Replicate 1 descriptor 3 times	
	3 04 033	Clear sky radiance	
3 10 016		(Meteosat Second Generation (MSG) radiance data)	
	3 01 072	Satellite identification	
	0 07 024	Satellite zenith angle	
	0 10 002	Height	
	3 03 041	Wind sequence	
	1 01 012	Replicate 1 descriptor 12 times	
	3 04 032	Cloud fraction	
	0 02 152	Satellite instrument used in data processing	
	0 02 024	Integrated mean humidity computational method	
	0 07 004	Pressure	
	0 07 004	Pressure	
	0 13 003	Relative humidity	
	1 01 012	Replicate 1 descriptor 12 times	
	3 04 033	Clear sky radiance	
3 10 018		(Ozone data)	
	0 01 007	Satellite identifier	
	0 05 040	Orbit number	
	0 04 001	Year	
	0 04 043	Day of the year	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	2 07 002	Increase scale, reference value and data width	
	0 26 030	Measurement integration time	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 33 072	Ozone error	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	2 07 002	Increase scale, reference value and data width	
	0 15 001	Total ozone	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 003	Vertical significance (satellite observations)	= 0 Surface

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 018 (continued)	2 07 001	Increase scale, reference value and data width	
	0 10 004	Pressure	Terrain
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 003	Vertical significance (satellite observations)	Set to missing (cancel)
	0 08 003	Vertical significance (satellite observations)	= 2 Cloud top
	0 33 042	Type of limit represented by following value	= 0 Exclusive lower limit
	2 07 001	Increase scale, reference value and data width	
	0 07 004	Pressure	
	2 07 000	Increase scale, reference value and data width	Cancel
	2 07 002	Increase scale, reference value and data width	
	0 15 001	Total ozone	Below cloud top pressure
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 003	Vertical significance (satellite observations)	Set to missing (cancel)
	2 07 002	Increase scale, reference value and data width	
	0 20 081	Cloud amount in segment	Cloud fraction
	2 07 000	Increase scale, reference value and data width	Cancel
	0 20 065	Snow cover	
	0 08 029	Surface type	
	2 07 004	Increase scale, reference value and data width	
	0 15 030	Aerosol contamination index	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 075	Ascending/descending orbit qualifier	
		(Ozone data)	
3 10 019	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	= 624 SBUV/2
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 07 025	Solar zenith angle	
	0 08 021	Time significance	= 28 Start of scan
	0 07 025	Solar zenith angle	
	0 08 021	Time significance	= 29 End of scan
	0 07 025	Solar zenith angle	
	0 08 021	Time significance	Set to missing (cancel)

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 019 (continued)	0 08 029	Surface type	
	0 05 040	Orbit number	
	0 08 075	Ascending/descending orbit qualifier	
	0 08 003	Vertical significance (satellite observations)	= 0 Surface
	0 10 004	Pressure	= Terrain
	0 08 003	Vertical significance (satellite observations)	Set to missing (cancel)
	2 07 002	Increase scale, reference value and data width	
	0 15 001	Total ozone	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 33 070	Total ozone quality	
	0 15 030	Aerosol contamination index	
	2 07 002	Increase scale, reference value and data width	
	0 20 081	Cloud amount in segment	Cloud fraction
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 003	Vertical significance (satellite observations)	= 2 Cloud top
	0 33 042	Type of limit represented by following value	= 0 Exclusive lower limit
	0 07 004	Pressure	
	2 07 002	Increase scale, reference value and data width	
	0 15 001	Total ozone	Below cloud top pressure
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 003	Vertical significance (satellite observations)	Set to missing (cancel)
	1 13 021	Replicate 13 descriptors 21 times	
	0 07 004	Pressure	Bottom of layer
	0 07 004	Pressure	Top of layer
	2 07 002	Increase scale, reference value and data width	
	0 08 021	Time significance	= 27 First guess
	0 15 005	Ozone p	
	0 08 021	Time significance	Set to missing (cancel)
	0 15 005	Ozone p	
	0 33 007	Per cent confidence	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 026	Matrix significance	= 0 Row of averaging kernel matrix
	1 01 020	Replicate 1 descriptor 20 times	
	0 25 143	Linear coefficient	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 019 (continued)	0 08 026	Matrix significance	Set to missing (cancel)
	0 08 043	Atmospheric chemical or physical constituent type	= 0 Ozone
	1 09 015	Replicate 9 descriptors 15 times	
	0 07 004	Pressure	
	0 08 090	Decimal scale of following significands	
	2 07 006	Increase scale, reference value and data width	
	0 15 008	Significand of volumetric mixing ratio	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 090	Decimal scale of following significands	Set to missing (cancel)
	2 07 002	Increase scale, reference value and data width	
	0 33 007	Per cent confidence	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 043	Atmospheric chemical or physical constituent type	Set to missing (cancel)
	0 33 071	Profile ozone quality	
	1 08 008	Replicate 8 descriptors 8 times	
	2 02 124	Change scale	
	2 01 107	Change data width	
	0 02 071	Spectrographic wavelength	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	2 07 002	Increase scale, reference value and data width	
	0 20 081	Cloud amount in segment	Cloud fraction
	2 07 000	Increase scale, reference value and data width	Cancel
		(Retrieved ozone data)	
3 10 020	3 10 022	Satellite identifier, instrument and product type	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	3 04 034	Latitude/longitude, solar elevation, number of layers	
	3 10 021	Integrated ozone density, height of defined layer	
3 10 021		(Integrated ozone density, height of defined layer)	
	1 08 000	Delayed replication of 8 descriptors	
	0 31 001	Delayed descriptor replication factor	
	2 01 131	Change data width	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 021 (continued)	2 02 129	Change scale	Cancel
	0 07 004	Pressure	
	0 07 004	Pressure	
	2 02 000	Change scale	
	2 01 000	Change data width	
	0 15 020	Integrated ozone density	
	0 10 002	Height	
3 10 022		(Satellite identifier, instrument and product type)	Cancel
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 033	Identification of originating/generating centre	
3 10 023	0 02 172	Product type for retrieved atmospheric gases	Cancel
		(Geostationary multi-channel satellite radiance data)	
	3 01 072	Satellite identification	
	0 30 021	Number of pixels per row	
	0 30 022	Number of pixels per column	
	0 08 012	Land/sea qualifier	
	0 07 024	Satellite zenith angle	
	0 07 025	Solar zenith angle	
	0 10 002	Height	
	1 01 012	Replicate 1 descriptor 12 times	
	3 04 032	Cloud fraction	
	1 05 002	Replicate 5 descriptors 2 times	
	0 02 152	Satellite instrument used in data processing	
	0 02 024	Integrated mean humidity computational method	
	0 07 004	Pressure	
	0 07 004	Pressure	
	0 13 003	Relative humidity	
	1 01 012	Replicate 1 descriptor 12 times	
	3 04 033	Clear sky radiance	
3 10 024		(Geostationary three-channel satellite radiance data)	Cancel
	3 01 072	Satellite identification	
	0 30 021	Number of pixels per row	
	0 30 022	Number of pixels per column	
	0 08 012	Land/sea qualifier	
	0 07 024	Satellite zenith angle	
	0 07 025	Solar zenith angle	
	0 10 002	Height	
	1 01 003	Replicate 1 descriptor 3 times	
	3 04 032	Cloud fraction	
	1 05 002	Replicate 5 descriptors 2 times	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 024 (continued)	0 02 152	Satellite instrument used in data processing	
	0 02 024	Integrated mean humidity computational method	
	0 07 004	Pressure	
	0 07 004	Pressure	
	0 13 003	Relative humidity	
	1 01 003	Replicate 1 descriptor 3 times	
	3 04 033	Clear sky radiance	
3 10 025		(SSMIS temperature data record)	
	0 01 007	Satellite identifier	
	0 08 021	Time significance	Scan start
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	2 01 138	Change data width	
	2 02 131	Change scale	
	0 04 006	Second	Milliseconds
	2 02 000	Change scale	
	2 01 000	Change data width	
	2 01 132	Change data width	
	0 05 041	Scan line number	Scan number
	2 01 000	Change data width	
	2 01 129	Change data width	
	0 05 043	Field of view number	Scene number
	2 01 000	Change data width	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 13 040	Surface flag	
	0 20 029	Rain flag	
	1 04 024	Replicate 4 descriptors 24 times	
	0 05 042	Channel number	
	0 12 163	Brightness temperature	
	0 21 083	Warm target calibration	
	0 21 084	Cold target calibration	
	1 15 003	Replicate 15 descriptors 3 times	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	2 01 142	Change data width	
	2 02 131	Change scale	
	0 04 026	Time period or displacement	Ephemeris milliseconds
	2 02 000	Change scale	
	2 01 000	Change data width	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 025 (continued)	0 05 001	Latitude (high accuracy)	Ephemeris
	0 06 001	Longitude (high accuracy)	Ephemeris
	2 01 138	Change data width	
	2 02 129	Change scale	
	0 07 001	Height of station	Ephemeris
	2 02 000	Change scale	
	2 01 000	Change data width	
	0 08 021	Time significance	Orbit start
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 05 040	Orbit number	
	1 01 003	Replicate 1 descriptor 3 times	
	0 12 070	Warm load temperature	
	0 25 054	SSMIS subframe ID number	
	1 01 004	Replicate 1 descriptor 4 times	
	0 25 055	Multiplexer housekeeping	
	0 08 007	Dimensional significance	Line
	1 04 028	Replicate 4 descriptors 28 times	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 02 111	Radar incidence angle	Earth angle
	0 05 021	Bearing or azimuth	
		(Satellite radio occultation data)	
3 10 026	3 10 022	Satellite identifier, instrument and product type	
	0 25 060	Software identification	
	0 08 021	Time significance	= 17 Start of phenomenon
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 01 138	Change data width	16 bits long
	2 02 131	Change scale	Scale: 3
	0 04 006	Second	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 33 039	Quality flags for radio occultation data	
	0 33 007	Per cent confidence	Whole message
	3 04 030	Location of platform	
	3 04 031	Speed of platform	
	0 02 020	Satellite classification	
	0 01 050	Platform transmitter ID number	
	2 02 127	Change scale	Scale: 1
	3 04 030	Location of platform	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 026 (continued)	2 02 000	Change scale	Cancel
	3 04 031	Speed of platform	
	2 01 133	Change data width	18 bits long
	2 02 131	Change scale	Scale: 3
	0 04 016	Time increment	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	3 01 021	Latitude/longitude (high accuracy)	
	3 04 030	Location of platform	
	0 10 035	Earth's local radius of curvature	
	0 05 021	Bearing or azimuth	
	0 10 036	Geoid undulation	
	1 13 000	Delayed replication of 13 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	3 01 021	Latitude/longitude (high accuracy)	
	0 05 021	Bearing or azimuth	
	1 08 000	Delayed replication of 8 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 02 121	Mean frequency	
	0 07 040	Impact parameter	
	0 15 037	Bending angle	
	0 08 023	First-order statistics	= 13 Root-mean-square
	2 01 125	Change data width	20 bits long
	0 15 037	Bending angle	
	2 01 000	Change data width	Cancel
	0 08 023	First-order statistics	Set to missing
	0 33 007	Per cent confidence	All data for current replication
	1 08 000	Delayed replication of 8 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 07 007	Height	
	0 15 036	Atmospheric refractivity	
	0 08 023	First-order statistics	= 13 Root-mean-square
	2 01 123	Change data width	14 bits long
	0 15 036	Atmospheric refractivity	
	2 01 000	Change data width	Cancel
	0 08 023	First-order statistics	Set to missing
	0 33 007	Per cent confidence	All data for current height
	1 16 000	Delayed replication of 16 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 07 009	Geopotential height	
	0 10 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 13 001	Specific humidity	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 026 (continued)	0 08 023	First-order statistics	= 13 Root-mean-square
	2 01 120	Change data width	6 bits long
	0 10 004	Pressure	
	2 01 000	Change data width	Cancel
	2 01 122	Change data width	6 bits long
	0 12 001	Temperature/air temperature	
	2 01 000	Change data width	Cancel
	2 01 123	Change data width	9 bits long
	0 13 001	Specific humidity	
	2 01 000	Change data width	Cancel
	0 08 023	First-order statistics	Set to missing
	0 33 007	Per cent confidence	All data for current height
	0 08 003	Vertical significance (satellite observations)	= 0 Surface
	0 07 009	Geopotential height	
	0 10 004	Pressure	
	0 08 023	First-order statistics	= 13 Root-mean-square
	2 01 120	Change data width	6 bits long
	0 10 004	Pressure	
	2 01 000	Change data width	Cancel
	0 08 023	First-order statistics	Set to missing
	0 33 007	Per cent confidence	Surface data
		(All sky radiance product main sequence) (see Note 1)	
3 10 027	3 01 071	Satellite identifier/Generating resolution	Product information
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 30 021	Number of pixels per row	
	0 30 022	Number of pixels per column	
	0 10 002	Height	Orbit height
	3 04 036	Cloud coverage	
	0 02 152	Satellite instrument used in data processing	
	0 02 167	Radiance computational method	
	1 01 011	Replicate 1 descriptor 11 times	
	3 04 035	All sky radiance data	
		(All sky radiance product main sequence)	
3 10 028	3 01 071	Satellite identifier/Generating resolution	Product information
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 30 021	Number of pixels per row	
	0 30 022	Number of pixels per column	
	0 10 002	Height	Orbit height

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 028 (continued)	3 04 036	Cloud coverage	
	0 02 152	Satellite instrument used in data processing	
	0 02 167	Radiance computational method	
	1 01 011	Replicate 1 descriptor 11 times	
	3 04 037	All sky radiance data	
3 10 029		(Layer, ozone, height, temperature and water vapour)	
	1 10 000	Delayed replication of 10 descriptors	
	0 31 001	Delayed descriptor replication factor	
	2 01 138	Change data width	
	2 02 130	Change scale	
	0 07 004	Pressure	
	0 07 004	Pressure	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 15 020	Integrated ozone density	
	0 10 002	Height	
	0 12 101	Temperature/air temperature	
	0 13 098	Integrated water vapour density	
3 10 030		(MIPAS or GOMOS instruments reporting)	
	3 10 022	Satellite identifier, instrument and product type	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	3 04 034	Latitude/longitude, solar elevation, number of layers	
3 10 050	3 10 029	Layer, ozone, height, temperature and water vapour	
		(Satellite collocated 1C reports with 3 instruments)	
	3 10 051	Satellite position and instrument temperatures	
	3 10 052	Satellite instrument type and position	AIRS
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 10 053	Satellite channels and brightness temperatures with expanded channel set	AIRS
	1 01 004	Replicate 1 descriptor 4 times	
	3 10 054	Satellite visible channels and albedos with expanded channel set	
	0 20 010	Cloud cover (total)	
	3 10 052	Satellite instrument type and position	AMSU-A
	1 01 015	Replicate 1 descriptor 15 times	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 050 (continued)	3 10 053	Satellite channels and brightness temperatures with expanded channel set	AMSU-A
	3 10 052	Satellite instrument type and position	HSB
	1 01 005	Replicate 1 descriptor 5 times	
	3 10 053	Satellite channels and brightness temperatures with expanded channel set	HSB
3 10 051		(Satellite position and instrument temperatures)	
	0 01 007	Satellite identifier	
	0 05 040	Orbit number	
	2 01 133	Change data width	
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel
	2 01 132	Change data width	
	0 25 070	Major frame count	
	2 01 000	Change data width	Cancel
	2 02 126	Change scale	
	0 07 001	Height of station	
	2 02 000	Change scale	Cancel
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	1 02 009	Replicate 2 descriptors 9 times	
	0 02 151	Radiometer identifier	
	0 12 064	Instrument temperature	
		(Satellite instrument type and position)	
3 10 052	0 02 019	Satellite instruments	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 02 131	Change scale	
	2 01 138	Change data width	
	0 04 006	Second	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 05 043	Field of view number	
		(Satellite channels and brightness temperatures with expanded channel set)	
	2 01 134	Change data width	
3 10 053	0 05 042	Channel number	
	2 01 000	Change data width	Cancel

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 053 (continued)	0 25 076	Log ₁₀ of (temperature-radiance central wave number) for ATOVS	Scale: 2
	0 33 032	Channel quality flags for ATOVS	
	0 12 163	Brightness temperature	
3 10 054		(Satellite visible channels and albedos with expanded channel set)	Cancel
	2 01 134	Change data width	
	0 05 042	Channel number	
	2 01 000	Change data width	
	0 25 076	Log ₁₀ of (temperature-radiance central wave number) for ATOVS	
	0 33 032	Channel quality flags for ATOVS	
	2 01 131	Change data width	
	2 02 129	Change scale	
	1 02 002	Replicate 2 descriptors 2 times	
	0 08 023	First-order statistics	
	0 14 027	Albedo	
	0 08 023	First-order statistics	
	2 02 000	Change scale	
	2 01 000	Change data width	
		(Satellite radiance/channel principal components)	
3 10 055	3 10 051	Satellite position and instrument temperatures	AIRS
	3 10 052	Satellite instrument type and position	
	1 02 020	Replicate 2 descriptors 20 times	
	0 25 076	Log ₁₀ of (temperature-radiance central wave number) for ATOVS	
	0 25 052	Log ₁₀ of principal components normalized fit to data	Satellite radiance
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	0 25 050	Principal component score	
3 10 060		(CrIS (Cross-Track Infrared Sounder) radiance data)	Cancel
	0 01 007	Satellite identifier	
	0 01 033	Identification of originating/generating centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 060 (continued)	3 04 030	Location of platform	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 08 075	Ascending/descending orbit qualifier	
	2 01 133	Change data width	Increase bit width
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel increase bit width
	0 05 045	Field of regard number	
	0 05 043	Field of view number	
	0 05 040	Orbit number	
	0 10 001	Height of land surface	
	2 01 129	Change data width	Increase bit width
	0 07 002	Height or altitude	
	2 01 000	Change data width	Cancel increase bit width
	2 02 127	Change scale	Increase scale
	2 01 125	Change data width	Increase bit width
	0 21 166	Land fraction	
	2 01 000	Change data width	Cancel increase bit width
	2 02 000	Change scale	Cancel increase scale
	0 08 012	Land/sea qualifier	
	0 20 010	Cloud cover (total)	
	0 20 014	Height of top of cloud	
	0 02 165	Radiance type flags	
	0 33 075	Scan-level quality flags	
	1 07 003	Replicate 7 descriptors 3 times	
	0 08 076	Type of band	
	0 06 029	Wave number	Start of range
	0 06 029	Wave number	End of range
	0 25 140	Start channel	
	0 25 141	End channel	
	0 33 076	Calibration quality flags	
	0 33 077	Field-of-view quality flags	
	0 08 076	Type of band	Set to missing (cancel)
	0 33 078	Geolocation quality	
	0 33 003	Quality information	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 002	Extended delayed descriptor replication factor	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 060 (continued)	2 01 133	Change data width	Increase bit width
	0 05 042	Channel number	
	2 01 000	Change data width	Cancel increase bit width
	0 14 044	Channel radiance	
3 10 061		(ATMS (Advanced Technology Microwave Sounder) data)	
	0 01 007	Satellite identifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 05 040	Orbit number	
	0 05 041	Scan line number	
	0 05 043	Field of view number	
	0 33 079	Granule level quality flags	
	0 33 080	Scan level quality flags	
	0 33 078	Geolocation quality	
	3 01 021	Latitude/longitude (high accuracy)	
	2 01 129	Change data width	Increase bit width
	0 07 002	Height or altitude	
	2 01 000	Change data width	Cancel increase bit width
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 25 075	Satellite antenna corrections version number	
	1 11 000	Delayed replication of 11 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 05 042	Channel number	
	2 02 131	Change scale	Increase scale by 3
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel increase scale
	0 02 104	Antenna polarization	
	0 12 066	Antenna temperature	
	0 12 163	Brightness temperature	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 061 (continued)	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	0 33 081	Channel data quality flags	
3 10 062		(VIIRS (Visible/Infrared Imager Radiometer Suite) data)	
	0 01 007	Satellite identifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 05 040	Orbit number	
	2 01 133	Change data width	Increase bit width
	0 05 041	Scan line number	
	0 05 043	Field of view number	
	2 01 000	Change data width	Cancel increase bit width
	0 08 076	Type of band	
	0 33 082	Geolocation quality flags	
	3 01 021	Latitude/longitude (high accuracy)	
	2 01 129	Change data width	Increase bit width
	0 07 002	Height or altitude	
	2 01 000	Change data width	Cancel increase bit width
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 08 072	Pixel(s) type	
	0 08 029	Surface type	
	1 05 000	Delayed replication of 5 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 05 042	Channel number	
	0 02 155	Satellite channel wavelength	
	0 33 083	Radiance data quality flags	
	0 14 043	Channel radiance	
	0 15 042	Reflectance	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 063	0 01 007	(SST (Sea-surface temperature) data) Satellite identifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 05 040	Orbit number	
	2 01 133	Change data width	Increase bit width
	0 05 041	Scan line number	
	0 05 043	Field of view number	
	2 01 000	Change data width	Cancel increase bit width
	0 33 082	Geolocation quality flags	
	3 01 021	Latitude/longitude (high accuracy)	
	2 01 129	Change data width	Increase bit width
	0 07 002	Height or altitude	
	2 01 000	Change data width	Cancel increase bit width
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 08 075	Ascending/descending orbit qualifier	
	0 08 013	Day/night qualifier	
	0 08 072	Pixel(s) type	
	0 33 084	Pixel level quality flags	
	0 07 062	Depth below sea/water surface	
	0 33 086	Quality of pixel level retrieval	
	0 22 043	Sea/water temperature	
	0 07 062	Depth below sea/water surface	Top of layer
	0 07 062	Depth below sea/water surface	Bottom of layer
	0 33 086	Quality of pixel level retrieval	
	0 22 043	Sea/water temperature	
3 10 064		(AOT (Aerosol optical thickness) data)	
	0 01 007	Satellite identifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 064 (continued)	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 05 040	Orbit number	
	2 01 133	Change data width	
	0 05 041	Scan line number	
	0 05 043	Field of view number	
	2 01 000	Change data width	Cancel
	0 33 082	Geolocation quality flags	
	3 01 021	Latitude/longitude (high accuracy)	
	2 01 129	Change data width	
	0 07 002	Height or altitude	
	2 01 000	Change data width	Cancel
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 08 075	Ascending/descending orbit qualifier	
	0 08 029	Surface type	
	0 08 046	Atmospheric chemical or physical constituent type	
	0 33 085	Aerosol optical thickness quality flags	
	0 33 086	Quality of pixel level retrieval	
	0 15 049	Aerosol Angstrom wavelength exponent	
	0 33 086	Quality of pixel level retrieval	
	1 02 011	Replicate 2 descriptors 11 times	
	0 02 155	Satellite channel wavelength	
	0 15 062	Aerosol optical thickness	
		(OMPS (Ozone mapping and profiler suite) nadir profile data)	
3 10 065	0 01 007	Satellite identifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 065 (continued)	2 07 003	Increase scale, reference value and data width	Cancel
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	
	0 05 040	Orbit number	
	0 33 082	Geolocation quality flags	
	3 01 021	Latitude/longitude (high accuracy)	
	2 01 129	Change data width	
	0 07 002	Height or altitude	
	2 01 000	Change data width	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	Cancel
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 08 075	Ascending/descending orbit qualifier	
	0 33 071	Profile ozone quality	
	0 33 070	Total ozone quality	
	0 20 021	Type of precipitation	
	0 15 045	Sulphur dioxide	
	0 15 046	Volcano contamination index	
	0 08 065	Sun-glint indicator	
	0 33 087	Extent of satellite within South Atlantic anomaly	Cancel
	0 08 003	Vertical significance (satellite observations)	
	0 10 004	Pressure	
	0 08 003	Vertical significance (satellite observations)	
	2 07 002	Increase scale, reference value and data width	
	0 15 001	Total ozone	
	2 07 000	Increase scale, reference value and data width	
	1 05 012	Replicate 5 descriptors 12 times	
	0 10 040	Number of retrieved layers	
	0 10 004	Pressure	
	2 07 003	Increase scale, reference value and data width	Cancel
	0 15 005	Ozone p	
	2 07 000	Increase scale, reference value and data width	
	0 08 046	Atmospheric chemical or physical constituent type	
	1 07 019	Replicate 7 descriptors 19 times	
	0 10 040	Number of retrieved layers	
	0 10 004	Pressure	
	0 08 090	Decimal scale of following significands	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 065 (continued)	2 07 006	Increase scale, reference value and data width	
	0 15 008	Significand of volumetric mixing ratio	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 090	Decimal scale of following significands	Set to missing (cancel)
3 10 066		(OMPS (Ozone mapping and profiler suite) total column data)	
	0 01 007	Satellite identifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 05 040	Orbit number	
	0 33 082	Geolocation quality flags	
	3 01 021	Latitude/longitude (high accuracy)	
	2 01 129	Change data width	
	0 07 002	Height or altitude	
	2 01 000	Change data width	Cancel
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 08 075	Ascending/descending orbit qualifier	
	0 20 081	Cloud amount in segment	Cloud fraction
	2 07 004	Increase scale, reference value and data width	
	0 15 030	Aerosol contamination index	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 20 065	Snow cover	
	0 15 041	Sulphur dioxide index	
	0 33 086	Quality of pixel level retrieval	
	0 33 087	Extent of satellite within South Atlantic anomaly	
	0 33 088	Ozone total column quality flag	
	0 08 003	Vertical significance (satellite observations)	= 0 Surface
	2 07 001	Increase scale, reference value and data width	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 066 (continued)	0 07 004	Pressure	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 003	Vertical significance (satellite observations)	Set to missing (cancel)
	2 07 002	Increase scale, reference value and data width	
	0 15 001	Total ozone	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 003	Vertical significance (satellite observations)	= 2 Cloud top
	0 33 042	Type of limit represented by following value	= 0 Exclusive lower limit (>)
	2 07 001	Increase scale, reference value and data width	
	0 07 004	Pressure	Cloud top pressure
	2 07 000	Increase scale, reference value and data width	Cancel
	2 07 002	Increase scale, reference value and data width	
	0 15 001	Total ozone	Below cloud
	2 07 000	Increase scale, reference value and data width	Cancel
	0 08 003	Vertical significance (satellite observations)	Set to missing (cancel)
	0 01 032	Generating application	= 0 First guess Defined by local generating centre
	2 07 002	Increase scale, reference value and data width	
	0 15 001	Total ozone	First guess total column ozone
	2 07 000	Increase scale, reference value and data width	Cancel
		(Satellite-derived winds) (see Note 2)	
		<i>Processing information</i>	
3 10 067	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 25 061	Software identification and version number	
	0 25 062	Database identification	
		<i>Satellite/instrument identification</i>	
	0 01 007	Satellite identifier	
	0 02 153	Satellite channel centre frequency	
	0 01 012	Direction of motion of moving observing platform	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 067 (continued)	2 01 138	Change data width	Cancel
	0 02 026	Cross-track resolution	
	0 02 027	Along-track resolution	
	2 01 000	Change data width	
		<i>Methods</i>	
	0 02 028	Segment size at nadir in x-direction	Target box size
	0 02 029	Segment size at nadir in y-direction	Target box size
	0 02 161	Wind processing method	
	0 02 164	Tracer correlation method	
	0 02 023	Satellite-derived wind computation method	
	0 08 012	Land/sea qualifier	
	0 08 013	Day/night qualifier	
		<i>Final AMV data</i>	
	0 01 124	Grid point identifier	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	0 04 086	Long time period or displacement	Seconds
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 11 003	u-component	
	0 11 004	v-component	
	0 02 162	Extended height assignment method	
	0 07 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 20 014	Height of top of cloud	
	0 07 024	Satellite zenith angle	
	0 01 023	Observation sequence number	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 02 162	Extended height assignment method	
	0 07 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 20 014	Height of top of cloud	
		<i>Image information (for each image used)</i>	
	1 13 000	Delayed replication of 13 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 04 086	Long time period or displacement	Seconds
	0 02 020	Satellite classification	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 05 042	Channel number	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 067 (continued)	0 02 153	Satellite channel centre frequency	
	0 05 040	Orbit number	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 02 162	Extended height assignment method	
	0 07 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 20 014	Height of top of cloud	
		<i>Intermediate vectors (for each component vector)</i>	
	1 19 000	Delayed replication of 19 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 04 086	Long time period or displacement	Seconds
	0 04 086	Long time period or displacement	Seconds
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 11 003	u-component	
	0 11 004	v-component	
	0 11 113	Tracking correlation of vector	
	0 25 148	Coefficient of variation	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 023	First order statistics	
	0 11 003	u-component	
	0 11 004	v-component	
	0 08 023	First order statistics	Set to missing (cancel)
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 20 111	x-axis error ellipse major component	
	0 20 112	y-axis error ellipse minor component	
	0 20 114	Angle of x-axis in error ellipse	
		<i>Corresponding forecast data</i>	
	0 01 033	Identification of originating/generating centre	
	0 08 021	Time significance	= 27 First guess
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
	0 07 004	Pressure	
	0 08 021	Time significance	= 4 Forecast
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
	0 07 004	Pressure	
	0 08 021	Time significance	Set to missing (cancel)
	0 08 086	Vertical significance for NWP	= 10 Level of best fit
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 067 (continued)	0 07 004	Pressure	
	0 08 086	Vertical significance for NWP	Set to missing (cancel)
		<i>Final AMV quality</i>	
	1 02 004	Replicate 2 descriptors 4 times	
	0 01 032	Generating application	
	0 33 007	Per cent confidence	
	0 08 092	Measurement uncertainty expression	= 0 Standard uncertainty
	0 11 003	u-component	
	0 11 004	v-component	
	0 07 004	Pressure	
	0 08 092	Measurement uncertainty expression	Set to missing (cancel)
	0 33 066	AMV quality flag	
		<i>Cloud data and microphysics (refers to the nominal image used for height assignment)</i>	
	0 20 081	Cloud amount in segment	
	0 20 012	Cloud type	
	0 20 056	Cloud phase	
	1 17 000	Delayed replication of 17 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 023	First order statistics	
	0 20 016	Pressure at top of cloud	
	0 08 092	Measurement uncertainty expression	= 0 Standard uncertainty
	0 08 003	Vertical significance (satellite observations)	= 2 Cloud top
	0 12 001	Temperature/air temperature	
	0 08 003	Vertical significance (satellite observations)	Set to missing (cancel)
	0 20 016	Pressure at top of cloud	
	0 08 092	Measurement uncertainty expression	Set to missing (cancel)
	0 25 149	Optimal estimation cost	
	0 20 016	Pressure at top of cloud	
	0 20 014	Height of top of cloud	
	0 13 093	Cloud optical thickness	
	0 13 109	Ice/liquid water path	
	0 40 038	Cloud particle size	
	0 08 011	Meteorological feature	= 12 Cloud
	0 14 050	Emissivity	
	0 08 011	Meteorological feature	Set to missing (cancel)
	0 08 023	First order statistics	Set to missing (cancel)

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 068	0 08 070	(VASS field of view variables) Vertical sounding product qualifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 12 064	Instrument temperature	
	0 05 040	Orbit number	
	2 01 136	Change data width	
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel
	0 05 043	Field of view number	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 01 138	Change data width	
	2 02 131	Change scale	
	0 04 006	Second	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	2 02 126	Change scale	
	0 07 001	Height of station	
	2 02 000	Change scale	Cancel
	0 10 007	Height	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 13 040	Surface flag	
	0 12 101	Temperature/air temperature	Land or ocean surface temperature
	2 01 131	Change data width	
	2 02 129	Change scale	
	0 11 011	Wind direction at 10 m	Ocean surface wind
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	2 01 130	Change data width	
	2 02 129	Change scale	
	0 11 012	Wind speed at 10 m	Ocean surface wind
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 20 029	Rain flag	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 068 (continued)	0 20 010	Cloud cover (total)	
	0 20 014	Height of top of cloud	
	0 13 162	Cloud liquid water	
	0 14 050	Emissivity	
3 10 069		(VASS channel variables)	
	0 05 042	Channel number	
	2 01 139	Change data width	
	0 02 155	Satellite channel wavelength	
	2 01 000	Change data width	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 007	Per cent confidence	
	2 01 132	Change data width	
	2 02 129	Change scale	
	0 12 063	Brightness temperature	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
3 10 070		(VASS MWTS report of FY-3)	
	3 10 068	VASS field of view variables	
	1 01 013	Replicate 1 descriptor 13 times	
3 10 071	3 10 069	VASS channel variables	
		(VASS MWHS report of FY-3)	
	3 10 068	VASS field of view variables	
3 10 072	1 01 015	Replicate 1 descriptor 15 times	
	3 10 069	VASS channel variables	
		(VASS IRAS report of FY-3)	
3 10 077	3 10 068	VASS field of view variables	
	1 01 026	Replicate 1 descriptor 26 times	
	3 10 069	VASS channel variables	
3 10 077		(Satellite-derived winds)	
		<i>Processing information</i>	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 25 061	Software identification and version number	
	0 25 062	Database identification	
		<i>Satellite/instrument identification</i>	
	0 01 007	Satellite identifier	
	0 02 153	Satellite channel centre frequency	
	0 01 012	Direction of motion of moving observing platform	
	2 01 138	Change data width	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 077 (continued)	0 02 026	Cross-track resolution	Cancel
	0 02 027	Along-track resolution	
	2 01 000	Change data width <i>Methods</i>	
	0 02 028	Segment size at nadir in x-direction	
	0 02 029	Segment size at nadir in y-direction	
	0 02 161	Wind processing method	
	0 02 164	Tracer correlation method	
	0 02 023	Satellite derived wind computation method	
	0 08 012	Land/sea qualifier	
	0 08 013	Day/night qualifier <i>Final AMV data</i>	
	0 01 124	Grid point identifier	Target box size
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	0 04 086	Long time period or displacement	Seconds
	0 02 162	Extended height assignment method	
	0 07 004	Pressure	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 11 003	u-component	
	0 11 004	v-component	
	0 12 001	Temperature/air temperature	
	0 20 014	Height of top of cloud	
	0 07 024	Satellite zenith angle	
	0 01 023	Observation sequence number	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 02 162	Extended height assignment method	
	0 07 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 20 014	Height of top of cloud <i>Image information (for each image used)</i>	
	1 13 000	Delayed replication of 13 descriptors	Seconds
	0 31 001	Delayed descriptor replication factor	
	0 04 086	Long time period or displacement	
	0 02 020	Satellite classification	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 05 042	Channel number	
	0 02 153	Satellite channel centre frequency	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 077 (continued)	0 05 040	Orbit number	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 02 162	Extended height assignment method	
	0 07 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 20 014	Height of top of cloud	
		<i>Intermediate vectors (for each component vector)</i>	
	1 19 000	Delayed replication of 19 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 04 086	Long time period or displacement	Seconds
	0 04 086	Long time period or displacement	Seconds
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 11 003	u-component	
	0 11 004	v-component	
	0 11 113	Tracking correlation of vector	
	0 25 148	Coefficient of variation	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 023	First order statistics	
	0 11 003	u-component	
	0 11 004	v-component	
	0 08 023	First order statistics	Set to missing (cancel)
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 20 111	x-axis error ellipse major component	
	0 20 112	y-axis error ellipse minor component	
	0 20 114	Angle of x-axis in error ellipse	
		<i>Corresponding forecast data</i>	
	0 01 033	Identification of originating/generating centre	
	0 08 021	Time significance	= 27 First guess
	0 07 004	Pressure	
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
	0 08 021	Time significance	= 4 Forecast
	0 07 004	Pressure	
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
	0 08 021	Time significance	Set to missing (cancel)
	0 08 086	Vertical significance for NWP	= 10 Level of best fit
	0 07 004	Pressure	
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 077 (continued)	0 08 086	Vertical significance for NWP	Set to missing (cancel)
		<i>Final AMV quality</i>	
	1 02 004	Replicate 2 descriptors 4 times	
	0 01 044	Standard generating application	
	0 33 007	Per cent confidence	
	0 08 092	Measurement uncertainty expression	= 0 Standard uncertainty
	0 07 004	Pressure	
	0 11 003	u-component	
	0 11 004	v-component	
	0 08 092	Measurement uncertainty expression	Set to missing (cancel)
	0 33 066	AMV quality flag	
		<i>Cloud data and microphysics (refers to the nominal image used for height assignment)</i>	
	0 20 081	Cloud amount in segment	
	0 20 012	Cloud type	
	0 20 056	Cloud phase	
	1 17 000	Delayed replication of 17 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 023	First order statistics	
	0 20 016	Pressure at the top of cloud	
	0 08 092	Measurement uncertainty expression	= 0 Standard uncertainty
	0 08 003	Vertical significance (satellite observations)	= 2 Cloud top
	0 12 001	Temperature/air temperature	
	0 08 003	Vertical significance (satellite observations)	Set to missing (cancel)
	0 20 016	Pressure at the top of cloud	
	0 08 092	Measurement uncertainty expression	Set to missing (cancel)
	0 25 149	Optimal estimation cost	
	0 20 016	Pressure at the top of cloud	
	0 20 014	Height of the top of cloud	
	0 13 093	Cloud optical thickness	
	0 13 109	Ice/liquid water path	
	0 40 038	Cloud particle size	
	0 08 011	Meteorological feature	= 12 Cloud
	0 14 050	Emissivity	
	0 08 011	Meteorological feature	Set to missing (cancel)
	0 08 023	First order statistics	Set to missing (cancel)
		<u>(Satellite sounding data)</u>	
	<u>0 01 007</u>	<u>Satellite identifier</u>	
	<u>0 01 016</u>	<u>Satellite sub-identifier</u>	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 02 019	Satellite instruments	Cancel
	0 02 020	Satellite classification	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	0 05 040	Orbit number	
	2 01 132	Change data width	
	0 05 041	Scan line number	
	2 01 000	Change data width	
	0 05 043	Field of view number	
	0 33 079	Granule level quality flags	
	0 33 080	Scan level quality flags	
	0 33 078	Geolocation quality	
	0 07 002	Height or altitude	
	1 02 003	Replicate 2 descriptors 3 times	
	0 08 097	Method used to calculate the average instrument temperature	
	0 12 164	Instrument temperature	
	1 17 000	Delayed replication of 17 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	1 09 000	Delayed replication of 9 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 042	Channel number	
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	0 02 104	Antenna polarization	
	0 12 066	Antenna temperature	
	0 12 163	Brightness temperature	
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	0 33 094	Calibration quality control flags	
		(Ice Cloud Imager Data (level 1B))	
3 10 080	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 01 007	Satellite identifier	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 02 019	Satellite instruments	
	0 05 040	Orbit number	
	0 25 061	Software identification and version number	
	2 01 133	Change data width	Add 8 to descriptor width
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	Cancel
	2 02 126	Change scale	Add -2 to descriptor scale
	0 07 001	Height of station	Spacecraft altitude
	2 02 000	Change scale	Cancel
	0 05 063	Spacecraft roll	
	0 05 064	Spacecraft pitch	
	0 05 066	Spacecraft yaw	
	0 05 077	Sub-satellite point latitude	
	0 06 043	Sub-satellite point longitude	
	0 06 041	Earth scan sample number	
	0 06 042	Space/moon scan sample number	
	0 08 098	Source of temperature measurement	Onboard calibration target (0)
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	Space view reflector (1)
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	Main reflector (2)
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	Sun shield (4)
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	Cancel significance (15)
	0 07 074	Solar elevation angle in instrument reference frame	
	0 05 076	Solar azimuth in instrument reference frame	
	2 01 124	Change data width	Add -4 to descriptor width
	2 02 127	Change scale	Add -1 to descriptor scale
	0 25 084	Geometric rotational angle	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 33 100	ICI temperatures flag	
	0 33 102	ICI scan quality flag	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 33 104	ICI navigation status flag	
	0 33 105	ICI processing flags	
	1 13 007	Replicate 13 descriptors 7 times	
	0 05 078	Horn number	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 07 073	Angle between moon and space view	
	2 01 132	Change data width	Add 4 to descriptor width
	2 02 129	Change scale	Add 1 to descriptor scale
	0 21 166	Land fraction	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	1 17 003	Replicate 17 descriptors 3 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 101	ICI calibration flag	
	0 33 103	ICI data quality flag	
	0 02 104	Antenna polarization	
	2 01 131	Change data width	Add 3 to descriptor width
	2 02 136	Change scale	Add 8 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 002	Replicate 17 descriptors 2 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 101	ICI calibration flag	
	0 33 103	ICI data quality flag	
	0 02 104	Antenna polarization	
	2 01 132	Change data width	Add 4 to descriptor width
	2 02 136	Change scale	Add 8 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 003	Replicate 17 descriptors 3 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 101	ICI calibration flag	
	0 33 103	ICI data quality flag	
	0 02 104	Antenna polarization	
	2 01 133	Change data width	Add 5 to descriptor width
	2 02 136	Change scale	Add 8 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 003	Replicate 17 descriptors 3 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 101	ICI calibration flag	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 33 103	ICI data quality flag	
	0 02 104	Antenna polarization	
	2 01 133	Change data width	Add 5 to descriptor width
	2 02 136	Change scale	Add 8 to descriptor scale
	0 140 45	Channel radiance	
	2 020 00	Change scale	Cancel
	2 010 00	Change data width	Cancel
	0 121 58	Noise-equivalent delta temperature while viewing cold target	
	0 121 59	Noise-equivalent delta temperature while viewing warm target	
	1 17 002	Repeat 17 descriptors 2 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 101	ICI calibration flag	
	0 33 103	ICI data quality flag	
	0 02 104	Antenna polarization	
	2 01 131	Change data width	Add 3 to descriptor width
	2 02 135	Change scale	Add 7 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
		(Microwave Imager Data (level 1B))	
	3 10 081	0 01 033	Identification of originating/generating centre
		0 01 034	Identification of originating/generating sub-centre
		0 01 007	Satellite identifier
		0 02 019	Satellite instruments
		0 05 040	Orbit number
		0 25 061	Software identification and version number
		2 01 133	Change data width
		0 05 041	Scan line number
		2 01 000	Change data width
			Add 8 to descriptor width
			Cancel

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	Cancel
	2 02 126	Change scale	Add -2 to descriptor scale
	0 07 001	Height of station	Spacecraft altitude
	2 02 000	Change scale	Cancel
	0 05 063	Spacecraft roll	
	0 05 064	Spacecraft pitch	
	0 05 066	Spacecraft yaw	
	0 05 077	Sub-satellite point latitude	
	0 06 043	Sub-satellite point longitude	
	0 06 041	Earth scan sample number	
	0 06 042	Space/moon scan sample number	
	0 08 098	Source of temperature measurement	Onboard calibration target (0)
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	Space view reflector (1)
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	Main reflector (2)
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	Racetrack (3)
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	Cancel significance (15)
	0 07 074	Solar elevation angle in instrument reference frame	
	0 05 076	Solar azimuth in instrument reference frame	
	2 01 124	Change data width	Add -4 to descriptor width
	2 02 127	Change scale	Add -1 to descriptor scale
	0 25 084	Geometric rotational angle	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 33 095	MWI temperatures flag	
	0 33 097	MWI scan quality flag	
	0 33 106	MWI processing flags	
	0 33 099	MWI navigation status flag	
	1 13 007	Replicate 13 descriptors 8 times	
	0 05 078	Horn number	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 024	Satellite zenith angle	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 07 073	Angle between moon and space view	
	2 01 132	Change data width	Add 4 to descriptor width
	2 02 129	Change scale	Add 1 to descriptor scale
	0 21 166	Land fraction	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	1 17 001	Replicate 17 descriptors 1 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 096	MWI calibration flag	
	0 33 098	MWI data quality flag	
	0 02 104	Antenna polarization	
	2 01 131	Change data width	Add 3 to descriptor width
	2 02 138	Change scale	Add 10 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 002	Replicate 17 descriptors 2 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 096	MWI calibration flag	
	0 33 098	MWI data quality flag	
	0 02 104	Antenna polarization	
	2 01 132	Change data width	Add 4 to descriptor width

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	2 02 138	Change scale	Add 10 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 003	Replicate 17 descriptors 3 times 333	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 096	MWI calibration flag	
	0 33 098	MWI data quality flag	
	0 02 104	Antenna polarization	
	2 01 132	Change data width	Add 4 to descriptor width
	2 02 138	Change scale	Add 10 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 003	Replicate 17 descriptors 3 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 096	MWI calibration flag	
	0 33 098	MWI data quality flag	
	0 02 104	Antenna polarization	
	2 01 131	Change data width	Add 3 to descriptor width
	2 02 137	Change scale	Add 9 to descriptor scale
	0 14 045	Channel radiance	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 002	Replicate 17 descriptors 2 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 096	MWI calibration flag	
	0 33 098	MWI data quality flag	
	0 02 104	Antenna polarization	
	2 01 132	Change data width	Add 4 to descriptor width
	2 02 137	Change scale	Add 9 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 003	Replicate 17 descriptors 3 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 096	MWI calibration flag	
	0 33 098	MWI data quality flag	
	0 02 104	Antenna polarization	
	2 01 133	Change data width	Add 5 to descriptor width
	2 02 137	Change scale	Add 9 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 003	Replicate 17 descriptors 3 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 096	MWI calibration flag	
	0 33 098	MWI data quality flag	
	0 02 104	Antenna polarization	
	2 01 131	Change data width	Add 3 to descriptor width
	2 02 136	Change scale	Add 8 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	
	0 12 159	Noise-equivalent delta temperature while viewing warm target	
	1 17 002	Replicate 17 descriptors 2 times	
	0 05 042	Channel number	
	2 02 131	Change scale	Add 3 to descriptor scale
	0 02 153	Satellite channel centre frequency	
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	0 33 096	MWI calibration flag	
	0 33 098	MWI data quality flag	
	0 02 104	Antenna polarization	
	2 01 131	Change data width	Add 3 to descriptor width
	2 02 136	Change scale	Add 8 to descriptor scale
	0 14 045	Channel radiance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 12 158	Noise-equivalent delta temperature while viewing cold target	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
<u>3 10 082</u>	<u>0 12 159</u>	Noise-equivalent delta temperature while viewing warm target	
		(Microwave Sounder Data (level 1B))	
	<u>0 08 070</u>	Vertical sounding product qualifier	
	<u>0 01 033</u>	Identification of originating/generating centre	
	<u>0 01 034</u>	Identification of originating/generating sub-centre	
	<u>0 01 007</u>	Satellite identifier	
	<u>0 02 019</u>	Satellite instruments	
	<u>0 05 040</u>	Orbit number	
	<u>0 25 061</u>	Software identification and version number	
	<u>2 01 133</u>	Change data width	Add 8 to descriptor width
	<u>0 05 041</u>	Scan line number	
	<u>2 01 000</u>	Change data width	Cancel
	<u>0 05 043</u>	Field of view number	
	<u>0 06 042</u>	Space/moon scan sample number	
	<u>3 01 011</u>	Year, month, day	
	<u>3 01 012</u>	Hour, minute	
	<u>2 07 003</u>	Increase scale, reference value and data width	
	<u>0 04 006</u>	Second	
	<u>2 07 000</u>	Increase scale, reference value and data width	Cancel
	<u>3 01 021</u>	Latitude/longitude (high accuracy)	
	<u>1 07 002</u>	Replicate 7 descriptors 2 times	
	<u>0 05 080</u>	Radius resolution	
	<u>2 01 132</u>	Change data width	Add 4 to descriptor width
	<u>2 02 129</u>	Change scale	Add 1 to descriptor scale
	<u>0 21 166</u>	Land fraction	
	<u>2 02 000</u>	Change scale	Cancel
	<u>2 01 000</u>	Change data width	Cancel
	<u>0 07 007</u>	Height	Terrain height
	<u>2 02 126</u>	Change scale	Add -2 to descriptor scale
	<u>0 07 001</u>	Height of station	Spacecraft altitude
	<u>2 02 000</u>	Change scale	Cancel
	<u>0 07 024</u>	Satellite zenith angle	
	<u>0 05 021</u>	Bearing or azimuth	
	<u>0 07 025</u>	Solar zenith angle	
	<u>0 05 022</u>	Solar azimuth	
	<u>2 01 124</u>	Change data width	Add -4 to descriptor width
	<u>2 02 127</u>	Change scale	Add -1 to descriptor scale

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 10 083	0 25 084	Geometric rotational angle	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 07 073	Angle between moon and space view	
	0 12 070	Warm load temperature	
	0 12 064	Instrument temperature	
	0 08 098	Source of temperature measurement	
	0 12 101	Temperature/air temperature	
	0 08 098	Source of temperature measurement	
	0 33 107	MWS scan line processing flags	
	0 33 108	MWS navigation status flags	
	0 33 109	MWS overall quality flags	
	1 18 024	Replicate 18 descriptors 24 times	
	0 05 042	Channel number	
	1 04 004	Replicate 4 descriptors 4 times	
	0 05 079	Band number	
	2 02 130	Change scale	Add 2 to descriptor scale
	0 02 154	Satellite channel band width	
	2 02 000	Change scale	Cancel
	0 02 104	Antenna polarization	
	0 02 153	Satellite channel centre frequency	
	0 25 077	Bandwidth correction coefficient 1	
	0 25 078	Bandwidth correction coefficient 2	
	2 07 002	Increase scale, reference value and data width	
	0 12 063	Brightness temperature	
	2 07 000	Increase scale, reference value and data width	Cancel
	2 07 001	Increase scale, reference value and data width	
	0 33 089	Noise equivalent delta temperature (NEdT) quality indicators for warm target calibration	
	0 33 090	NEdT quality indicators for cold target calibration	
	2 07 000	Increase scale, reference value and data width	
	0 33 110	MWS channel processing flags	
		(Metop-SG Scatterometer (SCA) Sigma zero full resolution level 1B (SZF))	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 25 060	Software identification	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	1 27 012	Replicate 27 descriptors 12 times	
	0 05 040	Orbit number	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	<u>2 01 130</u>	<u>Change data width</u>	<u>Change data width by adding +2</u>
	<u>0 06 034</u>	<u>Cross-track cell number</u>	
	<u>2 01 000</u>	<u>Change data width</u>	<u>Cancel</u>
	<u>0 05 034</u>	<u>Along-track row number</u>	
	<u>3 01 021</u>	<u>Latitude/longitude (high accuracy)</u>	
	<u>0 08 012</u>	<u>Land/sea qualifier</u>	
	<u>3 01 011</u>	<u>Year, month, day</u>	
	<u>3 01 012</u>	<u>Hour, minute</u>	
	<u>0 04 007</u>	<u>Seconds within a minute (microsecond accuracy)</u>	
	<u>0 08 085</u>	<u>Beam identifier</u>	
	<u>0 03 030</u>	<u>Antenna status</u>	
	<u>0 02 104</u>	<u>Antenna polarization</u>	
	<u>0 03 030</u>	<u>Antenna status</u>	
	<u>0 02 104</u>	<u>Antenna polarization</u>	
	<u>0 03 029</u>	<u>Swath</u>	
	<u>0 08 075</u>	<u>Ascending/descending orbit qualifier</u>	
	<u>2 02 129</u>	<u>Change scale</u>	
	<u>2 01 131</u>	<u>Change data width</u>	
	<u>0 02 111</u>	<u>Radar incidence angle</u>	
	<u>2 01 000</u>	<u>Change data width</u>	
	<u>2 02 000</u>	<u>Change scale</u>	
	<u>0 05 021</u>	<u>Bearing or azimuth</u>	
	<u>0 21 062</u>	<u>Backscatter</u>	
	<u>0 21 026</u>	<u>ASCAT sigma-0 usability</u>	
	<u>0 21 027</u>	<u>Land contribution ratio</u>	
	<u>0 33 111</u>	<u>SCA quality flags</u>	
		<u>(Metop-SG Scatterometer (SCA) Sigma zero resampled level 1B (SZR))</u>	
	<u>3 10 084</u>	<u>0 01 033</u>	<u>Identification of originating/generating centre</u>
		<u>0 01 034</u>	<u>Identification of originating/generating sub-centre</u>
		<u>0 25 060</u>	<u>Software identification</u>
		<u>0 01 007</u>	<u>Satellite identifier</u>
		<u>0 02 019</u>	<u>Satellite instruments</u>
		<u>0 05 040</u>	<u>Orbit number</u>
		<u>0 06 034</u>	<u>Cross-track cell number</u>
		<u>0 05 034</u>	<u>Along-track row number</u>
		<u>3 01 021</u>	<u>Latitude/longitude (high accuracy)</u>
		<u>3 01 011</u>	<u>Year, month, day</u>
		<u>3 01 012</u>	<u>Hour, minute</u>
		<u>0 04 007</u>	<u>Seconds within a minute (microsecond accuracy)</u>
		<u>0 14 058</u>	<u>Corrected cross-pole backscatter</u>
		<u>0 33 112</u>	<u>Faraday rotation angle (one way)</u>

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
<u>3 10 085</u>	<u>1 17 005</u>	<u>Replicate 17 descriptors 5 times</u>	
	<u>0 08 085</u>	<u>Beam identifier</u>	
	<u>0 08 012</u>	<u>Land/sea qualifier</u>	
	<u>0 03 030</u>	<u>Antenna status</u>	
	<u>0 02 104</u>	<u>Antenna polarization</u>	
	<u>0 03 030</u>	<u>Antenna status</u>	
	<u>0 02 104</u>	<u>Antenna polarization</u>	
	<u>0 08 075</u>	<u>Ascending/descending orbit qualifier</u>	
	<u>2 02 129</u>	<u>Change scale</u>	
	<u>2 01 131</u>	<u>Change data width</u>	
	<u>0 02 111</u>	<u>Radar incidence angle</u>	
	<u>2 01 000</u>	<u>Change data width</u>	
	<u>2 02 000</u>	<u>Change scale</u>	
	<u>0 05 021</u>	<u>Bearing or azimuth</u>	
	<u>0 21 062</u>	<u>Backscatter</u>	
	<u>0 21 026</u>	<u>ASCAT sigma-0 usability</u>	
	<u>0 21 027</u>	<u>Land contribution ratio</u>	
	<u>0 25 056</u>	<u>Normalised error estimate in backscatter measurement (Kp)</u>	<u>test</u>
		<u>(IASI-NG L1C (Radiances))</u>	
	<u>0 01 007</u>	<u>Satellite identifier</u>	
	<u>3 01 005</u>	<u>Originating centre/sub-centre</u>	
	<u>0 02 019</u>	<u>Satellite instruments</u>	
	<u>0 02 020</u>	<u>Satellite classification</u>	
	<u>0 04 001</u>	<u>Year</u>	
	<u>0 04 002</u>	<u>Month</u>	
	<u>0 04 003</u>	<u>Day</u>	
	<u>0 04 004</u>	<u>Hour</u>	
	<u>0 04 005</u>	<u>Minute</u>	
	<u>2 02 131</u>	<u>Change scale</u>	
	<u>2 01 138</u>	<u>Change data width</u>	
	<u>0 04 006</u>	<u>Second</u>	
	<u>2 01 000</u>	<u>Change data width</u>	
	<u>2 02 000</u>	<u>Change scale</u>	
	<u>0 05 001</u>	<u>Latitude (high accuracy)</u>	
	<u>0 06 001</u>	<u>Longitude (high accuracy)</u>	
	<u>0 07 024</u>	<u>Satellite zenith angle</u>	
	<u>0 05 021</u>	<u>Bearing or azimuth</u>	
	<u>0 07 025</u>	<u>Solar zenith angle</u>	
	<u>0 05 022</u>	<u>Solar azimuth</u>	
	<u>0 05 043</u>	<u>Field of view number</u>	
	<u>0 05 040</u>	<u>Orbit number</u>	
	<u>2 01 133</u>	<u>Change data width</u>	
	<u>0 05 041</u>	<u>Scan line number</u>	
	<u>2 01 000</u>	<u>Change data width</u>	
	<u>2 02 126</u>	<u>Change scale</u>	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 07 001	Height of station	Spacecraft altitude
	2 02 000	Change scale	
	0 33 113	IASI-NG general quality flags	
	1 05 170	Replicate 5 descriptor 170 times	
	1 04 100	Replicate 4 descriptor 100 times	
	2 01 137	Change data width	
	0 05 042	Channel number	
	2 01 000	Change data width	
	0 14 046	Scaled radiance	
	0 02 019	Satellite instruments	
	1 10 007	Replicate 10 descriptors 7 times	
	0 05 060	Y angular position from centre of gravity	
	0 05 061	Z angular position from centre of gravity	
	0 20 083	Amount of segment covered by scene	
	1 06 020	Replicate 6 descriptors 20 times	
	0 05 042	Channel number	
	0 08 023	First-order statistics	
	0 14 044	Channel radiance	
	0 08 023	First-order statistics	
	0 14 044	Channel radiance	
	0 08 023	First-order statistics	
	0 08 072	Pixel type	
	0 20 083	Amount of segment covered by scene	
	0 08 029	Surface type	
	0 20 083	Amount of segment covered by scene	
		(IASI-NG L1D (Principle Component Scores))	
3 10 086	0 01 007	Satellite identifier	
	3 01 005	Originating centre/sub-centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	2 02 131	Change scale	
	2 01 138	Change data width	
	0 04 006	Second	
	2 01 000	Change data width	
	2 02 000	Change scale	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 05 043	Field of view number	Spacecraft altitude
	0 05 040	Orbit number	
	2 01 133	Change data width	
	0 05 041	Scan line number	
	2 01 000	Change data width	
	2 02 126	Change scale	
	0 07 001	Height of station	
	2 02 000	Change scale	
	0 33 113	IASI-NG general quality flags	
	1 09 004	Replicate 9 descriptors 4 times	
	0 25 140	Start channel	
	2 01 129	Change data width	
	0 25 141	End channel	
	2 01 000	Change data width	
	0 40 026	Score quantization factor	
	0 40 016	Residual RMS in band	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	0 40 017	Non-normalized principal component score	
	0 02 019	Satellite instruments	
	1 10 007	Replicate 10 descriptors 7 times	
	0 05 060	Y angular position from centre of gravity	
	0 05 061	Z angular position from centre of gravity	
	0 20 083	Amount of segment covered by scene	
	1 06 020	Replicate 6 descriptors 20 times	
	0 05 042	Channel number	
	0 08 023	First-order statistics	
	0 14 044	Channel radiance	
	0 08 023	First-order statistics	
	0 14 044	Channel radiance	
	0 08 023	First-order statistics	
	0 08 072	Pixel type	
	0 20 083	Amount of segment covered by scene	
	0 08 029	Surface type	
	0 20 083	Amount of segment covered by scene	
		(FY-4 Geostationary Interferometric Infrared Sounder (GIIRS))	
3 10 191	0 01 007	Satellite identifier	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	

FM 94 BUFR

Category 10			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	2 07 003	Increase scale, reference value and data width	
	0 04 006	Second	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	1 02 002	Replicate 2 descriptors 2 times	
	0 08 076	Type of band	
	3 01 021	Latitude/longitude (high accuracy)	
	2 01 131	Change data width	+3
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel
	0 05 045	Field of regard number	
	2 01 133	Change data width	+5
	0 05 043	Field of view number	
	2 01 000	Change data width	Cancel
	2 02 126	Change scale	-2
	2 01 132	Change data width	+4
	0 07 001	Height of station	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	0 25 182	L1 processing flag	
	0 02 165	Radiance type flags	
	1 08 002	Replicate 8 descriptors 2 times	
	0 08 076	Type of band	
	0 06 029	Wave number	Start of range
	0 06 029	Wave number	End of range
	0 25 140	Start channel	
	0 25 141	End channel	
	0 33 076	Calibration quality flags	
	0 33 077	Field-of-view quality flags	
	0 25 187	Confidence flag	
	0 08 076	Type of band	Set to missing (cancel)
	1 05 000	Delayed replication of 5 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	2 01 133	Change data width	+5
	0 05 042	Channel number	
	2 01 000	Change data width	Cancel
	0 14 044	Channel radiance	
	0 14 049	Noise equivalent delta radiance	

Notes:

- (1) 3 10 027 is deprecated.
 - (2) In the context of 3 10 067, pressure values which immediately follow occurrences of wind components should be understood to pertain to those components.
-

Provisional Copy
2023

Category 11 – Single level report sequences (conventional data)

Category 11			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 11 001	3 01 051	(Aircraft reports) Flight number, navigational system, date/time, location, phase of flight	ASDAR
	0 07 002	Height or altitude	
	0 12 001	Temperature/air temperature	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 11 031	Degree of turbulence	
	0 11 032	Height of base of turbulence	
	0 11 033	Height of top of turbulence	
	0 20 041	Airframe icing	
3 11 002	3 01 065	(ACARS reports) ACARS identification	
	3 01 066	ACARS location	
	3 11 003	ACARS standard reported variables	
	3 11 004	ACARS supplementary reported variables	
3 11 003	0 10 070	(ACARS standard reported variables) Indicated aircraft altitude	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 12 001	Temperature/air temperature	
	0 13 002	Mixing ratio	
3 11 004	1 01 000	(ACARS supplementary reported variables) Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	0 11 034	Vertical gust velocity	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	0 11 035	Vertical gust acceleration	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	0 11 075	Mean turbulence intensity (eddy dissipation rate)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	0 11 076	Peak turbulence intensity (eddy dissipation rate)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	

FM 94 BUFR

Category 11			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 11 004 (continued)	0 33 025	ACARS interpolated values indicator	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	0 33 026	Moisture quality	
3 11 005		(Standard AMDAR reports)	
	0 01 008	Aircraft registration number or other identification	
	0 01 023	Observation sequence number	
	3 01 021	Latitude/longitude (high accuracy)	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	0 07 010	Flight level	
	0 08 009	Detailed phase of flight	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 11 031	Degree of turbulence	
	0 11 036	Maximum derived equivalent vertical gust speed	
	0 12 101	Temperature/air temperature	
	0 33 025	ACARS interpolated values indicator	
3 11 006		(AMDAR data or aircraft data for one level without latitude/longitude)	
	0 07 010	Flight level	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 02 064	Aircraft roll angle quality	
	0 12 101	Temperature/air temperature	
3 11 007	0 12 103	Dewpoint temperature	
		(Aircraft data for one level with latitude/longitude indicated)	
	0 07 010	Flight level	
	3 01 021	Latitude/longitude (high accuracy)	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 02 064	Aircraft roll angle quality	
	0 12 101	Temperature/air temperature	
3 11 008	0 12 103	Dewpoint temperature	
		(Aircraft ascent/descent profile without latitude/longitude indicated at each level)	
	0 01 008	Aircraft registration number or other identification	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	

FM 94 BUFR

Category 11			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 11 008 (continued)	0 08 004	Phase of aircraft flight	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 11 006	AMDAR data or aircraft data for one level without latitude/longitude	
3 11 009		(Aircraft ascent/descent profile with latitude/longitude given for each level)	
	0 01 008	Aircraft registration number or other identification	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 08 004	Phase of aircraft flight	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 11 007	Aircraft data for one level with latitude/longitude indicated	
3 11 010		(BUFR template for AMDAR, version 7)	
	0 01 008	Aircraft registration number or other identification	
	0 01 023	Observation sequence number	
	0 01 006	Aircraft flight number	
	0 01 110	Aircraft tail number	
	0 01 111	Origination airport	
	0 01 112	Destination airport	
	2 04 002	Add associated field	2 bits long = 8 Two bits quality information
	0 31 021	Associated field significance	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 010	Flight level	Pressure altitude
	0 10 053	Global navigation satellite system altitude	
	0 08 009	Detailed phase of flight	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 02 064	Aircraft roll angle quality	
	0 11 100	Aircraft true airspeed	
	0 11 101	Aircraft ground speed u-component	
	0 11 102	Aircraft ground speed v-component	
	0 11 103	Aircraft ground speed w-component	
	0 11 104	True heading of aircraft, ship or other mobile platform	True heading of aircraft
	0 12 101	Temperature/air temperature	
	0 02 170	Aircraft humidity sensors	
	2 01 144	Change data width	

FM 94 BUFR

Category 11			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 11 010 (continued)	2 02 133	Change scale	
	0 13 002	Mixing ratio	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	2 01 135	Change data width	
	2 02 130	Change scale	
	0 13 003	Relative humidity	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	0 12 103	Dewpoint temperature	
	0 33 026	Moisture quality	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	0 20 042	Airframe icing present	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 20 043	Peak liquid water content	
	0 20 044	Average liquid water content	
	0 20 045	Supercooled large droplet (SLD) conditions	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	0 33 025	ACARS interpolated values indicator	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 11 075	Mean turbulence intensity (eddy dissipation rate)	
	0 11 076	Peak turbulence intensity (eddy dissipation rate)	
	0 11 039	Extended time of occurrence of peak eddy dissipation rate	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 11 037	Turbulence index	EDR
	0 11 077	Reporting interval or averaging time for eddy dissipation rate	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 11 034	Vertical gust velocity	
	0 11 035	Vertical gust acceleration	
	0 11 036	Maximum derived equivalent vertical gust speed	
	2 04 000	Add associated field	Cancel
	1 19 000	Delayed replication of 19 descriptors	
	0 31 001	Delayed descriptor replication factor	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	

FM 94 BUFR

Category 11				
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION	
F X Y				
3 11 010 (continued)	3 01 021	Latitude/longitude (high accuracy)	7 bits long = 7 Percentage confidence	
	0 07 007	Height		
	0 11 105	EDR algorithm version		
	2 04 007	Add associated field		
	0 31 021	Associated field significance		
	0 11 076	Peak turbulence intensity (eddy dissipation rate)	Cancel	
	0 11 075	Mean turbulence intensity (eddy dissipation rate)		
	2 04 000	Add associated field		
	0 11 106	Running minimum confidence		
	0 11 107	Maximum number bad inputs		
	0 11 108	Peak location		
	0 11 109	Number of good EDR		
	0 12 101	Temperature/air temperature		
	0 11 001	Wind direction		
	2 01 130	Change data width		
0 11 084	Wind speed	Cancel		
2 01 000	Change data width			
	(IAGOS template for a single observation), version 2			
3 11 011	0 01 023		Observation sequence number	
	0 08 004		Phase of aircraft flight	
	3 01 011	Year, month, day		
	3 01 013	Hour, minute, second		
	0 05 002	Latitude (coarse accuracy)		
	0 06 002	Longitude (coarse accuracy)		
	0 07 004	Pressure		
	0 11 001	Wind direction		
	0 11 002	Wind speed		
	0 12 101	Temperature/air temperature		
	1 06 000	Delayed replication of 6 descriptors		
	0 31 001	Delayed descriptor replication factor		
	0 08 046	Atmospheric chemical or physical constituent type		
	2 01 139	Change data width	20 bits long	
	2 02 126	Change scale	Scale: 7	
0 15 026	Concentration of pollutant (mol mol ⁻¹)	Cancel		
2 02 000	Change scale			
2 01 000	Change data width			
1 06 000	Delayed replication of 6 descriptors	Cancel		
0 31 001	Delayed descriptor replication factor			
0 08 046	Atmospheric chemical or physical constituent type			
2 01 138	Change data width	19 bits long		
2 02 130	Change scale	Scale: 11		

FM 94 BUFR

Category 11			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 11 011 (continued)	0 15 026	Concentration of pollutant (mol mol ⁻¹)	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 15 052	Log ₁₀ of number density of aerosol particles with diameter greater than 5 nm	
	0 15 053	Log ₁₀ of number density of aerosol particles with diameter greater than 14 nm	
	0 15 054	Log ₁₀ of number density of aerosol particles with diameter between 0.25 and 2.5 µm	
	0 15 055	Non volatile aerosol ratio	
	0 07 004	Pressure	
	0 07 004	Pressure	
	0 13 099	Log ₁₀ of integrated cloud particle density	
	0 13 100	Log ₁₀ of integrated cloud particle area	
	0 13 101	Log ₁₀ of integrated cloud particle volume	
		(BUFR template for aircraft ascent/descent profile with latitude and longitude given for each level)	
	3 01 150	WIGOS identifier	
	0 01 008	Aircraft registration number or other identification	
3 11 012	0 01 111	Origination airport	To be reported in case of an ascent profile
	0 01 112	Destination airport	To be reported in case of a descent profile
	3 01 011	Year, month, day	Date/Time and position of first level in profile (for ascent profile first report/take off, for descent profile last report/touch down)
	3 01 013	Hour, minute, second	Ascent or descent profile
	3 01 021	Latitude/Longitude (high accuracy)	
		Phase of aircraft flight	
	1 10 000	Delayed replication of 10 descriptors	
	0 31 002	Extended delayed descriptor replication factor	Number of levels following
		<i>Aircraft ascent/descent profile data for one level with lat. long. indicated</i>	
	3 01 011	Year, month, day	Date of single level report
	3 01 013	Hour, minute, second	Time of single level report

FM 94 BUFR

Category 11			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 11 012 (continued)	3 11 007	Aircraft data for one level with latitude/longitude indicated	Flight level = pressure altitude, dewpoint temperature = value derived from mixing ratio, limited to $T_d \leq T$
	2 01 144	Change data width	
	2 02 133	Change scale	
	0 13 002	Mixing ratio	Originally measured value
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 13 003	Relative humidity	Value derived from mixing ratio, limited to $\leq 100\%$
	0 33 026	Moisture quality	Code table (report code figure 10 if $T_d > T$, see Code table)

Category 12 – Single level report sequences (satellite data)

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 001	3 01 043	Satellite identifier, wind computation method, date/time, location	
	3 04 001	Cloud top pressure, temperature, wind	
3 12 002	3 01 043	Satellite identifier, wind computation method, date/time, location	
	3 04 002	Cloud top pressure, wind	
3 12 003	3 01 042	Satellite identifier, instrument, data-processing technique, date/time, location	
	3 04 003	Surface temperature	
3 12 004	3 01 042	Satellite identifier, instrument, data-processing technique, date/time, location	
	3 04 004	Cloud top pressure, cloud cover, temperature	
3 12 005	3 01 042	Satellite identifier, instrument, data-processing technique, date/time, location	
	0 20 014	Height of top of cloud	
3 12 006	3 01 044	Satellite identifier, humidity computation method, date/time, location	
	3 04 005	Layer mean relative humidity	
3 12 007	3 01 042	Satellite identifier, instrument, data-processing technique, date/time, location	
	3 04 006	Radiation	
3 12 010		(Orbital information, Part I)	
	0 01 007	Satellite identifier	
	0 05 040	Orbit number	
	0 02 021	Satellite instrument data used in processing	
	0 05 041	Scan line number	
	0 04 001	Year	
	0 04 043	Day of the year	
3 12 011		(Orbital information, Part II)	
	2 02 131	Change scale	
	2 01 149	Change data width	
	0 04 006	Second	
	2 01 000	Change data width	
	2 02 126	Change scale	
	0 10 002	Height	
	2 02 000	Change scale	
	0 05 043	Field of view number	
	0 05 053	Field of view number increment	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 012	2 02 129	(HIRS brightness temperatures – channels 1-19) Change scale	
	2 01 132	Change data width	
	1 01 019	Replicate 1 descriptor 19 times	
	0 12 063	Brightness temperature	
	2 01 000	Change data width	
	2 02 000	Change scale	
3 12 013		(HIRS brightness temperatures – channel 20)	
	0 05 042	Channel number	
	2 02 129	Change scale	
	2 01 135	Change data width	
	0 12 063	Brightness temperature	
	2 01 000	Change data width	
	2 02 000	Change scale	
3 12 014		(HIRS satellite data)	
	3 12 010	Orbital information, Part I	
	3 12 011	Orbital information, Part II	
	1 05 056	Replicate 5 descriptors 56 times	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 05 042	Channel number	
	0 05 052	Channel number increment	
	3 12 012	HIRS brightness temperatures – channels 1-19	
	3 12 013	HIRS brightness temperatures – channel 20	
3 12 015		(MSU brightness temperatures – channels 1-4)	
	1 09 011	Replicate 9 descriptors 11 times	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 05 042	Channel number	
	0 05 052	Channel number increment	
	2 02 129	Change scale	
	2 01 132	Change data width	
	1 01 004	Replicate 1 descriptor 4 times	
	0 12 063	Brightness temperature	
	2 02 000	Change scale	
	2 01 000	Change data width	
3 12 016		(MSU satellite data)	
	3 12 010	Orbital information, Part I	
	3 12 011	Orbital information, Part II	
	3 12 015	MSU brightness temperatures – channels 1-4	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 017	1 09 008	(SSU brightness temperatures – channels 1–3) Replicate 9 descriptors 8 times	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 05 042	Channel number	
	0 05 052	Channel number increment	
	2 02 129	Change scale	
	2 01 132	Change data width	
	1 01 003	Replicate 1 descriptor 3 times	
	0 12 063	Brightness temperature	
	2 02 000	Change scale	
	2 01 000	Change data width	
3 12 018	3 12 010	(SSU satellite data) Orbital information, Part I	
	3 12 011	Orbital information, Part II	
	3 12 017	SSU brightness temperatures – channels 1-3	
3 12 019		(Wave scatterometer product with width change for wave number (spectral))	
	3 01 047	ERS product header	
	3 01 048	Radar parameters	
	0 15 015	Maximum image spectral component before normalization	
	0 29 002	Coordinate grid type	
	0 21 076	Representation of intensities	
	1 06 012	Replicate 6 descriptors 12 times	
	2 01 129	Change data width	14 bits long
	0 06 030	Wave number (spectral)	
	2 01 000	Change data width	Cancel
	1 02 012	Replicate 2 descriptors 12 times	
	0 05 030	Direction (spectral)	
	0 21 075	Image spectrum intensity	
	0 21 066	Wave scatterometer product confidence data	
3 12 020		(Wave scatterometer product)	
	3 01 047	ERS product header	
	3 01 048	Radar parameters	
	0 15 015	Maximum image spectral component before normalization	
	0 29 002	Coordinate grid type	
	0 21 076	Representation of intensities	
	1 04 012	Replicate 4 descriptors 12 times	
	0 06 030	Wave number (spectral)	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 020 (continued)	1 02 012	Replicate 2 descriptors 12 times	
	0 05 030	Direction (spectral)	
	0 21 075	Image spectrum intensity	
	0 21 066	Wave scatterometer product confidence data	
3 12 021		(Wind scatterometer product)	
	3 01 047	ERS product header	
	1 01 003	Replicate 1 descriptor 3 times	
	3 01 049	Radar beam data	
	0 11 012	Wind speed at 10 m	
	0 11 011	Wind direction at 10 m	
	0 21 067	Wind product confidence data	
3 12 022		(Radar altimeter product)	Number in average
	3 01 047	ERS product header	
	0 08 022	Total number (with respect to accumulation or average)	
	0 11 012	Wind speed at 10 m	
	0 11 050	Standard deviation of horizontal wind speed	
	0 22 070	Significant wave height	
	0 22 026	Standard deviation of significant wave height	
	3 12 041	Altitude	
	0 10 050	Standard deviation altitude	
	0 21 068	Radar altimeter product confidence data	
	0 21 071	Peakiness	
	0 21 072	Satellite altimeter calibration status	
	0 21 073	Satellite altimeter instrument mode	
	3 12 042	Altitude corrections	
	0 21 062	Backscatter	
	0 15 011	Log ₁₀ of integrated electron density	
3 12 023		(ATSR sea-surface temperature product)	Number in average
	3 01 047	ERS product header	
	1 03 003	Replicate 3 descriptors 3 times	
	0 08 022	Total number (with respect to accumulation or average)	
	0 12 061	Skin temperature	
	0 22 050	Standard deviation sea-surface temperature	
	0 21 069	SST product confidence data	
	0 21 085	ATSR sea-surface temperature across-track band number	
3 12 024		(Wave scatterometer product enhanced)	Range Number in sample Horizontal
	3 12 020	Wave scatterometer product	
	0 08 060	Sample scanning mode significance	
	0 08 022	Total number (with respect to accumulation or average)	
	0 08 060	Sample scanning mode significance	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 024 (continued)	0 08 022	Total number (with respect to accumulation or average)	Number in sample
	0 25 014	Azimuth clutter cut-off	
	0 22 101	Total energy (wavelength > 731m) at low wave numbers	
	0 22 097	Mean wavelength > 731 m of image spectrum at low wave numbers	
	0 22 098	Wavelength spread (wavelength > 731 m) at low wave numbers	
	0 22 099	Mean direction at low wave numbers (wavelength > 731 m)	
	0 22 100	Direction spread at low wave numbers (wavelength > 731 m)	
3 12 025		(Wave scatterometer enhanced product (with change of width for wave number (spectral)))	
	3 12 019	Wave scatterometer product with width change for wave number (spectral)	
	0 08 060	Sample scanning mode significance	Range
	0 08 022	Total number (with respect to accumulation or average)	Number in sample
	0 08 060	Sample scanning mode significance	Horizontal
	0 08 022	Total number (with respect to accumulation or average)	Number in sample
	0 25 014	Azimuth clutter cut-off	
	0 22 101	Total energy (wavelength > 731m) at low wave numbers	
	0 22 097	Mean wavelength > 731 m of image spectrum at low wave numbers	
	0 22 098	Wavelength spread (wavelength > 731 m) at low wave numbers	
	0 22 099	Mean direction at low wave numbers (wavelength > 731 m)	
	0 22 100	Direction spread at low wave numbers (wavelength > 731 m)	
		(QUIKSCAT data)	
3 12 026	3 01 046	Satellite identifier, direction of motion, sensor, model function, software, resolution	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 12 031	SEAWINDS wind	
	1 01 004	Replicate 1 descriptor 4 times	
	3 12 030	Wind, formal uncertainty, likelihood	
	0 21 110	Number of inner-beam sigma-0 (forward of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 027	Radar specification, normalized radar cross-section, Kp variance coefficient	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 026 (continued)	0 21 111	Number of outer-beam sigma-0 (forward of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 027	Radar specification, normalized radar cross-section, Kp variance coefficient	
	0 21 112	Number of inner-beam sigma-0 (aft of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 027	Radar specification, normalized radar cross-section, Kp variance coefficient	
	0 21 113	Number of outer-beam sigma-0 (aft of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 027	Radar specification, normalized radar cross-section, Kp variance coefficient	
3 12 027		(ATSR SST product (SADIST-2))	
	3 01 047	ERS product header	
	1 05 009	Replicate 5 descriptors 9 times	
	3 01 023	Latitude/longitude (coarse accuracy)	10-arcmin cell
	0 07 021	Elevation	Incidence angle nadir view Set to zero
	0 12 061	Skin temperature	SST (nadir-only view)
	0 07 021	Elevation	Incidence angle dual view Set to missing
	0 12 061	Skin temperature	SST (dual view)
	0 21 085	ATSR sea-surface temperature across-track band number	0-9
3 12 028	0 21 070	SST product confidence data (SADIST-2)	23-bit flag
		(SEAWINDS QUIKSCAT data)	
	3 01 046	Satellite identifier, direction of motion, sensor, model function, software, resolution	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 08 025	Time difference qualifier	
	2 01 136	Change data width	
	0 04 006	Second	
	2 01 000	Change data width	
	3 12 031	SEAWINDS wind	Cancel
	3 12 032	SEAWINDS precipitation	
	1 01 004	Replicate 1 descriptor 4 times	
	3 12 030	Wind, formal uncertainty, likelihood	
	1 01 002	Replicate 1 descriptor 2 times	
	3 12 033	Antenna polarization, brightness temperature	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 028 (continued)	0 21 110	Number of inner-beam sigma-0 (forward of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 028	Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient	
	0 21 111	Number of outer-beam sigma-0 (forward of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 028	Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient	
	0 21 112	Number of inner-beam sigma-0 (aft of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 028	Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient	
	0 21 113	Number of outer-beam sigma-0 (aft of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 028	Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient	
		(Scatterometer level 2b data)	
3 12 029	3 01 046	Satellite identifier, direction of motion, sensor, model function, software, resolution	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 08 025	Time difference qualifier	
	2 01 136	Change data width	
	0 04 006	Second	
	2 01 000	Cancel change data width	
	0 05 034	Along-track row number	
	2 01 129	Change data width	
	0 06 034	Cross-track cell number	
	2 01 000	Cancel change data width	
	0 33 055	Wind vector quality flag	
	0 11 081	Model wind direction at 10 m	
	0 11 082	Model wind speed at 10 m	
	0 21 101	Number of vector ambiguities	
	0 21 102	Index of selected wind vector	
	0 21 103	Total number of sigma-0 measurements	
	3 12 032	SEAWINDS precipitation	
	1 01 004	Replicate 1 descriptor 4 times	
	3 12 030	Wind, formal uncertainty, likelihood	
	1 01 002	Replicate 1 descriptor 2 times	
	3 12 033	Antenna polarization, brightness temperature	
	0 21 110	Number of inner-beam sigma-0 (forward of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 029 (continued)	3 21 028	Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient	
	0 21 111	Number of outer-beam sigma-0 (forward of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 028	Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient	
	0 21 112	Number of inner-beam sigma-0 (aft of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 028	Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient	
	0 21 113	Number of outer-beam sigma-0 (aft of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 028	Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient	
3 12 030		(Wind, formal uncertainty, likelihood)	
	2 01 130	Change data width	
	2 02 129	Change scale	
	0 11 012	Wind speed at 10 m	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 11 052	Formal uncertainty in wind speed	
	2 01 135	Change data width	
	2 02 130	Change scale	
	0 11 011	Wind direction at 10 m	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 11 053	Formal uncertainty in wind direction	
	0 21 104	Likelihood computed for solution	
3 12 031		(SEAWINDS wind)	
	0 05 034	Along-track row number	
	0 06 034	Cross-track cell number	
	0 21 109	SEAWINDS wind vector cell quality	
	0 11 081	Model wind direction at 10 m	
	0 11 082	Model wind speed at 10 m	
	0 21 101	Number of vector ambiguities	
	0 21 102	Index of selected wind vector	
	0 21 103	Total number of sigma-0 measurements	
3 12 032		(SEAWINDS precipitation)	
	0 21 120	Probability of rain	
	0 21 121	SEAWINDS NOF rain index	
	0 13 055	Intensity of precipitation	
	0 21 122	Attenuation correction on sigma-0 (from tB)	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 033	0 02 104	(Antenna polarization, brightness temperature) Antenna polarization	
	0 08 022	Total number (with respect to accumulation or average)	
	0 12 063	Brightness temperature	
	0 12 065	Standard deviation brightness temperature	
3 12 034	3 01 046	(CFOSAT scatterometer data) Satellite identifier, direction of motion, sensor, model function, software, resolution	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 08 025	Time difference qualifier	
	2 01 136	Change data width	
	0 04 006	Second	
	2 01 000	Change data width	
	3 12 031	Scatterometer wind	
	3 12 032	Scatterometer precipitation	
	1 01 004	Replicate 1 descriptor 4 times	
	3 12 030	Wind, formal uncertainty, likelihood	
	1 01 002	Replicate 1 descriptor 2 times	
	3 12 033	Antenna polarization, brightness temperature	
	1 03 018	Replicate 3 descriptors 18 times	
	0 21 110	Number of inner-beam sigma-0 (forward of satellite)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 21 028	Radar specification, normalized radar cross-section, Kp variance coefficient	
3 12 035	0 01 007	(Scatterometer level 2a data) Satellite identifier	
	0 01 031	Identification of originating/generating centre	
	0 02 048	Satellite sensor indicator	
	2 02 124	Change scale	
	0 02 026	Cross-track resolution	
	0 02 027	Along-track resolution	
	2 02 000	Cancel change scale	
	0 05 040	Orbit number	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 035 (continued)	0 05 034	Along-track row number	
	0 06 031	Column number	
	2 01 129	Change data width	
	0 06 034	Cross-track cell number	
	2 01 000	Cancel change data width	
	0 05 021	Bearing or azimuth	
	0 02 111	Radar incidence angle	
	0 12 063	Brightness temperature	
	0 21 095	Kp coefficient A	
	0 21 096	Kp coefficient B	
	0 21 097	Kp coefficient C	
	0 21 030	Signal-to-noise ratio	
	0 21 105	Normalized radar cross section	
	0 33 056	Sigma 0 quality flag	
		(Altitude)	
3 12 041	2 01 141	Change data width	28 bits long
	2 02 130	Change scale	Scale: 2
	0 07 001	Height of station	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
3 12 042		(Altitude corrections)	
	0 21 077	Altitude correction (ionosphere)	
	0 21 078	Altitude correction (dry troposphere)	
	0 21 079	Altitude correction (wet troposphere)	
	0 21 080	Altitude correction (calibration constant)	
	0 21 081	Open loop correction (height-time loop)	
	0 21 082	Open loop correction (auto gain control)	
3 12 045		(AATSR sea-surface temperatures)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 096	Station acquisition	
	0 25 061	Software identification and version number	
	0 05 040	Orbit number	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 002	Height or altitude	
	0 12 180	Averaged 12 micron BT for all clear pixels at nadir	
	0 12 181	Averaged 11 micron BT for all clear pixels at nadir	
	0 12 182	Averaged 3.7 micron BT for all clear pixels at nadir	
	0 12 183	Averaged 12 micron BT for all clear pixels, forward view	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 045 (continued)	0 12 184	Averaged 11 micron BT for all clear pixels, forward view	
	0 12 185	Averaged 3.7 micron BT for all clear pixels, forward view	
	0 02 174	Mean across-track pixel number	
	0 21 086	Number of pixels in nadir only, average	
	0 12 186	Mean nadir sea-surface temperature	
	0 21 087	Number of pixels in dual view, average	
	0 12 187	Mean dual view sea-surface temperature	
	0 33 043	AST confidence	
3 12 050		(MERIS instrument reporting)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 096	Station acquisition	
	0 25 061	Software identification and version number	
	0 05 040	Orbit number	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 10 080	Viewing zenith angle	
	0 27 080	Viewing azimuth angle	
	0 08 003	Vertical significance (satellite observations)	
	0 07 004	Pressure	
	0 13 093	Cloud optical thickness	
	0 08 003	Vertical significance (satellite observations)	
	2 01 131	Change data width	
	2 02 129	Change scale	
	0 07 004	Pressure	
	0 07 004	Pressure	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 13 095	Total column water vapour	
3 12 051		(Ocean cross spectra – WVS)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 096	Station acquisition	
	0 25 061	Software identification and version number	
	0 05 040	Orbit number	
	0 08 075	Ascending/descending orbit qualifier	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 051 (continued)	0 01 012	Direction of motion of moving observing platform	Cancel
	2 01 131	Change data width	
	0 01 013	Speed of motion of moving observing platform	
	2 01 000	Change data width	
	0 10 032	Satellite distance to Earth's centre	
	0 10 033	Altitude (platform to ellipsoid)	
	0 10 034	Earth's radius	
	0 07 002	Height or altitude	
	0 08 012	Land/sea qualifier	
	0 25 110	Image processing summary	
	0 25 111	Number of input data gaps	
	0 25 102	Number of missing lines excluding data gaps	
	0 02 104	Antenna polarization	
	0 25 103	Number of directional bins	
	0 25 104	Number of wavelength bins	
	0 25 105	First directional bin	
	0 25 106	Directional bin step	
	0 25 107	First wavelength bin	
	0 25 108	Last wavelength bin	
	0 02 111	Radar incidence angle	
	0 02 121	Mean frequency	
	0 02 026	Cross-track resolution	
	0 02 027	Along-track resolution	
	0 21 130	Spectrum total energy	
	0 21 131	Spectrum max energy	
	0 21 132	Direction of spectrum max on higher resolution grid	
	0 21 133	Wavelength of spectrum max on higher resolution grid	
	0 21 064	Clutter noise estimate	
	0 25 014	Azimuth clutter cut-off	
	0 21 134	Range resolution of cress covariance spectrum	
	1 07 018	Replicate 7 descriptors 18 times	
	0 05 030	Direction (spectral)	
	1 05 024	Replicate 5 descriptors 24 times	
	2 01 130	Change data width	
	0 06 030	Wave number (spectral)	
	2 01 000	Change data width	Cancel
	0 21 135	Real part of cross spectra polar grid number of bins	
	0 21 136	Imaginary part of cross spectra polar grid number of bins	
	0 33 044	ASAR quality information	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 052	0 01 007 0 02 019 0 01 096 0 25 061 0 05 040 0 25 120 0 25 121 0 25 124 0 25 125 0 25 122 0 25 123 3 01 011 3 01 013 3 01 021 0 07 002 0 02 119 0 33 047 0 10 081 0 10 082 0 10 083 0 10 084 0 02 116 0 02 117 0 02 118 0 02 156 0 02 157 0 14 055 0 22 150 0 22 151 0 22 152 0 22 153 0 22 154 0 22 155 0 22 156 0 22 157 0 22 158 0 22 159 0 21 137 0 21 138	(RA2 – radar altimeter-2) Satellite identifier Satellite instruments Station acquisition Software identification and version number Orbit number RA2-L2-processing flag RA2-L2-processing quality MWR-L2-processing flag MWR-L2-processing quality Hardware configuration for RF Hardware configuration for HPA Year, month, day Hour, minute, second Latitude/longitude (high accuracy) Height or altitude RA-2 instrument operations Measurement confidence data Altitude of COG above reference ellipsoid Instantaneous altitude rate Squared off nadir angle of the satellite from platform data Squared off nadir angle of the satellite from waveform data Percentage of 320 MHz band processed Percentage of 80 MHz band processed Percentage of 20 MHz band processed Percentage of valid Ku ocean retracker measurements Percentage of valid S ocean retracker measurements Solar activity index Number of 18 Hz valid points for Ku band Ku band ocean range STD of 18 Hz Ku band ocean range Number of 18 Hz valid points for S band S band ocean range STD of 18 Hz S band ocean range Ku band significant wave height STD of 18 Hz Ku band ocean range S band significant wave height STD of 18 Hz S band significant wave height Ku band corrected ocean backscatter coefficient STD Ku band corrected ocean backscatter coefficient	Significant wave height

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 052 (continued)	0 21 139	Ku band net instrumental correction for AGC	
	0 21 140	S band corrected ocean backscatter coefficient	
	0 21 141	STD S band corrected ocean backscatter coefficient	
	0 21 142	S band net instrumental correction for AGC	
	0 10 085	Mean sea-surface height	
	0 10 086	Geoid's height	
	0 10 087	Ocean depth/land elevation	
	0 10 088	Total geocentric ocean tide height (solution 1)	
	0 10 089	Total geocentric ocean tide height (solution 2)	
	0 10 090	Long period tide height	
	0 10 091	Tidal loading height	
	0 10 092	Solid Earth tide height	
	0 10 093	Geocentric pole tide height	
	0 11 002	Wind speed	
	0 25 126	Model dry tropospheric correction	
	0 25 127	Inverted barometer correction	
	0 25 128	Model wet tropospheric correction	
	0 25 129	MWR derived wet tropospheric correction	
	0 25 130	RA2 ionospheric correction on Ku band	
	0 25 131	Ionospheric correction from Doris on Ku band	
	0 25 132	Ionospheric correction from model on Ku band	
	0 25 133	Sea state bias correction on Ku band	
	0 25 134	RA2 ionospheric correction on S band	
	0 25 135	Ionospheric correction from Doris on S band	
	0 25 136	Ionospheric correction from model on S band	
	0 25 137	Sea state bias correction on S band	
	0 13 096	MWR water vapour content	
	0 13 097	MWR liquid water content	
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
	0 12 188	Interpolated 23.8 GHz brightness T from MWR	
	0 12 189	Interpolated 36.5 GHz brightness T from MWR	
	0 02 158	RA-2 instrument	
	0 02 159	MWR instrument	
	0 33 052	S band ocean retracking quality	
	0 33 053	Ku band ocean retracking quality	
	0 21 143	Ku band rain attenuation	
	0 21 144	Altimeter rain flag	
		(Ocean wave spectra)	
3 12 053	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 096	Station acquisition	
	0 25 061	Software identification and version number	
	0 05 040	Orbit number	
	0 08 075	Ascending/descending orbit qualifier	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 053 (continued)	3 01 011	Year, month, day	Cancel
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 01 012	Direction of motion of moving observing platform	
	2 01 131	Change data width	
	0 01 013	Speed of motion of moving observing platform	
	2 01 000	Change data width	
	0 10 032	Satellite distance to Earth's centre	
	0 10 033	Altitude (platform to ellipsoid)	
	0 10 034	Earth's radius	
	0 07 002	Height or altitude	
	0 08 012	Land/sea qualifier	
	0 25 110	Image processing summary	
	0 25 111	Number of input data gaps	
	0 25 102	Number of missing lines excluding data gaps	
	0 02 104	Antenna polarization	
	0 25 103	Number of directional bins	
	0 25 104	Number of wavelength bins	
	0 25 105	First directional bin	
	0 25 106	Directional bin step	
	0 25 107	First wavelength bin	
	0 25 108	Last wavelength bin	
	0 11 001	Wind direction	
	0 11 002	Wind speed	
	0 22 160	Normalized inverse wave age	
	0 25 138	Average signal-to-noise ratio	
	2 01 130	Change data width	
	2 02 129	Change scale	
	0 22 021	Height of waves	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 33 048	Confidence measure of SAR inversion	
	0 33 049	Confidence measure of wind retrieval	
	0 02 026	Cross-track resolution	
	0 02 027	Along-track resolution	
	0 21 130	Spectrum total energy	
	0 21 131	Spectrum max energy	
	0 21 132	Direction of spectrum max on higher resolution grid	
	0 21 133	Wavelength of spectrum max on higher resolution grid	
	0 25 014	Azimuth clutter cut-off	
	1 06 036	Replicate 6 descriptors 36 times	
	0 05 030	Direction (spectral)	
	1 04 024	Replicate 4 descriptors 24 times	
	2 01 130	Change data width	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 053 (continued)	0 06 030	Wave number (spectral)	Cancel
	2 01 000	Change data width	
	0 22 161	Wave spectra	
	0 33 044	ASAR quality information	
3 12 055		(ASCAT level 1b cell information)	
	0 05 033	Pixel size on horizontal – 1	
	0 05 040	Orbit number	
	0 06 034	Cross-track cell number	
	0 10 095	Height of atmosphere used	
	0 21 157	Loss per unit length of atmosphere used	
3 12 056		(Scatterometer wind cell information)	
	0 25 060	Software identification	
	0 01 032	Generating application	
	0 11 082	Model wind speed at 10 m	
	0 11 081	Model wind direction at 10 m	
	0 20 095	Ice probability	
	0 20 096	Ice age ("A" parameter)	
	0 21 155	Wind vector cell quality	
	2 01 133	Change data width	
3 12 057	0 21 101	Number of vector ambiguities	Increase data width by 5 bits
	0 21 102	Index of selected wind vector	
	2 01 000	Change data width	Cancel
		(Ambiguous wind data)	
	2 01 130	Change data width	
	2 02 129	Change scale	Increase data width by 2 bits Increase scaling by 10 ¹
	0 11 012	Wind speed at 10 m	Cancel
	2 02 000	Change scale	
	2 01 000	Change data width	Cancel
	2 01 131	Change data width	
	2 02 129	Change scale	Increase data width by 3 bits Increase scaling by 10 ¹
	0 11 011	Wind direction at 10 m	Cancel
	2 02 000	Change scale	
	2 01 000	Change data width	Cancel
	0 21 156	Backscatter distance	
	0 21 104	Likelihood computed for solution	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 058	3 01 125	(ASCAT level 1b data) ASCAT header information	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	3 12 055	ASCAT level 1b cell information	
	0 21 150	Beam co-location	
	1 01 003	Replicate 1 descriptor 3 times	
	3 21 030	ASCAT sigma-0 information	
3 12 059	3 12 056	(Scatterometer wind data) Scatterometer wind cell information	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 12 057	Ambiguous wind data	
3 12 060	0 25 060	(Scatterometer soil moisture data) Software identification	Extrapolated backscatter at 40 deg incidence angle (sigma0_40)
	0 25 062	Database identification	
	0 40 001	Surface soil moisture (ms)	
	0 40 002	Estimated error in surface soil moisture	
	0 21 062	Backscatter	
	0 21 151	Estimated error in sigma-0 at 40 degrees incidence angle	
	0 21 152	Slope at 40 degrees incidence angle	
	0 21 153	Estimated error in slope at 40 degrees incidence angle	
	0 21 154	Soil moisture sensitivity	
	0 21 062	Backscatter	
	0 21 088	Wet backscatter	
	0 40 003	Mean surface soil moisture	
	0 40 004	Rain fall detection	
	0 40 005	Soil moisture correction flag	
	0 40 006	Soil moisture processing flag	
	0 40 007	Soil moisture quality	
	0 20 065	Snow cover	
	0 40 008	Frozen land surface fraction	
	0 40 009	Inundation and wetland fraction	
	0 40 010	Topographic complexity	
3 12 061	3 12 058	(ASCAT level 1b and level 2 data) ASCAT level 1b data	Dry backscatter
	3 12 060	Scatterometer soil moisture data	
	3 12 059	Scatterometer wind data	

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 062	0 01 007	(Snow cover)	
	0 02 019	Satellite identifier	
	3 01 011	Satellite instruments	
	3 01 013	Year, month, day	
	3 01 021	Hour, minute, second	
	0 20 065	Latitude/longitude (high accuracy)	
	0 08 023	Snow cover	
	0 20 065	First-order statistics	
	0 08 023	Snow cover	
	0 08 023	First-order statistics	
3 12 070	0 01 007	(SMOS data)	
	0 02 019	Satellite identifier	
	0 01 144	Satellite instruments	
	0 01 124	Snapshot identifier	
	0 30 010	Grid point identifier	
	3 01 011	Number of grid points	
	3 01 013	Year, month, day	
	3 01 021	Hour, minute, second	
	0 07 012	Latitude/longitude (high accuracy)	
	0 15 012	Grid point altitude	
	0 12 165	Total electron count per square metre	
	0 12 166	Direct sun brightness temperature	
	0 12 167	Snapshot accuracy	
	0 12 168	Radiometric accuracy (pure polarization)	
	0 27 010	Radiometric accuracy (cross polarization)	
	0 28 010	Footprint axis 1	
	0 02 099	Footprint axis 2	
	0 13 048	Polarization	
	0 25 081	Water fraction	
	0 25 082	Incidence angle	
	0 25 083	Azimuth angle	
	0 25 084	Faraday rotational angle	
	0 12 080	Geometric rotational angle	
	0 12 081	Brightness temperature real part	
	0 12 082	Brightness temperature imaginary part	
0 25 174	Pixel radiometric accuracy		
0 33 028	SMOS information flag		
3 12 071	0 01 007	Snapshot overall quality	
	0 02 019	(CryoSat-2 SIRAL altimeter)	
	0 02 139	Satellite identifier	
	0 01 096	Satellite instruments	
		SIRAL instrument configuration	
		Station acquisition	Acquisition station name

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 071 (continued)	0 01 040	Processing centre ID code	
	0 25 061	Software identification and version number	
	0 05 040	Orbit number	
	0 05 044	Satellite cycle number	
	0 08 075	Ascending/descending orbit qualifier	
	0 08 077	Radiometer sensed surface type	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 10 081	Altitude of COG above reference ellipsoid	
	0 22 156	Ku band significant wave height	
	0 22 142	Square of significant wave height	
	1 01 020	Replicate 1 descriptor 20 times	
	0 22 149	20 Hz significant wave height squared	
	0 22 143	STD of 20 Hz SWH squared	
	0 22 144	Number of 20 Hz valid points for SWH squared	
	0 21 137	Ku band corrected ocean backscatter coefficient	
	1 01 020	Replicate 1 descriptor 20 times	
	0 21 181	20 Hz ocean backscatter coefficient	
	0 21 138	STD Ku band corrected ocean backscatter coefficient	
	0 21 180	Number of 20 Hz valid points for ocean backscatter coefficient	
	0 21 177	Corrected OCOG backscatter coefficient	
	0 21 178	STD of 20 Hz OCOG backscatter coefficient	
	0 21 179	Number of 20 Hz valid points for OCOG backscatter coefficient	
	0 10 079	Off nadir angle of the satellite from platform data	
	0 10 085	Mean sea-surface height	
	0 10 086	Geoid's height	
	0 10 087	Ocean depth/land elevation	
	0 10 089	Total geocentric ocean tide height (solution 2)	
	0 10 090	Long period tide height	
	0 10 091	Tidal loading height	
	0 10 092	Solid Earth tide height	
	0 10 093	Geocentric pole tide height	
	0 11 097	Wind speed from altimeter	
	0 21 093	Ku band peakiness	Average of 20 Hz values
	1 01 020	Replicate 1 descriptor 20 times	
	0 21 182	20 Hz Ku band peakiness	20 values

FM 94 BUFR

Category 12			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 12 071 (continued)	0 33 053	Ku band ocean retracking quality	L2 processing quality
	0 22 151	Ku band ocean range	
	0 22 145	STD of 20 Hz ocean range	
	0 22 148	Number of 20 Hz valid points for ocean range	
	0 22 146	OCOG range	
	0 22 147	STD of 20 Hz OCOG range	
	0 25 126	Model dry tropospheric correction	
	0 25 128	Model wet tropospheric correction	
	0 25 127	Inverted barometer correction	
	0 21 176	High frequency variability correction	
	0 25 132	Ionospheric correction from model on Ku band	
	0 25 133	Sea state bias correction on Ku band	
	0 25 182	L1 processing flag	
	0 25 183	L1 processing quality	
	0 25 180	LRM mode per cent	
	0 25 184	L2 product status	
	0 25 181	L2 processing flag	
	0 33 080	Scan level quality flags	

Notes:

- (1) Separation of single level satellite data into sets of BUFR messages helps compression and results in efficient data transmission and storage.
- (2) Each BUFR message may contain data for a number of locations; the BUFR compression technique involves negligible overheads for data items that are invariant.
- (3) Compound BUFR messages may be described within the data description section, if required (e.g. 3 01 041, 3 04 001, 3 04 002, 3 04 003, 3 04 004, 3 04 005, 3 04 006).

Category 13 – Sequences common to image data

Category 13			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 13 009	0 21 001	(Radar reflectivity values) Horizontal reflectivity	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 21 001	Horizontal reflectivity	
3 13 010		(Radar rainfall intensities)	
	0 21 036	Radar rainfall intensity	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
3 13 031	0 21 036	Radar rainfall intensity	
		(Non run-length encoded row for Pixel value (4 bits))	
	0 06 002	Longitude (coarse accuracy)	
		Longitude increment (coarse accuracy)	
3 13 032	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	0 30 001	Pixel value (4 bits)	
		(Non run-length encoded picture data for Pixel value (4 bits))	
3 13 041	0 05 002	Latitude (coarse accuracy)	
		Latitude increment (coarse accuracy)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
3 13 041	3 13 031	Non run-length encoded row for Pixel value (4 bits)	
		(Run-length encoded row for Pixel value (4 bits))	
	0 06 002	Longitude (coarse accuracy)	
		Longitude increment (coarse accuracy)	
3 13 041	1 10 000	Delayed replication of 10 descriptors	
	0 31 001	Delayed descriptor replication factor	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
3 13 041	0 06 012	Longitude increment (coarse accuracy)	
	1 01 000	Delayed replication of 1 descriptor	
		(Run-length encoded row for Pixel value (4 bits))	
	0 06 002	Longitude (coarse accuracy)	

FM 94 BUFR

Category 13			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 13 041 (continued)	0 31 012	Extended delayed descriptor and data repetition factor	
	0 30 001	Pixel value (4 bits)	
	0 06 012	Longitude increment (coarse accuracy)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 30 001	Pixel value (4 bits)	
3 13 042		(Run-length encoded picture data for Pixel value (4 bits))	
	0 05 002	Latitude (coarse accuracy)	First latitude location minus one increment
	0 05 012	Latitude increment (coarse accuracy)	Signed value so cannot cross pole
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 13 041	Run-length encoded row for pixel value (4 bits)	
3 13 043		(Run-length encoded picture data for pixel value (4 bits), regular grid)	
	0 06 002	Longitude (coarse accuracy)	First longitude location minus one increment
	0 05 002	Latitude (coarse accuracy)	First latitude location minus one increment
	0 05 012	Latitude increment (coarse accuracy)	
	1 12 000	Delayed replication of 12 descriptors	
	0 31 001	Delayed descriptor replication factor	
	1 10 000	Delayed replication of 10 descriptors	
	0 31 001	Delayed descriptor replication factor	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 06 012	Longitude increment (coarse accuracy)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 011	Delayed descriptor and data repetition factor	
	0 30 001	Pixel value (4 bits)	
	0 06 012	Longitude increment (coarse accuracy)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 30 001	Pixel value (4 bits)	

Category 15 – Oceanographic report sequences

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 001	0 01 011	(Typically reported underwater sounding without optional fields) Ship or mobile land station identifier	Ship's call sign
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 06 001	Depth, temperature	
3 15 002	0 01 011	(Typically reported underwater sounding without optional fields) Ship or mobile land station identifier	Ship's call sign
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 023	Latitude/longitude (coarse accuracy)	
	3 06 004	Depth, temperature, salinity	
3 15 003	0 01 087	(Temperature and salinity profile observed by profile floats) WMO marine observing platform extended identifier	
	0 01 085	Observing platform manufacturer's model	
	0 01 086	Observing platform manufacturer's serial number	
	0 02 036	Buoy type	
	0 02 148	Data collection and/or location system	
	0 02 149	Type of data buoy	
	0 22 055	Float cycle number	
	0 22 056	Direction of profile	
	0 22 067	Instrument type for water temperature/salinity profile measurement	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	1 09 000	Delayed replication of 9 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 07 065	Water pressure	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 045	Sea/water temperature	
	0 08 080	Qualifier for GTSP quality flag	

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 003 (continued)	0 33 050	Global GTSP quality flag	
	0 22 064	Salinity	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
3 15 004		(XBT temperature profile data sequence)	
	0 01 079	Unique identifier for the profile	Hexadecimal string
	0 01 011	Ship or mobile land station identifier	Ship's call sign
	0 01 103	IMO Number. Unique Lloyd's register	= 0 to 9999999
	0 01 087	WMO marine observing platform extended identifier (see Note 1)	
	0 01 019	Long station or site name	Ship name
	0 01 080	Ship line number according to SOOP	
	0 05 036	Ship transect number according to SOOP (see Note 2)	
	0 01 036	Agency in charge of operating the observing platform	
	0 01 013	Speed of motion of moving observing platform	
	0 01 012	Direction of motion of moving observing platform	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 02 002	Type of instrumentation for wind measurement	
	0 11 002	Wind speed	
	0 11 001	Wind direction	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	
	0 07 033	Height of sensor above water surface	
	0 12 101	Temperature/air temperature	
	0 12 103	Dewpoint temperature	
	0 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	0 07 033	Height of sensor above water surface	Set to missing (cancel)
	3 02 021	Waves	
	0 02 031	Duration and time of current measurement	
	0 02 030	Method of current measurement	
	0 22 005	Direction of sea-surface current	
	0 22 032	Speed of sea-surface current	
	0 22 063	Total water depth	
	0 08 080	Qualifier for GTSP quality flag	
	0 33 050	Global GTSP quality flag	
	0 22 178	XBT/XCTD launcher type	

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 004 (continued)	0 22 177	Height of XBT/XCTD launcher	Above sea level 0 to 50 m in units of whole m
	0 22 067	Instrument type for water temperature/salinity profile measurement	
	0 08 041	Data significance	
	0 26 021	Year	
	0 26 022	Month	
	0 26 023	Day	
	0 22 068	Water temperature profile recorder types	
	0 25 061	Software identification and version number	
	0 08 041	Data significance	Set to missing (cancel)
	0 08 080	Qualifier for GTSP quality flag	Set to missing (cancel)
	0 02 171	Instrument serial number for water temperature profile measurement	
	3 02 090	Sea/water temperature high precision	
	0 02 171	Instrument serial number for water temperature profile measurement	
	0 02 032	Indicator for digitization (see Note 3)	
	3 15 005	Water temperature profile (temperature profile observed by XBT or buoy)	
3 15 005		(Water temperature profile (temperature profile observed by XBT or buoy))	
	1 06 000	Delayed replication of 6 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 07 063	Depth below sea/water surface (cm)	
	0 08 080	Qualifier for GTSP quality flag	= 13 Water depth at a level
	0 33 050	Global GTSP quality flag	
	0 22 043	Sea/water temperature	
	0 08 080	Qualifier for GTSP quality flag	= 11 Water temperature at a level
3 15 007	0 33 050	Global GTSP quality flag	
		(Sequence for representation of data derived from a ship-based lowered instrument measuring subsurface sea/water temperature, salinity and current profiles)	
	3 01 003	Ship's call sign and motion <i>Extended identification</i>	
	0 01 019	Long station or site name	
	0 01 103	IMO Number. Unique Lloyd's register	Values are restricted to between 0 and 9999999

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 007 (continued)	0 01 087	WMO marine observing platform extended identifier	Set to missing, if ship's call sign is reported
		<i>Cruise/ship line information</i>	
	0 01 036	Agency in charge of operating the observing platform	
	0 01 115	Identifier of the cruise or mission under which the data were collected	Set to missing, if no cruise identifier is reported
	0 01 080	Ship line number according to SOOP	
	0 05 036	Ship transect number according to SOOP	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
		<i>Profile information</i>	
	0 01 079	Unique identifier for the profile	
	0 01 023	Observation sequence number	Cast/station number along the line/transect
	0 22 063	Total water depth	
		<i>Surface pressure</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 001	Pressure and 3-hour pressure change	
		<i>Waves</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 021	Waves	
		<i>Temperature and humidity data</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 052	Ship temperature and humidity data	
		<i>Wind data</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 059	Ship wind data	
		<i>Surface temperature, salinity and current</i>	
	0 22 067	Instrument type for water temperature/salinity profile measurement	
	0 02 171	Instrument serial number for water temperature profile measurement	
	3 02 090	Sea/water temperature high precision	Surface temperature
	3 06 033	Surface salinity	
	3 06 034	Surface current	
	0 02 171	Instrument serial number for water temperature profile measurement	Set to missing (cancel)
	0 22 067	Instrument type for water temperature/salinity profile measurement	Set to missing (cancel)

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 007 (continued)	0 02 038	<i>Temperature and salinity profile data</i> Method of water temperature and/or salinity measurement	
	0 22 067	Instrument type for water temperature/salinity profile measurement	
	0 22 068	Water temperature profile recorder types	
	0 02 171	Instrument serial number for water temperature profile measurement	
	0 02 033	Method of salinity/depth measurement	
	0 02 032	Indicator for digitization	
	0 22 056	Direction of profile	
	0 03 011	Method of depth calculation	
	3 06 035	Temperature and salinity profile	
		<i>Current profile data</i>	
	1 07 000	Delayed replication of 7 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 02 032	Indicator for digitization	
	0 03 010	Method of sea/water current measurement	
	0 02 031	Duration and time of current measurement	
	0 02 040	Method of removing velocity and motion of platform from current	
	0 22 056	Direction of profile	
	0 03 011	Method of depth calculation	
	3 06 036	Current profile	
		<i>Dissolved oxygen profile data</i>	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 02 032	Indicator for digitization	
	0 03 012	Instrument type/sensor for dissolved oxygen measurement	
	0 03 011	Method of depth calculation	
	3 06 037	Dissolved oxygen profile data	
		(Sequence for the representation of data from moored buoys)	
		<i>Buoy identification and location</i>	
	3 01 126	Sequence for representation of moored buoy identification	
		<i>Standard meteorological data</i>	
	3 06 038	Sequence for representation of standard surface marine meteorological observations from moored buoys	
		<i>Optional ancillary meteorological data</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 091	Sequence for representation of ancillary meteorological observations	
3 15 008			For buoys equipped with more than 1 anemometer, the height of sensor should relate to the one being used

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 008 (continued)		<i>Optional radiation measurements</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 02 082	Radiation data	
		<i>Optional basic wave measurements</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 039	Sequence for representation of basic wave measurements	
		<i>Optional spectral wave measurements</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 040	Sequence for representation of detailed spectral wave measurements	
		<i>Optional temperature profile measurements</i>	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 02 005	Precision of temperature observation	
	3 06 041	Depth and temperature profile (high accuracy/precision)	
		<i>Optional temperature and salinity profile measurements</i>	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 02 005	Precision of temperature observation	
	3 06 004	Depth, temperature, salinity	
		<i>Optional subsurface current measurements</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 005	Subsurface current measurements	
		(Sequence for the representation of data from drifting buoys)	
3 15 009	0 01 087	WMO marine observing platform extended identifier	
	0 01 019	Long station or site name	
	0 02 149	Type of data buoy	
		<i>Time/date of last known position</i>	
	0 08 021	Time significance	= 26 Time of last known position
	3 01 011	Year, month, day	Date of last known position
	3 01 012	Hour, minute	Time of last known position
		<i>Location and location quality</i>	
	3 01 021	Latitude/longitude (high accuracy)	
	2 08 016	Change width of CCITT IA5 field	Change to 16 characters

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 009 (continued)	0 01 051	Platform Transmitter ID number	Cancel = 1 Argos, = 8 Iridium and GPS, = 9 Argos-3 Platform drift direction Speed of motion of moving observing platform
	2 08 000	Change width of CCITT IA5 field	
	0 02 148	Data collection and/or location system	
	0 01 012	Direction of motion of moving observing platform	
	0 01 014	Platform drift speed (high precision)	
	0 33 022	Quality of buoy satellite transmission	
	0 33 023	Quality of buoy location	
	0 33 027	Location quality class (range of radius of 66% confidence)	
	0 25 026	Battery voltage (large range)	
		<i>Drogue status</i>	
	0 02 034	Drogue type	Platform battery voltage
	0 22 060	Lagrangian drifter drogue status	
	0 07 070	Drogue depth	
	0 02 190	Lagrangian drifter submergence (% time submerged)	
		<i>Time/date of observation</i>	
	0 08 021	Time significance	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
		<i>Surface temperature and salinity</i>	
	0 02 005	Precision of temperature observation	
	0 22 043	Sea/water temperature	
	0 02 033	Method of salinity/depth measurement	
	0 22 059	Sea-surface salinity	
		<i>Surface type/ice information</i>	
	0 08 029	Surface type	
	0 13 115	Ice thickness	
		<i>Optional temperature and salinity profile measurements</i>	
	1 03 000	Delayed replication of 3 descriptors	Set to missing (cancel)
	0 31 000	Short delayed descriptor replication factor	
	0 02 005	Precision of temperature observation	
	3 06 004	Depth, temperature, salinity	
	0 02 005	Precision of temperature observation	
		<i>Pressure and air temperature data</i>	
	0 10 004	Pressure	
	0 10 051	Pressure reduced to mean sea level	
	1 02 000	Delayed replication of 2 descriptors	

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 009 (continued)	0 31 000	Short delayed descriptor replication factor	
	0 07 033	Height of sensor above water surface	
	0 12 101	Temperature/air temperature <i>Wind data</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 042	Wind measurement from drifting buoy <i>Wave data</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 039	Sequence for representation of basic wave measurements	
		(First five Fourier components of the wave spectrum)	
3 15 010	1 12 000	Delayed replication of 12 descriptors	
	0 31 001	Delayed descriptor replication factor	
	2 01 144	Change data width	Add 16 bits to the width for each data element in Table B
	2 02 133	Change scale	Add 5 to the scale for each data element in Table B
	0 22 080	Waveband central frequency	Hz
	0 22 096	Spectral band width	Hz
	0 22 069	Spectral wave density	m ² Hz ⁻¹
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 42 011	a1 coefficient of the directional Fourier series	First moment of the directional wave spectrum
	0 42 012	b1 coefficient of the directional Fourier series	First moment of the directional wave spectrum
	0 42 013	a2 coefficient of the directional Fourier series	Second moment of the directional wave spectrum
	0 42 014	b2 coefficient of the directional Fourier series	Second moment of the directional wave spectrum
	0 42 015	Check factor K	Inverse of wave ellipticity
		(Met-ocean observations from autonomous surface vehicles)	
3 15 011	3 01 150	WIGOS identifier	
	0 01 087	WMO marine observing platform extended identifier	
	0 01 036	Agency in charge of operating the observing platform	
	0 01 085	Observing platform manufacturer's model	

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 011 (continued)	0 01 086	Observing platform manufacturer's serial number	UUID for report, 32-character hex string
	0 03 001	Surface station type	
	2 08 032	Change width of CCITT IA5 field	
	0 01 079	Unique ID for profile	
	2 08 000	Change width of CCITT IA5 field	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 01 012	Direction of motion of moving observing platform	
	0 01 014	Platform drift speed (high precision)	
	0 11 104	True heading of aircraft, ship or other mobile platform	
	1 03 000	Delayed replication of 3 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 07 031	Height of barometer above mean sea level	
	3 06 038	Sequence for representation of standard surface marine meteorological observations from moored buoys	
	0 12 161	Skin temperature	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 034	Surface current	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 039	Sequence for representation of basic wave measurements	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 033	Surface salinity	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 041	Depth and temperature profile (high accuracy/precision)	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 004	Depth, temperature, salinity	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 005	Subsurface current measurements	
	1 05 000	Delayed replication of 5 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 41 001	pCO ₂	
	0 08 043	Atmospheric chemical or physical constituent type	

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 15 011 (continued)	0 15 028	Mole fraction of atmospheric constituent/pollutant in dry air	
	0 08 043	Atmospheric chemical or physical constituent type	
	0 13 080	Water pH	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 41 005	Turbidity	
	0 41 003	Dissolved nitrates	
	0 22 188	Dissolved oxygen	
	0 41 002	Fluorescence	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 06 040	Sequence for representation of detailed spectral wave measurements	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 000	Short delayed descriptor replication factor	
	0 08 021	Time significance	
	0 04 025	Time period or displacement	
	0 14 017	Instantaneous long-wave radiation	
	0 14 018	Instantaneous short-wave radiation	
		(Sequence for reporting observations from a single glider trajectory profile)	
	3 01 150	WIGOS identifier	
<u>3 15 012</u>	<u>2 01 129</u>	<u>Change data width</u>	<u>Add one bit to width of following descriptor</u>
	<u>0 01 087</u>	<u>WMO marine observing platform extended identifier</u>	
	<u>2 01 000</u>	<u>Change data width</u>	<u>Cancel change width</u>
	<u>0 01 019</u>	<u>Long station or site name</u>	
	<u>0 01 036</u>	<u>Agency in charge of operating the observing platform</u>	
	<u>0 02 148</u>	<u>Data collection and/or location system</u>	
	<u>0 01 085</u>	<u>Observing platform manufacturer's model</u>	
	<u>0 01 086</u>	<u>Observing platform manufacturer's serial number</u>	
	<u>0 08 021</u>	<u>Time significance</u>	<u>Set to 25, nominal reporting time</u>
	<u>3 01 011</u>	<u>Year, month, day</u>	
	<u>3 01 013</u>	<u>Hour, minute, second</u>	
	<u>3 01 021</u>	<u>Latitude/longitude (high accuracy)</u>	
	<u>0 11 104</u>	<u>True heading of aircraft, ship or other mobile platform</u>	

FM 94 BUFR

Category 15			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
<u>3 15 012</u> <u>(continued)</u>	<u>0 02 169</u>	<u>Anemometer type</u>	<u>Set to 2, wind observation through ambient noise (WOTAN)</u>
	<u>0 11 002</u>	<u>Wind speed</u>	
	<u>0 11 001</u>	<u>Wind direction</u>	
	<u>0 02 169</u>	<u>Anemometer type</u>	<u>Set to missing / cancel previous value</u>
	<u>0 22 032</u>	<u>Speed of sea-surface current</u>	
	<u>0 22 005</u>	<u>Direction of sea-surface current</u>	
	<u>3 01 011</u>	<u>Year, month, day</u>	
	<u>3 01 013</u>	<u>Hour, minute, second</u>	
	<u>0 08 021</u>	<u>Time significance</u>	<u>Set to 2, time averaged</u>
	<u>0 04 025</u>	<u>Time period or displacement</u>	<u>Duration of dive, e.g. -10 (minutes)</u>
	<u>3 01 021</u>	<u>Latitude/longitude (high accuracy)</u>	
	<u>0 22 031</u>	<u>Speed of current</u>	
	<u>0 22 004</u>	<u>Direction of current</u>	
	<u>0 08 021</u>	<u>Time significance</u>	<u>Set to missing / cancel previous value</u>
	<u>0 05 068</u>	<u>Profile number</u>	
	<u>0 01 079</u>	<u>Unique identifier for the profile</u>	
	<u>1 26 000</u>	<u>Delayed replication of 26 descriptors</u>	
	<u>0 31 001</u>	<u>Delayed descriptor replication factor</u>	<u>Number of profile sections (e.g. descending, horizontal, ascending)</u>
	<u>0 22 056</u>	<u>Direction of profile</u>	<u>0 (ascending / upwards profile), 1 (descending / downwards profile), or 2 (horizontal)</u>
	<u>1 23 000</u>	<u>Delayed replication of 23 descriptors</u>	
	<u>0 31 002</u>	<u>Extended delayed descriptor replication factor</u>	
	<u>3 01 011</u>	<u>Year, month, day</u>	
	<u>3 01 013</u>	<u>Hour, minute, second</u>	
	<u>3 01 021</u>	<u>Latitude/longitude (high accuracy)</u>	
	<u>0 08 080</u>	<u>Qualifier for GTSP quality flag</u>	<u>20, position</u>
	<u>0 33 050</u>	<u>Global GTSP quality flag</u>	
	<u>0 07 062</u>	<u>Depth below sea/water surface</u>	
	<u>0 08 080</u>	<u>Qualifier for GTSP quality flag</u>	<u>13, water depth at a level</u>
	<u>0 33 050</u>	<u>Global GTSP quality flag</u>	
	<u>0 22 065</u>	<u>Water pressure</u>	
	<u>0 08 080</u>	<u>Qualifier for GTSP quality flag</u>	<u>10, water pressure at a level</u>
	<u>0 33 050</u>	<u>Global GTSP quality flag</u>	

FM 94 BUFR

Category 15			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
<u>3 15 012</u> <u>(continued)</u>	<u>0 22 045</u>	<u>Sea/water temperature</u>	
	<u>0 08 080</u>	<u>Qualifier for GTSP quality flag</u>	<u>11, water temperature at a level</u>
	<u>0 33 050</u>	<u>Global GTSP quality flag</u>	
	<u>0 22 066</u>	<u>Water conductivity</u>	
	<u>0 08 080</u>	<u>Qualifier for GTSP quality flag</u>	<u>25, water conductivity at a level</u>
	<u>0 33 050</u>	<u>Global GTSP quality flag</u>	
	<u>0 22 064</u>	<u>Salinity</u>	
	<u>0 08 080</u>	<u>Qualifier for GTSP quality flag</u>	<u>12, salinity at a level</u>
	<u>0 33 050</u>	<u>Global GTSP quality flag</u>	
	<u>0 42 016</u>	<u>Sea water potential density referenced to sea surface</u>	
	<u>0 08 080</u>	<u>Qualifier for GTSP quality flag</u>	<u>26, sea water potential density at a level</u>
	<u>0 33 050</u>	<u>Global GTSP quality flag</u>	
		(Sequence for reporting trajectory profile data from marine animal tags) <u>(see Note 4)</u>	
	3 01 150	WIGOS identifier	
	0 01 087	WMO marine observing platform extended identifier	WMO number, where assigned
	2 08 032	Change width of CCITT IA5	change width to 32 characters
	0 01 019	Ship or mobile land <u>Long station identifier or site name</u>	Platform ID, e.g. ct145-933-BAT2-18 (max 32 characters)
	2 08 000	Change width of CCITT IA5	Cancel change width
	0 03 001	Surface station type	10 (Marine animal)
	0 22 067	Instrument type for water temperature and/or salinity measurement	set to 995 (attached to marine animal)
3 15 013	0 01 051	Platform transmitter ID number	e.g. Argos PTT
	0 02 148	Data collection and/or location system	
	1 12 000	Delayed replication of 12 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 021	Time significance	set to 26, time of last known position
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 01 012	Direction of motion of moving observing platform	
	3 15 013	0 01 014	Platform drift speed (high precision)

FM 94 BUFR

Category 15			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
<u>3 15 013</u> (continued)	0 33 022	Quality of buoy satellite transmission	
	0 33 023	Quality of buoy location	
	0 33 027	Location quality class (range of radius of 66% confidence)	
	0 07 063	Depth below sea/water surface	
	0 22 045	Sea/water temperature	
	0 08 021	Time significance	Set to missing/cancel
	1 07 000	Delayed replication of 7 descriptors	
	0 31 001	Delayed descriptor replication factor	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 021	Latitude/longitude (high accuracy)	
	0 01 079	Unique identifier for the profile	Profile ID
	0 01 023	Observation sequence number	Upcast number
	0 22 056	Direction of profile	Set to 0 (ascending/upwards)
	3 06 035	Temperature and salinity profile	
		(Sequence for reporting trajectory profile data from marine animal tags)	
	<u>201129</u>	<u>Change width</u>	<u>Add one bit to width of following descriptor</u>
	<u>001087</u>	<u>WMO marine observing platform extended identifier</u>	<u>WMO number where assigned</u>
	<u>201000</u>	<u>Change width</u>	<u>Cancel change width</u>
	<u>208032</u>	<u>Change width of CCITT IA5</u>	<u>change width to 32 characters</u>
<u>3 15 023</u>	<u>001019</u>	<u>Long station or site name</u>	<u>Platform ID, e.g. ct145-933-BAT2-18 (max 32 characters)</u>
	<u>208000</u>	<u>Change width of CCITT IA5</u>	<u>Cancel change width</u>
	<u>003001</u>	<u>Surface station type</u>	<u>10 (Marine animal)</u>
	<u>022067</u>	<u>Instrument type for water temperature and/or salinity measurement</u>	<u>set to 995 (attached to marine animal)</u>
	<u>001051</u>	<u>Platform transmitter ID number</u>	<u>e.g. Argos PTT</u>
	<u>002148</u>	<u>Data collection and/or location system</u>	
	<u>112000</u>	<u>Delayed replication of 12 descriptors</u>	
	<u>031001</u>	<u>Delayed descriptor replication factor</u>	
	<u>008021</u>	<u>Time significance</u>	<u>set to 26, time of last known position</u>
	<u>301011</u>	<u>Year, month, day</u>	
	<u>301012</u>	<u>Hour, minute</u>	
	<u>301021</u>	<u>Latitude/longitude (high accuracy)</u>	

FM 94 BUFR

		Category 15	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	001012	Direction of motion of moving observing platform	
	001014	Platform drift speed (high precision)	
	033022	Quality of buoy satellite transmission	
	033023	Quality buoy location	
	033027	Location quality class (range of radius of 66% confidence)	
	007063	Depth below sea/water surface	
	022045	Sea/water temperature	
	008021	Time significance	Set to missing/cancel
	107000	Delayed replication of 7 descriptors	
	031001	Delayed descriptor replication factor	
	301011	Year, month, day	
	301012	Hour, minute	
	301021	Latitude/longitude (high accuracy)	
	001079	Unique identifier for the profile	Profile ID
	001023	Observation sequence number	Upcast number
	022056	Direction of profile	Set to 0 (ascending/upward s)
	306035	Temperature and salinity profile	
	201129	Change width	Add one bit to width of following descriptor
	001087	WMO marine observing platform extended identifier	WMO number where assigned
	201000	Change width	Cancel change width
	208032	Change width of CCITT IA5	change width to 32 characters
	001019	Long station or site name	Platform ID, e.g. ct145-933-BAT2-18 (max 32 characters)
	208000	Change width of CCITT IA5	Cancel change width
	003001	Surface station type	10 (Marine animal)

Notes:

- (1) If field 0 01 011 is used, this field will be left missing and vice versa.
- (2) Integer, assigned by the operator, incremented for each new transect (i.e. all drops have the same transect number while the ship is moving from one end point of the line to the other end point; as soon as the ship arrived to port and goes back to start a new transect then transect number is incremented). The initial value and subsequent values for transect numbers do not matter provided that each new transect by a ship on a line has a transect number higher than previous transect numbers for the same line and the same ship. In case a single cruise follows more than one SOOP line in a row, then the transect number should be incremented each time the cruise changes line.
- (3) This descriptor applies to the method used to select depths for the temperature profile encoded through 3 15 005. If temperatures are reported at significant depths, the values shall:

- (a) Be sufficient to reproduce basic features of the profile;
 - (b) Define the top and the bottom of isothermal layers.
- (4) It is recommended to use 3 15 023 instead of 3 15 013.
-

Provisional Copy
2023

Category 16 – Synoptic feature sequences

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 001	3 01 011	Year, month, day	15 m s ⁻¹ typically
	0 04 004	Hour	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 01 021	Synoptic feature identifier	
	0 02 041	Method for estimating reports related to synoptic features	
	0 19 001	Type of synoptic feature	
	0 10 051	Pressure reduced to mean sea level	
	0 19 002	Effective radius of feature	
	0 19 003	Wind speed threshold	
	0 19 004	Effective radius with respect to wind speeds above threshold	
3 16 002		(Header)	Data time (analysis)
	0 08 021	Time significance	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	Validity time (forecast)
	0 04 004	Hour	
	0 04 005	Minute	
	0 01 033	Identification of originating/generating centre	
	0 08 021	Time significance	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
3 16 003	0 07 002	Height or altitude	Flight level (base of chart layer)
	0 07 002	Height or altitude	Flight level (top of chart layer)
		(Jet stream)	Jet stream value Value for line
	1 10 000	Delayed replication of 10 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 011	Meteorological feature	
	0 08 007	Dimensional significance	
	1 04 000	Delayed replication of 4 descriptors	Flight level
	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 10 002	Height	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 003 (continued)	0 11 002	Wind speed	
	0 08 007	Dimensional significance	Cancel
	0 08 011	Meteorological feature	Cancel End of object
3 16 004		(Turbulence)	
	1 11 000	Delayed replication of 11 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 011	Meteorological feature	Value for turbulence
	0 08 007	Dimensional significance	Value for area
	0 07 002	Height or altitude	Flight level (base of layer)
	0 07 002	Height or altitude	Flight level (top of layer)
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 11 031	Degree of turbulence (see Note 1)	
	0 08 007	Dimensional significance	Cancel
	0 08 011	Meteorological feature	Cancel End of object
3 16 005		(Storm)	
	1 08 000	Delayed replication of 8 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 005	Meteorological attribute significance	Storm centre
	0 08 007	Dimensional significance	Value for point
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 01 026	WMO storm name	Use "UNKNOWN" for a sandstorm
	0 19 001	Type of synoptic feature	Value for type of storm
	0 08 007	Dimensional significance	Cancel
	0 08 005	Meteorological attribute significance	Cancel End of object
3 16 006		(Cloud)	
	1 12 000	Delayed replication of 12 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 011	Meteorological feature	Value for cloud
	0 08 007	Dimensional significance	Value for area
	0 07 002	Height or altitude	Flight level (base of layer)
	0 07 002	Height or altitude	Flight level (top of layer)
	1 02 000	Delayed replication of 2 descriptors	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 006 (continued)	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 20 011	Cloud amount (see Note 2)	
	0 20 012	Cloud type	
	0 08 007	Dimensional significance	Cancel
	0 08 011	Meteorological feature	Cancel End of object
3 16 007		(Front)	
	1 10 000	Delayed replication of 10 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 011	Meteorological feature (see Note 3)	Value for type of front
	0 08 007	Dimensional significance	Value for line
	1 04 000	Delayed replication of 4 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 19 005	Direction of motion of feature	
	0 19 006	Speed of motion of feature	
	0 08 007	Dimensional significance	Cancel
	0 08 011	Meteorological feature	Cancel End of object
		(Tropopause)	
3 16 008	1 11 000	Delayed replication of 11 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 001	Vertical sounding significance	Bit 3 set for tropopause
	0 08 007	Dimensional significance	Value for point
	0 08 023	First-order statistics (see Note 4)	Type of tropopause value
	1 03 000	Delayed replication of 3 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 10 002	Height	
	0 08 023	First-order statistics	Cancel
	0 08 007	Dimensional significance	Cancel
	0 08 001	Vertical sounding significance	Cancel End of object
		(Airframe icing area)	
3 16 009	1 11 000	Delayed replication of 11 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 011	Meteorological feature	Value for airframe icing

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 009 (continued)	0 08 007	Dimensional significance	Value for area
	0 07 002	Height or altitude	Flight level (base of layer)
	0 07 002	Height or altitude	Flight level (top of layer)
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 20 041	Airframe icing	Type of airframe icing
	0 08 007	Dimensional significance	Cancel
	0 08 011	Meteorological feature	Cancel End of object
3 16 010		(Name of feature)	
	1 07 000	Delayed replication of 7 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 011	Meteorological feature	
	0 08 007	Dimensional significance	Value for point
	0 01 022	Name of feature	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 08 007	Dimensional significance	Cancel
	0 08 011	Meteorological feature	Cancel End of object
3 16 011		(Volcano erupting)	
	1 17 000	Delayed replication of 17 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 011	Meteorological feature	Value for special clouds
	0 01 022	Name of feature	Volcano name
	0 08 007	Dimensional significance	Value for point
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 08 021	Time significance	Eruption starting time
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 011 (continued)	0 20 090	Special clouds	Clouds from volcanic eruptions
	0 08 021	Time significance	Cancel
	0 08 007	Dimensional significance	Cancel
	0 08 011	Meteorological feature	Cancel End of object
3 16 020		(Tropical storm identification)	
	0 01 033	Identification of originating/generating centre	
	0 01 025	Storm identifier	
	0 01 027	WMO long storm name	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
3 16 021		(Analysis data)	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 02 041	Method for estimating reports related to synoptic features	
	0 19 001	Type of synoptic feature	
	0 19 007	Effective radius of feature	
	0 19 005	Direction of motion of feature	
	0 19 006	Speed of motion of feature	
	0 19 008	Vertical extent of circulation	
	0 08 005	Meteorological attribute significance	= 1 Storm centre
	0 10 004	Pressure	Storm centre by virtue of preceding significance qualifier
	0 08 005	Meteorological attribute significance	= 2 Outer limit or edge of feature
	0 10 004	Pressure	Outer limit
	0 19 007	Effective radius of feature	Outer limit
	0 08 005	Meteorological attribute significance	= 3 Location of maximum wind
	0 08 021	Time significance	Time averaged
	0 04 075	Short time period or displacement	Minutes
	0 11 040	Maximum wind speed (mean wind)	
	0 19 007	Effective radius of feature	Maximum wind
	1 05 004	Replicate 5 descriptors 4 times	
	0 05 021	Bearing or azimuth	Starting
	0 05 021	Bearing or azimuth	Ending
	1 02 002	Replicate 2 descriptors 2 times	
	0 19 003	Wind speed threshold	
	0 19 004	Effective radius with respect to wind speeds above threshold	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 022	0 01 032	(Forecast data) Generating application	NWP model name, etc. code table defined by originating/ generating centre
	0 02 041	Method for estimating reports related to synoptic features	
	0 19 001	Type of synoptic feature	
	0 19 010	Method for tracking the centre of synoptic feature	
	1 18 000	Delayed replication of 18 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 021	Time significance	
	0 04 014	Time increment	
	0 08 005	Meteorological attribute significance	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 19 005	Direction of motion of feature	Forecast Hours Surface synoptic feature
	0 19 006	Speed of motion of feature	
	0 10 004	Pressure	
	0 11 041	Maximum wind gust speed	
	0 08 021	Time significance	
	0 04 075	Short time period or displacement	
	0 11 040	Maximum wind speed (mean wind)	
	0 19 008	Vertical extent of circulation	
	1 05 004	Replicate 5 descriptors 4 times	
	0 05 021	Bearing or azimuth	
	0 05 021	Bearing or azimuth	For example, used in the United States Forecast time averaged Minutes Starting Ending
	1 02 002	Replicate 2 descriptors 2 times	
	0 19 003	Wind speed threshold	
	0 19 004	Effective radius with respect to wind speeds above threshold	
3 16 026		(Tropical storm analysis information)	
	3 16 020	Tropical storm identification	
	3 16 021	Analysis data	
3 16 027		(Tropical storm forecast information)	
	3 16 020	Tropical storm identification	
	3 16 022	Forecast data	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 030	3 01 014	(SIGMET header) Time period	For which SIGMET is valid = 1 ATS unit serving FIR = 2 FIR, = 3 UIR, = 4 CTA = 6 MWO Set to missing (cancel)
	0 01 037	SIGMET sequence identifier	
	0 10 064	SIGMET cruising level	
	0 08 019	Qualifier for following centre identifier	
	0 01 062	Short ICAO location indicator	
	0 08 019	Qualifier for following centre identifier	
	0 01 065	ICAO region identifier	
	0 08 019	Qualifier for following centre identifier	
	0 01 062	Short ICAO location indicator	
	0 08 019	Qualifier for following centre identifier	
3 16 031	0 08 021	(SIGMET, Observed or forecast location and motion) Time significance	= 16 Analysis, = 4 Forecast Set to missing (cancel)
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 027	Description of a feature in 3-D or 2-D	
	0 19 005	Direction of motion of feature	
	0 19 006	Speed of motion of feature	
	0 20 028	Expected change in intensity	
	0 08 021	Time significance	
3 16 032	0 08 021	(SIGMET, Forecast position) Time significance	= 4 Forecast Set to missing (cancel)
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	3 01 027	Description of a feature in 3-D or 2-D	
	0 08 021	Time significance	
3 16 033	0 08 021	(SIGMET, Outlook) Time significance	= 4 Forecast Set to missing (cancel)
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 01 027	Description of a feature in 3-D or 2-D	
	0 08 021	Time significance	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 034	0 08 079	(Volcanic Ash SIGMET) Product status	= 0 Normal issue, = 1 Correction
	3 16 030	SIGMET header	
	0 08 011	Meteorological feature	= 17 Volcano
	0 01 022	Name of feature	
	0 08 007	Dimensional significance	= 0 Point
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 08 007	Dimensional significance	Set to missing (cancel)
	0 20 090	Special clouds	= 5 Clouds from volcanic eruptions
	3 16 031	SIGMET, Observed or forecast location and motion	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 16 032	SIGMET, Forecast position	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 16 033	SIGMET, Outlook	
	0 08 011	Meteorological feature	Set to missing (cancel)
	0 08 079	Product status	Set to missing (cancel)
3 16 035		(Thunderstorm SIGMET)	
	0 08 079	Product status	= 0 Normal issue, = 1 Correction
	3 16 030	SIGMET header	
	0 08 011	Meteorological feature	= 21 Thunderstorm
	0 20 023	Other weather phenomena	Bit 2 = Squalls or all 18 bits = Missing
	0 20 021	Type of precipitation	Bit 14 = Hail or all 30 bits = Missing
	0 20 008	Cloud distribution for aviation	= 15 OBSC, = 16 EMBD, = 12 FRQ, = 31 Missing
	3 16 031	SIGMET, Observed or forecast location and motion	
	0 08 011	Meteorological feature	Set to missing (cancel)
	0 08 079	Product status	Set to missing (cancel)

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 036	0 08 079	(Tropical cyclone SIGMET) Product status	= 0 Normal issue, = 1 Correction
	3 16 030	SIGMET header	
	0 08 011	Meteorological feature	= 22 Tropical cyclone
	0 01 027	WMO long storm name	
	3 16 031	SIGMET, Observed or forecast location and motion	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 000	Short delayed descriptor replication factor	
	3 16 032	SIGMET, Forecast position	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	3 16 033	SIGMET, Outlook	
	0 08 011	Meteorological feature	Set to missing (cancel)
	0 08 079	Product status	Set to missing (cancel)
3 16 037	0 08 079	(Turbulence SIGMET) Product status	= 0 Normal issue, = 1 Correction
	3 16 030	SIGMET header	
	0 08 011	Meteorological feature	= 13 Turbulence
	0 11 031	Degree of turbulence	= 10 Moderate, = 11 Severe
	3 16 031	SIGMET, Observed or forecast location and motion	
	0 08 011	Meteorological feature	Set to missing (cancel)
	0 08 079	Product status	Set to missing (cancel)
3 16 038	0 08 079	(Icing SIGMET) Product status	= 0 Normal issue, = 1 Correction
	3 16 030	SIGMET header	
	0 08 011	Meteorological feature	= 15 Airframe icing
	0 20 041	Airframe icing	= 7 Severe
	0 20 021	Type of precipitation	Bit 3 = Liquid freezing or all 30 bits = Missing
	3 16 031	SIGMET, Observed or forecast location and motion	
	0 08 011	Meteorological feature	Set to missing (cancel)
	0 08 079	Product status	Set to missing (cancel)

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 039	0 08 079	(Mountain wave, duststorm or sandstorm SIGMET) Product status	= 0 Normal issue, = 1 Correction
	3 16 030	SIGMET header	
	0 08 011	Meteorological feature	= 23 Mountain wave, = 24 Duststorm, = 25 Sandstorm
	0 20 024	Intensity of phenomena	= 3 Heavy, = 5 Severe
	3 16 031	SIGMET, Observed or forecast location and motion	
	0 08 011	Meteorological feature	Set to missing (cancel)
	0 08 079	Product status	Set to missing (cancel)
3 16 040		(Cancellation of SIGMET)	
	3 16 030	SIGMET header	
	0 08 079	Product status	= 4 Cancellation
	3 01 014	Time period	Of the SIGMET to be cancelled
	0 01 037	SIGMET sequence identifier	Of the SIGMET to be cancelled
	0 10 064	SIGMET cruising level	Of the SIGMET to be cancelled
	0 08 079	Product status	Set to missing (cancel)
3 16 050		(RADOB template – Part A: Information on tropical cyclone)	
	3 01 001	WMO block and station numbers	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	0 02 160	Wavelength of the radar	
	0 08 005	Meteorological attribute significance	= 1
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 08 005	Meteorological attribute significance	Cancel
	0 19 100	Time interval to calculate the movement of the tropical cyclone	
	0 19 005	Direction of motion of feature	
	0 19 006	Speed of motion of feature	
	0 19 101	Accuracy of the position of the centre of the tropical cyclone	
	0 19 102	Shape and definition of the eye of the tropical cyclone	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 050 (continued)	0 19 103	Diameter of major axis of the eye of the tropical cyclone	
	0 19 104	Change in character of the eye during the 30 minutes	
	0 19 105	Distance between the end of spiral band and the centre	
		(SAREP template – Part A: Information on tropical cyclone)	
3 16 052	3 01 005	Originating centre/sub-centre	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	0 01 007	Satellite identifier	
	0 25 150	Method of tropical cyclone intensity analysis using satellite data	
	1 22 000	Delayed replication of 22 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 01 027	WMO long storm name	
	0 19 150	Typhoon International Common Number (Typhoon Committee)	
	0 19 106	Identification number of tropical cyclone	
	0 08 005	Meteorological attribute significance	= 1
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 08 005	Meteorological attribute significance	Cancel
	0 19 107	Time interval over which the movement of the tropical cyclone has been calculated	
	0 19 005	Direction of motion of feature	
	0 19 006	Speed of motion of feature	
	0 19 108	Accuracy of geographical position of the tropical cyclone	
	0 19 109	Mean diameter of the overcast cloud of the tropical cyclone	
	0 19 110	Apparent 24-hour change in intensity of the tropical cyclone	
	0 19 111	Current Intensity (CI) number of the tropical cyclone	
	0 19 112	Data Tropical (DT) number of the tropical cyclone	
	0 19 113	Cloud pattern type of the DT-number	
	0 19 114	Model Expected Tropical (MET) number of the tropical cyclone	
	0 19 115	Trend of the past 24-hour change (+: Developed, -: Weakened)	
	0 19 116	Pattern Tropical (PT) number of the tropical cyclone	
	0 19 117	Cloud picture type of the PT-number	
	0 19 118	Final Tropical (T) number of the tropical cyclone	
	0 19 119	Type of the final T-number	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 060	3 01 011	(Definition of squall line (by 3 points: Centre, North, South) and forecasted trajectory and evolution) Year, month, day	
	3 01 012	Hour, minute <i>Position of squall line centre</i>	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	0 19 005	Direction of motion of feature	
	0 19 006	Speed of motion of feature <i>Amplitude of feature from most external points to centre point – North point</i>	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy) <i>Amplitude of feature from most external points to centre point – South point</i>	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy) <i>Amplitude of feature from most external points to centre point – Evolution</i>	
	0 04 074	Short time period or displacement	
	0 20 048	Evolution of feature	
	0 11 041	Maximum wind gust speed	
	0 13 055	Intensity of precipitation	
		(Definition of squall line (by centre and several points: North points and South points) and forecasted trajectory and evolution)	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
3 16 061	0 05 002	Latitude (coarse accuracy)	Period of validity Maximum burst expected Intensity of rain expected
	0 06 002	Longitude (coarse accuracy)	
	0 19 005	Direction of motion of feature	
	0 19 006	Speed of motion of feature <i>Amplitude of feature from most external points to centre point – North points</i>	
	1 02 000	Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 061 (continued)	1 02 000	Amplitude of feature from most external points to centre point – South points Delayed replication of 2 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
		Amplitude of feature from most external points to centre point – Evolution	
	0 04 074	Short time period or displacement	Period of validity
	0 20 048	Evolution of feature	
	0 11 041	Maximum wind gust speed	Maximum burst expected
	0 13 055	Intensity of precipitation	Intensity of rain expected
3 16 071	3 01 014	(Graphical AIRMET Sierra) Time period	For which AIRMET is valid
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 16 075	GFA IFR ceiling and visibility	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 16 076	GFA mountain obscuration	
3 16 072	3 01 014	(Graphical AIRMET Tango) Time period	For which AIRMET is valid
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 16 077	GFA turbulence	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 16 078	GFA strong surface wind	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 16 079	GFA low-level wind shear	
3 16 073	3 01 014	(Graphical AIRMET Zulu) Time period	For which AIRMET is valid
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 16 080	GFA icing	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 16 081	GFA freezing level	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 074	0 01 039	(GFA identifier and observed/forecast location) Graphical Area Forecast (GFA) sequence identifier	
	0 08 021	Time significance	= 4 Forecast, = 16 Analysis
	3 01 014	Time period	For which hazard is being observed/ forecast
	3 01 027	Description of a feature in 3-D or 2-D	
	0 08 021	Time significance	Set to missing (cancel)
3 16 075	0 08 079	(GFA IFR ceiling and visibility) Product status	= 0 Normal, = 1 COR, = 2 AMD, = 3 COR AMD, = 4 CNL
	0 08 041	Data significance	= 8 IFR ceiling and visibility
	3 16 074	GFA identifier and observed/forecast location	
	0 20 006	Flight rules	= 1 IFR
	0 33 042	Type of limit represented by following value	= 2 Exclusive upper limit, = 7 Missing
	0 20 013	Height of base of cloud	
	0 33 042	Type of limit represented by following value	= 2 Exclusive upper limit, = 7 Missing
	0 20 001	Horizontal visibility	
	0 20 025	Obscuration	
	0 20 026	Character of obscuration	= 6 Blowing, = 15 Missing
	0 08 041	Data significance	Set to missing (cancel)
	0 08 079	Product status	Set to missing (cancel)
3 16 076	0 08 079	(GFA mountain obscuration) Product status	= 0 Normal, = 1 COR, = 2 AMD, = 3 COR AMD, = 4 CNL
	0 08 041	Data significance	= 9 Mountain obscuration
	3 16 074	GFA identifier and observed/forecast location	
	0 20 006	Flight rules	= 1 IFR

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 076 (continued)	0 20 025 0 20 026 0 08 041 0 08 079	Obscuration Character of obscuration Data significance Product status	= 6 Blowing, = 15 Missing Set to missing (cancel) Set to missing (cancel)
3 16 077	0 08 079 0 08 011 3 16 074 0 11 031 0 08 011 0 08 079	(GFA turbulence) Product status Meteorological feature GFA identifier and observed/forecast location Degree of turbulence Meteorological feature Product status	= 0 Normal, = 1 COR, = 2 AMD, = 3 COR AMD, = 4 CNL = 13 Turbulence = 6 Moderate Set to missing (cancel) Set to missing (cancel)
3 16 078	0 08 079 0 08 041 3 16 074 0 33 042 0 11 012 0 08 041 0 08 079	(GFA strong surface wind) Product status Data significance GFA identifier and observed/forecast location Type of limit represented by following value Wind speed at 10 m Data significance Product status	= 0 Normal, = 1 COR, = 2 AMD, = 3 COR AMD, = 4 CNL = 10 Strong surface wind = 0 Exclusive lower limit Set to missing (cancel) Set to missing (cancel)
3 16 079	0 08 079 0 08 011 3 16 074 0 20 023	(GFA low-level wind shear) Product status Meteorological feature GFA identifier and observed/forecast location Other weather phenomena	= 0 Normal, = 1 COR, = 2 AMD, = 3 COR AMD, = 4 CNL = 16 Phenomenon Bit 12 = Wind shear

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 079 (continued)	0 20 024 0 08 011 0 08 079	Intensity of phenomena Meteorological feature Product status	Set to missing (cancel) Set to missing (cancel)
3 16 080	0 08 079 0 08 011 3 16 074 0 20 041 0 08 011 0 08 079	(GFA icing) Product status Meteorological feature GFA identifier and observed/forecast location Airframe icing Meteorological feature Product status	= 0 Normal, = 1 COR, = 2 AMD, = 3 COR AMD, = 4 CNL = 15 Airframe icing = 4 Moderate icing Set to missing (cancel) Set to missing (cancel)
3 16 081	0 08 079 0 08 041 3 16 074 0 08 041 0 08 079	(GFA freezing level) Product status Data significance GFA identifier and observed/forecast location Data significance Product status	= 0 Normal, = 1 COR, = 2 AMD, = 3 COR AMD, = 4 CNL = 11 Freezing level, = 12 Multiple freezing level Set to missing (cancel) Set to missing (cancel)
3 16 082	0 01 033 0 01 034 0 01 032 0 01 025 0 01 027 0 01 090 0 01 091 0 01 092 3 01 011 3 01 012 0 08 005 3 01 023 0 08 005	(Tropical cyclone track and wind radii) Identification of originating/generating centre Identification of originating/generating sub- centre Generating application Storm identifier WMO long storm name Technique for making up initial perturbations Ensemble member number Type of ensemble forecast Year, month, day Hour, minute Meteorological attribute significance Latitude/longitude (coarse accuracy) Meteorological attribute significance	

FM 94 BUFR

Category 16			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 16 082 (continued)	3 01 023	Latitude/longitude (coarse accuracy)	Set to missing (cancel)
	0 10 051	Pressure reduced to mean sea level	
	0 08 005	Meteorological attribute significance	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 11 012	Wind speed at 10 m	
	1 07 003	Delayed replication of 7 descriptors	
	0 19 003	Wind speed threshold	
	1 05 004	Delayed replication of 5 descriptors	
	0 05 021	Bearing or azimuth	
	0 05 021	Bearing or azimuth	
	2 01 131	Change data width	
	0 19 004	Effective radius with respect to wind speeds above threshold	
	2 01 000	Change data width	
	1 16 000	Delayed replication of 16 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 08 021	Time significance	
	0 04 024	Time period or displacement	
	0 08 005	Meteorological attribute significance	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 10 051	Pressure reduced to mean sea level	
	0 08 005	Meteorological attribute significance	
	3 01 023	Latitude/longitude (coarse accuracy)	
	0 11 012	Wind speed at 10 m	
	1 07 003	Delayed replication of 7 descriptors	
	0 19 003	Wind speed threshold	
	1 05 004	Delayed replication of 5 descriptors	
	0 05 021	Bearing or azimuth	
	0 05 021	Bearing or azimuth	
	2 01 131	Change data width	
	0 19 004	Effective radius with respect to wind speeds above threshold	
2 01 000	Change data width	Set to missing (cancel)	

Notes:

- (1) For MOD OCNL SEV code as 12 (extreme in clear air) or 13 (extreme in cloud).
- (2) Code table values:

FRQ	=	code figure 8 (8 oktas)
OCNL EMBD	=	code figure 6 (6 oktas)
ISOL	=	code figure 2 (2 oktas) when the cloud = Cb.
- (3) Front direction (towards which the front is moving) must always be given as it is needed for plotting purposes. A front direction with a front speed of zero would indicate a slow front. A value in the code table exists to represent a quasi-stationary front.

- (4) The statistic is to determine whether the following tropopause levels are minimum, maximum or spot values (missing code value).
 - (5) Decibel (dB) is a logarithmic measure of the relative power, or of the relative values of two flux densities, especially of sound intensities and radio and radar power densities. In radar meteorology, the logarithmic scale (dBZ) is used for measuring radar reflectivity factor (obtained from the American Meteorological Society *Glossary of Meteorology*).
-

Provisional Copy
2023

Category 18 – Radiological report sequences

Category 18			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 18 001	3 01 025 0 24 011	Latitude/longitude (coarse accuracy), day/time Dose	
3 18 003	3 01 026 0 24 005 0 24 004 0 24 021	Latitude/longitude (high accuracy), time period (day, hour, minute) Isotope mass Element name Air concentration (of named isotope type including gross beta)	
3 18 004	3 01 025 0 04 023 0 13 011 0 24 005 0 24 004 0 24 022	Latitude/longitude (coarse accuracy), day/time Time period or displacement Total precipitation/total water equivalent Isotope mass Element name Concentration in precipitation (of named isotope type)	

Category 21 – Radar report sequences

		Category 21	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 21 001	0 02 101	(Wind profiler – antenna characteristics) Type of antenna	
	0 02 114	Antenna effective surface area	
	0 02 105	Maximum antenna gain	
	0 02 106	3-dB beamwidth	
	0 02 107	Sidelobe suppression	
	0 02 121	Mean frequency	
3 21 003		(Wind profiler – moment data)	
	0 21 051	Signal power above 1 mW	
	0 21 014	Doppler mean velocity (radial)	
	0 21 017	Doppler velocity spectral width	
3 21 004	0 21 030	Signal to noise ratio	
		(Wind profiler – moment data sounding)	
	3 01 031	Identification and type of station, date/time, location (high accuracy), height of station	
	0 02 003	Type of measuring equipment used	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
3 21 005	3 21 003	Wind profiler – moment data	
		(Transmitter-receiver characteristics)	
	0 25 004	Echo processing	
	0 02 121	Mean frequency	
	0 02 122	Frequency agility range	
	0 02 123	Peak power	
	0 02 124	Average power	
	0 02 125	Pulse repetition frequency	
	0 02 126	Pulse width	
	0 02 127	Receiver intermediate frequency	
	0 02 128	Intermediate frequency bandwidth	
	0 02 129	Minimum detectable signal	
	0 02 130	Dynamic range	
	0 02 131	Sensitivity time control (STC)	
3 21 006		(Integration characteristics)	
	0 25 001	Range-gate length	
	0 25 002	Number of gates averaged	
	0 25 003	Number of integrated pulses	
	0 25 005	Echo integration	

FM 94 BUFR

		Category 21	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 21 007	0 25 009	(Corrections) Calibration method	Altitude of the tower base
	0 25 010	Clutter treatment	
	0 25 011	Ground occultation correction (screening)	
	0 25 012	Range attenuation correction	
	0 25 013	Bright-band correction	
	0 25 015	Radome attenuation correction	
	0 25 016	Clear-air attenuation correction	
	0 25 017	Precipitation attenuation correction	
3 21 008	0 25 006	(Z to R conversion) Z to R conversion	
	0 25 007	Z to R conversion factor	
	0 25 008	Z to R conversion exponent	
3 21 009	0 25 018	(A to Z law) A to Z law for attenuation factor	
	0 25 019	A to Z law for attenuation exponent	
3 21 010	0 02 101	(Antenna characteristics) Type of antenna	
	0 07 002	Height or altitude	
	0 02 102	Antenna height above tower base	
	0 02 103	Radome	
	0 02 104	Antenna polarization	
	0 02 105	Maximum antenna gain	
	0 02 106	3-dB beamwidth	
	0 02 107	Sidelobe suppression	
	0 02 108	Crosspol discrimination (on axis)	
	0 02 109	Antenna speed (azimuth)	
	0 02 110	Antenna speed (elevation)	
	0 02 132	Azimuth pointing accuracy	
	0 02 133	Elevation pointing accuracy	
3 21 011	0 30 031	(General characteristics) Picture type	
	0 30 032	Combination with other data	
	0 29 002	Coordinate grid type	
3 21 012	1 01 000	(Antenna elevations) Delayed replication of 1 descriptor	
	0 31 001	Delayed descriptor replication factor	
	0 02 135	Antenna elevation	

FM 94 BUFR

		Category 21	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 21 021	0 02 003	(Basic information (system/site header) on wind profiler/RASS) Type of measuring equipment used	
	0 02 101	Type of antenna	
	2 01 130	Change data width	8 bits long
	0 02 106	3-dB beamwidth	
	2 01 000	Change data width	Cancel
	2 01 132	Change data width	11 bits long
	2 02 130	Change scale	Scale: -6
	0 02 121	Mean frequency	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	2 01 133	Change data width	11 bits long
	2 02 129	Change scale	Scale: 0
	0 25 001	Range-gate length	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
3 21 022		(Wind profiler: processed-data winds)	
	0 07 007	Height	
	2 04 001	Add associated field	1 bit long
	0 31 021	Associated field significance	
	0 11 001	Wind direction	
	2 04 000	Add associated field	Cancel
	0 11 002	Wind speed	
	2 04 001	Add associated field	1 bit long
	0 31 021	Associated field significance	
	0 11 006	w-component	
	2 04 000	Add associated field	Cancel
3 21 023		(Wind profiler: raw-data winds)	
	0 07 007	Height	
	0 21 091	Radar signal Doppler spectrum 0th moment	
	0 21 030	Signal to noise ratio	
	2 02 129	Change scale	Scale: 2
	0 21 014	Doppler mean velocity (radial)	
	2 01 129	Change data width	9 bits long
	0 21 017	Doppler velocity spectral width	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel

FM 94 BUFR

		Category 21	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 21 024	0 07 007	(RASS-mode: processed-data RASS) Height	1 bit long
	2 04 001	Add associated field	
	0 31 021	Associated field significance	
	0 12 007	Virtual temperature	Cancel
	0 11 006	w-component	
	2 04 000	Add associated field	
	0 21 030	Signal to noise ratio	
3 21 025	0 07 007	(RASS-mode: raw-data RASS) Height	Scale: 2
	0 21 091	Radar signal Doppler spectrum 0th moment	
	0 21 030	Signal to noise ratio	
	2 02 129	Change scale	9 bits long
	0 21 014	Doppler mean velocity (radial)	
	2 01 129	Change data width	Cancel
	0 21 017	Doppler velocity spectral width	
	2 02 000	Change scale	Referring to RASS signal
	2 01 000	Change data width	
	0 21 092	RASS signal Doppler spectrum 0th moment, referring to RASS signal	9 bits long
	0 21 030	Signal to noise ratio	
	0 25 092	Acoustic propagation velocity	Scale: 2
	2 01 129	Change data width	
	2 02 129	Change scale	Referring to RASS signal
	0 21 017	Doppler velocity spectral width	
3 21 026	2 02 000	Change scale	Cancel
	2 01 000	Change data width	
		(RASS data – fluxes)	1 bit long
	0 07 007	Height	
	2 04 001	Add associated field	
	0 31 021	Associated field significance	
	0 12 007	Virtual temperature	
	0 25 091	Structure constant of the refraction index (C_n^2)	
	0 11 071	Turbulent vertical momentum flux	
	0 11 072	Turbulent vertical buoyancy flux	
	0 11 073	Turbulent kinetic energy	
	0 11 074	Dissipation energy	
	2 04 000	Add associated field	Cancel

FM 94 BUFR

		Category 21	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 21 027	0 21 118	(Radar specification, normalized radar cross-section, Kp variance coefficient)	
	2 02 129	Attenuation correction on sigma-0	
	2 01 132	Change scale	
	0 02 112	Change data width	
	2 01 000	Radar look angle	
	2 01 131	Change data width	Cancel
	0 02 111	Change data width	
	2 01 000	Radar incidence angle	
	2 02 000	Change data width	Cancel
	0 02 104	Change scale	Cancel
	0 21 105	Antenna polarization	
	0 21 106	Normalized radar cross-section	
	0 21 107	Kp variance coefficient (alpha)	
	0 21 114	Kp variance coefficient (beta)	
	0 21 115	Kp variance coefficient (gamma)	
	0 21 116	SEAWINDS sigma-0 quality	
	0 21 117	SEAWINDS sigma-0 mode	
	0 08 018	SEAWINDS land/ice surface type	
	0 21 117	Sigma-0 variance quality control	
3 21 028	0 21 118	(Radar specification, SEAWINDS normalized radar cross-section, Kp variance coefficient)	
	2 02 129	Attenuation correction on sigma-0	
	2 01 132	Change scale	
	0 02 112	Change data width	
	2 01 000	Radar look angle	
	2 01 131	Change data width	Cancel
	0 02 111	Change data width	
	2 01 000	Radar incidence angle	
	2 02 000	Change data width	Cancel
	0 02 104	Change scale	Cancel
	0 21 123	Antenna polarization	
	0 21 106	SEAWINDS normalized radar cross-section	
	0 21 107	Kp variance coefficient (alpha)	
	0 21 114	Kp variance coefficient (beta)	
	0 21 115	Kp variance coefficient (gamma)	
	0 21 116	SEAWINDS sigma-0 quality	
	0 21 117	SEAWINDS sigma-0 mode	
	0 08 018	SEAWINDS land/ice surface type	
	0 21 117	Sigma-0 variance quality control	

FM 94 BUFR

		Category 21	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 21 030	0 08 085	(ASCAT sigma-0 information) Beam identifier	
	2 02 129	Change scale	Increase scale by 10 ¹
	2 01 131	Change data width	Increase width by 3 bits
	0 02 111	Radar incidence angle	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	0 02 134	Antenna beam azimuth	
	0 21 062	Backscatter	
	0 21 063	Radiometric resolution (noise value)	
	0 21 158	ASCAT Kp estimate quality	
	0 21 159	ASCAT sigma-0 usability	
	0 21 160	ASCAT use of synthetic data	
	0 21 161	ASCAT synthetic data quantity	
	0 21 162	ASCAT satellite orbit and attitude quality	
	0 21 163	ASCAT solar array reflection contamination	
	0 21 164	ASCAT telemetry presence and quality	
	0 21 165	ASCAT extrapolated reference function presence	
	0 21 166	Land fraction	
3 21 031		(Satellite radar observations)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub- centre	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 10 033	Altitude (platform to ellipsoid)	
	0 08 043	Atmospheric chemical or physical constituent type	
	0 25 139	Processing level	
	0 02 153	Satellite channel centre frequency	
	1 06 000	Delayed replication of 6 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	0 07 071	Height (high resolution)	
	0 21 007	Radar reflectivity factor	

FM 94 BUFR

		Category 21	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 21 031 <i>(continued)</i>	0 21 008 0 21 009 0 21 010 0 33 003	Uncertainty in radar reflectivity factor Vertical Doppler velocity Uncertainty in vertical Doppler velocity Quality information	

Provisional Copy
2023

Category 22 – Chemical and aerosol sequences

		Category 22	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
<u>3 22 001</u>	<u>3 01 013</u> <u>3 01 021</u> <u>0 05 041</u> <u>0 05 043</u> <u>0 27 080</u> <u>0 05 022</u> <u>0 13 040</u> <u>0 20 010</u> <u>0 33 085</u> <u>0 33 095</u> <u>1 05 002</u> <u>0 08 098</u> <u>0 07 024</u> <u>0 07 025</u> <u>0 07 073</u> <u>0 07 074</u> <u>1 06 000</u> <u>0 31 001</u> <u>0 02 071</u> <u>0 08 043</u> <u>0 15 024</u> <u>0 08 043</u> <u>0 15 024</u> <u>0 15 042</u> <u>2 24 000</u> <u>2 36 000</u> <u>1 01 000</u> <u>0 31 002</u> <u>0 31 031</u> <u>0 01 033</u> <u>0 01 032</u> <u>0 08 023</u> <u>1 01 000</u> <u>0 31 002</u> <u>2 24 255</u>	<u>(Aerosol optical depth)</u> <u>Hour, minute, second</u> <u>Latitude/longitude (high accuracy)</u> <u>Scan line number</u> <u>Field of view number</u> <u>Viewing azimuth angle</u> <u>Solar azimuth</u> <u>Surface flag</u> <u>Cloud cover (total)</u> <u>Aerosol optical thickness quality flags</u> <u>Aerosol optical depth quality information</u> <u>Replicate 5 descriptors 2 times</u> <u>Sensing direction</u> <u>Satellite zenith angle</u> <u>Solar zenith angle</u> <u>Scattering angle</u> <u>Relative azimuth angle</u> <u>Delayed replication of 6 descriptors</u> <u>Delayed descriptor replication factor</u> <u>Spectrographic wavelength</u> <u>Atmospheric chemical or physical constituent type</u> <u>Optical depth</u> <u>Atmospheric chemical or physical constituent type</u> <u>Optical depth</u> <u>Reflectance</u> <u>First-order statistical values follow</u> <u>Define data present bit-map</u> <u>Delayed replication of 1 descriptors</u> <u>Extended delayed descriptor replication factor</u> <u>Data present indicator</u> <u>Identification of originating/generating centre</u> <u>Generating application</u> <u>First-order statistics</u> <u>Delayed replication of 1 descriptors</u> <u>Extended delayed descriptor replication factor</u> <u>First-order statistical values marker operator</u>	
3 22 028	0 01 007 0 02 019 0 04 001 0 04 002	(METOP GOME-2) Satellite identifier Satellite instruments Year Month	

FM 94 BUFR

		Category 22	
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 006	Second	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 27 001	Latitude (high accuracy)	
	0 28 001	Longitude (high accuracy)	
	0 27 001	Latitude (high accuracy)	
	0 28 001	Longitude (high accuracy)	
	0 27 001	Latitude (high accuracy)	
	0 28 001	Longitude (high accuracy)	
	0 27 001	Latitude (high accuracy)	
	0 28 001	Longitude (high accuracy)	
	0 10 001	Height of land surface	
	0 14 019	Surface albedo	
	0 07 025	Solar zenith angle	
	0 10 080	Viewing zenith angle	
	0 05 023	Sun to satellite azimuth difference	
	0 20 010	Cloud cover (total)	
	0 08 003	Vertical significance (satellite observations)	
	0 07 004	Pressure	
	0 14 026	Albedo at the top of clouds	
	0 20 014	Height of top of cloud	
	0 13 093	Cloud optical thickness	
	1 05 000	Delayed replication of 5 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 07 004	Pressure	
	0 07 004	Pressure	
	0 08 043	Atmospheric chemical or physical constituent type	
	0 08 044	CAS registry number	
	0 15 021	Integrated mass density	

Category 40 – Additional satellite report sequences

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 001	0 01 007	(IASI Level 1c data) Satellite identifier	
	0 01 031	Identification of originating/generating centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	2 02 131	Change scale	Add 3 to scale
	2 01 138	Change data width	Add 10 to width
	0 04 006	Second	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 05 043	Field of view number	
	0 05 040	Orbit number	
	2 01 133	Change data width	Add 5 to width
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel
	2 01 132	Change data width	Add 4 to width
	0 25 070	Major frame count	
	2 01 000	Change data width	Cancel
	2 02 126	Change scale	Subtract 2 from scale
	0 07 001	Height of station	
	2 02 000	Change scale	Cancel
	0 33 060	GqisFlagQual – individual IASI-System quality flag	
	0 33 061	GqisQualIndex – indicator for instrument noise performance (contributions from spectral and radiometric calibration)	
	0 33 062	GqisQualIndexLoc – indicator for geometric quality index	
	0 33 063	GqisQualIndexRad – indicator for instrument noise performance (contributions from radiometric calibration)	
	0 33 064	GqisQualIndexSpect – indicator for instrument noise performance (contributions from spectral calibration)	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 001 (continued)	0 33 065	GqisSysTecSondQual – output of system TEC (Technical Expertise Centre) quality function	
	1 01 010	Replicate 1 descriptor 10 times	
	3 40 002	Band description	
	1 01 087	Replicate 1 descriptor 87 times	
	3 40 003	IASI Level 1c 100 channels	
	0 02 019	Satellite instruments	
	0 25 051	AVHRR channel combination	
	1 01 007	Replicate 1 descriptor 7 times	
	3 40 004	IASI Level 1c AVHRR single scene	
3 40 002		(Band description)	
	0 25 140	Start channel	
	0 25 141	End channel	
	0 25 142	Channel scale factor	
3 40 003		(IASI Level 1c 100 channels)	
	1 04 100	Replicate 4 descriptors 100 times	
	2 01 136	Change data width	Add 8 to width
	0 05 042	Channel number	
	2 01 000	Change data width	Cancel
3 40 004	0 14 046	Scaled radiance	
		(IASI Level 1c AVHRR single scene)	
	0 05 060	Y angular position from centre of gravity	
	0 05 061	Z angular position from centre of gravity	
	0 25 085	Fraction of clear pixels in HIRS FOV	
	1 05 006	Replicate 5 descriptors 6 times	
	0 05 042	Channel number	
	0 25 142	Channel scale factor	
	0 14 047	Scaled mean AVHRR radiance	
	0 25 142	Channel scale factor	
3 40 005	0 14 048	Scaled standard deviation AVHRR radiance	
		(JASON2 OGDR data) (see Note)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 096	Station acquisition	
	0 25 061	Software identification and version number	
	0 05 044	Satellite cycle number	
	0 05 040	Orbit number	
	0 01 030	Numerical model identifier	
		<i>Datation</i>	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 005 (continued)	0 04 005	Minute	
	0 04 007	Seconds within a minute (microsecond accuracy)	
		<i>Location and surface type</i>	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 08 029	Surface type	
	0 08 074	Altimeter echo type	
	0 08 077	Radiometer sensed surface type	
		<i>Flags</i>	
	0 40 011	Interpolation flag	
	0 25 097	Three-dimensional error estimate of the navigator orbit	
	0 25 095	Altimeter state flag	
	0 25 098	Altimeter data quality flag	
	0 25 099	Altimeter correction quality flag	
	0 21 144	Altimeter rain flag	
	0 25 096	Radiometer state flag	
	0 40 012	Radiometer data quality flag	
	0 40 013	Radiometer brightness temperature interpretation flag	
	0 21 169	Ice presence indicator	
		<i>Altimeter: Ku band</i>	
	0 22 151	Ku band ocean range	
	0 22 162	RMS of 20 Hz Ku band ocean range	
	0 22 163	Number of 20 Hz valid points for Ku band	
	0 25 160	Ku band net instrumental correction	
	0 25 133	Sea state bias correction on Ku band	
	0 22 156	Ku band significant wave height	
	0 22 164	RMS 20 Hz Ku band significant wave height	
	0 22 165	Number of 20 Hz valid points for Ku band significant wave height	
	0 22 166	Ku band net instrumental correction for significant wave height	
	0 21 137	Ku band corrected ocean backscatter coefficient	
	0 21 138	STD Ku band corrected ocean backscatter coefficient	
	0 22 167	Number of valid points for Ku band backscatter	
	0 21 139	Ku band net instrumental correction for AGC	
	0 21 118	Attenuation correction on sigma-0	
	0 21 145	Ku band automatic gain control	
	0 21 146	RMS Ku band automatic gain control	
	0 21 147	Number of valid points for Ku band automatic gain control	
		<i>Altimeter: C band</i>	
	0 22 168	C band ocean range	
	0 22 169	RMS of C band ocean range	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 005 (continued)	0 22 170	Number of 20 Hz valid points for C band	
	0 25 161	C band net instrumental correction	
	0 25 162	Sea state bias correction on C band	
	0 22 171	C band significant wave height	
	0 22 172	RMS 20 Hz C band significant wave height	
	0 22 173	Number of 20 Hz valid points for C band significant wave height	
	0 22 174	C band net instrumental correction for significant wave height	
	0 21 170	C band corrected ocean backscatter coefficient	
	0 21 171	RMS C band corrected ocean backscatter coefficient	
	0 22 175	Number of valid points for C band backscatter	
	0 21 172	C band net instrumental correction for AGC	
	0 21 118	Attenuation correction on sigma-0	
	0 21 173	C band automatic gain control	
	0 21 174	RMS C band automatic gain control	
	0 21 175	Number of valid points for C band automatic gain control	
		<i>Radiometer</i>	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 13 090	Radiometer water vapour content	
	0 13 091	Radiometer liquid content	
		<i>Wind</i>	
	0 07 002	Height or altitude	
	0 11 097	Wind speed from altimeter	
	0 11 098	Wind speed from radiometer	
	0 07 002	Height or altitude	
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
		<i>Dynamic topography</i>	
	0 10 096	Mean dynamic topography	
	0 10 081	Altitude of COG above reference ellipsoid	
	0 10 082	Instantaneous altitude rate	
	0 10 083	Squared off nadir angle of the satellite from platform data	
	0 10 101	Squared off nadir angle of the satellite from waveform data	
	0 25 132	Ionospheric correction from model on Ku band	
	0 25 163	Altimeter ionospheric correction on Ku band	
	0 25 126	Model dry tropospheric correction	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 005 (continued)	0 25 128	Model wet tropospheric correction	
	0 25 164	Radiometer wet tropospheric correction	
	0 10 085	Mean sea-surface height	
	0 10 097	Mean sea-surface height from altimeter only	
	0 10 086	Geoid's height	
	0 10 087	Ocean depth/land elevation	
	0 10 092	Solid Earth tide height	
	0 10 088	Total geocentric ocean tide height (solution 1)	
	0 10 089	Total geocentric ocean tide height (solution 2)	
	0 10 098	Loading tide height geocentric ocean tide solution 1	
	0 10 099	Loading tide height geocentric ocean tide solution 2	
	0 10 090	Long period tide height	
	0 10 100	Non-equilibrium long period tide height	
	0 10 093	Geocentric pole tide height	
	0 25 127	Inverted barometer correction	Sea-surface height correction due to pressure loading
	0 40 014	High-frequency fluctuations of the sea-surface topography correction	
		(IASI Level 1c data (all channels))	
3 40 007	0 01 007	Satellite identifier	
	0 01 031	Identification of originating/generating centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	2 02 131	Change scale	Add 3 to scale
	2 01 138	Change data width	Add 10 to width
	0 04 006	Second	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 05 043	Field of view number	
	0 05 040	Orbit number	
	2 01 133	Change data width	Add 5 to width
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 007 (continued)	2 01 132	Change data width	Add 4 to width
	0 25 070	Major frame count	
	2 01 000	Change data width	Cancel
	2 02 126	Change scale	Subtract 2 from scale
	0 07 001	Height of station	
	2 02 000	Change scale	Cancel
	1 03 003	Replicate 3 descriptors 3 times	
	0 25 140	Start channel	
	0 25 141	End channel	
	0 33 060	GqisFlagQual – individual IASI-System quality flag	
	0 33 061	GqisQualIndex – indicator for instrument noise performance (contributions from spectral and radiometric calibration)	
	0 33 062	GqisQualIndexLoc – indicator for geometric quality index	
	0 33 063	GqisQualIndexRad – indicator for instrument noise performance (contributions from radiometric calibration)	
	0 33 064	GqisQualIndexSpect – indicator for instrument noise performance (contributions from spectral calibration)	
	0 33 065	GqisSysTecSondQual – output of system TEC (Technical Expertise Centre) quality function	
	0 40 020	GqisFlagQualDetailed – quality flag for the system	
	1 01 010	Replicate 1 descriptor 10 times	
	3 40 002	Band description	
	1 01 087	Replicate 1 descriptor 87 times	
	3 40 003	IASI Level 1c 100 channels	
	0 02 019	Satellite instruments	
	0 25 051	AVHRR channel combination	
	1 01 007	Replicate 1 descriptor 7 times	
	3 40 004	IASI Level 1c AVHRR single scene	
	0 20 081	Cloud amount in segment	
	0 08 029	Surface type	
	0 20 083	Amount of segment covered by scene	
	0 08 029	Surface type	
	0 40 018	GIacAvgImagIIS – average of imager measurements	
	0 40 019	GIacVarImagIIS – variance of imager measurements	
	0 40 021	Fraction of weighted AVHRR pixel in IASI FOV covered with snow/ice	
	0 40 022	Number of missing, bad or failed AVHRR pixels	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 008		(IASI sequence combining PC scores, channel selection and enhanced data)	
		<i>Satellite processing information</i>	
	0 01 007	Satellite identifier	
	0 01 031	Identification of originating/generating centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
		<i>Date and time</i>	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	2 02 131	Change scale	Add 3 to scale
	2 01 138	Change data width	Add 10 to width
	0 04 006	Second	
	2 01 000	Change data width	Cancel
	2 02 000	Change scale	Cancel
		<i>Location information</i>	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 024	Satellite zenith angle	
	0 05 021	Bearing or azimuth	
	0 07 025	Solar zenith angle	
	0 05 022	Solar azimuth	
	0 05 043	Field of view number	
	0 05 040	Orbit number	
	2 01 133	Change data width	Add 5 to width
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel
	2 01 132	Change data width	Add 4 to width
	0 25 070	Major frame count	
	2 01 000	Change data width	Cancel
	2 02 126	Change scale	Subtract 2 from scale
	0 07 001	Height of station	
	2 02 000	Change scale	Cancel
		<i>Quality information</i>	
	1 03 003	Replicate 3 descriptors 3 times	
	0 25 140	Start channel	
	0 25 141	End channel	
	0 33 060	GqisFlagQual – individual IASI-System quality flag	
	0 33 061	GqisQualIndex – indicator for instrument noise performance (contributions from spectral and radiometric calibration)	
	0 33 062	GqisQualIndexLoc – indicator for geometric quality index	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 008 (continued)	0 33 063	GqisQualIndexRad – indicator for instrument noise performance (contributions from radiometric calibration)	
	0 33 064	GqisQualIndexSpect – indicator for instrument noise performance (contributions from spectral calibration)	
	0 33 065	GqisSysTecSondQual – output of system TEC (Technical Expertise Centre) quality function	
	0 40 020	GqisFlagQualDetailed – quality flag for the system	
		<i>IASI subset of channels</i>	
	1 01 010	Replicate 1 descriptor 10 times	
	3 40 002	Band description	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	2 01 136	Change data width	Add 8 to width
	0 05 042	Channel number	
	2 01 000	Change data width	Cancel
	0 14 046	Scaled radiance	
		<i>Instrument band definition</i>	
	1 08 003	Replicate 8 descriptors 3 times	
	0 25 140	Start channel	
	0 25 141	End channel	
	0 40 026	Score quantization factor	
	0 40 016	Residual RMS in band	
	0 25 062	Database identification	
		<i>Principal component scores for band</i>	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	0 40 017	Non-normalized principal component score	
		<i>AVHRR scene analysis</i>	
	0 02 019	Satellite instruments	
	0 25 051	AVHRR channel combination	
	1 01 007	Replicate 1 descriptor 7 times	
	3 40 004	IASI Level 1c AVHRR single scene	
	0 20 081	Cloud amount in segment	
	0 08 029	Surface type	
	0 20 083	Amount of segment covered by scene	
	0 08 029	Surface type	
	0 40 018	GIacAvgImagIIS – average of imager measurements	
	0 40 019	GIacVarImagIIS – variance of imager measurements	
	0 40 021	Fraction of weighted AVHRR pixel in IASI FOV covered with snow/ice	
	0 40 022	Number of missing, bad or failed AVHRR pixels	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 009	0 01 007	(Normalized differential vegetation index (NDVI)) Satellite identifier	
	0 01 031	Identification of originating/generating centre	
	0 02 019	Satellite instruments	
	0 02 020	Satellite classification	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	0 05 040	Orbit number	
	2 01 136	Change data width	Add 8 to width
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel
	0 25 071	Frame count	
	0 05 001	Latitude (high accuracy)	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	1 07 064	Replicate 7 descriptors 64 times	
	1 06 032	Replicate 6 descriptors 32 times	
	0 08 012	Land/sea qualifier	
	0 08 013	Day/night qualifier	
	0 08 065	Sun-glint indicator	
	0 08 072	Pixel(s) type	
	0 13 039	Terrain type (ice/snow)	
	0 40 015	Normalized differential vegetation index (NDVI)	
3 40 010		(JASON-2 OGDR data)	
		<i>Satellite</i>	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 096	Station acquisition	
	0 25 061	Software identification and version number	
	0 05 044	Satellite cycle number	
	0 05 040	Orbit number	
	0 01 030	Numerical model identifier	
		<i>Datation</i>	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 007	Seconds within a minute (microsecond accuracy)	
		<i>Location and surface type</i>	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 010 (continued)	0 08 029	Surface type	
	0 08 074	Altimeter echo type	
	0 08 077	Radiometer sensed surface type	
		<i>Flags</i>	
	0 40 011	Interpolation flag	
	0 25 097	Three-dimensional error estimate of the navigator orbit	
	0 25 095	Altimeter state flag	
	0 25 098	Altimeter data quality flag	
	0 25 099	Altimeter correction quality flag	
	0 21 144	Altimeter rain flag	
	0 25 096	Radiometer state flag	
	0 40 012	Radiometer data quality flag	
	0 40 013	Radiometer brightness temperature interpretation flag	
	0 21 169	Ice presence indicator	
	0 40 023	Auxiliary altimeter state flags	
	0 40 024	Meteorological map availability	
	0 40 025	Interpolation flag for mean diurnal tide	
		<i>Altimeter: Ku band</i>	
	0 22 151	Ku band ocean range	
	0 22 162	RMS of 20 Hz Ku band ocean range	
	0 22 163	Number of 20 Hz valid points for Ku band	
	0 25 160	Ku band net instrumental correction	
	0 25 133	Sea state bias correction on Ku band	
	0 22 156	Ku band significant wave height	
	0 22 164	RMS 20 Hz Ku band significant wave height	
	0 22 165	Number of 20 Hz valid points for Ku band significant wave height	
	0 22 166	Ku band net instrumental correction for significant wave height	
	0 21 137	Ku band corrected ocean backscatter coefficient	
	0 21 138	STD Ku band corrected ocean backscatter coefficient	
	0 22 167	Number of valid points for Ku band backscatter	
	0 21 139	Ku band net instrumental correction for AGC	
	0 21 118	Attenuation correction on sigma-0	
	0 21 145	Ku band automatic gain control	
	0 21 146	RMS Ku band automatic gain control	
	0 21 147	Number of valid points for Ku band automatic gain control	
		<i>Altimeter: C band</i>	
	0 22 168	C band ocean range	
	0 22 169	RMS of C band ocean range	
	0 22 170	Number of 20 Hz valid points for C band	
	0 25 161	C band net instrumental correction	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 010 (continued)	0 25 162	Sea state bias correction on C band	
	0 22 171	C band significant wave height	
	0 22 172	RMS 20 Hz C band significant wave height	
	0 22 173	Number of 20 Hz valid points for C band significant wave height	
	0 22 174	C band net instrumental correction for significant wave height	
	0 21 170	C band corrected ocean backscatter coefficient	
	0 21 171	RMS C band corrected ocean backscatter coefficient	
	0 22 175	Number of valid points for C band backscatter	
	0 21 172	C band net instrumental correction for AGC	
	0 21 118	Attenuation correction on sigma-0	
	0 21 173	C band automatic gain control	
	0 21 174	RMS C band automatic gain control	
	0 21 175	Number of valid points for C band automatic gain control	
		<i>Radiometer</i>	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 13 090	Radiometer water vapour content	
	0 13 091	Radiometer liquid content	
		<i>Wind</i>	
	0 07 002	Height or altitude	
	0 11 097	Wind speed from altimeter	
	0 11 098	Wind speed from radiometer	
	0 07 002	Height or altitude	
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
		<i>Dynamic topography</i>	
	0 10 096	Mean dynamic topography	
	0 10 081	Altitude of COG above reference ellipsoid	
	0 10 082	Instantaneous altitude rate	
	0 10 083	Squared off nadir angle of the satellite from platform data	
	0 10 101	Squared off nadir angle of the satellite from waveform data	
	0 25 132	Ionospheric correction from model on Ku band	
	0 25 163	Altimeter ionospheric correction on Ku band	
	0 25 126	Model dry tropospheric correction	
	0 25 128	Model wet tropospheric correction	
	0 25 164	Radiometer wet tropospheric correction	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 010 (continued)	0 10 085	Mean sea-surface height	Sea-surface height correction due to pressure loading
	0 10 097	Mean sea-surface height from altimeter only	
	0 10 086	Geoid's height	
	0 10 087	Ocean depth/land elevation	
	0 10 092	Solid Earth tide height	
	0 10 088	Total geocentric ocean tide height (solution 1)	
	0 10 089	Total geocentric ocean tide height (solution 2)	
	0 10 098	Loading tide height geocentric ocean tide solution 1	
	0 10 099	Loading tide height geocentric ocean tide solution 2	
	0 10 090	Long period tide height	
	0 10 100	Non-equilibrium long period tide height	
	0 10 093	Geocentric pole tide height	
	0 25 127	Inverted barometer correction	
	0 40 014	High-frequency fluctuations of the sea- surface topography correction	
	0 10 102	Sea-surface height anomaly	
3 40 011		(SARAL AltiKa)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 096	Station acquisition	
	0 25 061	Software identification and version number	
	0 05 044	Satellite cycle number	
	0 05 040	Orbit number	
	0 01 030	Numerical model identifier	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 007	Seconds within a minute (microsecond accuracy)	
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 08 029	Surface type	
	0 08 077	Radiometer sensed surface type	
	0 40 011	Interpolation flag	
	0 25 097	Three-dimensional error estimate of the navigator orbit	
	0 25 112	Band specific altimeter data quality flag	
	0 25 113	Band specific altimeter correction quality flag	
	0 21 148	Trailing edge variation flag	
	0 21 169	Ice presence indicator	
	0 40 024	Meteorological map availability	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 011 (continued)	0 40 025	Interpolation flag for mean diurnal tide	
	0 02 153	Satellite channel centre frequency	
	0 22 189	Specific band ocean range	
	0 22 191	RMS of specific band ocean range	
	0 22 130	Number of valid points for specific band	
	0 25 167	Specific band net instrumental correction	
	0 25 166	Sea state bias correction on specific band	
	0 22 190	Specific band significant wave height	
	0 22 131	RMS specific band significant wave height	
	0 22 132	Number of valid points for specific band significant wave height	
	0 22 133	Specific band net instrument correction for significant wave height	
	0 21 183	Specific band corrected ocean backscatter coefficient	
	0 21 184	STD specific band corrected ocean backscatter coefficient	
	0 22 134	Number of valid points for specific band backscatter	
	0 21 185	Specific band net instrumental correction for AGC	
	0 21 118	Attenuation correction on sigma-0	
	0 21 186	Specific band automatic gain control	
	0 21 187	RMS specific band automatic gain control	
	0 21 188	Number of valid points for specific band automatic gain control	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 13 090	Radiometer water vapour content	
	0 13 160	Radiometer liquid content	
	0 07 002	Height or altitude	
	0 11 097	Wind speed from altimeter	
	0 07 002	Height or altitude	
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
	0 10 096	Mean dynamic topography	
	0 10 081	Altitude of COG above reference ellipsoid	
	0 10 082	Instantaneous altitude rate	
	0 10 083	Squared off-nadir angle of the satellite from platform data	
	0 10 101	Squared off-nadir angle of the satellite from waveform data	
	0 02 153	Satellite channel centre frequency	
	0 25 165	Ionospheric correction from model on specific band	
	0 25 126	Model dry tropospheric correction	
	0 25 128	Model wet tropospheric correction	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 011 (continued)	0 25 164	Radiometer wet tropospheric correction	
	0 10 085	Mean sea-surface height	
	0 10 086	Geoid's height	
	0 10 087	Ocean depth/land elevation	
	0 10 092	Solid Earth tide height	
	0 10 088	Total geocentric ocean tide height (solution 1)	
	0 10 089	Total geocentric ocean tide height (solution 2)	
	0 10 098	Loading tide height geocentric ocean tide solution 1	
	0 10 099	Loading tide height geocentric ocean tide solution 2	
	0 10 090	Long period tide height	
	0 10 100	Non-equilibrium long period tide height	
	0 10 093	Geocentric pole tide height	
	0 25 127	Inverted barometer correction	
	0 40 014	High-frequency fluctuations of the sea-surface topography correction	
	0 10 102	Sea-surface height anomaly	
		(GPM Microwave Imager (GMI))	
3 40 012	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 08 091	Coordinates significance	= 0 Satellite coordinates
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 07 002	Height or altitude	
	0 05 063	Spacecraft roll	
	0 05 064	Spacecraft pitch	
	0 05 066	Spacecraft yaw	
	0 05 041	Scan line number	
	0 05 067	Number of scan lines	
	3 01 011	Year, moth, day	
	3 01 012	Hour, minute	
	0 04 007	Seconds within a minute (microsecond accuracy)	
	0 08 091	Coordinates significance	= 1 Observation coordinates
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	1 07 000	Delayed replication of 7 descriptors	
	0 31 001	Delayed descriptor replication factor	
	0 05 042	Channel number	
	0 02 153	Satellite channel centre frequency	
	0 02 104	Antenna polarization	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 012 (continued)	0 40 028	GMI quality flag	
	0 07 024	Satellite zenith angle	
	0 40 027	Sun glint angle	
	0 12 063	Brightness temperature	
3 40 013		(Atmospheric Laser Doppler Instrument (ALADIN) L2b data)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub- centre	
	0 04 001	Year	
	0 04 002	Month	
	0 04 003	Day	
	0 04 004	Hour	
	0 04 005	Minute	
	0 04 007	Seconds within a minute (microsecond accuracy)	
	0 05 068	Profile number	
	0 05 070	Observation identifier	
	0 05 069	Receiver channel	
	0 40 036	Lidar L2b classification type	
	0 08 091	Coordinates significance	= 2 Start of observation
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 04 016	Time increment	
	0 08 091	Coordinates significance	= 3 End of observation
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 04 016	Time increment	
	0 08 091	Coordinates significance	= 4 Horizontal centre of gravity of observation
	0 05 001	Latitude (high accuracy)	
	0 06 001	Longitude (high accuracy)	
	0 04 016	Time increment	
	0 08 091	Coordinates significance	= 6 Top of observation
	0 07 071	Height (high resolution)	
	0 05 021	Bearing or azimuth	
	0 07 021	Elevation	
	0 40 035	Satellite range	
	0 08 091	Coordinates significance	= 7 Bottom of observation
	0 07 071	Height (high resolution)	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 013 (continued)	0 05 021	Bearing or azimuth	= 5 Vertical centre of gravity of observation
	0 07 021	Elevation	
	0 40 035	Satellite range	
	0 08 091	Coordinates significance	
	0 07 071	Height (high resolution)	
	0 05 021	Bearing or azimuth	
	0 07 021	Elevation	
	0 40 035	Satellite range	
	0 40 029	Horizontal observation integration length	
	0 40 030	Horizontal line of sight wind	
	0 40 031	Error estimate of horizontal line of sight wind	
	0 25 187	Confidence flag	
	0 10 004	Pressure	
	0 12 001	Temperature/air temperature	
	0 40 037	Backscatter ratio	
	0 40 032	Derivative wind to pressure	
	0 40 033	Derivative wind to temperature	
	0 40 034	Derivative wind to backscatter ratio	
3 40 015		(Global Precipitation Measurement (GPM) precipitation data)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	3 01 011	Year, month, day	
	3 01 012	Hour, minute	
	0 04 007	Seconds within a minute (microsecond accuracy)	
	2 01 133	Change data width	Increase bit width
	0 05 041	Scan line number	
	2 01 000	Change data width	Cancel increase bit width
	2 01 130	Change data width	Increase bit width
	0 05 043	Field of view number	
	2 01 000	Change data width	Cancel increase bit width
	2 07 001	Increase scale, reference value and data width	
	0 05 002	Latitude (coarse accuracy)	
	0 06 002	Longitude (coarse accuracy)	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 40 027	Sun glint angle	
	0 13 040	Surface flag	
	0 21 120	Probability of rain	
	2 07 003	Increase scale, reference value and data width	
	1 02 003	Replicate 2 descriptors 3 times	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 015 (continued)	0 02 186	Capability to detect precipitation phenomena Set bit 1 = unknown/unspecified (total precipitation) in the first replication, Set bit 6 = solid precipitation in the second replication, Set bit 24 = convective precipitation in the third replication	/see left column
	0 13 155	Intensity of precipitation (high accuracy)	
	2 07 000	Increase scale, reference value and data width	Cancel
	0 33 003	Quality information	
3 40 016		(Principal component scores, channel selection and enhanced data collected on board a geostationary platform)	
	3 01 129	Observing satellite and instruments	
	3 01 130	High precision timestamp	
	3 01 131	Pixel geolocation	
	2 02 134	Change scale	Add 6 to scale
	0 07 001	Height of station	
	2 02 000	Change scale	Cancel
	1 01 000	Delayed replicator of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 40 002	Band description	
	1 01 000	Delayed replication of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 04 039	Radiance in channel	
	1 01 000	Delayed replicator of 1 descriptor	
	0 31 002	Extended delayed descriptor replication factor	
	3 04 040	Principal component score in band	
3 40 017		(Sentinel-3 (S3) Level 2 Water Product)	
	0 01 007	Satellite identifier	= 61 Sentinel 3A or = 65 Sentinel 3B 178 (SRAL)
	0 02 019	Satellite instruments	
	0 05 044	Satellite cycle number	
	0 01 096	Station acquisition	
	0 05 040	Orbit number	
	0 01 040	Processing centre ID code	
	0 25 061	Software identification and version number	
	0 25 182	L1 processing flag	
	0 25 183	L1 processing quality	
	0 25 181	L2 processing flag	
	0 25 184	L2 product status	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	0 04 007	Seconds within a minute (microsecond accuracy)	
	3 01 021	Latitude/longitude (high accuracy)	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 017 (continued)	0 05 063	Spacecraft roll	
	0 05 064	Spacecraft pitch	
	0 05 066	Spacecraft yaw	
	0 10 081	Altitude of COG above reference ellipsoid	
	0 10 082	Instantaneous altitude rate	
	0 08 075	Ascending/descending orbit qualifier	
	0 25 090	Orbit state flag	
	0 08 029	Surface type	
	2 01 137	Change data width	Increase data width by 9 bits
	2 02 129	Change scale	Add 1 to scale
	0 06 021	Distance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 10 087	Ocean depth/land elevation	
	0 25 096	Radiometer state flag	
	0 40 012	Radiometer data quality flag	
	0 08 077	Radiometer sensed surface type	
	1 04 002	Replicate 4 descriptors 2 times	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 12 065	Standard deviation brightness temperature	
	0 40 013	Radiometer brightness temperature interpretation flag	
	0 07 002	Height or altitude	
	0 11 098	Wind speed from radiometer	
	0 13 090	Radiometer water vapour content	
	0 13 091	Radiometer liquid content	
	0 25 164	Radiometer wet tropospheric correction	
	0 25 095	Altimeter state flag	
	0 40 023	Auxiliary altimeter state flags	
	0 25 113	Band specific altimeter correction quality flag	
	0 08 074	Altimeter echo type	
	0 25 190	Altimeter echo processing mode	
	0 21 144	Altimeter rain flag	
	0 25 191	Altimeter tracking mode	
	0 21 143	Ku band rain attenuation	
	0 13 055	Intensity of precipitation	
	0 21 169	Ice presence indicator	
	0 10 101	Squared off-nadir angle of the satellite from waveform data	
	0 15 012	Total electron count per square metre	
	0 07 002	Height or altitude	
	0 11 097	Wind speed from altimeter	
	0 40 024	Meteorological map availability	
	0 07 002	Height or altitude	
	0 25 126	Model dry tropospheric correction	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 017 (continued)	0 25 128	Model wet tropospheric correction	
	0 40 011	Interpolation flag	
	0 07 002	Height or altitude	
	0 11 095	u-component of the model wind vector	
	0 11 096	v-component of the model wind vector	
	0 10 088	Total geocentric ocean tide height (solution 1)	
	0 10 089	Total geocentric ocean tide height (solution 2)	
	0 10 090	Long period tide height	
	0 10 092	Solid Earth tide height	
	0 10 093	Geocentric pole tide height	
	0 10 098	Loading tide height geocentric ocean tide solution 1	
	0 10 099	Loading tide height geocentric ocean tide solution 2	
	0 10 100	Non-equilibrium long period tide height	
	0 25 127	Inverted barometer correction	
	0 40 014	High-frequency fluctuations of the sea-surface topography correction	
	0 10 085	Mean sea-surface height	
	0 10 086	Geoid's height	
	0 10 096	Mean dynamic topography	
	0 10 103	Mean dynamic topography accuracy	
	0 10 102	Sea-surface height anomaly	
	0 22 080	Waveband central frequency	
	0 08 076	Type of band	
	0 22 189	Specific band ocean range	
	0 22 191	RMS of specific band ocean range	
	0 22 130	Number of valid points for specific band	
	0 25 165	Ionospheric correction from model on specific band	
	0 25 166	Sea state bias correction on specific band	
	0 25 167	Specific band net instrumental correction	
	0 21 183	Specific band corrected ocean backscatter coefficient	
	0 21 184	STD specific band corrected ocean backscatter coefficient	
	0 22 134	Number of valid points for specific band backscatter	
	0 21 122	Attenuation correction on sigma-0 (from tB)	
	0 22 190	Specific band significant wave height	
	0 22 131	RMS specific band significant wave height	
	0 22 132	Number of valid points for specific band significant wave height	
	0 22 133	Specific band net instrument correction for significant wave height	
	0 21 186	Specific band automatic gain control	
	0 21 187	RMS specific band automatic gain control	
	0 21 188	Number of valid points for specific band automatic gain control	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 017 (continued)	0 21 185	Specific band net instrumental correction for AGC	
	0 25 112	Band specific altimeter data quality flag	
	0 25 113	Band specific altimeter correction quality flag	
	0 33 092	Band specific ocean quality flag	
	0 08 076	Type of band	
	0 22 189	Specific band ocean range	
	0 22 191	RMS of specific band ocean range	
	0 22 130	Number of valid points for specific band	
	0 25 165	Ionospheric correction from model on specific band	
	0 25 166	Sea state bias correction on specific band	
	0 25 167	Specific band net instrumental correction	
	0 21 183	Specific band corrected ocean backscatter coefficient	
	0 21 184	STD specific band corrected ocean backscatter coefficient	
	0 22 134	Number of valid points for specific band backscatter	
	0 21 122	Attenuation correction on sigma-0 (from tB)	
	0 22 190	Specific band significant wave height	
	0 22 131	RMS specific band significant wave height	
	0 22 132	Number of valid points for specific band significant wave height	
	0 22 133	Specific band net instrument correction for significant wave height	
	0 21 186	Specific band automatic gain control	
	0 21 187	RMS specific band automatic gain control	
	0 21 188	Number of valid points for specific band automatic gain control	
	0 21 185	Specific band net instrumental correction for AGC	
	0 25 112	Band specific altimeter data quality flag	
	0 25 113	Band specific altimeter correction quality flag	
	0 33 092	Band specific ocean quality flag	
	0 25 190	Altimeter echo processing mode	
	0 11 097	Wind speed from altimeter	
	0 13 090	Radiometer water vapour content	
	0 13 091	Radiometer liquid content	
	0 21 143	Ku band rain attenuation	
	0 21 184	STD specific band corrected ocean backscatter coefficient	
	0 25 128	Model wet tropospheric correction	
	0 25 163	Altimeter ionospheric correction on Ku band	
	0 25 164	Radiometer wet tropospheric correction	
	0 10 102	Sea-surface height anomaly	
	0 22 189	Specific band ocean range	
	0 22 191	RMS of specific band ocean range	
	0 22 130	Number of valid points for specific band	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 017 (continued)	0 25 166	Sea state bias correction on specific band	
	0 21 183	Specific band corrected ocean backscatter coefficient	
	0 21 184	STD specific band corrected ocean backscatter coefficient	
	0 22 134	Number of valid points for specific band backscatter	
	0 22 190	Specific band significant wave height	
	0 22 131	RMS specific band significant wave height	
	0 22 132	Number of valid points for specific band significant wave height	
	0 25 112	Band specific altimeter data quality flag	
	0 25 113	Band specific altimeter correction quality flag	
	0 33 092	Band specific ocean quality flag	
	0 08 049	Number of observations	
	0 22 080	Waveband central frequency	
	1 34 021	Replicate 34 descriptors 21 times	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	0 04 007	Seconds within a minute (microsecond accuracy)	
	3 01 021	Latitude/longitude (high accuracy)	
	0 10 081	Altitude of COG above reference ellipsoid	
	0 10 082	Instantaneous altitude rate	
	0 08 029	Surface type	
	2 01 137	Change data width	Add 9 bits to data width
	2 02 129	Change scale	Add 1 to scale
	0 06 021	Distance	
	2 02 000	Change scale	Cancel
	2 01 000	Change data width	Cancel
	0 25 191	Altimeter tracking mode	
	0 21 071	Peakiness	
	0 10 085	Mean sea-surface height	
	0 40 011	Interpolation flag	
	0 10 102	Sea-surface height anomaly	
	0 22 189	Specific band ocean range	
	0 22 146	OCOG range	
	0 25 165	Ionospheric correction from model on specific band	
	0 25 167	Specific band net instrumental correction	
	0 21 183	Specific band corrected ocean backscatter coefficient	
	0 22 190	Specific band significant wave height	
	0 22 133	Specific band net instrument correction for significant wave height	
	0 21 177	Corrected OCOG backscatter coefficient	
	0 21 185	Specific band net instrumental correction for AGC	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 017 (continued)	0 13 164	Sea-ice freeboard	Subtract 2 bits from scale
	2 02 126	Change scale	
	0 22 046	Sea-ice fraction	Cancel
	2 02 000	Change scale	
	0 13 117	Snow density (liquid water content)	
	0 13 013	Total snow depth	
	0 25 112	Band specific altimeter data quality flag	
	0 33 092	Band specific ocean quality flag	
3 40 018		(Infrared Fourier spectrometer – 2 (IKFS-2) spectra)	Repeat for all channels
	3 01 129	Observing satellite and instruments	
	3 01 130	High precision timestamp	
	3 01 131	Pixel geolocation	
	0 07 072	Scan angle	
	0 40 074	General interferometry quality flags	
	1 04 000	Delayed repetition of 1 descriptor	
	0 31 002	Delayed descriptor replication factor	
	2 01 136	Change data width	
	0 05 042	Channel number	
	2 01 000	Change data width	
	0 14 044	Change radiance	
3 40 019		(Altimeter product)	
	3 40 020	Satellite general values	
	3 40 021	General radiometer values	
	3 40 022	Altimeter model values	
3 40 020	3 40 023	Altimeter main values	
		(Satellite general values)	
	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 05 044	Satellite cycle number	
	0 01 096	Station acquisition	
	0 05 040	Orbit number	
	0 01 040	Processing centre ID code	
	0 25 061	Software identification and version number	
	0 25 182	L1 processing flag	
	0 25 183	L1 processing quality	
	0 25 181	L2 processing flag	
	0 25 184	L2 product status	
	0 08 075	Ascending/descending orbit qualifier	
	0 25 090	Orbit state flag	
	3 01 011	Date	
	3 01 013	Time	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 020 (continued)	0 04 007	Seconds within a minute (microsecond accuracy)	
	3 01 021	Latitude and longitude (high resolution)	
	0 05 063	Spacecraft roll	
	0 05 064	Spacecraft pitch	
	0 05 066	Spacecraft yaw	
	0 10 081	Altitude of cog above reference ellipsoid	
	0 10 082	Instantaneous altitude rate	
3 40 021		(General radiometer values)	
	0 40 012	Radiometer data quality flag	
	0 08 077	Radiometer sensed surface type	
	1 04 000	Delayed replication	
	0 31 001	Delayed descriptor replication factor	
	0 02 153	Satellite channel centre frequency	
	0 12 063	Brightness temperature	
	0 12 065	Standard deviation brightness temperature	
	0 40 013	Radiometer brightness temperature interpretation flag	
	0 07 002	Height or altitude	
	0 11 098	Wind speed from radiometer	
		(Altimeter model values)	
3 40 022	0 08 029	Surface type	
	2 01 137	Change data width	
	2 02 129	Change data scale	
	0 06 021	Distance	
	2 02 000	Reset scale	
	2 01 000	Reset width	
	0 10 087	Ocean depth/land elevation	
	0 40 024	Meteorological map availability	
	0 07 002	Height or altitude	
	0 25 126	Model dry tropospheric correction	
	0 25 128	Model wet tropospheric correction	
	0 40 011	Interpolation flag	
	0 07 002	Height or altitude	
	0 11 095	U-component of the model wind vector	
	0 11 096	V-component of the model wind vector	
	0 10 088	Total geocentric ocean tide height (solution 1)	
	0 10 089	Total geocentric ocean tide height (solution 2)	
	0 10 090	Long period tide height	
	0 10 092	Solid Earth tide height	
	0 10 093	Geocentric pole tide height	
	0 10 098	Loading tide height geocentric ocean tide solution 1	
	0 10 099	Loading tide height geocentric ocean tide solution 2	
	010 100	Non-equilibrium long period tide height	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 022 (continued)	0 25 127	Inverted barometer correction	
	0 40 014	High-frequency fluctuations of the sea-surface topography correction	
	0 01 030	Numerical model identifier	
	0 10 085	Mean sea-surface height	
	0 01 030	Numerical model identifier	
	0 10 085	Mean sea-surface height	
	0 10 086	Geoid's height	
	0 10 096	Mean dynamic topography	
	0 10 103	Mean dynamic topography accuracy	
	0 21 169	Ice presence indicator	
	0 13 055	Intensity of precipitation	
	0 25 165	Ionospheric correction from model on specific band	
		(Altimeter main values)	
3 40 023	0 25 095	Altimeter state flag	
	0 40 023	Auxiliary altimeter state flags	
	0 08 074	Altimeter echo type	
	3 40 024	1 Hz C and Ku band values	
	3 40 024	1 Hz C and Ku band values	
	3 40 024	1 Hz C and Ku band values	
	3 40 025	20 Hz C and Ku band values	
3 40 024		(1 Hz C and Ku band values)	
	0 22 080	Waveband central frequency	
	0 08 076	Type of band	
	0 25 190	Altimeter echo processing mode	
	0 10 102	Sea-surface height anomaly	
	0 22 189	Specific band ocean range	
	0 22 191	RMS of specific band ocean range	
	0 22 130	Number of valid points for specific band	
	0 25 167	Specific band net instrumental correction	
	0 25 163	Altimeter ionospheric correction on Ku band	
	0 15 012	Total electron count per square metre	
	0 25 164	Radiometer wet tropospheric correction	
	0 13 090	Radiometer water vapour content	
	0 13 091	Radiometer liquid content	
	0 25 166	Sea state bias correction on specific band	
	0 07 002	Height or altitude	
	0 11 097	Wind speed from altimeter	
	0 21 183	Specific band corrected ocean backscatter coefficient	
	0 21 184	STD specific band corrected ocean backscatter coefficient	
	0 22 134	Number of valid points for specific band backscatter	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 024 (continued)	0 21 122	Attenuation correction on sigma-0 (from tB)	
	0 21 186	Specific band automatic gain control	
	0 21 187	RMS specific band automatic gain control	
	0 21 188	Number of valid points for specific band automatic gain control	
	2 01 131	Change data width	
	0 21 185	Specific band net instrumental correction for AGC	
	2 01 000	Reset width	
	0 22 179	Specific band significant wave height	
	0 22 131	RMS specific band significant wave height	
	0 22 132	Number of valid points for specific band significant wave height	
	0 22 133	Specific band net instrument correction for significant wave height	
	0 21 144	Altimeter rain flag	
	0 25 191	Altimeter tracking mode	
	0 21 143	Ku band rain attenuation	
	0 10 101	Squared off-nadir angle of the satellite from waveform data	
	0 25 112	Band-specific altimeter data quality flag	
	0 25 113	Band-specific altimeter correction quality flag	
	0 33 092	Band-specific ocean quality flag	
		(20 Hz C and Ku band values)	
	0 08 049	Number of observations	
3 40 025	0 22 080	Waveband central frequency	
	0 08 076	Type of band	
	0 25 190	Altimeter echo processing mode	
	1 46 021	Replication	
	3 01 011	Date	
	3 01 013	Time	
	0 04 007	Seconds within a minute (microsecond accuracy)	
	3 01 021	Latitude and longitude (high resolution)	
	0 10 081	Altitude of cog above reference ellipsoid	
	0 10 082	Instantaneous altitude rate	
	0 08 029	Surface type	
	2 01 137	Change data width	
	2 02 129	Change data scale	
	0 06 021	Distance	
	2 02 000	Reset scale	
	2 01 000	Reset width	
	0 25 191	Altimeter tracking mode	
	0 21 071	Peakiness	
	0 01 030	Numerical model identifier	
	0 10 085	Mean sea-surface height	
	0 01 030	Numerical model identifier	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 025 (continued)	0 10 085	Mean sea-surface height	
	0 40 011	Interpolation flag	
	0 10 088	Total geocentric ocean tide height (solution 1)	
	0 10 089	Total geocentric ocean tide height (solution 2)	
	0 25 164	Radiometer wet tropospheric correction	
	0 07 002	Height or altitude	
	0 25 126	Model dry tropospheric correction	
	0 25 128	Model wet tropospheric correction	
	0 10 102	Sea-surface height anomaly	
	0 22 189	Specific band ocean range	
	0 25 167	Specific band net instrumental correction	
	0 25 163	Altimeter ionospheric correction on Ku band	
	0 21 183	Specific band corrected ocean backscatter coefficient	
	2 01 131	Change data width	
	0 21 185	Specific band net instrumental correction for AGC	
	2 01 000	Reset width	
	0 22 179	Specific band significant wave height	
	0 22 133	Specific band net instrument correction for significant wave height	
	0 22 146	OCOG range	
	0 21 189	Corrected OCOG backscatter coefficient	
	0 13 163	Snow water equivalent	
	2 02 126	Change data scale	
	0 22 046	Sea-ice fraction	
	2 02 000	Reset scale	
	0 13 117	Snow density (liquid water content)	
	0 13 013	Total snow depth	
	0 25 112	Band-specific altimeter data quality flag	
	0 25 113	Band-specific altimeter correction quality flag	
	0 33 092	Band-specific ocean quality flag	
		(Lidar observations from satellite)	
3 40 026	0 01 007	Satellite identifier	
	0 02 019	Satellite instruments	
	0 01 033	Identification of originating/generating centre	
	0 01 034	Identification of originating/generating sub-centre	
	3 01 011	Year, month, day	
	3 01 013	Hour, minute, second	
	3 01 021	Latitude/longitude (high accuracy)	
	0 10 033	Altitude (platform to ellipsoid)	
	0 08 043	Atmospheric chemical or physical constituent type	
	0 25 139	Processing level	
	0 02 155	Satellite channel wavelength	
	1 12 000	Delayed replication of 12 descriptors	

FM 94 BUFR

Category 40			
TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
F X Y			
3 40 026 (continued)	0 31 002	Extended delayed descriptor replication factor	Cancel
	0 07 071	Height (high resolution)	
	0 33 003	Quality information	
	2 01 136	Change data width	
	0 15 074	Particle backscatter coefficient	
	0 15 066	Uncertainty in particle backscatter coefficient	
	0 15 075	Particle extinction coefficient	
	0 15 068	Uncertainty in particle extinction coefficient	
	2 01 000	Change data width	
	0 15 076	Particle lidar ratio	
	0 15 070	Uncertainty in lidar ratio	
	0 15 078	Particle depolarization ratio	
	0 15 072	Uncertainty in depolarization ratio	
	1 07 003	Delayed replication of 7 descriptors	
	0 05 069	Receiver channel	
	1 04 000	Delayed replication of 4 descriptors	
	0 31 002	Extended delayed descriptor replication factor	
	2 01 135	Change data width	
	0 15 073	Attenuated backscatter	
	0 15 064	Uncertainty in attenuated backscatter	
	2 01 000	Change data width	Cancel

Note: Descriptor 3 40 010 should be used in preference to 3 40 005.

CODE TABLES AND FLAG TABLES ASSOCIATED WITH BUFR/CREX TABLE B

Note: In developing code tables associated with BUFR/CREX Table B to specify units of elements, the following principles should be applied:

- (a) Code tables specifying the units for an element which is defined, in the *Manual on Codes*, by a single symbolic letter shall be compatible with the relevant existing WMO code tables;
- (b) Code tables combining two or more existing WMO code tables to specify the units for an element which is defined, in the *Manual on Codes*, by a group of symbolic letters shall be compatible with the combined code figures of the relevant group of symbolic letters;
- (c) Code tables combining two or more existing WMO code tables to specify the units for an element which is defined, in the *Manual on Codes*, by different symbolic letters shall be compatible with the code figures of the relevant symbolic letters, with successive tens or hundreds values added, as appropriate;
- (d) Code tables and flag tables should only be used for reporting qualitative information. Quantitative information should be reported as observed using entries in Table B. "Data description operators" from Table C should be applied when a "scale change" or "data width change" is required;
- (e) Reference to existing specification(s) and code table(s) in the *Manual on Codes*, with explanation of possible deviations, shall be given in an additional table annexed to the code tables associated with BUFR/CREX Table B.

0 01 003**WMO Region number/geographical area***Code table 0 01 003*

Code figure	
0	Antarctica
1	Region I
2	Region II
3	Region III
4	Region IV
5	Region V
6	Region VI
7	Missing value

0 01 007**Satellite identifier***(See Common Code table C-5 Part C/c.)***0 01 024****Wind speed source***Code table 0 01 024*

Code figure	
0	No wind speed data available
1	AMSR-E data
2	TMI data
3	NWP: ECMWF
4	NWP: UK Met Office
5	NWP: NCEP
6	Reference climatology
7	ERS_scatterometer
8-30	Reserved for future use
31	Missing value

01 028***Aerosol optical depth (AOD) source****Code table 0 01 028*

Code figure	
0	No AOD data available
1	NESDIS
2	NAVOCEANO
3	NAAPS
4	MERIS
5	AATSR
6–30	Reserved for future use
31	Missing value

0 01 029***SSI source****Code table 0 01 029*

Code figure	
0	No SSI data available
1	MSG_SEVIRI
2	GOES East
3	GOES West
4	ECMWF
5	NCEP
6	UK Met Office
7–30	Reserved for future use
31	Missing value

0 01 031***Identification of originating/generating centre****(See Common Code table C–1 in Part C/c.)***0 01 033*****Identification of originating/generating centre****(See Common Code table C–1 in Part C/c.)***0 01 034*****Identification of originating/generating sub-centre****(To be defined by centres themselves – See Common Code table C–12 in Part C/c.)*

0 01 035***Originating/generating centre****(See Common Code table C-11 in Part C/c.)***0 01 036*****Agency in charge of operating the observing platform****(The first three digits represent the ISO country code)**Code table 0 01 036*

Code figure	
0–36000	Reserved
36001	Australia, Bureau of Meteorology (BoM)
36002	Australia, Joint Australian Facility for Ocean Observing Systems (JAFOOS)
36003	Australia, the Commonwealth Scientific and Industrial Research Organization (CSIRO)
36004–124000	Reserved
124001	Canada, Marine Environmental Data Service (MEDS)
124002	Canada, Institute of Ocean Sciences (IOS)
124003–124172	Reserved
124173	Canada, Environment Canada
124174	Canada, Department of National Defence
124175	Canada, Nav Canada
124176–156000	Reserved
156001	China, The State Oceanic Administration
156002	China, Second Institute of Oceanography, State Oceanic Administration
156003	China, Institute of Ocean Technology
156004–250000	Reserved
250001	France, Institut de Recherche pour le Développement (IRD)
250002	France, Institut Français de Recherche pour l'Exploitation de la mer (IFREMER)
250003–276000	Reserved
276001	Germany, Bundesamt fuer Seeschifffahrt und Hydrographie (BSH)
276002	Germany, Institut fuer Meereskunde, Kiel
276003–356000	Reserved
356001	India, National Institute of Oceanography (NIO)
356002	India, National Institute for Ocean Technology (NIOT)
356003	India, National Centre for Ocean Information Service
356004–392000	Reserved
392001	Japan, Japan Meteorological Agency (JMA)
392002	Japan, Frontier Observational Research System for Global Change
392003	Japan, Japan Marine Science and Technology Centre (JAMSTEC)
392004–410000	Reserved
410001	Republic of Korea, Seoul National University
410002	Republic of Korea, Korea Ocean Research and Development Institute (KORDI)
410003	Republic of Korea, Meteorological Research Institute
410004–540000	Reserved
540001	New Caledonia, Institut de Recherche pour le Développement (IRD)
540002–554000	Reserved
554001	New Zealand, National Institute of Water and Atmospheric Research (NIWA)

FM 94 BUFR

Code table 0 01 036

Code figure	
554002–643000	Reserved
643001	Russian Federation, State Oceanographic Institute of Roshydromet
643002	Russian Federation, Federal Service for Hydrometeorology and Environmental Monitoring
643003–724000	Reserved
724001	Spain, Instituto Español de Oceanografía
724002–826000	Reserved
826001	United Kingdom, Hydrographic Office
826002	United Kingdom, National Oceanography Centre (NOC)
826003	United Kingdom, Centre for Environment, Fisheries and Aquaculture Science (Cefas)
826004	United Kingdom, Marine Scotland (MS)
826005	United Kingdom, Plymouth Marine Laboratory (PML)
826006	United Kingdom, British Antarctic Survey (BAS)
826007–840000	Reserved
840001	USA, NOAA Atlantic Oceanographic and Meteorological Laboratory (AOML)
840002	USA, NOAA Pacific Marine Environmental Laboratory (PMEL)
840003	USA, Scripps Institution of Oceanography (SIO)
840004	USA, Woods Hole Oceanographic Institution (WHOI)
840005	USA, University of Washington
840006	USA, Naval Oceanographic Office
840007–1048574	Reserved
1048575	Missing value

0 01 038

Source of sea-ice fraction

Code table 0 01 038

Code figure	
0	No sea-ice set
1	NSIDC SSM/I Cavalieri et al (1992)
2	AMSR-E
3	ECMWF
4	CMS (France) cloud mask used by Medspiration
5	EUMETSAT OSI-SAF
6–30	Reserved for future use
31	Missing value

0 01 044***Standard generating application****Code table 0 01 044*

Code figure	
0	Reserved
1	Full weighted mixture of individual quality tests
2	Weighted mixture of individual tests, but excluding forecast comparison
3	Recursive filter function
4	Common quality index (QI) without forecast
5	QI without forecast
6	QI with forecast
7	Estimated error in m/s converted to a percent confidence
8–254	Reserved
255	Missing value

0 01 052***Platform transmitter ID****Code table 0 01 052*

Code figure	
0	Primary
1	Secondary
2	Reserved
3	Missing value

0 01 090***Technique for making up initial perturbations****Code table 0 01 090*

Code figure	
0	Lagged-average forecasting (LAF)
1	Breeding
2	Singular vectors
3	Multiple analysis cycles
4–191	Reserved
192–254	Reserved for local use
255	Missing value

0 01 092***Type of ensemble forecast****Code table 0 01 092*

Code figure	
0	Unperturbed high-resolution control forecast
1	Unperturbed low-resolution control forecast
2	Negatively perturbed forecast
3	Positively perturbed forecast
4	Perturbed forecast
5–191	Reserved
192–254	Reserved for local use
255	Missing value

0 01 101***State identifier****Code table 0 01 101*

Code figure	
0–99	Reserved
100	Algeria
101	Angola
102	Benin
103	Botswana
104	Burkina Faso
105	Burundi
106	Cameroon
107	Cabo Verde
108	Central African Republic
109	Chad
110	Comoros
111	Congo
112	Côte d'Ivoire
113	Democratic Republic of the Congo
114	Djibouti
115	Egypt
116	Eritrea
117	Ethiopia
118	France (RA I)
119	Gabon
120	Gambia
121	Ghana
122	Guinea
123	Guinea-Bissau
124	Kenya
125	Lesotho
126	Liberia
127	Libya

Code table 0 01 101

Code figure	
128	Madagascar
129	Malawi
130	Mali
131	Mauritania
132	Mauritius
133	Morocco
134	Mozambique
135	Namibia
136	Niger
137	Nigeria
138	Portugal (RA I)
139	Rwanda
140	Sao Tome and Principe
141	Senegal
142	Seychelles
143	Sierra Leone
144	Somalia
145	South Africa
146	Spain (RA I)
147	Sudan
148	Eswatini
149	Togo
150	Tunisia
151	Uganda
152	United Kingdom of Great Britain and Northern Ireland (RA I)
153	United Republic of Tanzania
154	Zambia
155	Zimbabwe
156–199	Reserved for Region I (Africa)
200	Afghanistan
201	Bahrain
202	Bangladesh
203	Bhutan
204	Cambodia
205	China
206	Democratic People's Republic of Korea
207	Hong Kong, China
208	India
209	Iran, Islamic Republic of
210	Iraq
211	Japan
212	Kazakhstan
213	Kuwait
214	Kyrgyzstan
215	Lao People's Democratic Republic
216	Macao, China
217	Maldives

Code table 0 01 101

Code figure	
218	Mongolia
219	Myanmar
220	Nepal
221	Oman
222	Pakistan
223	Qatar
224	Republic of Korea
225	Yemen
226	Russian Federation (RA II)
227	Saudi Arabia
228	Sri Lanka
229	Tajikistan
230	Thailand
231	Turkmenistan
232	United Arab Emirates
233	Uzbekistan
234	Viet Nam
235–299	Reserved for Region II (Asia)
300	Argentina
301	Bolivia (Plurinational State of)
302	Brazil
303	Chile
304	Colombia
305	Ecuador
306	France (RA III)
307	Guyana
308	Paraguay
309	Peru
310	Suriname
311	Uruguay
312	Venezuela (Bolivarian Republic of)
313–399	Reserved for Region III (South America)
400	Antigua and Barbuda
401	Bahamas
402	Barbados
403	Belize
404	British Caribbean Territories
405	Canada
406	Colombia
407	Costa Rica
408	Cuba
409	Dominica
410	Dominican Republic
411	El Salvador
412	France (RA IV)
413	Guatemala

Code table 0 01 101

Code figure	
414	Haiti
415	Honduras
416	Jamaica
417	Mexico
418	Curaçao and Sint Maarten
419	Nicaragua
420	Panama
421	Saint Lucia
422	Trinidad and Tobago
423	United Kingdom of Great Britain and Northern Ireland (RA IV)
424	United States of America (RA IV)
425	Venezuela (Bolivarian Republic of)
426–499	Reserved for Region IV (North America, Central America and the Caribbean)
500	Australia
501	Brunei Darussalam
502	Cook Islands
503	Fiji
504	French Polynesia
505	Indonesia
506	Kiribati
507	Malaysia
508	Micronesia, Federated States of
509	New Caledonia
510	New Zealand
511	Niue
512	Papua New Guinea
513	Philippines
514	Samoa
515	Singapore
516	Solomon Islands
517	Tonga
518	United Kingdom of Great Britain and Northern Ireland (RA V)
519	United States of America (RA V)
520	Vanuatu
521–599	Reserved for Region V (South-West Pacific)
600	Albania
601	Armenia
602	Austria
603	Azerbaijan
604	Belarus
605	Belgium
606	Bosnia and Herzegovina
607	Bulgaria
608	Croatia
609	Cyprus
610	Czechia

Code table 0 01 101

Code figure	
611	Denmark
612	Estonia
613	Finland
614	France (RA VI)
615	Georgia
616	Germany
617	Greece
618	Hungary
619	Iceland
620	Ireland
621	Israel
622	Italy
623	Jordan
624	Kazakhstan
625	Latvia
626	Lebanon
627	Lithuania
628	Luxembourg
629	Malta
630	Monaco
631	Montenegro
632	Netherlands
633	Norway
634	Poland
635	Portugal (RA VI)
636	Republic of Moldova
637	Romania
638	Russian Federation (RA VI)
639	Serbia
640	Slovakia
641	Slovenia
642	Spain (RA VI)
643	Sweden
644	Switzerland
645	Syrian Arab Republic
646	North Macedonia
647	Turkey <u>Republic of Turkiye</u>
648	Ukraine
649	United Kingdom of Great Britain and Northern Ireland (RA VI)
650–699	Reserved for Region VI (Europe)
700–999	Reserved
1000–1022	Not used
1023	Missing value

0 01 150***Coordinate reference system****Code table 0 01 150*

Code figure	
0	WGS84, as used by ICAO since 1998
1	ETRS89, as defined by EPSG:4258
2	NAD83, as defined by EPSG:4269
3	DHDN, as defined by EPSG:4314
4	Ellipsoidal datum using the International Reference Meridian and the International Reference Pole as the prime meridian and prime pole, respectively, and the origin of the International Terrestrial Reference System (ITRS) (see Note 2). The International Reference Meridian, International Reference Pole and ITRS are maintained by the International Earth Rotation and Reference Systems Service (IERS)
5	Earth-centred, Earth-fixed (ECEF) coordinate system or Earth-centred rotational (ECR) system. This is a right-handed Cartesian coordinate system (X, Y, Z) rotating with the Earth. The origin is defined by the centre of mass of the Earth. (Footnote (5) of class 27 does not apply if ECEF coordinates are specified.)
6-65534	Reserved
65535	Missing value

Notes:

- (1) EPSG is a dataset of coordinate system and coordinate system transformations, originally produced and maintained by the European Petroleum Survey Group. It is now maintained by the Geodesy Subcommittee of the International Association of Oil and Gas Producers Geomatics Committee.
- (2) When Code figure 4 is used to specify a custom coordinate reference system, the ellipsoidal datum shall be an oblate ellipsoid of revolution, where the major axis is uniplanar with the equatorial plane and the minor axis traverses the prime meridian towards the prime pole. North corresponds to the direction from the Equator to the prime pole. East corresponds to the counterclockwise direction from the prime meridian as viewed from above the North Pole. In this case, the semi-major and semi-minor axes must be specified (e.g. by descriptors 0 01 152 and 0 01 153).

0 01 151***Fixed mean sea-level reference datum****Code table 0 01 151*

Code figure	
0	Earth Gravitational Model 1996
1	Baltic height system 1977
2-4094	Reserved
4095	Missing value

0 01 155***Retrieval identifier***

Code table 0 01 155

Code figure

0	Standard Correct Algorithm <u>(SCA)</u>
<u>1</u>	<u>Standard Correct Algorithm mid-bin (SCA mid-bin)</u>
<u>2</u>	<u>Maximum Likelihood Estimation (MLE)</u>
<u>3</u>	<u>Optimal Estimation Profile (OE-PRO)</u>
<u>4</u>	<u>Group</u>
<u>5</u>	<u>Group mid-bin</u>
6 -254	Reserved
255	Missing value

Provisional Copy
2023

0 02 001***Type of station****Code table 0 02 001*

Code figure	
0	Automatic
1	Manned
2	Hybrid: both manned and automatic
3	Missing value

0 02 002***Type of instrumentation for wind measurement****Flag table 0 02 002*

Bit No.	Type of Instrumentation and original units for wind measurement (measured in m s ⁻¹ unless otherwise indicated)
1	Certified instruments
2	Originally measured in knots
3	Originally measured in km h ⁻¹
All 4	Missing value

0 02 003***Type of measuring equipment used****Code table 0 02 003*

Code figure	
0	Pressure instrument associated with wind measuring equipment
1	Optical theodolite
2	Radio theodolite
3	Radar
4	VLF-Omega
5	Loran C
6	Wind profiler
7	Satellite navigation
8	Radio-acoustic Sounding System (RASS)
9	Sodar
10	Lidar
11–13	Reserved
14	Pressure instrument associated with wind measuring equipment but pressure element failed during ascent
15	Missing value

0 02 004

Type of instrumentation for evaporation measurement or type of crop for which evapotranspiration is reported

Code table 0 02 004

Code figure	Instrumentation or crop type	Type of data
0	USA open pan evaporimeter (without cover)	Evaporation
1	USA open pan evaporimeter (mesh covered)	
2	GGI-3000 evaporimeter (sunken)	
3	20 m ² tank	
4	Others	
5	Rice	Evapotranspiration
6	Wheat	
7	Maize	
8	Sorghum	
9	Other crops	
10-14	Reserved	
15	Missing value	

0 02 006

Upper Air Remote Sensing Instrument Type

Code table 0 02 006

Code figure	
0	Reserved
1	Elastic backscatter lidar
2	Raman backscatter lidar
3	Radar wind profiler
4	Lidar wind profiler
5	Sodar wind profiler
6	Wind profiler
7	Lidar
8-62	Reserved
63	Missing value

0 02 007***Type of sensor for water level measuring instrument****Code table 0 02 007*

Code figure	
0	Reserved
1	Shaft encoder float system
2	Ultrasonic
3	Radar
4	Pressure (single transducer)
5	Pressure (multiple transducer)
6	Pressure (in stilling well)
7	Bubbler pressure
8	Acoustic (with sounding tube)
9	Acoustic (in open air)
10–62	Reserved
63	Missing value

0 02 008***Type of offshore platform****Code table 0 02 008*

Code figure	
0	Fixed platform
1	Mobile offshore drill ship
2	Jack-up rig
3	Semi-submersible platform
4	Floating production storage and offloading (FPSO) unit
5	Light vessel
6–14	Reserved
15	Missing value

0 02 011***Radiosonde type****(See Common Code table C-2 in Part C/c.)***0 02 012*****Radiosonde computational method****(To be developed)*

0 02 013***Solar and infrared radiation correction****Code table 0 02 013*

Code figure	
0	No correction
1	CIMO solar corrected and CIMO infrared corrected
2	CIMO solar corrected and infrared corrected
3	CIMO solar corrected only
4	Solar and infrared corrected automatically by radiosonde system
5	Solar corrected automatically by radiosonde system
6	Solar and infrared corrected as specified by country
7	Solar corrected as specified by country
8	Solar and infrared corrected as specified by GRUAN
9	Solar corrected as specified by GRUAN
10–14	Reserved
15	Missing value

0 02 014***Tracking technique/status of system used****(See Common Code table C-7 in Part C/c.)***0 02 015*****Radiosonde completeness****Code table 0 02 015*

Code figure	
0	Reserved
1	Pressure only radiosonde
2	Pressure only radiosonde plus transponder
3	Pressure only radiosonde plus radar reflector
4	No-pressure radiosonde plus transponder
5	No-pressure radiosonde plus radar reflector
6–14	Reserved
15	Missing value

0 02 016***Radiosonde configuration****Flag table 0 02 016*

Bit No.	
1	Train regulator
2	Light unit
3	Parachute
4	Rooftop release
All 5	Missing value

0 02 017***Correction algorithms for humidity measurements****Code table 0 02 017*

Code figure	
0	No corrections
1	Time lag correction provided by the manufacturer
2	Solar radiation correction provided by the manufacturer
3	Solar radiation and time lag correction provided by the manufacturer
4–6	Reserved
7	GRUAN solar radiation and time lag correction
8–30	Reserved
31	Missing value

0 02 019***Satellite instruments****(See Common Code table C-8 in Part C/c.)***0 02 020*****Satellite classification****Code table 0 02 020*

Code figure	
0	Nimbus
1	VTPR
2	Tiros 1 (Tiros, NOAA-6 to NOAA-13)
3	Tiros 2 (NOAA-14 onwards)
10	EOS
20	GPM-core
31	DMSP
61	EUMETSAT Polar System (EPS)
62	EUMETSAT Polar System (EPS-SG)
91	ERS
92	Sentinel-3
121	ADEOS
122	GCOM
241	GOES
<u>251</u>	<u>TROPICS</u>
261	JASON
271	GMS
272	MTSAT
273	Himawari
281	COMS
301	INSAT
331	METEOSAT Operational Programme (MOP)
332	METEOSAT Transitional Programme (MTP)
333	METEOSAT Second Generation Programme (MSG)

Code table 0 02 020

Code figure	
334	METEOSAT Third Generation Programme (MTG)
351	GOMS
352	Meteor-M N2
380	FY-1
381	FY-2
382	FY-3
383	FY-4
384–400	Reserved
401	GPS
402	GLONASS
403	GALILEO
404	BDS (BeiDou navigation satellite system)
405	Quasi-Zenith Satellite System (QZSS)
406–510	Reserved
511	Missing value

0 02 021***Satellite instrument data used in processing***

Flag table 0 02 021

Bit No.	
1	High-resolution infrared sounder (HIRS)
2	Microwave sounding unit (MSU)
3	Stratospheric sounding unit (SSU)
4	AMI (advanced microwave instrument) wind mode
5	AMI (advanced microwave instrument) wave mode
6	AMI (advanced microwave instrument) image mode
7	Radar altimeter
8	ATSR (along-track scanning radiometer)
All 9	Missing value

0 02 022***Satellite data-processing technique used***

Flag table 0 02 022

Bit No.	
1	Processing technique not defined
2	Automated statistical regression
3	Clear path (see Note 2)
4	Partly cloudy path (see Note 3)
5	Cloudy path (see Note 4)
6–7	Reserved
All 8	Missing value

Notes:

- (1) Bit flags denoting the elements included in processing sounding data.

- (2) Clear path means the sounding has been generated from clear radiances derived from actual clear spot measurements. Tropospheric and stratospheric HIRS data, as well as MSU and SSU data, have been used.
- (3) Partly cloudy path means the sounding has been generated from clear radiances which have been calculated from partly cloudy spots. Tropospheric and stratospheric HIRS data, as well as MSU and SSU data, have been used.
- (4) Cloudy path means the sounding has been generated only from stratospheric HIRS data, MSU data and SSU data. Tropospheric HIRS data have not been used because of cloudy conditions.

0 02 023***Satellite-derived wind computation method****Code table 0 02 023*

Code figure	
0	Reserved
1	Wind derived from cloud motion observed in the infrared channel
2	Wind derived from cloud motion observed in the visible channel
3	Wind derived from cloud motion observed in the water vapour channel
4	Wind derived from motion observed in a combination of spectral channels
5	Wind derived from motion observed in the water vapour channel in clear air
6	Wind derived from motion observed in the ozone channel
7	Wind derived from motion observed in water vapour channel (cloud or clear air not specified)
8–12	Reserved
13	Root-mean-square
14	Reserved
15	Missing value

0 02 024***Integrated mean humidity computational method****Code table 0 02 024*

Code figure	
0	Reserved
1	Table with full range of humidity variation in layer
2	Regression technique on 2 humidity values in layer
3–14	Reserved
15	Missing value

0 02 025***Satellite channel(s) used in computation****Flag table 0 02 025*

Bit No.	Instrument (channels)
1	Reserved <i>Group 1</i> – Layer precipitable water for the layers: surface to 700 hPa, 700 to 500 hPa, and 500 to 300 hPa
2	HIRS
3	MSU
4–5	Reserved <i>Group 2</i> – Tropopause temperature and pressure
6	HIRS
7	MSU
8–9	Reserved <i>Group 3</i> – Total ozone
10	HIRS (1, 2, 3, 8, 9, 16, 17)
11	HIRS (1, 2, 3, 9, 17)
12	MSU
13–14	Reserved <i>Group 4</i> – Mean temperature for the layers: surface to 850 hPa, 850 to 700 hPa, 700 to 500 hPa, 500 to 400 hPa, 400 to 300 hPa, 300 to 200 hPa, and 200 to 100 hPa
15	HIRS
16	HIRS* (see Note 2)
17	MSU
18	SKINTK (ocean only)
19–20	Reserved <i>Group 5</i> – Channel combinations used to obtain mean temperatures for the layers 100 to 70 hPa, 70 to 50 hPa, 50 to 30 hPa, 30 to 10 hPa, 10 to 5 hPa, 5 to 2 hPa, 2 to 1 hPa, 1 to 0.4 hPa
21	HIRS* (see Note 2)
22	SSU
23	MSU (3, 4)
24	Reserved
All 25	Missing value

Notes:

- (1) Bit flags denoting the instrument and/or channels used in obtaining various physical parameters. If, in any grouping of parameters, all bits = 0, then no retrieval was made for that parameter or set of parameters.
- (2) HIRS* is equivalent to:
HIRS channels
 - 1 (669 cm⁻¹)
 - 2 (679 cm⁻¹)
 - 3 (690 cm⁻¹)
 - 4 (2358 cm⁻¹)

0 02 030***Method of current measurement****Code table 0 02 030*

Code figure	
0	Reserved
1	ADCP (Acoustic Doppler Current Profiler) (see Note)
2	GEK (Geomagnetic ElectroKinetograph)
3	Ship's set and drift determined by fixes 3–6 hours apart
4	Ship's set and drift determined by fixes more than 6 hours but less than 12 hours apart
5	Drift of buoy
6	ADCP (Acoustic Doppler Current Profiler)
7	Missing value

Note: Code figure 1 is deprecated. Code figure 6 should be used instead.

0 02 031***Duration and time of current measurement****Code table 0 02 031*

Code figure	
0	Reserved
1	Instantaneous
2	Averaged over 3 min or less
3	Averaged over more than 3 min, but 6 min at the most
4	Averaged over more than 6 min, but 12 min at the most
5	Instantaneous
6	Averaged over 3 min or less
7	Averaged over more than 3 min, but 6 min at the most
8	Averaged over more than 6 min, but 12 min at the most
9	Vector or Doppler current profiling method not used
10	Reserved
11	1 hour or less
12	More than 1 hour but 2 hours at the most
13	More than 2 hours but 4 hours at the most
14	More than 4 hours but 8 hours at the most
15	More than 8 hours but 12 hours at the most
16	More than 12 hours but 18 hours at the most
17	More than 18 hours but 24 hours at the most
18	Reserved
19	Drift method not used
20–30	Reserved
31	Missing value

} between H – 1 and H

} between H – 2 and H – 1

Notes:

- (1) Code figures 1–9: Duration and time of current measurement (vector or Doppler current profiling method).
- (2) Code figures 11–19: Period of current measurement (drift method).
- (3) H = Time of observation.

0 02 032***Indicator for digitization****Code table 0 02 032*

Code figure	
0	Values at selected depths (data points fixed by the instrument or selected by any other method)
1	Values at selected depths (data points taken from traces at significant depths)
2	Reserved
3	Missing value

0 02 033***Method of salinity/depth measurement****Code table 0 02 033*

Code figure	
0	No salinity measured
1	In situ sensor, accuracy better than 0.02 ‰
2	In situ sensor, accuracy less than 0.02 ‰
3	Sample analysis
4–6	Reserved
7	Missing value

0 02 034***Drogue type****Code table 0 02 034*

Code figure	
0	Unspecified drogue
1	Holey sock
2	TRISTAR
3	Window shade
4	Parachute
5	Non-Lagrangian sea anchor
6–30	Reserved (to be developed)
31	Missing value

0 02 036***Buoy type****Code table 0 02 036*

Code figure	
0	Drifting buoy
1	Fixed buoy
2	Subsurface float (moving)
3	Missing value

0 02 037**Method of tidal observation***Code table 0 02 037*

Code figure	
0	Reserved
1	Manual reading from vertical tide staff
2	Manual reading from single automatic recorder at station
3	Manual reading from multiple automatic recorders at station
4	Automatic reading from single automatic recorder at station without level reference check
5	Automatic reading from single automatic recorder at station with level reference check, or from multiple automatic recorders
6	Reserved
7	Missing value

0 02 038**Method of water temperature and/or salinity measurement***Code table 0 02 038*

Code figure	
0	Ship intake
1	Bucket
2	Hull contact sensor
3	Reversing thermometer
4	STD/CTD sensor
5	Mechanical BT
6	Expendable BT
7	Digital BT
8	Thermistor chain
9	Infrared scanner
10	Microwave scanner
11	Infrared radiometer
12	In-line thermosalinograph
13	Towed body
14	Other
15	Missing value

0 02 039**Method of wet-bulb temperature measurement***Code table 0 02 039*

Code figure	
0	Measured wet-bulb temperature
1	Iced bulb measured wet-bulb temperature
2	Computed wet-bulb temperature
3	Iced bulb computed wet-bulb temperature
4–6	Reserved
7	Missing value

0 02 040***Method of removing velocity and motion of platform from current****Code table 0 02 040*

Code figure		
0	Ship's motion removed by averaging	} Ship's velocity removed by bottom tracking
1	Ship's motion removed by motion compensation	
2	Ship's motion not removed	
3	Ship's motion removed by averaging	} Ship's velocity removed by navigation
4	Ship's motion removed by motion compensation	
5	Ship's motion not removed	
6	Doppler current profiling method not used	
7–14	Reserved	
15	Missing value	

0 02 041***Method for estimating reports related to synoptic features****Code table 0 02 041*

Code figure	
0	Information based on manual analysis
1	Information based on computer analysis
2	Information based on data assimilation
3	Information based on computer analysis or data assimilation manually modified
4–9	Reserved
10	Information based on the numerical weather prediction
11–62	Reserved for future use
63	Missing value

0 02 042***Indicator for sea-surface current speed****Code table 0 02 042*

Code figure	
0	Value originally reported in m/s
1	Value originally reported in knots
2	No sea-current data available
3	Missing value

0 02 044***Indicator for method of calculating spectral wave data****Code table 0 02 044*

Code figure	
0	Reserved for future use
1	Longuet-Higgins (1964)
2	Longuet-Higgins (F3 method)
3	Maximum likelihood method
4	Maximum entropy method
5–14	Reserved
15	Missing value

0 02 045***Indicator for type of platform****Code table 0 02 045*

Code figure	
0	Sea station
1	Automatic data buoy
2	Aircraft
3	Satellite
4–14	Reserved
15	Missing value

0 02 046***Wave measurement instrumentation****Code table 0 02 046*

Code figure	
0	Reserved for future use
1	Heave sensor
2	Slope sensor
3–14	Reserved
15	Missing value

0 02 047***Deep-ocean tsunameter type****Code table 0 02 047*

Code figure	
0	Reserved
1	DART II (PMEL)
2	DART ETD
3	SAIC Tsunami Buoy (STB)
4	GFZ – Potsdam
5	INCOIS (India)
6	InaBuoy (Indonesia)
7	Envirtech
8–99	Reserved
100–126	Not used
127	Missing value

0 02 048***Satellite sensor indicator****Code table 0 02 048*

Code figure	
0	HIRS
1	MSU
2	SSU
3	AMSU-A
4	AMSU-B
5	AVHRR
6	SSMI
7	NSCAT
8	SEAWINDS
9	POSEIDON altimeter
10	JMR (JASON Microwave Radiometer)
11	MHS
12	ASCAT
13	OSCAT2
14	Reserved
15	Missing value

0 02 049***Geostationary satellite data-processing technique used****Flag table 0 02 049*

Bit No.	
1	Processing technique not defined
2	Simultaneous physical retrieval
3	Clear sounding (see Note 1)
4	Cloudy sounding (see Note 2)
5–7	Reserved for future use
All 8	Missing value

Notes:

- (1) Clear sounding indicates the sounding has been generated from a set of clear radiances using all available sounder radiances.
- (2) Cloudy sounding indicates that sufficient clear radiances could not be identified in the sounding area. The sounding is calculated from the cloud top (cloud pressure greater than or equal to 780 hPa) upwards.

0 02 050***Geostationary sounder satellite channels used****Flag table 0 02 050*

Bit No.	Channel	Central wavelength (micrometres)
1	1	14.71
2	2	14.37
3	3	14.06
4	4	13.64
5	5	13.37
6	6	12.66
7	7	12.02
8	8	11.03
9	9	9.71
10	10	7.43
11	11	7.02
12	12	6.51
13	13	4.57
14	14	4.52
15	15	4.45
16	16	4.13
17	17	3.98
18	18	3.74
19	19	0.969
All 20	Missing value	

Note: Beginning with the first bit position (high order bit), if the bit position is set to one, then the channel is used. If the bit position is set to zero, then the channel is not used.

0 02 051***Indicator to specify observing method for extreme temperatures****Code table 0 02 051*

Code figure	
0	Reserved
1	Maximum/minimum thermometers
2	Automated instruments
3	Thermograph
4–14	Reserved
15	Missing value

0 02 052***Geostationary imager satellite channels used****Flag table 0 02 052*

Bit No.	Channel	Central wavelength (micrometres)
1	1	0.55 – 0.75
2	2	3.9
3	3	6.7
4	4	10.7
5	5	12.0
All 6	Missing value	

Note: Beginning with the first bit position (high order bit), if the bit position is set to one, then the channel is used. If the bit position is set to zero, then the channel is not used.

0 02 053***GOES-1/M brightness temperature characteristics****Code table 0 02 053*

Code figure	
0	Observed brightness temperature
1	Brightness temperature with bias correction applied
2	Brightness temperature calculated from first guess
3	Brightness temperature calculated from sounding
4–14	Reserved
15	Missing value

0 02 054***GOES-I/M soundings parameter characteristics****Code table 0 02 054*

Code figure	
0	Parameter derived using observed sounder brightness temperatures
1	Parameter derived using observed imager brightness temperatures
2	Parameter derived using first guess information
3	Parameter derived using NMC analysis information
4	Parameter derived using radiosonde information
5–14	Reserved
15	Missing value

0 02 055***Geostationary soundings statistical parameters****Code table 0 02 055*

Code figure	
0	Statistics generated comparing retrieval versus radiosonde
1	Statistics generated comparing retrieval versus first guess
2	Statistics generated comparing radiosonde versus first guess
3	Statistics generated comparing observed versus retrieval
4	Statistics generated comparing observed versus first guess
5	Statistics generated comparing radiosonde versus imager
6	Statistics generated comparing radiosonde versus sounder
7	Statistics generated for radiosonde
8	Statistics generated for first guess
9–14	Reserved
15	Missing value

0 02 056***Geostationary soundings accuracy statistics****Code table 0 02 056*

Code figure	
0	Sums of differences
1	Sums of squared differences
2	Sample size
3	Minimum difference
4	Maximum difference
5–14	Reserved
15	Missing value

0 02 057***Origin of first-guess information for GOES-I/M soundings****Code table 0 02 057*

Code figure	
0	Nested Grid Model (NGM)
1	Aviation Model (AVN)
2	Medium Range Forecast (MRF) Model
3	Global Data Assimilation System (GDAS) Forecast Model
4	Prior soundings (within 3 hours of current time)
5	Climatology
6–14	Reserved
15	Missing value

0 02 058***Valid times of first-guess information for GOES-I/M soundings****Code table 0 02 058*

Code figure	
0	12 hour and 18 hour
1	18 hour and 24 hour
2	6 hour and 12 hour
3	Greater than 24 hours
4–14	Reserved
15	Missing value

0 02 059***Origin of analysis information for GOES-I/M soundings****Code table 0 02 059*

Code figure	
0	NCEP Nested Grid Model (NGM) Analysis
1	NCEP Aviation Model (AVN) Analysis
2	NCEP Medium Range Forecast (MRF) Model Analysis
3	NCEP Global Data Assimilation System (GDAS) Forecast Model Analysis
4–14	Reserved
15	Missing value

0 02 060***Origin of surface information for GOES-I/M soundings****Code table 0 02 060*

Code figure	
0	Current surface hourly reports
1	Current ship reports
2	Current buoy reports
3	One hour old surface hourly reports
4	One hour old ship reports
5	One hour old buoy reports
6–14	Reserved
15	Missing value

0 02 061***Aircraft navigational system****Code table 0 02 061*

Code figure	
0	Inertial navigation system
1	OMEGA
2–6	Reserved
7	Missing value

0 02 062***Type of aircraft data relay system****Code table 0 02 062*

Code figure	
0	ASDAR
1	ASDAR (ACARS also available but not operative)
2	ASDAR (ACARS also available and operative)
3	ACARS
4	ACARS (ASDAR also available but not operative)
5	ACARS (ASDAR also available and operative)
6–14	Reserved
15	Missing value

0 02 064***Aircraft roll angle quality****Code table 0 02 064*

Code figure	
0	Good
1	Bad (see Note)
2	Reserved
3	Missing value

Note: Bad is currently defined as a roll angle > 5 degrees from vertical.

0 02 066***Radiosonde ground receiving system****Code table 0 02 066*

Code figure	
0	InterMet IMS 2000
1	InterMet IMS 1500C
2	Shanghai GTC1
3	Nanjing GTC2
4	Nanjing GFE(L)1
5	MARL-A radar
6	VEKTOR-M radar
7–61	Reserved
62	Other
63	Missing value

0 02 070***Original specification of latitude/longitude****Code table 0 02 070*

Code figure	
0	Actual location in seconds
1	Actual location in minutes
2	Actual location in degrees
3	Actual location in decidegrees
4	Actual location in centidegrees
5	Referenced to checkpoint in seconds
6	Referenced to checkpoint in minutes
7	Referenced to checkpoint in degrees
8	Referenced to checkpoint in decidegrees
9	Referenced to checkpoint in centidegrees
10	Actual location in tenths of a minute
11	Referenced to checkpoint in tenths of a minute
12–14	Reserved
15	Missing value

0 02 080**Balloon manufacturer***Code table 0 02 080*

Code figure	
0	Kaysam
1	Totex
2	KKS
3	Guangzhou Shuangyi (China)
4	ChemChina Zhuzhou (China)
5–61	Reserved
62	Other
63	Missing value

0 02 081**Type of balloon***Code table 0 02 081*

Code figure	
0	GP26
1	GP28
2	GP30
3	HM26
4	HM28
5	HM30
6	SV16
7	Totex TA type balloons
8	Totex TX type balloons
9–29	Reserved
30	Other
31	Missing value

0 02 083**Type of balloon shelter***Code table 0 02 083*

Code figure	
0	High bay
1	Low bay
2	Balloon-inflated launch system (BILS)
3	Roof-top BILS
4	Automated unmanned sounding system
5–13	Reserved
14	Other
15	Missing value

0 02 084***Type of gas used in balloon****Code table 0 02 084*

Code figure	
0	Hydrogen
1	Helium
2	Natural gas
3–13	Reserved
14	Other
15	Missing value

0 02 092***Ozone profile computation method****Code table 0 02 092*

Code figure	
0	UV-channel-based retrieval
1	Visible-channel-based retrieval
2	Combined UV-based retrieval and visible-based retrieval
3–6	Reserved
7	Missing value

0 02 095***Type of pressure sensor****Code table 0 02 095*

Code figure	
0	Capacitance aneroid
1	Derived from GPS
2	Resistive strain gauge
3	Silicon capacitor
4	Derived from radar height
5–29	Reserved
30	Other
31	Missing value

0 02 096***Type of temperature sensor****Code table 0 02 096*

Code figure	
0	Rod thermistor
1	Bead thermistor
2	Capacitance bead
3	Capacitance wire
4	Resistive sensor
5	Chip thermistor
6	Mercury
7	Alcohol/glycol
8–30	Reserved for future use
31	Missing value

0 02 097***Type of humidity sensor****Code table 0 02 097*

Code figure	
0	VIZ Mark II carbon hygistor
1	VIZ B2 hygistor
2	Vaisala A-Humicap
3	Vaisala H-Humicap
4	Capacitance sensor
5	Vaisala RS90
6	Sippican Mark IIA carbon hygistor
7	Twin alternatively heated Humicap capacitance sensor
8	Humicap capacitance sensor with active de-icing method
9	Carbon hygistor
10	Psychrometer
11	Capacitive (polymer)
12	Capacitive (ceramic, including metal oxide)
13	Resistive (generic)
14	Resistive (salt polymer)
15	Resistive (conductive polymer)
16	Thermal conductivity
17	Gravimetric
18	Paper-metal coil
19	Ordinary human hair
20	Rolled hair (torsion)
21	Goldbeater's skin
22	Chilled mirror hygrometer
23	Dew cell
24	Optical absorption sensor
25–30	Reserved for future use
31	Missing value

0 02 099**Polarization***Code table 0 02 099*

Code figure	
0	HH polarization
1	VV polarization
2	HV polarization real valued component
3	HV polarization imaginary valued component
4–6	Reserved
7	Missing value

0 02 101**Type of antenna***Code table 0 02 101*

Code figure	
0	Centre front-fed paraboloid
1	Offset front-fed paraboloid
2	Centre Cassegrain paraboloid
3	Offset Cassegrain paraboloid
4	Planar array
5	Coaxial-collinear array
6	Yagi elements array
7	Microstrip
8–13	Reserved
14	Other
15	Missing value

0 02 103**Radome***Flag table 0 02 103*

Bit No.	
1	Radar antenna is protected by a radome
All 2	Missing value

0 02 104***Antenna polarization****Code table 0 02 104*

Code figure	
0	Horizontal polarization
1	Vertical polarization
2	Right circular polarization
3	Left circular polarization
4	Horizontal and vertical polarization
5	Right and left circular polarization
6	Quasi-horizontal polarization
7	Quasi-vertical polarization
8–14	Reserved
15	Missing value

0 02 115***Type of surface observing equipment****Code table 0 02 115*

Code figure	
0	PDB
1	RSOIS
2	ASOS
3	Psychrometer
4	F420
5–29	Reserved
30	Other
31	Missing value

0 02 119***RA-2 instrument operations****Code table 0 02 119*

Code figure	
0	Intermediate frequency calibration mode (IF CAL)
1	Built-in test equipment digital (BITE DGT)
2	Built-in test equipment radio frequency (BITE RF)
3	Preset tracking (PSET TRK)
4	Preset LOOP OUT
5	ACQUISITION
6	TRACKING
7	Missing value

0 02 131***Sensitivity time control (STC)****Flag table 0 02 131*

Bit No.	
1	STC operational
All 2	Missing values

0 02 137***Radar dual PRF ratio****Code table 0 02 137*

Code figure	
1	3:2
2	4:3
3	5:4
4–14	Reserved
15	Missing value

0 02 138***Antenna rotation direction****Code table 0 02 138*

Code figure	
1	Clockwise rotation
2	Counterclockwise rotation
3	Missing value

0 02 139***SIRAL instrument configuration****Code table 0 02 139*

Code figure	
0	SIRAL nominal
1	SIRAL redundant
2	Missing value

0 02 143***Ozone instrument type****Code table 0 02 143*

Code figure	
0	Reserved
1	Brewer spectrophotometer
2	Caver Teichert
3	Dobson
4	Dobson (Japan)
5	Ehmet
6	Fecker telescope
7	Hoelper
8	Jodmeter
9	Filter Ozonometer M-83
10	Mast
11	Oxford
12	Paetzold
13	Regener
14	Reserved for future use
15	Vassy filter ozonometer
16	Carbon iodide
17	Surface ozone bubbler
18	Filter ozonometer M-124
19	ECC sonde
20–126	Reserved
127	Missing value

0 02 144***Light source type for Brewer spectrophotometer****Code table 0 02 144*

Code figure	
0	Direct sun
1	Direct sun, attenuator #1 (see Note)
2	Direct sun, attenuator #2 (see Note)
3	Focused moon
4	Focused sun
5	Focused sun corrected with adjacent sky measurements
6	Zenith sky
7–14	Reserved
15	Missing value

Note: Entries 1 and 2 should not be used.

0 02 145***Wavelength setting for Dobson instruments****Code table 0 02 145*

Code figure	
0	Wavelengths AD ordinary setting
1	Wavelengths BD ordinary setting
2	Wavelengths CD ordinary setting
3	Wavelengths CC' ordinary setting
4	Wavelengths AD focused image
5	Wavelengths BD focused image
6	Wavelengths CD focused image
7	Wavelengths CC' focused image
8–14	Reserved
15	Missing value

0 02 146***Source conditions for Dobson instruments****Code table 0 02 146*

Code figure	
0	On direct sun
1	On direct moon
2	On blue zenith sky
3	On zenith cloud (uniform stratified layer of small opacity)
4	On zenith cloud (uniform or moderately variable layer of medium opacity)
5	On zenith cloud (uniform or moderately variable layer of large opacity)
6	On zenith cloud (highly variable opacity, with or without precipitation)
7	On zenith cloud (fog)
8	On zenith haze
9	On direct sun through thin cloud, fog or haze
10–14	Reserved
15	Missing value

0 02 147***Method of transmission to collection centre****Code table 0 02 147*

Code figure	
0	Reserved
1	Direct leased circuit
2	Dialled up connection
3	Internet ISP
4	DCP via satellite (MTSAT, METEOSAT, etc.)
5	VSAT
6	GAN, BGAN
7	Thiss terminal
8	Iridium satellites
9	Mobile telephony
10–62	Reserved
63	Missing value

0 02 148***Data collection and/or location system****Code table 0 02 148*

Code figure	
0	Reserved
1	Argos
2	GPS
3	GOES DCP
4	METEOSAT DCP
5	ORBCOMM
6	INMARSAT
7	Iridium
8	Iridium and GPS
9	Argos-3
10	Argos-4
11–30	Reserved
31	Missing value

0 02 149***Type of data buoy****Code table 0 02 149*

Code figure	
0	Unspecified drifting buoy
1	Standard Lagrangian drifter (Global Drifter Programme)
2	Standard FGGE type drifting buoy (non-Lagrangian meteorological drifting buoy)
3	Wind measuring FGGE type drifting buoy (non-Lagrangian meteorological drifting buoy)
4	Ice drifter
5	SVPG Standard Lagrangian drifter with GPS
6	SVP-HR drifter with high-resolution temperature or thermistor string
7	Reserved
8	Unspecified subsurface float
9	SOFAR
10	ALACE
11	MARVOR
12	RAFOS
13	PROVOR
14	SOLO
15	APEX
16	Unspecified moored buoy
17	Nomad
18	3-metre discus
19	10-12-metre discus
20	ODAS 30 series
21	ATLAS (e.g. TAO area)
22	TRITON buoy
23	FLEX mooring (e.g. TIP area)
24	Omnidirectional waverider
25	Directional waverider
26	Subsurface ARGO float
27	PALACE
28	NEMO
29	NINJA
30	Ice buoy/float (POPS or ITP)
31-33	Reserved
34	Mooring oceanographic
35	Mooring meteorological
36	Mooring multidisciplinary (OceanSITES)
37	Mooring tide gauge or tsunami buoy
38	Ice beacon
39	Ice mass balance buoy
40-62	Reserved
63	Missing value

0 02 150***TOVS/ATOVs/AVHRR instrumentation channel number****Code table 0 02 150*

Code figure

0	Reserved
1	HIRS 1
2	HIRS 2
3	HIRS 3
4	HIRS 4
5	HIRS 5
6	HIRS 6
7	HIRS 7
8	HIRS 8
9	HIRS 9
10	HIRS 10
11	HIRS 11
12	HIRS 12
13	HIRS 13
14	HIRS 14
15	HIRS 15
16	HIRS 16
17	HIRS 17
18	HIRS 18
19	HIRS 19
20	HIRS 20
21	MSU 1
22	MSU 2
23	MSU 3
24	MSU 4
25	SSU 1
26	SSU 2
27	SSU 3
28	AMSU-A 1
29	AMSU-A 2
30	AMSU-A 3
31	AMSU-A 4
32	AMSU-A 5
33	AMSU-A 6
34	AMSU-A 7
35	AMSU-A 8
36	AMSU-A 9
37	AMSU-A 10
38	AMSU-A 11
39	AMSU-A 12
40	AMSU-A 13
41	AMSU-A 14
42	AMSU-A 15
43	AMSU-B 1 / MHS 1
44	AMSU-B 2 / MHS 2

FM 94 BUFR*Code table 0 02 150*

Code figure	
45	AMSU-B 3 / MHS 3
46	AMSU-B 4 / MHS 4
47	AMSU-B 5 / MHS 5
48	AVHRR 1
49	AVHRR 2
50	AVHRR 3a
51	AVHRR 3b
52	AVHRR 4
53	AVHRR 5
54–62	Reserved
63	Missing value

0 02 151**Radiometer identifier***Code table 0 02 151*

Code figure	
0	HIRS
1	MSU
2	SSU
3	AMSU-A1-1
4	AMSU-A1-2
5	AMSU-A2
6	AMSU-B
7	AVHRR
8	Reserved
9	MHS
10–2046	Reserved
2047	Missing value

0 02 152**Satellite instrument used in data processing***Flag table 0 02 152*

Bit No.	
1	High-resolution infrared sounder (HIRS)
2	Microwave sounding unit (MSU)
3	Stratospheric sounding unit (SSU)
4	AMI wind mode
5	AMI wave mode
6	AMI image mode
7	RADAR altimeter
8	ATSR
9	Geostationary imager
10	Geostationary sounder
11	Geostationary Earth radiation (GERB)

FM 94 BUFR*Flag table 0 02 152*

Bit No.	
12	Multi-channel scanning radiometer
13	Polar-orbiting imager
14–30	Reserved
All 31	Missing value

0 02 158***RA-2 instrument****Flag table 0 02 158*

Bit No.	
1	Mismatch in RED VEC HPA
2	Mismatch in RED VEC RFSS
3	PTR calibration band 320 MHz (Ku)
4	PTR calibration band 80 MHz (Ku)
5	PTR calibration band 20 MHz (Ku)
6	PTR calibration band 160 MHz (S)
7	Ku flight calibration parameters available
8	S flight calibration parameters available
All 9	Missing value

0 02 159***MWR instrument****Flag table 0 02 159*

Bit No.	
1	Temperature inconsistency
2	Data is missing
3	Redundancy channel
4	Power bus protection
5	Overvoltage/Overload protection
6	Reserved
7	Reserved
All 8	Missing value

0 02 160***Wave length of the radar****Code table 0 02 160*

Code figure	
0	Reserved
1	10 to less than 20 mm
2	Reserved
3	20 to less than 40 mm
4	Reserved
5	40 to less than 60 mm
6	Reserved
7	60 to less than 90 mm
8	90 to less than 110 mm
9	110 mm and greater
10–14	Not used
15	Missing value

0 02 161***Wind processing method****Flag table 0 02 161*

Bit No.	
1–10	Reserved
11	Wind height calculated from median cloud-top pressure of target
12	Target is cloudy
13	Low-level inversion
14	Cross correlation contribution (CCC) method
15	Nested tracking
All 16	Missing value

0 02 162***Extended height assignment method****Code table 0 02 162*

Code figure	
0	Auto editor
1	IRW height assignment
2	WV height assignment
3	H ₂ O intercept height assignment
4	CO ₂ slicing height assignment
5	Low pixel max gradient
6	Higher pixel max gradient
7	Primary height assignment
8	Layer thickness assignment
9	Cumulative contribution function – 10 per cent height
10	Cumulative contribution function – 50 per cent height

Code table 0 02 162

Code figure	
11	Cumulative contribution function – 90 per cent height
12	Cumulative contribution function – height of maximum gradient
13	IR/two WV channel rationing method
14	Composite height assignment
15	Optimal estimation
16	Inversion correction
17	Geometric height assignment
18–62	Reserved
63	Missing value

0 02 163***Height assignment method***

Code table 0 02 163

Code figure	
0	Auto editor
1	IRW height assignment
2	WV height assignment
3	H ₂ O intercept height assignment
4	CO ₂ slicing height assignment
5	Low pixel max gradient
6	Higher pixel max gradient
7	Primary height assignment
8	Layer thickness assignment
9	Cumulative contribution function – 10 per cent height
10	Cumulative contribution function – 50 per cent height
11	Cumulative contribution function – 90 per cent height
12	Cumulative contribution function – height of maximum gradient
13	IR / two WV channel ratioing method
14	Composite height assignment
15	Missing value

0 02 164***Tracer correlation method***

Code table 0 02 164

Code figure	
0	LP – Norms least square minimum
1	EN – Euclidean norm with radiance correlation
2	CC – Cross correlation
3	Stereo matching
4–6	Reserved
7	Missing value

0 02 165***Radiance type flags****Flag table 0 02 165*

Bit No.	
1	Clear path
2	Partly cloudy path
3	Cloudy path
4	Apodized
5	Unapodized
6	Reconstructed
7	Cloud cleared
8–14	Reserved
All 15	Missing value

0 02 166***Radiance type****Code table 0 02 166*

Code figure	
0	Type not defined
1	Automated statistical regression
2	Clear path
3	Partly cloudy path
4	Cloudy path
5–14	Reserved
15	Missing value

0 02 167***Radiance computational method****Code table 0 02 167*

Code figure	
0	Method not defined
1	1b raw radiance
2	Processed radiance
3–14	Reserved
15	Missing value

0 02 169**Anemometer type***Code table 0 02 169*

Code figure	
0	Cup rotor
1	Propeller rotor
2	Wind Observation Through Ambient Noise (WOTAN)
3	Sonic
4–14	Reserved
15	Missing value

0 02 170**Aircraft humidity sensors***Code table 0 02 170*

Code figure	Sensor type
0	SpectraSensors WVSS-II, Version 1
1	SpectraSensors WVSS-II, Version 2
2	SpectraSensors WVSS-II, Version 3
3–61	Reserved
62	Other
63	Missing value

0 02 172**Product type for retrieved atmospheric gases***Code table 0 02 172*

Code figure	
0	Reserved
1	Retrieval from a nadir sounding
2	Retrieval from a limb sounding
<u>3</u>	<u>Retrieval from an occultation sounding</u>
3 4–254	Reserved
255	Missing value

0 02 175***Method of precipitation measurement****Code table 0 02 175*

Code figure	
0	Manual measurement
1	Tipping bucket method
2	Weighing method
3	Optical method
4	Pressure method
5	Float method
6	Drop counter method
7–13	Reserved
14	Others
15	Missing value

0 02 176***Method of state of ground measurement****Code table 0 02 176*

Code figure	
0	Manual observation
1	Video camera method
2	Infrared method
3	Laser method
4–13	Reserved
14	Others
15	Missing value

0 02 177***Method of snow depth measurement****Code table 0 02 177*

Code figure	
0	Manual observation
1	Ultrasonic method
2	Video camera method
3	Laser method
4–13	Reserved
14	Others
15	Missing value

0 02 178***Method of liquid content measurement of precipitation****Code table 0 02 178*

Code figure	
0	Manual observation
1	Optical method
2	Capacitive method
3–13	Reserved
14	Others
15	Missing value

0 02 179***Type of sky condition algorithm****Code table 0 02 179*

Code figure	
0	Manual observation
1	VAISALA algorithm
2	ASOS (FAA) algorithm
3	AWOS (Canada) algorithm
4–13	Reserved
14	Others
15	Missing value

0 02 180***Main present weather detecting system****Code table 0 02 180*

Code figure	
0	Manual observation
1	Optical scatter system combined with precipitation occurrence sensing system
2	Forward and/or backscatter system of visible light
3	Forward and/or backscatter system of infrared light
4	Infrared light emitting diode (IRED) system
5	Doppler radar system
6–13	Reserved
14	Others
15	Missing value

0 02 181***Supplementary present weather sensor****Flag table 0 02 181*

Bit No.	
1	Rain detector
2	Freezing rain sensor
3	Ice detection sensor
4	Hail and ice pellet sensor
5–19	Reserved
20	Others
All 21	Missing value

0 02 182***Visibility measurement system****Code table 0 02 182*

Code figure	
0	Manual measurement
1	Transmissometer system (base > 25 m)
2	Transmissometer system (base < 25 m)
3	Forward scatter system
4	Backscatter system
5–13	Reserved
14	Others
15	Missing value

0 02 183***Cloud detection system****Code table 0 02 183*

Code figure	
0	Manual observation
1	Ceilometer system
2	Infrared camera system
3	Microwave visual camera system
4	Sky imager system
5	Video time-lapsed camera system
6	Micropulse lidar (MPL) system
7–13	Reserved
14	Others
15	Missing value

0 02 184***Type of lightning detection sensor****Code table 0 02 184*

Code figure	
0	Manual observation
1	Lightning imaging sensor
2	Electrical storm identification sensor
3	Magnetic finder sensor
4	Lightning strike sensor
5	Flash counter
6	ATDnet VLF waveform correlated sensor
7–13	Reserved
14	Others
15	Missing value

0 02 185***Method of evaporation measurement****Code table 0 02 185*

Code figure	
0	Manual measurement
1	Balanced floating method
2	Pressure method
3	Ultrasonic method
4	Hydraulic method
5–13	Reserved
14	Others
15	Missing value

0 02 186***Capability to detect precipitation phenomena****Flag table 0 02 186*

Bit No.	
1	Precipitation-unknown type
2	Liquid precipitation not freezing
3	Liquid freezing precipitation
4	Drizzle
5	Rain
6	Solid precipitation
7	Snow
8	Snow grains
9	Snow pellets
10	Ice pellets
11	Ice crystals
12	Diamond dust
13	Small hail

FM 94 BUFR*Flag table 0 02 186*

Bit No.	
14	Hail
15	Glaze
16	Rime
17	Soft rime
18	Hard rime
19	Clear ice
20	Wet snow
21	Hoar frost
22	Dew
23	White dew
24	Convective precipitation
25–29	Reserved
All 30	Missing value

0 02 187***Capability to detect other weather phenomena****Flag table 0 02 187*

Bit No.	
1	Dust/sand whirl
2	Squalls
3	Sand storm
4	Dust storm
5	Lightning – cloud to surface
6	Lightning – cloud to cloud
7	Lightning – distant
8	Thunderstorm
9	Funnel cloud not touching surface
10	Funnel cloud touching surface
11	Spray
12–17	Reserved
All 18	Missing value

0 02 188***Capability to detect obscuration****Flag table 0 02 188*

Bit No.	
1	Fog
2	Ice fog
3	Steam fog
4–6	Reserved
7	Mist
8	Haze
9	Smoke
10	Volcanic ash
11	Dust
12	Sand
13	Snow
14–20	Reserved
All 21	Missing value

0 02 189***Capability to discriminate lightning strikes****Flag table 0 02 189*

Bit No.	
1	Manual observation
2	All lightning strikes without discrimination
3	Lightning strikes cloud to ground only
4	All lightning strikes with discrimination between cloud to ground and cloud to cloud
5–11	Reserved
All 12	Missing value

0 02 191***Geopotential height calculation****Code table 0 02 191*

Code figure	
0	Geopotential height calculated from pressure
1	Geopotential height calculated from GPS height
2	Geopotential height calculated from radar height
3–14	Reserved
15	Missing value

0 03 001**Surface station type***Code table 0 03 001*

Code figure	
0	Land station (synoptic network)
1	Shallow water station (fixed to sea/lake floor)
2	Ship
3	Rig/platform
4	Moored buoy
5	Drifting buoy (or drifter)
6	Ice buoy
7	Land station (local network)
8	Land vehicle
9	Autonomous marine vehicle
10	Tag attached to marine animal
11–30	Reserved for future use
31	Missing value

0 03 003**Thermometer/hygrometer housing***Code table 0 03 003*

Code figure	
0	Screen
1	Sling/whirling
2	Unscreened
3	Radiation shield
4	Aspirated (e.g. Assmann)
5	Other shelter
6	Handheld
7–14	Reserved for future use
15	Missing value

0 03 004**Type of screen/shelter/radiation shield***Code table 0 03 004*

Code figure	
0	Stevenson screen
1	Marine Stevenson screen
2	Cylindrical section plate shield
3	Concentric tube
4	Rectangular section shield
5	Square section shield
6	Triangular section shield

FM 94 BUFR*Code table 0 03 004*

Code figure	
7	Open covered lean-to
8	Open covered inverted V roof
9	Integrated (e.g. chilled mirror)
10–14	Reserved for future use
15	Missing value

0 03 008***Artificially ventilated screen or shield****Code table 0 03 008*

Code figure	
0	Natural ventilation in use
1	Artificial aspiration in use: constant flow at time of reading
2	Artificial aspiration in use: variable flow at time of reading
3–6	Reserved
7	Missing value

0 03 010***Method of sea/water current measurement****Code table 0 03 010*

Code figure	
0	Reserved
1	ADCP (see Note)
2	GEK (Geomagnetic Electrokinetograph)
3	Ship's set and drift determined by fixes 3–6 hours apart
4	Ship's set and drift determined by fixes more than 6 hours but less than 12 hours apart
5	Drift of buoy
6	ADCP
7	ADCP bottom tracking mode
8	Electromagnetic sensor
9	Rotor and vane
10	Lowered ADCP
11–14	Reserved
15	Missing value

Note: Code figure 1 is deprecated. Code figure 6 should be used instead.

0 03 011***Method of depth calculation****Code table 0 03 011*

Code figure	
0	Depth calculated using fall rate equation
1	Depth calculated from water pressure/equation of state
2	Reserved
3	Missing value

0 03 012***Instrument type/sensor for dissolved oxygen measurement****Code table 0 03 012*

Code figure	
0	Aanderaa oxygen optode
1	Winkler bottle
2–14	Reserved
15	Missing value

0 03 016***Position of road sensors****Code table 0 03 016*

Code figure	
0	Fast lane between the wheel tracks
1	Fast lane between the wheel tracks in the opposite direction
2	Fast lane in the wheel tracks
3	Fast lane in the wheel tracks in the opposite direction
4	Slow lane between the wheel tracks
5	Slow lane between the wheel tracks in the opposite direction
6	Slow lane in the wheel tracks
7	Slow lane in the wheel tracks in the opposite direction
8–14	Reserved
15	Missing value

0 03 017***Extended type of station****Flag table 0 03 017*

Bit No.	
1	Automatic
2	Manned
3	Event triggered
4	Longer time period than the standard
5	Reserved
All 6	Missing value

0 03 018***Type of road****Code table 0 03 018*

Code figure	
0	Free track without further information
1	Free track, embankment
2	Free track, flat relative to surroundings
3	Free track, water basin(s) in vicinity
4	Free track, forest
5	Free track, cleft
6	Free track, on hilltop
7	Free track, on hilltop, forest
8	Free track, in valley
9	Free track, in valley, forest
10	Free track, north inclination
11	Free track, north inclination, forest
12	Free track, south inclination
13	Free track, south inclination, forest
14–19	Reserved
20	Bridge without further information
21	Bridge across a valley in an urban area
22	Bridge across a valley with forest/meadows/fields
23	Bridge across street/track
24	Bridge across big river/canal
25	Bridge across river/canal of medium size
26	Bridge across a small stream/loading canal
27–30	Reserved
31	Missing value

0 03 019***Type of construction****Code table 0 03 019*

Code figure	
0	Asphalt
1	Concrete
2	Concrete construction
3	Steel-girder construction
4	Box girder bridge
5	Orthotropic slab
6	Drain asphalt
7–14	Reserved
15	Missing value

0 03 020***Material for thermometer/hygrometer housing****Code table 0 03 020*

Code figure	
0	Wood
1	Metal alloy
2	Plastic/GRP
3	Reed/grass/leaf
4–6	Reserved for future use
7	Missing value

0 03 021***Hygrometer heating****Code table 0 03 021*

Code figure	
0	Unheated
1	Heated
2	Not applicable
3	Missing value

0 03 022***Instrument owner****Code table 0 03 022*

Code figure	
0	National hydrometeorological/weather service
1	Other
2	Standards institute
3–6	Reserved for future use
7	Missing value

0 03 023***Configuration of louvers for thermometer/hygrometer screen****Code table 0 03 023*

Code figure	
0	Single v-section louvers
1	Overlapping louvers
2	Double v-section louvers
3	Non-overlapping louvers
4	Vented, non-louvered
5	Not applicable
6	Reserved for future use
7	Missing value

0 03 027***Type of flight rig****Code table 0 03 027*

<i>Code figure</i>	
0	Solo (single radiosonde)
1	Block
2	Bar
3	Cross
4	T-rig
5	Double T-rig
6	Complex
7–14	Reserved
15	Missing value

0 03 028***Method of snow water equivalent measurement****Code table 0 03 028*

<i>Code figure</i>	
0	Multi-point manual snow survey
1	Single-point manual snow water equivalent measurement
2	Snow pillow or snow scale
3	Passive gamma
4	GNSS/GPS methods
5	Cosmic ray attenuation
6	Time domain reflectometry
7–62	Reserved
63	Missing value

0 03 029**Swath***Code table 0 03 029*

<i>Code figure</i>	
<u>0</u>	<u>Left hand side</u>
<u>1</u>	<u>Right hand side</u>
<u>2–6</u>	<u>Reserved</u>
<u>7</u>	<u>Missing</u>

0 03 030**Antenna Status***Code table 0 03 030*

<i>Code figure</i>	
<u>0</u>	<u>Transmitting</u>
<u>1</u>	<u>Receiving</u>

Code table 0 03 030

Code figure

<u>2-6</u>	<u>Reserved</u>
<u>Z</u>	<u>Missing</u>

Provisional Copy
2023

0 04 059***Times of observation used to compute the reported mean values****Flag table 0 04 059*

Bit No.	
1	0000 UTC
2	0600 UTC
3	1200 UTC
4	1800 UTC
5	Other hours
All 6	Missing value

0 04 080***Averaging period for following value****Code table 0 04 080*

Code figure	
0	Spot values
1	Less than 15 minutes
2	From 15 to 45 minutes
3	More than 45 minutes
4–8	Reserved
9	Data not available
10–14	Not used
15	Missing value

0 05 069***Receiver channel****Code table 0 05 069*

Code figure	
0	Mie
1	Rayleigh
2	Cross polar
3	Missing value

Provisional Copy
2023

0 08 001***Vertical sounding significance****Flag table 0 08 001*

Bit No.	
1	Surface
2	Standard level
3	Tropopause level
4	Maximum wind level
5	Significant level, temperature and/or relative humidity
6	Significant level, wind
All 7	Missing value

0 08 002***Vertical significance (surface observations)****Code table 0 08 002*

Code figure	
0	Observing rules for base of lowest cloud and cloud types of FM 12 SYNOP and FM 13 SHIP apply
1	First non-Cumulonimbus significant layer
2	Second non-Cumulonimbus significant layer
3	Third non-Cumulonimbus significant layer
4	Cumulonimbus layer
5	Ceiling
6	Clouds not detected below the following height(s)
7	Low cloud
8	Middle cloud
9	High cloud
10	Cloud layer with base below and top above the station
11	Cloud layer with base and top below the station level
12–19	Reserved
20	No clouds detected by the cloud detection system
21	First instrument detected cloud layer
22	Second instrument detected cloud layer
23	Third instrument detected cloud layer
24	Fourth instrument detected cloud layer
25–61	Reserved
62	Value not applicable
63	Missing value

0 08 003***Vertical significance (satellite observations)****Code table 0 08 003*

Code figure	
0	Surface
1	Base of satellite sounding
2	Cloud top
3	Tropopause
4	Precipitable water
5	Sounding radiances
6	Mean temperatures
7	Ozone
8	Low cloud
9	Med cloud
10	High cloud
11–62	Reserved
63	Missing value

0 08 004***Phase of aircraft flight****Code table 0 08 004*

Code figure	
0–1	Reserved
2	Unsteady (UNS)
3	Level flight, routine observation (LVR)
4	Level flight, highest wind encountered (LVW)
5	Ascending (ASC)
6	Descending (DES)
7	Missing value

0 08 005***Meteorological attribute significance****Code table 0 08 005*

Code figure	
0	Reserved
1	Storm centre
2	Outer limit or edge of storm
3	Location of maximum wind
4	Location of the storm in the perturbed analysis
5	Location of the storm in the analysis
6–14	Reserved
15	Missing value

0 08 006***Ozone vertical sounding significance****Flag table 0 08 006*

Bit No.	
1	Surface
2	Standard level
3	Tropopause level
4	Prominent maximum level
5	Prominent minimum level
6	Minimum pressure level
7	Reserved
8	Level of undetermined significance
All 9	Missing value

0 08 007***Dimensional significance****Code table 0 08 007*

Code figure	
0	Point
1	Line
2	Area
3	Volume
4–14	Reserved
15	Missing value

Note: A consecutive sequence of 2 or more of location coordinates, such as latitude and longitude pairs, defines a line or polygon. Points shall be joined in the order given in the message. Any area described will fall left of the drawn boundary in the direction established by the order of the points given in the message. This definition is for simple non-intersecting polygons without holes.

0 08 008***Radiation vertical sounding significance****Flag table 0 08 008*

Bit No.	
1	Surface
2	Standard level
3	Tropopause level
4	Level of beta radiation maximum
5	Level of gamma radiation maximum
6	Minimum pressure level
7	Reserved
8	Level of undetermined significance
All 9	Missing value

0 08 009***Detailed phase of flight****Code table 0 08 009*

Code figure	
0	Level flight, routine observation, unsteady
1	Level flight, highest wind encountered, unsteady
2	Unsteady (UNS)
3	Level flight, routine observation (LVR)
4	Level flight, highest wind encountered (LVW)
5	Ascending (ASC)
6	Descending (DES)
7	Ascending, observation intervals selected by time increments
8	Ascending, observation intervals selected by time increments, unsteady
9	Ascending, observation intervals selected by pressure increments
10	Ascending, observation intervals selected by pressure increments, unsteady
11	Descending, observation intervals selected by time increments
12	Descending, observation intervals selected by time increments, unsteady
13	Descending, observation intervals selected by pressure increments
14	Descending, observation intervals selected by pressure increments, unsteady
15	Missing value

0 08 010***Surface qualifier (for temperature data)******Type of station****Code table 0 08 010*

Code figure	
0	Reserved
1	Bare soil
2	Bare rock
3	Land grass cover
4	Water (lake, sea)
5	Flood water underneath
6	Snow
7	Ice
8	Runway or road
9	Ship or platform deck in steel
10	Ship or platform deck in wood
11	Ship or platform deck partly covered with rubber mat
12	Building roof
13–30	Reserved
31	Missing value

0 08 011***Meteorological feature******Type of station****Code table 0 08 011*

Code figure	
0	Quasi-stationary front at the surface
1	Quasi-stationary front above the surface
2	Warm front at the surface
3	Warm front above the surface
4	Cold front at the surface
5	Cold front above the surface
6	Occlusion
7	Instability line
8	Intertropical front
9	Convergence line
10	Jet stream
11	Cloud clear
12	Cloud
13	Turbulence
14	Storm
15	Airframe icing
16	Phenomenon
17	Volcano
18	Atmospherics
19	Reserved
20	Special clouds
21	Thunderstorm
22	Tropical cyclone
23	Mountain wave
24	Duststorm
25	Sandstorm
26–62	Reserved
63	Missing value

0 08 012***Land/sea qualifier******Type of station****Code table 0 08 012*

Code figure	
0	Land
1	Sea
2	Coast
3	Missing value

0 08 013***Day/night qualifier****Code table 0 08 013*

Code figure	
0	Night
1	Day
2	Twilight
3	Missing value

0 08 014***Qualifier for runway visual range****Code table 0 08 014*

Code figure	
0	10-minute mean value— normal value
1	10-minute mean value— above the upper limit for assessments of RVR (P)
2	10-minute mean value— below the lower limit for assessments of RVR (M)
3	one-minute minimum value— normal value
4	one-minute minimum value— above the upper limit for assessments of RVR (P)
5	one-minute minimum value— below the lower limit for assessments of RVR (M)
6	one-minute maximum value— normal value
7	one-minute maximum value— above the upper limit for assessments of RVR (P)
8	one-minute maximum value— below the lower limit for assessments of RVR (M)
9–14	Reserved
15	Missing value

0 08 015***Significant qualifier for sensor****Code table 0 08 015*

Code figure	
0	Single sensor
1	Primary sensor
2	Secondary sensor (Backup)
3–6	Reserved
7	Missing value

0 08 016***Change qualifier of a trend-type forecast or an aerodrome forecast****Code table 0 08 016*

Code figure	
0	NOSIG
1	BECMG
2	TEMPO
3	FM
4–6	Reserved
7	Missing value

0 08 017***Qualifier of the time when the forecast change is expected****Code table 0 08 017*

Code figure	
0	FM
1	TL
2	AT
3	Missing value

0 08 018***SEAWINDS land/ice surface type****Flag table 0 08 018*

Bit No.	
1	Land is present
2	Surface ice map indicates ice is present
3–10	Reserved
11	Ice map data not available
12	Attenuation map data not available
13–16	Reserved
All 17	Missing value

0 08 019***Qualifier for following centre identifier****Code table 0 08 019*

Code figure	
0	Reserved
1	ATS (Air Traffic Service) unit serving FIR (Flight Information Region)
2	FIR (Flight Information Region)
3	UIR (Upper Flight Information Region)
4	CTA (Control Area)
5	VAAC (Volcanic Ash Advisory Centre)
6	MWO (Meteorological Watch Office) issuing SIGMET
7–14	Reserved
15	Missing value

0 08 021***Time significance****Code table 0 08 021*

Code figure	
0	Reserved
1	Time series
2	Time averaged (see Note 1)
3	Accumulated
4	Forecast
5	Forecast time series
6	Forecast time averaged
7	Forecast accumulated
8	Ensemble mean (see Note 2)
9	Ensemble mean time series
10	Ensemble mean time averaged
11	Ensemble mean accumulated
12	Ensemble mean forecast
13	Ensemble mean forecast time series
14	Ensemble mean forecast time averaged
15	Ensemble mean forecast accumulated
16	Analysis
17	Start of phenomenon
18	Radiosonde launch time
19	Start of orbit
20	End of orbit
21	Time of ascending node
22	Time of occurrence of wind shift
23	Monitoring period
24	Agreed time limit for report reception
25	Nominal reporting time
26	Time of last known position
27	First guess
28	Start of scan

FM 94 BUFR*Code table 0 08 021*

Code figure	
29	End of scan or time of ending
30	Time of occurrence
31	Missing value

Notes:

- (1) "Time averaged" indicates that values are continuously averaged over a period of time.
- (2) "Ensemble mean" indicates that a number of distinct values corresponding to a set of time locations are averaged.
- (3) Time significance must be qualified by appropriate time periods being specified.

0 08 023***First-order statistics****Code table 0 08 023*

Code figure	
0-1	Reserved
2	Maximum value
3	Minimum value
4	Mean value
5	Median value
6	Modal value
7	Mean absolute error
8	Reserved
9	Best estimate of standard deviation (N-1)
10	Standard deviation (N)
11	Harmonic mean
12	Root-mean-square vector error
13	Root-mean-square
14	<u>Root-mean-square error</u>
15-31	Reserved
32	Vector mean
33-62	Reserved for local use
63	Missing value

Note: All first-order statistics are in the units defined by the original data descriptors.

0 08 024***Difference statistics****Code table 0 08 024*

Code figure	
0-1	Reserved
2	Observed minus maximum
3	Observed minus minimum
4	Observed minus mean
5	Observed minus median
6	Observed minus mode

Code table 0 08 024

Code figure	
7–10	Reserved
11	Observed minus climatology (anomaly)
12	Observed minus analysed value
13	Observed minus initialized analysed value
14	Observed minus forecast value (see Note 2)
15–20	Reserved
21	Observed minus interpolated value
22	Observed minus hydrostatically calculated value
23–31	Reserved
32–62	Reserved for local use
63	Missing value

Notes:

- (1) Difference statistics are difference values; they have dimensions the same as the corresponding reported values with respect to units, but assume a range centred on zero (e.g., the difference between reported and analysed values, the difference between reported and forecast values).
- (2) Where observed minus forecast values are represented, the period of the forecast shall be indicated by an appropriate descriptor from Class 04.

0 08 025***Time difference qualifier***

Code table 0 08 025

Code figure	
0	Universal Time Coordinated (UTC) minus Local Standard Time (LST)
1	Local Standard Time
2	Universal Time Coordinated (UTC) minus Satellite clock
3–4	Reserved
5	Time difference from edge of processing segment
6–14	Reserved
15	Missing value

0 08 026***Matrix significance***

Code table 0 08 026

Code figure	
0	Averaging kernel matrix
1	Correlation matrix (C)
2	Lower triangular correlation matrix square root (L from $C=LL^T$)
3	Inverse of lower triangular correlation matrix square root (L^{-1})
4–42	Reserved
43–62	Reserved for local use
63	Missing or undefined significance

0 08 029**Surface type***Code table 0 08 029*

Code figure	
0	Open ocean or semi-enclosed sea
1	Enclosed sea or lake
2	Continental ice
3	Land
4	Low inland (below sea level)
5	Mix of land and water
6	Mix of land and low inland
7–10	Reserved
11	River
12	Lake
13	Sea
14	Glacier
15	Urban land
16	Rural land
17	Suburban land
18	Sea ice
19–254	Reserved
255	Missing value

0 08 032**Status of operation***Code table 0 08 032*

Code figure	
0	Routine operation
1	Event triggered by storm surge
2	Event triggered by tsunami
3	Event triggered manually
4	Installation testing
5	Maintenance testing
6–14	Reserved
15	Missing value

0 08 033***Method of derivation of percentage confidence****Code table 0 08 033*

Code figure	
0	Reserved
1	Percentage confidence calculated using cloud fraction
2	Percentage confidence calculated using standard deviation of temperature
3	Percentage confidence calculated using probability of cloud contamination
4	Percentage confidence calculated using normality of distribution
5–126	Reserved
127	Missing value

0 08 034***Temperature/salinity measurement qualifier****Code table 0 08 034*

Code figure	
0	Secondary sampling: averaged
1	Secondary sampling: discrete
2	Secondary sampling: mixed
3	Near-surface sampling: averaged, pumped
4	Near-surface sampling: averaged, unpumped
5	Near-surface sampling: discrete, pumped
6	Near-surface sampling: discrete, unpumped
7	Near-surface sampling: mixed, pumped
8	Near-surface sampling: mixed, unpumped
9–14	Reserved
15	Missing value

0 08 035***Type of monitoring exercise****Code table 0 08 035*

Code figure	
0	Global
1	Regional
2	National
3	Special
4	Bilateral
5	Reserved
6	Reserved
7	Missing value

0 08 036***Type of centre or station performing monitoring****Code table 0 08 036*

Code figure	
0	WMO Secretariat
1	WMO
2	RSMC
3	NMC
4	RTH
5	Observing site
6	Other
7	Missing value

0 08 037***Baseline check significance****Code table 0 08 037*

Code figure	
0	Manufacturer's baseline check unit
1	Weather screen
2	GRUAN standard humidity chamber
3–30	Reserved
31	Missing value

0 08 038***Instrument data significance****Code table 0 08 038*

Code figure	
0	Verified instrument reading
1	Reference instrument reading
2–254	Reserved
255	Missing value

0 08 039***Time significance (Aviation forecast)****Code table 0 08 039*

Code figure	
0	Issue time of forecast
1	Time of commencement of period of the forecast
2	Time of ending of period of the forecast
3	Forecast time of maximum temperature
4	Forecast time of minimum temperature
5	Time of beginning of the forecast change
6	Time of ending of the forecast change
7–62	Reserved
63	Missing value

0 08 040***Flight level significance****Code table 0 08 040*

Code figure	
0	High-resolution data sample
1	Within 20 hPa of surface
2	Pressure less than 10 hPa (i.e., 9, 8, 7, etc.) when no other reason applies
3	Base pressure level for stability index
4	Begin doubtful temperature, height data
5	Begin missing data (all elements)
6	Begin missing relative humidity data
7	Begin missing temperature data
8	Highest level reached before balloon descent because of icing or turbulence
9	End doubtful temperature, height data
10	End missing data (all elements)
11	End missing relative humidity data
12	End missing temperature data
13	Zero degrees Celsius crossing(s) for RADAT
14	Standard pressure level
15	Operator-added level
16	Operator-deleted level
17	Balloon re-ascended beyond previous highest ascent level
18	Significant relative humidity level
19	Relative humidity level selection terminated
20	Surface level
21	Significant temperature level
22	Mandatory temperature level
23	Flight termination level
24	Tropopause(s)
25	Aircraft report
26	Interpolated (generated) level
27	Mandatory wind level
28	Significant wind level

Code table 0 08 040

Code figure	
29	Maximum wind level
30	Incremental wind level (fixed regional)
31	Incremental height level (generated)
32	Wind termination level
33	Pressure 100 to 110 hPa, when no other reason applies
34	Freezing level base
35	Freezing level top
36	Flight level base
37	Flight level top
38	Top of wind sounding
39	Bottom of wind sounding
40	Significant thermodynamic level (inversion)
41	Significant relative humidity level (according to NCDC criteria)
42	Significant temperature level (according to NCDC)
43	Begin missing wind data
44	End missing wind data
45–59	Reserved
60	Level of 80-knot isotach above jet
61	Level of 80-knot isotach below jet
62	Other
63	Missing value

0 08 041**Data significance**

Code table 0 08 041

Code figure	
0	Parent site
1	Observation site
2	Balloon manufacture date
3	Balloon launch point
4	Surface observation
5	Surface observation displacement from launch point
6	Flight level observation
7	Flight level termination point
8	IFR ceiling and visibility
9	Mountain obscuration
10	Strong surface wind
11	Freezing level
12	Multiple freezing level
13	Instrument manufacture date
14–30	Reserved
31	Missing value

0 08 042***Extended vertical sounding significance****Flag table 0 08 042*

Bit No.	
1	Surface
2	Standard level
3	Tropopause level
4	Maximum wind level
5	Significant temperature level
6	Significant humidity level
7	Significant wind level
8	Beginning of missing temperature data
9	End of missing temperature data
10	Beginning of missing humidity data
11	End of missing humidity data
12	Beginning of missing wind data
13	End of missing wind data
14	Top of wind sounding
15	Level determined by regional decision
16	Freezing level (see Note)
17	Pressure level originally indicated by height as the vertical coordinate
All 18	Missing value

Note:

- (1) Freezing level is the level at which temperature first decreases to 0 °C. The criteria for the selection of freezing level in upper-air observations are:
- (a) If the surface temperature is not lower than 0 °C when the radiosonde is released, then the lowest level at which the temperature first decreases to 0 °C will be selected as the freezing level.
 - (b) If the surface temperature is equal to 0 °C, then the surface level will be the freezing level.
 - (c) If during observation there is no level at which the temperature equals 0 °C, then the closest two levels between which the temperature crosses from a positive to a negative value should be used to interpolate the freezing-level temperature equal to 0 °C.
 - (d) The following elements will be calculated for the freezing level: time, elevation, pressure, humidity, dewpoint temperature, dewpoint depression, and deviation of longitude and latitude.

0 08 043***Atmospheric chemical or physical constituent type***

<i>Code table 0 08 043</i>			
Code figure	Name	Formula	CAS number (if applicable)
0	Ozone	O ₃	10028-15-6
1	Water vapour	H ₂ O	7732-18-5
2	Methane	CH ₄	74-82-8
3	Carbon dioxide	CO ₂	124-38-9
4	Carbon monoxide	CO	630-08-0
5	Nitrogen dioxide	NO ₂	10102-44-0
6	Nitrous oxide	N ₂ O	10024-97-2
7	Formaldehyde	HCHO	50-00-0
8	Sulphur dioxide	SO ₂	7446-09-5
9	Volcanic sulphur dioxide		
10–24	Reserved		
25	Particulate matter < 1.0 microns		
26	Particulate matter < 2.5 microns		
27	Particulate matter < 10 microns		
28	Aerosols (generic)		
29	Smoke (generic)		
30	Crustal material (generic dust)		
31	Volcanic ash		
32	Cloud		
33	Cloud and aerosols		
34–200	Reserved		
201–254	Reserved for local use		
255	Missing value		

Note: The last column in the table contains the associated registry number from the Chemical Abstracts Service (CAS) of the American Chemical Society.

0 08 046***Atmospheric chemical or physical constituent type***

(See Common Code table C–14 Part C/c.)

0 08 050***Qualifier for number of missing values in calculation of statistic***

<i>Code table 0 08 050</i>	
Code figure	
0	Reserved
1	Pressure
2	Temperature
3	Extreme temperature
4	Vapour pressure
5	Precipitation

FM 94 BUFR

Code table 0 08 050

Code figure	
6	Sunshine duration
7	Maximum temperature
8	Minimum temperature
9	Wind
10–14	Reserved
15	Missing value

0 08 051

Qualifier for number of missing values in calculation of statistic

Code table 0 08 051

Code figure	
1	Pressure
2	Temperature
3	Extreme temperature
4	Vapour pressure
5	Precipitation
6	Sunshine duration
7	Missing value

0 08 052

Condition for which number of days of occurrence follows

Code table 0 08 052

Code figure	
0	Mean wind speed over a 10-minute period observed or recorded equal to or more than 10 m s^{-1} or 20 knots
1	Mean wind speed over a 10-minute period observed or recorded equal to or more than 20 m s^{-1} or 40 knots
2	Mean wind speed over a 10-minute period observed or recorded equal to or more than 30 m s^{-1} or 60 knots
3	Maximum temperature less than 273.15 K
4	Maximum temperature equal to or more than 298.15 K
5	Maximum temperature equal to or more than 303.15 K
6	Maximum temperature equal to or more than 308.15 K
7	Maximum temperature equal to or more than 313.15 K
8	Minimum temperature less than 273.15 K
9	Maximum temperature equal to or more than 273.15 K
10	Precipitation equal to or more than 1.0 kg m^{-2}
11	Precipitation equal to or more than 5.0 kg m^{-2}
12	Precipitation equal to or more than 10.0 kg m^{-2}
13	Precipitation equal to or more than 50.0 kg m^{-2}
14	Precipitation equal to or more than 100.0 kg m^{-2}
15	Precipitation equal to or more than 150.0 kg m^{-2}
16	Snow depth more than 0.00 m
17	Snow depth more than 0.01 m
18	Snow depth more than 0.10 m

FM 94 BUFR*Code table 0 08 052*

Code figure	
19	Snow depth more than 0.50 m
20	Horizontal visibility less than 50 m
21	Horizontal visibility less than 100 m
22	Horizontal visibility less than 1000 m
23	Hail
24	Thunderstorm
25–30	Reserved
31	Missing value

0 08 053***Day of occurrence qualifier****Code table 0 08 053*

Code figure	
0	Value occurred on only one day in the month
1	Value occurred on more than one day in the month
2	Reserved
3	Missing value

0 08 054***Qualifier for wind speed or wind gusts****Code table 0 08 054*

Code figure	
0	Wind speed or gust is as reported
1	Wind speed is greater than that reported (P in METAR/TAF/SPECI)
2–6	Reserved
7	Missing value

0 08 060***Sample scanning mode significance****Code table 0 08 060*

Code figure	
0	Reserved
1	Range
2	Azimuth
3	Horizontal
4	Vertical
5	North/south
6	East/west
7–14	Reserved
15	Missing value

0 08 065***Sun-glint indicator****Code table 0 08 065*

Code figure	
0	No sun-glint
1	Sun-glint
2	Reserved
3	Missing value

0 08 066***Semi-transparency indicator****Code table 0 08 066*

Code figure	
0	Opaque
1	Semi-transparent
2	Reserved
3	Missing value

0 08 070***Vertical sounding product qualifier****Code table 0 08 070*

Code figure	
0	Reserved
1	Reserved
2	Earth located instrument counts, calibration coefficients and housekeeping (level 1b)
3	Earth located calibrated radiances (level 1c)
4	Mapped to a common footprint, Earth located calibrated radiances (level 1d)
5–14	Reserved
15	Missing value

0 08 072***Pixel(s) type****Code table 0 08 072*

Code figure	
0	Mixed
1	Clear
2	Cloudy
3	Probably clear
4	Probably cloudy
5–6	Reserved
7	Missing value

0 08 074***Altimeter echo type****Code table 0 08 074*

Code figure	
0	Open ocean or semi-enclosed sea
1	Non-ocean like
2	Reserved
3	Missing value

0 08 075***Ascending/descending orbit qualifier****Code table 0 08 075*

Code figure	
0	Ascending orbit
1	Descending orbit
2	Reserved
3	Missing value

0 08 076***Type of band****Code table 0 08 076*

Code figure	
0	Ku
1	C
2	Long-wave infrared
3	Medium-wave infrared
4	Short-wave infrared
5	M
6	I
7	Day/night
8-62	Reserved
63	Missing value

0 08 077***Radiometer sensed surface type****Code table 0 08 077*

Code figure	
0	Land
1	Sea
2	Coastal
3	Open ocean or semi-enclosed sea
4	Enclosed sea or lake
5	Continental ice
6–126	Reserved
127	Missing value

0 08 079***Product status****Code table 0 08 079*

Code figure	
0	Normal issue
1	Correction to a previously issued product (COR)
2	Amendment to a previously issued product (AMD)
3	Correction to a previously issued amended product (COR AMD)
4	Cancellation of a previously issued product (CNL)
5	No product available (NIL)
6	Special report (SPECI)
7	Corrected special report (SPECI COR)
8–14	Reserved
15	Missing or not applicable

0 08 080***Qualifier for GTSP quality flag****Code table 0 08 080*

Code figure	
0	Total water pressure profile
1	Total water temperature profile
2	Total water salinity profile
3	Total water conductivity profile
4	Total water depth
5–9	Reserved
10	Water pressure at a level
11	Water temperature at a level
12	Salinity at a level
13	Water depth at a level
14	Sea/water current speed at a level
15	Sea/water current direction at a level
16	Dissolved oxygen at a level

FM 94 BUFR*Code table 0 08 080*

Code figure	
17–19	Reserved
20	Position
21– 62 24	Reserved
<u>25</u>	<u>Water conductivity at a level</u>
<u>26</u>	<u>Sea water potential density referenced to sea surface at a level</u>
<u>27–62</u>	<u>Reserved</u>
63	Missing value

0 08 081***Type of equipment****Code table 0 08 081*

Code figure	
0	Sensor
1	Transmitter
2	Receiver
3	Observing platform
4–62	Reserved
63	Missing value

0 08 082***Modification of sensor height to another value****Code table 0 08 082*

Code figure	
0	Sensor height is not modified
1	Sensor height is modified to standard level (see Note)
2–6	Reserved
7	Missing value

Note: If 0 08 082 = 1, the standard level is indicated by the Class 07 descriptor, which immediately follows. It is possible to indicate the real height of the sensor by preceding the descriptor by the relevant Class 07 descriptor.

0 08 083***Nominal value indicator****Flag table 0 08 083*

Bit No.	
1	Adjusted to or with respect to representative height of sensor above local ground (or deck of marine platform)
2	Adjusted to or with respect to representative height of sensor above water surface
3	Adjusted with respect to standard surface roughness
4	Adjusted with respect to wind speed
5	Adjusted with respect to temperature
6	Adjusted with respect to pressure
7	Adjusted with respect to humidity
8	Adjusted with respect to evaporation
9	Adjusted with respect to wetting losses
10–14	Reserved
All 15	Missing value

0 08 085***Beam identifier****Code table 0 08 085*

Code figure	
0	Fore beam
1	Mid beam
2	Aft beam
3–6	Reserved
7	Missing value

0 08 086***Vertical significance for NWP****Flag table 0 08 086*

Bit No.	
1	Model "ground" surface
2	Standard level
3	Tropopause level
4	Maximum wind level
5	Significant temperature level
6	Significant humidity level
7	Significant wind level
8	Vertically interpolated level (This should be set to 1 for points on the vertical profile that fall between the model's native vertical levels.)
9	Virtual station height
10	Level of best fit
11	Reserved
All 12	Missing value

0 08 087***Corner position of observation****Code table 0 08 087*

Code figure	
0	Upper left
1	Upper right
2	Lower right
3	Lower left
4–6	Reserved
7	Missing value

0 08 088***Map significance****Code table 0 08 088*

Code figure	
0	Top view (geographical longitude on x-axis and latitude on y-axis)
1	North–south view (transect with geographical longitude on x-axis and vertical height on y-axis)
2	East–west view (transect with geographical latitude on x-axis and vertical height on y-axis)
3–62	Reserved
63	Missing

0 08 091***Coordinates significance****Code table 0 08 091*

Code figure	
0	Satellite coordinates
1	Observation coordinates
2	Start of observation
3	End of observation
4	Horizontal centre of gravity of the observation
5	Vertical centre of gravity of the observation
6	Top of the observation
7	Bottom of the observation
8	Projection origin
9	Coordinates of true scale
10–254	Reserved
255	Missing value

0 08 092**Measurement uncertainty expression**

Code table 0 08 092

Code figure	
0	Standard uncertainty
<u>1</u>	<u>Combined standard uncertainty (see Note)</u>
2 –30	Reserved
31	Missing value

Note: For determining combined standard uncertainty see the Guide to the Expression of Uncertainty in Measurement [JCGM 100:2008] from BIPM.

0 08 093**Measurement uncertainty significance**

Code table 0 08 093

Code figure	
0	Total uncertainty
1	Systematic component of uncertainty
2	Random component of uncertainty
3–30	Reserved
31	Missing value

0 08 094**Method used to calculate the average daily temperature**

Code table 0 08 094

Code figure	
0	Average of maximum and minimum values: $T_m = (T_x + T_n)/2$ (see Note)
1	Average of the 8 observations taken every three hours
2	Average of the 24 hourly observations
3	Weighted average of 3 observations: $T_m = (aT_1 + bT_2 + cT_3)$ (see Note)
4	Weighted average of 3 observations and also maximum and minimum values: $T_m = (aT_1 + bT_2 + cT_3 + dT_x + eT_n)$ (see Note)
5	Automatic weather station complete integration from minute data
6	Average of the 4 observations taken every six hours
7–254	Reserved
255	Missing value

Note: The letters a, b, c, d and e generically represent the weight associated with the respective temperature T. The sub-index of T: 1, 2, 3, x and n represent the values measured at different times or maximum (x) or minimum (n) values.

0 08 095***Siting and measurement quality classification for temperature***

0	Reserved
1	1A
2	1B
3	1C
4	1D
5	Reserved
6	2A
7	2B
8	2C
9	2D
10	Reserved
11	3A
12	3B
13	3C
14	3D
15	Reserved
16	4A
17	4B
18	4C
19	4D
20	Reserved
21	5A
22	5B
23	5C
24	5D
25	Reserved
26	1
27	2
28	3
29	4
30	5
31	A
32	B
33	C
34	D
35–254	Reserved

Notes:

- (1) Code figures 1–24 are siting classifications according to the [Guide to Instruments and Methods of Observation](#) (WMO-No. 8), Volume I, Chapter 1, Annex 1.D and Annex 1.G.
- (2) Code figures 26–30 are siting classifications according to the [Guide to Instruments and Methods of Observation](#) (WMO-No. 8), Volume I, Chapter 1, Annex 1.D.
- (3) Code figures 31–34 are measurement quality classifications according to the [Guide to Instruments and Methods of Observation](#) (WMO-No. 8), Volume I, Chapter 1, Annex 1.G.
- (4) Annex 1.G is a new annex that will be part of an updated version of WMO-No. 8 to be published in mid-2022.

0 08 096***Siting and measurement quality classification for precipitation****Code table 0 08 096*

Code figure	
0	Reserved
1	1A
2	1B
3	1C
4	1D
5	Reserved
6	2A
7	2B
8	2C
9	2D
10	Reserved
11	3A
12	3B
13	3C
14	3D
15	Reserved
16	4A
17	4B
18	4C
19	4D
20	Reserved
21	5A
22	5B
23	5C
24	5D
25	Reserved
26	1
27	2
28	3
29	4
30	5
31	A
32	B
33	C
34	D
35–254	Reserved

Notes:

- (1) Code figures 1–24 are siting classifications and measurement quality classifications according to the [Guide to Instruments and Methods of Observation](#) (WMO-No. 8), Volume I, Chapter 1, Annex 1.D and Annex 1.G.
- (2) Code figures 26–30 are siting classifications according to the [Guide to Instruments and Methods of Observation](#) (WMO-No. 8), Volume I, Chapter 1, Annex 1.D.

- (3) Code figures 31–34 are measurement quality classifications according to the [Guide to Instruments and Methods of Observation](#) (WMO-No. 8), Volume I, Chapter 1, Annex 1.G.
- (4) Annex 1.G is a new annex that will be part of an updated version of WMO-No. 8 to be published in mid-2022.

0 08 097**Method used to calculate the average instrument temperature**Code table 0 08 097

<u>Code figure</u>	
<u>0</u>	<u>The average of six temperature sensors placed throughout the payload</u>
<u>1</u>	<u>Average of WF-band IFP and RFE sensors for channels 1 to 8</u>
<u>2</u>	<u>Average of G-band RFE sensor for channels 9 to 12</u>
<u>3-126</u>	<u>Reserved</u>
<u>127</u>	<u>Missing</u>

0 08 098**Source of temperature measurement**Code table 0 08 098

<u>Code figure</u>	
<u>0</u>	<u>On-board calibration target</u>
<u>1</u>	<u>Space view reflector</u>
<u>2</u>	<u>Main reflector</u>
<u>3</u>	<u>Racetrack</u>
<u>4</u>	<u>Sun shield</u>
<u>5</u>	<u>Rotating reflector</u>
<u>6-14</u>	<u>Reserved</u>
<u>15</u>	<u>Missing</u>

0 08 099**Sensing direction**Code table 0 08 099

<u>Code figure</u>	
<u>0</u>	<u>Nadir</u>
<u>1</u>	<u>Oblique</u>
<u>2-14</u>	<u>Reserved</u>
<u>15</u>	<u>Missing value</u>

0 10 063***Characteristic of pressure tendency****Code table 0 10 063*

Code figure		
0	Increasing, then decreasing; atmospheric pressure the same or higher than three hours ago	
1	Increasing, then steady; or increasing, then increasing more slowly	} Atmospheric pressure now higher than three hours ago
2	Increasing (steadily or unsteadily)	
3	Decreasing or steady, then increasing; or increasing, then increasing more rapidly	
4	Steady; atmospheric pressure the same as three hours ago	
5	Decreasing, then increasing; atmospheric pressure the same or lower than three hours ago	
6	Decreasing, then steady; or decreasing, then decreasing more slowly	} Atmospheric pressure now lower than three hours ago
7	Decreasing (steadily or unsteadily)	
8	Steady or increasing, then decreasing; or decreasing, then decreasing more rapidly	
9–14	Reserved	
15	Missing value	

Notes:

- (1) In reports from automatic stations, code figure 2 shall be used when tendency is positive, 7 when negative, and 4 when pressure is the same as three hours before.
- (2) In reports from tropical stations reporting 24-hour pressure changes, code figure 2 shall be used when tendency is positive, 7 when negative, and 4 when pressure is the same as 24 hours before.

0 10 064***SIGMET cruising level****Code table 0 10 064*

Code figure	
0	Subsonic
1	Transonic
2	Supersonic
3–6	Reserved
7	Missing value

0 11 030***Extended degree of turbulence****Code table 0 11 030*

Code figure

0	Nil	}	in cloud
1	Light		
2	Moderate		
3	Severe		
4	Nil	}	in clear air
5	Light		
6	Moderate		
7	Severe		
8	Nil	}	cloud/clear air not specified
9	Light		
10	Moderate		
11	Severe		
12	Extreme, in clear air		
13	Extreme, in cloud		
14	Extreme, cloud/clear air not specified		
15	Light, isolated moderate		
16	Light, occasional moderate		
17	Light, frequently moderate		
18	Moderate, isolated severe		
19	Moderate, occasional severe		
20	Moderate, frequently severe		
21	Severe, isolated extreme		
22	Severe, occasional extreme		
23	Severe, frequently extreme		
24–62	Reserved		
63	Missing value		

0 11 031***Degree of turbulence****Code table 0 11 031*

Code figure		
0	Nil	} in cloud
1	Light	
2	Moderate	
3	Severe	} in clear air
4	Nil	
5	Light	
6	Moderate	} cloud/clear air not specified
7	Severe	
8	Nil	
9	Light	} cloud/clear air not specified
10	Moderate	

Code table 0 11 031

Code figure	
11	Severe
12	Extreme, in clear air
13	Extreme, in cloud
14	Extreme, cloud/clear air not specified
15	Missing value

0 11 037***Turbulence index***

Code table 0 11 037

Code figure	Average value of eddy dissipation rate (ave) ($\text{m}^{2/3} \text{s}^{-1}$)	Peak value of eddy dissipation rate (peak) ($\text{m}^{2/3} \text{s}^{-1}$)
0	ave < 0.1	peak < 0.1
1	ave < 0.1	0.1 ≤ peak < 0.2
2	0.1 ≤ ave < 0.2	0.1 ≤ peak < 0.2
3	ave < 0.1	0.2 ≤ peak < 0.3
4	0.1 ≤ ave < 0.2	0.2 ≤ peak < 0.3
5	0.2 ≤ ave < 0.3	0.2 ≤ peak < 0.3
6	ave < 0.1	0.3 ≤ peak < 0.4
7	0.1 ≤ ave < 0.2	0.3 ≤ peak < 0.4
8	0.2 ≤ ave < 0.3	0.3 ≤ peak < 0.4
9	0.3 ≤ ave < 0.4	0.3 ≤ peak < 0.4
10	ave < 0.1	0.4 ≤ peak < 0.5
11	0.1 ≤ ave < 0.2	0.4 ≤ peak < 0.5
12	0.2 ≤ ave < 0.3	0.4 ≤ peak < 0.5
13	0.3 ≤ ave < 0.4	0.4 ≤ peak < 0.5
14	0.4 ≤ ave < 0.5	0.4 ≤ peak < 0.5
15	ave < 0.1	0.5 ≤ peak < 0.8
16	0.1 ≤ ave < 0.2	0.5 ≤ peak < 0.8
17	0.2 ≤ ave < 0.3	0.5 ≤ peak < 0.8
18	0.3 ≤ ave < 0.4	0.5 ≤ peak < 0.8
19	0.4 ≤ ave < 0.5	0.5 ≤ peak < 0.8
20	0.5 ≤ ave < 0.8	0.5 ≤ peak < 0.8
21	ave < 0.1	0.8 ≤ peak
22	0.1 ≤ ave < 0.2	0.8 ≤ peak
23	0.2 ≤ ave < 0.3	0.8 ≤ peak
24	0.3 ≤ ave < 0.4	0.8 ≤ peak
25	0.4 ≤ ave < 0.5	0.8 ≤ peak
26	0.5 ≤ ave < 0.8	0.8 ≤ peak
27	0.8 ≤ ave	0.8 ≤ peak
28	Nil	Nil
29–62	Reserved	Reserved
63	Missing value	Missing value

0 11 038***Time of occurrence of peak eddy dissipation rate****Code table 0 11 038*

Code figure	Minutes prior to observation time (min)
0	min < 1
1	1 ≤ min < 2
2	2 ≤ min < 3
3	3 ≤ min < 4
4	4 ≤ min < 5
5	5 ≤ min < 6
6	6 ≤ min < 7
7	7 ≤ min < 8
8	8 ≤ min < 9
9	9 ≤ min < 10
10	10 ≤ min < 11
11	11 ≤ min < 12
12	12 ≤ min < 13
13	13 ≤ min < 14
14	14 ≤ min < 15
15	No timing information available
16–30	Reserved
31	Missing value

0 11 039***Extended time of occurrence of peak eddy dissipation rate****Code table 0 11 039*

Code figure	Minutes prior to observation time (min)
0	min < 1
1	1 ≤ min < 2
2	2 ≤ min < 3
3	3 ≤ min < 4
4	4 ≤ min < 5
5	5 ≤ min < 6
6	6 ≤ min < 7
7	7 ≤ min < 8
8	8 ≤ min < 9
9	9 ≤ min < 10
10	10 ≤ min < 11
11	11 ≤ min < 12
12	12 ≤ min < 13
13	13 ≤ min < 14
14	14 ≤ min < 15

Code table 0 11 039

Code figure	Minutes prior to observation time (min)
15–59	As above to $59 \leq \text{min} < 60$
60	No timing information available
61–62	Reserved
63	Missing value

Provisional Copy
2023

0 13 038***Superadiabatic indicator****Code table 0 13 038*

Code figure	
0	Not superadiabatic
1	Superadiabatic
2	Reserved
3	Missing value

0 13 039***Terrain type (ice/snow)****Code table 0 13 039*

Code figure	
0	Sea ice
1	Snow on land
2–6	Reserved
7	Missing value

0 13 040***Surface flag****Code table 0 13 040*

Code figure	
0	Land
1	Reserved
2	Near coast
3	Ice
4	Possible ice
5	Ocean
6	Coast
7	Inland water (see Note)
8	Snow cover
9	Sea ice
10	Standing water
11	Snow
12–14	Reserved
15	Missing value

Note: Inland water includes rivers, lakes, wetlands and swamps.

0 13 041***Pasquill-Gifford stability category****Code table 0 13 041*

Code figure	
1	A
2	A – B
3	B
4	B – C
5	C
6	D
7	E
8	F
9	G
10–14	Reserved
15	Missing value

0 13 051***Frequency group, precipitation****Code table 0 13 051*

Code figure	
0	Smaller than any value in the 30-year period
1	In the first quintile
2	In the second quintile
3	In the third quintile
4	In the fourth quintile
5	In the fifth quintile
6	Greater than any value in the 30-year period
7–14	Reserved
15	Missing value

0 13 056***Character and intensity of precipitation****Code table 0 13 056*

Code figure	
0	No precipitation
1	Light intermittent
2	Moderate intermittent
3	Heavy intermittent
4	Very heavy intermittent
5	Light continuous
6	Moderate continuous
7	Heavy continuous

FM 94 BUFR

Code table 0 13 056

Code figure	
8	Very heavy continuous
9	Variable – alternatively light and heavy
10–14	Reserved
15	Missing value

0 13 057***Time of beginning or end of precipitation***

Code table 0 13 057

Code figure	
0	No precipitation
1	Within the last hour
2	1 to 2 hours ago
3	2 to 3 hours ago
4	3 to 4 hours ago
5	4 to 5 hours ago
6	5 to 6 hours ago
7	6 to 8 hours ago
8	8 to 10 hours ago
9	More than 10 hours ago
10–14	Reserved
15	Missing value

0 15 025***Type of pollutant****Code table 0 13 001*

Code figure	
0	Ozone
1–10	Reserved
11	Fine particulate matter (diameter < 2.5 microns)
12	Fine particulate matter (diameter < 10 microns)
13–14	Reserved
15	Missing value

Provisional Copy
2023

0 19 001***Type of synoptic feature****Code table 0 19 001*

Code figure	
0	Depression or low (extratropical)
1	Tropical depression
2	Tropical storm
3	Severe tropical storm
4	Typhoon
5–9	Reserved
10	Dust/sandstorm
11–62	Reserved
63	Missing value

Note: New local names for storm of various strengths shall be added as necessary.

0 19 008***Vertical extent of circulation****Code table 0 19 008*

Code figure	
0	Reserved
1	Shallow (top of circulation below 700-hPa level)
2	Medium (top between 700-hPa and 400-hPa level)
3	Deep (top above 400-hPa level)
4–6	Reserved
7	Missing value

0 19 010***Method for tracking the centre of synoptic feature****Code table 0 19 010*

Code figure	
1	Minimum value of sea-level pressure
2	Maximum value of 850 hPa relative vorticity
3–14	Reserved
15	Missing value

0 19 100***Time interval to calculate the movement of the tropical cyclone****Code table 0 19 100*

Code figure	
0–2	Not used
3	During the preceding 15 minutes
4	During the preceding 30 minutes
5	During the preceding 1 hour
6	During the preceding 2 hours
7	During the preceding 3 hours
8	During the preceding 6 hours
9	During a period of more than 6 hours
10	Undetermined
11–14	Not used
15	Missing value

0 19 101***Accuracy of the position of the centre of the tropical cyclone****Code table 0 19 101*

Code figure	
0	Reserved
1	Eye visible on radar scope, accuracy good (within 10 km)
2	Eye visible on radar scope, accuracy fair (within 30 km)
3	Eye visible on radar scope, accuracy poor (within 50 km)
4	Position of the centre within the area covered by the radar scope, determination by means of the spiral-band overlay, accuracy good (within 10 km)
5	Position of the centre within the area covered by the radar scope, determination by means of the spiral-band overlay, accuracy fair (within 30 km)
6	Position of the centre within the area covered by the radar scope, determination by means of the spiral-band overlay, accuracy poor (within 50 km)
7	Position of the centre outside the area covered by the radar scope, extrapolation by means of the spiral-band overlay
8–9	Reserved
10	Accuracy undetermined
11–14	Not used
15	Missing value

0 19 102***Shape and definition of the eye of the tropical cyclone****Code table 0 19 102*

Code figure	
0	Circular
1	Elliptical – the minor axis is at least 3/4 the length of the major axis
2	Elliptical – the minor axis is less than 3/4 the length of the major axis
3	Apparent double eye
4	Other shape
5	Ill defined
6	Undetermined
7	Missing value

} well defined

0 19 103***Diameter of major axis of the eye of the tropical cyclone****Code table 0 19 103*

Code figure	
0	Less than 5 km
1	5 to less than 10 km
2	10 to less than 15 km
3	15 to less than 20 km
4	20 to less than 25 km
5	25 to less than 30 km
6	30 to less than 35 km
7	35 to less than 40 km
8	40 to less than 50 km
9	50 km and greater
10	Undetermined
11–14	Not used
15	Missing value

0 19 104***Change in character of the eye during the 30 minutes****Code table 0 19 104*

Code figure	
0	Eye has first become visible during the past 30 minutes
1	No significant change in the characteristics or size of the eye
2	Eye has become smaller with no other significant change in characteristics
3	Eye has become larger with no other significant change in characteristics
4	Eye has become less distinct with no significant change in size
5	Eye has become less distinct and decreased in size
6	Eye has become less distinct and increased in size
7	Eye has become more distinct with no significant change in size
8	Eye has become more distinct and decreased in size
9	Eye has become more distinct and increased in size
10	Change in character and size of eye cannot be determined
11–14	Not used
15	Missing value

0 19 105***Distance between the end of spiral band and the centre****Code table 0 19 105*

Code figure	
0	0 to less than 100 km
1	100 to less than 200 km
2	200 to less than 300 km
3	300 to less than 400 km
4	400 to less than 500 km
5	500 to less than 600 km
6	600 to less than 800 km
7	800 km or more
8–9	Reserved
10	Doubtful or undetermined
11–14	Not used
15	Missing value

0 19 107

***Time interval over which the movement of the tropical cyclone
has been calculated***

Code table 0 19 107

Code figure	
0	Less than 1 hour
1	1 to less than 2 hours
2	2 to less than 3 hours
3	3 to less than 6 hours
4	6 to less than 9 hours
5	9 to less than 12 hours
6	12 to less than 15 hours
7	15 to less than 18 hours
8	18 to less than 21 hours
9	21 to less than 30 hours
10–14	Not used
15	Missing value

0 19 108

Accuracy of geographical position of the tropical cyclone

Code table 0 19 108

Code figure	
0	Cyclone centre within 10 km of the transmitted position
1	Cyclone centre within 20 km of the transmitted position
2	Cyclone centre within 50 km of the transmitted position
3	Cyclone centre within 100 km of the transmitted position
4	Cyclone centre within 200 km of the transmitted position
5	Cyclone centre within 300 km of the transmitted position
6	Cyclone centre undetermined
7	Missing value

0 19 109***Mean diameter of the overcast cloud of the tropical cyclone****Code table 0 19 109*

Code figure	
0	Less than 1° of latitude
1	1° to less than 2° of latitude
2	2° to less than 3° of latitude
3	3° to less than 4° of latitude
4	4° to less than 5° of latitude
5	5° to less than 6° of latitude
6	6° to less than 7° of latitude
7	7° to less than 8° of latitude
8	8° to less than 9° of latitude
9	9° of latitude or more
10	Undetermined
11–14	Not used
15	Missing value

0 19 110***Apparent 24-hour change in intensity of the tropical cyclone****Code table 0 19 110*

Code figure	
0	Much weakening
1	Weakening
2	No change
3	Intensification
4	Strong Intensification
5–8	Reserved
9	Not observed previously
10	Undetermined
11–14	Not used
15	Missing value

0 19 113***Cloud pattern type of the DT-number****Code table 0 19 113*

Code figure	Type
1	Curved Band
2	Shear
3	Eye
4	Banding Eye
5	Central Dense Overcast (CDO)
6	Embedded Centre
7	Centre Cold Cover (CCC)
8–14	Reserved
15	Missing value

0 19 117***Cloud picture type of the PT-number****Code table 0 19 117*

Code figure	Type
1	A (curved band)
2	B (CDO)
3	C (shear)
4–6	Reserved
7	Missing value

0 19 119***Type of the final T-number****Code table 0 19 119*

Code figure	Type
1	DT-number
2	PT-number
3	MET-number
4–6	Reserved
7	Missing value

0 20 003***Present weather****Code table 0 20 003*

Code figure	
00–49	<i>No precipitation at the station at the time of observation</i>
00–19	No precipitation, fog, ice fog (except for 11 and 12), duststorm, sandstorm, drifting or blowing snow at the station at the time of observation or, except for 09 and 17, during the preceding hour (see Note 4)
00–03	No meteors except photometeors
00	Cloud development not observed or not observable
01	Clouds generally dissolving or becoming less developed
02	State of sky on the whole unchanged
03	Clouds generally forming or developing
Characteristic change of the state of sky during the past hour	
04–09	Haze, dust, sand or smoke
04	Visibility reduced by smoke, e.g. veldt or forest fires, industrial smoke or volcanic ashes
05	Haze
06	Widespread dust in suspension in the air, not raised by wind at or near the station at the time of observation
07	Dust or sand raised by wind at or near the station at the time of observation, but no well-developed dust whirl(s) or sand whirl(s), and no duststorm or sandstorm seen; or, in the case of sea stations and coastal stations, blowing spray at the station
08	Well-developed dust whirl(s) or sand whirl(s) seen at or near the station during the preceding hour or at the same time of observation, but no duststorm or sandstorm
09	Duststorm or sandstorm within sight at the time of observation, or at the station during the preceding hour
10	Mist
11	Patches
12	More or less continuous
shallow fog or ice fog at the station, whether on land or sea, not deeper than about 2 metres on land or 10 metres at sea	
13	Lightning visible, no thunder heard
14	Precipitation within sight, not reaching the ground or the surface of the sea
15	Precipitation within sight, reaching the ground or the surface of the sea, but distant, i.e. estimated to be more than 5 km from the station
16	Precipitation within sight, reaching the ground or the surface of the sea, near to, but not at the station
17	Thunderstorm, but no precipitation at the time of observation
18	Squalls
19	Funnel cloud(s) (see Note 5)
at or within sight of the station during the preceding hour or at the time of observation	
20–29	Precipitation, fog, ice fog or thunderstorm at the station during the preceding hour but not at the time of observation
20	Drizzle (not freezing) or snow grains
21	Rain (not freezing)
22	Snow
23	Rain and snow or ice pellets
24	Freezing drizzle or freezing rain
25	Shower(s) of rain
not falling as shower(s)	

FM 94 BUFR
Code table 0 20 003

Code figure	
26	Shower(s) of snow, or of rain and snow
27	Shower(s) of hail, or of rain and hail (see Note 6)
28	Fog or ice fog
29	Thunderstorm (with or without precipitation)
30–39	Duststorm, sandstorm, drifting or blowing snow
30	Slight or moderate duststorm or sandstorm
31	
32	
33	Severe duststorm or sandstorm
34	
35	
36	Slight or moderate drifting snow
37	Heavy drifting snow
38	Slight or moderate blowing snow
39	Heavy blowing snow
40–49	Fog or ice fog at the time of observation
40	Fog or ice fog at a distance at the time of observation, but not at the station during the preceding hour, the fog or ice fog extending to a level above that of the observer
41	Fog or ice fog in patches
42	Fog or ice fog, sky visible
43	Fog or ice fog, sky invisible
44	Fog or ice fog, sky visible
45	Fog or ice fog, sky invisible
46	Fog or ice fog, sky visible
47	Fog or ice fog, sky invisible
48	Fog, depositing rime, sky visible
49	Fog, depositing rime, sky invisible
50–99	<i>Precipitation at the station at the time of observation</i>
50–59	Drizzle
50	Drizzle, not freezing, intermittent
51	Drizzle, not freezing, continuous
52	Drizzle, not freezing, intermittent
53	Drizzle, not freezing, continuous
54	Drizzle, not freezing, intermittent
55	Drizzle, not freezing, continuous
56	Drizzle, freezing, slight
57	Drizzle, freezing, moderate or heavy (dense)
58	Drizzle and rain, slight
59	Drizzle and rain, moderate or heavy
60–69	Rain
60	Rain, not freezing, intermittent
61	Rain, not freezing, continuous
62	Rain, not freezing, intermittent
63	Rain, not freezing, continuous
64	Rain, not freezing, intermittent
65	Rain, not freezing, continuous

FM 94 BUFR

Code table 0 20 003

Code figure	
66	Rain, freezing, slight
67	Rain, freezing, moderate or heavy
68	Rain or drizzle and snow, slight
69	Rain or drizzle and snow, moderate or heavy
70–79	Solid precipitation not in showers
70	Intermittent fall of snowflakes
71	Continuous fall of snowflakes
72	Intermittent fall of snowflakes
73	Continuous fall of snowflakes
74	Intermittent fall of snowflakes
75	Continuous fall of snowflakes
76	Diamond dust (with or without fog)
77	Snow grains (with or without fog)
78	Isolated star-like snow crystals (with or without fog)
79	Ice pellets
80–99	Showery precipitation, or precipitation with current or recent thunderstorm
80	Rain shower(s), slight
81	Rain shower(s), moderate or heavy
82	Rain shower(s), violent
83	Shower(s) of rain and snow mixed, slight
84	Shower(s) of rain and snow mixed, moderate or heavy
85	Snow shower(s), slight
86	Snow shower(s), moderate or heavy
87	Shower(s) of snow pellets or small hail, with or without – slight rain or rain and snow mixed
88	Shower(s) of snow pellets or small hail, with or without – moderate or heavy rain or rain and snow mixed
89	Shower(s) of hail, with or without rain or rain and snow – slight mixed, not associated with thunder
90	Shower(s) of hail, with or without rain or rain and snow – moderate or heavy mixed, not associated with thunder
91	Slight rain at time of observation
92	Moderate or heavy rain at time of observation
93	Slight snow, or rain and snow mixed or hail at time of observation
94	Moderate or heavy snow, or rain and snow mixed or hail at time of observation (see Note 6)
95	Thunderstorm, slight or moderate, without hail, but with rain and/or snow at time of observation (see Note 6)
96	Thunderstorm, slight or moderate, with hail at time of observation (see Note 6)
97	Thunderstorm, heavy, without hail, but with rain and/or snow at time of observation (see Note 6)
98	Thunderstorm combined with duststorm or sandstorm at time of observation
99	Thunderstorm, heavy, with hail at time of observation (see Note 6)
Present weather reported from an automatic weather station	
100	No significant weather observed
101	Clouds generally dissolving or becoming less developed during the past hour
102	State of sky on the whole unchanged during the past hour

FM 94 BUFR

Code table 0 20 003

Code figure	
103	Clouds generally forming or developing during the past hour
104	Haze or smoke, or dust in suspension in the air, visibility equal to, or greater than, 1 km
105	Haze or smoke, or dust in suspension in the air, visibility less than 1 km
106–109	Reserved
110	Mist
111	Diamond dust
112	Distant lightning
113–117	Reserved
118	Squalls
119	Reserved
Code figures 120–126 are used to report precipitation, fog (or ice fog) or thunderstorm at the station during the preceding hour but not at the time of observation	
120	Fog
121	PRECIPITATION
122	Drizzle (not freezing) or snow grains
123	Rain (not freezing)
124	Snow
125	Freezing drizzle or freezing rain
126	Thunderstorm (with or without precipitation)
127	BLOWING OR DRIFTING SNOW OR SAND
128	Blowing or drifting snow or sand, visibility equal to, or greater than, 1 km
129	Blowing or drifting snow or sand, visibility less than 1 km
130	FOG
131	Fog or ice fog in patches
132	Fog or ice fog, has become thinner during the past hour
133	Fog or ice fog, no appreciable change during the past hour
134	Fog or ice fog, has begun or become thicker during the past hour
135	Fog, depositing rime
136–139	Reserved
140	PRECIPITATION
141	Precipitation, slight or moderate
142	Precipitation, heavy
143	Liquid precipitation, slight or moderate
144	Liquid precipitation, heavy
145	Solid precipitation, slight or moderate
146	Solid precipitation, heavy
147	Freezing precipitation, slight or moderate
148	Freezing precipitation, heavy
149	Reserved
150	DRIZZLE
151	Drizzle, not freezing, slight
152	Drizzle, not freezing, moderate
153	Drizzle, not freezing, heavy
154	Drizzle, freezing, slight

Code table 0 20 003

Code figure	
155	Drizzle, freezing, moderate
156	Drizzle, freezing, heavy
157	Drizzle and rain, slight
158	Drizzle and rain, moderate or heavy
159	Reserved
160	RAIN
161	Rain, not freezing, slight
162	Rain, not freezing, moderate
163	Rain, not freezing, heavy
164	Rain, freezing, slight
165	Rain, freezing, moderate
166	Rain, freezing, heavy
167	Rain (or drizzle) and snow, slight
168	Rain (or drizzle) and snow, moderate or heavy
169	Reserved
170	SNOW
171	Snow, slight
172	Snow, moderate
173	Snow, heavy
174	Ice pellets, slight
175	Ice pellets, moderate
176	Ice pellets, heavy
177	Snow grains
178	Ice crystals
179	Reserved
180	SHOWER(S) OR INTERMITTENT PRECIPITATION
181	Rain shower(s) or intermittent rain, slight
182	Rain shower(s) or intermittent rain, moderate
183	Rain shower(s) or intermittent rain, heavy
184	Rain shower(s) or intermittent rain, violent
185	Snow shower(s) or intermittent snow, slight
186	Snow shower(s) or intermittent snow, moderate
187	Snow shower(s) or intermittent snow, heavy
188	Reserved
189	Hail
190	THUNDERSTORM
191	Thunderstorm, slight or moderate, with no precipitation
192	Thunderstorm, slight or moderate, with rain showers and/or snow showers
193	Thunderstorm, slight or moderate, with hail
194	Thunderstorm, heavy, with no precipitation
195	Thunderstorm, heavy, with rain showers and/or snow showers
196	Thunderstorm, heavy, with hail
197–198	Reserved
199	Tornado

Code table 0 20 003

Code figure	
Present weather (in addition to present weather report from either a manned or an automatic station)	
Deciles 200–209	
200–203	Not used
204	Volcanic ash suspended in the air aloft
205	Not used
206	Thick dust haze, visibility less than 1 km
207	Blowing spray at the station
208	Drifting dust (sand)
209	Wall of dust or sand in distance (like haboob)
Deciles 210–219	
210	Snow haze
211	Whiteout
212	Not used
213	Lightning, cloud to surface
214–216	Not used
217	Dry thunderstorm
218	Not used
219	Tornado cloud (destructive) at or within sight of the station during preceding hour or at the time of observation
Deciles 220–229	
220	Deposition of volcanic ash
221	Deposition of dust or sand
222	Deposition of dew
223	Deposition of wet snow
224	Deposition of soft rime
225	Deposition of hard rime
226	Deposition of hoar frost
227	Deposition of glaze
228	Deposition of ice crust (ice slick)
229	Not used
Deciles 230–239	
230	Duststorm or sandstorm with temperature below 0 °C
231–238	Not used
239	Blowing snow, impossible to determine whether snow is falling or not
Deciles 240–249	
240	Not used
241	Fog on sea
242	Fog in valleys
243	Arctic or Antarctic sea smoke
244	Steam fog (sea, lake or river)
245	Steam log (land)
246	Fog over ice or snow cover
247	Dense fog, visibility 60–90 m
248	Dense fog, visibility 30–60 m

Code table 0 20 003

Code figure	
249	Dense fog, visibility less than 30 m
Deciles 250–259	
250	Drizzle, rate of fall
251	
252	
253	
254	
255	
256	
257	
258	Not used
259	Drizzle and snow
Deciles 260–269	
260	Rain, rate of fall
261	
262	
263	
264	
265	
266	
267	
268–269	Not used
Deciles 270–279	
270	Snow, rate of fall
271	
272	
273	
274	
275	
276	
277	
278	Snow or ice crystal precipitation from a clear sky
279	Wet snow, freezing on contact
Deciles 280–299	
280	Precipitation of rain
281	Precipitation of rain, freezing
282	Precipitation of rain and snow mixed
283	Precipitation of snow
284	Precipitation of snow pellets or small hail
285	Precipitation of snow pellets or small hail, with rain
286	Precipitation of snow pellets or small hail, with rain and snow mixed
287	Precipitation of snow pellets or small hail, with snow
288	Precipitation of hail
289	Precipitation of hail, with rain

Code table 0 20 003

Code figure	
290	Precipitation of hail, with rain and snow mixed
291	Precipitation of hail, with snow
292	Shower(s) or thunderstorm over sea
293	Shower(s) or thunderstorm over mountains
294–299	Not used
300–507	Reserved
508	No significant phenomenon to report, present and past weather omitted
509	No observation, data not available, present and past weather omitted
510	Present and past weather missing, but expected
511	Missing value

Notes:

- (1) The middle portion of this code table (code figures 100–199) includes terms on several levels to cover simple and increasingly complex automatic stations.
- (2) Generic terms for weather (e.g. fog, drizzle) are intended for use at automatic stations capable of determining types of weather but no other information. Generic terms are included in the code table using all capital letters.
- (3) Code figures for generic precipitation (code figures 140–148) are arranged in order of increasing complexity. For example, a very simple station that can sense only the presence or absence of precipitation would use code figure 140 (precipitation). At the next level, an automatic station capable of sensing amount but not type would use code figure 141 or 142. An automatic station capable of sensing gross type (liquid, solid, freezing) and amount would use code figures 143–148. An automatic station capable of reporting actual types of precipitation (e.g. drizzle rain), but not the amount, would use the appropriate whole decile number (e.g. 150 for generic drizzle, 160 for generic rain).
- (4) The expression “at the station” refers to a land station or a ship.
- (5) “Funnel cloud(s)” refer to tornado clouds or waterspouts.
- (6) “Hail” refers to hail, small hail or snow pellets.

0 20 004/0 20 005

Past weather (1) and (2)

Code table 0 20 004/0 20 005

Code figure	
0	Cloud covering 1/2 or less of the sky throughout the appropriate period
1	Cloud covering more than 1/2 of the sky during part of the appropriate period and covering 1/2 or less during part of the period
2	Cloud covering more than 1/2 of the sky throughout the appropriate period
3	Sandstorm, duststorm or blowing snow
4	Fog or ice fog or thick haze
5	Drizzle
6	Rain
7	Snow, or rain and snow mixed
8	Shower(s)
9	Thunderstorm(s) with or without precipitation
10	No significant weather observed
11	VISIBILITY REDUCED (see Note)
12	Blowing phenomena, visibility reduced
13	FOG (see Note)
14	PRECIPITATION (see Note)

FM 94 BUFR*Code table 0 20 004/0 20 005*

Code figure	
15	Drizzle
16	Rain
17	Snow or ice pellets
18	Showers or intermittent precipitation
19	Thunderstorm
20–30	Reserved
31	Missing value

Note: The weather descriptions in code figures 10 to 19 are progressively complex, to accommodate the different levels of weather discrimination capability of various automatic stations. Stations having only basic sensing capability may use the lower code figures and basic generic descriptions (shown in capital letters). Stations with progressively higher discrimination capability shall use the more detailed descriptions (higher codes).

0 20 006***Flight rules****Code table 0 20 006*

Code figure	
0	Low instrument flight rules – Ceiling < 500 feet and/or visibility < 1 mile
1	Instrument flight rules – Ceiling < 1000 feet and/or visibility < 3 miles
2	Marginal visual flight rules – 1000 feet ≤ Ceiling < 3000 feet and/or 3 miles ≤ visibility < 5 miles
3	Visual flight rules – Ceiling ≥ 3000 feet and/or visibility ≥ 5 miles
4–6	Reserved
7	Missing value

0 20 008***Cloud distribution for aviation****Code table 0 20 008*

Code figure	
0	Sky clear
1	Few
2	Scattered
3	Broken
4	Overcast
5	Reserved
6	Scattered/broken (Many forecasts use scattered/broken or broken/overcast)
7	Broken/overcast followed by cloud type(s))
8	Isolated (Used on aviation charts to describe the cloud type Cb)
9	Isolated embedded (Used on aviation charts to describe the cloud type Cb)
10	Occasional (Used on aviation charts to describe the cloud type Cb)
11	Occasional embedded (Used on aviation charts to describe the cloud type Cb)
12	Frequent (Used on aviation charts to describe the cloud type Cb)
13	Dense (Used on aviation charts to describe cloud that would cause sudden changes in visibility (less than 1 000 m))
14	Layers

FM 94 BUFR

Code table 0 20 008

Code figure	
15	Obscured (OBSC)
16	Embedded (EMBD)
17	Frequent embedded
18–30	Reserved

0 20 009

General weather indicator (TAF/METAR)

Code table 0 20 009

Code figure	
0	Reserved
1	NSC Nil Significant Cloud
2	CAVOK
3	SKC Sky Clear
4	NSW Nil Significant Weather
5	<u>NCD No clouds detected</u>
56–14	Reserved
15	Missing value

0 20 011

Cloud amount

Code table 0 20 011

Code figure		
0	0	0
1	1 okta or less, but not zero	1/10 or less, but not zero
2	2 oktas	2/10 – 3/10
3	3 oktas	4/10
4	4 oktas	5/10
5	5 oktas	6/10
6	6 oktas	7/10 – 8/10
7	7 oktas or more, but not 8 oktas	9/10 or more, but not 10/10
8	8 oktas	10/10
9	Sky obscured by fog and/or other meteorological phenomena	
10	Sky partially obscured by fog and/or other meteorological phenomena	
11	Scattered	
12	Broken	
13	Few	
14	Reserved	
15	Cloud cover is indiscernible for reasons other than fog or other meteorological phenomena, or observation is not made (see Note 1)	

Notes:

- (1) For use of code figure 15, see Regulation 12.1.4.
- (2) "Clear" and "overcast" are coded by 0 and 8, respectively.

0 20 012**Cloud type**

Code table 0 20 012

Code figure	
0	Cirrus (Ci)
1	Cirrocumulus (Cc)
2	Cirrostratus (Cs)
3	Alto cumulus (Ac)
4	Altostratus (As)
5	Nimbostratus (Ns)
6	Stratocumulus (Sc)
7	Stratus (St)
8	Cumulus (Cu)
9	Cumulonimbus (Cb)
10	No C _H clouds
11	Cirrus fibratus, sometimes uncinus, not progressively invading the sky
12	Cirrus spissatus, in patches or entangled sheaves, which usually do not increase and sometimes seem to be the remains of the upper part of a cumulonimbus; or cirrus castellanus or floccus
13	Cirrus spissatus cumulonimbogenitus
14	Cirrus uncinus or fibratus, or both, progressively invading the sky; they generally thicken as a whole
15	Cirrus (often in bands) and cirrostratus, or cirrostratus alone, progressively invading the sky; they generally thicken as a whole, but the continuous veil does not reach 45 degrees above the horizon
16	Cirrus (often in bands) and cirrostratus, or cirrostratus alone, progressively invading the sky; they generally thicken as a whole; the continuous veil extends more than 45 degrees above the horizon, without the sky being totally covered
17	Cirrostratus covering the whole sky
18	Cirrostratus not progressively invading the sky and not entirely covering it
19	Cirrocumulus alone, or cirrocumulus predominant among the C _H clouds
20	No C _M clouds
21	Altostratus translucidus
22	Altostratus opacus or nimbostratus
23	Altocumulus translucidus at a single level
24	Patches (often lenticular) of altocumulus translucidus, continually changing and occurring at one or more levels
25	Altocumulus translucidus in bands, or one or more layers of altocumulus translucidus or opacus, progressively invading the sky; these altocumulus clouds generally thicken as a whole
26	Altocumulus cumulogenitus (or cumulonimbogenitus)
27	Altocumulus translucidus or opacus in two or more layers, or altocumulus opacus in a single layer, not progressively invading the sky, or altocumulus with altostratus or nimbostratus
28	Altocumulus castellanus or floccus
29	Altocumulus of a chaotic sky, generally at several levels
30	No C _L clouds
31	Cumulus humilis or cumulus fractus other than of bad weather, or both (see Note)
32	Cumulus mediocris or congestus, towering cumulus (TCU), with or without cumulus of species fractus or humilis or stratocumulus, all having their bases at the same level
33	Cumulonimbus calvus, with or without cumulus, stratocumulus or stratus

Code table 0 20 012

Code figure	
34	Stratocumulus cumulogenitus
35	Stratocumulus other than stratocumulus cumulogenitus
36	Stratus nebulosus or stratus fractus other than of bad weather, or both
37	Stratus fractus or cumulus fractus of bad weather, or both (pannus), usually below altostratus or nimbostratus
38	Cumulus and stratocumulus other than stratocumulus cumulogenitus, with bases at different levels
39	Cumulonimbus capillatus (often with an anvil), with or without cumulonimbus calvus, cumulus, stratocumulus, stratus or pannus
40	C _H
41	C _M
42	C _L
43	Clear
44	Liquid water
45	Supercooled liquid water
46	Mixed phase
47	Optically thick ice
48	Optically thin ice
49	Multilayered ice
50–58	Reserved
59	Cloud not visible owing to darkness, fog, duststorm, sandstorm, or other analogous phenomena
60	C _H clouds invisible owing to darkness, fog, blowing dust or sand, or other similar phenomena, or because of a continuous layer of lower clouds
61	C _M clouds invisible owing to darkness, fog, blowing dust or sand, or other similar phenomena, or because of continuous layer of lower clouds
62	C _L clouds invisible owing to darkness, fog, blowing dust or sand, or other similar phenomena
63	Missing value

Note: "Bad weather" denotes the conditions which generally exist during precipitation and a short time before and after.

0 20 017**Cloud top description**

Code table 0 20 017

Code figure	
0	Isolated cloud fragments of clouds
1	Continuous cloud
2	Broken cloud – small breaks flat tops
3	Broken cloud – large breaks
4	Continuous cloud
5	Broken cloud – small breaks undulating tops
6	Broken cloud – large breaks
7	Continuous or almost continuous waves with towering clouds above the top of the layer

} flat tops

} undulating tops

FM 94 BUFR*Code table 0 20 017*

Code figure	
8	Groups of waves with towering clouds above the top of the layer
9	Two or more layers at different levels
10–14	Reserved
15	Missing value

0 20 018***Tendency of runway visual range****Code table 0 20 018*

Code figure	
0	Increasing (U)
1	Decreasing (D)
2	No distinct change (N)
3	Missing value

0 20 021***Type of precipitation****Flag table 0 20 021*

Bit No.	
1	Precipitation – unknown type
2	Liquid precipitation not freezing
3	Liquid freezing precipitation
4	Drizzle
5	Rain
6	Solid precipitation
7	Snow
8	Snow grains
9	Snow pellets
10	Ice pellets
11	Ice crystals
12	Diamond dust
13	Small hail
14	Hail
15	Glaze
16	Rime
17	Soft rime
18	Hard rime
19	Clear ice
20	Wet snow
21	Hoar frost
22	Dew

FM 94 BUFR*Flag table 0 20 021*

Bit No.	
23	White dew
24–29	Reserved
All 30	Missing value

Note: Mixed precipitation is indicated by setting to one the bits of all the observed single types of precipitation.

0 20 022***Character of precipitation****Code table 0 20 022*

Code figure	
0	No precipitation
1	Continuous
2	Intermittent
3	Shower
4	Not reaching ground
5	Deposition
6–14	Reserved
15	Missing value

0 20 023***Other weather phenomena****Flag table 0 20 023*

Bit No.	
1	Dust/sand whirl
2	Squalls
3	Sandstorm
4	Duststorm
5	Lightning – cloud to surface
6	Lightning – cloud to cloud
7	Lightning – distant
8	Thunderstorm
9	Funnel cloud not touching surface
10	Funnel cloud touching surface
11	Spray
12	Waterspout
13	Wind shear
14	Dust devils
15–17	Reserved
All 18	Missing value

0 20 024***Intensity of phenomena****Code table 0 20 024*

Code figure	
0	No phenomena
1	Light
2	Moderate
3	Heavy
4	Violent
5	Severe
6	Very severe
7	Missing value

0 20 025***Obscuration****Flag table 0 20 025*

Bit No.	
1	Fog
2	Ice fog
3	Steam fog
4–6	Reserved
7	Mist
8	Haze
9	Smoke
10	Volcanic ash
11	Dust
12	Sand
13	Snow
14	Cloud
15	Precipitation
16	Impossible to determine whether snow is falling or not
17–20	Reserved
All 21	Missing value

0 20 026***Character of obscuration****Code table 0 20 026*

Code figure	
0	No change
1	Shallow
2	Patches
3	Partial
4	Freezing
5	Low drifting
6	Blowing

Code table 0 20 026

Code figure	
7	Increasing
8	Decreasing
9	In suspension in the air
10	Wall
11	Dense
12	Whiteout
13	Drifting and blowing
14	Reserved
15	Missing value

0 20 027***Phenomena occurrence***

Flag table 0 20 027

Bit No.	
1	At time of observation
2	In past hour
3	In time period for past weather W_1W_2
4	In time period specified
5	Reserved
6	Below station level
7	At the station (see Note 2)
8	In the vicinity (see Note 3)
All 9	Missing value

Notes:

- (1) Phenomenon in this flag table means any phenomenon, including precipitation and obscuration.
- (2) In conjunction with the observation of waterspouts or funnel clouds, i.e., within 3 km of the station.
- (3) In conjunction with the observation of waterspouts or funnel clouds, i.e., more than 3 km from the station.

0 20 028***Expected change in intensity***

Code table 0 20 028

Code figure	
0	No change (NC)
1	Forecast to weaken (WKN)
2	Forecast to intensify (INTSF)
3–6	Reserved
7	Missing value

0 20 029***Rain flag****Code table 0 20 029*

Code figure	
0	No rain
1	Rain
2	Reserved
3	Missing value

0 20 032***Rate of ice accretion (estimated)****Code table 0 20 032*

Code figure	
0	Ice not building up
1	Ice building up slowly
2	Ice building up rapidly
3	Ice melting or breaking up slowly
4	Ice melting or breaking up rapidly
5–6	Reserved
7	Missing value

0 20 033***Cause of ice accretion****Flag table 0 20 033*

Bit No.	
1	Icing from ocean spray
2	Icing from fog
3	Icing from rain
All 4	Missing value

0 20 034**Sea-ice concentration**

Code table 0 20 034

Code figure	
0	No sea ice in sight
1	Ship in open lead more than 1.0 nautical mile wide, or ship in fast ice with boundary beyond limit of visibility
2	Sea ice present in concentrations less than 3/10 (3/8), open water or very open pack ice
3	4/10 to 6/10 (3/8 to less than 6/8), open pack ice
4	7/10 to 8/10 (6/8 to less than 7/8), close pack ice
5	9/10 or more, but not 10/10 (7/8 to less than 8/8), very close pack ice
6	Strips and patches of pack ice with open water between
7	Strips and patches of close or very close pack ice with areas of lesser concentration between
8	Fast ice with open water, very open or open pack ice to seaward of the ice boundary
9	Fast ice with close or very close pack ice to seaward of the boundary
10–13	Reserved
14	Unable to report, because of darkness, lack of visibility, or because ship is more than 0.5 nautical mile away from ice edge
15–30	Reserved
31	Missing value

Sea ice concentration is uniform in the observation area

Sea ice concentration is not uniform in the observation area

Ship in ice or within 0.5 nautical mile of ice edge

0 20 035**Amount and type of ice**

Code table 0 20 035

Code figure	
0	No ice of land origin
1	1–5 icebergs, no growlers or bergy bits
2	6–10 icebergs, no growlers or bergy bits
3	11–20 icebergs, no growlers or bergy bits
4	Up to and including 10 growlers and bergy bits – no icebergs
5	More than 10 growlers and bergy bits – no icebergs
6	1–5 icebergs, with growlers and bergy bits
7	6–10 icebergs, with growlers and bergy bits
8	11–20 icebergs, with growlers and bergy bits
9	More than 20 icebergs, with growlers and bergy bits – a major hazard to navigation

Code table 0 20 035

Code figure	
10–13	Reserved
14	Unable to report, because of darkness, lack of visibility or because only sea ice is visible
15	Missing value

0 20 036***Ice situation***

Code table 0 20 036

Code figure	
0	Ship in open water with floating ice in sight
1	Ship in easily penetrable ice; conditions improving
2	Ship in easily penetrable ice; conditions not changing
3	Ship in easily penetrable ice; conditions worsening
4	Ship in ice difficult to penetrate; conditions improving
5	Ship in ice difficult to penetrate; conditions not changing
6	Ship in ice difficult to penetrate and conditions worsening. Ice forming and floes freezing together
7	Ship in ice difficult to penetrate and conditions worsening. Ice under slight pressure
8	Ship in ice difficult to penetrate and conditions worsening. Ice under moderate or severe pressure
9	Ship in ice difficult to penetrate and conditions worsening. Ship beset
10–29	Reserved
30	Unable to report, because of darkness or lack of visibility
31	Missing value

0 20 037***Ice development***

Code table 0 20 037

Code figure	
0	New ice only (frazil ice, grease ice, slush, shuga)
1	Nilas or ice rind, less than 10 cm thick
2	Young ice (grey ice, grey-white ice), 10–30 cm thick
3	Predominantly new and/or young ice with some first-year ice
4	Predominantly thin first-year ice with some new and/or young ice
5	All thin first-year ice (30–70 cm thick)
6	Predominantly medium first-year ice (70–120 cm thick) and thick first-year ice (>120 cm thick) with some thinner (younger) first-year ice
7	All medium and thick first-year ice
8	Predominantly medium and thick first-year ice with some old ice (usually more than 2 metres thick)
9	Predominantly old ice
10–29	Reserved
30	Unable to report, because of darkness, lack of visibility or because only ice of land origin is visible or because ship is more than 0.5 nautical mile away from ice edge
31	Missing value

0 20 040***Evolution of drift snow****Code table 0 20 040*

Code figure	
0	Drift snow ended before the hour of observation
1	Intensity diminishing
2	No change
3	Intensity increasing
4	Continues, apart from interruption lasting less than 30 minutes
5	General drift snow has become drift snow near the ground
6	Drift snow near the ground has become general drift snow
7	Drift snow has started again after an interruption of more than 30 minutes
8–14	Reserved
15	Missing value

0 20 041***Airframe icing****Code table 0 20 041*

Code figure	
0	No icing
1	Light icing
2	Light icing in cloud
3	Light icing in precipitation
4	Moderate icing
5	Moderate icing in cloud
6	Moderate icing in precipitation
7	Severe icing
8	Severe icing in cloud
9	Severe icing in precipitation
10	Trace of icing
11	Trace of icing in cloud
12	Trace of icing in precipitation
13–14	Reserved
15	Missing value

0 20 042***Airframe icing present****Code table 0 20 042*

Code figure	
0	No icing
1	Icing present
2	Reserved
3	Missing value

0 20 045***Supercooled large droplet (SLD) conditions****Code table 0 20 045*

Code figure	
0	No SLD conditions present
1	SLD conditions present
2	Reserved
3	Missing value

0 20 048***Evolution of feature****Code table 0 20 048*

Code figure	
0	Stability
1	Diminution
2	Intensification
3	Unknown
4–14	Reserved
15	Missing value

0 20 050***Cloud index****Code table 0 20 050*

Code figure	
0	Reserved
1	1st low cloud
2	2nd low cloud
3	3rd low cloud
4	1st medium cloud
5	2nd medium cloud
6	3rd medium cloud
7	1st high cloud
8	2nd high cloud
9–254	Reserved
255	Missing value

0 20 055***State of sky in the tropics****Code table 0 20 055*

Code figure	
0	Cumulus, if any, are quite small; generally less than 2/8 coverage, except on windward slopes of elevated terrain; average width of cloud is at least as great as its vertical thickness
1	Cumulus of intermediate size with cloud cover less than 5/8; average cloud width is more than its vertical thickness; towers are vertical with little or no evidence of precipitation, except along slopes of elevated terrain; a general absence of middle and upper clouds
2	Swelling Cumulus with rapidly growing tall turrets which decrease in size with height and whose tops tend to separate from the longer cloud body and evaporate within minutes of the separation
3	Swelling Cumulus with towers having a pronounced tilt in a downwind direction; vertical cloud thickness is more than one and a half times that of its average width
4	Swelling Cumulus with towers having a pronounced tilt in an upwind direction; vertical cloud thickness is more than one and a half times that of its average width
5	Tall Cumulus congestus with vertical thickness more than twice the average width; not organized in clusters or lines; one or more layers of clouds extend out from the cloud towers, although no continuous cloud layers exist (see Note)
6	Isolated Cumulonimbus or large clusters of Cumulus turrets separated by wide areas in which clouds are absent; cloud bases are generally dark with showers observed in most cells; some scattered middle and upper clouds may be present; individual Cumulus cells are one to two times higher than they are wide
7	Numerous Cumulus extending through the middle troposphere with broken to overcast sheets of middle clouds and/or Cirrostratus; Cumulus towers do not decrease generally in size with height; ragged dark cloud bases with some showers present
8	Continuous dense middle clouds and/or Cirrostratus cloud sheets with some large isolated Cumulonimbus or Cumulus congestus clouds penetrating these sheets; light rain occasionally observed from the Altostratus; Cumulonimbus bases ragged and dark with showers visible (see Note)
9	Continuous sheets of middle clouds and/or Cirrostratus with Cumulonimbus and Cumulus congestus in organized lines or cloud bands; rain is generally observed from Altostratus sheets and heavy showers from Cumulonimbus; wind has a squally character
10	State of sky unknown or not described by any of the above
11–14	Reserved
15	Missing value

Note: In the event of obscuration of clouds due to heavy rain, the observer should use code 5 or 8. Code 5 should be used if the rain is localized or is brief in duration; Code 8 should be used if the rain is widespread or lasts for longer periods of time.

0 20 056***Cloud phase****Code table 0 20 056*

Code figure	
0	Unknown
1	Water
2	Ice
3	Mixed
4	Clear
5	Supercooled liquid water
6	Reserved
7	Missing value

0 20 062***State of the ground (with or without snow)****Code table 0 20 062*

Code figure	
0	Surface of ground dry (without cracks and no appreciable amount of dust or loose sand)
1	Surface of ground moist
2	Surface of ground wet (standing water in small or large pools on surface)
3	Flooded
4	Surface of ground frozen
5	Glaze on ground
6	Loose dry dust or sand not covering ground completely
7	Thin cover of loose dry dust or sand covering ground completely
8	Moderate or thick cover of loose dry dust or sand covering ground completely
9	Extremely dry with cracks
10	Ground predominantly covered by ice
11	Compact or wet snow (with or without ice) covering less than one half of the ground
12	Compact or wet snow (with or without ice) covering at least one half of the ground but ground not completely covered
13	Even layer of compact or wet snow covering ground completely
14	Uneven layer of compact or wet snow covering ground completely
15	Loose dry snow covering less than one half of the ground
16	Loose dry snow covering at least one half of the ground but ground not completely covered
17	Even layer of loose dry snow covering ground completely
18	Uneven layer of loose dry snow covering ground completely
19	Snow covering ground completely; deep drifts

without snow
or measurable
ice cover

with snow or
measurable ice
cover

Code table 0 20 062

Code figure	
20–30	Reserved
31	Missing value

Notes:

- (1) The definitions in code numbers 0 to 2 and 4 apply to representative bare ground and numbers 3, 5 to 9 and 10 to 19 to an open representative area.
- (2) In all instances the highest code figures applicable are to be reported.
- (3) In the above code table, whenever reference is made to ice, it also includes solid precipitation other than snow.

0 20 063***Special phenomena***

Code table 0 20 063

Code figure	
0	Reserved
1	Highest wind speed gusts greater than 11.5 m/s
2	Highest mean wind speed greater than 17.5 m/s
3–6	Reserved
7	Visibility greater than 100 000 m
8–9	Reserved
<i>10–19 Mirage</i>	
10	Mirage – No specification
11	Mirage – Image of distant object raised (looming)
12	Mirage – Image of distant object raised clear above the horizon
13	Mirage – Inverted image of distant object
14	Mirage – Complex, multiple images of distant object (images not inverted)
15	Mirage – Complex, multiple images of distant object (some images being inverted)
16	Mirage – Sun or moon seen appreciably distorted
17	Mirage – Sun visible, although astronomically below the horizon
18	Mirage – Moon visible, although astronomically below the horizon
19	Reserved
<i>20–22 Day darkness, worst in direction specified</i>	
20	Day darkness, bad, worst in direction specified
21	Day darkness, very bad, worst in direction specified
22	Day darkness, black, worst in direction specified
23–30	Reserved
<i>31–39 Coloration and/or convergence of clouds associated with a tropical disturbance</i>	
31	Slight coloration of clouds at sunrise associated with a tropical disturbance
32	Deep-red coloration of clouds at sunrise associated with a tropical disturbance
33	Slight coloration of clouds at sunset associated with a tropical disturbance
34	Deep-red coloration of clouds at sunset associated with a tropical disturbance
35	Convergence of CH clouds at a point below 45° forming or increasing and associated with a tropical disturbance
36	Convergence of CH clouds at a point above 45° forming or increasing and associated with a tropical disturbance

Code table 0 20 063

Code figure	
37	Convergence of CH clouds at a point below 45° dissolving or diminishing and associated with a tropical disturbance
38	Convergence of CH clouds at a point above 45° dissolving or diminishing and associated with a tropical disturbance
39	Reserved
	<i>40–43 Hoar frost or coloured precipitation</i>
40	Hoar frost on horizontal surfaces
41	Hoar frost on horizontal and vertical surfaces
42	Precipitation containing sand or desert dust
43	Precipitation containing volcanic ash
44–49	Reserved
	<i>50–59 Nature and/or type of squall</i>
50	Calm or light wind followed by a squall
51	Calm or light wind followed by a succession of squalls
52	Gusty weather followed by a squall
53	Gusty weather followed by a succession of squalls
54	Squall followed by gusty weather
55	General gusty weather with squall at intervals
56	Squall approaching station
57	Line squall
58	Squall with drifting or blowing dust or sand
59	Line squall with drifting or blowing dust or sand
	<i>60–69 Variation of temperature during the period specified, associated with glaze or rime</i>
60	Temperature steady
61	Temperature falling, without going below 0 °C
62	Temperature rising, without going above 0 °C
63	Temperature falling to a value below 0 °C
64	Temperature rising to a value above 0 °C
65	Irregular variation, oscillations of temperature passing through 0 °C
66	Irregular variation, oscillations of temperature not passing through 0 °C
67	Variation of temperature not observed
68	Not allocated
69	Variation of temperature unknown owing to lack of thermograph
	<i>70–79 Variation of visibility during the period specified</i>
70	Visibility has not varied (sun visible) towards direction specified (see Note)
71	Visibility has not varied (sun invisible) towards direction specified (see Note)
72	Visibility has increased (sun visible) towards direction specified (see Note)
73	Visibility has increased (sun invisible) towards direction specified (see Note)
74	Visibility has decreased (sun visible) towards direction specified (see Note)
75	Visibility has decreased (sun invisible) towards direction specified (see Note)
76	Fog coming from direction specified
77	Fog has lifted, without dissipating
78	Fog has dispersed without regard to direction
79	Moving patches or banks of fog
	<i>80–89 Optical phenomena</i>
80	Brocken spectre
81	Rainbow
82	Solar or lunar halo

Code table 0 20 063

Code figure	
83	Parhelia or anthelia
84	Sun pillar
85	Corona
86	Twilight glow
87	Twilight glow on the mountains (Alpenglühen)
88	Mirage
89	Zodiacal light
90	St Elmo's fire
91–1022	Reserved
1023	Missing value

Note: "Sun" can also be sky (if sun is low), or moon or stars at night.

0 20 071***Accuracy of fix and rate of atmospheric***

Code table 0 20 071

Code figure	Accuracy of fix (estimated error)	Repetition rate
0	No assessment	No assessment
1	Less than 50 km	Less than 1 per second
2	Between 50 and 200 km	Less than 1 per second
3	More than 200 km	Less than 1 per second
4	Less than 50 km	1 or more per second
5	Between 50 and 200 km	1 or more per second
6	More than 200 km	1 or more per second
7	Less than 50 km	Rate so rapid number cannot be counted
8	Between 50 and 200 km	Rate so rapid number cannot be counted
9	More than 200 km	Rate so rapid number cannot be counted
10–14	Reserved	
15	Missing value	

0 20 085***General condition of runway***

Code table 0 20 085

Code figure	
0	Cleared (CLRD//)
1	All runways closed (SNOCLO)
2–14	Reserved
15	Missing value

0 20 086***Runway deposits****Code table 0 20 086*

Code figure	
0	Clear and dry
1	Damp
2	Wet with water patches
3	Rime and frost covered (depth normally less than 1 mm)
4	Dry snow
5	Wet snow
6	Slush
7	Ice
8	Compacted or rolled snow
9	Frozen ruts or ridges
10–14	Reserved
15	Missing or not reported (e.g. due to runway clearance in progress)

0 20 087***Runway contamination****Code table 0 20 087*

Code figure	
0	Reserved
1	Less than 10% of runway covered
2	11% to 25% of runway covered
3–4	Reserved
5	26% to 50% of runway covered
6–8	Reserved
9	51% to 100% of runway covered
10–14	Reserved
15	Missing or not reported (e.g. due to runway clearance in progress)

0 20 089***Runway friction coefficient****Code table 0 20 089*

Code figure	
0	0.00
1	0.01
2–88	0.02...0.88
89	0.89
90	0.90
91	Braking action poor
92	Braking action medium to poor
93	Braking action medium
94	Braking action medium to good
95	Braking action good

FM 94 BUFR*Code table 0 20 089*

Code figure	
96–98	Reserved
99	Unreliable
100–126	Reserved
127	Missing, not reported and/or runway not operational

0 20 090***Special clouds****Code table 0 20 090*

Code figure	
0	Reserved
1	Nacreous clouds
2	Noctilucent clouds
3	Clouds from waterfalls
4	Clouds from fires
5	Clouds from volcanic eruptions
6–14	Reserved
15	Missing value

0 20 101***Locust (acridian) name****Code table 0 20 101*

Code figure	
0	Reserved
1	Schistocerca gregaria
2	Locusta migratoria
3	Nomadacris septemfasciata
4	Oedaleus senegalensis
5	Anracridium spp
6	Other locusts
7	Other grasshoppers
8	Other crickets
9	Spodoptera exempta
10–14	Reserved
15	Missing value

0 20 102***Locust (maturity) colour****Code table 0 20 102*

Code figure	
0	Green
1	Green or black
2	Black
3	Yellow and black
4	Straw/grey
5	Pink
6	Dark red/brown
7	Mixed red and yellow
8	Yellow
9	Other
10–14	Reserved
15	Missing value

0 20 103***Stage of development of locusts****Code table 0 20 103*

Code figure	
0	Hoppers (nymphs, larvae), stage 1
1	Hoppers (nymphs, larvae), stage 2 or mixed 1, 2 instars (stages)
2	Hoppers (nymphs, larvae), stage 3 or mixed 2, 3 instars
3	Hoppers (nymphs, larvae), stage 4 or mixed 3, 4 instars
4	Hoppers (nymphs, larvae), stage 5 or mixed 4, 5 instars
5	Hoppers (nymphs, larvae), stage mixed, all or many instars
6	Fledglings (wings too soft for sustained flight)
7	Immature adults
8	Mixed maturity adults
9	Mature adults
10–14	Reserved
15	Missing value

0 20 104***Organization state of swarm or band of locusts****Code table 0 20 104*

Code figure	
0	Hoppers only, mainly in bands or clusters
1	Winged adults in the vicinity more than 10 kilometres from point of observation
2	Locusts in flight, a few seen at the station
3	Locusts at the station, most of them on the ground
4	Locusts, some on ground and others in flight at a height less than 10 metres
5	Locusts, some on ground and others in flight at a height greater than 10 metres
6	Locusts, most in flight at a height less than 10 metres

Code table 0 20 104

Code figure	
7	Locusts, most in flight at a height greater than 10 metres
8	Locusts, all over inflicting severe damage to vegetation, no extermination operation
9	Locusts, all over inflicting severe damage to vegetation, extermination operation in progress
10–14	Reserved
15	Missing value

0 20 105***Size of swarm or band of locusts and duration of passage of swarm***

Code table 0 20 105

Code figure	
When 0 20 104 (organization state of swarm or band of locusts) = 0	
0	Reserved
1	Area covered by isolated bands < 10 m ²
2	Area covered by isolated bands 10 – 100 m ²
3	Area covered by isolated bands 100 – 1000 m ²
4	Area covered by isolated bands 1 000 – 10000 m ²
5	Area covered by isolated bands 1 – 10 ha
6	Area covered by isolated bands > 10 ha
7	Area covered by dispersed bands < 100 km ²
8	Area covered by dispersed bands 100 – 1000 km ²
9	Area covered by dispersed bands > 1000 km ²
10–14	Reserved
15	Missing value
When 0 20 104 (organization state of swarm or band of locusts) = 1 to 9	
0	Small swarm less than 1 km ² or adults in ground, tens or hundreds of individuals visible simultaneously, duration of passage less than 1 hour ago
1	Small swarm less than 1 km ² or adults in ground, tens or hundreds of individuals visible simultaneously, duration of passage 1 to 6 hours ago
2	Small swarm less than 1 km ² or adults in ground, tens or hundreds of individuals visible simultaneously, duration of passage over 6 hours ago
3	Medium swarm or scattered adults, several visible simultaneously, duration of passage less than 1 hour ago
4	Medium swarm or scattered adults, several visible simultaneously, duration of passage 1 to 6 hours ago
5	Medium swarm or scattered adults, several visible simultaneously, duration of passage over 6 hours ago
6	Large swarm or isolated adults, seen singly, duration of passage less than 1 hour ago
7	Large swarm or isolated adults, seen singly, duration of passage 1 to 6 hours ago
8	Large swarm or isolated adults, seen singly, duration of passage over 6 hours ago
9	More than one swarm of locusts
10	Size of swarm and/or duration of passage not determined owing to darkness or similar phenomena
11–14	Reserved
15	Missing value

0 20 106***Locust population density****Code table 0 20 106*

Code figure	
0	Reserved
1	Thin density swarm (swarm visible only when near enough for individual locusts to be discerned)
2	Medium density swarm
3	Dense swarm (obscuring nearby features, e.g. trees)
4	Isolated hoppers seen singly
5	Scattered hoppers, several visible simultaneously
6–14	Reserved
15	Missing value

0 20 107***Direction of movements of locust swarm****Code table 0 20 107*

Code figure	
0	Reserved
1	Generally in the direction NE
2	Generally in the direction E
3	Generally in the direction SE
4	Generally in the direction S
5	Generally in the direction SW
6	Generally in the direction W
7	Generally in the direction NW
8	Generally in the direction N
9	Specific direction indeterminable
10–14	Reserved
15	Missing value

0 20 108***Extent of vegetation****Code table 0 20 108*

Code figure	
0	Bare ground
1	Dry, presence of few and isolated shrubs
2	Sparse vegetation (sprouting)
3	Dense vegetation (sprouting)
4	Sparse vegetation (growing)
5	Dense vegetation (growing)
6	Sparse vegetation in flower
7	Dense vegetation in flower
8–14	Reserved
15	Missing value

0 20 119***Lightning discharge polarity****Code table 0 20 119*

Code figure	
0	Not defined
1	Positive
2	Negative
3	Missing value

0 20 124***Lightning stroke or flash****Code table 0 20 124*

Code figure	
0	Not defined
1	Lightning stroke
2	Lightning flash, by manual observation, or if equipment insensitive to stroke resolution
3	Missing value

0 20 136***Supplementary cloud type****Code table 0 20 136*

Code figure	
<i>0–7 Nature of clouds of vertical development (C_a – Code table 0531)</i>	
0	Isolated cumulus humilis and/or cumulus mediocris
1	Numerous cumulus humilis and/or cumulus mediocris
2	Isolated cumulus congestus
3	Numerous cumulus congestus
4	Isolated cumulonimbus
5	Numerous cumulonimbus
6	Isolated cumulus and cumulonimbus
7	Numerous cumulus and cumulonimbus
8–9	Reserved
<i>10–19 Orographic clouds (C_o – Code table 0561)</i>	
10	Reserved
11	Isolated orographic clouds, pileus, incus, forming
12	Isolated orographic clouds, pileus, incus, not changing
13	Isolated orographic clouds, pileus, incus, dissolving
14	Irregular banks of orographic cloud, föhn bank, etc., forming
15	Irregular banks of orographic cloud, föhn bank, etc., not changing
16	Irregular banks of orographic cloud, föhn bank, etc., dissolving
17	Compact layer of orographic cloud, föhn bank, etc., forming
18	Compact layer of orographic cloud, föhn bank, etc., not changing
19	Compact layer of orographic cloud, föhn bank, etc., dissolving
<i>20–29 Cloud conditions over mountains and passes (N_m – Code table 2745)</i>	

} of vertical development

Code table 0 20 136

Code figure	
20	All mountains open, only small amounts of cloud present
21	Mountains partly covered with detached clouds (not more than half the peaks can be seen)
22	All mountain slopes covered, peaks and passes free
23	Mountains open on observer's side (only small amounts of cloud present), but a continuous wall of cloud on the other side
24	Clouds low above the mountains, but all slopes and mountains open (only small amounts of cloud on the slopes)
25	Clouds low above the mountains, peaks partly covered by precipitation trails or clouds
26	All peaks covered but passes open, slopes either open or covered
27	Mountains generally covered but some peaks free, slopes wholly or partially covered
28	All peaks, passes and slopes covered
29	Mountains cannot be seen owing to darkness, fog, snowstorm, precipitation, etc.
30–34	Reserved
	<i>35–39 Condensation trails (N_t – Code table 2752)</i>
35	Non-persistent condensation trails
36	Persistent condensation trails covering less than 1/8 of the sky
37	Persistent condensation trails covering 1/8 of the sky
38	Persistent condensation trails covering 2/8 of the sky
39	Persistent condensation trails covering 3/8 or more of the sky
	<i>40–49 Cloud conditions observed from a higher level (N_v – Code table 2754)</i>
40	No cloud or mist
41	Mist, clear above
42	Fog patches
43	Layer of slight fog
44	Layer of thick fog
45	Some isolated clouds
46	Isolated clouds and fog below
47	Many isolated clouds
48	Sea of clouds
49	Bad visibility obscuring the downward view
50–510	Reserved
511	Missing value

observed from a higher level

0 20 137***Evolution of clouds***

Code table 0 20 137

Code figure	
0	No change
1	Cumulification
2	Slow elevation
3	Rapid elevation
4	Elevation and stratification
5	Slow lowering
6	Rapid lowering
7	Stratification

FM 94 BUFR*Code table 0 20 137*

Code figure	
8	Stratification and lowering
9	Rapid change
10–14	Reserved
15	Missing value

0 20 138***Road surface condition****Code table 0 20 138*

Code figure	
0	Dry
1	Moist
2	Wet
3	Rime
4	Snow
5	Ice
6	Glaze
7	Not dry
8–14	Reserved
15	Missing value

Provisional Copy
2023

0 21 026***ASCAT sigma-0 usability****Code table 0 21 026*

<u>Code figure</u>	
<u>0</u>	<u>Nominal</u>
<u>1</u>	<u>Close to nominal</u>
<u>2</u>	<u>Far from nominal</u>
<u>3-6</u>	<u>Reserved</u>
<u>7</u>	<u>Missing</u>

0 21 066***Wave scatterometer product confidence data****Flag table 0 21 066*

Bit No.	
1	Processing equipment not working
2	Equipment failed
3	PRF code changed during image generation
4	Sampling window changed during image generation
5	Gain changed during image generation
6	Chirp replica exceeds specified value
7	Input data mean and standard deviation of in-phase and quadrature out of range
8	Doppler centroid confidence > MMCC value
9	Doppler centroid absolute value > PRF/2
10	Doppler ambiguity confidence < MMCC value
11	Output data mean and standard deviation ≤ MMCC value
All 12	Missing value

0 21 067***Wind product confidence data****Flag table 0 21 067*

Bit No.	
1	No forebeam calculation
2	No midbeam calculation
3	No aftbeam calculation
4	Forebeam arcing detected
5	Midbeam arcing detected
6	Aftbeam arcing detected
7	Any beam noise content above or equal to threshold
8	Land (any land in cell footprint)
9	Autonomous ambiguity removal not used
10	Meteorological background not used
11	Minimum residual exceeded threshold
12	Frame checksum error detected

FM 94 BUFR*Flag table 0 21 067*

Bit No.	
All 13	Missing value

0 21 068***Radar altimeter product confidence data****Flag table 0 21 068*

Bit No.	
1	Standard deviation of wind speed outside MMCC limit
2	Standard deviation of significant wave height outside MMCC limit
3	Standard deviation of altitude outside MMCC limit
4	Mean peakiness outside MMCC limit
5	Frame checksum error detected
6	Height-time loop time constant correction not performed
7	Not enough measurements ($N < 10$)
All 8	Missing value

0 21 069***SST product confidence data****Flag table 0 21 069*

Bit No.	
1	12.0 μm channel present in source data
2	11.0 μm channel present in source data
3	3.7 μm channel present in source data
4	1.6 μm channel present in source data
5	Cloud identification used 1.6 μm histogram reflectance cloud test
6	1.6 μm histogram reflectance cloud test used dynamic threshold
7	Sun glint detected by 1.6 μm reflectance cloud test
8	3.7 μm channel used in sea-surface temperature retrieval
9	Sea-surface temperature derivation used daytime data (night-time if zero)
All 10	Missing value

0 21 070***SST product confidence data (SADIST-2)****Flag table 0 21 070*

Bit No.	
1–9	Nadir-only view SST retrieval used 3.7 micron channel (one bit per 10-arcmin cell)
1	Cell 1: nadir-only view SST used 3.7 micron channel
2	Cell 2: nadir-only view SST used 3.7 micron channel
3	Cell 3: nadir-only view SST used 3.7 micron channel
4	Cell 4: nadir-only view SST used 3.7 micron channel

Cell Numbering:		
NW	7 8 9	NE

FM 94 BUFR

Flag table 0 21 070

Bit No.																										
5	Cell 5: nadir-only view SST used 3.7 micron channel	<table><tr><td></td><td>4</td><td>5</td><td>6</td></tr><tr><td></td><td>1</td><td>2</td><td>3</td></tr><tr><td>SW</td><td></td><td></td><td>SE</td></tr></table>		4	5	6		1	2	3	SW			SE												
	4		5	6																						
	1		2	3																						
SW				SE																						
6	Cell 6: nadir-only view SST used 3.7 micron channel																									
7	Cell 7: nadir-only view SST used 3.7 micron channel																									
8	Cell 8: nadir-only view SST used 3.7 micron channel																									
9	Cell 9: nadir-only view SST used 3.7 micron channel																									
10–18	Dual view SST retrieval used 3.7 micron channel (one bit per 10-arcmin cell)																									
10	Cell 1: dual view SST used 3.7 micron channel	<table><tr><td colspan="4">Cell Numbering:</td></tr><tr><td>NW</td><td></td><td></td><td>NE</td></tr><tr><td></td><td>7</td><td>8</td><td>9</td></tr><tr><td></td><td>4</td><td>5</td><td>6</td></tr><tr><td></td><td>1</td><td>2</td><td>3</td></tr><tr><td>SW</td><td></td><td></td><td>SE</td></tr></table>	Cell Numbering:				NW			NE		7	8	9		4	5	6		1	2	3	SW			SE
Cell Numbering:																										
NW				NE																						
	7		8	9																						
	4		5	6																						
	1		2	3																						
SW				SE																						
11	Cell 2: dual view SST used 3.7 micron channel																									
12	Cell 3: dual view SST used 3.7 micron channel																									
13	Cell 4: dual view SST used 3.7 micron channel																									
14	Cell 5: dual view SST used 3.7 micron channel																									
15	Cell 6: dual view SST used 3.7 micron channel																									
16	Cell 7: dual view SST used 3.7 micron channel																									
17	Cell 8: dual view SST used 3.7 micron channel																									
18	Cell 9: dual view SST used 3.7 micron channel																									
19	Nadir view contains day-time data (night if zero)																									
20	Forward view contains day-time data (night if zero)																									
21	Record contains contributions from instrument scans acquired when ERS platform not in yaw-steering mode																									
22	Record contains contributions from instrument scans for which product confidence data show quality is poor or unknown																									
All 23	Missing value																									

0 21 072

Satellite altimeter calibration status

Flag table 0 21 072

Bit No.	
1	Height error correction applied instead of open loop calibration
2	Microwave sounder used for troposphere correction
3	AGC output correction applied instead of open loop calibration
All 4	Missing value

0 21 073

Satellite altimeter instrument mode

Flag table 0 21 073

Bit No.	
1	Blank data record
2	Test
3	Calibration (closed loop)
4	BITE
5	Acquisition on ice
6	Acquisition on ocean
7	Tracking on ice
8	Tracking on ocean

Flag table 0 21 073

Bit No.	
All 9	Missing value

0 21 076***Representation of intensities***

Code table 0 21 076

Code figure	
0	Linear
1	Logarithmic (base e)
2	Logarithmic (base 10)
3–6	Reserved
7	Missing value

0 21 109***SEAWINDS wind vector cell quality***

Flag table 0 21 109

Bit No.	
1	Not enough good sigma-0 available for wind retrieval
2	Poor azimuth diversity among sigma-0 for wind retrieval
3–7	Reserved
8	Some portion of wind vector cell is over land
9	Some portion of wind vector cell is over ice
10	Wind retrieval not performed for wind vector cell
11	Reported wind speed is greater than 30 m s ⁻¹
12	Reported wind speed is less than or equal to 3 m s ⁻¹
13–16	Reserved
All 17	Missing value

0 21 115***SEAWINDS sigma-0 quality***

Flag table 0 21 115

Bit No.	
1	Sigma-0 measurement is not usable
2	Signal to noise ratio is low
3	Sigma-0 is negative
4	Sigma-0 is outside of acceptable range
5	Scatterometer pulse quality is not acceptable
6	Sigma-0 cell location algorithm does not converge
7	Frequency shift lies beyond the range of the x factor table
8	Spacecraft temperature is beyond calibration coefficient range
9	No applicable altitude records were found for this sigma-0
10	Interpolated ephemeris data are not acceptable for this sigma-0
11–16	Reserved

FM 94 BUFR*Flag table 0 21 115*

Bit No.	
All 17	Missing value

0 21 116***SEAWINDS sigma-0 mode****Flag table 0 21 116*

Bit No.	
1	Calibration/measurement pulse flag (1)
2	Calibration/measurement pulse flag (2)
3	Outer antenna beam
4	Sigma-0 cell is aft of spacecraft
5	Current mode (1)
6	Current mode (2)
7	Effective gate width – slice resolution (1)
8	Effective gate width – slice resolution (2)
9	Effective gate width – slice resolution (3)
10	Low-resolution mode – whole pulse data
11	Scatterometer electronic subsystem B
12	Alternate spin rate – 19.8 rpm
13	Receiver protection on
14	Slices per composite flag (1)
15	Slices per composite flag (2)
16	Slices per composite flag (3)
All 17	Missing value

0 21 119***Wind scatterometer geophysical model function****Code table 0 21 119*

Code figure	
0	Reserved
1	SASS
2	SASS2
3	NSCAT0
4	NSCAT1
5	NSCAT2
6	QSCAT0
7	QSCAT1
8–30	Reserved
31	CMOD1
32	CMOD2
33	CMOD3
34	CMOD4
35	CMOD5
36–62	Reserved
63	Missing value

0 21 144***Altimeter rain flag****Flag table 0 21 144*

Bit No.	
1	Rain
All 2	Missing value

0 21 148***Trailing edge variation flag****Flag table 0 21 148*

Bit No.	
1	Non short scale variation
2	Short scale variation
3–8	Reserved
All 9	Missing value

0 21 150***Beam co-location****Code table 0 21 150*

Code figure	
0	Data from single ground station (no co-location)
1	Data from multiple ground station (co-located data)
2	Reserved
3	Missing value

0 21 155***Wind vector cell quality****Flag table 0 21 155*

Bit No.	
1	Not enough good sigma-0 available for wind retrieval
2	Poor azimuth diversity among sigma-0 for wind retrieval
3	Any beam noise content above threshold
4	Product monitoring not used
5	Product monitoring flag
6	KNMI quality control fails
7	Variational quality control fails
8	Some portion of wind vector cell is over land
9	Some portion of wind vector cell is over ice
10	Wind retrieval not performed for wind vector cell
11	Reported wind speed is greater than 30 m/s
12	Reported wind speed is less than or equal to 3 m/s
13	Rain flag for the wind vector cell is not usable
14	Rain flag algorithm detects rain

FM 94 BUFR*Flag table 0 21 155*

Bit No.	
15	No meteorological background used
16	Data are redundant
17–23	Reserved
All 24	Missing value

0 21 158***ASCAT Kp estimate quality****Code table 0 21 158*

Code figure	
0	Acceptable
1	Not acceptable
2	Reserved
3	Missing value

0 21 159***ASCAT sigma-0 usability****Code table 0 21 159*

Code figure	
0	Good
1	Usable
2	Bad
3	Missing value

0 21 169***Ice presence indicator****Code table 0 21 169*

Code figure	
0	No ice present
1	Ice present
2	Reserved
3	Missing value

0 22 056***Direction of profile****Code table 0 22 056*

Code figure	
0	Upwards profile
1	Downwards profile
2	Horizontal
3	Missing value

0 22 060***Lagrangian drifter drogue status****Code table 0 22 060*

Code figure	
0	Drogue is detached
1	Drogue is attached
2	Drogue status unknown
3–6	Reserved
7	Missing value

0 22 061***State of the sea****Code table 0 22 061*

Code figure		Height in metres
0	Calm (glassy)	0
1	Calm (rippled)	0 – 0.1
2	Smooth (wavelets)	0.1 – 0.5
3	Slight	0.5 – 1.25
4	Moderate	1.25 – 2.5
5	Rough	2.5 – 4
6	Very rough	4 – 6
7	High	6 – 9
8	Very high	9 – 14
9	Phenomenal	Over 14
10–14	Reserved	
15	Missing value	

Notes:

- (1) These values refer to well-developed wind waves of the open sea. While priority shall be given to the descriptive terms, these height values may be used for guidance by the observer when reporting the total state of agitation of the sea resulting from various factors such as wind, swell, currents, angle between swell and wind, etc.
- (2) The exact bounding height shall be assigned for the lower code figure; e.g., a height of 4 m is coded as 5.

0 22 067***Instrument type for water temperature/salinity profile measurement****(See common Code table C-3)***0 22 068*****Water temperature profile recorder types****(See common Code table C-4)***0 22 120*****Tide station automated water level check****Code table 0 22 120*

Code figure	
0	Good data
1	Maximum (high) water level limit exceeded
2	Minimum (low) water level limit exceeded
3	Rate of change limit for water level exceeded
4	Flat limit for water level exceeded
5	Observed minus predicted water level value limit exceeded
6	Observed value from primary water level sensor minus backup water level sensor
7	Value exceeded specified tolerance from expected value
8	Water level QA parameter (sigmas and/or outliers) limits exceeded
9	Sea temperature outside of expected range
10	Multiple QC checks (above) failed
11	No automated water level checks performed
12-30	Reserved
31	Missing value

0 22 121***Tide station manual water level check****Code table 0 22 121*

Code figure	
0	Operational
1	Possible clogging problem or otherwise degraded water level data
2	Possible datum shift
3	Unknown status of water level sensor
4	Suspected or known sea-temperature sensor problem
5	Multiple possible problems (above)
6	Bad data – DO NOT DISSEMINATE!
7	No manual water level checks performed
8-30	Reserved
31	Missing value

0 22 122***Tide station automated meteorological data check****Code table 0 22 122*

Code figure	
0	Good data from all sensors
1	Wind direction outside of allowable range
2	Wind speed outside of expected range
3	Barometric pressure outside of expected range
4	Air temperature outside of expected range
5	Multiple sensors failed QC checks
6	No automated meteorological data checks performed
7–30	Reserved
31	Missing value

0 22 123***Tide station manual meteorological data check****Code table 0 22 123*

Code figure	
0	Operational
1	Suspected or known problem with wind sensor
2	Suspected or known problem with barometric pressure sensor
3	Suspected or known problem with air temperature sensor
4	Unknown status of all sensors
5	Suspected or known problems with multiple sensors
6	Bad data – DO NOT DISSEMINATE!
7	No manual meteorological data checks performed
8–30	Reserved
31	Missing value

0 22 178***XBT/XCTD launcher type****Code table 0 22 178*

Code figure	
0	Unknown
1	LM-2A Deck-mounted
2	LM-3A Hand-Held
3	LM-4A Thru-Hull
4–9	Reserved
10	AL-12 TSK Autolauncher (up to 12 probes)
11–19	Reserved
20	SIO XBT Autolauncher (up to 6 probes)
21–29	Reserved
30	AOML XBT V6 Autolauncher (up to 6 Deep Blue probes)
31	AOML XBT V8.0 Autolauncher (up to 8 Deep Blue probes)
32	AOML XBT V8.1 Autolauncher (up to 8 Deep Blue and Fast Deep probes)

Code table 0 22 178

Code figure	
33–89	Reserved
90	CSIRO Devil Autolauncher
91–99	Reserved
100	MFSTEP Autolauncher (Mediterranean)
101–254	Reserved
255	Missing value

Provisional Copy
2023

0 23 001***Accident early notification – article applicable****Code table 0 23 001*

Code figure	
0	Reserved
1	Articles 1 and 2
2	Article 3
3	Article 5.2
4–6	Reserved
7	Missing value

0 23 002***Activity or facility involved in incident****Code table 0 23 002*

Code figure	
0	Reserved
1	Nuclear reactor on ground
2	Nuclear reactor at sea
3	Nuclear reactor in space
4	Nuclear fuel facility
5	Radioactive waste management facility
6	Transport of nuclear fuel or radioactive waste
7	Storage of nuclear fuel or radioactive waste
8	Manufacture of radio-isotopes
9	Use of radio-isotopes
10	Storage of radio-isotopes
11	Disposal of radio-isotopes
12	Transport of radio-isotopes
13	Use of radio-isotopes for power generation
14–29	Reserved
30	Other
31	Missing value

0 23 003***Type of release****Code table 0 23 003*

Code figure	
0	No release
1	Release to atmosphere
2	Release to water
3	Release to both atmosphere and water
4	Expected release to atmosphere
5	Expected release to water
6	Expected release to both atmosphere and water
7	Missing value

0 23 004***Countermeasures taken near border****Code table 0 23 004*

Code figure	
0	No countermeasures
1	Evacuation
2	Sheltering
3	Prophylaxis
4	Water
5-6	Reserved
7	Missing value

0 23 005***Cause of incident****Code table 0 23 005*

Code figure	
0	Incident State does not understand what happened
1	Incident State knows the cause of the incident
2	Reserved
3	Missing value

0 23 006***Incident situation****Code table 0 23 006*

Code figure	
0	No improvement
1	Unstable
2	No deterioration
3	Improving
4	Stable
5	Deteriorating
6	Reserved
7	Missing value

0 23 007***Characteristics of release****Code table 0 23 007*

Code figure	
0	No release
1	Release has stopped
2	Release
3	Release is continuing
4–6	Reserved
7	Missing value

0 23 008/0 23 009***State of current or expected release****Code table 0 0 23 008/0 23 009*

Code figure	
0	Gaseous
1	Particulate
2	Mixture of gaseous and particulate
3	Missing value

0 23 016***Possibility of significant chemical toxic health effect****Code table 0 23 016*

Code figure	
0	No significant chemical toxic health effect
1	Significant chemical toxic health effect possible
2	Reserved
3	Missing value

0 23 018***Release behaviour over time****Code table 0 23 018*

Code figure	
0	Release no longer occurring
1	Release still occurring
2	Release expected to increase in next six hours
3	Release expected to remain constant in next six hours
4	Release expected to decrease in next six hours
5–6	Reserved
7	Missing value

0 23 031***Possibility that plume will encounter precipitation
in State in which incident occurred****Code table 0 23 031*

Code figure	
0	Plume will not encounter rain in incident State
1	Plume will encounter rain in incident State
2	Reserved
3	Missing value

0 23 032***Plume will encounter change in wind direction and/or speed flag****Code table 0 23 032*

Code figure	
0	No significant change expected within the next six hours
1	Anticipated significant change expected within the next six hours
2	Reserved
3	Missing value

0 24 003***Composition of release***

<i>Code table 0 24 003</i>	
Code figure	
0	Noble gases
1	Iodines
2	Caesiums
3	Transuranics
4–30	Reserved
31	Missing value

Provisional Copy
2023

0 25 004***Echo processing****Code table 0 25 004*

Code figure	
0	Incoherent
1	Coherent (Doppler)
2	Reserved
3	Missing value

0 25 005***Echo integration****Code table 0 25 005*

Code figure	
0	Logarithm – 2.5 dB
1	Linear
2	Special
3	Missing value

0 25 006***Z to R conversion****Code table 0 25 006*

Code figure	
0	ZH to R conversion
1	(ZH, ZDR) to (NO, DO) to R
2	(Z (F1), Z (F2)) to attenuation to R
3–5	Reserved
6	Other
7	Missing value

0 25 009***Calibration method****Flag table 0 25 009*

Bit No.	
1	None
2	Calibration target or signal
3	Against raingauges
4	Against other Instruments (disdrometer – attenuation)
All 4	Missing value

Note: Descriptor 0 25 009 is deprecated. 0 25 029 should be used instead.

0 25 010***Clutter treatment****Code table 0 25 010*

Code figure	
0	None
1	Map
2	Insertion of higher elevation data and map
3	Analysis of the fluctuating logarithm signal (clutter detection)
4	Extraction of the fluctuating part of linear signal (clutter suppression)
5	Clutter suppression – Doppler
6	Multiparameter analysis
7–14	Reserved
15	Missing value

0 25 011***Ground occultation correction (screening)****Code table 0 25 011*

Code figure	
0	None
1	Map of correction factors
2	Interpolation (azimuth or elevation)
3	Missing value

0 25 012***Range attenuation correction****Code table 0 25 012*

Code figure	
0	Hardware
1	Software
2	Hardware and software
3	Missing value

0 25 013***Bright-band correction****Flag table 0 25 013*

Bit No.	
1	Bright-band correction
All 2	Missing value

0 25 015***Radome attenuation correction****Flag table 0 25 015*

Bit No.	
1	Radome attenuation correction
All 2	Missing value

0 25 017***Precipitation attenuation correction****Flag table 0 25 017*

Bit No.	
1	Precipitation attenuation correction
All 2	Missing value

0 25 020***Mean speed estimation****Code table 0 25 020*

Code figure	
0	FFT (fast Fourier transform)
1	PPP (pulse-pair processing)
2	VPC (vector-phase change)
3	Missing value

0 25 021***Wind computation enhancement****Flag table 0 25 021*

Bit No.	
1	Simple average
2	Consensus average
3	Median check
4	Vertical consistency check
5	Other
6–7	Reserved
All 8	Missing value

0 25 022***GHR SST rejection flag****Flag table 0 25 022*

Bit No.	
1	Unprocessed
2	Land suspected
3	Wind speed too large
4	Ice detected
5	Rain detected (Microwave retrievals only)
6	Cloudy detected (Infra-red retrievals only)
7	Cosmetic value
8	SST out of range
All 9	Missing value

0 25 023***GHR SST confidence flag****Flag table 0 25 023*

Bit No.	
1	Default confidence value has been used
2	Default bias and standard deviation have been used
3	Sun glint suspected
4	Sea-ice retrieval for microwave data
5	High wind speed retrieval
6	Inaccurate SST due to low SST (< 285K) (only applies to the TMI instrument)
7	Relaxed rain contamination suspected
8	Potential side lobe contamination
All 9	Missing value

0 25 024***GHR SST data quality****Code table 0 25 024*

Code figure	
0	Unprocessed infrared retrieval
1	Cloudy retrievals
2	Bad: Data that are probably contaminated by cloud
3	Suspect data
4	Acceptable data
5	Excellent data
6	Cool skin suspected
7-9	Reserved
10	Unprocessed microwave retrieval
11	Questionable microwave retrieval that may be contaminated

Code table 0 25 024

Code figure	
12	Acceptable microwave retrieval
13	High probability of diurnal variability
14	Reserved
15	Missing value

0 25 029**Calibration method**

Flag table 0 25 029

Bit No.	
1	Reserved
2	Calibration target or signal
3	Against raingauges
4	Against other instruments (disdrometer – attenuation)
5	Reserved
All 6	Missing value

0 25 030**Running mean sea-surface temperature usage**

Code table 0 25 030

Code figure	
0	Running mean sea-surface temperature not used because usage criteria not met
1	Running mean sea-surface temperature not used because data not available
2	Running mean sea-surface temperature used as predictor
3	Missing value

0 25 031**NWP-generated vertical profile thinning method**

Code table 0 25 031

Code figure	Meaning
0	Reserved
1	No thinning applied (all native model levels are included from base to top of pseudo-sounding)
2	Native model levels are present only if they are significant levels as per regulations B/C 25 for conventional TEMP soundings
3	A predefined subset of native model levels is present
4	No native model levels are present. All profile levels are interpolated to a predefined set of pressure coordinate levels
5–6	Reserved
7	Missing value

Note: None of the code figures exclude the addition of interpolated levels at the discretion of the generating centre.

0 25 032***Wind profiler mode information****Code table 0 25 032*

Code figure	
0	Reserved
1	Data from low mode
2	Data from high mode
3	Missing value

0 25 033***Wind profiler submode information****Code table 0 25 033*

Code figure	
0	Wind profiler operating in submode A
1	Wind profiler operating in submode B
2	Reserved
3	Missing value

0 25 034***Wind profiler quality control test results****Flag table 0 25 034*

Bit No.	Meaning (1 = true, 0 = false)
1	Test A performed and failed
2	Test B performed and failed
3	Test results inconclusive
All 4	Missing value

0 25 035***Decision method for polarity****Code table 0 25 035*

Code figure	
0	Not defined
1	Individual voltage deflection
2	Current based, above a threshold
3	Voltage based, above a threshold
4	Consensus of sensors, current above a threshold
5	Consensus of sensors, voltage above a threshold
6	Reserved
7	Missing value

0 25 036***Atmospherics location method****Code table 0 25 036*

Code figure	
0	Network of several direction-finders operating on the same individual atmospherics
1	Network of several arrival-time stations operating on the same individual atmospherics
2-5	Reserved
6	Single station range bearing technique
7-14	Reserved
15	Missing value

0 25 040***CO₂ wind product derivation****Code table 0 25 040*

Code figure	
0	Non-specific mode
1	First guess data
2	Cloud data
3	Average vector data
4	Primary data
5	Guess data
6	Vector data
7	Tracer data; this image
8	Tracer data to next image
9-14	Reserved
15	Missing value

0 25 041***Moving platform direction reporting method****Code table 0 25 041*

Code figure	
0	Direction originally reported in true degrees
1	Direction originally reported using Code table 0700, FM 13
2	Reserved
3	Missing value

Note: Where the original reporting method is as indicated by code figure 1, the following conversion is recommended to obtain a suitable data value corresponding to descriptor 0 01 012:

Reported value	Data value
0	0
1	45
2	90
3	135
4	180
5	225
6	270
7	315
8	360
9	511

0 25 042***Moving platform speed reporting method****Code table 0 25 042*

Code figure	
0	Speed originally reported in metres per second
1	Speed originally reported using Code table 4451, FM 13
2	Reserved
3	Missing value

Note: Where the original reporting method is as indicated by code figure 1, the following conversion is recommended to obtain a suitable data value corresponding to descriptor 0 01 013:

Reported value	Data value
0	0
1	1
2	4
3	7
4	9
5	12
6	14
7	17
8	19
9	21
/	1023

0 25 045***HIRS channel combination****Flag table 0 25 045*

Bit No.	
1–20	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 21	Missing value

0 25 046***MSU channel combination****Flag table 0 25 046*

Bit No.	
1–4	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 5	Missing value

0 25 047***SSU channel combination****Flag table 0 25 047*

Bit No.	
1–3	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present; if bit position is set to 0, then channel is not present
All 4	Missing value

0 25 048***AMSU-A channel combination****Flag table 0 25 048*

Bit No.	
1–15	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 16	Missing value

0 25 049***AMSU-B channel combination****Flag table 0 25 049*

Bit No.	
1–5	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 6	Missing value

0 25 051***AVHRR channel combination****Flag table 0 25 051*

Bit No.	
1–6	Beginning with first bit position (high order bit), if bit position is set to 1, then channel is present, if bit position is set to 0, then channel is not present
All 7	Missing value

0 25 053***Observation quality****Flag table 0 25 053*

Bit No.	
1	Good
2	Redundant
3	Questionable
4	Bad
5	Experimental
6	Precipitating
7–11	Reserved
All 12	Missing value

0 25 063***Central processor or system identifier****Code table 0 25 063*

Code figure	
0	Not defined
1	Main processor
2	Backup processor
3–254	Reserved
255	Missing value

0 25 069***Flight level pressure corrections****Flag table 0 25 069*

Bit No.	
1	Smoothed
2	Baseline adjusted
3	Normalized time interval
4	Outlier checked
5	Plausibility checked
6	Consistency checked
7	Interpolated
All 8	Missing value

0 25 086***Depth correction indicator****Code table 0 25 086*

Code figure	
0	Depths are not corrected
1	Depths are corrected
2	Reserved
3	Missing value

0 25 090***Orbit state flag****Code table 0 25 090*

Code figure	
0	Orbit computed during a manoeuvre
1	Adjusted mission operations orbit
2	Extrapolated mission operations orbit
3	Adjusted (preliminary/precise) orbit
4	(Preliminary/precise) orbit is estimated during a manoeuvre period
5	(Preliminary/precise) orbit is interpolated over a tracking data gap
6	(Preliminary/precise) orbit is extrapolated for a duration less than 1 day
7	(Preliminary/precise) orbit is extrapolated for a duration that ranges from 1 day to 2 days
8	(Preliminary/precise) orbit is extrapolated for a duration larger than 2 days, or that the orbit is extrapolated just after a manoeuvre
9	DORIS DIODE navigator orbit (see Note)
10–14	Reserved
15	Missing value

Note: DIODE means *détermination immédiate d'orbite par DORIS embarqué* or immediate on-board orbit determination by DORIS. It is part of the DORIS instrument, which calculates the satellite's position and velocity.

0 25 093***RASS computation correction****Flag table 0 25 093*

Bit No.	
1	No correction
2	Vertical velocity correction
3–6	Reserved
7	All corrections
All 8	Missing value

0 25 095***Altimeter state flag****Flag table 0 25 095*

Bit No.	
1	Altimeter operating (0 if nominal, 1 if backup)
All 2	Missing value

0 25 096***Radiometer state flag****Flag table 0 25 096*

Bit No.	
1	Mode indicator (0 if mode 2, 1 if mode 1)
2	Mode 1 calibration sequence indicator (0 if normal data taking either mode 1 or 2, 1 if mode 1 calibration sequence)
Bits 3 and 4 indicate active 23.8 GHz channel(s):	
3	Channel 2 (0 if on, 1 if off)
4	Channel 3 (0 if on, 1 if off)
All 5	Missing value

0 25 097***Three-dimensional error estimate of the navigator orbit****Code table 0 25 097*

Code figure	
0	Ranges between 0 and 30 cm
1	Ranges between 30 and 60 cm
2	Ranges between 60 and 90 cm
3	Ranges between 90 and 120 cm
4	Ranges between 120 and 150 cm
5	Ranges between 150 and 180 cm
6	Ranges between 180 and 210 cm
7	Ranges between 210 and 240 cm
8	Ranges between 240 and 270 cm
9	Ranges larger than 270 cm
10–14	Reserved
15	Missing value

0 25 098***Altimeter data quality flag****Flag table 0 25 098*

Bit No.	(0 is good, 1 is bad)
1	Ku band range
2	C band range
3	Ku band SWH
4	C band SWH
5	Ku band backscatter coefficient
6	C band backscatter coefficient
7	Off nadir angle from Ku band waveform parameters
8	Off nadir angle from platform
All 9	Missing value

0 25 099***Altimeter correction quality flag****Flag table 0 25 099*

Bit No.	(0 is good, 1 is bad)
1	Ku band range instrumental correction
2	C band range instrumental correction
3	Ku band SWH instrumental correction
4	C band SWH instrumental correction
5	Ku band backscatter coefficient instrumental correction
6	C band backscatter coefficient instrumental correction
7-8	Reserved
All 9	Missing value

0 25 110***Image processing summary****Flag table 0 25 110*

Bit No.	
1	Raw data analysis used for raw data correction. Correction done using default parameters
2	Raw data analysis used for raw data correction. Correction done using raw data analysis results
3	Antenna elevation pattern correction applied
4	Nominal chirp replica used
5	Reconstructed chirp used
6	Slant range to ground range conversion applied
7-9	Reserved
All 10	Missing value

0 25 112***Band specific altimeter data quality flag****Flag table 0 25 112*

Bit No.	(0 is good, 1 is bad)
1	Band specific range
2	Band specific significant wave height
3	Band specific backscatter coefficient
4	Off nadir angle from band specific waveform parameters
5	Off nadir angle from platform
6–8	Reserved
All 9	Missing value

0 25 113***Band specific altimeter correction quality flag****Flag table 0 25 113*

Bit No.	(0 is good, 1 is bad)
1	Band specific range instrumental correction
2	Band specific significant wave height instrumental correction
3	Band specific backscatter coefficient instrumental correction
4–8	Reserved
All 9	Missing value

0 25 120***RA2-L2-processing flag****Code table 0 25 120*

Code figure	
0	Percentage of DSRs free of processing errors during Level 2 processing is greater than the acceptable threshold
1	Percentage of DSRs free of processing errors during Level 2 processing is less than the acceptable threshold
2	Reserved
3	Missing value

0 25 122***Hardware configuration for RF****Code table 0 25 122*

Code figure	
0	Hardware configuration for RF is A
1	Hardware configuration for RF is B
2	Reserved
3	Missing value

0 25 123***Hardware configuration for HPA****Code table 0 25 123*

Code figure	
0	Hardware configuration for HPA is A
1	Hardware configuration for HPA is B
2	Reserved
3	Missing value

0 25 124***MWR-L2-processing flag****Code table 0 25 124*

Code figure	
0	Percentage of DSRs free of processing errors during Level 2 processing is greater than the acceptable threshold
1	Percentage of DSRs free of processing errors during Level 2 processing is less than the acceptable threshold
2	Reserved
3	Missing value

0 25 139***Processing level****Code table 0 25 139*

Code figure	
0	L1B
1	L2A
2–30	Reserved
31	Missing value

0 25 150***Method of tropical cyclone intensity analysis using satellite data****Code table 0 25 150*

Code figure	
1	The Dvorak's VIS (VISual imagery) intensity analysis
2	The Dvorak's EIR (Enhanced InfraRed imagery) intensity analysis
3–14	Reserved
15	Missing value

0 25 174**SMOS information flag***Flag table 0 25 174*

Bit No.	Meaning
1	Pixel is affected by RFI effects
2	Pixel is located in the hexagonal alias direction centred on Sun alias
3	Pixel is close to the border delimiting the extended alias free zone
4	Pixel is inside the extended alias free zone
5	Pixel is inside the exclusive of alias free zone
6	Pixel is located in a zone where a Moon alias was reconstructed
7	Pixel is located in a zone where Sun reflection has been detected
8	Pixel is located in a zone where Sun alias was reconstructed
9	Flat target transformation has been performed during image reconstruction of this pixel
10	Scene has been combined with an adjustment scene in opposite polarization during image reconstruction to account for cross-polarization leakage
11	Direct Moon correction has been performed during image reconstruction of this pixel
12	Reflected Sun correction has been performed during image reconstruction of this pixel
13	Direct Sun correction has been performed during image reconstruction of this image
All 14	Missing value

0 25 181**L2 processing flag***Code table 0 25 181*

Code figure	Meaning
0	OK
1	Percentage of L2b records free of processing errors is less than acceptable threshold
2	Missing value

0 25 182**L1 processing flag***Code table 0 25 182*

Code figure	Meaning
0	OK
1	Percentage of L1b records free of processing errors is less than acceptable threshold
2	Missing value

0 25 184***L2 product status****Code table 0 25 184*

Code figure	Meaning
0	OK
1	Product as a duration shorter than the input product
2	Missing value

0 25 185***Encryption method****Code table 0 25 185*

Code figure	Meaning
0	AES 256
1–254	Reserved
255	Missing value

0 25 187***Confidence flag****Code table 0 25 187*

Code figure	Meaning
0	Valid
1	Invalid
2–14	Reserved
15	Missing value

0 25 188***Method for reducing pressure report to sea level****Code table 0 25 188*

Code figure	Meaning
0	Pressure adjusted to mean sea level following WMO-No. 8 for low level (< 50 m) stations (see Note)
1	Pressure adjusted to mean sea level following WMO-No. 8 for stations below 750 m
2	Pressure adjusted to sea level following national practice
3	Pressure adjusted to local water level following national practice
4	Pressure not corrected for height
5–14	Reserved
15	Missing value

Note: WMO-No. 8 is the [Guide to Instruments and Methods of Observation](#).

0 25 190***Altimeter echo processing mode****Code table 0 25 190*

Code figure	
0	Low-resolution mode (LRM)
1	Synthetic aperture radar (SAR)
2	LRM and SAR (interleaved)
3	Reserved
4	Pseudo-LRM (PLRM)
5	SAR interferometric mode (SARin)
6–254	Reserved
255	Missing value

0 25 191***Altimeter tracking mode****Code table 0 25 191*

Code figure	
0	Open loop
1	Closed loop
2	Open loop fixed gain
3–254	Reserved
255	Missing value

0 26 010***Hours included****Flag table 0 26 010*

Bit No.

1	0100 included
2	0200 included
3	0300 included
4	0400 included
5	0500 included
6	0600 included
7	0700 included
8	0800 included
9	0900 included
10	1000 included
11	1100 included
12	1200 included
13	1300 included
14	1400 included
15	1500 included
16	1600 included
17	1700 included
18	1800 included
19	1900 included
20	2000 included
21	2100 included
22	2200 included
23	2300 included
24	2400 included
25	Unknown mixture of hours
All 26	Missing value

0 29 001***Projection type****Code table 0 29 001*

Code figure	
1	Polar stereographic projection
2	Lambert's conformal conic projection
3	Mercator's projection
4	Scanning cone (radar) (see Note)
5	Reserved
6	No projection
7	Missing value

Note: Projection type 4 indicates a Cartesian grid placed directly on the scanning cone defined by the azimuthal sweep of the radar.

0 29 002***Coordinate grid type****Code table 0 29 002*

Code figure	
0	Cartesian
1	Polar
2	Other
3-6	Reserved
7	Missing value

0 30 031***Picture type****Code table 0 30 031*

Code figure	
0	PPI
1	Composite
2	CAPPI
3	Vertical section
4	Alphanumeric data
5	Map of subject clutter
6	Map
7	Test picture
8	Comments
9	Map of ground occultation
10	Map of radar beam height
11–13	Reserved
14	Other
15	Missing value

0 30 032***Combination with other data****Flag table 0 30 032*

Bit No.	
1	Map
2	Satellite IR
3	Satellite VIS
4	Satellite WV
5	Satellite multispectral
6	Synoptic observations
7	Forecast parameters
8	Lightning data
9–14	Reserved
15	Other data
All 16	Missing value

0 31 021***Associated field significance****Code table 0 31 021*

Code figure		
0	Reserved	
1	1-bit indicator of quality	0 = Good 1 = Suspect or bad
2	2-bit indicator of quality	0 = Good 1 = Slightly suspect 2 = Highly suspect 3 = Bad
3–4	Reserved	
5	8-bit indicator of quality control	0 = Data checked and declared good 1 = Data checked and declared suspect 2 = Data checked and declared aggregated 3 = Data checked and declared out of instrument range 4 = Data checked, declared aggregated, and out of instrument range 5 = Parameter is not measured at the station 6 = Daily value not provided 7 = Data unchecked 8–254 = Reserved 255 = Missing (QC info not available)
6	4-bit indicator of quality control class according to GTSP	0 = Unqualified 1 = Correct value (all checks passed) 2 = Probably good but value inconsistent with statistics (differ from climatology) 3 = Probably bad (spike, gradient, ... if other tests passed) 4 = Bad value, impossible value (out of scale, vertical instability, constant profile) 5 = Value modified during quality control 6–7 = Not used (reserved) 8 = Interpolated value 9 = Missing value
7	Percentage confidence	
8		0 = Not suspected 1 = Suspected 2 = Reserved 3 = Information not required
9	Status of ancillary data	0 = Data present, good, collocated 1 = Data available but of degraded quality and not used 2 = No spatiotemporally collocated data available 3–14 = Not used (reserved) 15 = Missing value
10–20	Reserved	
21	1-bit indicator of correction (see Note 2)	0 = Original value 1 = Substituted/corrected value
22–62	Reserved for local use	
63	Missing value	

Notes:

- (1) Associated field significance shall be used initially in conjunction with the quality of observed data.

- (2) The code figure 21 may be used within corrected messages with the substituted/corrected values identified.
- (3) Further applications may be developed.

0 31 031

Data present indicator

Flag table 0 31 031

Bit No.	Value	
1	0	Data present
	1	Data not present

Provisional Copy
2023

0 33 002**Quality information***Code table 0 33 002*

Code figure	
0	Data not suspect
1	Data suspect
2	Reserved
3	Quality information not given

0 33 003**Quality information***Code table 0 33 003*

Code figure	
0	Data not suspect
1	Data slightly suspect
2	Data highly suspect
3	Data considered unfit for use
4–6	Reserved
7	Quality information not given

0 33 005**Quality information (AWS data)***Flag table 0 33 005*

Bit No.	
1	No automated meteorological data checks performed
2	Pressure data suspect
3	Wind data suspect
4	Air temperature data suspect
5	Wet-bulb temperature data suspect
6	Humidity data suspect
7	Ground temperature data suspect
8	Soil temperature (depth 1) data suspect
9	Soil temperature (depth 2) data suspect
10	Soil temperature (depth 3) data suspect
11	Soil temperature (depth 4) data suspect
12	Soil temperature (depth 5) data suspect
13	Cloud data suspect
14	Visibility data suspect
15	Present weather data suspect
16	Lightning data suspect
17	Ice deposit data suspect
18	Precipitation data suspect
19	State of ground data suspect

FM 94 BUFR*Flag table 0 33 005*

Bit No.	
20	Snow data suspect
21	Water content data suspect
22	Evaporation/evapotranspiration data suspect
23	Sunshine data suspect
24–29	Reserved
All 30	Missing value

0 33 006***Internal measurement status information (AWS)****Code table 0 33 006*

Code figure	
0	Self-check OK
1	At least one warning active, no alarms
2	At least one alarm active
3	Sensor failure
4–6	Reserved
7	Missing value

0 33 015***Data quality-check indicator****Code table 0 33 015*

Code figure	
0	Passed all checks
1	Missing data check
2	Descending/reascending balloon check
3	Data plausibility check (above limits)
4	Data plausibility check (below limits)
5	Superadiabatic lapse rate check
6	Limiting angles check
7	Ascension rate check
8	Excessive change from previous flight
9	Balloon overhead check
10	Wind speed check
11	Wind direction check
12	Dependency check
13	Data valid but modified
14	Data outlier check
15–62	Reserved
63	Missing value

0 33 020***Quality control indication of following value****Code table 0 33 020*

Code figure	
0	Good
1	Inconsistent
2	Doubtful
3	Wrong
4	Not checked
5	Has been changed
6	Estimated
7	Missing value

0 33 021***Quality of following value****Code table 0 33 021*

Code figure	
0	Within limits
1	Outside limits
2	Reserved
3	Missing value

0 33 022***Quality of buoy satellite transmission****Code table 0 33 022*

Code figure	
0	Good (several identical reports have been received)
1	Dubious (no identical reports have been received)
2	Reserved
3	Missing value

0 33 023***Quality of buoy location****Code table 0 33 023*

Code figure	
0	Reliable (location was made over two satellite passes)
1	Latest known (no location over the corresponding pass)
2	Dubious (location made over one pass only; a second solution is possible in 5 per cent of the cases)
3	Missing value

0 33 024***Station elevation quality mark (for mobile stations)****Code table 0 33 024*

Code figure	
0	Reserved
1	Excellent – within 3 metres
2	Good – within 10 metres
3	Fair – within 20 metres
4	Poor – more than 20 metres
5	Excellent – within 10 feet
6	Good – within 30 feet
7	Fair – within 60 feet
8	Poor – more than 60 feet
9–14	Reserved
15	Missing value

0 33 025***ACARS interpolated values indicator****Code table 0 33 025*

Code figure	
0	Time interpolated, latitude and longitude reported
1	Time reported, latitude and longitude interpolated
2	Time, latitude, and longitude interpolated
3	Time, latitude, and longitude reported
4–6	Reserved
7	Missing value

0 33 026***Moisture quality****Code table 0 33 026*

Code figure	
0	Normal operations – measurement mode
1	Normal operations – non-measurement mode
2	Small RH
3	Humidity element is wet
4	Humidity element contaminated
5	Heater fail
6	Heater fail and wet/contaminated humidity element
7	At least one of the input parameters used in the calculation of mixing ratio is invalid
8	Numeric error
9	Sensor not installed
10	Calculated RH > 100%
11	Input laser power too low
12	Probe WV temperature out of range

FM 94 BUFR*Code table 0 33 026*

Code figure	
13	Probe WV pressure out of range
14	Spectral line out of range
15	No laser output
16–62	Reserved
63	Missing value

0 33 027***Location quality class (range of radius of 66% confidence)****Code table 0 33 027*

Code figure	
0	Radius \geq 1500 m
1	500 m \leq Radius $<$ 1500 m
2	250 m \leq Radius $<$ 500 m
3	Radius $<$ 250 m
4	\leq 100 m
5–6	Reserved
7	Missing value

0 33 028***Snapshot overall quality****Code table 0 33 028*

Code figure	
1	Nominal
2	Degraded by SW error; any error reported by the algorithms
3	Degraded by instrument error
4	Degraded by corrupted /missing ADF
5–6	Reserved
7	Missing value

0 33 030***Scan line status flags for ATOVS****Flag table 0 33 030*

Bit No.	
1	Do not use scan for product generation
2	Time sequence error detected with this scan
3	Data gap precedes this scan
4	No calibration
5	No Earth location
6	First good time following a clock update
7	Instrument status changed with this scan
8–23	Reserved
All 24	Missing value

Note: If bit is set to 1 then statement is true.

0 33 031***Scan line quality flags for ATOVS****Flag table 0 33 031*

Bit No.	
1	Time field is bad but can probably be inferred from the previous good time
2	Time field is bad and cannot be inferred from the previous good time
3	This record starts a sequence that is inconsistent with previous times (i.e. there is a time discontinuity). This may or may not be associated with a spacecraft clock update (see scan line status flags for ATOVS)
4	Start of a sequence that apparently repeats scan times that have been previously accepted
5	Scan line was not calibrated because of bad time
6	Scan line was calibrated using fewer than the preferred number of scan lines because of proximity to start or end of data or to a data gap
7	Scan line was not calibrated because of bad or insufficient PRT data
8	Scan line was calibrated but with marginal PRT data
9	Some uncalibrated channels on this scan
10	Uncalibrated due to instrument mode
11	Questionable calibration because of antenna position error of space view
12	Questionable calibration because of antenna position error of black body
13	Not Earth located because of bad time
14	Earth location questionable because of questionable time code (see time problem code bits)
15	Earth location questionable – only marginal agreement with reasonableness check
16	Earth location questionable – fails reasonableness check
17	Earth location questionable because of antenna position check
18	Scan line calibration cold black body
19	Scan line calibration warm black body
20	Scan line calibration space view

FM 94 BUFR*Flag table 0 33 031*

Bit No.	
21	Earth view
22–23	Reserved
All 24	Missing value

Notes:

- (1) If bit is set to 1 then statement is true.
- (2) Bits 1–4 represent time problem code. All bits off implies the scan time is as expected.
- (3) Bits 5–10 represent calibration problem code. All bits set to zero indicated normal calibration. Where any of bits 5, 7, 10 are set, secondary calibration coefficients have been used.
- (4) Bits 11–17 represent Earth location problem code. All bits set to zero implies the Earth location was normal.

0 33 032***Channel quality flags for ATOVS****Flag table 0 33 032*

Bit No.	
1	No good blackbody counts for scan line
2	No good space view counts for this line
3	No good PRTs for this line
4	Some bad blackbody view counts for this line
5	Some bad space view counts for this line
6	Some bad PRT temps on this line
7	Quality for this scan is reduced
8–23	Reserved (bits set to zero)
All 24	Missing value

Note: All bits off implies a good calibration.

0 33 033***Field of view quality flags for ATOVS****Flag table 0 33 033*

Bit No.	
1	Set if secondary calibration used
2–21	Bit n set to 1 if brightness temperature in channel n – 1 is physically unreasonable or has not been calculated due to calibration problems (see Note 2)
22	Set if all the channels are missing
23	Suspect
All 24	Missing value

Notes:

- (1) All bits off implies a good calibration.
- (2) Bits 2–21 used for HIRS, but only bits 2–16 used for AMSU-A and only bits 2–6 used for AMSU-B.

0 33 035***Manual/automatic quality control****Code table 0 33 035*

Code figure	
0	Automatic quality control passed and not manually checked
1	Automatic quality control passed and manually checked and passed
2	Automatic quality control passed and manually checked and deleted
3	Automatic quality control failed and manually not checked
4	Automatic quality control failed and manually checked and failed
5	Automatic quality control failed and manually checked and re-inserted
6	Automatic quality control flagged data as questionable and not manually checked
7	Automatic quality control flagged data as questionable and manually checked and failed
8	Manually checked and failed
9–14	Reserved
15	Missing value

0 33 037***Wind correlation error****Flag table 0 33 037*

Bit No.	
1	u departure from guess
2	v departure from guess
3	u and v departure from guess
4	u acceleration
5	v acceleration
6	u and v acceleration
7	Possible land feature
8	u acceleration and possible land feature
9	v acceleration and possible land feature
10	u and v acceleration and possible land feature
11	Bad wind guess
12	Correlation failure
13	Search box off edge of area
14	Target box off edge of area
15	Pixel brightness out of bounds (noisy line)
16	Target outside of latitude/longitude box
17	Target outside of pressure minimum/maximum
18	Autoeditor flagged slow vector
19	Autoeditor flagged vectors
All 20	Missing value

0 33 038***Quality flags for ground-based GNSS data****Flag table 0 33 038*

Bit No.	
1	Total zenith delay quality is considered poor
2	GALILEO satellites used
3	GLONASS satellites used
4	GPS satellites used
5	Meteorological data applied
6	Atmospheric loading correction applied
7	Ocean tide loading applied
8	Climate quality data processing
9	Near-real time data processing
All 10	Missing value

0 33 039***Quality flags for radio occultation data****Flag table 0 33 039*

Bit No.	
1	Non-nominal quality
2	Offline product
3	Ascending occultation flag
4	Excess phase processing non-nominal
5	Bending angle processing non-nominal
6	Refractivity processing non-nominal
7	Meteorological processing non-nominal
8	Open loop data included
9	Surface reflections detected
10	L2C GNSS signals used
11–13	Reserved
14	Background profile non-nominal
15	Background (i.e. not retrieved) profile present
All 16	Missing value

0 33 041***Attribute of following value****Code table 0 33 041*

Code figure	
0	The following value is the true value
1	The following value is higher than the true value (the measurement hit the lower limit of the instrument)
2	The following value is lower than the true value (the measurement hit the higher limit of the instrument)
3	Missing value

Note: This descriptor will be associated with visibility data or height of clouds data to specify if the value is bounded. If the reported data is the true value, the code figure is 0. However, the measurement can hit the limit of the instrument measurement capability. If the reported value is higher than the true value, the code figure is 1; if the reported value is lower than the true value, the code figure is 2.

0 33 042***Type of limit represented by following value****Code table 0 33 042*

Code figure	
0	Exclusive lower limit ($>$)
1	Inclusive lower limit (\geq)
2	Exclusive upper limit ($<$)
3	Inclusive upper limit (\leq)
4-6	Reserved
7	Missing value

0 33 043***AST confidence****Flag table 0 33 043*

Bit No.	
1	Sea MDS. Nadir only SST retrieval used 3.7 micron channel. Land MDS reserved
2	Sea MDS. Dual view SST retrieval used 3.7 micron channel. Land MDS reserved
3	Nadir view contains day time data
4	Forward view contains day time data
5-7	Reserved
All 8	Missing value

0 33 044**ASAR quality information***Flag table 0 33 044*

Bit No.	
1	Input data mean outside nominal range flag
2	Input data standard deviation outside nominal range flag
3	Number of input data gaps > threshold value
4	Percentage of missing lines > threshold value
5	Doppler centroid uncertain. Confidence measure < specific value
6	Doppler ambiguity estimate uncertain. Confidence measure < specific value
7	Output data mean outside nominal range flag
8	Output data standard deviation outside nominal range flag
9	Chirp reconstruction failed or is of low quality flag
10	Data set missing
11	Invalid downlink parameters
12	Azimuth cut-off iteration count. The azimuth cut-off fit did not converge within a minimum number of iterations
13	Azimuth cut-off fit did not converge within a minimum number of iterations
14	Phase information confidence measure. The imaginary spectral peak is less than a minimum threshold, or the zero lag shift is greater than a minimum threshold
All 15	Missing value

0 33 047**Measurement confidence data***Flag table 0 33 047*

Bit No.	
1	Error detected and attempts to recover made
2	Anomaly in on-board data handling (OBDH) value detected
3	Anomaly in ultra-stable oscillator processing (USOP) value detected
4	Errors detected by on-board computer
5	Automatic gain control (AGC) out of range
6	Reception (Rx) delay fault. Rx distance out of range
7	Wave form samples fault identifier. Error
8	S band anomaly/error detected
9-11	Reserved
12	Brightness temperature (channel 1) out of range
13	Brightness temperature (channel 2) out of range
14	Reserved
15	Ku band ocean retracking error
16	S band ocean retracking error
17	Ku band ice 1 retracking error
18	S band ice 1 retracking error
19	Ku band ice 2 retracking error
20	S band ice 2 retracking error
21	Ku band sea ice retracking error
22	Arithmetic fault error
23	Meteo data state. No map
24	Meteo data state. 1 map

FM 94 BUFR*Flag table 0 33 047*

Bit No.	
25	Meteo data state. 2 maps degraded
26	Meteo data state. 2 maps nominal
27	Orbit propagator status for propagation mode, several errors
28	Orbit propagator status for propagation mode, warning detected
29	Orbit propagator status for initialization mode, several errors
30	Orbit propagator status for initialization mode, warning detected
All 31	Missing value

0 33 048***Confidence measure of SAR inversion****Code table 0 33 048*

Code figure	
0	Inversion successful
1	Inversion not successful
2	Reserved
3	Missing value

0 33 049***Confidence measure of wind retrieval****Code table 0 33 049*

Code figure	
0	External wind direction used during inversion
1	External wind direction not used during inversion
2	Reserved
3	Missing value

0 33 050***Global GTSP quality flag****Code table 0 33 050*

Code figure	
0	Unqualified
1	Correct value (all checks passed)
2	Probably good but value inconsistent with statistics (differ from climatology)
3	Probably bad (spike, gradient, etc., if other tests passed)
4	Bad value, impossible value (out of scale, vertical instability, constant profile)
5	Value modified during quality control
6–7	Reserved
8	Interpolated value
9	Good for operational use; caution; check literature for other uses
10–14	Reserved
15	Missing value

0 33 052***S band ocean retracking quality****Flag table 0 33 052*

Bit No.	
1–20	First 20 least significant bits correspond to the 20 values (one per data block containing: 0 = valid measurement, 1 = invalid). Bit 1 applies to the 20th data block
All 21	Missing value

0 33 053***Ku band ocean retracking quality****Flag table 0 33 053*

Bit No.	
1–20	First 20 least significant bits correspond to the 20 values (one per data block containing: 0 = valid measurement, 1 = invalid). Bit 1 applies to the 20th data block
All 21	Missing value

0 33 055***Wind vector quality flag****Code table 0 33 055*

Code figure	
1–10	Reserved
11	Ocean sigma-0 is not available for wind retrievals
12	Background wind is not available
13	Background model detect land
14	Background model detect ice
15	Sigma-0 is not land/ice free
16	Sigma-0 land contamination
17	Sigma-0 ice contamination
18	Not enough azimuthal diversity
19	Inversion is not done
20	Overall WVC flag
21	Inversion is attempted (flag is set)
22	Rain flag is attempted (flag is set)
23	Rain is detected
All 24	Missing value

0 33 056***Sigma-0 quality flag****Code table 0 33 056*

Code figure	
1–7	Reserved
8	Ascending
9	VV polarisation
10	Fore of spacecraft
11	Land
12	Poor sigma-0 (summary)
13	Invalid sigma-0 (summary)
14	Poor BT
15	Invalid BT
16	Land–sea boundary
17	Negative sigma-0
18–20	Reserved
21	Ice
22	Missing data at a given latitude–longitude for sea-ice flagging process for 2 or more days
23	Ice–ocean contamination
All 24	Missing value

0 33 060***GqisFlagQual – individual IASI-System quality flag****Code table 0 33 060*

Code figure	
0	Good
1	Bad
2	Reserved
3	Missing value

0 33 066***AMV quality flag****Flag table 0 33 066*

Bit No.	
1–19	Reserved
20	Good wind, but an alternative channel used for feature tracking
21	Good wind, but an alternative set of channels used for the determination of cloud-top height/AMV height assignment
22	Correlation surface constraint fails
23	Reserved
All 24	Missing value

0 33 070**Total ozone quality****Type of station***Code table 0 33 070*

Code figure	
0	Good retrieval
1	Bad aerosol information flag or NOAA-16 radiance anomaly
2	Solar zenith angle greater than 84 degrees
3	380 nm residue greater than limit
4	Ozone inconsistency
5	Difference between profile ozone and step 3 total ozone exceeds threshold (set to 25 DU)
6	Step 1 ozone iteration did not converge
7	Any channel residue greater than 16 or bad radiance
8	Insufficient pixels – not processed
9	First guess good – ozone forecast data used
10	High cloud in pixel – not processed
11	Successful ozone retrieval
12	Unsuccessful ozone retrieval
13–14	Reserved
15	Missing value

0 33 071**Profile ozone quality***Code table 0 33 071*

Code figure	
0	Good retrieval
1	Solar zenith angle greater than 84 degrees
2	Difference between step 3 and profile total ozone greater than limit (25 DU)
3	Average final residue for wavelengths used in retrieval greater than threshold
4	Final residue greater than 3 times a priori error
5	Difference between retrieved and a priori greater than 3 times a priori error
6	Non-convergent solution
7	Upper level profile anomaly or stray light anomaly
8	Initial residue greater than 18.0 N-value units
9–14	Reserved
15	Missing value

0 33 072**Ozone error***Code table 0 33 072*

Code figure	
0	Good retrieval
1	Reflectivity out of range
2	Larger pixels (Number of cross-track pixels less than 32) or backward scans error
3	Solar zenith angle greater than 88 degrees
4	Latitude/longitude out of range
5	Viewing zenith angle or solar zenith angle out of range
6	Step-one process failed in general
7	First guess ozone out of range
8	Too many iterations (exceed 8)
9	Step-one residue calculation failed
10	Step-two process failed in general
11	First guess ozone profile out of range
12	Step-two ozone value out of range
13	Step-two residue calculation failed
14	Step-three process failed in general
15	Polarization correction accuracy alert
16	Radiance or irradiance less or equal to zero
17–30	Reserved
31	Missing value

0 33 075**Scan-level quality flags***Flag table 0 33 075*

Bit No.	
1	Gap in raw data record (RDR) data detected (i.e., missing scan(s) preceding the current scan)
2	Recorded time is not in sequence (i.e., the scan start time is out of sequence)
3	Lambda monitored calculation cannot be updated (see Note 1)
4	The measured temperatures of any instrument components (e.g., beam-splitter, scan mirror, scan baffle) are outside the allowable ranges (see Note 2)
5	At least one of the monitored instrument temperatures has drifted more than a specified tolerance value
6–12	Reserved
All 13	Missing value

Notes:

- (1) Set to 1 if laser wavelength calculation is invalid due to laser diode bias current and/or laser diode temperature measurements being outside the predetermined allowable ranges. These ranges are tunable. In this case Lambda monitored calculation shall have 1 bit per scan.
- (2) These temperatures are used to compute the "environmental" contribution to the internal calibration target (ICT) radiances. When this bit is set to 1, the invalid temperatures shall be replaced with the validated temperature values of the ICT.

0 33 076**Calibration quality flags***Flag table 0 33 076*

Bit No.	
1	Lunar intrusion on first deep space view (see Note)
2	Lunar intrusion on second deep space view (see Note)
3–8	Reserved
All 9	Missing value

Note: Set to 1 if at least one spectrum in the deep space moving average was invalidated due to a lunar intrusion.

0 33 077**Field-of-view quality flags***Flag table 0 33 077*

Bit No.	
1	Degraded SDR quality
2	Invalid SDR quality (see Note 1)
3	Invalid SDR geolocation information
4	Degraded radiometric calibration
5	Invalid radiometric calibration (see Note 2)
6	Degraded spectral calibration
7	Invalid spectral calibration (see Note 3)
8	Fringe count error detected and corrected (see Note 4)
9	Day/night indicator (see Note 5)
10	Invalid RDR data (see Note 6)
11	Significant fringe count error detected (see Note 7)
12	Bit trim failed
13–18	Reserved
All 19	Missing value

Notes:

- (1) SDR quality is invalid if bit trim failed (see bit 12), or fringe count error detected (see bit 11), or invalid raw data record (RDR) data (see bit 10), or invalid radiometric calibration (see bit 5), or invalid spectral calibration (see bit 7).
- (2) Radiometric calibration is invalid if radiometric calibration is not performed, or if it is performed with invalid calibration data (e.g., deep space window size = 0).
- (3) Spectral calibration is invalid if fringe count error detected and corrected (see bit 8), or if neon calibration is suspect and Lambda monitored calculation cannot be updated (see "Scan-level quality flags" (0 33 075) – bit 3).
- (4) Set to 0 if no fringe count error was detected (see bit 11), or a fringe count error was detected but it was not corrected.
- (5) Set to 0 if day (solar zenith angle < 90°). Set to 1 if night (solar zenith angle ≥ 90°).
- (6) This flag indicates the instrument exhibited operational errors and the associated interferogram(s) is/are excluded from SDR processing.
- (7) This flag indicates that a significant number of fringes have been missed, shifting the interferogram ZPD outside of a window monitored by the instrument, and the interferogram is excluded from SDR processing.

0 33 078***Geolocation quality****Code table 0 33 078*

Code figure	
0	Nominal – altitude and ephemeris data available
1	Missing at most a small gap of altitude and ephemeris data
2	Missing more than a small gap of altitude and ephemeris data, but no more than a granule boundary
3	Missing more than a granule boundary of altitude and ephemeris data
4–14	Reserved
15	Missing value

0 33 079***Granule level quality flags****Flag table 0 33 079*

Bit No.	
1–5	Reserved
6	The No. 1–No.7 health checks failed
7	The No. 8–No.15 health checks failed
8	The No. 16–No.23 health checks failed
9	The No. 24–No.31 health checks failed
10	The No. 32–No.39 health checks failed
11	The No. 40–No.47 health checks failed
12	The No. 48–No.55 health checks failed
13	The No. 56–No.63 health checks failed
14	The No. 64–No.70 health checks failed
15	Quadratic correction applied to the radiometric transfer function for non-linearity correction
All 16	Missing value

0 33 080***Scan level quality flags****Flag table 0 33 080*

Bit No.	
1–6	Reserved
7	Divide-by-zero condition or computation loop failed to converge in the K/Ka and V (KAV) band PRT
8	Divide-by-zero condition or computation loop failed to converge in the WG band PRT
9	Divide-by-zero condition or computation loop failed to converge in the K/Ka, V, W, G band receiver shelf PRT K temperature computation
10	Out of range condition for the K/Ka and V band PRT
11	Out of range condition for the WG band PRT
12	KAV PRT temperature inconsistency
13	WG PRT temperature inconsistency
14	Time sequence error

Flag table 0 33 080

Bit No.	
15	Data gap – missing scan(s) preceding the current scan
16	KAV PRT sufficiency – insufficient KAV PRT data are available
17	WG PRT sufficiency – insufficient WG PRT data are available
18	Space view antenna position error
19	Blackbody antenna position error
All 20	Missing value

0 33 081**Channel data quality flags**

Flag table 0 33 081

Bit No.	
1–2	Reserved
3	Moon in space view
4	Gain error – the lowest blackbody count is smaller than or equal to the highest space view count in a scan
5	Calibration with fewer than preferred samples
6	Space view data sufficiency check – insufficient space view samples are available
7	Blackbody view data sufficiency check – insufficient blackbody view samples are available
8	Out of range condition for the space view
9	Out of range condition for the blackbody view
10	Space view inconsistency
11	Blackbody view inconsistency
All 12	Missing value

0 33 082**Geolocation quality flags**

Flag table 0 33 082

Bit No.	
1–5	Reserved
6	Within South Atlantic anomaly
7	Invalid input data (indicates that any of the spacecraft ephemeris or attitude data are invalid)
8	Bad pointing (indicates that the sensor LOS does not intersect the geoid, is near the limb, has invalid sensor angles or other similar condition)
9	Bad terrain (indicates that the algorithm could not obtain a valid terrain value)
10	Invalid solar angles
11	Missing at most a small gap of altitude and ephemeris data
12	Missing more than a small gap of altitude and ephemeris data, but no more than a granule boundary
13	Missing more than a granule boundary of altitude and ephemeris data
14	The number of encoder pulse values per delta time is not as expected
15	Solar eclipse during Earth view scan
All 16	Missing value

0 33 083***Radiance data quality flags****Flag table 0 33 083*

Bit No.	
1–5	Reserved
6	Pixel is affected by radio-frequency interference
7	Poor calibration quality due to bad space view offsets, OBC view offsets, etc. or use of a previous calibration view
8	Saturated pixel
9	Missing data – data required for calibration processing are not available for processing
10	Calibrated pixel radiance out of range
11	Calibrated pixel reflectance or EBBT out of range
12	The moon has corrupted the space view
13	Scan data is not present (no valid data)
14	Quality for this scan-line is reduced. The value is determined by the combined number of steps required to find a replacement for thermistor or calibration source data
15	Bad detector
All 16	Missing value

0 33 084***Pixel level quality flags****Flag table 0 33 084*

Bit No.	
1–5	Reserved
6	Bulk SST outside of validation range
7	Skin SST outside of validation range
8	Sensor zenith angle > 40 degrees (pixel is not within 40 degrees of nadir and therefore is not of high quality)
9	Degradation – horizontal cell size (HCS) > 1.3 km (HCS > 1.3 km, swath width > 1 700 km, sensor zenith angle > 50.3 degrees)
10	Exclusion: no ocean in pixel
11	Degradation: aerosol optical thickness (AOT) > 0.6 (AOT in horizontal cell > 0.6 on the slant path (AOT @550 nm))
12	Exclusion: AOT > 1.0 (AOT in horizontal cell > 1.0 on the slant path (AOT @550 nm))
13	Sun glint present in pixel
14	Ice concentration threshold exceeded (SST not retrieved due to ice concentration exceeding threshold in system spec)
15	Thin cirrus detected in pixel
All 16	Missing value

0 33 085***Aerosol optical thickness quality flags****Flag table 0 33 085*

Bit No.	
1–3	Reserved
4	Angstrom exponent is outside of the system specification range
5	Excluded, Angstrom exponent for AOT at 550 nm < 0.15
6	Bright surface in cell (if over land), or shallow or turbid water in cell (if over ocean)
7	Low sun, excluded, Solar Zenith Angle > 80 degrees
8	Low sun, degraded, 65 degrees < Solar Zenith Angle ≤ 80 degrees
9	Fire detected in cell
10	Snow/Ice in cell
11	Cloud shadow in cell
12	Sun glint in cell
13	Bad SDR data present in horizontal cell (quality of AOT/APSP degraded or AOT/APSP not retrieved due to bad SDR data in horizontal cell)
14	Cirrus contamination in cell
15	Cloud adjacent to cell
16	Cloud contamination in cell
17	AOT is outside of the system specification range
All 18	Missing value

0 33 086***Quality of pixel level retrieval****Code table 0 33 086*

Code figure	
0	Not retrieved
1	Excluded
2	Degraded
3	High quality
4–6	Reserved
7	Missing value

0 33 087**Extent of satellite within South Atlantic anomaly (based on climatological data)***Code table 0 33 087*

Code figure	
0	Less than or equal to 10%
1	Greater than 10% but less than or equal to 20%
2	Greater than 20% but less than or equal to 30%
3	Greater than 30% but less than or equal to 40%
4	Greater than 40% but less than or equal to 50%
5	Greater than 50% but less than or equal to 60%
6	Greater than 60% but less than or equal to 70%
7	Greater than 70% but less than or equal to 80%
8	Greater than 80%
9–14	Reserved
15	Missing value

0 33 088**Ozone total column quality flag***Flag table 0 33 088*

Bit No.	
1–5	Reserved
6	Surface reflectivity out of range
7	Residual too large
8	Aerosol index limit exceeded
9	Solar eclipse present (all or part of the IFOV is affected by a solar eclipse, umbra or penumbra viewing)
10	Sun glint present within IFOV
11	Snow or ice surface is within the IFOV
12	Solar zenith angle in excluded (night) condition (solar zenith angle ≥ 88 degrees)
13	Solar zenith angle in degraded condition (80 degrees \leq solar zenith angle < 88 degrees)
14	SO ₂ index > 6 DU (degraded condition)
15	Residues are not consistent (indicates whether the residues from the 22 wavelengths are consistent)
16	O ₃ triplet selection is not consistent within retrieval (ozone triplet consistency)
17	Input data quality is not good
All 18	Missing value

0 33 092**Band-specific ocean quality flag***Flag table 0 33 092*

Bit No.	
1	Altimeter operating
2	Microwave radiometer (MWR) operating
3–8	Reserved
All 9	Missing value

0 33 093***Extended quality flags for ground-based GNSS data****Flag table 0 33 093*

Bit No.	
1	Path delay quality is considered poor
2	GALILEO satellites used
3	GLONASS satellites used
4	GPS satellites used
5	BeiDou satellites used
6–8	Reserved for new GNSS
9	Meteorological data applied
10	Atmospheric loading correction applied
11	Ocean tide loading applied
12	Second order ionosphere corrections applied
13	Third order ionosphere corrections applied
14	PPP solution
15	Gradients applied to path delay
16	Multipath corrections applied to path delay
17	Residual applied to path delay
18	Climate quality data processing
19	Re-processing
20	Post-processing
21	Near-real-time data processing
22	Real-time data processing
23–30	Reserved
All 31	Missing value

0 33 094**Calibration quality control flags***Flag table 0 33 094*

Bit No.	
<u>1–15</u>	<u>Reserved</u>
<u>16</u>	<u>Non-ocean</u>
<u>17</u>	<u>Lunar or solar intrusion</u>
<u>18</u>	<u>Spacecraft maneuver</u>
<u>19</u>	<u>Cold calibration consistency</u>
<u>20</u>	<u>Warm calibration consistency</u>
<u>21</u>	<u>Descending</u>
<u>22</u>	<u>Night</u>
<u>23</u>	<u>Payload rear orientation</u>
<u>All 24</u>	<u>Missing value</u>

0 33 095**MWI temperatures flag***Flag table 0 33 095*

<u>Bit No.</u>	
<u>1</u>	<u>PRTs or THMs temperatures are missing or with anomalous readings</u>
<u>2</u>	<u>PRT temperatures of OBCT used in the radiometric calibrations is missing or with anomalous readings</u>
<u>3</u>	<u>THMs temperatures of SVR used in the radiometric calibrations are missing or with anomalous readings</u>
<u>4</u>	<u>THMs temperatures of main reflector are missing or with anomalous readings</u>
<u>5</u>	<u>THMs temperatures of the racetrack are missing or with anomalous readings</u>
<u>6</u>	<u>THMs temperatures of the receivers are missing or with anomalous readings</u>
<u>7</u>	<u>Reserved</u>
<u>8</u>	<u>Missing</u>

0 33 096**MWI calibration flag***Flag table 0 33 096*

<u>Bit No.</u>	
<u>1</u>	<u>Radiometric calibration failed or is degraded</u>
<u>2</u>	<u>OBCT view counts averaged value over scans is missing (this is valid for the high-reference calibration load when the back-up calibration is applied for channels MWI-1 to MWI-3)</u>
<u>3</u>	<u>Cold space view counts averaged value over scans is missing (this is valid for the low-reference calibration load when the back-up calibration is applied for channels MWI-1 to MWI-3)</u>
<u>4</u>	<u>OBCT view counts averaged value over scans is degraded due to missing or anomalous counts values (this is valid for the high-reference calibration load when the back-up calibration is applied for channels MWI-1 to MWI-3)</u>
<u>5</u>	<u>Cold space view counts averaged value over scans is degraded due to missing or anomalous counts values (this is valid for the low-reference calibration load when the back-up calibration is applied for channels MWI-1 to MWI-3)</u>
<u>6</u>	<u>OBCT view radiance averaged value over scans is missing (this is valid for the high-reference calibration load when the back-up calibration is applied for channels MWI-1 to MWI-3)</u>
<u>7</u>	<u>Cold space view radiance averaged value over scans is missing (this is valid for the low-reference calibration load when the back-up calibration is applied for channels MWI-1 to MWI-3)</u>
<u>8</u>	<u>OBCT view radiance averaged value over scans is degraded due to missing or anomalous values (this is valid for the high-reference calibration load when the back-up calibration is applied for channels MWI-1 to MWI-3)</u>
<u>9</u>	<u>Cold space view radiance averaged value over scans is degraded due to missing or anomalous values (this is valid for the low-reference calibration load when the back-up calibration is applied for channels MWI-1 to MWI-3)</u>
<u>10</u>	<u>Non-linearity parameter computed using noise diodes is missing (meaningful only for channels MWI-1 to MWI-3)</u>
<u>11</u>	<u>Non-linearity parameter computed using noise diodes is degraded (meaningful only for channels MWI-1 to MWI-3)</u>
<u>12</u>	<u>PRTs or THMs temperatures of current scan are missing or with anomalous readings</u>
<u>13</u>	<u>Moon intrusion in cold space degraded calibration (less than Nvalid c valid samples are not affected by Moon for the considered channel and scan)</u>

Flag table 0 33 096

<u>Bit No.</u>	
<u>14</u>	<u>Back-up calibration with noise diodes performed (meaningful only for MWI-1 to MWI-3)</u>
<u>15</u>	<u>Degraded receiver temperatures lead to degraded calibration</u>
<u>All 16</u>	<u>Missing</u>

0 33 097**MWI scan quality flag***Flag table 0 33 097*

<u>Bit No.</u>	
<u>1</u>	<u>Scan is degraded in raw data record</u>
<u>2</u>	<u>Time sequence error</u>
<u>3</u>	<u>Current scan is acquired after a gap</u>
<u>4</u>	<u>Scan is in period of initialization of calibration of data averages over scans (because of cold start/cold end, missing warm/cold L0 packets or data gaps).</u>
<u>5</u>	<u>Moon intrusion angle in space view below threshold for at least one channel</u>
<u>6</u>	<u>Moon correction is applied but is degraded for at least one channel</u>
<u>7</u>	<u>Sun glint angle below threshold for at least one channel</u>
<u>8</u>	<u>RFI contamination in the Earth view or RFI packet missing for the considered scan (only for MWI-1V and MWI-1H)</u>
<u>9</u>	<u>Satellite manoeuvre occurs in current scan</u>
<u>10</u>	<u>Missing warm or cold L0 packets for the considered scan</u>
<u>11-15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 098**MWI data quality flag***Flag table 0 33 098*

<u>Bit No.</u>	
<u>1</u>	<u>MWI spectral radiance data of channel is missing or degraded</u>
<u>2</u>	<u>Earth view counts of channel within scan are missing or out of bounds</u>
<u>3</u>	<u>Radiometric calibration failed or is degraded</u>
<u>4</u>	<u>Geolocation of channel is erroneous or degraded</u>
<u>5</u>	<u>NEAT of this data granule is above threshold</u>
<u>6</u>	<u>MR emissivity and spillover correction failed or degraded</u>
<u>7</u>	<u>MR sidelobe correction failed or degraded</u>
<u>8</u>	<u>Channel is defective</u>
<u>All 9</u>	<u>Missing</u>

0 33 099**MWI navigation status flag***Flag table 0 33 099*

<u>Bit No.</u>	
<u>1</u>	<u>Geolocation of channel is erroneous or degraded</u>

Flag table 0 33 099

<u>Bit No.</u>	
<u>2</u>	<u>Time sequence error</u>
<u>3</u>	<u>Missing or corrupted NAVATT file lead to the use of predicted orbit files</u>
<u>4</u>	<u>NAVATT attitude data is degraded</u>
<u>5</u>	<u>Time correlation error (missing IERS bulletin)</u>
<u>6</u>	<u>Invalid ephemeris or attitude data</u>
<u>7</u>	<u>Satellite manoeuvre occurs in current scan</u>
<u>8</u>	<u>Non-nominal attitude with yaw, pitch, roll error above threshold Delta YPR (nominally these angles are 0.0 deg for YSM)</u>
<u>9</u>	<u>Sampling time not within prescribed limits</u>
<u>10</u>	<u>Scan velocity not within prescribed limits</u>
<u>11</u>	<u>Bad pointing (sensor LOS does not intersect ellipsoid or not compliant with observation azimuth/elevation limits)</u>
<u>12</u>	<u>Invalid solar azimuth/zenith angles computed</u>
<u>13</u>	<u>DEM geolocation not performed (with use DEM flag = 1)</u>
<u>14</u>	<u>Error in land fraction computation</u>
<u>15</u>	<u>Predicted orbit file not available</u>
<u>All 16</u>	<u>Missing</u>

0 33 100**ICI temperatures flag***Flag table 0 33 100*

<u>Bit No.</u>	
<u>1</u>	<u>PRTs or THMs temperatures are missing or with anomalous readings</u>
<u>2</u>	<u>PRT temperatures of OBCT used in the radiometric calibrations is missing or with anomalous readings</u>
<u>3</u>	<u>PRT temperatures of SVR used in the radiometric calibrations are missing or with anomalous readings</u>
<u>4</u>	<u>PRT temperatures of IRP and sun shield are missing or with anomalous readings</u>
<u>5</u>	<u>THMs temperature of back-end are missing or with anomalous readings</u>
<u>6</u>	<u>THMs temperature of front-end are missing or with anomalous readings</u>
<u>7</u>	<u>PRT temperatures of main reflector are missing or with anomalous readings</u>
<u>All 8</u>	<u>Missing</u>

0 33 101**ICI calibration flag***Flag table 0 33 101*

<u>Bit No.</u>	
<u>1</u>	<u>Radiometric calibration failed or is degraded</u>
<u>2</u>	<u>OBCT view counts averaged value over scans is missing</u>
<u>3</u>	<u>Cold space view counts averaged value over scans is missing</u>
<u>4</u>	<u>OBCT view counts averaged value over scans is degraded due to missing or anomalous counts values</u>
<u>5</u>	<u>Cold space view counts averaged value over scans is degraded due to missing or anomalous counts values</u>
<u>6</u>	<u>OBCT view radiance averaged value over scans is missing</u>
<u>7</u>	<u>Cold space view radiance averaged value over scans is missing</u>

Flag table 0 33 101

<u>Bit No.</u>	
<u>8</u>	<u>OBCT view radiance averaged value over scans is degraded due to missing or anomalous values</u>
<u>9</u>	<u>Cold space view radiance averaged value over scans is degraded due to missing or anomalous values</u>
<u>10</u>	<u>PRTs or THMs temperatures of current scan are missing or with anomalous readings</u>
<u>11</u>	<u>Moon intrusion in cold space degraded calibration (less than Nvalid c valid samples are not affected by Moon for the considered channel and scan)</u>
<u>12</u>	<u>Degraded or missing Back-end Temperatures lead to degraded calibration</u>
<u>13-15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 102**ICI navigation status flag***Flag table 0 33 102*

<u>Bit No.</u>	
<u>1</u>	<u>Scan is degraded in raw data records</u>
<u>2</u>	<u>Time sequence error</u>
<u>3</u>	<u>Current scan is acquired after a gap</u>
<u>4</u>	<u>Scan is in period of initialization of calibration of data averages over scans (because of cold start/cold end, missing warm/cold L0 packets or data gaps)</u>
<u>5</u>	<u>Moon intrusion angle in space view below threshold for at least one channel</u>
<u>6</u>	<u>Moon correction is applied but is degraded for at least one channel</u>
<u>7</u>	<u>Sun glint angle below threshold for at least one channel</u>
<u>8</u>	<u>Satellite manoeuvre occurs in current scan</u>
<u>9</u>	<u>Missing warm or cold L0 packets for the considered scan</u>
<u>10-15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 103**ICI scan quality flag***Flag table 0 33 103*

<u>Bit No.</u>	
<u>1</u>	<u>ICI spectral radiance data of channel is missing or degraded</u>
<u>2</u>	<u>Earth view counts of channel within scan are missing or out of bounds</u>
<u>3</u>	<u>Radiometric calibration failed or is degraded</u>
<u>4</u>	<u>Geolocation of channel is erroneous or degraded</u>
<u>5</u>	<u>NEAT of this data granule is above threshold</u>
<u>6</u>	<u>MR emissivity and spillover correction failed or degraded</u>
<u>7</u>	<u>MR sidelobe correction failed or degraded</u>
<u>8</u>	<u>Channel is defective</u>
<u>All 9</u>	<u>Missing</u>

0 33 104**ICI navigation status flag***Flag table 0 33 104*

<u>Bit No.</u>	
<u>1</u>	<u>Geolocation of channels is erroneous or degraded</u>
<u>2</u>	<u>Time sequence error</u>
<u>3</u>	<u>Missing or corrupted NAVATT file lead to the use of predicted orbit files</u>
<u>4</u>	<u>NAVATT attitude data is degraded</u>
<u>5</u>	<u>Time correlation error (missing IERS bulletin)</u>
<u>6</u>	<u>Invalid ephemeris or attitude data</u>
<u>7</u>	<u>Satellite manoeuvre occurs in current scan</u>
<u>8</u>	<u>Non-nominal attitude with yaw, pitch, roll error above threshold Delta YPR (nominally these angles are 0.0 deg for YSM)</u>
<u>9</u>	<u>Sampling time not within prescribed limits</u>
<u>10</u>	<u>Scan velocity not within prescribed limits</u>
<u>11</u>	<u>Bad pointing (sensor LOS does not intersect ellipsoid or not compliant with observation azimuth/elevation limits)</u>
<u>12</u>	<u>Invalid solar azimuth/zenith angles computed</u>
<u>13</u>	<u>DEM geolocation not performed (with use DEM flag = 1)</u>
<u>14</u>	<u>Error in land fraction computation</u>
<u>15</u>	<u>Predicted orbit file not available</u>
<u>All 16</u>	<u>Missing</u>

0 33 105**ICI processing flags***Flag table 0 33 105*

<u>Bit No.</u>	
<u>1</u>	<u>Moon contamination correction on cold space view counts is not applied</u>
<u>2</u>	<u>MR spillover correction relative to emission by instrument platform is not applied</u>
<u>3</u>	<u>SVR spillover correction relative to emission by instrument platform is not applied</u>
<u>4</u>	<u>SVR sidelobe correction is not applied</u>
<u>5</u>	<u>Full cross-polarization correction including small angles correction is applied</u>
<u>6</u>	<u>Dynamic sidelobe correction is not applied for ICI-1</u>
<u>7</u>	<u>Dynamic sidelobe correction is not applied for ICI-2</u>
<u>8</u>	<u>Dynamic sidelobe correction is not applied for ICI-3</u>
<u>9</u>	<u>Dynamic sidelobe correction is not applied for ICI-4 V and ICI-4 H</u>
<u>10-15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 106**MWI processing flags***Flag table 0 33 106*

<u>Bit No.</u>	
<u>1</u>	<u>Moon contamination correction on cold space view counts is not applied</u>
<u>2</u>	<u>Calibration with noise diodes is not applied for at least one channel among MWI-1 to MWI-3</u>

Flag table 0 33 106

<u>Bit No.</u>	
<u>3</u>	<u>MR spillover correction relative to emission by instrument platform is not applied</u>
<u>4</u>	<u>SVR spillover correction relative to emission by instrument platform is not applied</u>
<u>5</u>	<u>SVR sidelobe correction is not applied</u>
<u>6</u>	<u>Full cross-polarization correction including small angles correction is applied</u>
<u>7</u>	<u>RFI correction in the Earth view is not applied</u>
<u>8</u>	<u>Dynamic sidelobe correction is not applied for MWI-1</u>
<u>9</u>	<u>Dynamic sidelobe correction is not applied for MWI-2</u>
<u>10</u>	<u>Dynamic sidelobe correction is not applied for MWI-3</u>
<u>11</u>	<u>Dynamic sidelobe correction is not applied for MWI-4</u>
<u>12</u>	<u>Dynamic sidelobe correction is not applied for MWI-8</u>
<u>13-15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 107**MWS scan line processing flag***Flag table 0 33 107*

<u>Bit No.</u>	
<u>1</u>	<u>Non-nominal scan due to gap</u>
<u>2</u>	<u>Non-nominal warm target temperature</u>
<u>3</u>	<u>Non-nominal along-track averaging of warm target temperatures</u>
<u>4</u>	<u>Non-nominal instrument temperature</u>
<u>5</u>	<u>Non-nominal along-track averaging of instrument temperatures</u>
<u>6</u>	<u>Non-nominal rotating reflector temperature</u>
<u>7</u>	<u>Non-nominal along-track averaging of rotating reflector temperatures</u>
<u>8</u>	<u>Non-nominal antenna scan angle Earth view</u>
<u>9</u>	<u>Non-nominal antenna scan angle cold view</u>
<u>10</u>	<u>Non-nominal antenna scan angle warm view</u>
<u>11</u>	<u>Non-nominal geolocation</u>
<u>12</u>	<u>Non-nominal LSM and DEM assignment</u>
<u>13</u>	<u>Ongoing satellite manoeuvre</u>
<u>14</u>	<u>Redundant 50GHz rec and PRT set in use</u>
<u>15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 108**MWS navigation status flag***Flag table 0 33 108*

<u>Bit No.</u>	
<u>1</u>	<u>Non-nominal condition</u>
<u>2</u>	<u>Scan not processed</u>
<u>3</u>	<u>Geolocation not successful</u>
<u>4</u>	<u>Orbit not initialized with NAVATT</u>
<u>5</u>	<u>Attitude not initialized with NAVATT</u>
<u>6</u>	<u>Predicted orbit file ingest error</u>
<u>7</u>	<u>Manoeuvre</u>

Flag table 0 33 108

<u>Bit No.</u>	
<u>8</u>	<u>IERS bulletin A ingest error</u>
<u>9</u>	<u>Time correlation and EOP initialized with predicted orbit file</u>
<u>10</u>	<u>Full accuracy of NAVATT initialized attitude not reached</u>
<u>11</u>	<u>Pointing mode not YSM</u>
<u>12</u>	<u>NAVATT ingest error</u>
<u>13-15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 109**MWS overall quality flags***Flag table 0 33 109*

<u>Bit No.</u>	
<u>1</u>	<u>Missing input product(s)</u>
<u>2</u>	<u>Data gap(s)</u>
<u>3</u>	<u>Corrupted input product(s)</u>
<u>4</u>	<u>Instrument anomaly</u>
<u>5</u>	<u>Missing or degraded auxiliary data</u>
<u>6</u>	<u>Degraded due to manoeuvre</u>
<u>7-15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 110**MWS channel processing flags***Flag table 0 33 110*

<u>Bit No.</u>	
<u>1</u>	<u>Channel is off</u>
<u>2</u>	<u>Non-nominal mean warm view count</u>
<u>3</u>	<u>Non-nominal along-track averaging of warm view counts</u>
<u>4</u>	<u>Non-nominal mean cold view count</u>
<u>5</u>	<u>Non-nominal along-track averaging of cold view counts</u>
<u>6</u>	<u>Non-nominal calibration coefficients</u>
<u>7</u>	<u>Moon intrusion in some of the cold view FOVS</u>
<u>8</u>	<u>Non-nominal processing or excessive value for NEDT (cold or warm)</u>
<u>All 9</u>	<u>Missing</u>

0 33 111**SCA quality flags***Flag table 0 33 111*

<u>Bit No.</u>	
<u>1</u>	<u>Predicted orbit file used</u>
<u>2</u>	<u>Manoeuvre taking place</u>
<u>3</u>	<u>Reserved</u>
<u>4</u>	<u>Satellite is not in yaw steering mode</u>

Flag table 0 33 111

<u>Bit No.</u>	
<u>5</u>	<u>Transponder signal is present</u>
<u>6</u>	<u>Noise estimate is poor</u>
<u>7</u>	<u>Noise estimate is very poor</u>
<u>8</u>	<u>Noise outlier is present</u>
<u>9</u>	<u>Ancillary data is poor</u>
<u>10</u>	<u>Ancillary data is very poor</u>
<u>11</u>	<u>Characterisation table limits exceeded</u>
<u>12</u>	<u>Power-gain estimate is poor</u>
<u>13</u>	<u>Power-gain estimate is very poor</u>
<u>14</u>	<u>Power-gain out of limits</u>
<u>15</u>	<u>Waveguide loss estimate is poor</u>
<u>16</u>	<u>Waveguide loss estimate is very poor</u>
<u>17</u>	<u>Waveguide table limits exceeded</u>
<u>18</u>	<u>Echo is out of ADC range</u>
<u>19</u>	<u>Reserved</u>
<u>20</u>	<u>Missing normalisation tables</u>
<u>21</u>	<u>Number of samples in window is low</u>
<u>22</u>	<u>Number of samples in window is very low</u>
<u>23</u>	<u>Negative backscatter in resampled data</u>
<u>24</u>	<u>Possible interference from solar array</u>
<u>25</u>	<u>Reserved</u>
<u>26</u>	<u>Reserved</u>
<u>27</u>	<u>Reserved</u>
<u>28</u>	<u>Land</u>
<u>29</u>	<u>Water</u>
<u>30</u>	<u>Ascending pass</u>
<u>31</u>	<u>Descending pass</u>
<u>All 32</u>	<u>Missing</u>

0 33 113**IASI-NG general quality flags***Flag table 0 33 113*

<u>Bit No.</u>	
<u>1</u>	<u>General quality (0 if bits 2 to 11 are all 0, 1 otherwise)</u>
<u>2</u>	<u>Sounder radiometric</u>
<u>3</u>	<u>Sounder spectral</u>
<u>4</u>	<u>Imager geometric</u>
<u>5</u>	<u>Imager classification</u>
<u>6</u>	<u>Imager radiometric</u>
<u>7</u>	<u>General sounder</u>
<u>8</u>	<u>Presence of mathematical errors</u>
<u>9</u>	<u>TM data missing</u>
<u>10</u>	<u>TM data corrupt</u>
<u>11</u>	<u>TM integrity instrument</u>
<u>12-15</u>	<u>Reserved</u>
<u>All 16</u>	<u>Missing</u>

0 33 114**Out of bounds check***Flag table 0 33 114*

<u>Bit No.</u>	
<u>1</u>	<u>Temperature profile</u>
<u>2</u>	<u>Water vapour profile</u>
<u>3</u>	<u>Ozone profile</u>
<u>4</u>	<u>Surface skin temperature</u>
<u>5</u>	<u>Surface air temperature</u>
<u>6</u>	<u>Surface air dew point temperature</u>
<u>7</u>	<u>Surface pressure</u>
<u>8</u>	<u>Surface skin temperature error estimate (quality indicator)</u>
<u>9</u>	<u>Surface air temperature error estimate (quality indicator)</u>
<u>10</u>	<u>Surface air dew point temperature error estimate (quality indicator)</u>
<u>11</u>	<u>Surface pressure error estimate (quality indicator)</u>
<u>12</u>	<u>Surface emissivity coarse infrared spectrum</u>
<u>13</u>	<u>Surface emissivity microwave spectrum</u>
<u>14</u>	<u>CO2 profile</u>
<u>15</u>	<u>CH4 profile</u>
<u>16</u>	<u>N2O profile</u>
<u>All 17</u>	<u>Missing</u>

0 33 115**Aerosol optical depth quality information***Code table 0 33 115*

<u>Code figure</u>	
<u>0</u>	<u>Good</u>
<u>1</u>	<u>Cloudy nadir</u>
<u>2</u>	<u>Cloudy oblique</u>
<u>3</u>	<u>Glint nadir</u>
<u>4</u>	<u>Glint oblique</u>
<u>5-30</u>	<u>Reserved</u>
<u>31</u>	<u>Missing value</u>

0 35 000***FM and Regional Code number****Code table 0 35 000*

Code figure	
000–099	International FM Codes
100–199	RA I Codes
200–299	RA II Codes
300–399	RA III Codes
400–499	RA IV Codes
500–599	RA V Codes
600–699	RA VI Codes
700–799	Antarctic Codes
800–999	Reserved
1000–1022	Not used
1023	Missing value

0 35 001***Time frame for monitoring****Code table 0 35 001*

Code figure	
0	Real time
1	Near-real time
2	Non-real time
3–6	Reserved
7	Missing value

0 35 030***Discrepancies in the availability of expected data****Code table 0 35 030*

Code figure	
0	No discrepancies
1	Non-compliance with standard and recommended practices and procedures including those of monitoring
2	Catalogues of meteorological bulletins not updated in a timely manner
3	Incorrect routing directories
4	Lack of flexibility in the routing arrangements
5	Deficiencies in the operation of GTS centres and circuits
6	Loss of data or delays in relaying data on the GTS
7	Routing of data different from the routing provided in the plan
8	Various malpractices
9–14	Reserved
15	Missing value

0 35 031***Qualifier on monitoring results****Code table 0 35 031*

Code figure	
1	Sufficient and all of acceptable quality
2	Sufficient but partly of acceptable quality
3	Insufficient but all of acceptable quality
4	Insufficient and of unacceptable quality
5	Some messages not complete
6	Suspect or wrongly coded groups could not be interpreted confidently
7	Gross coding errors
8	Transmission sequential order not observed
9	Report completely garbled and thus discarded
10	Deficiencies identified and rectified
11	Deficiencies identified but not rectified
12	Deficiencies not identified
13	Measuring errors
14	Mutual inconsistency
15	Temporal inconsistency
16	Forecast error
17	Bias
18	Improve system of quality control
19	Expand training programmes
20–98	Reserved
99–126	Not used
127	Missing value

0 35 032***Cause of missing data****Code table 0 35 032*

Code figure	
1	Data groups missing due to radio fading
2	Data groups missing due to outage of centre
3	Data groups missing due to outage of circuit
4	Non-implementation or maintenance of required RBSN density
5	Shortage of qualified staff to man stations
6	Lack of consumables
7	Instrument failure
8	Non-adherence to telecommunication procedures
9	Some observing programmes ceased
10–14	Not used
15	Missing value

0 35 033***Observation and collection deficiencies****Code table 0 35 033*

Code figure	
1	No deficiency
2	Observations not made regularly
3	Observations not made at right time
4	Observations made but not disseminated
5	Observations made and sent to incorrect users
6	Collection not received
7	Collection transmitted late
8	Collection not transmitted
9	Difficulties in HF propagation and selection of suitable frequency
10	Difficulties in maintenance of communication equipment at remote stations
11	No alternative arrangement for routing meteorological observation
12-99	Reserved
100-122	Not used
123	Missing value

0 35 034***Statistical trends for availability of data (during the survey period(s))****Code table 0 35 001*

Code figure	
1	Slight improvement
2	Significant improvement
3	Most significant improvement
4	Steady
5	Decreasing
6	Efforts required to improve night-time observations
7	Missing value

0 35 035***Reason for termination****Code table 0 35 035*

Code figure	
0	Reserved
1	Balloon burst
2	Balloon forced down by icing
3	Leaking or floating balloon
4	Weak or fading signal
5	Battery failure
6	Ground equipment failure
7	Signal interference
8	Radiosonde failure
9	Excessive missing data frames

FM 94 BUFR

Code table 0 35 035

Code figure

10	Reserved
11	Excessive missing temperature
12	Excessive missing pressure
13	User terminated
14	Sudden loss of signal
15	Tracking lost
16	Increasing pressure
17	Invalid and/or missed data time limits exceeded
18–29	Reserved
30	Other
31	Missing value

Provisional Copy
2023

0 40 005***Soil moisture correction flag****Flag table 0 40 005*

Bit No.	
1	Soil moisture between –20% and 0%
2	Soil moisture between 100% and 120%
3	Correction of wet backscatter reference
4	Correction of dry backscatter reference
5	Correction of volume scattering in sand
6–7	Reserved
All 8	Missing value

Note: The nominal range for the surface soil moisture is 0%–100%. In extreme cases, the extrapolated backscatter at 40 degrees incidence angle may exceed the dry or the wet backscatter reference. In these cases, the value provided by the measurement process of surface soil moisture is, respectively, less than 0% or more than 100%.

0 40 006***Soil moisture processing flag****Flag table 0 40 006*

Bit No.	
1	Not soil
2	Sensitivity to soil moisture below limit
3	Azimuthal noise above limit
4	Backscatter Fore-Aft beam out of range
5	Slope Mid-Fore beam out of range
6	Slope Mid-Aft beam out of range
7	Soil moisture below –20%
8	Soil moisture above 120%
9–15	Reserved
All 16	Missing value

Note: The nominal range for the surface soil moisture is 0%–100%. In extreme cases, the extrapolated backscatter at 40 degrees incidence angle may exceed the dry or the wet backscatter reference. In these cases, the value provided by the measurement process of surface soil moisture is, respectively, less than 0% or more than 100%.

0 40 011***Interpolation flag****Flag table 0 40 011*

Bit No.	
1	Mean sea-surface (MSS) interpolation flag
2	Ocean tide solution 1 interpolation flag (0 = 4 points over ocean, 1 = less than 4 points)
3	Ocean tide solution 2 interpolation flag (0 = 4 points over ocean, 1 = less than 4 points)
4	Meteorological data interpolation flag (0 = 4 points over ocean, 1 = less than 4 points)
5–7	Reserved
All 8	Missing value

0 40 012***Radiometer data quality flag****Flag table 0 40 012*

Bit No.	(0 is good, 1 is bad)
1	18.7 GHz brightness temperature
2	23.8 GHz brightness temperature
3	34 GHz brightness temperature
4–7	Reserved
All 8	Missing value

0 40 013***Radiometer brightness temperature interpretation flag****Code table 0 40 013*

Code figure	
0	Interpolation with no gap between JMR data
1	Interpolation with gaps between JMR data
2	Extrapolation of JMR data
3	Failure of extrapolation and interpolation
4–6	Reserved
7	Missing value

0 40 020***GqisFlagQualDetailed – quality flag for the system****Flag table 0 40 020*

Bit No.	
1	NZPD and complex calibration error
2	Band 3 affected by spike
3	Band 3 affected by saturation
4	Band 2 affected by spike
5	Band 1 affected by spike
6	Overflow/under flow
7	On-board processing error
8	Spectral calibration error
9	Radiometric calibration error
10	Missing AVHRR data
11	Missing IIS data
12	Missing sounder data
13	GqisFlagQual summary flag for all bands
14	On-ground processing error
15	Inter-calibration error IASI/AVHRR
16	Spare
All 17	Missing value

0 40 023***Auxiliary altimeter state flags****Flag table 0 40 023*

Bit No.	
1	Band sequence (0 = 3Ku_1C_3Ku, 1 = 2Ku_1C_2Ku)
2	C band frequency (0 = 320 MHz, 1 = 100 MHz)
3	C band status (0 = On, 1 = Off)
4	Ku band status (0 = On, 1 = Off)
All 5	Missing value

0 40 024***Meteorological map availability****Code table 0 40 024*

Code figure	
0	2 maps available (6 hours apart)
1	2 maps available (> 6 hours apart)
2	1 map available; data extrapolated
3	No maps used
4–6	Reserved
7	Missing value

0 40 025***Interpolation flag for mean diurnal tide****Code table 0 40 025*

Code figure	
0	Good
1	Bad
2	Reserved
3	Missing value

0 40 028***GMI quality flag****Code table 0 40 028*

Code figure	
0	Good data
1	Possible sun glint
2	Possible radio-frequency interference
3	Degraded geolocation data
4	Data corrected for warm load intrusion
5	Scan blanking on
6	Data is missing from file or unreadable
7	Unphysical brightness temperature
8	Error in geolocation data
9	Data missing in one channel
10	Data missing in multiple channels
11	Latitude/longitude values are out of range
12	Non-normal status modes
13	Distance to corresponding low frequency pixel > 7 km
14	Reserved
15	Missing value (no quality information available)

0 40 036***Lidar L2b classification type****Code table 0 40 036*

Code figure	
0	Clear
1	Cloud
2–14	Reserved
15	Missing value

0 40 043***Satellite manoeuvre indicator****Code table 0 40 043*

Code figure	
0	The platform is not undergoing a manoeuvre
1	The platform is undergoing a manoeuvre, nominal processing
2	The platform is undergoing a manoeuvre, no processing
3–6	Reserved
7	Missing value

0 40 045***Cloud formation and height assignment****Flag table 0 40 045*

Bit No.	
1	Cloud products retrieved with the chi-squared method
2	Cloud products retrieved with the CO ₂ -slicing
3	Height assignment performed with statistical first guess retrieval
4	Height assignment performed with NWP forecasts
All 5	Missing value

0 40 046***Cloudiness summary****Code table 0 40 046*

Code figure	
0	The IASI IFOV is clear
1	Small cloud contamination possible
2	The IASI IFOV is partially covered by clouds
3	High or full cloud coverage
4–6	Reserved
7	Missing value

0 40 047***Validation flag for IASI or IASI-NG level 1 product****Code table 0 40 047*

Code figure	
0	The measurements and side information are available and of good quality for L2 processing
1	The L1c products are of degraded quality according to L1c flags, no L2 processing
2	Quality control indicates that the L1c data are of degraded quality (not indicated by the IASI L1c flags), no L2 processing
3–6	Reserved
7	Missing value

0 40 048**Validation flag of AMSU-A level 1 data flow***Code table 0 40 048*

Code figure	
0	The expected AMSU measurements are available, of good quality and collocated with IASI for processing
1	AMSU-A data are available but of degraded quality (according to AMSU L1 flags or QC tests) and not used for processing
2	No coincident (time and space) AMSU measurements available for processing
3–6	Reserved
7	Missing value

0 40 049**Cloud tests executed and results***Flag table 0 40 049*

Bit No.	
1–3	Reserved
4	IASI cloud optical thickness indicates a cloud
5	IASI cloud optical thickness computed
6	AVHRR heterogeneity test indicates a cloud
7	AVHRR heterogeneity test executed
8	IASI-AVHRR ANN cloud test indicates a cloud
9	IASI-AVHRR ANN cloud test executed
10	AVHRR integrated cloud fraction indicates a cloud
11	AVHRR integrated cloud fraction assessed
12	AMSU cloud test indicates a cloud
13	AMSU cloud test executed
14	IASI Window cloud test indicates a cloud
15	IASI Window cloud test executed
All 16	Missing value

0 40 050**Retrieval initialization***Flag table 0 40 050*

Bit No.	
1–4	Reserved
5	MHS included
6	AMSU included
7	IASI included
All 8	Missing value

0 40 051***Convergence of the iterative retrieval****Code table 0 40 051*

Code figure	
0	Optimal estimation methods (OEM) not attempted
1	OEM aborted because first guess residuals too high
2	The minimization did not converge, sounding rejected
3	The minimization did not converge, sounding accepted
4	The minimization converged but sounding rejected
5	The minimization converged, sounding accepted
6	Reserved
7	Missing value

0 40 052***Indication of super-adiabatic and super-saturation in final retrieval****Flag table 0 40 052*

Bit No.	
1–3	Reserved
4	Supersaturation conditions in the OEM retrieval
5	Superadiabatic conditions in the OEM retrieval
6	Supersaturation conditions in the first guess
7	Superadiabatic conditions in the first guess
All 8	Missing value

0 40 054***Potential processing and inputs errors****Flag table 0 40 054*

Bit No.	
1	An error has been detected
2	Message from L1
3	Message from L2
4	Message from ancillary data
5	Message from fitting procedure
6	File opening
7	File reading
8	Quality flag
9	Level 2 "from linear regression" (F_Qual), report a pixel where L2 are not fully trusted
10	Empty field or data
11	Missing surface pressure value
12	Radiance filtering
All 13	Missing value

0 40 055***Diagnostics on the retrieval****Flag table 0 40 055*

Bit No.	
1	Radiance filtering
2	Polar regions
3	Location in the night
4	Negative altitude surface below mean sea level
5	Cloud covered scene
6	Scene above the sea
7	Scene above desert
8	Skin temperature
9	Skin temperature differential
10	Spectral line contrast too weak
11	Maximum number of iterations exceeded
12	Negative partial columns
13	Matrix ill conditioned
14	Fit diverged
15	Error in GNU scientific library (GSL) usage
16	Residuals "biased"
17	Residuals "sloped"
18	Residuals root mean square (RMS) error is large
19	Weird averaging kernels
20	Ice presence detected
All 21	Missing value

0 40 056***General retrieval quality****Code table 0 40 056*

Code figure	
0	Use not recommended
1	Use with caution
2	Best quality
3–6	Reserved
7	Missing value

0 40 057***IASI level 2 retrieval flags****Flag table 0 40 057*

Bit No.	
1	An error has been detected
2	Message from L1
3	Message from L2
4	Message from ancillary data
5	Message from fitting procedure
6	Reserved
7	Bad L1 or L2 flag raised
8	Level 2 not fully trusted
9	Missing temperature or humidity levels in the vertical profile
10	Missing surface pressure value
11	Radiance filtering
12	Polar regions
13	Location in the night
14	Negative altitude
15	Cloud covered scene
16	Scene above the sea
17	Scene above desert
18	Missing skin temperature
19	Retrieved skin temperature too different from model
20	Spectral line contrast too weak
21	Maximum number of iterations exceeds
22	Negative partial columns
23	Matrix ill conditioned
24	Fit diverged
25	Error in GSL usage
26	Residuals biased
27	Residuals sloped
28	Residuals RMS error is large
29	Weird averaging kernels
30	Ice presence detected
All 31	Missing value

0 40 068***General retrieval quality flag for SO2****Code table 0 40 068*

Code figure	
0	Values calculated with IASI L2
1	Pressure and temperature profiles missing in IASI L2 data; model/forecast data used instead
2	Best quality
3–14	Reserved
15	Missing value

0 40 074***General interferometry quality flags****Code table 0 40 074*

Code figure	
1	Incompatibility of a scan angle for electroencephalogram
2	Calibration failure (limit of black body temperature reached, not enough sources for interferometry, etc.)
3	Geolocation executed taking into account the orientation of the spacecraft and using the star catalogue
4	High level of cryogenic sediment reached, requiring outgassing of the radiation cooler. Set when NESR level of the ice cover threshold crossed.
5	Interferometry package flag
6	General accuracy flag
7	Noise present during the interferometry
8	Outgassing of the radiation cooler
9	Flag preceding the first 24 hours/day mark (set to on as a rule)
10	Telemetry package flag
11–15	Reserved
All 16	Missing value

0 42 004***Confidence of inversion for each partition of swell wave spectra***

Code table 0 42 004

Code figure	
0	Wave direction resolved
1	180-degree ambiguity not resolved
2–14	Reserved
15	Missing

Provisional Copy
2023

c. WMO CF-Extensions

Definitions

CF Conventions: The Climate and Forecast Conventions for netCDF (CF Conventions) define a minimum set of metadata required to ensure that conforming netCDF files meet a basic level of self-description and interoperability. The required (minimal) set of metadata ensures that all variables in a dataset have “an associated description of what it represents, including physical units if appropriate, and that each value can be located in space (relative to earth-based coordinates) and time”. Additional metadata are defined by the CF Conventions but are only recommended where they may not be needed or appropriate for all datasets.

Current and previous versions of the CF Conventions can be found at: <https://cfconventions.org/>.

WMO-CF Extensions: The WMO-CF Extensions build on the CF Conventions to provide the framework for standardizing semantics and metadata, further reducing the effort involved in specifying data products and increasing interoperability. The WMO-CF:

- Define additional metadata requirements or recommendations that are not defined by the CF Conventions;
- Specify the set of optional CF Conventions metadata that this extension requires, making those optional metadata mandatory.

WMO-CF Profiles: The WMO-CF Profiles implement the WMO-CF Extensions for different data types by, inter alia: defining the standardized metadata and semantics; specifying the names of dimension and coordinate variables; and specifying the ordering of dimensions. The WMO-CF Profiles reduce the degrees of freedom available when creating netCDF files, increasing the standardization of data from different publishers for the same type of data.

FM NUMBERS OF WMO-CF PROFILES

FM 301-2022 WMO-CF Radial	Reports from operational weather radar
FM 302-2022 WMO-CF Marine Trajectory	Profile for the representation of meteorological/oceanographic observations along a trajectory within the ocean (or other body of water) or at/near the ocean surface.

Note: Example observing platforms for FM302-2022 include, inter alia: crewed vessels making observations at the sea surface along a track; autonomous surface vehicles making similar measurements; and oceanographic gliders making measurements along a track.

WMO-CF GENERAL REGULATIONS:

WMO-CF.1 NetCDF version and features

WMO-CF.1.1 WMO-CF files should be encoded in version 4 of the NetCDF format.

WMO-CF.1.2 String data should be encoded using the string atomic data type.

WMO-CF.2 Representation of information in the WMO-CF Extensions and WMO-CF Profiles

WMO-CF.2.1 Data shall conform with version 1.8 or higher of the netCDF conventions for CF (Climate and Forecast) metadata (CF hereafter). The version shall be specified in the *Conventions* global attribute (see Regulation WMO-CF.6).

Note: May conform with version 1.3 or higher of the Attribute Convention for Data Discovery (ACDD) conventions. Where this is the case, the version is recommended to be specified in the *Conventions* global attribute (see Regulation WMO-CF.6). The

ACDD conventions can be found at:
https://wiki.esipfed.org/Attribute_Convention_for_Data_Discovery_1-3.

- WMO-CF.2.2 Data shall also conform with the regulations and the WMO-CF extensions defined within this document.
- WMO-CF.2.3 Data conforming with the WMO-CF Extensions shall be identified by the use of the label *WMO-CF n.n* in the *Conventions* global attribute (see Regulation WMO-CF.6) where *n.n* is the version number.
- WMO-CF.2.4 Data shared on the WIS shall conform with one of the WMO-CF Profiles defined within this document.
- WMO-CF.2.5 Creators of WMO-CF files shall ensure that they validate against the specified CF conventions and the WMO-CF Extensions.
- WMO-CF.2.6 Attributes defined as part of the WMO-CF Extensions shall use the *wmo* namespace (double underscore).
- WMO-CF.2.7 Any attribute using the *wmo* namespace but not defined as part of the WMO-CF Extensions shall be invalid.
- WMO-CF.3 Dimensions and Coordinate Variables**
- WMO-CF.3.1 Dimension names shall be specified within the WMO-CF Profiles.
- WMO-CF.3.2 The order of the dimensions within a variable shall be specified within the WMO-CF Profiles.
- WMO-CF.3.3 The coordinate variable names shall be defined within the WMO-CF Profiles.
- WMO-CF.3.4 The *standard_name* attribute shall be used for all coordinate variables.
- WMO-CF.3.5 The *units* attribute shall be used for all coordinate variables.
- WMO-CF.3.6 The *axis* attribute shall be used to indicate the spatiotemporal coordinates (X, Y, Z, T) when present.
- WMO-CF.3.7 When longitude and latitude are reported in units of degrees these shall be qualified with the direction, i.e. *degrees north* and *degrees east*.
- WMO-CF.3.8 Time coordinate variables (T) shall include the *calendar* attribute.
- WMO-CF.4 Station identifiers**
- WMO-CF.4.1 Each station included in a data file shall be identifiable via:
- WMO-CF.4.1.1 A WIGOS Station Identifier (WSI), or
- WMO-CF.4.1.2 A traditional WMO Identifier (e.g. 5-digit or 7-digit code), if no WIGOS Station Identifier has been assigned, or
- WMO-CF.4.1.3 An alternative station identifier, if no WIGOS Station Identifier or traditional WMO Identifier has been assigned. For example, ship ITU callsign.
- WMO-CF.4.2 The *WIGOS Station Identifier* shall be stored as a string using the standard notation:
- WMO-CF.4.2.1 <WIGOS station identifier series>-<issuer of identifier>-<issue number>-<local identifier>
- WMO-CF.4.3 The form of the traditional WMO Identifier to be used shall be specified within the WMO-CF profiles.
- WMO-CF.4.4 The form of the alternative station identifier, if required, shall be specified within the WMO-CF profiles.

WMO-CF.4.5 Data files containing data from a single station shall store the WIGOS Station Identifier and traditional WMO identifier using the `wmo_wsi` and `wmo_id` global attributes respectively. See WMO-CF.6.10.6 and WMO-CF.6.10.7.

WMO-CF.4.6 The rules specified in the WMO Manual on the WMO Integrated Global Observing System (WMO-No. 1160) shall be followed for WMO observing stations.

WMO-CF.4.7 Data files containing data from multiple stations shall store station identifiers according to the WMO-CF profiles.

WMO-CF.5 General regulations for variables and variable attributes

WMO-CF.5.1 A distinction is made between those variables that contain observed, measured or simulated data (hereafter data variables, see Regulation WMO-CF.5.2), those containing metadata or ancillary information (ancillary data, see Regulation WMO-CF.5.3) and those containing information defining the dimensions and coordinates (dimension and coordinate variables, see Regulation WMO-CF.3).

WMO-CF.5.2 Data variables

WMO-CF.5.2.1 Table WMO-CF-1 below lists the variable attributes that are defined for observed data and for use with the WMO-CF Extensions.

WMO-CF.5.2.2 Attributes marked mandatory (M) shall be included for all variables.

WMO-CF.5.2.3 Attributes marked conditional (C) shall be included when the conditions described below are met.

WMO-CF.5.2.4 Attributes marked optional (O) are optional.

WMO-CF.5.2.5 Additional attributes may be defined as part of the WMO-CF Profiles.

WMO-CF.5.2.6 Other attributes not defined, either in the general regulations or in the profiles, may be used but have no meaning within the context of the WMO-CF Extensions.

WMO-CF.5.2.7 The `standard_name` attribute shall be used when there is an existing definition in the CF conventions.

WMO-CF.5.2.8 The `long_name` attribute should be used to describe the content of the variable.

WMO-CF.5.2.9 The `wmo_parameter_uri` and `wmo_parameter_name` attributes shall be used to unambiguously identify the observed/measured parameter being reported.

WMO-CF.5.2.10 The `wmo_parameter_uri` shall point to an entry in a codes registry authorized for use within the profile of the data product. The use of codes.wmo.int is authorized for all profiles; individual WMO-CF Profiles may additionally define their own list of authorized registries.

WMO-CF.5.2.11 The `units` attribute shall be reported for all variables that represent dimensional quantities.

WMO-CF.5.2.12 When reported, the `units` shall be selected from those in WMO Common Code Table C-6 and represented using a string recognisable by the UDUnits package.

WMO-CF.5.2.13 If a variable is packed into an integer value the `scale_factor` and `add_offset` shall be used as defined in the NetCDF User Guide (NUG) and in the CF Conventions.

Note: The current version of the NetCDF User Guide can be found at:
https://www.unidata.ucar.edu/software/netcdf/docs/user_guide.html

WMO-CF.5.2.14 Variables that contain missing data shall include the `FillValue` attribute and use this to indicate the default fill value and value of missing data.

WMO-CF.5.2.15 Variables that contain missing data shall also include the `valid_range` attribute to indicate the range of valid values expected.

WMO-CF.5.2.16 The `valid_range` attribute shall indicate the full range of values that are valid and not just the range of values reported in the file.

- WMO-CF.5.2.17 For observed variables where metadata or other information is available in an ancillary variable the link shall be made using the *ancillary_variables* attribute.
- WMO-CF.5.2.18 Where there is a requirement for metadata to be reported this shall be included in the profile definitions below.
- WMO-CF.5.3 Ancillary data**
- WMO-CF.5.3.1 Ancillary variables contain metadata or information about one or more observed variables.
- WMO-CF.5.3.2 Ancillary variables shall be referenced from the associated data variables with CF *ancillary_variables* attributes as described in CF Section 3.4 "Ancillary Variables".
- WMO-CF.5.3.3 Where the ancillary variable has a physical meaning, for example observation height above a reference surface, then the rules for observed data shall also apply.
- WMO-CF.5.3.4 For efficiency the ancillary data may be encoded using either flags or masks following the CF conventions, see example 1.
- WMO-CF.5.3.5 When ancillary data are encoded the *flag_meanings* and either *flag_values* or *flag_masks* shall be included in the file following the CF conventions.
- WMO-CF.5.3.6 Where a code list or controlled vocabulary is specified in a WMO-CF profile then only values from that code list shall be valid for the *flag_meanings*.
- WMO-CF.5.3.7 The relevant code list or controlled vocabulary shall be indicated via the *wmo_parameter_name* and *wmo_parameter_uri* attribute, see example 1.
- WMO-CF.5.3.8 Attributes containing Boolean values shall be encoded as either the string 'true' or 'false'.
- WMO-CF.5.3.9 No meaning or default value should be inferred by the absence of an ancillary variable.
- WMO-CF.5.3.10 No meaning shall be inferred by data set to the missing value.
- WMO-CF.6 Global attributes**
- WMO-CF.6.1 Table WMO-CF-2 lists the global attributes defined for use with WMO CF-1.0. This includes attributes defined in other conventions, such as the Attribute Convention for Data Discovery 1-3 (ACDD 1-3) and the CF conventions, and the netCDF user guide (NUG).
- WMO-CF.6.2 Attributes marked mandatory (M) shall be included for all variables.
- WMO-CF.6.3 Attributes marked conditional (C) shall be included when the conditions described below are met.
- WMO-CF.6.4 Attributes marked optional (O) are optional.
- WMO-CF.6.5 Additional attributes may be defined as part of the WMO-CF Profiles.
- WMO-CF.6.6 Other attributes not defined in the general regulations, the profiles or the CF conventions may be used but have no meaning within the context of the WMO-CF Extensions.
- WMO-CF.6.7 The *Conventions* attribute shall be used to indicate the conventions followed by a dataset. Where multiple conventions are followed these shall be comma separated.
- WMO-CF.6.8 The *featureType* attribute shall be used for files containing discrete sampling geometries to indicate the type of geometry.
- WMO-CF.6.9 The *standard_name_vocabulary* attribute shall be used to indicate the version of the *standard_name* table used.
- WMO-CF.6.10 The following global attributes are defined as part of the WMO-CF Extensions and

shall be included:

- WMO-CF.6.10.1 wmo_cf_profile. The wmo_cf_profile attribute shall indicate the specific profile included within a file and shall reference one of the profiles defined within this volume.
- WMO-CF.6.10.2 wmo_originating_centre. The wmo_originating_centre attribute shall be used to identify the originator of the files. Valid values are defined in Common Code Table C-11. Where data originate from outside of the WMO system the wmo_originating_centre attribute may be omitted.
- WMO-CF.6.10.3 wmo_originating_sub_centre. The wmo_originating_sub_centre attribute shall be used to identify the originating sub centre where different from the originating centre. Valid values are defined in Common Code Table C-12. Where data originate from outside of the WMO system the wmo_originating_sub_centre attribute may be omitted.
- WMO-CF.6.10.4 wmo_data_category. The wmo_data_category attribute shall be included to identify the type of data contained within the file. Valid values are given in Common Code Table C-13.
- WMO-CF.6.10.5 wmo_update_sequence_number. The wmo_update_sequence_number attribute shall be included and used to indicate whether the data are original or updated. The rules shall follow those defined for BUFR (zero for original messages and for messages containing only delayed reports; incremented for the other updates).
- WMO-CF.6.10.6 wmo_wsi. The wmo_wsi attribute shall be used to indicate a WIGOS Station Identifier of the observing station or platform to which the file relates. The wmo_wsi attribute shall be omitted if the file contains data related to multiple stations, or if no WIGOS station identifier has been assigned.
- WMO-CF.6.10.7 wmo_id. The wmo_id attribute shall be used to indicate the traditional WMO identifier of the observing station or platform to which the file relates. The wmo_id attribute shall be omitted if the file contains data related to multiple stations.

WMO-CF.7 Compression and chunking

- WMO-CF.7.1 Compression, or chunking, may be used on variables within a NetCDF file.
- WMO-CF.7.2 Data can furthermore be compressed or chunked using HDF filters. If this is the case however the data producer must use a method that has been agreed upon by ET-Data. In that case the filter in question would be described in this volume. The following minimum requirements shall apply:
- WMO-CF.7.2.1 Decompression algorithm is open;
- WMO-CF.7.2.2 Software implementing this is freely available;
- WMO-CF.7.2.3 Filter number is registered with HDF Group to avoid name clashes.

WMO-CF General Regulations: Tables

Table WMO-CF-1: List of defined variable attributes for ancillary and data variables.

Attribute name	Description	Mandatory (M), Conditional (C) or Optional (O)
<u>standard_name</u>	A standard name that references a description of a variables content in the standard name table.	C - see Regulations WMO-CF.3.4 and WMO-CF.5.2.7. See also profile definitions.
<u>long_name</u>	A descriptive name that indicates a variables content. This name is not standardized.	O

<u>wmo_parameter_uri</u>	<u>Link to external code registry to unambiguously identify the parameter or variable reported. This may be one from the codes.wmo.int registry or from another registry specified in the profile definitions.</u>	<u>M</u>
<u>wmo_parameter_name</u>	<u>Parameter name used to unambiguously identify the parameter or variable reported. Analogous to standard_name.</u>	<u>M</u>
<u>_FillValue</u>	<u>A value used to represent missing or undefined data. Allowed for auxiliary coordinate variables but not allowed for coordinate variables.</u>	<u>C - see Regulation WMO-CF.5.2.14</u>
<u>valid_range</u>	<u>Smallest and largest valid values of a variable.</u>	<u>M</u>
<u>scale_factor</u>	<u>If present for a variable, the data are to be multiplied by this factor after the data are read by an application. See also the add_offset attribute.</u>	<u>O</u>
<u>add_offset</u>	<u>If present for a variable, this number is to be added to the data after it is read by an application. If both scale_factor and add_offset attributes are present, the data are first scaled before the offset is added.</u>	<u>O</u>
<u>units</u>	<u>Units of a variable's content.</u>	<u>C - see Regulations WMO-CF.5.2.11 and WMO-CF.5.2.12</u>
<u>coordinates</u>	<u>Identifies auxiliary coordinate variables, label variables, and alternate coordinate variables.</u>	<u>C - see profile definitions</u>
<u>ancillary_variables</u>	<u>Identifies a variable that contains closely associated data, e.g. the measurement uncertainties of instrument data.</u>	<u>C - see Regulation WMO-CF.5.2.17</u>

Table WMO-CF-2: List of defined global attributes.

Attribute name	Description	Mandatory (M), Conditional (C) or Optional (O)
<u>Conventions</u>	A comma-separated list of the conventions that are followed by the dataset. e.g. NUG, ACDD-1.3, CF-1.8, WMO CF-1.0	<u>M</u>
<u>featureType</u>	Specifies the type of discrete sampling geometry to which the data in the scope of this attribute belongs, and implies that all data variables in the scope of this attribute contain collections of features of that type.	C – see Regulation WMO-CF.6.8, mandatory for discrete sampling geometries.
<u>title</u>	Short description of the file contents.	<u>M</u>
<u>wmo_cf_profile</u>	The WMO CF profile used to represent the data contained within the file.	<u>M</u>
<u>wmo_data_category</u>	The type of data contained within the file according to Common Code Table C-13	<u>M</u>
<u>wmo_data_policy</u>	Options are: core, recommended	<u>M</u>
<u>wmo_originating_centre</u>	The originator of the data according to Common Code Table C-11.	C - see Regulation WMO-CF.6.10.2.
<u>wmo_originating_sub_centre</u>	The originating sub centre for the data if different from the <u>wmo_originating_centre</u> . See common code table C-12	C - see Regulation WMO-CF.6.10.3.
<u>wmo_update_sequence_number</u>	Indicator as to whether the data are original or updated. The rules shall follow those defined for BUFR in Volume I.2 (zero for original messages and for messages containing only delayed reports; incremented for other updates).	C - see Regulation WMO-CF.6.10.5.
<u>wmo_id</u>	The traditional WMO identifier for the observing station/platform.	C - see Regulations WMO-CF.6.10.6 and WMO-CF.6.10.7.
<u>wmo_wsi</u>	The WIGOS Station Identifier (WSI) for the observing station/platform.	C - see Regulations WMO-CF.6.10.6 and WMO-CF.6.10.7.

Examples

Example 1 Minimal example showing the use of flag values and flag meanings attribute to record the anemometer type.

```
int anemometer_type( obs );
anemometer_type:long_name="type of anemometer";
anemometer_type:flag_values= 0, 1, 2, 3, 15;
anemometer_type:flag_meanings="Cup rotor Propeller rotor Sonic Wind observation through ambient noise Missing value";
anemometer_type:wmo_parameter_name="Anemometer type";
anemometer_type:wmo_parameter_uri="http://codes.wmo.int/bufr4/codeflag/0-02-169";
```

FM 301-2022 WMO-CF RADIAL**REGULATIONS****301.1 Scope**

301.1.1 This profile is for the representation of weather radar and lidar data in the native

instrument-centric polar coordinates. Such data is the primary output of the radar/lidar signal processor known as "Level 2" data. This is the lowest level output commonly available from operational instruments and is well suited to data exchange.

301.1.2 The structure of this profile conforms to the WMO Information and Data Models for Radial Radar and Lidar Data. Effort has also been made to maximize compatibility with the CfRadial 2 format from which this profile has been derived.

301.2 Overview

301.2.1 Level 2 radar/lidar data may be conceptualized as a simple hierarchy of data objects where each object contains a collection of objects from the level below. These objects are:

301.2.1.1 Volume – The top-level object for the profile. A Volume is a collection of logically associated sweeps. Typically, these sweeps will represent a continuous or near-continuous series of observations acquired by the instrument during a single cycle of the scan schedule.

301.2.1.2 Sweep – Represents a subset of the data in the volume over which certain fundamental conditions remain constant. A common example is for a sweep to contain the data observed during a single 360-degree scan at a fixed elevation angle.

301.2.1.3 Ray – Represents a collection of data along a single direction of pointing from the instrument.

301.2.1.4 Range Bin – Represents a collection of data within a ray that are related to the same short window of range along the beam propagation path.

301.2.1.5 Dataset – A measured or calculated quantity that is associated with a range bin. Each Dataset will typically represent one of the measured radar moments such as reflectivity or Doppler velocity, but may also be used to store derived information such as quality control metrics.

301.2.2 Within a Sweep all Range Bins contain the same collection of Datasets, and all Rays contain the same collection of Range Bins. This allows the lower three levels of the hierarchy to be collapsed into a collection of 2D variables. Each variable stores a single Dataset, with dimensions for Ray and Range Bin.

301.2.3 To facilitate the hierarchical nature of the data to be represented, netCDF groups are used. The global scope is used to store the Volume object, a group is used for each Sweep object, and a variable within each Sweep group is used for each Dataset. Coordinate variables and ancillary variables within the Sweep groups provide metadata related to the Ray and Range Bin objects.

301.3 Global scope/root group

301.3.1 The global scope of the profile contains data and metadata which are relevant to the entire volume.

301.3.2 Attributes

301.3.2.1 Table 301-1 lists the global attributes that shall be included in addition to those defined under General Regulation WMO-CF.6.

301.3.2.2 Table 301-2 lists the mandatory values that shall be used for the global attributes where defined.

301.3.2.3 Table 301-3 lists additionally defined global attributes that are optional.

301.3.3 Ancillary variables

301.3.3.1 Table 301-4 lists the global variables that shall be included in the global root group.

301.3.3.2 Table 301-5 lists the global variables that should be included in the global/root

group.

301.4 Sweep groups

301.4.1 A sweep group contains all of the data and metadata related to Sweep object. This includes the dimensions and coordinates which define the basic geometry of the sweep (Rays and Range Bins), the measured radar/lidar quantities (Datasets), as well as many supporting ancillary variables. Each sweep group may also contain subgroups to cater for specialized metadata such as monitoring information.

301.4.2 Sweep groups shall be named `sweep <n>` where `<n>` is the sweep number starting at 0 for the first sweep acquired during the volume and increasing sequentially in acquisition order.

301.4.3 Dimensions

301.4.3.1 The `time` dimension shall define the number of Rays in the sweep. It shall be used as the primary dimension for Dataset variables.

301.4.3.2 The `range` dimension shall define the number of Range Bins in the sweep. It shall be used as the secondary dimension for Dataset variables.

301.4.3.3 The `frequency` dimension shall define the number of operating frequencies. Where a single frequency is present this dimension shall have length 1.

301.4.3.4 The `pri` dimension may define the number of pulse repetition times used in a pulsing scheme. This dimension is optional for fixed, staggered and dual PRT schemes but required for more complex schemes.

301.4.4 Coordinate variables

301.4.4.1 Table 301-6 lists the coordinate variables that shall be used in the sweep groups.

301.4.5 Ancillary variables

301.4.5.1 Table 301-7 lists the ancillary variables that shall be included in the sweep groups.

301.4.5.2 Table 301-8 lists the ancillary variables that may be included in the sweep groups.

301.4.6 Dataset variables (observed and quality data)

301.4.6.1 Dataset variables shall have dimensions `(time, range)`.

301.4.6.2 Dataset variables for well-known radar moments shall be named according to Table 301-9.

301.4.6.3 The General Regulations for variables (WMO-CF.5) shall apply, including the regulations on mandatory and optional attributes.

301.4.6.4 The `coordinates` attribute shall be set to `"elevation azimuth range"`

301.4.6.5 Additional attributes for field/geophysical variables are defined in Table 301-10.

301.4.7 Monitoring subgroup

301.4.7.1 If monitoring data is available, a monitoring subgroup will be included in each relevant sweep group, to store the monitoring variables.

301.4.7.2 The group shall be named `monitoring`.

301.4.7.3 Table 301-11 lists the variables that may be included in this subgroup when present.

301.5 Radar parameters group

301.5.1 The radar parameters group holds optional ancillary variables that are specific to the radar instrument.

301.5.2 This group shall be located at the global scope and named radar_parameters.

301.5.3 Table 301-12 lists the variables which may be included in this group.

301.5.4 This group may be omitted from the file if no radar parameters are to be stored.

301.6 Lidar parameters group

301.6.1 The lidar group holds optional ancillary variables that are specific to the lidar instrument.

301.6.2 This group shall be located at the global scope and named lidar_parameters.

301.6.3 Table 301-13 lists the variables which may be included in this group.

301.6.4 This group may be omitted from the file if no lidar parameters are to be stored.

301.7 Radar calibration group

301.7.1 The radar calibration group holds optional ancillary variables that are related to calibrations of the radar instrument. Several calibrations may be stored, typically one per pulse width.

301.7.2 This group shall be located at the global scope and named radar_calibration.

301.7.3 Dimensions

301.7.3.1 The calib dimension shall define the number of calibrations stored.

301.7.4 Table 301-14 lists the ancillary variables which may be included in this group.

301.7.5 This group may be omitted from the file if no radar calibrations are to be stored.

301.8 Lidar calibration group

301.8.1 The lidar calibration group holds optional ancillary variables that are related to calibrations of the lidar instrument.

301.8.2 This group shall be located at the global scope and named lidar_calibration.

301.8.3 No ancillary variables have been defined for this group. It is reserved for future use.

301.8.4 This group may be omitted from the file if no lidar calibration variables are to be stored.

FM 301-2022 Tables

Table 301-1: Global attributes for the global scope/root group that shall be reported in addition to those defined in General Regulation WMO-CF.6.

Name	Type	Convention	Value or description
instrument_name	string	CF/Radial	Name of radar or lidar
institution	String	CF	See CF Conventions Appendix A
references	String	CF	See CF Conventions Appendix A
source	String	CF	See CF Conventions Appendix A
history	String	CF	See CF Conventions Appendix A
comment	String	CF	See CF Conventions Appendix A
platform_is_mobile	string	CF/Radial	"false" (mobile platforms are not supported by this profile)

Table 301-2: Mandatory values defined for the global attributes.

Attribute name	Type	Value
Conventions	string	"CF-1.8, WMO CF-1.0"
wmo_cf_profile	string	"FM 301-2022"

Table 301-3: Global attributes defined for this profile that are conditional or optional.

Attribute name	Type	Convention	Value or description
<u>site_name</u>	string	CF/Radial	Name of site where data were gathered
<u>scan_name</u>	string	CF/Radial	Name of scan strategy used, if applicable
<u>scan_id</u>	int	CF/Radial	Scan strategy id, if applicable. Assumed 0 if missing.
<u>ray times increase</u>	Boolean	CF/Radial	"true" or "false". Set to true if ray times increase monotonically throughout all of the sweeps in the volume.
<u>simulated</u>	Boolean	ODIM	"true" or "false". Set to true if data in this file are simulated.

Table 301-4a: Metadata variables with global scope that shall be included in WMO-CF Radial files. Units and other attributes are defined in Table 301-4b.

variable path/name	Dimensions	Type	Comment
<u>/volume_number</u>		int	Volume numbers are sequential, relative to some arbitrary start time, and may wrap.
<u>/time_coverage_start</u>		string	UTC time of first ray in file.
<u>/time_coverage_end</u>		string	UTC time of the last ray in the file.
<u>/latitude</u>		double	Latitude of instrument using WGS84. For a mobile platform this is the latitude of the instrument at the start of the volume
<u>/longitude</u>		double	Longitude of instrument using WGS84. For a mobile platform this is the longitude of the instrument at the start of the volume
<u>/altitude</u>		double	Altitude of instrument above mean sea level, using WGS84 and EGM2008 geoid corrections. For a scanning radar this is the centre of rotation of the antenna. For a mobile platform this is the altitude at the start of the volume.
<u>/platform_type</u>		string	Type of platform upon which the radar system is mounted. Allowed values are listed in Table 15
<u>/instrument_type</u>		string	Type of instrument. Allowed values are listed in Table 15.

Table 301-4b: Mandatory attributes for the global variables defined in Table 301-4a.

Variable path/name	Attribute	Type	Value
<u>/time_coverage_start</u>	units	string	"seconds since <reftime>" where <reftime> is an ISO8601 time string of the form YYYY-MM-DDThh:mm:ssZ
	calendar	string	See CF Conventions Appendix A
	standard_name	string	"time"
<u>/time_coverage_end</u>	units	string	"seconds since <reftime>" where <reftime> is an ISO8601 time string of the form YYYY-MM-DDThh:mm:ssZ
	calendar	string	See CF Conventions Appendix A
	standard_name	string	"time"
<u>/latitude</u>	units	string	"degrees_north"
	standard_name	string	"latitude"
<u>/longitude</u>	units	string	"degrees_east"
	standard_name	string	"longitude"
<u>/altitude</u>	units	string	"meters"
	standard_name	string	"height above reference ellipsoid"

Table 301-5a: Metadata variables with global scope that are conditional or optional. Attributes are listed in Table 301-5b.

Variable path/name	Dimensions	Type	Comment
<u>/altitude_aql</u>		double	Altitude of instrument above ground level. This is the centre of rotation of the antenna
<u>/primary_axis</u>		string	Principle axis of rotation. Allowed values are specified in Table 301-15.
<u>/status_str</u>		string	General-purpose string for storing any information that is not included in other parts of the data structure. Any text-based encoding may be used including simple text, XML, JSON etc

Table 301-5b: Attributes for those variables listed in Table 301-5a.

Variable path/name	Attribute	Type	Value
--------------------	-----------	------	-------

<u>/altitude_aql</u>	<u>units</u> <u>standard_name</u>	<u>string</u> <u>string</u>	<u>"meters"</u> <u>"height"</u>
----------------------	--------------------------------------	--------------------------------	------------------------------------

Table 301-6a: Coordinate variables for the sweep groups. Attributes are defined in Table 301-6b.

<u>Variable path/name</u>	<u>Dimensions</u>	<u>Type</u>	<u>Comment</u>
<u>/sweep <n>/time</u>	<u>(time)</u>	<u>double</u>	<u>Coordinate variable for the time dimension. Each value is the time at centre of each ray</u>
<u>/sweep <n>/range</u>	<u>(range)</u>	<u>float</u>	<u>Coordinate variable for the range dimension. Each value is range along beam propagation path to the centre of each range bin</u>
<u>/sweep <n>/frequency</u>	<u>(frequency)</u>	<u>float</u>	<u>List of operating frequencies in Hertz. In most cases only a single frequency is used.</u>

Table 301-6b: Mandatory attributes for the sweep group coordinate variables listed in Table 301-6a.

<u>Variable path/name</u>	<u>attribute</u>	<u>kind</u>	<u>value</u>
<u>/sweep <n>/time</u>	<u>units</u>	<u>string</u>	<u>"seconds since <reftime>" where <reftime> is an ISO8601 time string of the form YYYY-MM-DDThh:mm:ssZ</u> <u>See CF Conventions Appendix A.</u>
<u>/sweep <n>/range</u>	<u>calendar</u>	<u>string</u>	<u>"time"</u>
	<u>standard_name</u>	<u>string</u>	<u>"meters"</u>
	<u>units</u>	<u>string</u>	<u>"projection_range_coordinate"</u>
	<u>standard_name</u>	<u>string</u>	<u>"range to measurement volume"</u>
	<u>long_name</u>	<u>string</u>	<u>"radial range coordinate"</u>
	<u>axis</u>	<u>string</u>	<u>"true" if range bins are evenly spaced</u>
	<u>spacing is constant</u>	<u>Boolean/</u> <u>string</u>	
	<u>meters to center of first gate</u>	<u>float</u>	<u>Range to start of first gate in meters</u>
	<u>meters between gates</u>	<u>float</u>	<u>Range between consecutive gates in meters. Required if</u> <u>spacing_is_constant is true</u>
<u>/frequency</u>	<u>units</u> <u>standard_name</u>	<u>string</u> <u>string</u>	<u>"s -1"</u>

Table 301-7a: Mandatory metadata variables that shall be included in the sweep groups. Table 301-7b lists the attributes for these variables where defined.

<u>Variable path/name</u>	<u>Dimensions</u>	<u>Kind</u>	<u>Comment</u>
<u>/sweep <n>/sweep_number</u>	<u>(range)</u>	<u>int</u>	<u>The index of the sweep within the volume, 0-based.</u>
<u>/sweep <n>/sweep_mode</u>	<u>none</u>	<u>string</u>	<u>Type of sweep that was performed. Allowed values are listed in Table 301-15</u>
<u>/sweep <n>/follow_mode</u>	<u>none</u>	<u>string</u>	<u>Target following mode used to control antenna pointing. Allowed value are listed in Table 301-15.</u>
<u>/sweep <n>/prt_mode</u>	<u>none</u>	<u>string</u>	<u>Pulsing mode used for sweep. Standard allowed values are listed in Table 301-15. More complicated pulsing schemes may also be represented using a sequence of "H" and "V" characters. For example "HHVVH"</u>
<u>/sweep <n>/fixed_angle</u>	<u>none</u>	<u>float</u>	<u>Target angle for the sweep. In most sweep modes this is the elevation angle, for RHI mode this is the azimuth angle</u>
<u>/sweep <n>/azimuth</u>	<u>(time)</u>	<u>float</u>	<u>Azimuth of the antenna relative to true north at the centre of dwell for each ray of the sweep.</u>
<u>/sweep <n>/elevation</u>	<u>(time)</u>	<u>float</u>	<u>Elevation of the antenna relative to true north at the centre of dwell for each ray of the sweep.</u>

Table 301-7b: Mandatory attributes defined for the sweep group metadata variables listed in Table 301-7a.

<u>Variable path/name</u>	<u>attribute</u>	<u>kind</u>	<u>value</u>
<u>/sweep <n>/fixed_angle</u>	<u>units</u>	<u>string</u>	<u>"degrees"</u>
<u>/sweep <n>/azimuth</u>	<u>units</u>	<u>string</u>	<u>"degrees"</u>
	<u>standard_name</u>	<u>string</u>	<u>"sensor to target azimuth angle"</u>
	<u>long_name</u>	<u>string</u>	<u>"Azimuth angle from true north"</u>

<u>/sweep <n>/elevation</u>	<u>axis</u> <u>units</u> <u>standard name</u> <u>long_name</u> <u>axis</u>	<u>string</u> <u>string</u> <u>string</u> <u>string</u> <u>string</u>	<u>"radial azimuth coordinate"</u> <u>"degrees"</u> <u>"sensor to target elevation angle"</u> <u>"Elevation angle from horizontal plane"</u> <u>"radial elevation coordinate"</u>
-----------------------------------	--	---	---

Table 301-8a: Optional/conditional metadata variables that may be reported in the sweep groups.
Attributes are defined in Table 301-8b.

<u>Variable path/name</u>	<u>Dimensions</u>	<u>Kind</u>	<u>Comment</u>
<u>/sweep <n>/polarization_mode</u>	<u>none</u>	<u>string</u>	Polarization mode used during sweep. Allowed values are listed in Table 301-15.
<u>/sweep <n>/polarization_sequence</u>	<u>(prt)</u>	<u>string</u>	Polarization sequence for each PRT that is used. Only applicable if <i>prt_mode</i> is "hybrid". As an example, the form of it would be ['H','H','V','V','H'] for HHV VH pulsing
<u>/sweep <n>/rays_are_indexed</u>	<u>none</u>	<u>Boolean/</u> <u>string</u>	Indicates whether or not the ray angles (elevation in RHI sweep mode, azimuth in other modes) are indexed to a regular grid.
<u>/sweep <n>/rays_angle_resolution</u>	<u>none</u>	<u>float</u>	If <i>rays_are_indexed</i> is true, this is the resolution of the angular grid – i.e. the delta angle between successive ray
<u>/sweep <n>/qc_procedures</u>	<u>none</u>	<u>string</u>	General-purpose string for storing any information that describes the QC procedures performed on this sweep. Any text-based encoding may be used including simple text, XML, JSON etc
<u>/sweep <n>/target_scan_rate</u>	<u>none</u>	<u>float</u>	Intended scan rate for this sweep. The actual scan rate is stored in <i>scan_rate</i> . This variable is optional. Omit if not available.
<u>/sweep <n>/scan_rate</u>	<u>(time)</u>	<u>float</u>	Actual antenna scan rate. Set to negative if counter- clockwise in azimuth or decreasing in elevation. Positive otherwise.
<u>/sweep <n>/antenna_transition</u>	<u>(time)</u>	<u>byte</u>	1 if antenna is in transition, i.e. between sweeps, 0 if not. If transition rays are not included in the file this variable may be omitted.
<u>/sweep <n>/pulse_width</u>	<u>(time)</u>	<u>float</u>	Length of transmitted pulse.
<u>/sweep <n>/calib_index</u>	<u>(time)</u>	<u>int</u>	Index for the radar calibration that applies to this pulse width. The value must match one of the calibration indexes listed by <i>/radar_calibration/calib_index</i> .
<u>/sweep <n>/rx_range_resolution</u>	<u>(time)</u>	<u>float</u>	Resolution of the raw receiver samples if different to 'meters between gates'. Raw data may be resampled before data storage.
<u>/sweep <n>/prt</u>	<u>(time)</u>	<u>float</u>	Pulse repetition time. For staggered prt, also see <i>prt_ratio</i> .
<u>/sweep <n>/prt_ratio</u>	<u>(time)</u>	<u>float</u>	Ratio of prt/prt2. For dual/staggered prt mode.
<u>/sweep <n>/prt_sequence</u>	<u>(time, prt)</u>	<u>float</u>	Sequence of prts used. Optional for fixed, staggered and dual, which can make use of <i>prt</i> and <i>prt_ratio</i> . Required for more complicated pulsing schemes.
<u>/sweep <n>/nyquist_velocity</u>	<u>(time)</u>	<u>float</u>	Unambiguous velocity. This is the effective Nyquist velocity after unfolding. See also the field-specific attributes <i>fold_limit_lower</i> and <i>fold_limit_upper</i> .
<u>/sweep <n>/unambiguous_range</u>	<u>(time)</u>	<u>float</u>	Unambiguous range
<u>/sweep <n>/n_samples</u>	<u>(time)</u>	<u>int</u>	Maximum number of samples used to compute moments. The actual number of samples used may vary from field to field. This value refers to the maximum number of samples used for any field. The Dataset attribute <i>sampling_ratio</i> is the actual number of samples used for a given field, divided by <i>n_samples</i> . It will generally be 1.0, the default.

Table 301-8b: Attributes for the optional sweep group metadata variables defined in Table 301-8a.

Variable path/name	Attribute	Kind	Value
/sweep <n>/rays angle resolution	units	string	"degrees"
/sweep <n>/target scan rate	units	string	"degrees/s"
/sweep <n>/scan rate	units	string	"degrees/s"
/sweep <n>/pulse width	units	string	"seconds"
/sweep <n>/rx range resolution	units	string	"meters"
/sweep <n>/prt	units	string	"seconds"
/sweep <n>/prt sequence	units	string	"seconds"
/sweep <n>/nyquist velocity	units	string	"meters/s"
/sweep <n>/unambiguous range	units	string	"meters"

Table 301-9: Dataset variable names, standard_name and long_name attributes for well-known radar moments.

Variable path/name	Quantity (standard_name)	Description (long_name)
/sweep <n>/DBZH	radar equivalent reflectivity factor h	Equivalent reflectivity factor H
/sweep <n>/DBZV	radar equivalent reflectivity factor v	Equivalent reflectivity factor V
/sweep <n>/ZH	radar linear equivalent reflectivity factor h	Linear equivalent reflectivity factor H
/sweep <n>/ZV	radar linear equivalent reflectivity factor v	Linear equivalent reflectivity factor V
/sweep <n>/DBTH	radar equivalent reflectivity factor h	Total power H (uncorrected reflectivity)
/sweep <n>/DBTV	radar equivalent reflectivity factor v	Total power V (uncorrected reflectivity)
/sweep <n>/TH	radar linear equivalent reflectivity factor h	Linear total power H (uncorrected reflectivity)
/sweep <n>/TV	radar linear equivalent reflectivity factor v	Linear total power V (uncorrected reflectivity)
/sweep <n>/VRADH	radial velocity of scatterers away from instrument h	Radial velocity of scatterers away from instrument H
/sweep <n>/VRADV	radial velocity of scatterers away from instrument v	Radial velocity of scatterers away from instrument V
/sweep <n>/WRADH	radar doppler spectrum width h	Doppler spectrum width H
/sweep <n>/WRADV	radar doppler spectrum width v	Doppler spectrum width V
/sweep <n>/ZDR	radar differential reflectivity hv	Log differential reflectivity H/V
/sweep <n>/LDR	radar linear depolarization ratio	Log-linear depolarization ratio HV
/sweep <n>/LDRH	radar linear depolarization ratio h	Log-linear depolarization ratio H
/sweep <n>/LDRV	radar linear depolarization ratio v	Log-linear depolarization ratio V
/sweep <n>/PHIDP	radar differential phase hv	Differential

<u>Variable path/name</u>	<u>Quantity (standard_name)</u>	<u>Description (long_name)</u>
<u>/sweep <n>/KDP</u>	<u>radar_specific_differential_phase_hv</u>	<u>phase HV</u> <u>Specific differential phase HV</u>
<u>/sweep <n>/PHIHx</u>	<u>radar_differential_phase_copolar_h_crosspolar_v</u>	<u>Cross-polar differential phase</u>
<u>/sweep <n>/RHOHV</u>	<u>radar_correlation_coefficient_hv</u>	<u>Correlation coefficient HV</u>
<u>/sweep <n>/RHOHX</u>	<u>radar_correlation_coefficient_copolar_h_crosspolar_v</u>	<u>Co-to-cross polar correlation coefficient H</u>
<u>/sweep <n>/RHOVX</u>	<u>radar_correlation_coefficient_copolar_v_crosspolar_h</u>	<u>Co-to-cross polar correlation coefficient V</u>
<u>/sweep <n>/DBM</u>	<u>radar_received_signal_power</u>	<u>Log power</u>
<u>/sweep <n>/DBMHC</u>	<u>radar_received_signal_power_copolar_h</u>	<u>Log power co-polar H</u>
<u>/sweep <n>/DBMHX</u>	<u>radar_received_signal_power_crosspolar_h</u>	<u>Log power cross-polar H</u>
<u>/sweep <n>/DBMVC</u>	<u>radar_received_signal_power_copolar_v</u>	<u>Log power co-polar V</u>
<u>/sweep <n>/DBMVX</u>	<u>radar_received_signal_power_crosspolar_v</u>	<u>Log power cross-polar V</u>
<u>/sweep <n>/SNR</u>	<u>radar_signal_to_noise_ratio</u>	<u>Signal-to-noise ratio</u>
<u>/sweep <n>/SNRHC</u>	<u>radar_signal_to_noise_ratio_copolar_h</u>	<u>Signal-to-noise ratio co-polar H</u>
<u>/sweep <n>/SNRHx</u>	<u>radar_signal_to_noise_ratio_crosspolar_h</u>	<u>Signal-to-noise ratio cross-polar H</u>
<u>/sweep <n>/SNRVC</u>	<u>radar_signal_to_noise_ratio_copolar_v</u>	<u>Signal-to-noise ratio co-polar V</u>
<u>/sweep <n>/SNRVX</u>	<u>radar_signal_to_noise_ratio_crosspolar_v</u>	<u>Signal to noise ratio cross polar V</u>
<u>/sweep <n>/NCP</u>	<u>radar_normalized_coherent_power</u>	<u>Normalized coherent power</u>
<u>/sweep <n>/NCPH</u>	<u>radar_normalized_coherent_power_h</u>	<u>Normalized coherent power co-polar H</u>
<u>/sweep <n>/NCPV</u>	<u>radar_normalized_coherent_power_v</u>	<u>Normalized coherent power co-polar V</u>
<u>/sweep <n>/RR</u>	<u>radar_estimated_precipitation_rate</u>	<u>Rain rate</u>
<u>/sweep <n>/REC</u>	<u>radar_scatterer_classification</u>	<u>Radar echo classification</u>

Table 301-10: List of optional/conditional attributes that may be reported for Dataset variables.

<u>Attribute name</u>	<u>Type</u>	<u>Convention</u>	<u>Value or description</u>
<u>Undetect</u>	<u>same as field data</u>	<u>ODIM</u>	<u>Indicates an area (range bin) that has been radiated but has not produced a valid echo</u>
<u>sampling_ratio</u>	<u>float</u>	<u>CF/Radial</u>	<u>Number of samples for this field divided by <i>n</i> samples.</u>
<u>is_discrete</u>	<u>Boolean/string</u>	<u>CF/Radial</u>	<u>"true" or "false". If "true", this indicates that the field takes on discrete values, rather than floating point values. For example, if a field is used to indicate the hydrometeor type, this would be a discrete field.</u>
<u>field_folds</u>	<u>Boolean/string</u>	<u>CF/Radial</u>	<u>"true" or "false". Used to indicate that a field is limited between a min and max value, and that it folds between the two extremes. This typically applies to such fields as radial velocity and PhiDP</u>
<u>fold_limit_lower</u>	<u>float</u>	<u>CF/Radial</u>	<u>If <i>field_folds</i> is "true", this indicates the lower limit at which the field folds.</u>
<u>fold_limit_upper</u>	<u>float</u>	<u>CF/Radial</u>	<u>If <i>field_folds</i> is "true", this indicates the upper limit at which the field folds.</u>

<u>is_quality_field</u>	Boolean/ string	CF/Radial	Set to "true" if this Dataset stores a quality control field.
<u>flag_values</u>	same as field data	CF	Array of flag values. These values have special meaning, as documented in <i>flag_meanings</i> .
<u>flag_meanings</u>	string	CF	Meaning of <i>flag_values</i> or <i>flag_masks</i> .
<u>flag_masks</u>	same as field data	CF	Valid bit-wise masks used in a flag field that is comprised of bit-wise combinations of mask values. See <i>flag_meanings</i> .
<u>qualified_variables</u>	string	CF/Radial	Applicable if <i>is_quality_field</i> is "true". Array list of variables that this variable qualifies. Every field variable in this list should list this variable in its <i>ancillary_variable</i> attribute.
<u>ancillary_variables</u>	string	CF	Array list of variables to which this variable is related. In particular, this is intended to list the variables that contain quality information about this field. In that case, the quality field will list this field in its <i>qualified_variable</i> attribute.
<u>thresholding_xml</u>	string	CF/Radial	Thresholding details. Supplied if thresholding has been applied to the field.
			This should be in self-descriptive XML. For example:
			<thresholding field="DBZ">
			<field_used>
			<name>NCP</name>
			<min_val>0.15</min_val>
			</field_used>
			<field_used>
			<name>SNR</name>
			<min_val>-3.0</min_val>
			</field_used>
			</thresholding>

Table 301-11a: Optional/conditional variables that may be included in the monitoring subgroup when present. Attributes are defined in Table 301-11b.

<u>Variable path/name</u>	<u>Dimensions</u>	<u>Kind</u>	<u>Comment</u>
<u>/sweep <n>/monitoring/radar_measured_transmit_power_h</u>	(time)	float	Measured transmit power H polarization
<u>/sweep <n>/monitoring/radar_measured_transmit_power_v</u>	(time)	float	Measured transmit power V polarization
<u>/sweep <n>/monitoring/radar_measured_sky_noise</u>	(time)	float	Noise measured at the receiver when connected to the antenna with no noise source connected.
<u>/sweep <n>/monitoring/radar_measured_cold_noise</u>	(time)	float	Noise measured at the receiver when connected to the noise source, but it is not enabled.
<u>/sweep <n>/monitoring/radar_measured_hot_noise</u>	(time)	float	Noise measured at the receiver when it is connected to the noise source and the noise source is on.

/sweep <n>/monitoring/phase difference transmit hv	(time)	float	Phase difference between transmitted horizontally and vertically-polarized signals as determined from the first valid range bins
/sweep <n>/monitoring/antenna pointing accuracy elev	(time)	float	Antenna-pointing accuracy in elevation
/sweep <n>/monitoring/antenna pointing accuracy az	(time)	float	Calibration offset for the horizontal channel
/sweep <n>/monitoring/calibration offset h	(time)	float	Calibration offset for the horizontal channel
/sweep <n>/monitoring/calibration offset v	(time)	float	Calibration offset for the vertical channel
/sweep <n>/monitoring/zdr_offset	(time)	float	ZDR offset (bias)

Table 301-11b: Attributes defined for those variables listed in Table 301-11a.

Variable path/name	Attribute	Kind	Value
/sweep <n>/monitoring/radar_measured_transmit_power_h	units	string	dBm
/sweep <n>/monitoring/radar_measured_transmit_power_v	units	string	dBm
/sweep <n>/monitoring/radar_measured_sky_noise	units	string	dBm
/sweep <n>/monitoring/radar_measured_cold_noise	units	string	dBm
/sweep <n>/monitoring/radar_measured_hot_noise	units	string	dBm
/sweep <n>/monitoring/phase difference transmit hv	units	string	degrees
/sweep <n>/monitoring/antenna pointing accuracy elev	units	string	degrees
/sweep <n>/monitoring/antenna pointing accuracy az	units	string	degrees
/sweep <n>/monitoring/calibration_offset_h	units	string	dB
/sweep <n>/monitoring/calibration_offset v	units	string	dB
/sweep <n>/monitoring/zdr_offset	units	string	dB

Table 301-12a: List of optional/conditional metadata variables that may be reported for the radar parameters group. Attributes are defined in Table 301_12b.

Variable path/name	Dimensions	Kind	Comment
/radar_parameters/antenna_gain_h	none	float	Nominal antenna gain, H polarization
/radar_parameters/antenna_gain_v	none	float	Nominal antenna gain, V polarization
/radar_parameters/beam_width_h	none	float	Antenna beam width, H polarization
/radar_parameters/beam_width_v	none	float	Antenna beam width, V polarization
/radar_parameters/receiver_bandwidth	none	float	Bandwidth of radar receiver

Table 301-12b: Attributes defined for those variables listed in Table 301-12a.

Variable path/name	Attribute	Kind	Value
/radar_parameters/antenna_gain_h	units	string	dBi
/radar_parameters/antenna_gain_v	units	string	dBi
/radar_parameters/beam_width_h	units	string	degrees
/radar_parameters/beam_width_v	units	string	degrees
/radar_parameters/receiver_bandwidth	units	string	s-1

Table 301-13a: List of optional/conditional metadata variables that may be reported for the lidar parameters group. Attributes are defined in Table 301-13b.

Variable path/name	Dimensions	Kind	Comment
/lidar_parameters/beam_divergence	none	float	Transmit side

/lidar_parameters/field_of_view	none	float	Receive side
/lidar_parameters/aperture_diameter	none	float	
/lidar_parameters/aperture_efficiency	none	float	
/lidar_parameters/peak_power	none	float	
/lidar_parameters/pulse_energy	none	float	

Table 301-13b: Attributes defined for those variables listed in Table 301-13a.

Variable path/name	Attribute	Kind	Value
/lidar_parameters/beam_divergence	units	string	milliradians
/lidar_parameters/field_of_view	units	string	milliradians
/lidar_parameters/aperture_diameter	units	string	cm
/lidar_parameters/aperture_efficiency	units	string	percent
/lidar_parameters/peak_power	units	string	watts
/lidar_parameters/pulse_energy	units	string	joules

Table 301-14a: List of optional/conditional metadata variables that may be reported for the radar calibration group. Attributes are defined in Table 301-14b.

Variable path/name	Dimensions	Kind	Comment
/radar_calibration/calib_index	(calib)	byte	Calibration index for each ray
/radar_calibration/time	(calib)	float	Time of calibration
/radar_calibration/pulse_width	(calib)	float	Pulse width for this calibration
/radar_calibration/antenna_gain_h	(calib)	float	Derived antenna gain, H channel
/radar_calibration/antenna_gain_v	(calib)	float	Derived antenna gain, V channel
/radar_calibration/xmit_power_h	(calib)	float	Transmit power H channel
/radar_calibration/xmit_power_v	(calib)	float	Transmit power V channel
/radar_calibration/two_way_waveguide_loss_h	(calib)	float	2-way waveguide loss measurement plan to feed horn, H channel
/radar_calibration/two_way_waveguide_loss_v	(calib)	float	2-way waveguide loss measurement plane to feed horn, V channel
/radar_calibration/two_way_radome_loss_h	(calib)	float	2-way radome loss, H channel
/radar_calibration/two_way_radome_loss_v	(calib)	float	2-way radome loss, V channel
/radar_calibration/receiver_mismatch_loss	(calib)	float	Receiver filter bandwidth mismatch loss
/radar_calibration/receiver_mismatch_loss_h	(calib)	float	Receiver filter bandwidth mismatch loss, H channel
/radar_calibration/receiver_mismatch_loss_v	(calib)	float	Receiver filter bandwidth mismatch loss, V channel
/radar_calibration/radar_constant_h	(calib)	float	Radar constant, H channel
/radar_calibration/radar_constant_v	(calib)	float	Radar constant, V channel
/radar_calibration/probert_jones_correction	(calib)	float	Probert Jones antenna correction factor
/radar_calibration/dielectric_factor_used	(calib)	float	The K2 in the radar equation
/radar_calibration/noise_hc	(calib)	float	Measured noise level, H co-pol channel
/radar_calibration/noise_vc	(calib)	float	Measured noise level, V co-pol channel
/radar_calibration/noise_hx	(calib)	float	Measured noise level, H cross-pol channel
/radar_calibration/noise_vx	(calib)	float	Measured noise level, V cross-pol channel
/radar_calibration/receiver_gain_hc	(calib)	float	Measured receiver gain, H co-pol channel
/radar_calibration/receiver_gain_vc	(calib)	float	Measured receiver

Variable path/name	Dimensions	Kind	Comment
/radar_calibration/receiver_gain_hx	(calib)	float	gain, V co-pol channel Measured receiver gain, H cross-pol channel
/radar_calibration/receiver_gain_vx	(calib)	float	Measured receiver gain, V cross-pol channel
/radar_calibration/base_1km_hc	(calib)	float	Reflectivity at 1km for SNR=0dB noise corrected, H co-pol channel
/radar_calibration/base_1km_vc	(calib)	float	Reflectivity at 1km for SNR=0dB noise corrected, V co-pol channel
/radar_calibration/base_1km_hx	(calib)	float	Reflectivity at 1km for SNR=0dB noise corrected, H cross-pol channel
/radar_calibration/base_1km_vx	(calib)	float	Reflectivity at 1km for SNR=0dB noise corrected, V cross-pol channel
/radar_calibration/sun_power_hc	(calib)	float	Calibrated sun power, H co-pol channel
/radar_calibration/sun_power_vc	(calib)	float	Calibrated sun power, V co-pol channel
/radar_calibration/sun_power_hx	(calib)	float	Calibrated sun power, H cross-pol channel
/radar_calibration/sun_power_vx	(calib)	float	Calibrated sun power, V cross-pol channel
/radar_calibration/noise_source_power_h	(calib)	float	Noise source power, H channel
/radar_calibration/noise_source_power_v	(calib)	float	Noise source power, V channel
/radar_calibration/power_measure_loss_h	(calib)	float	Power measurement loss in coax and connectors, H channel
/radar_calibration/power_measure_loss_v	(calib)	float	Power measurement loss in coax and connectors, V channel
/radar_calibration/coupler_forward_loss_h	(calib)	float	Coupler loss into waveguide, H channel
/radar_calibration/coupler_forward_loss_v	(calib)	float	Coupler loss into waveguide, V channel
/radar_calibration/zdr_correction	(calib)	float	corrected = measured + correction
/radar_calibration/ldr_correction_h	(calib)	float	corrected = measured + correction
/radar_calibration/ldr_correction_v	(calib)	float	corrected = measured + correction
/radar_calibration/system_phidp	(calib)	float	System PhiDP, as seen in drizzle close to radar
/radar_calibration/test_power_h	(calib)	float	Calibration test power, H channel
/radar_calibration/test_power_v	(calib)	float	Calibration test power, V channel
/radar_calibration/receiver_slope_hc	(calib)	float	Computed receiver slope, ideally 1.0, H co-pol channel
/radar_calibration/receiver_slope_vc	(calib)	float	Computed receiver slope, ideally 1.0, V co-pol channel
/radar_calibration/receiver_slope_hx	(calib)	float	Computed receiver slope, ideally 1.0, H cross-pol channel
/radar_calibration/receiver_slope_vx	(calib)	float	Computed receiver slope, ideally 1.0, V cross-pol channel

Table 301-14b: Attributes defined for those variables listed in Table 301-14a.

<u>Variable path/name</u>	<u>Attribute</u>	<u>Kind</u>	<u>Value</u>
<u>/radar_calibration/time</u>	<u>units</u>	<u>string</u>	"seconds since <reftime>" where <reftime> is an ISO8601 time string of the form YYYY-MM- DDThh:mm:ssZ
<u>/radar_calibration/pulse_width</u>	<u>units</u>	<u>string</u>	<u>seconds</u>
<u>/radar_calibration/antenna_gain_h</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/antenna_gain_v</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/xmit_power_h</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/xmit_power_v</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/two_way_waveguide_loss_h</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/two_way_waveguide_loss_v</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/two_way_radome_loss_h</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/two_way_radome_loss_v</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/receiver_mismatch_loss</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/receiver_mismatch_loss_h</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/receiver_mismatch_loss_v</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/radar_constant_h</u>	<u>units</u>	<u>string</u>	<u>m/mW dB units</u>
<u>/radar_calibration/radar_constant_v</u>	<u>units</u>	<u>string</u>	<u>m/mW dB units</u>
<u>/radar_calibration/probert_jones_correction</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/noise_hc</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/noise_vc</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/noise_hx</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/noise_vx</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/receiver_gain_hc</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/receiver_gain_vc</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/receiver_gain_hx</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/receiver_gain_vx</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/base_1km_hc</u>	<u>units</u>	<u>string</u>	<u>dBZ</u>
<u>/radar_calibration/base_1km_vc</u>	<u>units</u>	<u>string</u>	<u>dBZ</u>
<u>/radar_calibration/base_1km_hx</u>	<u>units</u>	<u>string</u>	<u>dBZ</u>
<u>/radar_calibration/base_1km_vx</u>	<u>units</u>	<u>string</u>	<u>dBZ</u>
<u>/radar_calibration/sun_power_hc</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/sun_power_vc</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/sun_power_hx</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/sun_power_vx</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/noise_source_power_h</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/noise_source_power_v</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/power_measure_loss_h</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/power_measure_loss_v</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/coupler_forward_loss_h</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/coupler_forward_loss_v</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/zdr_correction</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/ldr_correction_h</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/ldr_correction_v</u>	<u>units</u>	<u>string</u>	<u>dB</u>
<u>/radar_calibration/system_phidp</u>	<u>units</u>	<u>string</u>	<u>degrees</u>
<u>/radar_calibration/test_power_h</u>	<u>units</u>	<u>string</u>	<u>dBm</u>
<u>/radar_calibration/test_power_v</u>	<u>units</u>	<u>string</u>	<u>dBm</u>

Table 301-15: Allowed values for enumerated string variables.

<u>variable path/name</u>	<u>valid values</u>
<u>/platform_type</u>	<u>fixed</u> <u>vehicle</u> <u>ship</u> <u>aircraft</u> <u>aircraft_fore</u> <u>aircraft_aft</u> <u>aircraft_tail</u> <u>aircraft_belly</u> <u>aircraft_roof</u> <u>aircraft_nose</u> <u>satellite_orbit</u> <u>satellite_geostat</u>
<u>/instrument_type</u>	<u>radar</u> <u>lidar</u>
<u>/primary_axis</u>	<u>axis_z</u> <u>axis_y</u>

<u>variable path/name</u>	<u>valid values</u>
<u>/sweep <n>/sweep_mode</u>	<u>axis_x</u> <u>axis_z_prime</u> <u>axis_y_prime</u> <u>axis_x_prime</u> <u>sector</u> <u>coplane</u> <u>rhi</u> <u>vertical_pointing</u> <u>idle</u> <u>azimuth_surveillance</u> <u>elevation_surveillance</u> <u>sunscan</u> <u>pointing</u> <u>manual_ppi</u> <u>manual_rhi</u> <u>doppler_beam_swinging</u> <u>complex_trajectory</u> <u>electronic_steering</u>
<u>/sweep <n>/follow_mode</u>	<u>none</u> <u>sun</u> <u>vehicle</u> <u>aircraft</u> <u>target</u> <u>manual</u>
<u>/sweep <n>/prt_mode</u>	<u>fixed</u> <u>staggered</u> <u>dual</u> <u>hybrid</u>
<u>/sweep <n>/polarization_mode</u>	<u>horizontal</u> <u>vertical</u> <u>hv_alt</u> <u>hv_sim</u> <u>circular</u>

FM 302-2022 WMO-CF MARINE TRAJECTORY

REGULATIONS

302.1 Scope

- 302.1.1 This profile is intended for the reporting of meteorological and/or oceanographic observations along one or more trajectories, including both at or near the ocean surface and at depth, from a single platform. The trajectory may follow an undulating profile.
- 302.1.2 A ragged array representation is used to allow multiple trajectories to be reported (e.g. see CF v1.8 conventions). This may be either a contiguous or indexed ragged array.
- 302.1.3 Only data for a single platform shall be included in the file.
- 302.1.4 Groups are not supported in this profile and groups other than the root group shall not be used.

302.2 Global scope/root group

- 302.2.1 *Global attributes*
- 302.2.1.1 The regulations defined in General Regulation WMO-CF.6 for global attributes shall apply.
- 302.2.1.2 Table 302-1 lists the values to be used for the indicate attributes.
- 302.2.2 *Station/platform identifier*

302.2.2.1	The rules for station identifiers (WMO-CF.4.5, WMO-CF.4.6, WMO-CF.6.10.6 and WMO-CF.6.10.7) shall be observed.
302.2.3	<i>Dimensions</i>
302.2.3.1	Files containing marine profile trajectory data shall have the following dimensions:
302.2.3.1.1	<i>obs</i> , the <i>obs</i> dimension shall be used to indicate the total number of observations within the file.
302.2.3.1.2	<i>trajectory</i> , the <i>trajectory</i> dimension shall be used to indicate the number of trajectories contained in the file and to index the observations to a trajectory. When there is a single trajectory in the file this shall have dimension 1.
302.2.4	<i>Coordinate Variables</i>
302.2.4.1	Table 302-2 lists the coordinate variables that shall be used with this profile.
302.2.4.2	For platforms located at the sea surface the depth shall be given as zero.
302.2.4.3	The observation locations relative to the sea surface shall then be given by the sensor installation height (<i>/(<measurand short name> <n> sensor installed height)</i> variable. See Regulation 302.2.7.4.
302.2.5	<i>Trajectory identification</i>
302.2.5.1	Table 302-3 lists the variables that shall be used to identify the trajectory that an observation belongs to.
302.2.5.2	<i>trajectory</i> provides the identifier for a trajectory.
302.2.5.3	<i>trajectory_index</i> provides the trajectory that an observation belongs to.
302.2.6	<i>Data variables</i>
302.2.6.1	The general regulations for data variables, including mandatory attributes, defined in General Regulation WMO-CF.5 shall apply.
302.2.6.2	Only data variables with a valid <i>standard_name</i> shall be included.
302.2.6.3	Data variables shall have a single dimension <i>obs</i> .
302.2.6.4	The NetCDF variable name shall be interpreted as the short name for the variable.
302.2.6.5	Multiple variables sharing the same short name shall follow the following naming convention: <i><measurand short name> <n></i> , where <i><n></i> is incremented for each additional variable sharing the same short name. For example, <i>salinity_1</i> and <i>salinity_2</i> in the case of two salinity sensors on an observing platform.
302.2.6.6	The <i>trajectory_index</i> variable shall be used to indicate which trajectory an observation belongs to.
302.2.7	<i>Ancillary variables</i>
302.2.7.1	The naming of the ancillary variables shall take the form <i><measurand short name> <n> <ancillary variable></i>
302.2.7.2	Table 302-4 lists the mandatory ancillary variables that shall be reported for each observed/measured variable
302.2.7.3	Table 302-5 lists the conditional or optional ancillary variables defined for the observed/measured variables.
302.2.7.4	The installed height of a sensor shall be included when the sensor is not at the same depth (or height) specified by the depth variable. In this case the sensor depth (or height) relative to the sea surface shall be given by the installed height added to the depth.

FM 302-2022 tables

Table 302-1: Values that shall be used for the indicated global attributes.

Attribute name	Type	Value
Conventions	string	"CF-1.8, WMO CF-1.0"
wmo_cf_profile	string	"FM 302-2022"
featureType	string	"trajectory"

Table 302-2a: Coordinate variables that shall be used in the marine trajectory profile. Attributes are given in Table 302-2b.

Variable path/name	Dimensions	Type	Comments
/lat	(obs)	float or double	Latitude of the observations
/lon	(obs)	float or double	Longitude of the observations
/depth	(obs)	float or double	Vertical position of the observing station or platform relative to sea level, for example glider depth.
/time	(obs)	float or double	Date and time of the observation

Table 302-2b: Attributes defined for the coordinate variables given in Table 302-2a.

Variable path/name	Attribute	Type	Value
/lat	standard_name	string	latitude
	units	string	degrees_north
	axis	string	Y
/lon	standard_name	string	longitude
	units	string	degrees_east
	axis	string	X
/depth	standard_name	string	depth
	units	string	meters
	axis	string	Z
	positive	string	down
	long_name	string	depth_below_sea_level
/time	standard_name	string	time
	units	string	"seconds since <reftime>" where <reftime> is an ISO8601 time string of the form YYYY-MM-DDThh:mm:ssZ
	axis	string	T
	calendar	string	standard

Table 302-3a: Variables defined to identify the trajectory an observation belongs to and that shall be included in marine trajectory files. Attributes are listed in Table 302-3b.

Variable path/name	Dimensions	Type	Comments
/trajectory	(trajectory)	string	Identifier for trajectory
/trajectory_index	(obs)	int	Index of the trajectory an observation belongs to.

Table 302-3b: Attributes defined for the trajectory variables listed in Table 302-3a.

Variable path/name	Attribute	Type	Value
/trajectory	cf_role	string	trajectory_id
/trajectory_index	long_name	string	Index of the trajectory that this observation belongs to
	instance_dimension	string	trajectory

Table 302-4a: Ancillary variables defined and that shall be reported for each measured/observed variable. Attributes are given in Table 302-4b. <prefix> has been used to represent <measurand short name> <n>.

Variable path/name	Dimensions	Type	Comments
/<prefix>_sensor	(trajectory)	string	Name of sensor
/<prefix>_sensor_make	(trajectory)	string	Manufacturer of sensor
/<prefix>_sensor_model	(trajectory)	string	Model of sensor
/<prefix>_sensor_serial_number	(trajectory)	string	Sensor serial number
/<prefix>_sensor_calibration_date	(trajectory)	float	Last calibration data of sensor

Table 302-4b: Attributes for the ancillary variables defined in Table 302-4a. <prefix> has been used to represent <measurand_short_name> <n>.

Variable path/name	Attribute	Type	Value
/<prefix>_sensor_calibration_date	standard_name	string	time
	units	string	"seconds since <reftime>" where <reftime> is an ISO8601 time string of the form YYYY-MM-DDThh:mm:ssZ
	axis	string	T
	calendar	string	standard

Table 302-5a: Conditional/optional ancillary variables defined and that should be reported for each measured/observed variable when the described conditions are met. Attributes are given in Table 302-5b. <prefix> has been used to represent <measurand_short_name> <n>.

Variable path/name	Dimensions	Type	Comments
/<prefix>_sensor_installed_height	(trajectory)	float	Value to be added to sensor_depth to get vertical position of sensor relative to sea surface.
</prefix>_sensor_measurement_method	(trajectory)	string	The method used by the sensor to measure the parameter, e.g., capacitive humidity sensor.

Table 302-5b: Attributes for the ancillary variables defined in Table 302-5a. <prefix> has been used to represent <measurand_short_name> <n>.

Variable path/name	Attribute	Type	Value
/<prefix>_sensor_installed_height	units	string	meters
</prefix>_sensor_measurement_method	wmo_parameter_name	string	
	wmo_parameter_uri	string	

PART C

COMMON FEATURES TO BINARY AND ALPHANUMERIC CODES

- a. FM system of numbering table-driven alphanumeric codes**
 - b. List of table-driven alphanumeric codes with their specifications and associated code tables**
 - Attachment: CREX template examples
 - c. Common code tables to binary and alphanumeric codes**
 - d. Regulations for reporting traditional observation data in Table-Driven Code Forms (TDCF): BUFR or CREX**
 - Attachment I: Examples of templates for the transmission in BUFR or CREX of other data types
 - Attachment II: List of alphanumeric code tables related to BUFR and CREX code tables and flag tables
-

a. FM SYSTEM OF NUMBERING TABLE-DRIVEN ALPHANUMERIC CODES

Each table-driven code bears a number, preceded by the letters FM. Before 2018, This-this number ~~is~~-was followed by a Roman numeral to identify the session of CBS which either approved the code as a new one or made the latest amendment to its previous version. A code approved or amended by correspondence after a session of CBS ~~receives~~-received the number of that session.

Furthermore, an indicator term is used to designate the code colloquially and is therefore called a “code name”.

Note on nomenclature:

Changes and augmentations to the structure of the CREX data representation shall be identified as different “CREX edition numbers”. The previous edition number was 1. The new edition number is 2.

Changes to the content of the parameter Tables A, B, C and D shall be identified as different “table versions”. The previous tables were Version 32; the changes described in this edition will become “Tables A, B, C and D, Version 33”.

Further CREX editions and table versions may be generated independently of one another in the future as requirements dictate.

The FM system of numbering the codes, together with the corresponding code names and their reference list of ~~CBS~~-approved decisions_s, is the following:

FM SYSTEM OF TABLE-DRIVEN ALPHANUMERIC CODES

FM 95–XIV CREX

Character form for the representation and exchange of data

Res. 8 (EC-LI), Rec. 8 (CBS-99), Rec. 9 (CBS-00), approved by the President of WMO, Res. 4 (EC-LIII), Rec. 9 (CBS-01), approved by the President of WMO, Res. 2 (EC-LVII), Res. 10 (EC-LIX) and Res. 7 (EC-LXI), and adoption between CBS sessions (2010, 2012 and 2013)

b. LIST OF TABLE-DRIVEN ALPHANUMERIC CODES WITH THEIR SPECIFICATIONS AND ASSOCIATED CODE TABLES

FM 95–XIV CREX

Character form for the representation and exchange of data

CODE FORM

SECTION 0	Indicator section
SECTION 1	Data description section
SECTION 2	Data section
SECTION 3	Optional section
SECTION 4	End section

Notes:

- (1) CREX is the name of a character code for the representation and exchange of meteorological and other data.
- (2) CREX uses many of the principles of FM 94 BUFR.
- (3) CREX may be used for the exchange of data for which there is no suitable existing WMO code form.
- (4) A CREX message shall consist of one or more subsets of related meteorological data defined, described, and represented by a single CREX entity. For observational data, each subset shall correspond to one report.
- (5) A CREX message consists of sections:

<i>Section number</i>	<i>Name</i>	<i>Contents</i>
0	Indicator section	"CREX"
1	Data description section	CREX master table number, edition number, table version number, BUFR master table number, version number of local table, data category and sub-category, originating centre and sub-centre, sequence number of message, number of subsets, date and time, then a collection of descriptors which define the form and content of data subsets making the data section, and an optional check digit indicator "E"
2	Data section	A set of data items defined by Section 1
3	Optional section	"SUPP" followed by additional items for local use
4	End section	"7777"

- (6) It will be noted that CREX representation is suitable for the manual encoding and visual display of meteorological and other data.

REGULATIONS

95.1 General

- 95.1.1 The beginning and ending of the data representation form shall be identified by the characters "CREX" and "7777", respectively.
- 95.1.2 Information within CREX shall be character coded.
- 95.1.3 A group is a sequence of one or more contiguous characters corresponding to a single data descriptor or data value. Groups shall be separated from each other by one or more space characters. Multiple space characters shall be used when needed to improve human readability.
- 95.1.4 The subset terminator shall be represented by the character string "+". The subset terminator shall not be used when the subset is the last subset.
- 95.1.5 The section terminator shall be represented by the character string "++". The section terminator shall additionally function as a subset terminator for the last subset.

95.2 Section 0 – Indicator section

- 95.2.1 Section 0 shall be four characters long consisting of the character sequence "CREX".

95.3 Section 1 – Data description section

95.3.1 Table indicators

- 95.3.1.1 The data description section shall begin with the CREX table descriptor starting with the letter T and followed by a 10-digit number (tteevbbww) without a separator character. The first two digits (tt) shall define the CREX master table used (tt = 00 if the standard WMO FM 95 CREX tables are used). The next two digits (ee) shall indicate the CREX edition number used, the next two (vv) the CREX table version number used, the next two (bb) the BUFR master table version number used and the last two (ww) the version number of local table (*however for use of local table see Notes 6 and 7 of CREX Table B*).

- 95.3.1.2 Immediately following the CREX table descriptor and a space character as separator, Section 1 shall contain a six-digit number (nnnmmm) preceded by the letter A. The first three digits (nnn) define the data category referenced to CREX Table A. The next three digits (mmm) shall indicate the sub-category from Common Code table C-13.

95.3.2 Other indicators

- 95.3.2.1 Immediately following the CREX table descriptors and a space character as separator, Section 1 shall contain an eight-digit number (ooooopp) preceded by the letter P. The first five digits (ooooo) define the originating centre from Common Code table C-11. The next three digits (ppp) shall indicate the originating sub-centre from Common Code table C-12.
- 95.3.2.2 Immediately following the CREX indicator for originating centre and a space character as separator, Section 1 shall contain a two-digit number (uu) preceded by the letter U. The two digits (uu) define the sequence number of the message (00 for original message, uu for updated version).
- 95.3.2.3 Immediately following the CREX indicator for the sequence number and a space character as separator, Section 1 shall contain a three-digit number (sss) preceded by the letter S. The three digits (sss) define the number of subsets in the report.
- 95.3.2.4 Immediately following the CREX indicator for the number of subsets and a space character as separator, Section 1 shall contain an eight-digit number (yyyymmdd) preceded by the letter Y.

The first four digits (yyyy) define the year of the most typical time for the CREX message content. The next two digits (mm) define the month and the last two digits (dd) define the day.

- 95.3.2.5 Immediately following the CREX indicator for the date and a space character as separator, Section 1 shall contain a four-digit number (hhnn) preceded by the letter H. The first two digits (hh) define the hour of the most typical time for the CREX message content and the next two digits (nn) define the minutes.

95.3.3 Data description syntax for CREX

- 95.3.3.1 After the CREX indicators defining the most typical time for the CREX message content, Section 1 shall have one or more data descriptor(s). Data descriptors shall be preceded by a space character as separator. Data descriptors shall occupy 6 characters. Each descriptor shall have three parts: F (one letter), xx (two digits), yyy (three digits or – (minus sign) followed by two digits for C02yyy data description operator for negative scales – see CREX Table C).

- 95.3.3.2 The first part (F) of a data descriptor shall be: B, C, D or R.

- 95.3.3.3 If F = B, the descriptor shall function as “element descriptor”, and it shall define a single data item by reference to CREX Table B named: Bxyyy.

- 95.3.3.4 If F = C, the descriptor shall function as “operator descriptor”, and it shall define an operation by reference to CREX Table C named: Cxyyy.

- 95.3.3.5 If F = R, the descriptor shall function as “replication descriptor”. The two digits “xx” shall define the number of following descriptors to be repeated the number of times defined by the three digits “yyy”. If “yyy” equal “000”, the descriptor defines a delayed replication. Delayed replication is the replication of data values of which the number of replication is known only in the observed report and will therefore be part of the data section (for example: number of levels in a sounding). A corresponding number of four digits in the data section shall then define the number of replications of the data values corresponding to the following xx descriptors in the data description section.

- 95.3.3.6 If F = D, the descriptor shall function as “sequence descriptor”, and it shall define a list of element descriptors, replication descriptors, operator descriptors and/or sequence descriptors by reference to CREX Table D and named: Dxyyy.

- 95.3.4 CREX Table B shall define the element descriptors. If one entry in CREX Table B and one entry in BUFR Table B have the same table reference, the element name shall be the same in both tables. CREX Table B entries shall contain:

- (a) The table reference (B xx yyy);
- (b) The element name (64 characters maximum);
- (c) The units to be used for data representation in CREX, or instead, a reference to a code table or flag table which will then define the possible data value for the element;
- (d) The scale factor to be applied to the data value for CREX purposes; the scale defines the precision of the value. No decimal points shall be used in the data section, so a positive scale means that so many figures after the decimal point are included (e.g. scale = 2 means values coded in hundredths, e.g. height coded in centimetre). A negative scale means that so many figures before the decimal point are not included (e.g. heights in hundreds of metres would have scale = –2);
- (e) The number of characters to be used in CREX to represent the corresponding data value (without counting the sign);
- (f) Reference values for CREX elements are always zero and there shall be no column for this attribute in CREX tables.

Note: Each entry in CREX Table B defining element descriptor should correspond with entries in BUFR Table B and listed in the same table, in Part B, Binary codes, BUFR/CREX Table B.

- 95.3.4.1 Units should be based on standard international units of the SI system. Alternatively, in exceptional cases, consideration may be given to other standard common units used by the data producer and the users, where a convincing case can be made that those units are more

appropriate. In such a case, priority shall be given to units contained in WMO Common Table C-6 or, in the case of descriptors for aviation products, ICAO Annex 5.

- 95.3.4.2 An operator descriptor shall be used to define change of unit, scale, or data width. The change shall apply only to the data value of the element referenced in the following element descriptor. The “yyy” digits of the operator descriptor shall define the new unit (yyy being equal to the code figure of the new unit defined in Common Code table C-6 listing all the possible units), the new scale or the new data width. The original Table B unit, scale or data width shall be back in force again for that element when subsequently referenced in the data description section until a new change occurs.

Note: Change of unit, scale or data width should be avoided; it should be only a last resort solution. These changes are not recommended in a common CREX Table D sequence. The change operators should not be used when the end user of the message would be a human reader.

- 95.3.4.3 CREX code tables shall have the same code figures as BUFR code tables. As CREX code tables are generally longer than corresponding BUFR code tables (for example: 99 entries rather than 63), the value corresponding to “Missing” and the values over within the BUFR code table shall be declared “Not used” within the corresponding CREX table (“63” to “99” Not used, in the example).

- 95.3.4.4 CREX flag tables shall be the same as BUFR flag tables. However, in CREX, flag tables shall be expressed using the octal representation in the following way: a set of three bits being represented by a figure from 0 to 7 (the leftmost bit being the first bit in the table rank), zeros being added on the left when the number of flags is not a multiple of 3:

000 = 0 (no bit set)

001 = 1 (bit 3 set)

010 = 2 (bit 2 set)

011 = 3 (bits 2 and 3 set)

100 = 4 (bit 1 set)

101 = 5 (bits 1 and 3 set)

110 = 6 (bits 1 and 2 set)

111 = 7 (all bits set)

For example, the seven flag table sequence “1100110” transformed with the addition on the left of two zeros to “001100110” would be translated to “146” in octal.

Missing value for a flag table shall be indicated by a set of solidi “/” covering the data width.

- 95.3.5 Element descriptors corresponding to the following classes in CREX Table B shall remain in effect until superseded by redefinition:

Class

00 Reserved

01 Identification

02 Instrumentation

03 Reserved

04 Location (time)

05 Location (horizontal-1)

06 Location (horizontal-2)

07 Location (vertical)

08 Significance qualifiers

09 Reserved

Note: Redefinition is effected by the occurrence of element descriptors which contradict the preceding element descriptors from these classes. If two or more elements from the same class do not contradict one another, they all apply.

- 95.3.5.1 The consecutive occurrence of two identical element descriptors or identical sets of element

descriptors from Classes 04 to 07, inclusive, shall denote a range of values bounded by the corresponding element values. This enables the definition of layers and simple time periods.

- 95.3.5.2 The definition of line, areas, volumes and more complex time attributes shall be accomplished using descriptors from Classes 04 to 07 in association with suitable descriptors from Class 08.
- 95.3.5.3 The consecutive occurrence of two or more non-identical element descriptors from Classes 04 to 07, inclusive, shall infer that all such elements remain in effect until redefined, unless such elements define an increment.
- 95.3.5.4 Data items defined by element descriptors in Class 10 or above shall not behave as coordinates with respect to subsequent data.
- 95.3.5.5 Increments:
Any occurrence of an element descriptor from Classes 04 to 07 which defines an increment shall indicate that the location corresponding to that class shall be incremented by the corresponding data value. In the case of successive increments from the same class, this means that each increment shall apply in a cumulative manner, with all preceding increments remaining in effect.
Displacements:
In contrast, any displacement descriptor from Classes 04 to 07 does not redefine the location corresponding to that class, but shall define only a transient displaced location from the location corresponding to that class. In the case of successive displacements from the same class, this means that each displacement shall apply independently and in a non-cumulative manner to the location corresponding to that class.
- 95.3.5.6 Time or location increment descriptors, from Classes 04 to 07 inclusive, may be associated with replication descriptors in the following way: when an increment descriptor immediately precedes a replication descriptor, or is separated from it by one or more operator descriptors from Table C, this shall signify that such increments shall be applied for each replication; the application of the increments shall take effect from the beginning of each defined replication, including the first.
- 95.3.5.7 If a CREX message is made up of more than one subset, each subset shall be treated as though it was the first subset encountered.
- 95.3.6 A check digit indicator is optional at the end of section 1. If present, it shall take the form of the single character "E".

95.4 **Section 2 – Data section**

- 95.4.1 The data section shall be comprised of one or more subsets of groups. Each group shall represent one data value. The sequence of data values shall correspond in order to the list of descriptors defined by Section 1 and shall be terminated by subset terminator, or, in the case of the last subset, by the section terminator.
- 95.4.2 Each data value shall be coded using the number of characters defined in the CREX Table B entry of the corresponding direct element descriptor in Section 1 or of the corresponding element descriptor within a sequence of descriptors defined by a sequence descriptor in Section 1. However, values of the CREX Table B entry, which are equal to or beyond the missing value of the corresponding BUFR Table B entry, shall not be used. If the data value is a number defining a delayed replication (descriptor "Rxx000" in Section 1), it shall comprise four digits.
- 95.4.3 Each numerical data value shall include leading zeroes when the number of digits required to

represent the value is smaller than the number of characters defined in the corresponding CREX Table B entry or for the delayed repetition number, to keep the number of characters representing the data value always equal to the original data width defined in CREX tables or Regulations, in order to facilitate the presentation alignment and the decoding process.

- 95.4.4 Positive numerical data values shall be unsigned. Negative numerical data values only shall be signed and represented with the negative sign immediately preceding the data value.
- 95.4.5 Each data value having a unit defined as character shall include trailing blanks when the number of characters required to represent the data value is smaller than the number of characters defined in the corresponding CREX Table B entry, to keep the number of characters representing the data value always equal to the original data width defined in CREX tables, in order to facilitate the presentation alignment and the decoding process.
- 95.4.6 A missing value shall be represented as a group of solidi "/" characters equal in number to the number of characters normally required to represent the value concerned.
- 95.4.7 If the check digit indicator "E" is present at the end of Section 1, a check digit shall be added in front of each data value, immediately preceding the first character of each data value. The check digit shall take the value of the unit digit of the ordered number of the data value, counting along the data subset in which it is contained, starting from 0 (the digit increases from 0 to 9 cyclically). The check digit shall precede immediately the negative sign if the data value is negative.
- 95.5 **Section 3 – Optional section**
- 95.5.1 Section 3 is optional and if present, shall contain additional items as may be defined within each centre for specific use.
- 95.5.2 Section 3, if present, shall start with the four-character sequence "SUPP" and shall end with a section terminator.
- 95.6 **Section 4 – End section**
- 95.6.1 Section 4 shall be four characters long coded as "7777". Section 4 shall not have a section terminator.

SPECIFICATIONS OF SECTIONS

Notes:

- (1) Each section contains one or more groups of characters separated by one separator character.
- (2) In the following, each group is numbered as group 1, group 2 and so on, from the beginning of the section.

Section 0 – Indicator section

Group No.	Contents	Meaning
1	CREX	CREX: Beginning of the CREX message

Section 1 – Data description section

Group No.	Contents	Meaning
1	Ttteevvbbww	T: Indicator for CREX tables tt: CREX Master Table used (00 for WMO standard FM 95 CREX tables) ee: CREX edition number (02) vv: CREX master table version number (see Common Code table C-0) bb: BUFR master table version number used (see Common Code table C-0) ww: Version number of local table
2	Annnmmm	A: Indicator for CREX Table A entry nnn: Data category from CREX Table A mmm: International data sub-category from Common Code table C-13
3	Pooooopp	P: Indicator for originating centre ooooo: Originating centre from Common Code table C-11 ppp: Originating sub-centre from Common Code table C-12
4	Uuu	U: Indicator for sequence number of message uu: Update sequence number (00 for original messages and for messages containing only delayed reports; incremented for the other updates)
5	Ssss	S: Indicator for number of subsets sss: Number of subsets included in the report
6	Yyyymmdd	Y: Indicator for date yyyy: Year mm: Month dd: Day
7	Hhhnn	H: Indicator for time hh: Hour nn: Minute
8 to n	Bxyyy, Cxyyy, Dxyyy, and/or Rxyyy	B,C,D: Indicators for CREX Tables B, C, D entries xyyy: 5 digits each which indicate references from CREX Tables B, C, and/or D R: Indicator for replication xx: Number of replicated descriptors yyy: Number of replications (delayed replication if yyy = 0)
(n + 1)	(E)	E: Optional check digit indicator

Note: When accuracy of the time does not define a time unit, then the value for this unit is set to zero (e.g. SYNOP observation at 09 UTC, then minute = 0).

Section 2 – Data section

Group No.	Contents	Meaning
1 to m	(d) Data values	d: Optional check digit Data: Data values corresponding to section 1 descriptors values

Section 3 – Optional section

Group No.	Contents	Meaning
1	SUPP	SUPP: The four letters SUPP indicate the presence of a supplementary optional section
2 to p	Items for local use	Additional items for local use developed by the generating centre

Section 4 – End section

Group No.	Contents	Meaning
1	7777	7777: End of CREX

VISUALIZATION OF CREX CODE FORM

(Bold characters are fixed alphanumeric characters; features in brackets are optional)

CREX++

Tteevvbbww **A**nnnmmm **P**ooooopp **U**uu **S**sss **Y**yyymmdd **H**hhnn

Rxyyy (E)++

or **B**xyyy

or **C**xyyy

or **D**xyyy

((d)Data values+)

.....

.....

((d)Data values+)

(d)Data values++

(**SUPP** Items for local use++)

7777

Note: If there is more than one subset, there shall be one "+" padded at the end of each subset, except for the last one (see Regulations 95.1.4, 95.1.5 and 95.4.1).

Provisional Copy
2023

CREX TABLES, CODE TABLES, FLAG TABLES AND TEMPLATE EXAMPLES

FM 95 CREX refers to three types of tables: CREX tables, code tables and flag tables.

CREX tables

Tables containing information used to describe, classify and define the contents of a CREX message are called CREX tables. Four CREX tables are defined: Tables A, B, C and D. Entry numbering shall be the same in CREX tables and BUFR tables for the same entity represented. Table B entries shall be listed in the common BUFR/CREX Table B in Part B, Binary codes. Table D common sequences shall not be defined in both CREX Table D and BUFR Table D unless otherwise a conversion between both Tables D is not simple, that is, the conversion is not completed by simple replacement of part "F" of each descriptor. If a CREX Table D sequence is not defined in BUFR Table D, it shall be assigned a number not used by any BUFR sequence. Similarly, new BUFR Table D sequences shall be assigned a number not used by any CREX Table D sequence.

Code tables and flag tables

CREX Table B defines some elements by means of code tables or flag tables. Within this general description are included code tables referenced by code figures and flag tables, where each bit is set to 0 or 1 to indicate a false or true value with respect to a specific criterion. Within CREX all code tables and flag tables refer to elements defined within CREX Table B; they are numbered according to the xx and yyy values of the corresponding Table B reference.

Code tables in CREX

CREX code tables have the same code figure as BUFR code tables and are not reproduced. Values of the CREX code, which are equal to or beyond the missing value of BUFR code figure, shall not be used. A missing value in CREX for a code table shall be indicated by a set of solidi "/" covering the data width.

Flag tables in CREX

CREX flag tables shall be the same as BUFR flag tables. However flag tables in CREX shall be expressed using octal representation in the following way: a set of three bits being represented by a figure from 0 to 7 (the leftmost bit being the first bit in the table rank), zeros being added on the left when the number of flags is not a multiple of 3:

000 = 0 (not bit set)
 001 = 1 (bit 3 set)
 010 = 2 (bit 2 set)
 011 = 3 (bits 2 and 3 set)
 100 = 4 (bit 1 set)
 101 = 5 (bits 1 and 3 set)
 110 = 6 (bits 1 and 2 set)
 111 = 7 (all bits set).

For example, the seven flag table sequence "1100110" transformed with the addition on the left of two zeros to "001100110" would be translated to "146" in octal.

CREX flag tables are the same as BUFR flag tables and are not reproduced here.

In CREX, a missing value for a flag table shall be indicated by a set of solidi "/" covering the data width.

CREX template examples

Examples of templates of some CREX messages are listed as models in Part C, CREX Attachment to help users understand the CREX code.

CREX TABLE RELATIVE TO SECTION 1**CREX Table A – *Data category***

Code figure	Data type
000	Surface data – land
001	Surface data – sea
002	Vertical soundings (other than satellite)
003	Vertical soundings (satellite)
004	Single level upper-air data (other than satellite)
005	Single level upper-air data (satellite)
006	Radar data
007	Synoptic features
008	Physical/chemical constituents
009	Dispersal and transport
010	Radiological data
011	CREX tables, complete replacement or update
012	Surface data (satellite)
013–019	Reserved
020	Status information
021	Radiances (satellite measured)
022	Radar (satellite) but not altimeter and scatterometer
023	Lidar (satellite)
024	Scatterometry (satellite)
025	Altimetry (satellite)
026	Spectrometry (satellite)
027	Gravity measurement (satellite)
028	Precision orbit (satellite)
029	Space environment (satellite)
030	Calibration datasets (satellite)
031	Oceanographic data
032–100	Reserved
101	Image data (satellite)
102–239	Reserved
240–254	For experimental use
255	Other category

CREX TABLES RELATIVE TO SECTION 2**CREX Table B – Classification of elements**

F	X	Class	Comments
B	00	BUFR/CREX table entries	
B	01	Identification	Identifies origin and type of data
B	02	Instrumentation	Defines instrument types used
B	03	Instrumentation	Defines instrument types used
B	04	Location (time)	Defines time and time derivatives
B	05	Location (horizontal – 1)	Defines geographical position, including horizontal derivatives, in association with Class 06 (first dimension of horizontal space)
B	06	Location (horizontal – 2)	Defines geographical position, including horizontal derivatives, in association with Class 05 (second dimension of horizontal space)
B	07	Location (vertical)	Defines height, altitude, pressure level, including vertical derivatives of position
B	08	Significance qualifiers	Defines special character of data
B	09	Reserved	
B	10	Non-coordinate location (vertical)	Height, altitude, pressure and derivatives observed or measured, <i>not</i> defined as a vertical location
B	11	Wind and turbulence	Wind speed, direction, etc.
B	12	Temperature	
B	13	Hydrographic and hydrological elements	Humidity, rainfall, snowfall, etc.
B	14	Radiation and radiance	
B	15	Physical/chemical constituents	
B	19	Synoptic features	
B	20	Observed phenomena	Defines present/past weather, special phenomena, etc.
B	21	Radar data	
B	22	Oceanographic elements	
B	23	Dispersal and transport	
B	24	Radiological elements	
B	25	Processing information	
B	26	Non-coordinate location (time)	Defines time and time derivatives that are not coordinates
B	27	Non-coordinate location (horizontal – 1)	Defines geographical positions, in conjunction with Class 28, that are not coordinates
B	28	Non-coordinate location (horizontal – 2)	Defines geographical positions, in conjunction with Class 27, that are not coordinates
B	29	Map data	
B	30	Image	
B	33	Quality information	
B	35	Data monitoring information	
B	40	Satellite data	
B	41	Oceanographic/biogeochemical parameters	
B	42	Oceanographic elements	

(continued)

(CREX Table B – continued)

Notes:

- (1) Where a code table or flag table is appropriate, “code table” or “flag table”, respectively is entered in the UNIT column.
- (2) The code tables and flag tables associated with Table B are numbered to correspond with the xx and yyy part of the table reference.
- (3) To encode values into CREX, the data (with units as specified in the UNIT column) must be multiplied by 10 to the power SCALE.
- (4) Where a UNIT is given as Character, data shall be coded as character data left justified within the field width.
- (5) Classes 48 to 63 are reserved for local use; all other classes are reserved for future development.
- (6) Entries 192 to 255 within all classes are reserved for local use.
- (7) The use of local descriptors, as defined in Notes 5 and 6, in messages intended for non-local or international exchange is strongly discouraged.
- (8) First-order statistics are included in Table B only when they are produced, as such, by the observing system.

CREX Table B entries from Classes 00 to 42 are defined in BUFR/CREX Table B in Part B, Binary codes, of the Manual.

Note: Class 31 does not exist in CREX.

CREX Table C – Data description operators

REFERENCE	OPERAND	OPERATOR NAME	OPERATION DEFINITION
C 01	YYY	Data width replacement	YYY characters (from 000 to 999) replace specified Table B data width
C 02	YYY	Scale factor replacement	YYY (from –99 to 999) replaces the specified Table B scale factor
C 05	YYY	Character insertion	YYY characters (from 001 to 999), including spaces, are inserted as a data field
C 07	YYY	Units replacement	Change unit to unit defined in Common Code table C–6 by code figure equal to YYY, for example: YYY = 040 changes unit to Celsius YYY = 741 changes unit to km h ⁻¹ YYY = 201 changes unit to knot YYY = 740 changes unit to km
C 41	000	Define event	This operator denotes the beginning of the definition of an event (see Note 2)
C 41	999	Cancel define event	This operator denotes the conclusion of the event definition that was begun via the previous C 41 000 operator
C 42	000	Define conditioning event	This operator denotes the beginning of the definition of a conditioning event (see Note 2)
C 42	999	Cancel define conditioning event	This operator denotes the conclusion of the conditioning event definition that was begun via the previous C 42 000 operator
C 43	000	Categorical forecast values follow	The values which follow are categorical forecast values (see Note 3)
C 43	999	Cancel categorical forecast values follow	This operator denotes the conclusion of the definition of categorical forecast values that was begun via the previous C 43 000 operator
C 60	YYY	National letters insertion (see Note 4)	YYY national letters including spaces are inserted as a data field

Notes:

- (1) The operations specified by operator descriptors C 41 000, C 42 000 and C 43 000 remain defined until cancelled or until the end of the data subset. Regulation 95.3.4.2 shall not apply here.
- (2) An event, as defined for use with operators C 41 000 and C 42 000, is a set of one or more circumstances described using appropriate Table B descriptors along with their corresponding data values. The grouping of such descriptors together as a single "event" allows them to be collectively assigned as the target of a separate descriptor such as B 33 045 or B 33 046. When defining a circumstance within an event, descriptor B 33 042 may be employed preceding the appropriate Table B descriptor in order to indicate that the corresponding value is actually a bound for a range of values.

(continued)

(CREX Table C – continued)

- (3) A categorical forecast value represents a "best guess" from among a set of related, and often mutually exclusive, data values or categories. Operator C 43 000 may be used to designate one or more values as being categorical forecast values, and descriptor B 33 042 may be employed preceding any such value in order to indicate that that value is actually a bound for a range of values.
- (4) Only the characters from the International Telegraphic Alphabet No. 2 (ITA2) are likely to be transmitted accurately to all recipients.

Provisional Copy
2023

CREX Table D – List of common sequences

F	X	Category of sequences
D	00	CREX table entries sequences
D	01	Location and identification sequences
D	02	Meteorological sequences common to surface data
D	03	Meteorological sequences common to vertical soundings data
D	04	Meteorological sequences common to satellite observations (<i>not to be used in CREX for transmission</i>)
D	05	Meteorological or hydrological sequences common to hydrological observations
D	06	Meteorological or oceanographic sequences common to oceanographic observations
D	07	Surface report sequences (land)
D	08	Surface report sequences (sea)
D	09	Vertical sounding sequences (conventional data)
D	10	Vertical sounding sequences (satellite data) (<i>not to be used in CREX for transmission</i>)
D	11	Single level report sequences (conventional data)
D	12	Single level report sequences (satellite data) (<i>not to be used in CREX for transmission</i>)
D	13	Sequences common to image data (<i>not to be used in CREX for transmission</i>)
D	14	Reserved
D	15	Oceanographic report sequences
D	16	Synoptic feature sequences
D	18	Radiological report sequences
D	21	Radar report sequences (<i>not to be used in CREX for transmission</i>)
D	22	Chemical and aerosol sequences
D	35	Monitoring information

Notes:

- (1) From a conceptual point of view, Table D is *not necessary*.
 - (a) The Data description section can fully and completely describe the data using only element descriptors, operator descriptors and the rules of description;
 - (b) Such a means of defining the data would involve considerable overheads in terms of the length of the Data description section. Table D is a device to reduce these overheads;
 - (c) Each entry within Table D contains a list of descriptors. Each sequence descriptor that references to Table D may be “expanded” by replacing it with the list corresponding to that entry. The process of “expansion” is well defined, provided it results in a set of element descriptors and operator descriptors;
 - (d) Descriptors listed in entries to Table D may themselves refer to Table D, provided no circularity results on repeated expansion;
 - (e) The initial Table D has been limited to lists of descriptors likely to be used frequently. Every attempt has been made not to produce initial tables that are too comprehensive. *Minor differences of reporting practice can be accommodated by not endeavouring to reduce each observation type to a single descriptor.* Indeed, much more flexibility is retained if the Data description section is envisaged as containing three or four descriptors.
- (2) It should be noted that, initially, effort has been concentrated on the requirements for observational data. Extensions forecast data, time series data, products, etc., follow logically and can be added at an appropriate future date.
- (4) Underwater soundings are included, with some minor omissions, to illustrate the facility to describe data of slightly different contents.
- (7) Categories 48 to 63 are reserved for local use; all other categories are reserved for future development.
- (8) Entries 192 to 255 within all categories are reserved for local use.

Editorial note: Notes are numbered so as to be consistent with the BUFR Table D for convenience.

Provisional Copy
2023

Category 00 – CREX table entries sequences

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 00 010	D 00 003 R 01 000 B 00 030	F, X, Y of descriptor to be added or defined Delayed replication of 1 descriptor Descriptor defining sequence	Up to 9999 entries
D 00 015	B 00 030 R 02 000 B 00 024 B 00 025	(Code table definition) Descriptor defining sequence Delayed replication of 2 descriptors Code figure Code figure meaning	
D 00 016	B 00 030 R 02 000 B 00 026 B 00 027	(Flag table definition) Descriptor defining sequence Delayed replication of 2 descriptors Bit number Bit number meaning	

Notes:

- (1) These entries include the facility to update the Table A code figure and data description.
- (2) It is better to use different Class 00 descriptors for the defining and defined elements, in the same way as different descriptors correspond to pressure considered as a coordinate and pressure measured at a given point; otherwise special rules would be needed to interpret such message. Entries B 00 010 to B 00 012 define F, X and Y for Tables B and D; entry B 00 030 is a descriptor used as data and provides the F, X and Y values defining a sequence for Table D entries.
- (3) It could be argued that, as only additions are possible, only complete lines should be allowed; but it is conceivable that local areas will require changes as well as additions, so it is better and in any case clearer to provide descriptions for all the fields.

Provisional Copy
2023

Category 01 – Location and identification sequences

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 01 027	B 08 007	(Description of a feature in 3-D or 2-D) Dimensional significance	= 0 Point, = 1 Line, = 2 Area, = 3 Volume
	R 01 000	Delayed replication of 1 descriptor (see Note 5)	
	D 01 028	Horizontal section of a feature described as a polygon, circle, line or point	Set to missing (cancel)
	B 08 007	Dimensional significance	

Note:

(5) This replication factor shall have a value of “1” when a 2-D feature is being described, whereas 3-D features may be described via any one of the following methods:

- (a) Via two or more horizontal sections in successive ascending flight levels. In this case, each section shall be described by an identical number of latitude/longitude points listed in identical order (i.e. where each point x of section n is to be joined via a straight line to point x of section n+1), in order to ensure that the overall shape of the 3-D feature is unambiguously described. In this case, all values reported for B 33 042 shall be “missing”.
- (b) Via a single horizontal section with an appropriate value reported for B 33 042, as follows. In all such cases, the corresponding horizontal section description applies throughout the entire region.
 - (i) A value of “0” to indicate a region above (but not including) the reported flight level and with unspecified upper bound.
 - (ii) A value of “1” to indicate a region above (and including) the reported flight level and with unspecified upper bound.
 - (iii) A value of “2” to indicate a region below (but not including) the reported flight level and extending to the surface.
 - (iv) A value of “3” to indicate a region below (and including) the reported flight level and extending to the surface.
- (c) Via two replications of the same horizontal section at the same reported flight level, in order to indicate a region extending both below and above (and including!) the reported flight level. In this case, the values reported for the two replications of B 33 042 shall be as follows:
 - (i) Values of “3” and “1”, respectively, to indicate a region beginning from below a reported flight level, but continuing through that level upward to some unspecified point above (e.g. TOP ABV FL100).
 - (ii) Values of “1” and “3”, respectively, to indicate a region beginning from above a reported flight level, but continuing through that level downward to some unspecified point below (e.g. CIGS BLW FL010).

Provisional Copy
2023

Category 02 – Meteorological sequences common to surface data

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 02 013	D 02 006	(Basic surface report)	
	D 02 003	Pressure and 24-hour pressure change	
	R 01 000	Wind, temperature, humidity, visibility, weather	
	D 02 005	Delayed replication of 1 descriptor	
D 02 035		Cloud layer	
		(Basic synoptic “instantaneous” data)	
	D 02 032	Temperature and humidity data	
	D 02 033	Visibility data	
	D 02 034	Precipitation past 24 hours	
	B 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	D 02 004	General cloud information	
	R 01 000	Delayed replication of 1 descriptor	
D 02 036	D 02 005	Cloud layer	Individual cloud layer or mass
		(Clouds with bases below station level)	
	R 05 000	Delayed replication of 5 descriptors	
	B 08 002	Vertical significance (surface observations)	
	B 20 011	Cloud amount	
	B 20 012	Cloud type	
	B 20 014	Height of top of cloud	
	B 20 017	Cloud top description	
D 02 054		(Ship “instantaneous” data)	
	D 02 052	Ship temperature and humidity data	
	D 02 053	Ship visibility data	
	B 07 033	Height of sensor above water surface	Set to missing (cancel)
	D 02 034	Precipitation past 24 hours	
	B 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	D 02 004	General cloud information	
	R 01 000	Delayed replication of 1 descriptor	
D 02 084	D 02 005	Cloud layer	
		(“Instantaneous” data of sequence D 07 096)	
	D 02 031	Pressure information	
	D 02 072	Temperature and humidity data	
	R 03 000	Delayed replication of 3 descriptors	
	R 01 005	Replicate 1 descriptor 5 times	
	D 07 063	Depth below land surface and soil temperature	
	B 07 061	Depth below land surface	Set to missing (cancel)

(continued)

(Category 02 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 02 084 (continued)	R 01 000	<i>Visibility data</i> Delayed replication of 1 descriptor	
	D 02 069	Visibility data	
	B 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	B 07 033	Height of sensor above water surface	Set to missing (cancel)
		<i>Marine data</i>	
	R 05 000	Delayed replication of 5 descriptors	
	B 20 031	Ice deposit (thickness)	
	B 20 032	Rate of ice accretion (estimated)	
	B 02 038	Method of water temperature and/or salinity measurement	
	B 22 043	Sea/water temperature	Scale: 2
	D 02 021	Waves	
		<i>State of ground and snow depth measurement</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 078	State of ground and snow depth measurement	
	B 12 113	Ground minimum temperature, past 12 hours	Scale: 2
		<i>Cloud data</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 004	General cloud information	
	R 05 000	Delayed replication of 5 descriptors	
	B 08 002	Vertical significance (surface observations)	
	B 20 011	Cloud amount	
	B 20 012	Cloud type	
	B 33 041	Attribute of following value	
	B 20 013	Height of base of cloud	
	D 02 036	Clouds with bases below station level	
		<i>Direction of cloud drift $6D_L D_M D_H$</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 047	Direction of cloud drift	
	B 08 002	Vertical significance (surface observations)	
		<i>Direction and elevation of cloud $57CD_a e_c$</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 048	Direction and elevation of cloud	Set to missing (cancel)
		("Period" data of sequence D 07 096)	
		<i>Present and past weather data</i>	
D 02 085	R 05 000	Delayed replication of 5 descriptors	
	B 20 003	Present weather	
	R 03 002	Replicate 3 descriptors 2 times	

(continued)

(Category 02 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 02 085 (continued)	B 04 024	Time period or displacement = –1 hour in the first replication, = –x hours in the second replication, x corresponding to the time period of W_1W_2 in the SYNOP report	/see left column
	B 20 004	Past weather (1)	
	B 20 005	Past weather (2) <i>Intensity of precipitation, size of precipitation element</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 175	Intensity of precipitation, size of precipitation element <i>Precipitation, obscuration and other phenomena</i>	
	R 02 000	Delayed replication of 2 descriptors	
	B 04 025	Time period or displacement	= –10 minutes
	D 02 076	Precipitation, obscuration and other phenomena <i>Lightning data</i>	
	R 02 000	Delayed replication of 2 descriptors	
	B 04 025	Time period or displacement	= –10 minutes
	B 13 059	Number of flashes (thunderstorm) <i>Wind data</i>	
	B 07 032	Height of sensor above local ground (or deck of marine platform)	
	B 07 033	Height of sensor above water surface	
	B 08 021	Time significance	= 2 Time averaged
	B 04 025	Time period or displacement	= –10 minutes, or number of minutes after a significant change of wind
	B 11 001	Wind direction	
	B 11 002	Wind speed	
	B 08 021	Time significance	Set to missing
	R 03 003	Replicate 3 descriptors 3 times	
	B 04 025	Time period or displacement = –10 minutes in the first replication, = –60 minutes in the second replication, = –60x3 or 60x6 minutes in the third replication	/ see left column
	B 11 043	Maximum wind gust direction	
	B 11 041	Maximum wind gust speed	
	B 04 025	Time period or displacement	= –10 minutes
	B 11 016	Extreme counterclockwise wind direction of a variable wind	

(continued)

(Category 02 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 02 085 (continued)	B 11 017	Extreme clockwise wind direction of a variable wind <i>Extreme temperature data</i>	Set to missing (cancel)
	D 02 077	Extreme temperature data	
	B 07 033	Height of sensor above water surface	
	D 02 041	Extreme temperature data <i>Precipitation measurement</i>	
	R 06 000	Delayed replication of 6 descriptors	
	B 07 032	Height of sensor above local ground (or deck of marine platform)	
	B 02 175	Method of precipitation measurement	
	B 02 178	Method of liquid content measurement of precipitation	
	R 02 005	Replicate 2 descriptors 5 times	
	B 04 024	Time period or displacement	
			= –1 hour in the first replication, = –3, –6, –12 and –24 hours in the other replications
	B 13 011	Total precipitation/total water equivalent	Set to missing (cancel)
	B 07 032	Height of sensor above local ground (or deck of marine platform) <i>Evaporation data</i>	
	R 03 000	Delayed replication of 3 descriptors	
	B 02 185	Method of evaporation measurement	
	R 01 002	Replicate 1 descriptor 2 times	
	D 02 044	Evaporation data <i>Total sunshine data</i>	
	R 02 000	Delayed replication of 2 descriptors	
	R 01 002	Replicate 1 descriptor 2 times	
	D 02 039	Sunshine data (from 1 hour and 24-hour period) <i>Radiation data</i>	
	R 02 000	Delayed replication of 2 descriptors	
	R 01 002	Replicate 1 descriptor 2 times	
	D 02 045	Radiation data (from 1 hour and 24-hour period) <i>Temperature change group 54g₀s_nd_T</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 046	Temperature change <i>First-order statistics of P, W, T, U data</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 083	First-order statistics of P, W, T, U data	

Category 05 – Meteorological or hydrological sequences common to hydrological observations

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 05 003	D 01 012	(SADC-HYCOS measurement array definition) Hour, minute	First single measurement minus increment Time interval between measurements
	B 04 065	Short time increment	
	R 01 000	Delayed replication of 1 descriptor	
	D 05 001	SADC-HYCOS single measurement	
D 05 006		(MEDHYCOS measurement)	Kelvin 4 characters long
	B 13 072	Downstream water level	
	B 13 082	Water temperature	
	B 13 019	Total precipitation past 1 hour	
	C 07 005	Units replacement	
	C 01 004	Data width replacement	
	B 12 001	Temperature/air temperature	
	B 13 073	Maximum water level	
D 05 007		(MEDHYCOS report)	Time of first measurement Time interval between measurements Single measurement
	D 01 029	Identification	
	D 01 012	Hour, minute	
	B 04 065	Short time increment	
	R 01 000	Delayed replication of 1 descriptor	
	D 05 006	MEDHYCOS measurement	
D 05 008		(AOCHYCOS – Chad measurement)	Same as MEDHYCOS type measurement Kelvin 4 characters long At –50 cm
	D 05 006	MEDHYCOS measurement	
	C 07 005	Units replacement	
	C 01 004	Data width replacement	
D 05 009		(AOCHYCOS – Chad report)	Time of first measurement Time interval between measurements Single measurement
	D 01 029	Identification	
	D 01 012	Hour, minute	
	B 04 065	Short time increment	
	R 01 000	Delayed replication of 1 descriptor	
	D 05 008	AOCHYCOS – Chad measurement	

(continued)

(Category 05 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 05 011	D 01 029	(MEDHYCOS report type 2) Identification	Time of first measurement Time interval between measurements Single measurement
	D 01 012	Hour, minute	
	B 04 065	Short time increment	
	R 01 000 D 05 010	Delayed replication of 1 descriptor MEDHYCOS – Measurement type 2	
D 05 018	D 01 029	(MEDHYCOS report with meteorology and water quality data) Identification	Time of first measurement Hour increment Same as AOCHYCOS type measurement
	D 01 012	Hour, minute	
	B 04 065	Short time increment	
	R 03 000	Delayed replication of 3 descriptors	
	D 05 008	AOCHYCOS – Chad measurement	
	D 05 016	Meteorological parameters associated with hydrological data	
	D 05 017	Water quality measurement	

Category 06 – Meteorological or oceanographic sequences common to oceanographic observations

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 06 001	B 02 032	(Depth, temperature) Indicator for digitization	
	R 02 000	Delayed replication of 2 descriptors	
	B 07 062	Depth below sea/water surface	
	B 22 042	Sea/water temperature	
D 06 004	B 02 032	(Depth, temperature, salinity) Indicator for digitization	
	B 02 033	Method of salinity/depth measurement	
	R 03 000	Delayed replication of 3 descriptors	
	B 07 062	Depth below sea/water surface	
	B 22 043	Sea/water temperature	
	B 22 062	Salinity	
D 06 005	B 02 031	Duration and time of current measurement	
	R 03 000	Delayed replication of 3 descriptors	
	B 07 062	Depth below sea/water surface	
	B 22 004	Direction of current	
	B 22 031	Speed of current	
D 06 013		(Sequence for representation of water level and residual in the time series)	Reference date for the time series Reference time for the time series Added to reset the reference time Added to each data value in the time series
	D 06 012	Sequence for representation of sensor type, significant qualifier for sensor and status of operation	
	D 01 011	Year, month, day	
	D 01 013	Hour, minute, second	
	B 22 120	Tide station automated water level check	
	B 22 121	Tide station manual water level check	
	B 04 015	Time increment	
	B 04 065	Short time increment	
	R 02 000	Delayed replication of 2 descriptors	
	B 22 038	Tidal elevation with respect to local chart datum	
	B 22 040	Meteorological residual tidal elevation (surge or offset)	
D 06 014		(Sequence for representation of water level in the time series, similar to D 06 013 but with no residual)	Reference date for the time series
	D 06 012	Sequence for representation of sensor type, significant qualifier for sensor and status of operation	
	D 01 011	Year, month, day	

(continued)

(Category 06 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 06 014 (continued)	D 01 013	Hour, minute, second	Reference time for the time series
	B 22 120	Tide station automated water level check	Added to reset the reference time Added to each data value in the time series
	B 22 121	Tide station manual water level check	
	B 04 015	Time increment	
	B 04 065	Short time increment	Alphanumeric
	R 01 000	Delayed replication of 1 descriptor	
	B 22 038	Tidal elevation with respect to local chart datum	
D 06 019		(Tide report identification, water level checks, time increments)	2 characters long
	B 01 075	Tide station identification	
	D 01 011	Year, month, day	
	D 01 012	Hour, minute	Message status Reference date/time for the time series
	B 22 042	Sea/water temperature	
	B 22 120	Tide station automated water level check	
	B 22 121	Tide station manual water level check	
D 06 030	C 01 002	Data width replacement	BPR CPU Acoustic modem DSP Acoustic modem
	B 04 015	Time increment (see Note 1)	
	B 04 065	Short time increment	
		(Sequence for representation of DART buoy standard hourly report)	Added to reset the reference time Added to each data value in the time series
	D 06 027	Sequence for representation of DART buoy identification, transmitter ID, type of tsunameter and the time the message is transmitted to the ground system	
	D 06 029	Sequence for representation of tsunameter sampling information for water column heights in the time series report	
	R 11 000	Delayed replication of 11 descriptors	BPR CPU Acoustic modem DSP Acoustic modem
	B 33 002	Quality information	
	D 01 011	Year, month, day	
	D 01 013	Hour, minute, second	Added to reset the reference time Added to each data value in the time series
	B 25 025	Battery voltage	
	B 25 025	Battery voltage	
	B 25 026	Battery voltage (large range)	Replicate 1 descriptor 4 times Water column height
	B 22 185	BPR transmission count	
	B 04 015	Time increment	
	B 04 065	Short time increment	
	R 01 004	Replicate 1 descriptor 4 times	
	B 22 182	Water column height	

(continued)

(Category 06 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 06 031	D 06 027	(Sequence for representation of DART buoy tsunami event reports and extended tsunami event reports) Sequence for representation of DART buoy identification, transmitter ID, type of tsunameter and the time the message is transmitted to the ground system	<p>Message status Time when tsunami is detected</p> <p>Reference date/time for the time series</p> <p>Determination of actual value reported in the time series Added to reset the reference time Added to each data value in the time series</p> <p>Number of frequency bins</p>
	D 06 029	Sequence for representation of tsunameter sampling information for water column heights in the time series report	
	B 01 053	Tsunameter report sequence number triggered by a tsunami event	
	B 33 002	Quality information	
	D 01 011	Year, month, day	
	D 01 013	Hour, minute, second	
	D 01 011	Year, month, day	
	D 01 013	Hour, minute, second	
	B 22 185	BPR transmission count	
	B 22 182	Water column height	
	B 04 016	Time increment	
	B 04 066	Short time increment	
	R 01 000	Delayed replication of 1 descriptor	
	B 22 184	Water column height deviation from the reference value	
D 06 040	B 22 078	(Sequence for representation of detailed spectral wave measurements) Duration of wave record	
	B 22 082	Maximum non-directional spectral wave density	
	R 06 000	Delayed replication of 6 descriptors	
	B 22 080	Waveband central frequency	
	B 22 069	Spectral wave density	
	B 22 086	Mean direction from which waves are coming	
	B 22 087	Principal direction from which waves are coming	
	B 22 088	First normalized polar coordinate from Fourier coefficients	
	B 22 089	Second normalized polar coordinate from Fourier coefficients	

(continued)

(Category 06 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 06 041	B 02 032	(Depth and temperature profile (high accuracy /precision)) Indicator for digitization	= 0 Fixed sensor depths Number of depths
	R 02 000	Delayed replication of 2 descriptors	
	B 07 062	Depth below sea/water surface	
	B 22 043	Sea/water temperature	

Note:

- (1) Range of value for parameter B 04 015 limited from –99 to 99; CREX common sequence D 06 019 being the original sequence with 2 characters only for the corresponding descriptor.

Category 07 – Surface report sequences (land)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 07 003	D 07 001	(Low altitude station) Low altitude station	Location (high accuracy) and basic report
	R 01 000 D 02 005	Delayed replication of 1 descriptor Cloud layer	
D 07 004	D 07 002	(Low altitude station) Low altitude station	Location (coarse accuracy) and basic report
	R 01 000 D 02 005	Delayed replication of 1 descriptor Cloud layer	
D 07 012	R 03 000 B 08 023 B 05 021	(Horizontal visibility) Delayed replication of 3 descriptors First-order statistics Bearing or azimuth	Up to 3 Direction of visibility observed VVVV
	B 20 001	Horizontal visibility	
D 07 013	R 06 000 B 01 064 B 08 014 B 20 061 B 08 014 B 20 061 B 20 018	(Runway visual range) Delayed replication of 6 descriptors Runway designator Qualifier for runway visual range Runway visual range (RVR) Qualifier for runway visual range Runway visual range (RVR) Tendency of runway visual range	Up to 4 D _R D _R V _R V _R V _R V _R V _R V _R V _R V _R i
	R 01 000 B 20 019	(Significant present or forecast weather) Delayed replication of 1 descriptor Significant present or forecast weather	
D 07 014	R 01 000 B 20 019	(Significant present or forecast weather) Delayed replication of 1 descriptor Significant present or forecast weather	Up to 3 w'w'
	R 01 000 D 02 005 B 20 002	(Clouds group(s)) Delayed replication of 1 descriptor Cloud layer Vertical visibility	
D 07 015	R 01 000 D 02 005 B 20 002	(Clouds group(s)) Delayed replication of 1 descriptor Cloud layer Vertical visibility	N _s N _s N _s , CC, h _s h _s h _s VVh _s h _s h _s
	R 01 000 B 20 020	(Significant recent weather phenomena) Delayed replication of 1 descriptor Significant recent weather phenomena	
D 07 016	R 01 000 B 20 020	(Significant recent weather phenomena) Delayed replication of 1 descriptor Significant recent weather phenomena	Up to 3 REw'w'
	R 01 000 B 11 070	(Wind shear on runway(s)) Delayed replication of 1 descriptor Designator of the runway affected by wind shear (including ALL)	
D 07 017	R 01 000 B 11 070	(Wind shear on runway(s)) Delayed replication of 1 descriptor Designator of the runway affected by wind shear (including ALL)	WS RWYD _R D _R

(continued)

(Category 07 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 07 018	B 08 016	(Trend-type landing forecast) Change qualifier of a trend-type forecast or an aerodrome forecast	TTTTT
	R 02 000	Delayed replication of 2 descriptors	Up to 2
	B 08 017	Qualifier of the time when the forecast change is expected	FM, TL, AT
	D 01 012	Hour, minute	GG, gg
	R 04 000	Delayed replication of 4 descriptors	Up to 1
	B 07 006	Height above station	
	B 11 001	Wind direction	ddd
	B 11 002	Wind speed	ff
	B 11 041	Maximum wind gust speed	f _m f _m
	B 20 009	General weather indicator (TAF/METAR)	
	R 01 000	Delayed replication of 1 descriptor	Up to 1
	B 20 001	Horizontal visibility	VVVV
	D 07 014	Significant present or forecast weather	w'w'
D 07 046		(METAR/SPECI visibility)	
	B 20 060	Prevailing horizontal visibility	VVVV or VVVVNDV
	R 02 000	Delayed replication of 2 descriptors	Up to 2
	B 05 021	Bearing or azimuth	Direction of minimum visibility observed D _v
	B 20 059	Minimum horizontal visibility	V _N V _N V _N V _N
D 07 047		(METAR/SPECI/TAF clouds), replacing D 07 015	
	R 05 000	Delayed replication of 5 descriptors	
	B 08 002	Vertical significance (surface observations)	
	B 20 011	Cloud amount	N _s N _s N _s
	B 20 012	Cloud type	CC
	B 20 013	Height of base of cloud	h _s h _s h _s – m
	B 20 092	Height of base of cloud	h _s h _s h _s – ft
	B 20 002	Vertical visibility	VVh _s h _s h _s – m
	B 20 091	Vertical visibility	VVh _s h _s h _s – ft
D 07 048		(Trend type forecast), replacing D 07 018	
	B 08 016	Change qualifier of a trend-type forecast or an aerodrome forecast	TTTTT NOSIG
	R 02 000	Delayed replication of 2 descriptors	= 0, 1 or 2
	B 08 017	Qualifier of the time when the forecast change is expected	TT
	D 01 012	Hour, minute	GGgg
	R 12 000	Delayed replication of 12 descriptors	= 0 or 1
	B 07 032	Height of sensor above local ground (or deck of marine platform)	= 10 m (if the actual value is not available)
	B 11 001	Wind direction	ddd
	B 08 054	Qualifier for wind speed or wind gusts	P

(continued)

(Category 07 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 07 048 (continued)	B 11 083	Wind speed (see Note 5)	ff – km/h
	B 11 084	Wind speed (see Note 5)	ff – kt
	B 11 002	Wind speed (see Note 5)	ff – m/s
	B 08 054	Qualifier for wind speed or wind gusts	P
	B 11 085	Maximum wind gust speed (see Note 6)	$f_m f_m$ – km/h
	B 11 086	Maximum wind gust speed (see Note 6)	$f_m f_m$ – kt
	B 11 041	Maximum wind gust speed (see Note 6)	$f_m f_m$ – m/s
	B 08 054	Qualifier for wind speed or wind gusts	Set to missing (cancel)
	B 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	B 20 009	General weather indicator (TAF/METAR)	CAVOK NSW NSC
	R 01 000	Delayed replication of 1 descriptor	= 0 or 1
	B 20 060	Prevailing horizontal visibility	VVVV
	D 07 014	Significant present and forecast weather	Weather intensity and phenomena w'w'
	D 07 047	METAR/SPECI/TAF clouds, replacing D 07 015	$N_s N_s N_s h_s h_s h_s$
		(Sea conditions)	
D 07 049	R 02 000	Delayed replication of 2 descriptors	= 0 or 1
	B 22 043	Sea/water temperature	$T_s T_s$
	B 22 021	Height of waves	S'
D 07 050		(Runway state)	
	R 01 000	Delayed replication of 1 descriptor	= 0 or 1
	B 20 085	General condition of runway	SNOCLO
	R 02 000	Delayed replication of 2 descriptors	
	B 01 064	Runway designator	$D_R D_R$
	B 20 085	General condition of runway	CLRD//
	R 05 000	Delayed replication of 5 descriptors	
	B 01 064	Runway designator	$D_R D_R$
	B 20 086	Runway deposits	E_R
	B 20 087	Runway contamination	C_R
	B 20 088	Depth of runway deposits	$e_R e_R$
	B 20 089	Runway friction coefficient	$B_R B_R$
D 07 051		(Full METAR/SPECI), replacing D 07 021	
	D 07 045	Main part of METAR/SPECI, replacing D 07 011	
	D 07 046	METAR/SPECI visibility	VVVV or VVVVNDV
			$V_N V_N V_N V_N D_V$
	D 07 013	Runway visual range	$R D_R D_R / V_R V_R V_R V_R$
	D 07 014	Significant present and forecast weather	Weather intensity and phenomena w'w'
	D 07 047	METAR/SPECI/TAF clouds, replacing D 07 015	$N_s N_s N_s h_s h_s h_s$
	D 07 016	Significant recent weather phenomena	$R E w' w'$
	D 07 017	Wind shear on runway(s)	$W S R D_R D_R$

(continued)

(Category 07 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 07 051 (continued)	D 07 049	Sea conditions	WT _s T _s /SS' RD _R DR/ERCRERERBR _R = 0 to 3 normally
	D 07 050	Runway state	
	R 01 000	Delayed replication of 1 descriptor	
	D 07 048	Trend type forecast, replacing D 07 018	
D 07 056		(Aerodrome forecast – full TAF)	
	D 07 052	Aerodrome forecast identification and time interval	
	D 07 053	Forecast weather at an aerodrome	
	D 07 054	Forecast of extreme temperatures	
	R 01 000	Delayed replication of 1 descriptor	
	D 07 055	Change indicator and forecast changes	
D 07 079		(Sequence for representation of synoptic reports from fixed land stations suitable for SYNOP data and for maritime data from coastal stations)	
	D 01 090	Surface station identification; time, horizontal and vertical coordinates	
	D 02 031	Pressure information	
	D 02 035	Basic synoptic “instantaneous” data	
	D 02 036	Clouds with bases below station level	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 047	Direction of cloud drift	
	B 08 002	Vertical significance (surface observations)	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 048	Direction and elevation of cloud	
	D 02 037	State of ground, snow depth, ground minimum temperature	
	R 02 000	Delayed replication of 2 descriptors	
	B 22 061	State of the sea	
	B 20 058	Visibility seawards from a coastal station	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 056	Sea/water temperature	
			Sea/water surface temperature, method of measurement, depth below water surface
	R 01 000	Delayed replication of 1 descriptor	
	D 02 055	Icing and ice	
	D 02 043	Basic synoptic “period” data	
	D 02 044	Evaporation data	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 045	Radiation data (from 1 hour and 24-hour period)	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 046	Temperature change	

(continued)

(Category 07 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 07 084	D 01 090	(Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data in compliance with reporting practices in RA IV) Surface station identification; time, horizontal and vertical coordinates	Set to missing (cancel)
	D 02 031	Pressure information	
	D 02 035	Basic synoptic “instantaneous” data	
	D 02 036	Clouds with bases below station level	
	D 02 047	Direction of cloud drift	
	B 08 002	Vertical significance (surface observations)	
	D 02 048	Direction and elevation of cloud	
	D 02 037	State of ground, snow depth, ground minimum temperature	
	B 20 055	State of sky in the tropics	
	R 01 000	Delayed replication of 1 descriptor	
	C 05 001	Character insertion	
	D 02 043	Basic synoptic “period” data	
	D 02 044	Evaporation data	
	R 01 002	Replicate 1 descriptor 2 times	
	D 02 045	Radiation data (from 1 hour and 24-hour period)	
	D 02 046	Temperature change	
		(“Instantaneous” parameters of sequence D 07 089) <i>Surface station identification, time, horizontal and vertical coordinates</i>	
D 07 087	D 01 001	WMO block and station number	Iiii ix YY GG, gg
	B 02 001	Type of station	
	D 01 011	Year, month, day	
	D 01 012	Hour, minute	
	D 01 023	Latitude/longitude (coarse accuracy)	
	B 07 030	Height of station ground above mean sea level	
	B 07 031	Height of barometer above mean sea level	
		<i>Pressure data</i>	
	D 02 001	Pressure and 3-hour pressure change	
	B 10 062	24-hour pressure change	
	B 07 004	Pressure	
	B 10 009	Geopotential height	

(continued)

(Category 07 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 07 087 (continued)	B 07 032	<i>Temperature and humidity</i> Height of sensor above local ground (or deck of marine platform)	Temperature measurement
	B 12 101	Temperature/air temperature	$s_n T_{TT}$ Scale: 2
	B 12 103	Dewpoint temperature	$s_n T_d T_d$ Scale: 2
	B 13 003	Relative humidity	
	B 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
		<i>Visibility</i>	
	B 20 001	Horizontal visibility	VV
		<i>Cloud data</i>	
	D 02 004	General cloud information	/see left column
		Cloud cover (total) N: If N = 9, then B 20 010 = 113; if N = /, then B 20 010 = missing Vertical significance: If C_L are observed, then B 08 002 = 7 Low cloud: If C_L are not observed and C_M are observed, then B 08 002 = 8 Middle cloud: If only C_H are observed, B 08 002 = 0; if N = 9, then B 08 002 = 5, if N = 0, then B 08 002 = 62; if N = /, then B 08 002 = missing Cloud amount (of low or middle clouds) N_h : If N = 0, then B 20 011 = 0; if N = 9, then B 20 011 = 9; if N = /, then B 20 011 = missing Height of base of cloud h: If N = 0 or /, then B 20 013 = missing Cloud type (low clouds) C_L : B 20 012 = $C_L + 30$; if N = 0, then B 20 012 = 30; if N = 9 or /, then B 20 012 = 62 Cloud type (middle clouds) C_M : B 20 012 = $C_M + 20$; if N = 0, then B 20 012 = 20; if N = 9 or / or C_M = /, then B 20 012 = 61 Cloud type (high clouds) C_H : B 20 012 = $C_H + 10$; if N = 0, then B 20 012 = 10; if N = 9 or / or C_H = /, then B 20 012 = 60	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 005	Cloud layer Vertical significance: In any Cb layer, B 08 002 = 4, else in the first replication, if N = 9, then B 08 002 = 5, if N = /, then B 08 002 = missing, else B 08 002 = 1, in the other replications B 08 002 = 2, 3, 4 Cloud amount N_s : In the first replication, if N = /, then B 20 011 = missing, else B 20 011 = N_s , in the other replications B 20 011 = N_s Cloud type C: If N = 9 or /, then B 20 012 = missing, else B 20 012 = C Height of base of cloud $h_s h_s$	/see left column

(continued)

(Category 07 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 07 091		(CREX template for surface observations from one-hour period with national and WMO station identification)	
	D 01 089	National station identification	
	D 01 090	Surface station identification; time, horizontal and vertical coordinates	
	B 08 010	Surface qualifier (temperature data)	
	D 01 091	Surface station instrumentation	
	D 02 001	Pressure and 3-hour pressure change	
	B 07 004	Pressure	Standard level
	B 10 009	Geopotential height	Standard level
	D 02 072	Temperature and humidity data	
	R 03 000	Delayed replication of 3 descriptors	
	R 01 005	Replicate 1 descriptor 5 times	
	D 07 063	Depth below land surface and soil temperature	
	B 07 061	Depth below land surface	Set to missing (cancel)
	R 01 000	Delayed replication of 1 descriptor	
	D 02 069	Visibility data	
	B 07 032	Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)
	B 07 033	Height of sensor above water surface	Set to missing (cancel)
	R 05 000	Delayed replication of 5 descriptors	
	B 20 031	Ice deposit (thickness)	
	B 20 032	Rate of ice accretion (estimated)	
	B 02 038	Method of water temperature and/or salinity measurement	
	B 22 043	Sea/water temperature	Scale: 2
	D 02 021	Waves	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 078	State of ground and snow depth measurement	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 073	Cloud data	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 074	Present and past weather	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 175	Intensity of precipitation, size of precipitation element	
	R 02 000	Delayed replication of 2 descriptors	
	B 04 025	Time period or displacement	= –10 (minutes)
	D 02 076	Precipitation, obscuration and other phenomena	
	D 02 071	Wind data from one-hour period	
	D 02 077	Extreme temperature data	
	B 07 033	Height of sensor above water surface	Set to missing (cancel)
	R 01 000	Delayed replication of 1 descriptor	

(continued)

(Category 07 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 07 091 (continued)	D 02 079	Precipitation measurement	Set to missing (cancel) = –10 (minutes)
	B 07 032	Height of sensor above local ground (or deck of marine platform)	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 080	Evaporation measurement	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 081	Total sunshine data	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 082	Radiation data	
	R 02 000	Delayed replication of 2 descriptors	
	B 04 025	Time period or displacement	
	B 13 059	Number of flashes (thunderstorm)	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 083	First-order statistics of P, W, T, U data	
	B 33 005	Quality information (AWS data)	
	B 33 006	Internal measurement status information (AWS)	

Notes:

- (5) Within D 07 045, D 07 048 and D 07 053, wind speed shall be reported in the same units as in the original TAC data and:
 B 11 083 shall be set to missing, if wind speed is reported in knots or m s^{-1} in TAC data,
 B 11 084 shall be set to missing, if wind speed is reported in km h^{-1} or m s^{-1} in TAC data.
- (6) Within D 07 045, D 07 048 and D 07 053, maximum wind speed (gusts) shall be reported in the same units as in the original TAC data and:
 B 11 085 shall be set to missing, if maximum wind speed is reported in knots or m s^{-1} in TAC data,
 B 11 086 shall be set to missing, if maximum wind speed is reported in km h^{-1} or m s^{-1} in TAC data.

Category 08 – Surface report sequences (sea)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 08 010	B 01 011	(TRACKOB template) Ship or mobile land station identifier	
	R 13 000	Delayed replication of 13 descriptors	
	D 01 011	Year, month, day	
	D 01 012	Hour, minute	
	D 01 021	Latitude/longitude (high accuracy)	
	B 04 080	Averaging period for following value	
	B 22 049	Sea-surface temperature	
	B 04 080	Averaging period for following value	
	B 22 059	Sea-surface salinity	
	B 04 080	Averaging period for following value	
	B 22 005	Direction of sea-surface current	
	B 02 042	Indicator for sea-surface current speed	
	B 22 032	Speed of sea-surface current	
	B 02 042	Indicator for sea-surface current speed	Cancel
	B 04 080	Averaging period for following value	Cancel

Provisional Copy
2023

Category 09 – Vertical sounding sequences (conventional data)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 09 001	D 01 037	(Vertical wind profile) Land station for vertical soundings	Identification, etc. (land station, high accuracy position)
	R 01 000 D 03 011	Delayed replication of 1 descriptor Wind at height	
D 09 002	D 01 038	(Vertical wind profile) Land station for vertical soundings	Identification, etc. (land station, coarse accuracy position)
	R 01 000 D 03 011	Delayed replication of 1 descriptor Wind at height	
D 09 003	D 01 037	(Vertical wind profile) Land station for vertical soundings	Identification, etc. (land station, high accuracy position)
	R 01 000 D 03 012	Delayed replication of 1 descriptor Wind at pressure level	
D 09 004	D 01 038	(Vertical wind profile) Land station for vertical soundings	Identification, etc. (land station, coarse accuracy position)
	R 01 000 D 03 012	Delayed replication of 1 descriptor Wind at pressure level	
D 09 005	D 01 037	(Vertical sounding with relative humidity) Land station for vertical soundings	Identification, etc. (land station, high accuracy position) Significant cloud layer
	D 02 004	General cloud information	
	R 01 000 D 03 013	Delayed replication of 1 descriptor Geopotential, temperature, humidity, wind at pressure level	
D 09 006	D 01 038	(Vertical sounding with relative humidity) Land station for vertical soundings	Identification, etc. (land station, coarse accuracy position) Significant cloud layer
	D 02 004	General cloud information	
	R 01 000 D 03 013	Delayed replication of 1 descriptor Geopotential, temperature, humidity, wind at pressure level	
D 09 007	D 01 037	(Vertical sounding with dewpoint data) Land station for vertical soundings	Identification, etc. (land station, high accuracy position) Significant cloud layer
	D 02 004	General cloud information	
	R 01 000 D 03 014	Delayed replication of 1 descriptor Geopotential, temperature, dewpoint temperature, wind at pressure level	

(continued)

(Category 09 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 09 008	D 01 038	(Vertical sounding with dewpoint data) Land station for vertical soundings	Identification, etc. (land station, coarse accuracy position) Significant cloud layer
	D 02 004	General cloud information	
	R 01 000	Delayed replication of 1 descriptor	
	D 03 014	Geopotential, temperature, dewpoint temperature, wind at pressure level	
D 09 011	D 01 039	(Vertical wind profile) Ship for vertical soundings	Ship's identification, etc.
	R 01 000	Delayed replication of 1 descriptor	
	D 03 011	Wind at height	
D 09 012	D 01 039	(Vertical wind profile) Ship for vertical soundings	Ship's identification, etc.
	R 01 000	Delayed replication of 1 descriptor	
	D 03 012	Wind at pressure level	
D 09 013	D 01 039	(Vertical sounding with relative humidity) Ship for vertical soundings	Ship's identification, etc. Significant cloud layer
	D 02 004	General cloud information	
	R 01 000	Delayed replication of 1 descriptor	
	D 03 013	Geopotential, temperature, humidity, wind at pressure level	
D 09 014	D 01 039	(Vertical sounding with dewpoint data) Ship for vertical soundings	Ship's identification, etc. Significant cloud layer
	D 02 004	General cloud information	
	R 01 000	Delayed replication of 1 descriptor	
	D 03 014	Geopotential, temperature, dewpoint temperature, wind at pressure level	
D 09 015	D 01 040	(Vertical wind profile) Ship for vertical soundings	Ship's identification, etc.
	R 01 000	Delayed replication of 1 descriptor	
	D 03 011	Wind at height	
D 09 016	D 01 040	(Vertical wind profile) Ship for vertical soundings	Ship's identification, etc.
	R 01 000	Delayed replication of 1 descriptor	
	D 03 012	Wind at pressure level	

(continued)

(Category 09 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 09 017	D 01 040	(Vertical sounding with relative humidity) Ship for vertical soundings	Ship's identification, etc. Significant cloud layer
	D 02 004	General cloud information	
	R 01 000	Delayed replication of 1 descriptor	
	D 03 013	Geopotential, temperature, humidity, wind at pressure level	
D 09 018	D 01 040	(Vertical sounding with dewpoint data) Ship for vertical soundings	Ship's identification, etc. Significant cloud layer
	D 02 004	General cloud information	
	R 01 000	Delayed replication of 1 descriptor	
	D 03 014	Geopotential, temperature, dewpoint temperature, wind at pressure level	
D 09 019	D 01 031	(Wind profiler – wind data sounding) Identification and type of station, date/time, location (high accuracy), height of station	
	B 02 003	Type of measuring equipment used	
	R 01 000	Delayed replication of 1 descriptor	
	D 03 011	Wind at height	
D 09 020	D 01 031	(Wind profiler – Cartesian coordinates) Identification and type of station, date/time, location (high accuracy), height of station	
	B 02 003	Type of measuring equipment used	
	R 04 000	Delayed replication of 4 descriptors	
	B 07 003	Geopotential	
	B 11 003	u-component	
	B 11 004	v-component	
	B 11 005	w-component	
D 09 030	B 15 004	(Ozone sonde flight data) (see Note 1) Ozone sounding correction factor (CF)	Since launch time, if needed, in minutes
	B 15 005	Ozone p	
	R 04 000	Delayed replication of 4 descriptors	
	B 04 015	Time increment	
	B 08 006	Ozone vertical sounding significance	
	B 07 004	Pressure	
	B 15 003	Measured ozone partial pressure (sounding)	
D 09 031	B 15 004	(Ozone sonde flight data) Ozone sounding correction factor (CF)	Since launch time in minutes
	B 15 005	Ozone p	
	R 04 000	Delayed replication of 4 descriptors	
	B 04 025	Time period or displacement	
	B 08 006	Ozone vertical sounding significance	
	B 07 004	Pressure	
	B 15 003	Measured ozone partial pressure (sounding)	

(continued)

(Category 09 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 09 054	D 01 001	(Sequence for representation of CLIMAT TEMP and CLIMAT TEMP SHIP data) WMO block and station numbers	Identification of launch site
	B 01 011	Ship or mobile land station identifier	Ship's call sign
	D 01 011	Year, month, day	
	D 01 012	Hour, minute	
	D 01 021	Latitude/longitude (high accuracy)	
	B 07 030	Height of station ground above mean sea level	
	B 07 031	Height of barometer above mean sea level	
	B 07 007	Height	Release of sonde above mean sea level
		<i>Monthly mean data</i>	
	B 04 023	Time period or displacement	Number of days in the month
	B 04 059	Times of observation used to compute the reported mean values	
	R 15 000	Delayed replication of 15 descriptors	
	B 08 001	Vertical sounding significance	
	B 08 023	First-order statistics	= 4 Mean value
	B 07 004	Pressure	
	B 10 009	Geopotential height	
	B 12 101	Temperature/air temperature	
	B 12 103	Dewpoint temperature	
	B 08 023	First-order statistics	= 32 Vector mean
	B 11 001	Wind direction	
	B 11 002	Wind speed	
	B 08 023	First-order statistics	Set to missing
	B 11 019	Steadiness of wind	
	B 08 050	Qualifier for number of missing values in calculation of statistic	= 2 Temperature
	B 08 020	Total number of missing entities (with respect to accumulation or average)	Days
	B 08 050	Qualifier for number of missing values in calculation of statistic	= 9 Wind
	B 08 020	Total number of missing entities (with respect to accumulation or average)	Days
D 09 071		(Sequence for representation of PILOT in the area of ASECNA)	
	D 01 001	WMO block and station numbers	
	B 02 014	Tracking technique/status of system used	
	B 02 003	Type of measuring equipment used	
	D 01 113	Date/time of launch	
	D 01 114	Horizontal and vertical coordinates of launch site	
	D 01 023	Latitude/longitude (coarse accuracy)	
	B 07 030	Height of station ground above mean sea level	
	B 07 007	Height	Release of balloon
	R 03 000	Delayed replication of 3 descriptors	

(continued)

(Category 09 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 09 071 (continued)	B 07 009 B 11 001 B 11 002	Geopotential height Wind direction Wind speed	

Note:

- (1) Sequence D 09 030 is deprecated because of incorrect usage of descriptor B 04 015; sequence D 09 031 should be used instead.

Provisional Copy
2023

Provisional Copy
2023

Category 11 – Single level report sequences (conventional data)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 11 004	R 01 000	(ACARS supplementary reported variables) Delayed replication of 1 descriptor	
	B 11 034	Vertical gust velocity	
	R 01 000	Delayed replication of 1 descriptor	
	B 11 035	Vertical gust acceleration	
	R 01 000	Delayed replication of 1 descriptor	
	B 11 075	Mean turbulence intensity (eddy dissipation rate)	
	R 01 000	Delayed replication of 1 descriptor	
	B 11 076	Peak turbulence intensity (eddy dissipation rate)	
	R 01 000	Delayed replication of 1 descriptor	
	B 33 025	ACARS interpolated values indicator	
	R 01 000	Delayed replication of 1 descriptor	
	B 33 026	Moisture quality	
D 11 008		(Aircraft ascent/descent profile without latitude/longitude indicated at each level)	
	B 01 008	Aircraft registration number or other identification	
	D 01 011	Year, month, day	
	D 01 013	Hour, minute, second	
	D 01 021	Latitude/longitude (high accuracy)	
	B 08 004	Phase of aircraft flight	
	R 01 000	Delayed replication of 1 descriptor	
	D 11 006	AMDAR data or aircraft data for one level without latitude/longitude	
D 11 009		(Aircraft ascent/descent profile with latitude/longitude given for each level)	
	B 01 008	Aircraft registration number or other identification	
	D 01 011	Year, month, day	
	D 01 013	Hour, minute, second	
	D 01 021	Latitude/longitude (high accuracy)	
	B 08 004	Phase of aircraft flight	
	R 01 000	Delayed replication of 1 descriptor	
	D 11 007	Aircraft data for one level with latitude/longitude indicated	

Provisional Copy
2023

B 01 087	WMO marine observing platform extended identifier
	<i>Cruise/ship line information</i>
B 01 036	Agency in charge of operating the observing platform
B 01 115	Identifier of the cruise or mission under which the data were collected
B 01 080	Ship line number according to SOOP
B 05 036	Ship transect number according to SOOP
D 01 011	Year, month, day
D 01 012	Hour, minute
D 01 021	Latitude/longitude (high accuracy)
	<i>Profile information</i>
B 01 079	Unique identifier for the profile
B 01 023	Observation sequence number
B 22 063	Total water depth
	<i>Surface pressure</i>
R 01 000	Delayed replication of 1 descriptor
D 02 001	Pressure and 3-hour pressure change
	<i>Waves</i>
R 01 000	Delayed replication of 1 descriptor
D 02 021	Waves

B 01 087	WMO marine observing platform extended identifier
	<i>Cruise/ship line information</i>
B 01 036	Agency in charge of operating the observing platform
B 01 115	Identifier of the cruise or mission under which the data were collected
B 01 080	Ship line number according to SOOP
B 05 036	Ship transect number according to SOOP
D 01 011	Year, month, day
D 01 012	Hour, minute
D 01 021	Latitude/longitude (high accuracy)
	<i>Profile information</i>
B 01 079	Unique identifier for the profile
B 01 023	Observation sequence number
B 22 063	Total water depth
	<i>Surface pressure</i>
R 01 000	Delayed replication of 1 descriptor
D 02 001	Pressure and 3-hour pressure change
	<i>Waves</i>
R 01 000	Delayed replication of 1 descriptor
D 02 021	Waves

B 01 087	WMO marine observing platform extended identifier
	<i>Cruise/ship line information</i>
B 01 036	Agency in charge of operating the observing platform
B 01 115	Identifier of the cruise or mission under which the data were collected
B 01 080	Ship line number according to SOOP
B 05 036	Ship transect number according to SOOP
D 01 011	Year, month, day
D 01 012	Hour, minute
D 01 021	Latitude/longitude (high accuracy)
	<i>Profile information</i>
B 01 079	Unique identifier for the profile
B 01 023	Observation sequence number
B 22 063	Total water depth
	<i>Surface pressure</i>
R 01 000	Delayed replication of 1 descriptor
D 02 001	Pressure and 3-hour pressure change
	<i>Waves</i>
R 01 000	Delayed replication of 1 descriptor
D 02 021	Waves

(Category 15 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 15 007 (continued)	B 02 171	Instrument serial number for water temperature profile measurement	Set to missing (cancel)
	B 22 067	Instrument type for water temperature/salinity profile measurement <i>Temperature and salinity profile data</i>	Set to missing (cancel)
	B 02 038	Method of water temperature and/or salinity measurement	
	B 22 067	Instrument type for water temperature/salinity profile measurement	
	B 22 068	Water temperature profile recorder types	
	B 02 171	Instrument serial number for water temperature profile measurement	
	B 02 033	Method of salinity/depth measurement	
	B 02 032	Indicator for digitization	
	B 22 056	Direction of profile	
	B 03 011	Method of depth calculation	
	D 06 035	Temperature and salinity profile <i>Current profile data</i>	
	R 07 000	Delayed replication of 7 descriptors	
	B 02 032	Indicator for digitization	
	B 03 010	Method of sea/water current measurement	
	B 02 031	Duration and time of current measurement	
	B 02 040	Method of removing velocity and motion of platform from current	
	B 22 056	Direction of profile	
	B 03 011	Method of depth calculation	
	D 06 036	Current profile <i>Dissolved oxygen profile data</i>	
	R 04 000	Delayed replication of 4 descriptors	
	B 02 032	Indicator for digitization	
	B 03 012	Instrument type/sensor for dissolved oxygen measurement	
	B 03 011	Method of depth calculation	
	D 06 037	Dissolved oxygen profile data	
		(Sequence for the representation of data from moored buoys) <i>Buoy identification and location</i>	
	D 01 126	Sequence for representation of moored buoy identification <i>Standard meteorological data</i>	
	D 06 038	Sequence for representation of standard surface marine meteorological observations from moored buoys	For buoys equipped with more than 1 anemometer the height of sensor should relate to the one being used

(continued)

(Category 15 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 15 008 (continued)		<i>Optional ancillary meteorological data</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 091	Sequence for representation of ancillary meteorological observations	
		<i>Optional radiation measurements</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 02 082	Radiation data	
		<i>Optional basic wave measurements</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 06 039	Sequence for representation of basic wave measurements	
		<i>Optional spectral wave measurements</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 06 040	Sequence for representation of detailed spectral wave measurements	
		<i>Optional temperature profile measurements</i>	
	R 02 000	Delayed replication of 2 descriptors	
	B 02 005	Precision of temperature observation	
	D 06 041	Depth and temperature profile (high accuracy/precision)	
		<i>Optional temperature and salinity profile measurements</i>	
	R 02 000	Delayed replication of 2 descriptors	
	B 02 005	Precision of temperature observation	
	D 06 004	Depth, temperature, salinity	
		<i>Optional subsurface current measurements</i>	
	R 01 000	Delayed replication of 1 descriptor	
	D 06 005	Subsurface current measurements	

Provisional Copy
2023

Category 16 – Synoptic feature sequences

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 16 003	R 09 000	(Jet stream) Delayed replication of 9 descriptors	Jet stream value Value for line Flight level Cancel Cancel End of object
	B 08 011	Meteorological feature	
	B 08 007	Dimensional significance	
	R 04 000	Delayed replication of 4 descriptors	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 10 002	Height	
	B 11 002	Wind speed	
	B 08 007	Dimensional significance	
	B 08 011	Meteorological feature	
D 16 004	R 10 000	(Turbulence) Delayed replication of 10 descriptors	Value for turbulence Value for area Flight level (base of layer) Flight level (top of layer) Cancel Cancel End of object
	B 08 011	Meteorological feature	
	B 08 007	Dimensional significance	
	B 07 002	Height or altitude	
	B 07 002	Height or altitude	
	R 02 000	Delayed replication of 2 descriptors	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 11 031	Degree of turbulence (see Note 1)	
	B 08 007	Dimensional significance	
	B 08 011	Meteorological feature	
D 16 005	R 08 000	(Storm) Delayed replication of 8 descriptors	Storm centre Value for point Use “UNKNOWN” for a sandstorm Value for type of storm Cancel Cancel End of object
	B 08 005	Meteorological attribute significance	
	B 08 007	Dimensional significance	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 01 026	WMO storm name	
	B 19 001	Type of synoptic feature	
	B 08 007	Dimensional significance	
	B 08 005	Meteorological attribute significance	
D 16 006	R 11 000	(Cloud) Delayed replication of 11 descriptors	Value for cloud Value for area Flight level (base of layer) Flight level (top of layer)
	B 08 011	Meteorological feature	
	B 08 007	Dimensional significance	
	B 07 002	Height or altitude	
	B 07 002	Height or altitude	

(continued)

(Category 16 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 16 006 (continued)	R 02 000	Delayed replication of 2 descriptors	Cancel Cancel End of object
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 20 011	Cloud amount (see Note 2)	
	B 20 012	Cloud type	
	B 08 007	Dimensional significance	
	B 08 011	Meteorological feature	
D 16 007		(Front)	Value for type of front Value for line Cancel Cancel End of object
	R 09 000	Delayed replication of 9 descriptors	
	B 08 011	Meteorological feature (see Note 3)	
	B 08 007	Dimensional significance	
	R 04 000	Delayed replication of 4 descriptors	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 19 005	Direction of motion of feature	
	B 19 006	Speed of motion of feature	
	B 08 007	Dimensional significance	
	B 08 011	Meteorological feature	
D 16 008		(Tropopause)	Bit 3 set for tropopause Value for point Type of tropopause value Cancel Cancel Cancel End of object
	R 10 000	Delayed replication of 10 descriptors	
	B 08 001	Vertical sounding significance	
	B 08 007	Dimensional significance	
	B 08 023	First-order statistics (see Note 4)	
	R 03 000	Delayed replication of 3 descriptors	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 10 002	Height	
	B 08 023	First-order statistics	
	B 08 007	Dimensional significance	
	B 08 001	Vertical sounding significance	
		(Airframe icing area)	
	R 10 000	Delayed replication of 10 descriptors	
D 16 009	B 08 011	Meteorological feature	Value for airframe icing Value for area Flight level (base of layer) Flight level (top of layer) Type of airframe icing Cancel Cancel End of object
	B 08 007	Dimensional significance	
	B 07 002	Height or altitude	
	B 07 002	Height or altitude	
	R 02 000	Delayed replication of 2 descriptors	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 20 041	Airframe icing	
	B 08 007	Dimensional significance	
	B 08 011	Meteorological feature	

(continued)

(Category 16 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 16 010	R 07 000	(Name of feature)	Value for point
	B 08 011	Delayed replication of 7 descriptors	
	B 08 007	Meteorological feature	
	B 01 022	Dimensional significance	
	B 05 002	Name of feature	
	B 06 002	Latitude (coarse accuracy)	
	B 08 007	Longitude (coarse accuracy)	
	B 08 011	Dimensional significance	
D 16 011	B 08 011	Meteorological feature	Cancel Cancel End of object
		(Volcano erupting)	
	R 16 000	Delayed replication of 16 descriptors	Value for special clouds Volcano name Value for point
	B 08 011	Meteorological feature	
	B 01 022	Name of feature	
	B 08 007	Dimensional significance	Eruption starting time
	R 02 000	Delayed replication of 2 descriptors	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 08 021	Time significance	
	B 04 001	Year	
	B 04 002	Month	
	B 04 003	Day	
	B 04 004	Hour	
	B 04 005	Minute	
	B 20 090	Special clouds	
	B 08 021	Time significance	
	B 08 007	Dimensional significance	
	B 08 011	Meteorological feature	
D 16 022		(Forecast data)	NWP model name, etc. code table defined by originating/ generating centre
	B 01 032	Generating application	
	B 02 041	Method for estimating reports related to synoptic features	
	B 19 001	Type of synoptic feature	
	B 19 010	Method for tracking the centre of synoptic feature	
	R 18 000	Delayed replication of 18 descriptors	
	B 08 021	Time significance	
	B 04 014	Time increment	
	B 08 005	Meteorological attribute significance	
	D 01 023	Latitude/longitude (coarse accuracy)	

(continued)

(Category 16 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 16 022 (continued)	B 19 005	Direction of motion of feature	For example, used in the United States Forecast time averaged Minutes Starting Ending
	B 19 006	Speed of motion of feature	
	B 10 004	Pressure	
	B 11 041	Maximum wind gust speed	
	B 08 021	Time significance	
	B 04 075	Short time period or displacement	
	B 11 040	Maximum wind speed (mean wind)	
	B 19 008	Vertical extent of circulation	
	R 05 004	Replicate 5 descriptors 4 times	
	B 05 021	Bearing or azimuth	
	B 05 021	Bearing or azimuth	
	R 02 002	Replicate 2 descriptors 2 times	
	B 19 003	Wind speed threshold	
	B 19 004	Effective radius with respect to wind speeds above threshold	
D 16 033		(SIGMET, Outlook)	= 4 Forecast
	B 08 021	Time significance	
	D 01 011	Year, month, day	
	D 01 012	Hour, minute	
	R 01 000	Delayed replication of 1 descriptor	
	D 01 027	Description of a feature in 3-D or 2-D	
D 16 034	B 08 021	Time significance	Set to missing (cancel)
		(Volcanic Ash SIGMET)	
	B 08 079	Product status	= 0 Normal issue, = 1 Correction
	D 16 030	SIGMET header	
	B 08 011	Meteorological feature	= 17 Volcano
	B 01 022	Name of feature	
	B 08 007	Dimensional significance	= 0 Point
	D 01 023	Latitude/longitude (coarse accuracy)	
	B 08 007	Dimensional significance	Set to missing (cancel)
	B 20 090	Special clouds	
	D 16 031	SIGMET, Observed or forecast location and motion	= 5 Clouds from volcanic eruptions
	R 01 000	Delayed replication of 1 descriptor	
	D 16 032	SIGMET, Forecast position	Set to missing (cancel)
	R 01 000	Delayed replication of 1 descriptor	
	D 16 033	SIGMET, Outlook	Set to missing (cancel)
	B 08 011	Meteorological feature	
	B 08 079	Product status	Set to missing (cancel)

(continued)

(Category 16 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 16 036	B 08 079	(Tropical cyclone SIGMET) Product status	= 0 Normal issue, = 1 Correction
	D 16 030	SIGMET header	
	B 08 011	Meteorological feature	
	B 01 027	WMO long storm name	= 22 Tropical cyclone
	D 16 031	SIGMET, Observed or forecast location and motion	
	R 01 000	Delayed replication of 1 descriptor	
	D 16 032	SIGMET, Forecast position	
	R 01 000	Delayed replication of 1 descriptor	
	D 16 033	SIGMET, Outlook	
	B 08 011	Meteorological feature	Set to missing (cancel)
	B 08 079	Product status	Set to missing (cancel)
D 16 052		(SAREP template – Part A: Information on tropical cyclone)	
	D 01 005	Originating centre/sub-centre	
	D 01 011	Year, month, day	
	D 01 012	Hour, minute	
	B 01 007	Satellite identifier	
	B 25 150	Method of tropical cyclone intensity analysis using satellite data	
	R 22 000	Delayed replication of 22 descriptors	
	B 01 027	WMO long storm name	
	B 19 150	Typhoon International Common Number (Typhoon Committee)	
	B 19 106	Identification number of tropical cyclone	
	B 08 005	Meteorological attribute significance	= 1
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 08 005	Meteorological attribute significance	Cancel
	B 19 107	Time interval over which the movement of the tropical cyclone has been calculated	
	B 19 005	Direction of motion of feature	
	B 19 006	Speed of motion of feature	
	B 19 108	Accuracy of geographical position of the tropical cyclone	
	B 19 109	Mean diameter of the overcast cloud of the tropical cyclone	
	B 19 110	Apparent 24-hour change in intensity of the tropical cyclone	
	B 19 111	Current Intensity (CI) number of the tropical cyclone	
	B 19 112	Data Tropical (DT) number of the tropical cyclone	
	B 19 113	Cloud pattern type of the DT-number	
	B 19 114	Model Expected Tropical (MET) number of the tropical cyclone	

(continued)

(Category 16 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 16 052 (continued)	B 19 115	Trend of the past 24-hour change (+: Developed, –: Weakened)	
	B 19 116	Pattern Tropical (PT) number of the tropical cyclone	
	B 19 117	Cloud picture type of the PT-number	
	B 19 118	Final Tropical (T) number of the tropical cyclone	
	B 19 119	Type of the final T-number	
D 16 061		(Definition of squall line (by centre and several points: North points and South points) and forecasted trajectory and evolution)	
	D 01 011	Year, month, day	
	D 01 012	Hour, minute	
		<i>Position of squall line centre</i>	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
	B 19 005	Direction of motion of feature	
	B 19 006	Speed of motion of feature	
		<i>Amplitude of feature from most external points to centre point – North points</i>	
	R 02 000	Delayed replication of 2 descriptors	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
		<i>Amplitude of feature from most external points to centre point – South points</i>	
	R 02 000	Delayed replication of 2 descriptors	
	B 05 002	Latitude (coarse accuracy)	
	B 06 002	Longitude (coarse accuracy)	
		<i>Amplitude of feature from most external points to centre point – Evolution</i>	
	B 04 074	Short time period or displacement	Period of validity
	B 20 048	Evolution of feature	Maximum burst expected
	B 11 041	Maximum wind gust speed	
	B 13 055	Intensity of precipitation	Intensity of rain expected

Notes:

- (1) For MOD OCNL SEV code as 12 (extreme in clear air) or 13 (extreme in cloud).
- (2) Code table values:
 - FRQ = code figure 8 (8 oktas)
 - OCNL EMBD = code figure 6 (6 oktas)
 - ISOL = code figure 2 (2 oktas) when the cloud = Cb.
- (3) Front direction (towards which the front is moving) must always be given as it is needed for plotting purposes. A front direction with a front speed of zero would indicate a slow front. A value in the code table exists to represent a quasi-stationary front.

(continued)

(Category 16 – continued)

- (4) The statistic is to determine whether the following tropopause levels are minimum, maximum or spot values (missing code value).
- (5) Decibel (dB) is a logarithmic measure of the relative power, or of the relative values of two flux densities, especially of sound intensities and radio and radar power densities. In radar meteorology, the logarithmic scale (dBZ) is used for measuring radar reflectivity factor (obtained from the American Meteorological Society *Glossary of Meteorology*).

Provisional Copy
2023

Provisional Copy
2023

Category 22 – Chemical and aerosol sequences

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 22 028	B 01 007	(METOP GOME–2) Satellite identifier	
	B 02 019	Satellite instruments	
	B 04 001	Year	
	B 04 002	Month	
	B 04 003	Day	
	B 04 004	Hour	
	B 04 005	Minute	
	B 04 006	Second	
	B 05 001	Latitude (high accuracy)	
	B 06 001	Longitude (high accuracy)	
	B 27 001	Latitude (high accuracy)	
	B 28 001	Longitude (high accuracy)	
	B 27 001	Latitude (high accuracy)	
	B 28 001	Longitude (high accuracy)	
	B 27 001	Latitude (high accuracy)	
	B 28 001	Longitude (high accuracy)	
	B 27 001	Latitude (high accuracy)	
	B 28 001	Longitude (high accuracy)	
	B 10 001	Height of land surface	
	B 14 019	Surface albedo	
	B 07 025	Solar zenith angle	
	B 10 080	Viewing zenith angle	
	B 05 023	Sun to satellite azimuth difference	
	B 20 010	Cloud cover (total)	
	B 08 003	Vertical significance (satellite observations)	
	B 07 004	Pressure	
	B 14 026	Albedo at the top of clouds	
	B 20 014	Height of top of cloud	
	B 13 093	Cloud optical thickness	
	R 05 000	Delayed replication of 5 descriptors	
	B 07 004	Pressure	
	B 07 004	Pressure	
	B 08 043	Atmospheric chemical or physical constituent type	
	B 08 044	CAS registry number	
	B 15 021	Integrated mass density	

Provisional Copy
2023

Category 35 – Monitoring information

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 35 001	B 08 035	(Specify monitoring station)	
	B 35 001	Type of monitoring exercise	
	B 08 036	Time frame for monitoring	
	D 01 001	Type of centre or station performing monitoring	
D 35 002	B 08 035	WMO block and station numbers	
	B 35 001	(Specify monitoring centre)	
	B 08 036	Type of monitoring exercise	
	B 01 033	Time frame for monitoring	
D 35 003	B 08 021	Type of centre or station performing monitoring	(23) Monitoring period
	B 04 001	Identification of originating/generating centre	
	B 04 002	(Specify monitoring period)	
	B 04 003	Time significance	
	B 04 004	Year	
	B 04 073	Month	
D 35 004	B 08 021	Day	(24) Agreed time limit for report reception
	B 04 004	Hour	
	B 08 021	Short time period or displacement	
	B 04 004	(Specify report type and single station being monitored)	
	B 08 021	Time significance	
	B 04 004	Hour	
	B 35 000	FM and regional code number	
	D 01 001	WMO block and station numbers	
D 35 005	B 35 011	Number of reports actually received	(25) Nominal reporting time
	B 08 021	(Specify report type and WMO block being monitored)	
	B 04 004	Time significance	
	B 04 004	Hour	
	B 08 021	Hour	
	B 04 004	Time significance	
	B 35 000	FM and regional code number	
	B 01 001	WMO block number	
D 35 006	B 35 011	Number of reports actually received	(24) Agreed time limit for report reception
	B 08 021	(Specify report type and WMO Region being monitored)	
	B 04 004	Time significance	
	B 08 021	Hour	
	B 04 004	Time significance	(25) Nominal reporting time
	B 08 021	Hour	

(continued)

(Category 35 – continued)

SEQUENCE	TABLE REFERENCES	ELEMENT NAME	ELEMENT DESCRIPTION
	F X Y		
D 35 006 (continued)	B 04 004	Hour	
	B 35 000	FM and regional code number	
	B 01 003	WMO Region number/geographical area	
	B 35 011	Number of reports actually received	
D 35 007		(Report type and multiple stations from one block being monitored)	(24) Agreed time limit for report reception
	B 08 021	Time significance	
	B 04 004	Hour	
	B 08 021	Time significance	
	B 04 004	Hour	(25) Nominal reporting time
	B 35 000	FM and regional code number	
	B 01 001	WMO block number	
	R 02 000	Delayed replication of 2 descriptors	
	B 01 002	WMO station number	Count of stations
	B 35 011	Number of reports actually received	
		(Monitoring a report type from multiple stations)	
	D 35 002	Specify monitoring centre	
D 35 010	D 35 003	Specify monitoring period	
	D 35 007	Report type and multiple stations from one block being monitored	

ATTACHMENT

CREX TEMPLATE EXAMPLES

PROPOSED BLOEMHOF FLOOD MONITORING CREX CODE (HYDROLOGY)

Indicator section and data description section

CREX++

T000101 A000 D05004++

Station identification

Sequence: D 01 030 consisting of

B 01 018	WMO station identifier
B 02 001	Type of station
D 01 011	Date
D 01 024	Latitude and longitude and height

Hourly environmental data

Sequence: D 05 002 consisting of

D 01 012	Time (hour, minute)
B 12 001	Air temperature
B 13 003	Relative humidity
B 14 051	Direct solar radiation during the last hour
B 13 060	Total accumulated precipitation (modulo 10 000 kg m ⁻²)
B 13 072	Downstream water level
B 13 080	pH
B 13 081	Conductivity
B 13 082	Water temperature
B 13 083	Dissolved oxygen
B 13 084	Turbidity

Multiple measurement array definition

Sequence: D 05 003 consisting of

D 01 012	Time of first measurement (hour, minute) minus increment
B 04 065	Short time increment – time interval between measurements in the array (12 minutes)
R 01 000	Delayed replication of one next descriptor (D 05 001) – Number of measurements in the array (5)
D 05 001	Single measurement

Single measurement

Sequence: D 05 001 consisting of

B 11 001	Wind direction
B 11 002	Wind speed
B 13 060	Total accumulated precipitation (modulo 10 000 kg m ⁻²)
B 13 071	Upstream water level

End of message

...++

7777

Thus the format of the message D 05 004 for the BLOEMHOF Flood Monitoring System will be:

Indicator section and data description section then:

D 01 030	Identification
D 05 002	Hourly instantaneous values
D 05 003	Array definition
n x D 05 001	Multiple measurements
++ 7777	End of message

Example

A CREX message transmitted at 1046 UTC would be the following:

```

CREX++
T000101 A000 D05004++
12345 2 1998 02 03 -2600 02800 01570
10 00 285 065 0326 03842 0683 075 2600 2805 // 0156
09 00 12 0005
290 0102 00012 1226
250 0250 00025 1230
245 0175 00028 1235
230 0105 00004 1241
220 0025 00001 1249++
7777
  
```

Note that the + at end of lines are not needed, only at the end of the whole report (in that case after 1249 – last line) and only if a whole message was to be repeated one or more times. The whole message from 12345 to 1249 is called a “subset” (See Regulation 95.4.1). The space before –2 600 is required for transmission purposes, but optional for display (to keep alignment). Fifth line, last group = delayed replication – 4 digits only = 0005.

Line 1: Message identification

Line 3:

Station number: 12345
 Station type: 2
 Date of main measurement: 3 February 1998
 Position of station: 26 degrees South, 28 degrees East, 1 570 m high

Line 4:

Time of hourly measurement: 1000 UTC
 Air temperature at 1000 UTC: 28.5 °C
 Relative humidity at 1000 UTC: 65%
 Direct solar radiation integrated over the period 0900 to 1000 UTC: 326 000 J m⁻²
 Total accumulated precipitation at 1000 UTC: 384.2 kg m⁻²
 Downstream water level at 1000 UTC: 6.83 m
 Water pH: 7.5
 Conductivity at 1000 UTC: 2.6 Siemens m⁻¹ = 26 mS cm⁻¹
 Water temperature at 1000 UTC: 280.5 K
 Dissolved oxygen at 1000 UTC: Not available
 Turbidity at 1000 UTC: 156 Lumen

Line 5: Measurement array definition

First measurement minus 12 minutes at 0900 UTC
 Interval between measurements is 12 minutes
 Number of measurements is 5

Line 6: First set of measurements at 0912 UTC

Instantaneous wind direction at 0912 UTC: 290
 Instantaneous wind speed at 0912 UTC: 10.2 m s⁻¹
 Total precipitation between 0900 and 0912 UTC: 1.2 kg m⁻²
 Upstream water level at 0912 UTC: 12.26 m

Line 7: Second set of measurements at 0924 UTC

Instantaneous wind direction at 0924 UTC: 250
 Instantaneous wind speed at 0924 UTC: 25.0 m s⁻¹
 Total precipitation between 0912 and 0924 UTC: 2.5 kg m⁻²
 Upstream water level at 0924 UTC: 12.30 m

Line 8: Third set of measurements at 0936 UTC

Instantaneous wind direction at 0936 UTC: 245
 Instantaneous wind speed at 0936 UTC: 17.5 m s⁻¹
 Total precipitation between 0912 and 0936 UTC: 2.8 kg m⁻²
 Upstream water level at 0936 UTC: 12.35 m

Line 9: Fourth set of measurements at 0948 UTC

Instantaneous wind direction at 0948 UTC: 230
 Instantaneous wind speed at 0948 UTC: 10.5 m s⁻¹
 Total precipitation between 0912 and 0948 UTC: 0.4 kg m⁻²
 Upstream water level at 0948 UTC: 12.41 m

ATTACHMENT

Line 10: Fifth set of measurements at 1000 UTC

Instantaneous wind direction at 1000 UTC: 220

Instantaneous wind speed at 1000 UTC: 2.5 m s^{-1}

Total precipitation between 0912 and 1000 UTC: 0.1 kg m^{-2}

Upstream water level at 1000 UTC: 12.49 m

Line 11: End of message identifier

TIDE GAUGE DATA EXAMPLE

CREX++

T000101 A001 D06025++

RI010 1998 01 23 15 00 2761 00 00 30 -30

01407 1225 01384 1217 01382 1221 01395 1220 01473 1262 01502 1227+

CT010 1998 01 23 15 00 2781 01 00 30 -30

02024 1757 02043 1717 02124 1728 02177 1716 ///// //// 02259 1670++

7777

Interpretation of the example:

Line	Group	Meaning
1	CREX	Indicator of a CREX message
2	T000101	CREX Master Table Number 00, Edition 01, Version 01
	A0001	Data type 001: Surface data – sea
	D 06 025	Tide elevation series
3	RI010	Tide station RI010
	1998	Year: 1998
	01	Month: January
	23	Day: 23
	15	Hour: 1500 UTC
	00	Minute: 00
	2761	Sea/water temperature: 276.1 K
	00	Tide station automated water level check: Good data
	00	Tide station manual water level check: Operational
	30	Time increment: Time is now hour 1500, minute 30
	-30	Short time increment: Increment is applied prior to each replication of two descriptors indicated by the group R 02 006, thus the time is now hour 1500, minute 00
4	01407	Tide elevation of 1 407 mm at hour 1500, minute 00
	1225	Meteorological residual tidal elevation of 1 225 mm at hour 1500, minute 00
	01384	Tide elevation of 1 384 mm at hour 1400, minute 30

ATTACHMENT

1217 Meteorological residual tidal elevation of 1 217 mm at hour 1400, minute 30
01382 Tide elevation of 1 382 mm at hour 1400, minute 00
1221 Meteorological residual tidal elevation of 1 221 mm at hour 1400, minute 00
01395 Tide elevation of 1 395 mm at hour 1300, minute 30
1220 Meteorological residual tidal elevation of 1 220 mm at hour 1300, minute 30
01473 Tide elevation of 1 473 mm at hour 1300, minute 30
1262 Meteorological residual tidal elevation of 1 262 mm at hour 1300, minute 00
01502 Tide elevation of 1 502 mm at hour 1200, minute 30
1227 Meteorological residual tidal elevation of 1 227 mm at hour 1200, minute 30
+ End of report for station RI010

5 CT010 Tide station CT010
1998 Year: 1998
01 Month: January
23 Day: 23
15 Hour: 1500 UTC
00 Minute: 00
2761 Sea/water temperature: 276.1 K
00 Tide station automated water level check: Good data
00 Tide station manual water level check: Operational
30 Time increment: Time is now hour 1500, minute 30
-30 Short time increment: Increment is applied prior to each replication of two descriptors indicated by the group R 02 006, thus the time is now hour 1500, minute 00

6 02024 Tide elevation of 2 024 mm at hour 1500, minute 00
1715 Meteorological residual tidal elevation of 1 715 mm at hour 1500, minute 00
02043 Tide elevation of 2 043 mm at hour 1400, minute 30
1717 Meteorological residual tidal elevation of 1 717 mm at hour 1400, minute 30
02124 Tide elevation of 2 124 mm at hour 1400, minute 00
1728 Meteorological residual tidal elevation of 1 728 mm at hour 1400, minute 00
02177 Tide elevation of 2 177 mm at hour 1300, minute 30
1716 Meteorological residual tidal elevation of 1 716 mm at hour 1300, minute 30
///// Tide elevation missing at hour 1300, minute 30
//// Meteorological residual tidal elevation missing at hour 1300, minute 00
02259 Tide elevation of 2 259 mm at hour 1200, minute 30
1670 Meteorological residual tidal elevation of 1 670 mm at hour 1200, minute 30
++ End of report for station CT010; also, end of Data section

7 7777 End of CREX message

**TOTAL OZONE MEASUREMENT FROM A BREWER GROUND-BASED SPECTROPHOTOMETER
OBTAINED FROM AVERAGED OBSERVATIONS**

KULD40 OKOH 041643

CREX++

T0002071500 A008002 P00089001 U00 S001 Y20110504 H0748 D07042++

11 649 Hradec Kralove 5018 01583 00285 2011 05 04 07

48 08 0526 001 98 00 00022 04 0383 09 0012 11 157++

7777

CREX

T0002071500	CREX master table		00
	CREX edition number		02
	CREX table version number		07
	BUFR Master table version number used		15
	Version number of local table		00
A008002	Data category		008
	International data subcategory		002
P00089001	Originating centre (Common Code table C-11)		00089
	Originating sub-centre (Common Code table C-12)		001
U00	Update sequence number (00 for original and delayed messages; incremented for corrected messages)		00
S001	Number of subsets included in the report		001
Y20110504	Year		2011
	Month		05
	Day		04
H0748	Hour		07
	Minute		48
D07042	D01001		
	B01001 WMO block number		11
	B01002 WMO station number		649
	B01015 Station or site name ⁽¹⁾		Hradec
Kralove			
	D01024		
	B05002 Latitude ^{(2) (3)}	50.18 deg N	5018
	B06002 Longitude ^{(2) (3)}	15.83 deg E	01583
	B07001 Height of station		00285
	D01011		
	B04001 Year (of ozone measurement)		2011
	B04002 Month (of ozone measurement)		05
	B04003 Day (of ozone measurement)		04
	D01012		
	B04004 Hour (of ozone measurement) ⁽⁴⁾		07
	B04005 Minute (of ozone measurement) ⁽⁴⁾		48
	B08021 Time significance = 8 = ensemble mean ⁽⁵⁾		08
	B04025 Time period (in minutes)		0526
	D01070		
	B02143 Ozone instrument type		001
	B02142 Ozone instrument serial number ⁽¹⁾		98^^

ATTACHMENT

B02144	Light source type for Brewer spectrophotometer ⁽⁶⁾	00
D07031		
B08022	Number of measurements	00022
B08023	First order statistic = 4 = mean value	04
B15001	Value (average) of ozone measurement	0383
B08023	First order statistic = 9 = best estimate of std deviation	09
B15001	Best estimate of std deviation of the ozone measurement	0012
B08023	First order statistic = 11 = harmonic mean	11
B15002	Harmonic mean of the air mass	157

7777

Notes:

- (1) Characters "^^^^" are used for visualization of the corresponding number of space characters.
- (2) Latitude and longitude shall be reported in degrees with precision in hundredths of a degree.
- (3) South latitude and west longitude shall be assigned negative values.
- (4) Hour and minute specify the time of the first measurement of the series.
- (5) "Ensemble mean" indicates that a number of distinct values corresponding to a set of time locations are averaged.
- (6) Ozone measurements of only one light source shall be selected, i.e. the best light source of the day.

ATTACHMENT

EXAMPLE OF AN OZONE SOUNDING COUPLED TO A BREWER SPECTROPHOTOMETER

Note: ^ means space in the definitions below

CREX++		
T000101		
A008		
D 01 001	WMO block number	71
	WMO station	913
B 01 015	Station or site name	Churchill~~~~~
D 01 024	Latitude	5875
	Longitude	-09400
	Elevation	00029
D 01 011	Year	1998
	Month	04
	Day	29
D 01 012	Hours	13
	Minutes	46
B 08 021	Time significance = 8 = ensemble mean	08
B 04 025	Time period (minutes)	0550
D 01 070	Ozone instrument type	001
	Ozone instrument serial number (Brewer)	26^
	Light source type for Brewer (direct sun)	00
B 08 022	Number of measurements	00010
B 08 023	First order statistics = 4 = mean value	04
B 15 001	Value of ozone measurement	0399
B 08 023	First order statistics = 9 = best estimate of standard deviation	09
B 15 001	Best estimate of standard deviation	0010
B 08 023	First order statistics = harmonic mean	11
B 15 002	Harmonic mean of the air mass	202
D 01 001	WMO block and station number	71
		913
B 01 015	Station or site name	Churchill~~~~~
D 01 024	Latitude	5875
	Longitude	-09400
	Elevation	00029
B 08 021	18 = launch time follows	18
D 01 011	Year	1998
	Month	04
	Day	29
D 01 012	Hours	11
	Minutes	22
B 02 011	Radiosonde type	061
B 02 143	Ozone instrument type	019
B 02 142	Ozone sonde serial number	////
D 15 004	Ozone sounding correction factor	0893
D 15 005	Ozone p	373

ATTACHMENT

R 04 000	Delayed replication factor = number of levels	0093
	The next four descriptors are repeated 93 times	
B 04 025	Time displacement since launch time (minutes)	See below
B 08 006	Ozone VSS	See below
B 07 004	Pressure	See below
B 15 003	Measured ozone partial pressure	See below
++		
7777	End of message	

KULA01 CWA0 051800

CREX++

T000101 A008 D09047++

71 913 CHURCHILL 5875 -09400 00029 1998 04 29 13 46
08 0550 001 26 00 00010 04 0399 09 0010 11 202
71 913 CHURCHILL 5875 -09400 00029 18 1998 04 29 11 22
061 019 //// 0893 373 0093
0000 400 10041 029 0000 200 10000 029 0000 002 09915 031
0001 002 09735 036 0001 002 09678 038 0002 002 09273 038
0003 002 09111 039 0004 200 08500 039 0009 200 07000 037
0011 002 06450 037 0012 002 06279 036 0012 002 06159 031
0014 002 05847 034 0016 002 05347 030 0016 002 05269 029
0017 002 05100 040 0018 200 05000 034 0019 002 04821 030
0023 200 04000 030 0027 002 03400 026 0029 002 03000 028
0031 002 02857 029 0031 002 02818 024 0032 002 02743 017
0034 200 02500 015 0036 002 02225 014 0038 002 02078 029
0038 002 02049 036 0039 200 02000 066 0039 002 01992 066
0039 002 01952 093 0040 002 01909 105 0040 002 01866 105
0041 002 01800 115 0042 002 01765 103 0042 002 01741 100
0043 002 01693 112 0043 002 01656 112 0044 002 01612 109
0044 002 01590 092 0044 002 01580 066 0045 002 01559 052
0045 002 01517 049 0046 002 01500 059 0046 002 01488 070
0046 002 01469 098 0047 002 01440 107 0047 002 01391 107
0048 002 01335 117 0049 002 01291 162 0050 002 01257 153
0051 002 01206 155 0051 002 01190 141 0051 002 01182 141
0052 002 01142 156 0053 002 01103 154 0054 002 01059 177
0055 002 01005 170 0056 200 01000 178 0056 002 00978 197
0057 002 00951 187 0058 002 00914 183 0058 002 00889 171
0059 002 00866 182 0059 002 00855 195 0060 002 00837 198
0061 002 00808 175 0061 002 00797 172 0064 200 00700 160
0065 002 00671 157 0067 002 00630 142 0068 002 00592 153

ATTACHMENT

0068 002 00583 162 0070 002 00531 157 0072 002 00501 164
 0072 200 00500 161 0073 002 00479 162 0073 002 00462 151
 0075 002 00435 156 0076 002 00418 153 0078 002 00378 161
 0081 002 00319 132 0082 002 00311 136 0083 200 00300 130
 0086 002 00258 111 0091 200 00200 095 0097 002 00143 079
 0099 002 00126 078 0103 200 00100 071 0110 200 00070 058
 0115 002 00054 044 0116 200 00050 039 0120 002 00043 032++

7777

EXAMPLE OF AN OZONE SOUNDING NOT COUPLED TO A BREWER SPECTROPHOTOMETER

CREX++

T000101

A008

D 01 001	WMO station and block number	71
		917
B 01 015	Station or site name	Eureka~~~~~
D 01 024	Latitude	7598
	Longitude	-08593
	Elevation	00010
B 08 021	18 = launch time follows	18
D 01 011	Year	1998
	Month	04
	Day	29
D 01 012	Hours	23
	Minutes	18
B 02 011	Radiosonde type	061
B 02 143	Ozone instrument type	019
B 02 142	Ozone sonde serial number	////
D 15 004	Ozone sounding correction factor	////
D 15 005	Ozone p	375
R 04 000	Delayed replication factor = number of levels	0082
	The next four descriptors are repeated 82 times	
B 04 025	Time displacement since launch time (minutes)	See below
B 08 006	Ozone VSS	See below
B 07 004	Pressure	See below
B 15 003	Measured ozone partial pressure	See below
++		
7777	End of message	

ATTACHMENT

KULA01 CWA0 051800

CREX++

T000101 A008 D09045++

71 917 EUREKA 7598 -08593 00010 18 1998 04 29 23 18

061 019 //// //// 375 0082

0000 400 10137 030 0000 200 10000 030 0001 002 09687 037

0002 002 09366 033 0004 002 08831 037 0005 200 08500 036

0007 002 08013 043 0007 002 07881 047 0008 002 07646 037

0009 002 07442 042 0011 200 07000 031 0012 002 06849 027

0013 002 06710 036 0015 002 06291 029 0022 200 05000 028

0025 002 04557 027 0029 002 04065 024 0029 200 04000 020

0032 002 03626 025 0038 002 03000 020 0040 002 02890 021

0040 002 02829 065 0041 002 02726 105 0043 002 02576 118

0044 200 02500 135 0048 002 02218 165 0049 002 02147 161

0050 002 02104 171 0051 002 02031 153 0051 002 02010 159

0051 200 02000 171 0052 002 01941 188 0054 002 01854 198

0056 002 01744 187 0056 002 01717 194 0057 002 01683 191

0058 002 01640 161 0058 002 01623 159 0059 002 01585 168

0059 002 01576 185 0060 002 01545 197 0061 002 01500 202

0063 002 01414 221 0064 002 01370 220 0065 002 01335 230

0066 002 01269 219 0067 002 01232 227 0067 002 01226 235

0068 002 01208 241 0072 002 01055 242 0074 200 01000 236

0075 002 00960 228 0076 002 00936 192 0077 002 00912 180

0078 002 00897 187 0078 002 00883 210 0079 002 00868 221

0079 002 00850 202 0080 002 00841 199 0081 002 00815 208

0081 002 00807 189 0081 002 00803 171 0082 002 00790 152

0082 002 00777 157 0083 002 00764 172 0084 002 00741 156

0084 002 00722 156 0085 002 00715 162 0085 200 00700 188

0085 200 00700 193 0086 002 00682 203 0088 002 00639 212

0090 002 00608 206 0091 002 00588 190 0091 002 00582 192

0092 002 00570 209 0092 002 00557 215 0096 200 00500 197

0099 002 00437 171 0108 002 00316 139 0110 200 00300 128

0115 002 00242 108++

7777

ATTACHMENT

SAMPLE DATA WITH CREX SEQUENCE FOR EXCHANGE OF FORECAST RESULT ON
TROPICAL CYCLONES

Descriptor	Order No.	Sample data	Corresponding meaning	Unit	Scale	Data width
B 01 033	1	034	Originating Centre = RSMC Tokyo	Code table	0	3
B 01 025	2	21W	Storm identifier	Character	0	3
B 01 027	3	ZANE	WMO storm name	Character	0	10
D 01 011			(sequence descriptor)			
B 04 001	4	1996	Year	Year	0	4
B 04 002	5	10	October	Month	0	2
B 04 003	6	01	1st	Day	0	2
D 01 012			(sequence descriptor)			
B 04 004	7	06	6 o'clock (UTC)	Hour	0	2
B 04 005	8	00	0 minute (UTC)	Minute	0	2
B 01 032	9	XXX	(to be defined)			
			Identification of NWP model	Code table	0	3
B 02 041	0	01	Based on computer analysis	Code table	0	2
B 19 001	1	02	Tropical storm	Code table	0	2
B 19 010	2	01	Minimum value of sea-level pressure	Code table	0	2
R 18 000	3	0003	(**delayed replication descriptor**)	Numeric	0	4
			Data for 3 forecast times of 18 descriptors follow			
B 08 021	4	04	Forecast data follow	Code table	0	2
B 04 014	5	0012	12 hour forecast data follow	Hour	0	4
B 08 005	6	01	Data of storm centre follow	Code table	0	2
D 01 023			(sequence descriptor)			
B 05 002	7	3010	Latitude of the storm centre is 30.1N	Degree	2	4
B 06 002	8	14200	Longitude of the storm centre is 142.0E	Degree	2	5
B 19 005	9	270	Direction of motion of storm is 270	Degree true	0	3
B 19 006	0	00500	Speed of motion of storm is 5 m s ⁻¹	m s ⁻¹	2	5
B 10 004	1	09750	Pressure of storm centre is 975 hPa	Pa	-1	5
B 11 041	2	0576	Gust wind speed is 57.6 m s ⁻¹	m s ⁻¹	1	4
B 08 021	3	06	Forecast time averaged follow	Code table	0	2
B 04 075	4	10	10 minutes mean value follow	Minute	0	2
B 11 040	5	0360	Maximum wind speed is 36.0 m s ⁻¹	m s ⁻¹	1	4
B 19 008	6	2	Storm depth is medium	Code table	0	1
R 05 004			*** (replication descriptor)			
			4 times replication of following 5 descriptors			
B 05 021	7	31500	Sector 1 (from 315 degrees	Degree true	2	5
B 05 021	8	04500	to 45 degrees)	Degree true	2	5
R 02 002			*** (replication descriptor)			
			2 times replication of following 2 descriptors			
B 19 003	9	025	Wind speed threshold is 25 m s ⁻¹	m s ⁻¹	0	3
B 19 004	0	1950	Effective radius is 195 km	m	-2	4

ATTACHMENT

Descriptor	Order No.	Sample data	Corresponding meaning
	1	015	Wind speed threshold is 15 m s ⁻¹
	2	4000	Effective radius is 400 km
	3	04500	Sector 2 (from 45 degrees to 135 degrees)
	4	13500	
	5	025	Wind speed threshold is 25 m s ⁻¹
	6	1950	Effective radius is 195 km
	7	015	Wind speed threshold is 15 m s ⁻¹
	8	4300	Effective radius is 430 km
	9	13500	Sector 3 (from 135 degrees to 225 degrees)
	0	22500	
	1	025	Wind speed threshold is 25 m s ⁻¹
	2	1950	Effective radius is 195 km
	3	015	Wind speed threshold is 15 m s ⁻¹
	4	6090	Effective radius is 609 km
	5	22500	Sector 4 (from 225 degrees to 315 degrees)
	6	31500	
	7	025	Wind speed threshold is 25 m s ⁻¹
	8	1950	Effective radius is 195 km
	9	015	Wind speed threshold is 15 m s ⁻¹
	0	4700	Effective radius is 470 km
	1	04	(24- and 36-hour forecast data follow as same as the second fourth order above)
		

CREX MESSAGE COMPOSED OF ABOVE DATA ELEMENTS:

CREX++

T000101 A007 B01033 B01025 B01027 D01011 D01012 B01032 B02041 B19001 B19010 R18000 B08021 B04014 B08005 D01023 B19005 B19006 B10004 B11041 B08021 B04075 B11040 B19008 R05004 B05021 B05021 R02002 B19003 B19004E++
0034 121W 2ZANE 31996 410 501 606 700 8XXX 901 002 101 20003 304 40012 501 63010 714200 8270 900500 009750 10576 206 310 40360 52 631500 704500 8025 91950 0015 14000 204500 313500 4025 51950 6015 74300 813500 922500 0025 11950 2015 36090 422500 531500 6025 71950 8015 94700 004++
7777

or (with big common sequence definition)

CREX++

T000101 A007 D16027E++
0034 121W 2ZANE 31996 410 501 606 700 8XXX 901 002 101 20003 304 40012 501 63010 714200 8270 900500 009750 10576 206 310 40360 52 631500 704500 8025 91950 0015 14000 204500 313500 4025 51950 6015 74300 813500 922500 0025 11950 2015 36090 422500 531500 6025 71950 8015 94700 004++
7777

or without check digit:

CREX++

T000101 A007 D16027++
034 21W ZANE 1996 10 01 06 00 XXX 01 02 01 0003 04 0012 01 3010 14200 270 00500 09750 0576 06 10 0360 2 31500 04500 025 1950 015 4000 04500 13500 025 1950 015 4300 13500 22500 025 1950 015 6090 22500 31500 025 1950 015 4700 04++
7777

ATTACHMENT

MONITORING INFORMATION SAMPLE MESSAGE

CREX++ (indicator section)
T000101 A020 D35010++ (description section)
1 2 4 014 23 1996 10 01 00 15 24 06 25 00 012 63 0003 740 0360 894 0353
792 0125++ (data section)
7777 (end section)

1 Regional exercise
2 Non-real time
4 RTH
014 Nairobi
23 Monitoring period follows
1996 YYYY
10 MM
01 DD
00 HH
15 Days duration
24 Data cut-off follows
06 Hours
25 Report time follows
00 Hours
012 SYNOP
63 Block number
0003 Stations
740 Nairobi
0360 Well done
894 Dar es Salaam
0353 Very good
792 A station
0125 Must do better!
++
7777

c. COMMON CODE TABLES TO BINARY AND ALPHANUMERIC CODES

COMMON CODE TABLE C-0: *GRIB, BUFR and CREX master table version number*

Octet 10 in Section 1 of GRIB Edition 2
Octet 14 in Section 1 of BUFR Edition 4
vv and bb in Group No. 1 in Section 1 of CREX Edition 2

COMMON CODE TABLE C-1: *Identification of originating/generating centre*

F₁F₂ for alphanumeric codes
F₃F₃F₃ for alphanumeric codes
Code table 0 in GRIB Edition 1/Code table 0 01 033 in BUFR
Octet 5 in Section 1 of GRIB Edition 1/Octet 6 in Section 1 of BUFR Edition 3

COMMON CODE TABLE C-2: *Radiosonde/sounding system used*

Code table 3685 – r_ar_a (Radiosonde/sounding system used) – for alphanumeric codes
Code table 0 02 011 (Radiosonde type) in BUFR

COMMON CODE TABLE C-3: *Instrument make and type for water temperature profile measurement with fall rate equation coefficients*

Code table 1770 – I_xI_xI_x (Instrument type for XBT, with fall rate equation coefficients) – for alphanumeric codes
Code table 0 22 067 (Instrument type for water temperature/salinity profile measurement) in BUFR

COMMON CODE TABLE C-4: *Water temperature profile recorder types*

Code table 4770 – X_RX_R (Recorder type) – for alphanumeric codes
Code table 0 22 068 (Water temperature profile recorder types) in BUFR

COMMON CODE TABLE C-5: *Satellite identifier*

I₆I₆I₆ for alphanumeric codes
Code table 0 01 007 in BUFR
Code used in GRIB Edition 2

COMMON CODE TABLE C-6: *List of units for TDCFs*

(Used only in Volume I.2, Parts B and C)

COMMON CODE TABLES

COMMON CODE TABLE C-7: *Tracking technique/status of system used*

Code table 3872 – s_as_a for alphanumeric code
Code table 0 02 014 in BUFR

COMMON CODE TABLE C-8: *Satellite Instruments*

Code table 0 02 019 in BUFR

COMMON CODE TABLE C-11: *Originating/generating centres*

BUFR 0 01 035
CREX Edition 2, ooooo in Group Poooooppp in Section 1
GRIB Edition 2, Octets 6-7 in Section 1
BUFR Edition 4, Octets 5-6 in Section 1

COMMON CODE TABLE C-12: *Sub-centres of originating centres defined by entries in Common Code tables C-1 or C-11*

BUFR 0 01 034
BUFR Edition 3, Octet 5 in Section 1
BUFR Edition 4, Octets 7-8 in Section 1
GRIB Edition 1, Octet 26 in Section 1
GRIB Edition 2, Octets 8-9 in Section 1
CREX Edition 2, ppp in Group Poooooppp in Section 1

COMMON CODE TABLE C-13: *Data sub-categories of categories defined by entries in BUFR Table A*

BUFR Edition 4, Octet 12 in Section 1 (if = 255, it means other sub-category or undefined)
CREX Edition 2, mmm in Group Annnmmm of Section 1

COMMON CODE TABLE C-14: *Atmospheric chemical or physical constituent type*

Code Table 4.230 in GRIB 2
Code table 0 08 046 in BUFR

COMMON CODE TABLES

COMMON CODE TABLE C-0: GRIB, BUFR and CREX master table version number

Common Code table { Octet 10 in Section 1 of GRIB Edition 2
Octet 14 in Section 1 of BUFR Edition 4
vv and bb in Group No. 1 in Section 1 of CREX Edition 2

<i>Common code table C-0</i>			
GRIB	Version number		Effective date
	BUFR	CREX	
0	0	0	Experimental
	1		1 November 1988
	2		1 November 1993
	3		2 November 1994
	4		8 November 1995
	5		6 November 1996
	6		5 November 1997
	7		4 November 1998
	8	1	3 May 2000
	9		8 November 2000
1	10	2	7 November 2001
2	11	3	5 November 2003
3	12	4	2 November 2005
4	13	5	7 November 2007
5	14	6	4 November 2009
6	15	7	15 September 2010
7	16	16	4 May 2011
8	17	17	2 November 2011
9	18	18	2 May 2012
10	19	19	7 November 2012
11	20	20	8 May 2013
12	21	21	14 November 2013
13	22	22	7 May 2014
14	23	23	5 November 2014
15	24	24	6 May 2015
16	25	25	11 November 2015
17	26	26	4 May 2016
18	27	27	2 November 2016
19	28	28	3 May 2017
20	29	29	8 November 2017
21	30	30	2 May 2018
22	31	31	7 November 2018
23	32	32	15 May 2019
24	33	33	6 November 2019
25	34	34	6 May 2020
26	35	35	16 November 2020

COMMON CODE TABLES

Common code table C-0			
GRIB	Version number		Effective date
	BUFR	CREX	
27	36	36	15 June 2021
28	37	37	15 November 2021
29	38	38	15 May 2022
<u>30</u>	<u>39</u>	<u>39</u>	<u>15 November 2022</u>
<u>31</u>	<u>40</u>	<u>40</u>	<u>15 May 2023</u>
32 0-254	41 <u>39</u> -254	39 <u>41</u> -254	Future versions
255	255	255	Missing

Notes:

- (1) Introduction of Common Code table C-0 is a legal initiative. WMO Members and other TDCF users could practically deal with the version numbers the same as before until their software becomes capable of referring to the common code table.
- (2) CREX master table version numbers 8-15 are not used.
- (3) In the case of BUFR and CREX, these version numbers apply to the master table 0.

COMMON CODE TABLES

COMMON CODE TABLE C–1: Identification of originating/generating centre

Common Code table { F_1F_2 for alphanumeric codes
 $F_3F_3F_3$ for alphanumeric codes
Code table 0 in GRIB Edition 1/Code table 0 01 033 in BUFR
Octet 5 in Section 1 of GRIB Edition 1/Octet 6 in Section 1 of BUFR Edition 3

Common code table C–1			
Code figure for F_1F_2	Code figure for $F_3F_3F_3$	Octet 5 in Section 1 of GRIB Edition 1 Octet 6 in Section 1 of BUFR Edition 3	
00	000	0	WMO Secretariat
01–09: WMCs			
01	001	1	Melbourne
02	002	2	Melbourne
03	003	3)
04	004	4	Moscow
05	005	5	Moscow
06	006	6)
07	007	7	US National Weather Service – National Centres for Environmental Prediction (NCEP)
08	008	8	US National Weather Service Telecommunications Gateway (NWSGTG)
09	009	9	US National Weather Service – Other
10–25: Centres in Region I			
10	010	10	Cairo (RSMC)
11	011	11)
12	012	12	Dakar (RSMC)
13	013	13)
14	014	14	Nairobi (RSMC)
15	015	15)
16	016	16	Casablanca (RSMC)
17	017	17	Tunis (RSMC)
18	018	18	Tunis – Casablanca (RSMC)
19	019	19)
20	020	20	Las Palmas
21	021	21	Algiers (RSMC)
22	022	22	ACMAD
23	023	23	Mozambique (NMC)
24	024	24	Pretoria (RSMC)
25	025	25	La Réunion (RSMC)
26–40: Centres in Region II			
26	026	26	Khabarovsk (RSMC)
27	027	27)
28	028	28	New Delhi (RSMC)

COMMON CODE TABLES

Common code table C-1			
Code figure for F ₁ F ₂	Code figure for F ₃ F ₃ F ₃	Octet 5 in Section 1 of GRIB Edition 1 Octet 6 in Section 1 of BUFR Edition 3	
29	029	29)
30	030	30	Novosibirsk (RSMC)
31	031	31)
32	032	32	Tashkent (RSMC)
33	033	33	Jeddah (RSMC)
34	034	34	Tokyo (RSMC), Japan Meteorological Agency
35	035	35)
36	036	36	Bangkok
37	037	37	Ulaanbaatar
38	038	38	Beijing (RSMC)
39	039	39)
40	040	40	Seoul
41–50: Centres in Region III			
41	041	41	Buenos Aires (RSMC)
42	042	42)
43	043	43	Brasilia (RSMC)
44	044	44)
45	045	45	Santiago
46	046	46	Brazilian Space Agency - INPE
47	047	47	Colombia (NMC)
48	048	48	Ecuador (NMC)
49	049	49	Peru (NMC)
50	050	50	Venezuela (Bolivarian Republic of) (NMC)
51–63: Centres in Region IV			
51	051	51	Miami (RSMC)
52	052	52	Miami (RSMC), National Hurricane Centre
53	053	53	MSC Monitoring
54	054	54	Montreal (RSMC)
55	055	55	San Francisco
56	056	56	ARINC Centre
57	057	57	US Air Force – Air Force Global Weather Central
58	058	58	Fleet Numerical Meteorology and Oceanography Center, Monterey, CA, United States
59	059	59	The NOAA Forecast Systems Laboratory, Boulder, CO, United States
60	060	60	United States National Center for Atmospheric Research(NCAR)
61	061	61	Service ARGOS – Landover
62	062	62	US Naval Oceanographic Office
63	063	63	International Research Institute for Climate and Society (IRI)

COMMON CODE TABLES

Common code table C-1			
Code figure for F ₁ F ₂	Code figure for F ₃ F ₃ F ₃	Octet 5 in Section 1 of GRIB Edition 1 Octet 6 in Section 1 of BUFR Edition 3	
64–73: Centres in Region V			
64	064	64	Honolulu (RSMC)
65	065	65	Darwin (RSMC)
66	066	66)
67	067	67	Melbourne (RSMC)
68	068	68	Reserved
69	069	69	Wellington (RSMC)
70	070	70)
71	071	71	Nadi (RSMC)
72	072	72	Singapore
73	073	73	Malaysia (NMC)
74–99: Centres in Region VI			
74	074	74	UK Meteorological Office - Exeter (RSMC)
75	075	75)
76	076	76	Moscow (RSMC)
77	077	77	Reserved
78	078	78	Offenbach (RSMC)
79	079	79)
80	080	80	Rome (RSMC)
81	081	81)
82	082	82	Norrköping
83	083	83)
84	084	84	Toulouse (RSMC)
85	085	85	Toulouse (RSMC)
86	086	86	Helsinki
87	087	87	Belgrade
88	088	88	Oslo
89	089	89	Prague
90	090	90	Episkopi
91	091	91	Ankara
92	092	92	Frankfurt/Main
93	093	93	London (WAFC)
94	094	94	Copenhagen
95	095	95	Rota
96	096	96	Athens
97	097	97	European Space Agency (ESA)
98	098	98	European Centre for Medium-Range Weather Forecasts (ECMWF) (RSMC)
99	099	99	De Bilt
Additional Centres			
Not applicable	100	100	Brazzaville
Not applicable	101	101	Abidjan
Not applicable	102	102	Libya (NMC)

COMMON CODE TABLES

<i>Common code table C-1</i>			
Code figure for F ₁ F ₂	Code figure for F ₃ F ₃ F ₃	Octet 5 in Section 1 of GRIB Edition 1 Octet 6 in Section 1 of BUFR Edition 3	
Not applicable	103	103	Madagascar (NMC)
Not applicable	104	104	Mauritius (NMC)
Not applicable	105	105	Niger (NMC)
Not applicable	106	106	Seychelles (NMC)
Not applicable	107	107	Uganda (NMC)
Not applicable	108	108	United Republic of Tanzania (NMC)
Not applicable	109	109	Zimbabwe (NMC)
Not applicable	110	110	Hong-Kong, China
Not applicable	111	111	Afghanistan (NMC)
Not applicable	112	112	Bahrain (NMC)
Not applicable	113	113	Bangladesh (NMC)
Not applicable	114	114	Bhutan (NMC)
Not applicable	115	115	Cambodia (NMC)
Not applicable	116	116	Democratic People's Republic of Korea (NMC)
Not applicable	117	117	Islamic Republic of Iran (NMC)
Not applicable	118	118	Iraq (NMC)
Not applicable	119	119	Kazakhstan (NMC)
Not applicable	120	120	Kuwait (NMC)
Not applicable	121	121	Kyrgyzstan (NMC)
Not applicable	122	122	Lao People's Democratic Republic (NMC)
Not applicable	123	123	Macao, China
Not applicable	124	124	Maldives (NMC)
Not applicable	125	125	Myanmar (NMC)
Not applicable	126	126	Nepal (NMC)
Not applicable	127	127	Oman (NMC)
Not applicable	128	128	Pakistan (NMC)
Not applicable	129	129	Qatar (NMC)
Not applicable	130	130	Yemen (NMC)
Not applicable	131	131	Sri Lanka (NMC)
Not applicable	132	132	Tajikistan (NMC)
Not applicable	133	133	Turkmenistan (NMC)
Not applicable	134	134	United Arab Emirates (NMC)
Not applicable	135	135	Uzbekistan (NMC)
Not applicable	136	136	Viet Nam (NMC)
Not applicable	137-139	137-139	Reserved for other centres
Not applicable	140	140	Bolivia (Plurinational State of) (NMC)
Not applicable	141	141	Guyana (NMC)
Not applicable	142	142	Paraguay (NMC)
Not applicable	143	143	Suriname (NMC)
Not applicable	144	144	Uruguay (NMC)
Not applicable	145	145	French Guiana
Not applicable	146	146	Brazilian Navy Hydrographic Centre
Not applicable	147	147	National Commission on Space Activities (CONAE) – Argentina
Not applicable	148	148	Brazilian Department of Airspace Control – DECEA

COMMON CODE TABLES

<i>Common code table C-1</i>			
Code figure for F ₁ F ₂	Code figure for F ₃ F ₃ F ₃	Octet 5 in Section 1 of GRIB Edition 1 Octet 6 in Section 1 of BUFR Edition 3	
Not applicable	149	149	Reserved for other centres
Not applicable	150	150	Antigua and Barbuda (NMC)
Not applicable	151	151	Bahamas (NMC)
Not applicable	152	152	Barbados (NMC)
Not applicable	153	153	Belize (NMC)
Not applicable	154	154	British Caribbean Territories Centre
Not applicable	155	155	San José
Not applicable	156	156	Cuba (NMC)
Not applicable	157	157	Dominica (NMC)
Not applicable	158	158	Dominican Republic (NMC)
Not applicable	159	159	El Salvador (NMC)
Not applicable	160	160	US NOAA/NESDIS
Not applicable	161	161	US NOAA Office of Oceanic and Atmospheric Research
Not applicable	162	162	Guatemala (NMC)
Not applicable	163	163	Haiti (NMC)
Not applicable	164	164	Honduras (NMC)
Not applicable	165	165	Jamaica (NMC)
Not applicable	166	166	Mexico City
Not applicable	167	167	Curaçao and Sint Maarten (NMC)
Not applicable	168	168	Nicaragua (NMC)
Not applicable	169	169	Panama (NMC)
Not applicable	170	170	Saint Lucia (NMC)
Not applicable	171	171	Trinidad and Tobago (NMC)
Not applicable	172	172	French Departments in RA IV
Not applicable	173	173	US National Aeronautics and Space Administration (NASA)
Not applicable	174	174	Integrated Science Data Management/Marine Environmental Data Service (ISDM/MEDS) – Canada
Not applicable	175	175	University Corporation for Atmospheric Research (UCAR) – United States
Not applicable	176	176	Cooperative Institute for Meteorological Satellite Studies(CIMSS) – United States
Not applicable	177	177	NOAA National Ocean Service – United States
Not applicable	178	178	Spire Global, Inc.
Not applicable	179	179	GeoOptics, Inc.
Not applicable	180	180	PlanetiQ
Not applicable	181–189	181–189	Reserved for other centres
Not applicable	190	190	Cook Islands (NMC)
Not applicable	191	191	French Polynesia (NMC)
Not applicable	192	192	Tonga (NMC)
Not applicable	193	193	Vanuatu (NMC)
Not applicable	194	194	Brunei Darussalam (NMC)
Not applicable	195	195	Indonesia (NMC)
Not applicable	196	196	Kiribati (NMC)
Not applicable	197	197	Federated States of Micronesia (NMC)

COMMON CODE TABLES

Common code table C-1

Code figure for F ₁ F ₂	Code figure for F ₃ F ₃ F ₃	Octet 5 in Section 1 of GRIB Edition 1 Octet 6 in Section 1 of BUFR Edition 3	
Not applicable	198	198	New Caledonia (NMC)
Not applicable	199	199	Niue
Not applicable	200	200	Papua New Guinea (NMC)
Not applicable	201	201	Philippines (NMC)
Not applicable	202	202	Samoa (NMC)
Not applicable	203	203	Solomon Islands (NMC)
Not applicable	204	204	National Institute of Water and Atmospheric Research(NIWA – New Zealand)
Not applicable	205–209	205–209	Reserved
Not applicable	210	210	Frascati (ESA/ESRIN)
Not applicable	211	211	Lannion
Not applicable	212	212	Lisbon
Not applicable	213	213	Reykjavik
Not applicable	214	214	Madrid
Not applicable	215	215	Zurich
Not applicable	216	216	Service ARGOS – Toulouse
Not applicable	217	217	Bratislava
Not applicable	218	218	Budapest
Not applicable	219	219	Ljubljana
Not applicable	220	220	Warsaw
Not applicable	221	221	Zagreb
Not applicable	222	222	Albania (NMC)
Not applicable	223	223	Armenia (NMC)
Not applicable	224	224	Austria (NMC)
Not applicable	225	225	Azerbaijan (NMC)
Not applicable	226	226	Belarus (NMC)
Not applicable	227	227	Belgium (NMC)
Not applicable	228	228	Bosnia and Herzegovina (NMC)
Not applicable	229	229	Bulgaria (NMC)
Not applicable	230	230	Cyprus (NMC)
Not applicable	231	231	Estonia (NMC)
Not applicable	232	232	Georgia (NMC)
Not applicable	233	233	Dublin
Not applicable	234	234	Israel (NMC)
Not applicable	235	235	Jordan (NMC)
Not applicable	236	236	Latvia (NMC)
Not applicable	237	237	Lebanon (NMC)
Not applicable	238	238	Lithuania (NMC)
Not applicable	239	239	Luxembourg
Not applicable	240	240	Malta (NMC)
Not applicable	241	241	Monaco
Not applicable	242	242	Romania (NMC)
Not applicable	243	243	Syrian Arab Republic (NMC)
Not applicable	244	244	North Macedonia (NMC)
Not applicable	245	245	Ukraine (NMC)

COMMON CODE TABLES

Common code table C-1

Code figure for F ₁ F ₂	Code figure for F ₃ F ₃ F ₃	Octet 5 in Section 1 of GRIB Edition 1 Octet 6 in Section 1 of BUFR Edition 3	
Not applicable	246	246	Republic of Moldova (NMC)
Not applicable	247	247	Operational Programme for the Exchange of weather RADar information (OPERA) – EUMETNET
Not applicable	248	248	Montenegro (NMC)
Not applicable	249	249	Barcelona Dust Forecast Center
Not applicable	250	250	COnsortium for Small scale MOdelling (COSMO)
Not applicable	251	251	Meteorological Cooperation on Operational NWP (MetCoOp)
Not applicable	252	252	Max Planck Institute for Meteorology (MPI-M)
Not applicable	253	253	Reserved for other centres
Not applicable	254	254	EUMETSAT Operation Centre
Not applicable	255	255	Missing value
Not applicable	256–999	Not applicable	Not used

Notes:

- (1) The closed bracket sign) indicates that the corresponding code figure is reserved for the previously named centre.
- (2) With GRIB or BUFR, to indicate whether the originating/generating centre is a sub-centre or not, the following procedure should be applied:
In GRIB edition 1, use octet 26 of section 1, or in BUFR edition 3, use octet 5 of section 1, with the following meaning:
Code figure

0	Not a sub-centre, the originating/generating centre is the centre defined by Octet 5 in section 1 of GRIB Edition 1, or by octet 6 in section 1 of BUFR edition 3.
1 to 254	Identifier of the sub-centre which is the originating/generating centre. The identifier of the sub-centre is allocated by the associated centre which is defined by octet 5 in section 1 of GRIB edition 1, or octet 6 in section 1 of BUFR edition 3. The sub-centre identifiers should be supplied to the WMO Secretariat by the associated centre(s) for publication.
- (3) For the definitions of sub-centres provided to the WMO Secretariat, see Common Code table C-12.

COMMON CODE TABLES

COMMON CODE TABLE C-2: Radiosonde/sounding system used

Common Code table { Code table 3685 – r_ar_a (Radiosonde/sounding system used) –
for alphanumeric codes
Code table 0 02 011 (Radiosonde type) in BUFR

Common code table C-2			
Date of assignment of number (necessary after 30/06/2007)	Code figure for r _a r _a (Code table 3685)	Code figure for BUFR (Code table 0 02 011)	
Not applicable	00	0	Reserved
Before	01	1	iMet-1-BB (United States)
Not applicable	02	2	No radiosonde – passive target (e.g. reflector)
Not applicable	03	3	No radiosonde – active target (e.g. transponder)
Not applicable	04	4	No radiosonde – passive temperature-humidity profiler
Not applicable	05	5	No radiosonde – active temperature-humidity profiler
Not applicable	06	6	No radiosonde – radio-acoustic sounder
Before	07	7	iMet-1-AB (United States)
Not applicable	08	8	No radiosonde –... (reserved)
Not applicable	09	9	No radiosonde – system unknown or not specified
Before	10	10	VIZ type A pressure-commutated (United States)
Before	11	11	VIZ type B time-commutated (United States)
Before	12	12	RS SDC (Space Data Corporation – United States)
Before	13	13	Astor (no longer made – Australia)
Before	14	14	VIZ MARK I MICROSONDE (United States)
Before	15	15	EEC Company type 23 (United States)
Before	16	16	Elin (Austria)
Before	17	17	Graw G. (Germany)
Before	18	18	Graw DFM-06 (Germany)
Before	19	19	Graw M60 (Germany)
Before	20	20	Indian Meteorological Service MK3 (India)
Before	21	21	VIZ/Jin Yang MARK I MICROSONDE (Republic of Korea)
Before	22	22	Meisei RS2-80 (Japan)
Before	23	23	Mesural FMO 1950A (France)
Before	24	24	Mesural FMO 1945A (France)
Before	25	25	Mesural MH73A (France)
Before	26	26	Meteolabor Basora (Switzerland)
Before	27	27	AVK-MRZ (Russian Federation)
Before	28	28	Meteorit MARZ2-1 (Russian Federation)
Before	29	29	Meteorit MARZ2-2 (Russian Federation)

COMMON CODE TABLES

<i>Common code table C-2</i>			
Date of assignment of number (necessary after 30/06/2007)	Code figure for raRa (Code table 3685)	Code figure for BUFR (Code table 0 02 011)	
Before	30	30	Oki RS2-80 (Japan)
Before	31	31	VIZ/Valcom type A pressure-commutated (Canada)
Before	32	32	Shanghai Radio (China)
Before	33	33	UK Met Office MK3 (UK)
Before	34	34	Vinohrady (Czechia)
Before	35	35	Vaisala RS18 (Finland)
Before	36	36	Vaisala RS21 (Finland)
Before	37	37	Vaisala RS80 (Finland)
Before	38	38	VIZ LOCATE Loran-C (United States)
Before	39	39	Sprenger E076 (Germany)
Before	40	40	Sprenger E084 (Germany)
Before	41	41	Sprenger E085 (Germany)
Before	42	42	Sprenger E086 (Germany)
Before	43	43	AIR IS - 4A - 1680 (United States)
Before	44	44	AIR IS - 4A - 1680 X (United States)
Before	45	45	RS MSS (United States)
Before	46	46	AIR IS - 4A - 403 (United States)
Before	47	47	Meisei RS2-91 (Japan)
Before	48	48	VALCOM (Canada)
Before	49	49	VIZ MARK II (United States)
Before	50	50	Graw DFM-90 (Germany)
Before	51	51	VIZ-B2 (United States)
Before	52	52	Vaisala RS80-57H
Before	53	53	AVK-RF95 (Russian Federation)
Before	54	54	Graw DFM-97 (Germany)
Before	55	55	Meisei RS-01G (Japan)
Before	56	56	M2K2 (France)
Before	57	57	Modem M2K2-DC (France)
Before	58	58	AVK-BAR (Russian Federation)
Before	59	59	Modem M2K2-R 1680 MHz RDF radiosonde with pressure sensor chip (France)
Before	60	60	Vaisala RS80/MicroCora (Finland)
Before	61	61	Vaisala RS80/Loran/Digicora I, II or Marwin (Finland)
Before	62	62	Vaisala RS80/PCCora (Finland)
Before	63	63	Vaisala RS80/Star (Finland)
Before	64	64	Orbital Sciences Corporation, Space Data Division, transponder radiosonde, type 909-11-XX, where XX corresponds to the model of the instrument (United States)
Before	65	65	VIZ transponder radiosonde, model number 1499-520 (United States)
Before	66	66	Vaisala RS80 /Autosonde (Finland)
Before	67	67	Vaisala RS80/Digicora III (Finland)
Before	68	68	AVK-RZM-2 (Russian Federation)

COMMON CODE TABLES

<i>Common code table C-2</i>			
Date of assignment of number (necessary after 30/06/2007)	Code figure for raRa (Code table 3685)	Code figure for BUFR (Code table 0 02 011)	
Before	69	69	MARL-A or Vektor-M-RZM-2 (Russian Federation)
Before	70	70	Vaisala RS92/Star (Finland)
Before	71	71	Vaisala RS90/Loran/Digicora I, II or Marwin (Finland)
Before	72	72	Vaisala RS90/PC-Cora (Finland)
Before	73	73	Vaisala RS90/Autosonde (Finland)
Before	74	74	Vaisala RS90/Star (Finland)
Before	75	75	AVK-MRZ-ARMA (Russian Federation)
Before	76	76	AVK-RF95-ARMA (Russian Federation)
Before	77	77	GEOLINK GPSonde GL98 (France)
Before	78	78	Vaisala RS90/Digicora III (Finland)
Before	79	79	Vaisala RS92/Digicora I, II or Marwin (Finland)
Before	80	80	Vaisala RS92/Digicora III (Finland)
Before	81	81	Vaisala RS92/Autosonde (Finland)
Before	82	82	Sippican MK2 GPS/STAR (United States) with rod thermistor, carbon element and derived pressure
Before	83	83	Sippican MK2 GPS/W9000 (United States) with rod thermistor, carbon element and derived pressure
Before	84	84	Sippican MARK II with chip thermistor, carbon element and derived pressure from GPS height
Before	85	85	Sippican MARK IIA with chip thermistor, carbon element and derived pressure from GPS height
Before	86	86	Sippican MARK II with chip thermistor, pressure and carbon element
Before	87	87	Sippican MARK IIA with chip thermistor, pressure and carbon element
Before	88	88	MARL-A or Vektor-M-MRZ (Russian Federation)
Before	89	89	MARL-A or Vektor-M-BAR (Russian Federation)
Not applicable	90	90	Radiosonde not specified or unknown
Not applicable	91	91	Pressure only radiosonde
Not applicable	92	92	Pressure only radiosonde plus transponder
Not applicable	93	93	Pressure only radiosonde plus radar reflector
Not applicable	94	94	No pressure radiosonde plus transponder
Not applicable	95	95	No pressure radiosonde plus radar reflector
Not applicable	96	96	Descending radiosonde
Before	97	97	iMet-2/iMet-1500 RDF radiosonde with pressure sensor chip (South Africa)
Before	98	98	iMet-2/iMet-1500 GPS radiosonde with derived pressure from GPS height (South Africa)
Before	99	99	iMet-2/iMet-3200 GPS radiosonde with derived pressure from GPS height (South Africa)
	Not available	100	Reserved for BUFR only

COMMON CODE TABLES

Common code table C-2			
Date of assignment of number (necessary after 30/06/2007)	Code figure for raRa (Code table 3685)	Code figure for BUFR (Code table 0 02 011)	
	01	101	Not vacant
	Not available	102-106	Reserved for BUFR only
	07	107	Not vacant
	Not available	108-109	Reserved for BUFR only
01/01/2008	10	110	Sippican LMS5 w/Chip Thermistor, duct mounted capacitance relative humidity sensor and derived pressure from GPS height
01/01/2008	11	111	Sippican LMS6 w/Chip Thermistor, external boom mounted capacitance relative humidity sensor, and derived pressure from GPS height
06/05/2015	12	112	Jin Yang RSG-20A with derived pressure from GPS height/GL-5000P (Republic of Korea)
15/09/2010	13	113	Vaisala RS92/MARWIN MW32 (Finland)
03/11/2011	14	114	Vaisala RS92/DigiCORA MW41 (Finland)
01/12/2011	15	115	PAZA-12M/Radiotheodolite-UL (Ukraine)
01/12/2011	16	116	PAZA-22/AVK-1 (Ukraine)
02/05/2012	17	117	Graw DFM-09 (Germany)
	18	118	Not vacant
08/05/2019	19	119	Polus-MRZ-N1 (Russian Federation)
	20	120	Not vacant
06/05/2015	21	121	Jin Yang 1524LA LORAN-C/GL5000 (Republic of Korea)
02/05/2012	22	122	Meisei RS-11G GPS radiosonde w/thermistor, capacitance relative humidity sensor, and derived pressure from GPS height (Japan)
03/11/2011	23	123	Vaisala RS41/DigiCORA MW41 (Finland)
03/11/2011	24	124	Vaisala RS41/AUTOSONDE (Finland)
03/11/2011	25	125	Vaisala RS41/MARWIN MW32 (Finland)
07/05/2014	26	126	Meteolabor SRS-C34/Argus 37 (Switzerland)
	27	127	Not vacant
15/09/2011	28	128	AVK - AK2-02 (Russian Federation)
15/09/2011	29	129	MARL-A or Vektor-M - AK2-02 (Russian Federation)
01/01/2010	30	130	Meisei RS-06G (Japan)
03/11/2011	31	131	Taiyuan GTS1-1/GFE(L) (China)
03/11/2011	32	132	Shanghai GTS1/GFE(L) (China)
03/11/2011	33	133	Nanjing GTS1-2/GFE(L) (China)
Needed	34	134	Vacant
07/05/2014	35	135	Meisei iMS-100 GPS radiosonde w/thermistor sensor, capacitance relative humidity sensor, and derived pressure from GPS height (Japan)
02/05/2018	36	136	Meisei iMDS-17 GPS dropsonde w/thermistor sensor, capacitance relative humidity sensor, and capacitance pressure sensor (Japan)
	37	137	Not vacant
<u>21/03/2022</u>	<u>38</u>	<u>138</u>	<u>WEATHEX WxR-301D with derived pressure from GPS (Republic of Korea)</u>
Needed	38 39-40	138 139-140	Vacant

COMMON CODE TABLES

Common code table C-2			
Date of assignment of number (necessary after 30/06/2007)	Code figure for raRa (Code table 3685)	Code figure for BUFR (Code table 0 02 011)	
03/11/2011	41	141	Vaisala RS41 with pressure derived from GPS height/DigiCORA MW41 (Finland)
03/11/2011	42	142	Vaisala RS41 with pressure derived from GPS height/AUTOSONDE (Finland)
07/05/2014	43	143	NanJing Daqiao XGP-3G (China) (see Note 4)
07/05/2014	44	144	TianJin HuaYunTianYi GTS(U)1 (China) (see Note 4)
07/05/2014	45	145	Beijing Changfeng CF-06 (China) (see Note 4)
07/05/2014	46	146	Shanghai Changwang GTS3 (China) (see Note 4)
	47	147	Not vacant
02/05/2012	48	148	PAZA-22M/MARL-A
	49	149	Not vacant
02/11/2016	50	150	Meteolabor SRS-C50/Argus (Switzerland)
	51	151	Not vacant
03/11/2011	52	152	Vaisala RS92-NGP/Intermet IMS-2000 (United States)
06/05/2015	53	153	AVK – I-2012 (Russian Federation)
08/05/2019	54	154	Graw DFM-17 (Germany)
	55-59	155-159	Not vacant
06/05/2015	60	160	MARL-A or Vektor-M – I-2012 (Russian Federation)
	61	161	Not vacant
06/05/2015	62	162	MARL-A or Vektor-M – MRZ-3MK (Russian Federation)
07/11/2018	63	163	Modem M20 radiosonde w/thermistor sensor, capacitance relative humidity sensor, and derived pressure from GPS height (France)
07/11/2018	64	164	Modem PilotSonde GPS radiosonde (France)
15/05/2022	65	165	Meteosis MTS-01 (Republic of Türkiye Turkey)
Needed	66	166	Vacant
	67-72	167-172	Not vacant
02/11/2016	73	173	MARL-A (Russian Federation) – ASPAN-15 (Kazakhstan)
	74-76	174-176	Not vacant
15/03/2010	77	177	Modem GPSonde M10 (France)
	78-81	178-181	Not vacant
07/11/2012	82	182	Lockheed Martin LMS-6 w/chip thermistor; external boom mounted polymer capacitive relative humidity sensor; capacitive pressure sensor and GPS wind
07/11/2012	83	183	Vaisala RS92-D/Intermet IMS 1500 w/silicon capacitive pressure sensor, capacitive wire temperature sensor, twin thin-film heated polymer capacitive relative humidity sensor and RDF wind
06/11/2019	84	184	iMet-54/iMet-3200/3400 GPS radiosonde with derived pressure from GPS height (South Africa)
	85-89	185-189	Not vacant

COMMON CODE TABLES

<i>Common code table C-2</i>			
Date of assignment of number (necessary after 30/06/2007)	Code figure for raFa (Code table 3685)	Code figure for BUFR (Code table 0 02 011)	
	Not available	190	NCAR research dropsonde NRD94 with GPS and Vaisala RS92-based sensor module (United States)
	Not available	191	NCAR research dropsonde NRD41 with GPS and Vaisala RS41-based sensor module (United States)
	Not available	192	Vaisala/NCAR dropsonde RD94 with GPS and Vaisala RS92-based sensor module (Finland/United States)
	Not available	193	Vaisala/NCAR dropsonde RD41 with GPS and Vaisala RS41-based sensor module (Finland/United States)
	Not available	194–196	Reserved for BUFR only
	97–99	197–199	Not vacant
16/11/2020	Not available	200	Nanjing GTS11 (China)
16/11/2020	Not available	201	Shanghai GTS12 (China)
16/11/2020	Not available	202	Taiyuan GTS13 (China)
15/05/2022	Not available	203	Shanghai GTS14 (China)
	Not available	204–254	Reserved for BUFR only
		255	Missing value

Notes:

- (1) References to countries in brackets indicate the manufacturing location rather than the country using the instrument.
- (2) Some of the radiosondes listed are no longer in use but are retained for archiving purposes.
- (3) The alphanumeric code format reports only 2 digits, and the first digit for BUFR is identified from the date: the first digit is 0 if the introduction of the radiosonde for observation was before 30 June 2007, or 1 otherwise. Entries in the second part of the table (after 99), which are declared "Vacant" can be used for new radiosondes because the 2-digit number was originally attributed to sondes, which are no longer used. This system has been adopted to accommodate reporting in TEMP traditional alphanumeric code format up to the time BUFR is fully used for radiosonding reports.
- (4) All GPS radiosondes are with thermistor, silicon piezoresistive pressure sensor or pressure derived from GPS height, capacitive relative humidity sensor and wind derived from GPS height.

COMMON CODE TABLES

COMMON CODE TABLE C-3: Instrument make and type for water temperature profile measurement with fall rate equation coefficients

Common Code table { Code table 1770 – I_XI_XI_X (Instrument type for XBT, with fall rate equation coefficients) – for alphanumeric codes
Code table 0 22 067 (Instrument type for water temperature/salinity profile measurement) in BUFR

Common code table C-3				
Code figure for I _X I _X I _X	Code figure for BUFR (Code table 0 22 067)	Meaning		
		Instrument make and type	Equation Coefficients	
			<i>a</i>	<i>b</i>
001	1	Sippican T-4	6.472	-2.16
002	2	Sippican T-4	6.691	-2.25
011	11	Sippican T-5	6.828	-1.82
021	21	Sippican Fast Deep	6.346	-1.82
031	31	Sippican T-6	6.472	-2.16
032	32	Sippican T-6	6.691	-2.25
041	41	Sippican T-7	6.472	-2.16
042	42	Sippican T-7	6.691	-2.25
051	51	Sippican Deep Blue	6.472	-2.16
052	52	Sippican Deep Blue	6.691	-2.25
061	61	Sippican T-10	6.301	-2.16
071	71	Sippican T-11	1.7779	-0.255
081	81	Sippican AXBT (300 m probes)	1.52	0.0
201	201	TSK T-4	6.472	-2.16
202	202	TSK T-4	6.691	-2.25
211	211	TSK T-6	6.472	-2.16
212	212	TSK T-6	6.691	-2.25
221	221	TSK T-7	6.472	-2.16
222	222	TSK T-7	6.691	-2.25
231	231	TSK T-5	6.828	-1.82
241	241	TSK T-10	6.301	-2.16
251	251	TSK Deep Blue	6.472	-2.16
252	252	TSK Deep Blue	6.691	-2.25
261	261	TSK AXBT		
401	401	Sparton XBT-1	6.301	-2.16
411	411	Sparton XBT-3	5.861	-0.0904
421	421	Sparton XBT-4	6.472	-2.16
431	431	Sparton XBT-5	6.828	-1.82
441	441	Sparton XBT-5DB	6.828	-1.82
451	451	Sparton XBT-6	6.472	-2.16
461	461	Sparton XBT-7	6.472	-2.16
462	462	Sparton XBT-7	6.705	-2.28
471	471	Sparton XBT-7DB	6.472	-2.16
481	481	Sparton XBT-10	6.301	-2.16
491	491	Sparton XBT-20	6.472	-2.16
501	501	Sparton XBT-20DB	6.472	-2.16
510	510	Sparton 536 AXBT	1.524	0

COMMON CODE TABLES

Common code table C-3				
Code figure for IxIxIx	Code figure for BUFR (Code table 0 22 067)	Meaning		
		Instrument make and type	Equation Coefficients	
			<i>a</i>	<i>b</i>
700	700	Sippican XCTD Standard		
710	710	Sippican XCTD Deep		
720	720	Sippican AXCTD		
730	730	Sippican SXCTD		
741	741	TSK XCTD/XCTD-1/XCTD-1N	3.42543	-0.47
742	742	TSK XCTD-2/XCTD-2N	3.43898	-0.31
743	743	TSK XCTD-2F	3.43898	-0.31
744	744	TSK XCTD-3/XCTD-3N	5.07598	-0.72
745	745	TSK XCTD-4/XCTD-4N	3.68081	-0.47
751	751	TSK AXCTD		
780	780	Sea-Bird SBE21 SEACAT Thermosalinograph	Not applicable	
781	781	Sea-Bird SBE45 MicroTSG Thermosalinograph	Not applicable	
800	800	Mechanical BT	Not applicable	
810	810	Hydrocast	Not applicable	
820	820	Thermistor chain	Not applicable	
825	825	Temperature (sonic) and pressure probes	Not applicable	
830	830	CTD	Not applicable	
831	831	CTD-P-ALACE float	Not applicable	
834	834	PROVOR V SBE	Not applicable	
835	835	PROVOR-IV	Not applicable	
836	836	PROVOR-III	Not applicable	
837	837	ARVOR_C, SBE conductivity sensor		
838	838	ARVOR_D, SBE conductivity sensor		
839	839	PROVOR-II, SBE conductivity sensor		
840	840	PROVOR, no conductivity sensor	Not applicable	
841	841	PROVOR, Sea-Bird conductivity sensor	Not applicable	
842	842	PROVOR, FSI conductivity sensor	Not applicable	
843	843	Polar Ocean Profiling System (POPS), PROVOR, SBE CTD		
844	844	Profiling float, ARVOR, Sea-Bird conductivity sensor		
845	845	Webb Research, no conductivity sensor	Not applicable	
846	846	Webb Research, Sea-Bird conductivity sensor	Not applicable	
847	847	Webb Research, FSI conductivity sensor	Not applicable	
848	848	APEX-EM, SBE conductivity sensor		
849	849	APEX_D, SBE conductivity sensor		
850	850	SOLO, no conductivity sensor	Not applicable	
851	851	SOLO, Sea-Bird conductivity sensor	Not applicable	
852	852	SOLO, FSI conductivity sensor	Not applicable	
853	853	Profiling float, SOLO2 (SCRIPPS), Sea-Bird conductivity sensor		
854	854	S2A, SBE conductivity sensor		
855	855	Profiling float, NINJA, no conductivity sensor	Not applicable	

COMMON CODE TABLES

Code figure for IxIxIx	Code figure for BUFR (Code table 0 22 067)	Common code table C-3	
		Meaning	
		Instrument make and type	Equation Coefficients
			<i>a</i> <i>b</i>
856	856	Profiling float, NINJA, SBE conductivity sensor	Not applicable
857	857	Profiling float, NINJA, FSI conductivity sensor	Not applicable
858	858	Profiling float, NINJA, TSK conductivity sensor	Not applicable
859	859	Profiling float, NEMO, no conductivity sensor	Not applicable
860	860	Profiling float, NEMO, SBE conductivity sensor	Not applicable
861	861	Profiling float, NEMO, FSI conductivity sensor	Not applicable
862	862	SOLO_D, SBE conductivity sensor	
863	863	NAVIS-A, SBE conductivity sensor	
864	864	NINJA_D, SBE conductivity sensor	
865	865	NOVA, SBE conductivity sensor	
866	866	ALAMO, no conductivity sensor	
867	867	ALAMO, RBR conductivity sensor	
868	868	ALAMO, SBE conductivity sensor	
869	869	Reserved	
870	870	HM2000	Not applicable
871	871	COPEX	Not applicable
872	872	S2X	Not applicable
873	873	ALTO	Not applicable
874	874	SOLO_D_MR	Not applicable
875	875	ALTO RBR	Not applicable
876	876	ALTO SBE	Not applicable
877	877	APEX RBR	Not applicable
878	878	ARVOR RBR	Not applicable
879	879	SOLO II RBR	Not applicable
880	880	S2A RBR	Not applicable
<u>881</u>	<u>881</u>	<u>HM4000 SBE</u>	<u>Not applicable</u>
<u>882</u>	<u>882</u>	<u>HM6000 SBE</u>	<u>Not applicable</u>
881-883 -899	881-899	Reserved	
900	900	Sippican LMP-5 XBT	9.727 -0.0473
901	901	Ice-tethered Profiler (ITP), SBE CTD	
902	902	Brooke Ocean Moving Vessel Profiler (MVP)	
903	903	Sea-Bird CTD	
904	904	AML Oceanographic CTD	
905	905	Falmouth Scientific CTD	
906	906	Ocean Sensors CTD	
907	907	Valeport CTD	
908	908	Oceanscience MVP	
909	909	IDRONAUT CTD	
910	910	Sea-Bird SBE 38	

COMMON CODE TABLES

<i>Common code table C-3</i>				
Code figure for IxIxIx	Code figure for BUFR (Code table 0 22 067)	Meaning		
		Instrument make and type	Equation Coefficients	
			<i>a</i>	<i>b</i>
911-994	911-994	Reserved		
995	995	Instrument attached to marine mammals	Not applicable	
996	996	Instrument attached to animals other than marine mammals	Not applicable	
997-999	997-999	Reserved		
	1000-1022	Reserved		
	1023	Missing value		

Notes:

- (1) The depth is calculated from coefficients *a* and *b* and the time *t* as follows: $z = at + 10^{-3} bt^2$
- (2) All unassigned numbers are reserved for future use.
- (3) The values of *a* and *b* are supplied for information only.

COMMON CODE TABLES

COMMON CODE TABLE C-4: Water temperature profile recorder types

Common Code table { Code table 4770 – XrXr (Recorder type) – for alphanumeric codes
Code table 0 22 068 (Water temperature profile recorder types) in BUFR

Common code table C-4		
Code figure for IrIr	Code figure for BUFR (Code table 0 22 068)	Meaning
01	1	Sippican Strip Chart Recorder
02	2	Sippican MK2A/SSQ-61
03	3	Sippican MK-9
04	4	Sippican AN/BHQ-7/MK8
05	5	Sippican MK-12
06	6	Sippican MK-21
07	7	Sippican MK-8 Linear Recorder
08	8	Sippican MK-10
10	10	Sparton SOC BT/SV Processor Model 100
11	11	Lockheed-Sanders Model OL5005
20	20	ARGOS XBT-ST
21	21	CLS-ARGOS/Protecno XBT-ST Model-1
22	22	CLS-ARGOS/Protecno XBT-ST Model-2
30	30	BATHY Systems SA-810
31	31	Scripps Metrobyte Controller
32	32	Murayama Denki Z-60-16 III
33	33	Murayama Denki Z-60-16 II
34	34	Protecno ETSM2
35	35	Nautilus Marine Service NMS-XBT
40	40	TSK MK-2A
41	41	TSK MK-2S
42	42	TSK MK-30
43	43	TSK MK-30N
45	45	TSK MK-100
46	46	TSK MK-130 Compatible recorder for both XBT and XCTD
47	47	TSK MK-130A XCTD recorder
48	48	TSK AXBT RECEIVER MK-300
49	49	TSK MK-150/MK-150N Compatible recorder for both XBT and XCTD
50	50	JMA ASTOS
60	60	ARGOS communications, sampling on up transit
61	61	ARGOS communications, sampling on down transit
62	62	Orbcomm communications, sampling on up transit
63	63	Orbcomm communications, sampling on down transit
64	64	Iridium communications, sampling on up transit
65	65	Iridium communications, sampling on down transit
70	70	CSIRO Devil-1 XBT acquisition system
71	71	CSIRO Devil-2 XBT acquisition system
72	72	TURO/CSIRO Quoll XBT acquisition system
80	80	Applied Microsystems Ltd., MICRO-SVT&P

COMMON CODE TABLES

Common code table C-4		
Code figure for I _R I _R	Code figure for BUFR (Code table 0 22 068)	Meaning
81	81	Sea Mammal Research Unit, Univ. St. Andrews, UK, uncorrected salinity from a sea mammal mounted instrument
82	82	Sea Mammal Research Unit, Univ. St. Andrews, UK, corrected salinity from a sea mammal mounted instrument
99	99	Unknown
	127	Missing value

Note: All unassigned numbers are reserved for future use.

Provisional Copy
2023

COMMON CODE TABLES

COMMON CODE TABLE C-5: Satellite identifier

Common Code table { I₆I₆I₆ for alphanumeric codes
Code table 0 01 007 in BUFR
Code used in GRIB Edition 2

(EVEN DECILES INDICATE POLAR-ORBITING SATELLITES AND ODD DECILES INDICATE GEOSTATIONARY SATELLITES.)

Common code table C-5			
Code figure for I ₆ I ₆ I ₆	Code figure for BUFR (Code table 0 01 007)	Code figure for GRIB Edition 2	
000	0	0	Reserved
001-099: Numbers allocated to Europe			
001	1	1	ERS 1
002	2	2	ERS 2
003	3	3	METOP-1 (Metop-B)
004	4	4	METOP-2 (Metop-A)
005	5	5	METOP-3 (Metop-C)
020	20	20	SPOT1
021	21	21	SPOT2
022	22	22	SPOT3
023	23	23	SPOT4
024	24	24	Metop-D
025	25	25	Metop-E
026	26	26	Metop-F
027	27	27	Metop-G
028	28	28	Metop-H
029	29	29	Metop-I
040	40	40	OERSTED
041	41	41	CHAMP
042	42	42	TerraSAR-X
043	43	43	TanDEM-X
044	44	44	PAZ
<u>045</u>	<u>45</u>	<u>45</u>	<u>ALTIUS</u>
046	46	46	SMOS
047	47	47	CryoSat-2
048	48	48	AEOLUS
<u>049</u>	<u>49</u>	<u>49</u>	<u>EarthCARE</u>
050	50	50	METEOSAT 3
051	51	51	METEOSAT 4
052	52	52	METEOSAT 5
053	53	53	METEOSAT 6
054	54	54	METEOSAT 7
055	55	55	METEOSAT 8
056	56	56	METEOSAT 9

COMMON CODE TABLES

Common code table C-5

Code figure for I ₆ I ₆ I ₆	Code figure for BUFR (Code table 0 01 007)	Code figure for GRIB Edition 2	
057	57	57	METEOSAT 10
058	58	58	METEOSAT 1
059	59	59	METEOSAT 2
060	60	60	ENVISAT
061	61	61	Sentinel 3A
062	62	62	Sentinel 1A
063	63	63	Sentinel 1B
064	64	64	Sentinel 5P
065	65	65	Sentinel 3B
066	66	66	Sentinel-6A
067	67	67	Sentinel-6B
070	70	70	METEOSAT 11
071	71	71	METEOSAT 12
072	72	72	METEOSAT 13
073	73	73	METEOSAT 14
074	74	74	METEOSAT 15
075	75	75	METEOSAT 16
076	76	76	METEOSAT 17
100–199: Numbers allocated to Japan			
120	120	120	ADEOS
121	121	121	ADEOS II
122	122	122	GCOM-W1
140	140	140	GOSAT
150	150	150	GMS 3
151	151	151	GMS 4
152	152	152	GMS 5
153	153	153	GMS
154	154	154	GMS 2
171	171	171	MTSAT-1R
172	172	172	MTSAT-2
173	173	173	Himawari-8
174	174	174	Himawari-9
200–299: Numbers allocated to the United States			
200	200	200	NOAA 8
201	201	201	NOAA 9
202	202	202	NOAA 10
203	203	203	NOAA 11
204	204	204	NOAA 12
205	205	205	NOAA 14
206	206	206	NOAA 15

COMMON CODE TABLES

<i>Common code table C-5</i>			
Code figure for I ₆ I ₆ I ₆	Code figure for BUFR (Code table 0 01 007)	Code figure for GRIB Edition 2	
207	207	207	NOAA 16
208	208	208	NOAA 17
209	209	209	NOAA 18
220	220	220	LANDSAT 5
221	221	221	LANDSAT 4
222	222	222	LANDSAT 7
223	223	223	NOAA 19
224	224	224	NPP
225	225	225	NOAA 20
226	226	226	NOAA 21
<u>227</u>	<u>227</u>	<u>227</u>	<u>TROPICS-02</u>
<u>228</u>	<u>228</u>	<u>228</u>	<u>TROPICS-03</u>
<u>229</u>	<u>229</u>	<u>229</u>	<u>TROPICS-04</u>
240	240	240	DMSP 7
241	241	241	DMSP 8
242	242	242	DMSP 9
243	243	243	DMSP 10
244	244	244	DMSP 11
245	245	245	DMSP 12
246	246	246	DMSP 13
247	247	247	DMSP 14
248	248	248	DMSP 15
249	249	249	DMSP 16
250	250	250	GOES 6
251	251	251	GOES 7
252	252	252	GOES 8
253	253	253	GOES 9
254	254	254	GOES 10
255	255	255	GOES 11
256	256	256	GOES 12
257	257	257	GOES 13
258	258	258	GOES 14
259	259	259	GOES 15
260	260	260	JASON 1
261	261	261	JASON 2
262	262	262	JASON 3
<u>263</u>	<u>263</u>	<u>263</u>	<u>TROPICS-05</u>
<u>264</u>	<u>264</u>	<u>264</u>	<u>TROPICS-06</u>
265	265	265	GeoOptics CICERO OP1
266	266	266	GeoOptics CICERO OP2
267	267	267	PlanetiQ GNOMES-A
268	268	268	PlanetiQ GNOMES-B
269	269	269	Spire Lemur 3U CubeSat

COMMON CODE TABLES

Common code table C-5			
Code figure for I ₆ I ₆ I ₆	Code figure for BUFR (Code table 0 01 007)	Code figure for GRIB Edition 2	
270	270	270	GOES 16
271	271	271	GOES 17
272	272	272	GOES 18
273	273	273	GOES 19
281	281	281	QUIKSCAT
282	282	282	TRMM
283	283	283	CORIOLIS
<u>284</u>	<u>284</u>	<u>284</u>	<u>TROPICS-07</u>
285	285	285	DMSP 17
286	286	286	DMSP 18
287	287	287	DMSP 19
288	288	288	GPM-core
289	289	289	Orbiting Carbon Observatory – 2 (OCO-2, NASA)
300–399: Numbers allocated to the Russian Federation			
310	310	310	GOMS 1
311	311	311	GOMS 2
320	320	320	METEOR 2-21
321	321	321	METEOR 3-5
322	322	322	METEOR 3M-1
323	323	323	METEOR 3M-2
324	324	324	METEOR-M N2
325	325	325	METEOR-M N2 2
341	341	341	RESURS 01-4
400–499: Numbers allocated to India			
410	410	410	KALPANA-1
421	421	421	Oceansat-2
422	422	422	ScatSat-1
423	423	423	Oceansat-3
430	430	430	INSAT 1B
431	431	431	INSAT 1C
432	432	432	INSAT 1D
440	440	440	Megha-Tropiques
441	441	441	SARAL
450	450	450	INSAT 2A
451	451	451	INSAT 2B
452	452	452	INSAT 2E

COMMON CODE TABLES

Common code table C-5			
Code figure for I ₆ I ₆ I ₆	Code figure for BUFR (Code table 0 01 007)	Code figure for GRIB Edition 2	
470	470	470	INSAT 3A
471	471	471	INSAT 3D
472	472	472	INSAT 3E
473	473	473	INSAT 3DR
474	474	474	INSAT 3DS
500–599: Numbers allocated to China			
500	500	500	FY-1C
501	501	501	FY-1D
502	502	502	Hai Yang 2A (HY-2A, SOA/NSOAS China)
503	503	503	Hai Yang 2B (HY-2B, SOA/NSOAS China)
504	504	504	Hai Yang 2C (HY-2C, SOA/NSOAS China)
505	505	505	Hai Yang 2D (HY-2D, SOA/NSOAS China)
510	510	510	FY-2
512	512	512	FY-2B
513	513	513	FY-2C
514	514	514	FY-2D
515	515	515	FY-2E
516	516	516	FY-2F
517	517	517	FY-2G
518	518	518	FY-2H
520	520	520	FY-3A
521	521	521	FY-3B
522	522	522	FY-3C
523	523	523	FY-3D
524	524	524	FY-3E
530	530	530	FY-4A
531	531	531	FY-4B
600–699: Numbers allocated to Europe			
700–799: Numbers allocated to the United States			
700	700	700	TIROS M (ITOS 1)
701	701	701	NOAA 1
702	702	702	NOAA 2
703	703	703	NOAA 3
704	704	704	NOAA 4
705	705	705	NOAA 5
706	706	706	NOAA 6
707	707	707	NOAA 7
708	708	708	TIROS-N
<u>709</u>	<u>709</u>	<u>709</u>	<u>TROPICS-01 (Pathfinder)</u>

COMMON CODE TABLES

Common code table C-5			
Code figure for I ₆ I ₆ I ₆	Code figure for BUFR (Code table 0 01 007)	Code figure for GRIB Edition 2	
710	710	710	GOES (SMS 1)
711	711	711	GOES (SMS 2)
720	720	720	TOPEX
721	721	721	GFO (GEOSAT follow on)
722	722	722	GRACE A
723	723	723	GRACE B
724	724	724	COSMIC-2 P1
725	725	725	COSMIC-2 P2
726	726	726	COSMIC-2 P3
727	727	727	COSMIC-2 P4
728	728	728	COSMIC-2 P5
729	729	729	COSMIC-2 P6
731	731	731	GOES 1
732	732	732	GOES 2
733	733	733	GOES 3
734	734	734	GOES 4
735	735	735	GOES 5
740	740	740	COSMIC-1
741	741	741	COSMIC-2
742	742	742	COSMIC-3
743	743	743	COSMIC-4
744	744	744	COSMIC-5
745	745	745	COSMIC-6
750	750	750	COSMIC-2 E1
751	751	751	COSMIC-2 E2
752	752	752	COSMIC-2 E3
753	753	753	COSMIC-2 E4
754	754	754	COSMIC-2 E5
755	755	755	COSMIC-2 E6
761	761	761	NIMBUS 1
762	762	762	NIMBUS 2
763	763	763	NIMBUS 3
764	764	764	NIMBUS 4
765	765	765	NIMBUS 5
766	766	766	NIMBUS 6
767	767	767	NIMBUS 7
780	780	780	ERBS
781	781	781	UARS
782	782	782	EARTH PROBE
783	783	783	TERRA
784	784	784	AQUA

COMMON CODE TABLES

Common code table C-5			
Code figure for I ₆ I ₆ I ₆	Code figure for BUFR (Code table 0 01 007)	Code figure for GRIB Edition 2	
785	785	785	AURA
786	786	786	C/NOFS
787	787	787	CALIPSO
788	788	788	CloudSat
789	789	789	SMAP
800–849 Numbers allocated to other satellite operators			
800	800	800	SUNSAT
801	801	801	International Space Station (ISS)
802	802	802	CFOSAT
803	803	803	GRACE C (GRACE-FO)
804	804	804	GRACE D (GRACE-FO)
810	810	810	COMS
811	811	811	GEO-KOMPSAT-2A
812	812	812	SCISAT-1
813	813	813	ODIN
820	820	820	SAC-C
821	821	821	SAC-D
825	825	825	KOMPSAT-5
850	850	850	Combination of TERRA and AQUA
851	851	851	Combination of NOAA 16 to NOAA 19
852	852	852	Combination of Metop-1 to Metop-3
853	853	853	Combination of METEOSAT and DMSP
854	854	854	Non-specific mixture of geostationary and low Earth-orbiting satellites
855	855	855	Combination of INSAT 3D and INSAT 3DR
856	856	856	Combination of Sentinel-3 satellites
870–998	870–998	870–998	Reserved
999 Missing value	999–1022	999–65534	Reserved
	1023	65535	Missing value

Note: Within the ranges 000 to 849 and 870 to 998, even deciles indicate polar orbiting satellites and odd deciles indicate geostationary satellites. The range from 850 to 869 shall be used to indicate combinations of satellites, so the aforementioned decile rule does not apply to values in this range.

COMMON CODE TABLES

COMMON CODE TABLE C-6: List of units for TDCFs

Common code table C-6					
Code figure		Conventional abbreviation	Abbreviation in IA5/ASCII (5)	Abbreviation in ITA2 (5)	Definition in base units (2)
Base SI units (1)					
001	metre	m	m	M	
002	kilogram	kg	kg	KG	
003	second	s	s	S	
004	ampere	A	A	A	
005	kelvin	K	K	K	
006	mole	mol	mol	MOL	
007	candela	cd	cd	CD	
Supplementary SI Units (1)					
021	radian	rad	rad	RAD	
022	steradian	sr	sr	SR	
Derived SI Units with special names (1)					
030	hertz	Hz	Hz	HZ	s^{-1}
031	newton	N	N	N	$kg\ m\ s^{-2}$
032	pascal	Pa	Pa	PAL	$kg\ m^{-1}\ s^{-2}$
033	joule	J	J	J	$kg\ m^2\ s^{-2}$
034	watt	W	W	W	$kg\ m^2\ s^{-3}$
035	coulomb	C	C	C	A s
036	volt	V	V	V	$kg\ m^2\ s^{-3}\ A^{-1}$
037	farad	F	F	F	$kg^{-1}\ m^{-2}\ s^4\ A^2$
038	ohm	Ω	Ohm	OHM	$kg\ m^2\ s^{-3}\ A^{-2}$
039	siemens	S	S	SIE	$kg^{-1}\ m^{-2}\ s^3\ A^2$
040	weber	Wb	Wb	WB	$kg\ m^2\ s^{-2}\ A^{-1}$
041	tesla	T	T	T	$kg\ s^{-2}\ A^{-1}$
042	henry	H	H	H	$kg\ m^2\ s^{-2}\ A^{-2}$
060	degree Celsius	$^{\circ}C$	Cel	CEL	K+273.15
070	lumen	lm	lm	LM	cd sr
071	lux	lx	lx	LX	cd sr m^{-2}
080	becquerel	Bq	Bq	BQ	s^{-1}
081	grey	Gy	Gy	GY	$m^2\ s^{-2}$
082	sievert	Sv	Sv	SV	$m^2\ s^{-2}$
SI Unit prefixes (1) (3) (4)					
no	(yotta)	(Y)	(Y)	(Y)	
no	(zetta)	(Z)	(Z)	(Z)	
no	exa	E	E	E	
no	peta	P	P	PE	
no	tera	T	T	T	
no	giga	G	G	G	
no	mega	M	M	MA	
no	kilo	k	k	K	
no	hecto	h	h	H	
no	deca	da	da	DA	
no	deci	d	d	D	

COMMON CODE TABLES

		Common code table C-6		
Code figure		Conventional abbreviation	Abbreviation in IA5/ASCII (5)	Abbreviation in ITA2 (5) Definition in base units (2)
no	centi	c	c	C
no	milli	m	m	M
no	micro	μ	u	U
no	nano	n	n	N
no	pico	p	p	P
no	femto	f	f	F
no	atto	a	a	A
no	(zepto)	(z)	(z)	
no	(yocto)	(y)	(y)	
Other, non-SI, units recognized by CGPM (4)				
110	degree (angle)	°	deg	DEG
111	minute (angle)	'	'	MNT
112	second (angle)	"	"	SEC
120	litre	l or L	l or L	L
130	minute (time)	min	min	MIN
131	hour	h	h	HR
132	day	d	d	D
150	tonne	t	t	TNE
160	electron volt	eV	eV	EV
161	atomic mass unit	u	u	U
170	astronomic unit	AU	AU	ASU
171	parsec	pc	pc	PRS
Non-SI Units tolerated because of widespread use				
200	nautical mile			
201	knot	kt	kt	KT
210	decibel (6)	dB	dB	DB
220	hectare	ha	ha	HAR
230	week			
231	year	a	a	ANN
Other Units as used by WMO (7)				
300	per cent	%	%	PERCENT
301	parts per thousand	‰	0/00	PERTHOU
310	eighths of cloud	okta	okta	OKTA
320	degrees true	°	deg	DEG
321	degrees per second	degree/s	deg/s	DEG/S
350	degrees Celsius (8)	°C	C	C
351	degrees Celsius per metre	°C/m	C/m	C/M
352	degrees Celsius per 100 metres	°C/100 m	C/100 m	C/100 M
360	Dobson Unit (9)	DU	DU	DU
430	month	mon	mon	MON
441	per second (same as hertz)	s ⁻¹	/s	/S
442	per second squared	s ⁻²	s-2	
501	knots per 1000 metres	kt/1000 m	kt/km	KT/KM
510	foot	ft	ft	FT
511	inch	in	in	IN

COMMON CODE TABLES

Common code table C-6					
Code figure		Conventional abbreviation	Abbreviation in IA5/ASCII (5)	Abbreviation in ITA2 (5)	Definition in base units (2)
520	decipascals per second (microbar per second)	dPa s ⁻¹	dPa/s	DPAL/S	
521	centibars per second	cb s ⁻¹	cb/s	CB/S	
522	centibars per 12 hours	cb/12 h	cb/12 h	CB/12 HR	
523	dekapascal	daPa	daPa	DAPAL	
530	hectopascal	hPa	hPa	HPAL	
531	hectopascals per second	hPa s ⁻¹	hPa/s	HPAL/S	
532	hectopascals per hour	hPa h ⁻¹	hPa/h	HPAL/HR	
533	hectopascals per 3 hours	hPa/3 h	hPa/3 h	HPAL/3 HR	
535	nanobar = hPa 10 ⁻⁶	nbar	nbar	NBAR	
620	grams per kilogram	g kg ⁻¹	g/kg	G/KG	
621	grams per kilogram per second	g kg ⁻¹ s ⁻¹	g kg ⁻¹ s ⁻¹		
622	kilograms per kilogram	kg kg ⁻¹	kg/kg	KG/KG	
623	kilograms per kilogram per second	kg kg ⁻¹ s ⁻¹	kg kg ⁻¹ s ⁻¹		
624	kilograms per square metre	kg m ⁻²	kg m ⁻²		
630	acceleration due to gravity	g	g		
631	geopotential metre	gpm	gpm		
710	millimetre	mm	mm	MM	
711	millimetres per second	mm s ⁻¹	mm/s	MM/S	
712	millimetres per hour	mm h ⁻¹	mm/h	MM/HR	
713	millimetres to the sixth power per cubic metre	mm ⁶ m ⁻³	mm ⁶ m ⁻³		
715	centimetre	cm	cm	CM	
716	centimetres per second	cm s ⁻¹	cm/s	CM/S	
717	centimetres per hour	cm h ⁻¹	cm/h	CM/HR	
720	decimetre	dm	dm	DM	
731	metres per second	m s ⁻¹	m/s	M/S	
732	metres per second per metre	m s ⁻¹ /m	m s ⁻¹ /m		
733	metres per second per 1000 metres	m s ⁻¹ /1000 m	m s ⁻¹ /km		
734	square metres	m ²	m ²	M2	
735	square metres per second	m ² s ⁻¹	m ² /s	M2/S	
740	kilometre	km	km	KM	
741	kilometres per hour	km h ⁻¹	km/h	KM/HR	
742	kilometres per day	km/d	km/d	KM/D	
743	per metre	m ⁻¹	m ⁻¹	/M	
750	becquerels per litre	Bq l ⁻¹	Bq/l	BQ/L	
751	becquerels per square metre	Bq m ⁻²	Bq m ⁻²	BQ/M2	
752	becquerels per cubic metre	Bq m ⁻³	Bq m ⁻³	BQ/M3	
753	millisievert	mSv	mSv	MSV	
760	metres per second squared	m s ⁻²	m s ⁻²		
761	square metres second	m ² s	m ² s		

COMMON CODE TABLES

Common code table C-6					
Code figure		Conventional abbreviation	Abbreviation in IA5/ASCII (5)	Abbreviation in ITA2 (5)	Definition in base units (2)
762	square metres per second squared	m ² s ⁻²	m2 s-2		
763	square metres per radian second	m ² rad ⁻¹ s	m2 rad-1 s		
764	square metres per hertz	m ² Hz ⁻¹	m2/Hz		
765	cubic metres	m ³	m3		
766	cubic metres per second	m ³ s ⁻¹	m3/s		
767	cubic metres per cubic metre	m ³ m ⁻³	m3 m-3		
768	metres to the fourth power	m ⁴	m4		
769	metres to the two thirds power per second	m ^{2/3} s ⁻¹	m2/3 s-1		
772	logarithm per metre	log (m ⁻¹)	log (m-1)		
773	logarithm per square metre	log (m ⁻²)	log (m-2)		
775	kilograms per metre	kg m ⁻¹	kg/m		
776	kilograms per square metre per second	kg m ⁻² s ⁻¹	kg m-2 s-1		
777	kilograms per cubic metre	kg m ⁻³	kg m ⁻³		
778	per square kilogram per second	kg ⁻² s ⁻¹	kg-2 s-1		
779	seconds per metre	s m ⁻¹	s/m		
785	kelvin metres per second	K m s ⁻¹	K m s-1		
786	kelvins per metre	K m ⁻¹	K/m		
787	kelvin square metres per kilogram per second	K m ² kg ⁻¹ s ⁻¹	K m2 kg-1 s-1		
788	moles per mole	mol mol ⁻¹	mol/mol		
790	radians per metre	rad m ⁻¹	rad/m		
795	newtons per square metre	N m ⁻²	N m-2		
800	pascals per second	Pa s ⁻¹	Pa/s		
801	kilopascal	kPa	kPa		
805	joules per square metre	J m ⁻²	J m-2		
806	joules per kilogram	J kg ⁻¹	J/kg		
810	watts per metre per steradian	W m ⁻¹ sr ⁻¹	W m-1 sr-1		
811	watts per square metre	W m ⁻²	W m-2		
812	watts per square metre per steradian	W m ⁻² sr ⁻¹	W m-2 sr-1		
813	watts per square metre per steradian centimetre	W m ⁻² sr ⁻¹ cm	W m-2 sr-1 cm		
814	watts per square metre per steradian metre	W m ⁻² sr ⁻¹ m	W m-2 sr-1 m		
815	watts per cubic metre per steradian	W m ⁻³ sr ⁻¹	W m-3 sr-1		
820	siemens per metre	S m ⁻¹	S/m		
825	square degrees	degree ²	deg2		
830	becquerel seconds per cubic metre	Bq s m ⁻³	Bq s m-3		
835	decibels per metre	dB m ⁻¹	dB/m		

COMMON CODE TABLES

Common code table C-6					
Code figure		Conventional abbreviation	Abbreviation in IA5/ASCII (5)	Abbreviation in ITA2 (5)	Definition in base units (2)
836	decibels per degree	dB degree ⁻¹	dB/deg		
841	pH unit	pH unit	pH unit		
842	N units	N units	N units		
843	Nephelometric turbidity units	NTU	NTU		
844	Total electron content unit	TECU	TECU	TECU	10 ¹⁶ Electrons m ⁻²

Notes:

- (1) The international system of units, *Système International d'Unités* (SI), was established by the eleventh General Conference on Weights and Measures in 1960, and extended at the 1980 Conference. There are seven base units, two dimensionless supplementary units and a set of prefixes for decimal scaling. These may be combined to give compound units. Some compound units have special names, and are called derived Units.
- (2) When documenting compound SI units, each symbol for each base unit has been separated from the others by a space. There is no space between the unit and any prefix or exponent. Any prefix establishes a new unit to which any exponent applies (e.g. km² = (km)² = m⁶ not k(m²) = m⁵). Prefixes must be in the case specified. The full name of the unit must not start with an upper case letter. If the solidus (/) is used, there must be only one. There is no space before or after it.
- (3) Prefixes beyond exa and atto have been proposed but not yet adopted. Use of the prefixes hecto, deca, deci and centi is discouraged.
- (4) Prefixes generally should not be used with units having non-decimal multiples and sub-multiples, such as units of time and angle, or with knots and nautical miles.
- (5) Non-WMO abbreviations with limited character sets taken from ISO 2955-1983. Other abbreviations try to be consistent with this.
- (6) The decibel is one tenth of a bel, which is the decimal logarithm of a ratio of two powers. Frequently, suffixes are supplied to indicate information about one of the quantities in the ratio, such as dB(mW), dBm, dBZ, dBW, dBmW, dB(μV/m). It is recommended that only dB is used, with the full meaning of the ratio explained, including reference levels.
- (7) This list consists of the units not mentioned previously that occur in existing WMO Manuals.
- (8) The abbreviation for degrees Celsius proposed for WMO use, C, could be confused with Coulombs. In this case, Amperes second should be used instead.
- (9) Dobson Unit = DU. One Dobson Unit corresponds to a layer of 0.01 mm of pure ozone, if the whole column of atmosphere were compressed at P = 1013 hPa and T = 0 °C.

COMMON CODE TABLES

COMMON CODE TABLE C-7: Tracking technique/status of system used

Common Code table { Code table 3872 – s_as_a for alphanumeric codes
Code table 0 02 014 in BUFR

Common code table C-7		
Code figure for s _a s _a	Code figure for BUFR (Code table 0 02 014)	
00	0	No wind finding
01	1	Automatic with auxiliary optical direction finding
02	2	Automatic with auxiliary radio direction finding
03	3	Automatic with auxiliary ranging
04	4	Not used
05	5	Automatic with multiple VLF-Omega signals
06	6	Automatic cross chain Loran-C
07	7	Automatic with auxiliary wind profiler
08	8	Automatic satellite navigation
09-18	9-18	Reserved
19	19	Tracking technique not specified
TRACKING TECHNIQUES/STATUS OF ASAP SYSTEM		
STATUS OF SHIP SYSTEM		
20	20	Vessel stopped
21	21	Vessel diverted from original destination
22	22	Vessel's arrival delayed
23	23	Container damaged
24	24	Power failure to container
25-28	25-28	Reserved for future use
29	29	Other problems
SOUNDING SYSTEM		
30	30	Major power problems
31	31	UPS inoperative
32	32	Receiver hardware problems
33	33	Receiver software problems
34	34	Processor hardware problems
35	35	Processor software problems
36	36	NAVAID system damaged
37	37	Shortage of lifting gas
38	38	Reserved
39	39	Other problems
LAUNCH FACILITIES		
40	40	Mechanical defect
41	41	Material defect (hand launcher)
42	42	Power failure

COMMON CODE TABLES

Common code table C-7

Code figure for S _a S _a	Code figure for BUFR (Code table 0 02 014)	
43	43	Control failure
44	44	Pneumatic/hydraulic failure
45	45	Other problems
46	46	Compressor problems
47	47	Balloon problems
48	48	Balloon release problems
49	49	Launcher damaged
DATA ACQUISITION SYSTEM		
50	50	R/S receiver antenna defect
51	51	NAVAID antenna defect
52	52	R/S receiver cabling (antenna) defect
53	53	NAVAID antenna cabling defect
54-58	54-58	Reserved
59	59	Other problems
COMMUNICATIONS		
60	60	ASAP communications defect
61	61	Communications facility rejected data
62	62	No power at transmitting antenna
63	63	Antenna cable broken
64	64	Antenna cable defect
65	65	Message transmitted power below normal
66-68	66-68	Reserved
69	69	Other problems
70	70	All systems in normal operation
71-98	71-98	Reserved
99	99	Status of system and its components not specified
Not available	100-126	Reserved
Not available	127	Missing value

COMMON CODE TABLES

COMMON CODE TABLE C-8: Satellite instruments

Common Code table Code table 0 02 019 in BUFR

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
<u>8</u>	<u>DoD</u>	<u>Radiometer</u>	<u>SSM/T</u>	<u>Special Sensor Microwave-Temperature</u>
<u>9</u>	<u>DoD</u>	<u>Radiometer</u>	<u>SSM/T2</u>	<u>Special Sensor Microwave-Humidity</u>
10	BNSC	Radiometer	AATSR	Advanced along track scanning radiometer
11	BNSC	Radiometer	ATSR	Along track scanning radiometer
12	BNSC	Radiometer	ATSR-2	Along track scanning radiometer-2
13	BNSC	Radiometer	MWR	Microwave radiometer
14	UKSA	Radiometer	PMR	Pressure modulator radiometer
<u>15</u>	<u>UKSA</u>	<u>Radiometer</u>	<u>SCR</u>	<u>Selective Chopper Radiometer</u>
30	CNES	Communications	ARGOS	
40	CNES	Lidar	Laser reflectors	
41	CNES	Lidar	DORIS	Doppler orbitography and radio-positioning integrated by satellite
42	CNES	Lidar	DORIS-NG	Doppler orbitography and radio-positioning integrated by satellite-NG
47	CNES	Radar altimeter	POSEIDON-1 (SSALT1)	Positioning ocean, solid Earth, ice dynamics orbiting navigator (single frequency solid state radar altimeter)
48	CNES	Radar altimeter	POSEIDON-2 (SSALT2)	Positioning ocean, solid Earth, ice dynamics orbiting navigator (double frequency solid state radar altimeter)
49	CNES	Radar altimeter	POSEIDON-3 (SSALT3)	Positioning ocean, solid Earth, ice dynamics orbiting navigator (double frequency solid state radar altimeter)
50	CNES	Imaging radiometer	ATSR/M	ATSR/M
51	CNES	High-resolution optical imager	HRG	
52	CNES	Radiometer	HRV	High-resolution visible
53	CNES	Radiometer	HRVIR	High-resolution visible and infrared
54	CNES	Radiometer	ScaRaB/MV2	Scanner for Earth's radiation budget
55	CNES	Radiometer	POLDER	POLDER

COMMON CODE TABLES

<i>Common code table C-8</i>				
Code	Agency	Type	Instrument short name	Instrument long name
56	CNES	Imaging multi-spectral radiometer	IIR	Imaging Infrared Radiometer
57	ESA/ EUMETSAT	Radar altimeter	POSEIDON-4	High precision altimetry, dual frequency (C- and Ku-band) pulse-width limited radar altimeter, synthetic-aperture processing, interleaved low rate and high rate
60	CNES	Spectrometer	VEGETATION	VEGETATION
61	CNES	Spectrometer	WINDII	WINDII
62	CNES	Altimeter	AltiKa	Ka band Radar Altimeter
63	CNES	Rotating multi-beam altimeter	SWIM	Surface Waves Investigation and Monitoring
80	CSA	Communications	RADARSAT DTT	
81	CSA	Communications	RADARSAT TTC	
85	CSA	Radar	SAR (CSA)	Synthetic aperture radar (CSA)
90	CSA	Radiometer	MOPITT	Measurements of pollution in the troposphere
91	CSA	Atmospheric chemistry instrument	OSIRIS	Optical spectrograph and Infrared imaging system
92	CSA	Limb-scanning sounder	ACE-FTS	Atmospheric Chemistry Experiment – Fourier Transform Spectrometer
97	CSIRO	Radiometer	Panchromatic imager	
98	CRCSS	Atmospheric temperature and humidity sounder	GPS receiver	
102	DLR	Radiometer	CHAMP GPS sounder	GPS turborogue space receiver (TRSR)
103	DLR	Radiometer	IGOR	Integrated GPS and Occultation Receiver
104	NASA	GNSS occultation sounder	Tri-G	Triple-G (GPS, Galileo, GLONASS)
116	DLR	Magnetometer	CHAMP gravity package (Accelerometer+ GPS)	STAR accelerometer
117	DLR	Magnetometer	CHAMP magnetometry package (1 scalar+ 2 vector magnetometer)	Overhauser magnetometer (OVM) and fluxgate magnetometer (FGM)
120	ESA	Communications	ENVISAT Comms	Communications package on ENVISAT
121	ESA	Communications	ERS Comms	Communication package for ERS
130	ESA	Lidar	ALADIN	Atmospheric laser Doppler instrument

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
131	ESA	Lidar	ATLID	Atmospheric lidar
140	ESA	Radar	AMI/SAR/image	Active microwave instrumentation image mode
141	ESA	Radar	AMI/SAR/wave	Active microwave instrumentation wave mode
142	ESA	Radar	AMI/scatterometer	Active microwave instrumentation wind mode
143	ESA	Radar	ASAR	ASAR
144	ESA	Imaging microwave	ASAR	Advanced synthetic aperture radar (image mode)
145	ESA	Imaging microwave	ASAR	Advanced synthetic aperture radar (wave mode)
146	ESA	Cloud profile and rain radar	CPR	Cloud radar
147	ESA	Radar	RA-2/MWR	Radar altimeter-2
148	ESA	Radar	RA/MWR	Radar altimeter
150	ESA	Scatterometer	SCATTEROMETER	Scatterometer
151	ESA	Imaging radar	SAR-C	Synthetic Aperture Radar (C-band)
152	ESA	Cross-nadir scanning	SW	Sounder TROPOMI Tropospheric Monitoring Instrument
161	ESA	Radiometer	MIPAS	Michelson interferometric passive atmosphere sounder
162	ESA	Imaging multi-spectral radiometer (passive microwave)	MWR-2	Microwave radiometer-2
163	ESA	Atmospheric chemistry instrument	SOPRANO	Sub-millimetre observation of processes in the absorption noteworthy for ozone
170	ESA	Atmospheric chemistry instrument	GOME	Global ozone monitoring experiment
172	ESA	Spectrometer	GOMOS	Global ozone monitoring by occultation of stars
<u>173</u>	<u>ESA</u>	<u>Spectrometer</u>	<u>ALTIUS</u>	<u>Atmospheric Limb Tracker for Investigation of the Upcoming Stratosphere</u>
174	ESA	Spectrometer	MERIS	Medium resolution imaging spectrometer
175	ESA	Spectrometer	SCIAMACHY	Scanning imaging absorption spectrometer for atmospheric cartography

COMMON CODE TABLES

<i>Common code table C-8</i>				
Code	Agency	Type	Instrument short name	Instrument long name
176	ESA	Radiometer	MIRAS	Microwave imaging radiometer using aperture synthesis
177	ESA	Radar Altimeter	SIRAL	SAR/Interferometric Radar Altimeter
178	ESA	Radar altimeter	SRAL	Synthetic aperture radar altimeter
179	ESA	Moderate resolution optical imager	OLCI	Ocean and land colour imager
180	ESA	Moderate resolution optical imager	SLSTR	Sea and land surface temperature radiometer
181	EUMETSAT	Communications	METEOSAT Comms	Communications package for METEOSAT
182	EUMETSAT	Communications	MSG Comms	Communications package for MSG
190	ESA/ EUMETSAT	Scatterometer	ASCAT	Advanced scatterometer
200	EUMETSAT	Radiometer	GERB	Geostationary Earth radiation budget
202	ESA/ EUMETSAT	Radiometer	GRAS	GNSS receiver for atmospheric sounding
203	EUMETSAT	Radiometer	MHS	Microwave humidity sounder
205	EUMETSAT	Radiometer	MVIRI	METEOSAT visible and infrared imager
207	EUMETSAT	Radiometer	SEVIRI	Spinning enhanced visible and infrared imager
208	EUMETSAT	Imaging multi-spectral radiometer (vis/IR)	VIRI	VIRI
210	ESA/ EUMETSAT/ Thales Alenia Space	Imager	FCI	Flexible combined imager
211	ESA/ EUMETSAT/ Leonardo	Imager	LI	Lightning imager
212	ESA/ EUMETSAT/ OHB	Interferometer	IRS	Infrared sounder
213	ESA/ EUMETSAT/ Copernicus – Airbus	Spectrometer	S4	Ultraviolet and Near-Infrared Multispectral Spectrometer (S4 UVN)
220	ESA/ EUMETSAT	Spectrometer	GOME-2	Global ozone monitoring experiment-2
221	CNES/ EUMETSAT	Atmospheric temperature and humidity sounder	IASI	Infrared atmospheric sounding interferometer
230	ESA/ EUMETSAT	Radiometer	3MI	Multi-viewing Multi-channel Multi-polarisation Imaging

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
231	CNES/ EUMETSAT	Sounder – interferometer	IASI-NG	Infrared Atmospheric Sounding Interferometer – New Generation
232	DLR/ EUMETSAT	Radiometer	METImage	Meteorological Imager
233	ESA/ EUMETSAT	Radiometer	MWS	Microwave Sounder
234	ESA/ EUMETSAT	Radio Occultation	RO	Radio Occultation
235	ESA/ EUMETSAT/ EU	Spectrometer	S5/UVNS	Copernicus Sentinel-5 Ultraviolet Visible Near-infrared and Shortwave-infrared Spectrometer
236	ESA/ EUMETSAT	Radiometer	ICI	Ice Cloud Imager
237	ESA/ EUMETSAT	Radiometer	MWI	Microwave Imager
238	ESA/ EUMETSAT	Radar	SCA	Scatterometer
240	CAST	Communications	DCP	Data-collection platform transponder
245	CAST	Radiometer	CCD	High-resolution CCD camera
246	INPE	Atmospheric temperature and humidity sounder	HSB	Humidity sounder/Brazil
248	INPE	Imaging multi-spectral radiometer (vis/IR)	OBA	Observador Brasileiro da Amazonia
250	CAST	Radiometer	WFI	Wide field imager
255	CAST	Spectrometer	IRMSS	Infrared multispectral scanner
260	ISRO	Precision orbit	BSS & FSS transponders	
261	ISRO	Precision orbit	DRT-S&R	
262	ISRO	Communications	INSAT Comms	Communications package for INSAT
268	ISRO	High-resolution optical imager	HR-PAN	High-resolution panchromatic camera
269	ISRO	Imaging multi-spectral radiometer (passive microwave)	MSMR	Multifrequency scanning microwave radiometer
270	ISRO	Imaging multi-spectral radiometer (vis/IR)	VHRR	Very high-resolution radiometer
271	ISRO	Imaging multi-spectral radiometer (vis/IR)	WiFS	Wide field sensor

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
275	ISRO	High-resolution optical imager	AWiFS	Advanced wide field sensor
276	ISRO	High-resolution optical imager	LISS-I	Linear imaging self scanner-I
277	ISRO	High-resolution optical imager	LISS-II	Linear imaging self scanner-II
278	ISRO	High-resolution optical imager	LISS-III	Linear imaging self scanner-III
279	ISRO	High-resolution optical imager	LISS-IV	Linear imaging self scanner-IV
284	ISRO	High-resolution optical imager	PAN	Panchromatic sensor
285	ISRO	Imaging multi-spectral radiometer (vis/IR)	MOS	Modular opto-electronic scanner
286	ISRO	Ocean colour Instrument	OCM	Ocean colour monitor
287	ASI		ROSA	Radio Occultation Sounder of the Atmosphere
288	ISRO	Scatterometer	SCAT	Scatterometer
289	ISRO	Optical imager	IMG	Imager
290	JMA	Communications	MTSAT Comms	Communications package for MTSAT
291	JMA	Communications	Himawari Comms	Communications package for Himawari
294	JMA	Imaging multi-spectral radiometer	JAMI	Japanese Advanced Meteorological Imager
295	JMA	Imaging multi-spectral radiometer	IMAGER/MTSAT-2	Imager/MTSAT-2
296	JMA	Imaging multi-spectral radiometer	VISSR	Visible and infrared spin scan radiometer
297	JMA	Imaging multi-spectral radiometer	AHI	Advanced Himawari Imager
300	NASA	Lidar	GLAS	Geoscience laser altimeter system
301	NASA	Precision orbit	LRA	Laser retroreflector array
302	NASA	Lidar	MBLA	Multi-beam laser altimeter
303	NASA	Lidar	CALIOP	Cloud-aerosol lidar with orthogonal polarization
309	NASA	Cloud profile and rain radar	CPR (Cloudsat)	Cloud profiling radar
312	NASA	Radar	NSCAT	NASA scatterometer
313	NASA	Radar	SeaWinds	ADEOS II – NASA scatterometer
314	NASA	Radar	RapidScat	RapidScat scatterometer
330	NASA	Earth radiation budget radiometer	ACRIM	Active cavity radiometer irradiance monitor

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
334	NASA	Total and profile ozone	BUV	Backscatter ultraviolet instrument
336	NASA	High-resolution optical imager	ALI	Advanced land imager
347	NASA	High-resolution optical imager	ASTER	Advanced spaceborne thermal emission and
348	NASA	Earth radiation budget radiometer	CERES-2	Cloud and the Earth's radiant energy system
351	NASA	Atmospheric temperature and humidity sounder	GPSDR	GPS demonstration receiver
353	NASA	Total and profile ozone	HiRDLS	High-resolution dynamics limb sounder
354	NASA	Total and profile ozone	HRDI	High-resolution Doppler imager
356	NASA	Radiometer	LIS	Lightning imaging sensor
358	NASA	Magnetic field, auroal imagery scintillation boundary	PEM	Particle environment monitor
359	NASA	Ocean colour instrument	SeaWiFS	Sea-viewing wide field-of-view sensor
360	NASA	Earth radiation budget radiometer	SUSIM (UARS)	Solar ultraviolet irradiance monitor
363	NASA	Total and profile ozone	SBUV/1	Solar backscatter ultraviolet 1 instrument
365	NASA	Imaging multi-spectral radiometer (passive microwave)	TMI	TRMM microwave imager
366	NASA	Imaging multi-spectral radiometer (passive microwave)	JMR	JASON-1 microwave radiometer
367	NASA	Imaging multi-spectral radiometer	AMR	Advanced microwave radiometer
369	NASA	Total and profile ozone	LIMS	Limb infrared monitor of the stratosphere
370	NASA	Total and profile ozone	LRIR	Limb radiance inversion radiometer instrument
371	NASA	Total and profile ozone	EPIC	Earth polychromatic imaging camera
372	NASA	Earth radiation budget radiometer	NISTAR	NIST advanced radiometer
373	NASA	Magnetic field, auroal imagery scintillation boundary	Plasma-Mag	
374	NASA	Other	XPS	XUV photometer system

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
375	NASA	Imaging multi-spectral radiometer (vis/IR)	VIRS	Visible infrared scanner
376	CNES	Multiple direction/polarization radiometer	POLDER II	Polarization and directionality of the Earth's reflectance-II
377	NASA	Earth radiation budget radiometer	TIM	Total irradiance monitor
379	NASA	Imaging multi-spectral radiometer (vis/IR)	WFC	Wide field camera
382	NASA	Spectro-radiometer	CLAES	Cryogenic limb array etalon spectrometer
383	NASA	Spectro-radiometer	HALOE	Halogen occultation experiment
384	NASA	Spectro-radiometer	ISAMS	Improved stratospheric and mesospheric sounder
385	NASA	Spectro-radiometer	MISR	Multi-angle imaging spectroradiometer
386	NASA	Spectro-radiometer	MLS	Microwave limb sounder
387	NASA	Spectro-radiometer	MLS (EOS-Aura)	Microwave limb sounder (EOS-Aura)
389	NASA	Spectro-radiometer	MODIS	Moderate-resolution imaging spectroradiometer
393	NASA	Gravity	HAIRS	High accuracy inter-satellite ranging system
394	NASA	Total and profile ozone	OMI	Ozone measuring instrument
395	NASA	Radiometer	Atmospheric corrector	Atmospheric corrector
396	NASA	Radiometer	Hyperion	Hyperspectral imager
397	NASA	Radiometer	HRIR	High-resolution infrared radiometer
398	NASA	Radiometer	MRIR	Medium resolution infrared radiometer
399	NASA	Spectro-radiometer	SAGE I	Stratospheric aerosol and gas experiment-I
400	NASA	Spectro-radiometer	SAGE II	Stratospheric aerosol and gas experiment-II
401	NASA	Spectro-radiometer	SAGE III	Stratospheric aerosol and gas experiment-III
402	NASA	Spectro-radiometer	SAMS	Stratospheric and mesospheric sounder
403	NASA	Spectro-radiometer	SAM-II	Stratospheric aerosol measurement-II
404	NASA	Spectro-radiometer	IRIS	Infrared interferometer spectrometer
405	NASA	Atmospheric temperature and Humidity sounder	GIFTS	Geosynchronous imaging Fourier transform spectrometer

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
420	NASA	Spectrometer	AIRS	Atmospheric Infrared sounder
421	NASA	Spectrometer	SIRS-A	Satellite infrared spectrometer-A
422	NASA	Spectrometer	SIRS-B	Satellite infrared spectrometer-B
426	NASA	Spectrometer	SOLSTICE	Solar stellar irradiance comparison experiment
430	NASA	Spectrometer	TES	Tropospheric emission spectrometer
431	NASA	Spectrometer	TOMS	Total ozone mapping spectrometer
432	NASA	Spectrometer	OCO	Orbiting carbon observatory
433	NASA	Spectrometer	TMS	TROPICS Millimeter-wave Sounder
434	NASA	MW radiometer	SMAP	Soil Moisture Active-Passive
450	JAXA	Communications	ADEOS Comms	Communications package for ADEOS
451	JAXA	Communications	DCS (JAXA)	Data-collection system (JAXA)
453	NASDA	Communications	GMS Comms	Communications package on GMS
454	NASDA	Communications	JERS-1 Comms	Communications package for JERS-1
460	NASDA	Lidar	RIS	Retroreflector in space
461	NASDA	Radar	PR	Precipitation radar
462	NASDA	Imaging microwave radar	SAR	Synthetic aperture radar
470	JAXA	Imaging microwave radar	PALSAR	Phased array type L-band synthetic aperture radar
478	JAXA	Imaging multi-spectral radiometer (passive microwave)	AMSR2	Advanced Microwave Scanning Radiometer 2
479	JAXA	Imaging multi-spectral radiometer (passive microwave)	AMSR-E	Advanced microwave scanning radiometer – EOS
480	JAXA	High-resolution optical imager	PRISM (ALOS)	Panchromatic remote-sensing instrument for stereo mapping
481	JAXA	Radiometer	AMSR	Advanced microwave scanning radiometer
482	NASDA	High-resolution optical imager	AVNIR	Advanced visible and near infrared radiometer
483	JAXA	High-resolution optical imager	AVNIR-2	Advanced visible and near infrared radiometer type 2
484	JAXA	Imager	GLI	Global imager
485	NASDA	Radiometer	MESSR	Multispectral electronic self scanning radiometer

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
486	NASDA	Radiometer	MSR	Microwave scanning radiometer
487	NASDA	Radiometer	OCTS	Ocean colour and temperature scanner
488	NASDA	Radiometer	OPS	Optical sensor
489	NASDA	Radiometer	VISSR (GMS-5)	Visible and infrared spin scan radiometer (GMS-5)
490	NASDA	Radiometer	VTIR	Visible and thermal infrared radiometer
510	NASDA	Spectrometer	ILAS-I	Improved limb atmospheric spectrometer
511	NASDA	Spectrometer	ILAS-II	Improved limb atmospheric spectrometer
512	NASDA	Spectrometer	IMG	Inferometric monitor of greenhouse gases
514	NASDA	Space environment	SEM	Space environment monitor (NASDA)
515	JAXA	Total and profile ozone	SOFIS	Solar occultation Fourier transform spectrometer for inclined orbit satellite
516	JAXA	Spectrometer	TANSO-FTS	Thermal and Near infrared Sensor for carbon Observations (TANSO) Fourier Transform Spectrometer (FTS)
517	JAXA	Imager	TANSO-CAI	Thermal and Near infrared Sensor for carbon Observations (TANSO) Cloud and Aerosol Imager (CAI)
518	JAXA	Cloud and precipitation radar	DPR	Dual-frequency precipitation radar
519	NASA	MW imaging/sounding radiometer, conical scanning	GMI	GPM microwave imager
<u>520</u>	<u>NASA</u>	<u>Imaging radiometer</u>	<u>SMMR</u>	<u>Scanning Multichannel Microwave Radiometer</u>
526	GeoOptics	GNSS occultation sounder	Cion-A	GeoOptics Cion GNSS occultation receiver A
527	GeoOptics	GNSS occultation sounder	Cion-B	GeoOptics Cion GNSS occultation receiver B
528	GeoOptics	GNSS occultation sounder	Cion-C	GeoOptics Cion GNSS occultation receiver C
529	GeoOptics	GNSS occultation sounder	Cion-D	GeoOptics Cion GNSS occultation receiver D
530	Spire	GNSS occultation sounder	SGNOS-A	Spire global navigation satellite system
531	Spire	GNSS occultation sounder	SGNOS-B	Spire global navigation satellite system occultation sounder

COMMON CODE TABLES

<i>Common code table C-8</i>				
Code	Agency	Type	Instrument short name	Instrument long name
532	Spire	GNSS occultation sounder	SGNOS-C	Spire global navigation satellite system occultation sounder C
533	Spire	GNSS occultation sounder	SGNOS-D	Spire global navigation satellite system occultation sounder D
534	PlanetiQ	GNSS occultation sounder	Pyxis-A	PlanetiQ Pyxis GNSS occultation receiver A
535	PlanetiQ	GNSS occultation sounder	Pyxis-B	PlanetiQ Pyxis GNSS occultation receiver B
540	NOAA	Communications	DCS (NOAA)	Data-collection system (NOAA)
541	NOAA	Communications	GOES Comms	Communications package on GOES
542	NOAA	Communications	LANDSAT Comms	Communications package for LANDSAT
543	NOAA	Communications	NOAA Comms	Communications package for NOAA
544	NOAA	Communications	S&R (GOES)	Search and rescue
545	NOAA	Communications	S&R (NOAA)	Search and rescue
546	NOAA	Communications	WEFAX	Weather facsimile
547	NOAA	Spectrometer	SEM (GOES)	Space environment monitor
550	NOAA	Magnetic field	SSM	Special sensor magnetometer
551	NOAA	Magnetic field	SSJ/4	Special sensor precipitating plasma monitor
552	NOAA	Space environment	SSIES-2	Special sensor ionospheric plasma drift/scintillation meter
553	NOAA	Space environment	SSB/X-2	Special sensor gamma ray particle detector
570	NOAA	Radiometer	AMSU-A	Advanced microwave sounding unit-A
574	NOAA	Radiometer	AMSU-B	Advanced microwave sounding unit-B
580	NOAA	Radiometer	ATOVS (HIRS/3 + AMSU + AVHRR/3)	Advanced TIROS operational vertical sounder
590	NOAA	Radiometer	AVHRR/2	Advanced very high-resolution radiometer/2
591	NOAA	Radiometer	AVHRR/3	Advanced very high-resolution radiometer/3
592	NOAA	Radiometer	AVHRR/4	Advanced very high-resolution radiometer/4
600	NOAA	Radiometer	ERBE	Earth's radiation budget experiment
601	NOAA	Radiometer	ETM+	Enhanced thematic mapper
604	NOAA	Radiometer	HIRS/1	High-resolution infrared sounder/1
605	NOAA	Radiometer	HIRS/2	High-resolution infrared sounder/2

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
606	NOAA	Radiometer	HIRS/3	High-resolution infrared sounder/3
607	NOAA	Radiometer	HIRS/4	High-resolution infrared sounder/4
615	NOAA	Radiometer	IMAGER	Imager
616	NOAA	Imaging multi-spectral radiometer (vis/IR)	VIIRS	Visible/infrared imager radiometer suite
617	NOAA	Imaging multi-spectral radiometer	ABI	Advanced baseline imager
618	NOAA	High-resolution optical imager	GLM	Geostationary lightning mapper
620	NOAA	Atmospheric temperature and humidity sounder	CrIRS/NP	Cross-track infrared sounder/NPOESS
621	NOAA	Atmospheric temperature and humidity sounder	ATMS	Advanced technology microwave sounder
622	NOAA	Radiometer	MSS	Multispectral scanning system
623	NOAA	Radiometer	MSU	Microwave sounding unit
624	NOAA	Radiometer	SBUV/2	Solar backscatter ultraviolet instrument/2
625	NOAA	Radiometer	SBUV/3	Solar backscatter ultraviolet instrument/3
626	NOAA	Radiometer	SOUNDER	SOUNDER
627	NOAA	Radiometer	SSU	Stratospheric sounding unit
628	NOAA	Radiometer	TM	Thematic mapper
629	NOAA	Radiometer	TOVS (HIRS/2 +	TIROS operational vertical sounder MSU + SSU)
630	NOAA	Radiometer	VAS	VISSR atmospheric sounder
631	NOAA	Radiometer	SSZ	
645	NOAA	Spectrometer	SEM	Space environment monitor
650	NRSCC	Radiometer	MVIRSR (10 channel)	Multispectral visible and infrared scan radiometer
651	NRSCC	Radiometer	MVIRSR (3 channel)	Multispectral visible and infrared scan radiometer
652	NRSCC	Radiometer	MVIRSR (5 channel)	Multispectral visible and infrared scan radiometer
670	NSAU	Radar	RLSBO	Side looking microwave radar
680	NSAU	High-resolution optical imager	MSU-EU	Multispectral radiometer with high resolution
681	NSAU	Imaging multi-spectral radiometer (vis/IR)	MSU-UM	Visible multispectral radiometer

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
682	NSAU	Radiometer	RM-08	Imaging microwave radiometer
683	NSAU	High-resolution optical imager	SU-UMS	Stereo radiometer with high resolution
684	NSAU	High-resolution optical imager	SU-VR	Visible radiometer with high resolution
685	NSAU	Radiometer	TRASSER	
686	SOA	Scatterometer	SCAT	Scatterometer
687	SOA	Radar altimeter	ALT	Radar altimeter
688	SOA	Microwave radiometer	MWI	Microwave radiometer
<u>689</u>	<u>ME(NIER)</u>	<u>Spectrometer</u>	<u>GEMS</u>	<u>Geostationary Environmental Monitoring Spectrometer</u>
700	ROSCOSMOS	Communications	KONDOR-2	Data-collection and transmission system
701	ROSCOSMOS	Communications	BRK	
710	ROSCOSMOS	Lidar	ALISSA	Backscatter lidar
712	ROSCOSMOS	Lidar	Balkan-2 lidar	
715	ROSCOSMOS	Lidar	MK-4	
716	ROSCOSMOS	Lidar	MK-4M	
730	ROSCOSMOS	Radar	Greben	Radar altimeter
731	ROSCOSMOS	Radar	SAR-10	Synthetic aperture radar
732	ROSCOSMOS	Radar	SAR-3	Synthetic aperture radar
733	ROSCOSMOS	Radar	SAR-70	Synthetic aperture radar
740	ROSCOSMOS	Radar	SLR-3	Side looking radar
745	ROSCOSMOS	Radar	Travers SAR	
750	ROSCOSMOS	Radiometer	174-K	Temperature and humidity profiler
751	ROSCOSMOS	Radiometer	BTVK	Scanning television radiometer
752	ROSCOSMOS	Radiometer	Chaika	Scanning infrared radiometer
753	ROSCOSMOS	Radiometer	DELTA-2	Multispectral microwave scanner
755	ROSCOSMOS	Radiometer	IKAR-D	Multispectral microwave scanner
756	ROSCOSMOS	Radiometer	IKAR-N	Multispectral microwave scanner
757	ROSCOSMOS	Radiometer	IKAR-P	Multispectral microwave scanner
760	ROSCOSMOS	Radiometer	ISP	
761	ROSCOSMOS	Radiometer	KFA-1000	Photographic camera
762	ROSCOSMOS	Radiometer	KFA-200	Photographic camera
763	ROSCOSMOS	Radiometer	KFA-3000	Photographic camera
770	ROSCOSMOS	Radiometer	Klimat	Scanning infrared radiometer
771	ROSCOSMOS	Radiometer	Klimat-2	Scanning infrared radiometer
775	ROSCOSMOS	Radiometer	MIRAS	
776	ROSCOSMOS	Radiometer	MIVZA	

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
777	ROSCOSMOS	Radiometer	MIVZA-M	Microwave scanning radiometer
780	ROSCOSMOS	Radiometer	MR-2000	
781	ROSCOSMOS	Radiometer	MR-2000M	
785	ROSCOSMOS	Radiometer	MR-900	Scanning telephotometer
786	ROSCOSMOS	Radiometer	MR-900B	Scanning visual band telephotometer
790	ROSCOSMOS	Radiometer	MSU-E	Multispectral high-resolution electronic scanner
791	ROSCOSMOS	Radiometer	MSU-E1	Multispectral high-resolution electronic scanner
792	ROSCOSMOS	Radiometer	MSU-E2	Multispectral high-resolution electronic scanner
793	ROSCOSMOS	Radiometer	MSU-M	
794	ROSCOSMOS	Radiometer	MSU-S	Multispectral medium-resolution scanner
795	ROSCOSMOS	Radiometer	MSU-SK	Multispectral medium-resolution conical scanner
796	ROSCOSMOS	Radiometer	MSU-V	Multispectral high-resolution conical scanner
810	ROSCOSMOS	Radiometer	MTZA	
815	ROSCOSMOS	Imaging multi-spectral radiometer (passive microwave)	MZOAS	Scanning microwave radiometer
820	ROSCOSMOS	Imaging multi-spectral radiometer (passive microwave)	R-225	Single channel microwave radiometer
821	ROSCOSMOS	Radiometer	R-400	
822	ROSCOSMOS	Radiometer	R-600	Single channel microwave radiometer
830	ROSCOSMOS	Radiometer	RMS	Radiation measurement system
835	ROSCOSMOS	Radiometer	TV camera	
836	ROSCOSMOS	Radiometer	SILVA	
840	ROSCOSMOS	Spectro-radiometer	SROSMO	Spectroradiometer for ocean monitoring
850	ROSCOSMOS	Spectrometer	BUFS-2	Backscatter spectrometer/2
851	ROSCOSMOS	Spectrometer	BUFS-4	Backscatter spectrometer/4
855	ROSCOSMOS	Spectrometer	ISTOK-1	Infrared spectrometer
856	ROSCOSMOS	Spectrometer	SFM-2	Spectrometer to measure direct solar radiation
857	ROSCOSMOS	Spectrometer	DOPI	
858	ROSCOSMOS	Spectrometer	KGI-4	
859	ROSCOSMOS	Spectrometer	Ozon-M	

COMMON CODE TABLES

<i>Common code table C-8</i>				
Code	Agency	Type	Instrument short name	Instrument long name
860	ROSCOSMOS	Spectrometer	RMK-2	
861	ROSCOSMOS	Atmospheric temperature and humidity sounder	MTVZA-GY	Module for temperature and humidity
862	ROSCOSMOS	Spectrometer	IKFS-2	Infrared Fourier spectrometer
900	NOAA	Radiometer	MAXIE	Magnetospheric atmospheric X-ray imaging experiment
901	NOAA	Radiometer	OLS	Operational linescan system
905	NOAA	Radiometer	SSM/I	Mission sensor microwave imager
906	NOAA	Radiometer	SSM/T-1	Mission sensor microwave temperature sounder
907	NOAA	Radiometer	SSM/T-2	Mission sensor microwave water vapour sounder
908	NOAA	Radiometer	SSMIS	Special sensor microwave imager sounder
909	NOAA	Radiometer	VTPR	Vertical temperature profile radiometer
910	NOAA	Radiometer	SXI	Solar X-ray imager
930	NOAA	Spectrometer	EHIC	Energetic heavy ion composition experiment
931	NOAA	Spectrometer	X-ray astronomy payload	
932	NRSCC	Imaging multi-spectral radiometer (vis/IR)	IVISSR (FY-2)	Improved multispectral visible and Infrared scan radiometer (5 channels)
933	NRSCC	Atmospheric temperature and humidity sounder	IRAS	Infrared atmospheric sounder
934	NRSCC	Atmospheric temperature and humidity sounder	MWAS	Microwave atmospheric sounder
935	NRSCC	Atmospheric temperature and humidity sounder	IMWAS	Improved Microwave atmospheric sounder
936	NRSCC	Atmospheric temperature and humidity sounder	MWHS	Microwave humidity sounder
937	NRSCC	Imaging multi-spectral radiometer (vis/IR)	MVIRS	Moderate resolution visible and infrared imaging spectroradiometer
938	NRSCC	Imaging multi-spectral radiometer (passive microwave)	MWRI	Microwave radiation imager
940	ROSCOSMOS	Atmospheric temperature and humidity sounder	MTVZA-OK	Scanning microwave radiometer

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
941	CNES	Atmospheric temperature and humidity sounder	SAPHIR	
942	CNES	Microwave imager	MADRAS	Microwave Analysis and Detection of Rain and Atmospheric Structures
943	CNSA	Scatterometer	SCAT (on CFOSAT)	Scatterometer
944	NOAA	Radar altimeter	ALT	Altimeter
945	NOAA	Earth radiation budget radiometer	TSIS	Total solar irradiance sensor
946	NOAA	Imaging multi-spectral radiometer (passive microwave)	CMIS	Conical-scanning microwave imager/sounder
947	NOAA	Total and profile ozone	OMPS- <u>nadir</u>	Ozone mapping and profiler suite
948	NOAA	Space environment	GPSOS atmospheric temperature and humidity sounder	Global positioning system occultation sensor
949	NOAA	Magnetic field, auroal imagery scintillation boundary	SESS	Space environmental sensor suite
950	NRSCC	Imaging multi-spectral radiometer (vis/IR)	VIRR	Multispectral visible and infrared scan radiometer (10 channels)
951	NRSCC	Total and profile ozone	TOM	Total ozone mapper
952	NRSCC	Total and profile ozone	OP	Ozone profiler
953	CMA	Microwave sounding radiometer, crosstrack scanning	MWHS-2	Microwave humidity sounder-2
954	CMA	Microwave sounding radiometer, crosstrack scanning	MWTS-2	Microwave temperature sounder-2
955	CMA	Cross-nadir scanning IR sounder	HIRAS	Hyperspectral infrared atmospheric sounder
956	CMA	Spectrometer	SBUS	Solar backscatter ultraviolet sounder
957	CMA	Spectrometer	TOU	Total ozone unit
958	CMA	GNSS occultation sounder	GNOS	Global navigation satellite system occultation sounder
959	SNSB	Limb-scanning sounder	SMR	Sub-millimetre radiometer
<u>960</u> 960	<u>NASA</u> Reserve d	<u>Total and profile ozone</u>	<u>OMPS-limb</u>	<u>Ozone Mapping and Profiler Suite</u>

COMMON CODE TABLES

Common code table C-8				
Code	Agency	Type	Instrument short name	Instrument long name
961	CMA	Imaging multi-spectral radiometer	AGRI	Advanced Geostationary Radiation Imager
962	CMA	Atmospheric temperature and humidity sounder	GIIRS	Geostationary Interferometric Infrared Sounder
963	CMA	High-resolution optical imager	LMI	Lightning Mapping Imager
964	CMA	Space environment	SEP	Space Environment Package
<u>965</u>	<u>CMA</u>	<u>GNSS occultation</u>	<u>GNOS-2</u>	<u>GNSS radio occultation sounder-2</u>
<u>966</u>	<u>CMA</u>	<u>Microwave sounding radiometer, cross-track scanning</u>	<u>MWTS-3</u>	<u>Microwave temperature sounder-3</u>
965 967-979	Reserved			
980	KMA	Imager	AMI	Advanced Meteorological Imager
981	KMA	Imager	MI	Meteorological Imager
982	KMA	Space environment	KSEM	Korea Space wEather Monitor
983-989		Reserved		
990	NASA	Radiometer	SMMR	Scanning multichannel microwave radiometer
991	NASA	Radiometer	THIR	Temperature-humidity infrared radiometer
<u>992</u>	<u>NASA</u>	<u>Radiometer</u>	<u>NEMS</u>	<u>Nimbus-E Microwave Sounder</u>
<u>993</u>	<u>NASA</u>	<u>Radiometer</u>	<u>SCAMS</u>	<u>Scanning Microwave Spectrometer</u>
<u>994</u>	<u>NASA</u>	<u>Radiometer</u>	<u>ESMR</u>	<u>Electrically Scanning Microwave Radiometer</u>
992 995-999	Reserved			
1000-2046		Reserved for long-term future use		
2047		Missing value		

COMMON CODE TABLES

COMMON CODE TABLE C- 11: Originating/generating centres

Common Code table { BUFR 0 01 035
CREX Edition 2, 00000 in Group P00000ppp in Section 1
GRIB Edition 2, Octets 6-7 in Section 1
BUFR Edition 4, Octets 5-6 in Section 1

Common code table C-11		
CREX Edition 2 B 01 035 (5 characters) and Group 3 in Section 1	GRIB Edition 2 Octets 6-7 in Section 1 BUFR Edition 4 0 01 035 (16 bits) and Octets 5-6 in Section 1	
00000	0	WMO Secretariat
		00001-00009: WMCs
00001	1	Melbourne
00002	2	Melbourne
00003	3)
00004	4	Moscow
00005	5	Moscow
00006	6)
00007	7	US National Weather Service, National Centres for Environmental Prediction (NCEP)
00008	8	US National Weather Service Telecommunications Gateway (NWSTG)
00009	9	US National Weather Service – Other
		00010-00025: Centres in Region I
00010	10	Cairo (RSMC)
00011	11)
00012	12	Dakar (RSMC)
00013	13)
00014	14	Nairobi (RSMC)
00015	15)
00016	16	Casablanca (RSMC)
00017	17	Tunis (RSMC)
00018	18	Tunis-Casablanca (RSMC)
00019	19)
00020	20	Las Palmas
00021	21	Algiers (RSMC)
00022	22	ACMAD
00023	23	Mozambique (NMC)
00024	24	Pretoria (RSMC)
00025	25	La Réunion (RSMC)

COMMON CODE TABLES

Common code table C-11

CREX Edition 2 B 01 035 (5 characters) and Group 3 in Section 1	GRIB Edition 2 Octets 6–7 in Section 1 BUFR Edition 4 0 01 035 (16 bits) and Octets 5–6 in Section 1	
00026–00040: Centres in Region II		
00026	26	Khabarovsk (RSMC)
00027	27)
00028	28	New Delhi (RSMC)
00029	29)
00030	30	Novosibirsk (RSMC)
00031	31)
00032	32	Tashkent (RSMC)
00033	33	Jeddah (RSMC)
00034	34	Tokyo (RSMC), Japan Meteorological Agency
00035	35)
00036	36	Bangkok
00037	37	Ulaanbaatar
00038	38	Beijing (RSMC)
00039	39)
00040	40	Seoul
00041–00050: Centres in Region III		
00041	41	Buenos Aires (RSMC)
00042	42)
00043	43	Brasilia (RSMC)
00044	44)
00045	45	Santiago
00046	46	Brazilian Space Agency - INPE
00047	47	Colombia (NMC)
00048	48	Ecuador (NMC)
00049	49	Peru (NMC)
00050	50	Venezuela (Bolivarian Republic of) (NMC)
00051–00063: Centres in Region IV		
00051	51	Miami (RSMC)
00052	52	Miami RSMC, National Hurricane Centre
00053	53	MSC Monitoring
00054	54	Montreal (RSMC)
00055	55	San Francisco
00056	56	ARINC Centre
00057	57	US Air Force – Air Force Global Weather Central
00058	58	Fleet Numerical Meteorology and Oceanography Center, Monterey, CA, United States
00059	59	The NOAA Forecast Systems Laboratory, Boulder, CO, United States

COMMON CODE TABLES

<i>Common code table C-11</i>		
CREX Edition 2 B 01 035 (5 characters) and Group 3 in Section 1	GRIB Edition 2 Octets 6–7 in Section 1 BUFR Edition 4 0 01 035 (16 bits) and Octets 5–6 in Section 1	
00060	60	United States National Center for Atmospheric Research (NCAR)
00061	61	Service ARGOS – Landover
00062	62	US Naval Oceanographic Office
00063	63	International Research Institute for Climate and Society (IRI)
00064–00073: Centres in Region V		
00064	64	Honolulu (RSMC)
00065	65	Darwin (RSMC)
00066	66)
00067	67	Melbourne (RSMC)
00068	68	Reserved
00069	69	Wellington (RSMC)
00070	70)
00071	71	Nadi (RSMC)
00072	72	Singapore
00073	73	Malaysia (NMC)
00074–00099: Centres in Region VI		
00074	74	UK Meteorological Office – Exeter (RSMC)
00075	75)
00076	76	Moscow (RSMC)
00077	77	Reserved
00078	78	Offenbach (RSMC)
00079	79)
00080	80	Rome (RSMC)
00081	81)
00082	82	Norrköping
00083	83)
00084	84	Toulouse (RSMC)
00085	85	Toulouse (RSMC)
00086	86	Helsinki
00087	87	Belgrade
00088	88	Oslo
00089	89	Prague
00090	90	Episkopi
00091	91	Ankara
00092	92	Frankfurt/Main
00093	93	London (WAFC)
00094	94	Copenhagen
00095	95	Rota
00096	96	Athens

COMMON CODE TABLES

<i>Common code table C-11</i>		
CREX Edition 2 B 01 035 (5 characters) and Group 3 in Section 1	GRIB Edition 2 Octets 6–7 in Section 1 BUFR Edition 4 0 01 035 (16 bits) and Octets 5–6 in Section 1	
00097	97	European Space Agency (ESA)
00098	98	European Centre for Medium Range Weather Forecasts (ECMWF) (RSMC)
00099	99	De Bilt
Additional Centres		
00100	100	Brazzaville
00101	101	Abidjan
00102	102	Libya (NMC)
00103	103	Madagascar (NMC)
00104	104	Mauritius (NMC)
00105	105	Niger (NMC)
00106	106	Seychelles (NMC)
00107	107	Uganda (NMC)
00108	108	United Republic of Tanzania (NMC)
00109	109	Zimbabwe (NMC)
00110	110	Hong Kong, China
00111	111	Afghanistan (NMC)
00112	112	Bahrain (NMC)
00113	113	Bangladesh (NMC)
00114	114	Bhutan (NMC)
00115	115	Cambodia (NMC)
00116	116	Democratic People's Republic of Korea (NMC)
00117	117	Islamic Republic of Iran (NMC)
00118	118	Iraq (NMC)
00119	119	Kazakhstan (NMC)
00120	120	Kuwait (NMC)
00121	121	Kyrgyzstan (NMC)
00122	122	Lao People's Democratic Republic (NMC)
00123	123	Macao, China
00124	124	Maldives (NMC)
00125	125	Myanmar (NMC)
00126	126	Nepal (NMC)
00127	127	Oman (NMC)
00128	128	Pakistan (NMC)
00129	129	Qatar (NMC)
00130	130	Yemen (NMC)
00131	131	Sri Lanka (NMC)
00132	132	Tajikistan (NMC)
00133	133	Turkmenistan (NMC)
00134	134	United Arab Emirates (NMC)

COMMON CODE TABLES

<i>Common code table C-11</i>		
CREX Edition 2 B 01 035 (5 characters) and Group 3 in Section 1	GRIB Edition 2 Octets 6–7 in Section 1 BUFR Edition 4 0 01 035 (16 bits) and Octets 5–6 in Section 1	
00135	135	Uzbekistan (NMC)
00136	136	Viet Nam (NMC)
00137–00139	137–139	Reserved for other centres
00140	140	Bolivia (Plurinational State of) (NMC)
00141	141	Guyana (NMC)
00142	142	Paraguay (NMC)
00143	143	Suriname (NMC)
00144	144	Uruguay (NMC)
00145	145	French Guiana
00146	146	Brazilian Navy Hydrographic Centre
00147	147	National Commission on Space Activities (CONAE) – Argentina
00148	148	Brazilian Department of Airspace Control – DECEA
00149	149	Reserved for other centres
00150	150	Antigua and Barbuda (NMC)
00151	151	Bahamas (NMC)
00152	152	Barbados (NMC)
00153	153	Belize (NMC)
00154	154	British Caribbean Territories Centre
00155	155	San José
00156	156	Cuba (NMC)
00157	157	Dominica (NMC)
00158	158	Dominican Republic (NMC)
00159	159	El Salvador (NMC)
00160	160	US NOAA/NESDIS
00161	161	US NOAA Office of Oceanic and Atmospheric Research
00162	162	Guatemala (NMC)
00163	163	Haiti (NMC)
00164	164	Honduras (NMC)
00165	165	Jamaica (NMC)
00166	166	Mexico
00167	167	Curaçao and Sint Maarten (NMC)
00168	168	Nicaragua (NMC)
00169	169	Panama (NMC)
00170	170	Saint Lucia (NMC)
00171	171	Trinidad and Tobago (NMC)
00172	172	French Departments in RA IV
00173	173	US National Aeronautics and Space Administration (NASA)
00174	174	Integrated Science Data Management/Marine Environmental Data Service (ISDM/MEDS – Canada)

COMMON CODE TABLES

Common code table C-11

CREX Edition 2 B 01 035 (5 characters) and Group 3 in Section 1	GRIB Edition 2 Octets 6-7 in Section 1 BUFR Edition 4 0 01 035 (16 bits) and Octets 5-6 in Section 1	
00175	175	University Corporation for Atmospheric Research (UCAR) – United States
00176	176	Cooperative Institute for Meteorological Satellite Studies (CIMSS) – United States
00177	177	NOAA National Ocean Service – United States
00178	178	Spire Global, Inc.
00179	179	GeoOptics, Inc.
00180	180	PlanetiQ
00181-00189	181-189	Reserved for other centres
00190	190	Cook Islands (NMC)
00191	191	French Polynesia (NMC)
00192	192	Tonga (NMC)
00193	193	Vanuatu (NMC)
00194	194	Brunei Darussalam (NMC)
00195	195	Indonesia (NMC)
00196	196	Kiribati (NMC)
00197	197	Federated States of Micronesia (NMC)
00198	198	New Caledonia (NMC)
00199	199	Niue
00200	200	Papua New Guinea (NMC)
00201	201	Philippines (NMC)
00202	202	Samoa (NMC)
00203	203	Solomon Islands (NMC)
00204	204	National Institute of Water and Atmospheric Research (NIWA) – New Zealand
00205-00209	205-209	Reserved for other centres
00210	210	Frascati (ESA/ESRIN)
00211	211	Lannion
00212	212	Lisboa
00213	213	Reykjavik
00214	214	Madrid
00215	215	Zurich
00216	216	Service ARGOS Toulouse
00217	217	Bratislava
00218	218	Budapest
00219	219	Ljubljana
00220	220	Warsaw
00221	221	Zagreb
00222	222	Albania (NMC)
00223	223	Armenia (NMC)
00224	224	Austria (NMC)

COMMON CODE TABLES

<i>Common code table C-11</i>		
CREX Edition 2 B 01 035 (5 characters) and Group 3 in Section 1	GRIB Edition 2 Octets 6–7 in Section 1 BUFR Edition 4 0 01 035 (16 bits) and Octets 5–6 in Section 1	
00225	225	Azerbaijan (NMC)
00226	226	Belarus (NMC)
00227	227	Belgium (NMC)
00228	228	Bosnia and Herzegovina (NMC)
00229	229	Bulgaria (NMC)
00230	230	Cyprus (NMC)
00231	231	Estonia (NMC)
00232	232	Georgia (NMC)
00233	233	Dublin
00234	234	Israel (NMC)
00235	235	Jordan (NMC)
00236	236	Latvia (NMC)
00237	237	Lebanon (NMC)
00238	238	Lithuania (NMC)
00239	239	Luxembourg
00240	240	Malta (NMC)
00241	241	Monaco
00242	242	Romania (NMC)
00243	243	Syrian Arab Republic (NMC)
00244	244	North Macedonia (NMC)
00245	245	Ukraine (NMC)
00246	246	Republic of Moldova (NMC)
00247	247	Operational Programme for the Exchange of weather RAdar information (OPERA) – EUMETNET
00248	248	Montenegro (NMC)
00249	249	Barcelona Dust Forecast Center
00250	250	Consortium for Small scale MOdelling (COSMO)
00251	251	Meteorological Cooperation on Operational NWP (MetCoOp)
00252	252	Max Planck Institute for Meteorology (MPI-M)
00253	253	Reserved for other centres
00254	254	EUMETSAT Operation Centre
00255	255	Not to be used
00256	256	Angola (NMC)
00257	257	Benin (NMC)
00258	258	Botswana (NMC)
00259	259	Burkina Faso (NMC)
00260	260	Burundi (NMC)
00261	261	Cameroon (NMC)
00262	262	Cabo Verde (NMC)
00263	263	Central African Republic (NMC)

COMMON CODE TABLES

<i>Common code table C-11</i>		
CREX Edition 2 B 01 035 (5 characters) and Group 3 in Section 1	GRIB Edition 2 Octets 6–7 in Section 1 BUFR Edition 4 0 01 035 (16 bits) and Octets 5–6 in Section 1	
00264	264	Chad (NMC)
00265	265	Comoros (NMC)
00266	266	Democratic Republic of the Congo (NMC)
00267	267	Djibouti (NMC)
00268	268	Eritrea (NMC)
00269	269	Ethiopia (NMC)
00270	270	Gabon (NMC)
00271	271	Gambia (NMC)
00272	272	Ghana (NMC)
00273	273	Guinea (NMC)
00274	274	Guinea-Bissau (NMC)
00275	275	Lesotho (NMC)
00276	276	Liberia (NMC)
00277	277	Malawi (NMC)
00278	278	Mali (NMC)
00279	279	Mauritania (NMC)
00280	280	Namibia (NMC)
00281	281	Nigeria (NMC)
00282	282	Rwanda (NMC)
00283	283	Sao Tome and Principe (NMC)
00284	284	Sierra Leone (NMC)
00285	285	Somalia (NMC)
00286	286	Sudan (NMC)
00287	287	Eswatini (NMC)
00288	288	Togo (NMC)
00289	289	Zambia (NMC)
00290	290	EUMETNET E-Profile
00291	291	Institute of Atmospheric Physics (IAP) of the Chinese Academy of Sciences (CAS)
00292	292	Helmholtz Centre for Environmental Research (UFZ)
00293–65534	292–65534	Reserved for other centres
65535	65535	Missing value
65536–99999	Not applicable	Not used

Notes:

- (1) The closed bracket sign ")" indicates that the corresponding code figure is reserved for the previously named centre.

COMMON CODE TABLES

- (2) With GRIB or BUFR, to indicate whether the originating/generating centre is a sub-centre or not, the following procedure should be applied:

In GRIB edition 2, use octets 8–9 of section 1, or in BUFR edition 4, use octets 7–8 of section 1, with the following meaning:

Code figure

- | | |
|----------|---|
| 0 | Not a sub-centre, the originating/generating centre is the centre defined by octets 6–7 in section 1 of GRIB edition 2, or by octets 5–6 in section 1 of BUFR edition 4. |
| 1 to 254 | Identifier of the sub-centre which is the originating/generating centre. The identifier of the sub-centre is allocated by the associated centre, which is defined by octets 6–7 in section 1 of GRIB edition 2 or by octets 5–6 in section 1 of BUFR edition 4. The sub-centre identifiers should be supplied to the WMO Secretariat by the associated centre(s) for publication. |
- (3) For the definitions of sub-centres provided to the WMO Secretariat, see Common Code table C–12.

Provisional Copy
2023

COMMON CODE TABLES

COMMON CODE TABLE C-12: Sub-centres of originating centres defined by entries in Common Code tables C-1 or C-11

Common code table C-12			
ORIGINATING CENTRES C-1, C-11 or C-12		SUB-CENTRES	
		BUFR 0 01 034 BUFR Edition 3, Octet 5 in Section 1 BUFR Edition 4, Octets 7-8 in Section 1 GRIB Edition 1, Octet 26 in Section 1 GRIB Edition 2, Octets 8-9 in Section 1 CREX Edition 2, ppp in Group Pooooopp in Section 1	
Code figure	Name	Code figure	Name
REGION II		0	No sub-centre
34	Tokyo (RSMC), Japan Meteorological Agency	207	Syowa
		240	Kiyose
		241	Reanalysis project
39	Beijing (RSMC)	225	Beijing
		226	Guangzhou
		228	Urumuqi
40	Seoul	243	Seoul
		245	Jincheon
110	Hong-Kong, China	229	Hong-Kong
REGION III		10	Cachoeira Paulista (INPE)
46	Brazilian Space Agency – INPE	11	Cuiaba (INPE)
		12	Brasilia (SEPIS – INMET)
		13	Fortaleza (FUNCEME)
		14	Natal (Navy Hygrog. Centre)
		15	Manaus (SIVAM)
		16	Natal (INPE)
		17	Boa Vista
		18	SIPAM-Porto Velho-RO
		19	SIPAM-Belém-PA
		25	São Paulo University – USP
<u>145</u>	<u>French Guiana</u>	<u>1</u>	<u>DBNet station of Cayenne (French Guiana)</u>
147	National Commission on Space Activities (CONAE) – Argentina	10	Córdoba
		15	Ushuaia
		20	Marambio
		30	Santiago de Chile
		40	Punta Arenas
		50	Base Presidente Frei
		60	Cotopaxi
148	Brazilian Department of Airspace Control – DECEA	1	Integrated Center of Aeronautical Meteorology – CIMAER

COMMON CODE TABLES

Common code table C-12

ORIGINATING CENTRES C-1, C-11 or C-12		SUB-CENTRES	
		BUFR 0 01 034 BUFR Edition 3, Octet 5 in Section 1 BUFR Edition 4, Octets 7-8 in Section 1 GRIB Edition 1, Octet 26 in Section 1 GRIB Edition 2, Octets 8-9 in Section 1 CREX Edition 2, ppp in Group Pooooopp in Section 1	
Code figure	Name	Code figure	Name
REGION IV			
7	US National Weather Service, NCEP	1	NCEP Reanalysis Project
		2	NCEP Ensemble Products
		3	NCEP Central Operations
		4	Environmental Modeling Center
		5	Weather Prediction Center
		6	Ocean Prediction Center
		7	Climate Prediction Center
		8	Aviation Weather Center
		9	Storm Prediction Center
		10	National Hurricane Center
		11	NWS Techniques Development Laboratory
		12	NESDIS Office of Research and Applications
		13	Federal Aviation Administration
		14	NWS Meteorological Development Laboratory
		15	North American Regional Reanalysis Project
		16	Space Weather Prediction Center
		17	ESRL Global Systems Division
160	United States NOAA/NESDIS	1	National Climatic Data Center
		2	National Geophysical Data Center
		3	National Oceanographic Data Center
		4	Center for Satellite Applications and Research (STAR)
		5	Joint Polar Satellite System
		10	Tromso (Norway)
		11	McMurdo (Antarctica)
161	United States NOAA Office of Oceanic and Atmospheric Research (NOAA/OAR)	1	Great Lakes Environmental Research Laboratory
		2	Earth System Research Laboratory
		3	Atlantic Oceanographic and Meteorological Laboratory
		4	Pacific Marine Environmental Laboratory
		5	Air Resources Laboratory
		6	Geophysical Fluid Dynamics Laboratory
		7	National Severe Storms Laboratory

COMMON CODE TABLES

Common code table C-12

ORIGINATING CENTRES C-1, C-11 or C-12		SUB-CENTRES	
		BUFR 0 01 034 BUFR Edition 3, Octet 5 in Section 1 BUFR Edition 4, Octets 7-8 in Section 1 GRIB Edition 1, Octet 26 in Section 1 GRIB Edition 2, Octets 8-9 in Section 1 CREX Edition 2, ppp in Group Pooooopp in Section 1	
Code figure	Name	Code figure	Name
REGION IV (continued)			
173	United States National Aeronautics and Space Administration (NASA)	1	Ames Research Center
		2	Dryden Flight Research Center
		3	Glenn Research Center
		4	Goddard Space Flight Center
		5	Jet Propulsion Laboratory
		6	Johnson Space Center
		7	Kennedy Space Center
		8	Langley Research Center
		9	Marshall Space Flight Center
		10	Stennis Space Center
		11	Goddard Institute for Space Studies
		12	Independent Verification and Validation Facility
		13	NASA Shared Service Center
		14	Wallops Flight Facility
176	Cooperative Institute for Meteorological Satellite Studies (CIMSS) -United States	10	Tromso (Norway)
		11	McMurdo (Antarctica)
		12	Sodankyla (Finland)
		13	Fairbanks (United States)
		14	Barrow (United States)
		15	Rothera (Antarctica)
		20	Honolulu (United States)
		21	Gilmore Creek (United States)
		22	Madison (United States)
		23	Miami (United States)
		24	Mayaguez (Puerto Rico)
		25	Monterey (United States)
		26	Guam
		27	Corvallis (United States)
		28	Hampton (United States)
		29	New York City (United States)
177	NOAA National Ocean Service - United States	1	Center for Operational Oceanographic Products and Services
		2	Coast Survey Development Laboratory

COMMON CODE TABLES

Common code table C-12

ORIGINATING CENTRES C-1, C-11 or C-12		SUB-CENTRES	
		BUFR 0 01 034 BUFR Edition 3, Octet 5 in Section 1 BUFR Edition 4, Octets 7-8 in Section 1 GRIB Edition 1, Octet 26 in Section 1 GRIB Edition 2, Octets 8-9 in Section 1 CREX Edition 2, ppp in Group Pooooopp in Section 1	
Code figure	Name	Code figure	Name
REGION V			
2	Melbourne	201	Casey
		203	Davis
		210	Alice Springs
		211	Melbourne Crib Point 1
		214	Darwin
		217	Perth
		219	Townsville
		232	Fiji
		235	Noumea
		237	Papeete
		250	Vladivostock
		251	Guam
		252	Honolulu
69	Wellington (RSMC)	204	National Institute of Water and Atmospheric Research (NIWA – New Zealand)
		205	Niue
		206	Rarotonga (Cook Islands)
		207	Apia (Samoa)
		208	Tonga
		209	Tuvalu
		210	Kiribati
		211	Tokelau
		243	Kelburn
72	Singapore	249	Singapore
191	French Polynesia (NMC)	1	RARS station of Tahiti (French Polynesia)
204	National Institute of Water and Atmospheric Research (NIWA – New Zealand)	101	Maupuia
		102	Lauder

COMMON CODE TABLES

Common code table C-12

ORIGINATING CENTRES C-1, C-11 or C-12		SUB-CENTRES	
		BUFR 0 01 034 BUFR Edition 3, Octet 5 in Section 1 BUFR Edition 4, Octets 7-8 in Section 1 GRIB Edition 1, Octet 26 in Section 1 GRIB Edition 2, Octets 8-9 in Section 1 CREX Edition 2, ppp in Group Pooooopp in Section 1	
Code figure	Name	Code figure	Name
REGION VI			
74	UK Met Office, Exeter (RSMC)	1	Shanwick Oceanic Area Control Centre
		2	Fucino
		3	Gatineau
		4	Maspalomas (Spain)
		5	ESA ERS Central Facility
		6	Prince Albert
		7	West Freugh
		13	Tromsø
		21	Agenzia Spaziale Italiana (Italy)
		22	Centre National de la Recherche Scientifique (France)
		23	GeoForschungs Zentrum (Germany)
		24	Geodetic Observatory Pecny (Czechia)
		25	Institut d'Estudis Espacials de Catalunya (Spain)
		26	Federal Office of Topography (Switzerland)
		27	Nordic Commission of Geodesy (Norway)
		28	Nordic Commission of Geodesy (Sweden)
		29	Institute Géographique National (France) – Service de géodésie
		30	Bundesamt für Kartographie und Geodäsie (Germany)
		31	Institute of Engineering Satellite Surveying and Geodesy (United Kingdom)
		32	Joint Operational Meteorology and Oceanography Centre (JOMOC)
		33	Koninklijk Nederlands Meteorologisch Instituut (Netherlands)
		34	Nordic GPS Atmospheric Analysis centre (Sweden)
		35	Instituto Geografico Nacional de España (Spain)
		36	Met Éireann (Ireland)
		37	Royal Observatory of Belgium (Belgium)

COMMON CODE TABLES

Common code table C-12

ORIGINATING CENTRES C-1, C-11 or C-12		SUB-CENTRES	
		BUFR 0 01 034 BUFR Edition 3, Octet 5 in Section 1 BUFR Edition 4, Octets 7-8 in Section 1 GRIB Edition 1, Octet 26 in Section 1 GRIB Edition 2, Octets 8-9 in Section 1 CREX Edition 2, ppp in Group Poooooppp in Section 1	
Code figure	Name	Code figure	Name
REGION VI (continued)			
78	Offenbach (RSMC)	10	POLARA (Polarimetric Radar Algorithms instance)
		64	Bundeswehr Geoinformation Office (BGIO)
		110	NowCast mobile (Lightning data)
		221	Schleswig-Holstein, Traffic Operations Computing Centre (TOCC) Kiel/Neumünster
		222	Hamburg, TOCC Hamburg
		223	Niedersachsen, TOCC Hannover
		224	Austria (NMC)
		225	Nordrhein-Westfalen, TOCC Kamen
			Leverkusen
		226	Hessen, TOCC Rüsselsheim
		227	Rheinland-Pfalz, TOCC Koblenz
		228	Baden-Württemberg, TOCC Ludwigsburg
		229	Bayern, TOCC Freimann
		230	Saarland, TOCC Rohrbach
		231	Bayern, Autobahn directorate Nordbayern
		232	Brandenburg, TOCC Stolpe
		233	Mecklenburg-Vorpommern, TOCC Malchow
		234	Sachsen, TOCC Dresden
		235	Sachsen-Anhalt, TOCC Halle
		236	Thüringen, TOCC Erfurt
		237	EasyWay – Meteotrans
		254	EUMETSAT
80	Rome (RSMC)	101	Albania (NMC)
		102	National Research Council/Institute of Atmospheric Sciences and Climate (CNR-ISAC)
85	Toulouse (RSMC)	200	Institut National de l'Environnement Industriel et des Risques (France)
		201	Rheinisches Institut für Umweltforschung an der Universität zu Köln E.V. (Germany)

COMMON CODE TABLES

Common code table C-12

ORIGINATING CENTRES C-1, C-11 or C-12		SUB-CENTRES	
		BUFR 0 01 034 BUFR Edition 3, Octet 5 in Section 1 BUFR Edition 4, Octets 7-8 in Section 1 GRIB Edition 1, Octet 26 in Section 1 GRIB Edition 2, Octets 8-9 in Section 1 CREX Edition 2, ppp in Group Pooooopp in Section 1	
Code figure	Name	Code figure	Name
REGION VI (continued)			
85	Toulouse (RSMC)	202	Institut Français de Recherche pour l'Exploitation de la Mer
		203	Aarhus University (Denmark)
		204	Institute of Environmental Protection – National Research Institute (Poland)
89	Prague (RTH)	1	Solar and Ozone Observatory Hradec Kralove
96	Athens	1	Cyprus (NMC)
211	Lannion	10	Saint-Denis (La Réunion)
227	Belgium (NMC)	1	Luxembourg (NMC)
250	COSMO (COnsortium for Small scale MOdelling)	76	Roshydromet (Russian Federation)
		78	Deutscher Wetterdienst (Germany)
		80	Ufficio Generale Spazio Aereo e Meteorologia (Italy)
		96	Hellenic National Meteorological Service (Greece)
		215	MeteoSwiss (Switzerland)
		220	Institute of Meteorology and Water Management (Poland)
		242	National Meteorological Administration (Romania)
254	EUMETSAT Operation Centre	10	Tromso (Norway)
		20	Maspalomas (Spain)
		30	Kangerlussuaq (Greenland)
		40	Edmonton (Canada)
		50	Bedford (Canada)
		60	Gander (Canada)
		70	Monterey (United States)
		80	Wallops Island (United States)
		90	Gilmor Creek (United States)
		100	Athens (Greece)

COMMON CODE TABLES

Common code table C-12

ORIGINATING CENTRES C-1, C-11 or C-12		SUB-CENTRES	
		BUFR 0 01 034 BUFR Edition 3, Octet 5 in Section 1 BUFR Edition 4, Octets 7-8 in Section 1 GRIB Edition 1, Octet 26 in Section 1 GRIB Edition 2, Octets 8-9 in Section 1 CREX Edition 2, ppp in Group Pooooopp in Section 1	
Code figure	Name	Code figure	Name
REGION VI <i>(continued)</i>			
254	EUMETSAT Operation Centre	120	Ewa Beach, Hawaii
		125	Ford Island, Hawaii
		130	Miami, Florida
		140	Lannion (France)
		150	Svalbard (Norway)
		170	Saint-Denis (La Réunion)
254	EUMETSAT Operation Centre	180	Moscow
		190	Muscat
		200	Khabarovsk
		210	Novosibirsk
		220	<u>NOAA Satellite Operations Facility (NSOF)</u>

COMMON CODE TABLES

COMMON CODE TABLE C-13: Data sub-categories of categories defined by entries in BUFR Table A

Common code table C-13			
DATA CATEGORIES		INTERNATIONAL DATA SUB-CATEGORIES	
BUFR Edition 4, Octet 11 in Section 1 CREX Edition 2, nnn in Group		BUFR Edition 4, Octet 12 (if = 255, it means other sub-category or undefined)	
Annnmmm of Section 1		CREX Edition 2, mmm in Group Annnmmm of Section 1	
Code figure	Name	Code figure	Name (corresponding traditional alphanumeric codes are in brackets)
0	Surface data – land	0	Hourly synoptic observations from fixed-land stations (SYNOP)
		1	Intermediate synoptic observations from fixed-land stations (SYNOP)
		2	Main synoptic observations from fixed-land stations (SYNOP)
		3	Hourly synoptic observations from mobile-land stations (SYNOP MOBIL)
		4	Intermediate synoptic observations from mobile-land stations (SYNOP MOBIL)
		5	Main synoptic observations from mobile-land stations (SYNOP MOBIL)
		6	One-hour observations from automated stations
		7	n-minute observations from AWS stations
		8	Radiation observations from one-hour period
		9	Radiation observations from n-minute period
		10	Routine aeronautical observations (METAR)
		11	Special aeronautical observations (SPECI)
		14	Ground-based GPS humidity observations (GPSIWV)
		20	Climatological observations (CLIMAT)
		21	Climatological observations (monthly reports of daily climate data)
		30	Sferics locations
		40	Hydrologic reports
		50	Hourly synoptic observations with supplementary one-hour data
		51	Intermediate synoptic observations with supplementary one-hour data
		52	Main synoptic observations with supplementary one- hour data
1	Surface data – sea	0	Synoptic observations (SHIP)
		6	One-hour observations from automated stations
		7	n-minute observations from AWS stations
		15	Uncrewed surface vehicle
		20	Climatological observations (CLIMAT SHIP)
		25	Buoy observation (BUOY)
		30	Tide gauge
		31	Observed water level time series

COMMON CODE TABLES

Common code table C-13

DATA CATEGORIES		INTERNATIONAL DATA SUB-CATEGORIES	
BUFR Edition 4, Octet 11 in Section 1 CREX Edition 2, nnn in Group		BUFR Edition 4, Octet 12 (if = 255, it means other sub-category or undefined)	
Annnmmm of Section 1		CREX Edition 2, mmm in Group Annnmmm of Section 1	
Code figure	Name	Code figure	Name (corresponding traditional alphanumeric codes are in brackets)
2	Vertical soundings (other than satellite)	1	Upper-wind reports from fixed-land stations (PILOT)
		2	Upper-wind reports from ships (PILOT SHIP)
		3	Upper-wind reports from mobile land stations (PILOT MOBIL)
		4	Upper-level temperature/humidity/wind reports from fixed-land stations (TEMP)
		5	Upper-level temperature/humidity/wind reports from ships (TEMP SHIP)
		6	Upper-level temperature/humidity/wind report from mobile land stations (TEMP MOBIL)
		7	Upper-level temperature/humidity/wind reports from dropwindsondes (TEMP DROP)
		10	Wind profiler reports
		11	RASS temperature profiles
		14	Upper-level temperature/humidity/wind reports from descent radiosondes originally launched from fixed land stations
		15	Upper-level temperature/humidity/wind reports from descent radiosondes originally launched from ships
		16	Upper-level temperature/humidity/wind reports from descent radiosondes originally launched from mobile land stations
		20	ASDAR/ACARS profiles (AMDAR)
		21	Profiles of atmospheric constituents concentrations
		25	Climatological observations from fixed-land stations (CLIMAT TEMP)
		26	Climatological observations from ships (CLIMAT TEMP SHIP)
3	Vertical soundings (satellite)	0	Temperature (SATEM)
		1	TIROS (TOVS)
		2	ATOVS
		3	AMSU-A
		4	AMSU-B
		5	HIRS
		6	MHS
		7	IASI
		8	VASS (Vertical atmospheric sounding system)
		20	IR temperature/humidity sounding
		30	Hyperspectral temperature/humidity sounding
		40	MW temperature/humidity sounding
		50	Radio occultation sounding

COMMON CODE TABLES

Common code table C-13			
DATA CATEGORIES		INTERNATIONAL DATA SUB-CATEGORIES	
BUFR Edition 4, Octet 11 in Section 1 CREX Edition 2, nnn in Group		BUFR Edition 4, Octet 12 (if = 255, it means other sub-category or undefined)	
Annnmmm of Section 1		CREX Edition 2, mmm in Group Annnmmm of Section 1	
Code figure	Name	Code figure	Name (corresponding traditional alphanumeric codes are in brackets)
4	Single level upper-air data (other than satellite)	0	ASDAR/ACARS (AMDAR)
		1	Manual (AIREP, PIREP)
		2	Mode-S
5	Single level upper-air data (satellite)	0	Cloud wind data (SATOB)
		1	Cloud properties
6	Radar data	0	Reflectivity data
		1	Doppler wind profiles
		2	Derived products
		3	Ground radar weather (RADOB)
7	Synoptic features	0	Forecast tropical cyclone tracks from EPS
		1	Squall line
		2	Forecast tropical cyclone from deterministic system
8	Physical/chemical constituents	0	Surface ozone
		1	Ozone vertical sounding
		2	Total ozone
		3	Acid rain
		4	<u>Aerosol</u>
9	Dispersal and transport	0	Trajectories, analysis or forecast
10	Radiological data	1	Observation (RADREP)
		2	Forecast (RADOF)
12	Surface data (satellite)	0	ERS-uwa
		1	ERS-uwi
		2	ERS-ura
		3	ERS-uat
		4	SSM/I radiometer
		5	Quikscat
		6	Surface temp./radiation (SATOB)
		7	ASCAT data
		8	Soil moisture
		9	Normalized differential vegetation index (NDVI)
		10	Normalized radar backscatter
		11	Surface emissivity
		12	Sea-surface temperature
		13	Precipitation

COMMON CODE TABLES

Common code table C-13			
DATA CATEGORIES		INTERNATIONAL DATA SUB-CATEGORIES	
BUFR Edition 4, Octet 11 in Section 1 CREX Edition 2, nnn in Group		BUFR Edition 4, Octet 12 (if = 255, it means other sub-category or undefined)	
Annnmmm of Section 1		CREX Edition 2, mmm in Group Annnmmm of Section 1	
Code figure	Name	Code figure	Name (corresponding traditional alphanumeric codes are in brackets)
21	Radiances (satellite measured)	0	Earth radiation budget
		5	Cross-track infrared sounder
		6	Advanced technology microwave sounder
		7	Visible/infrared imager radiometer suite
22	Radar (satellite) but not altimeter and scatterometer	0	Cloud and precipitation radar
		1	Synthetic aperture radar
23	Lidar (satellite)	0	Lidar based missions (for wind, for cloud/aerosol, for water vapour, for altimetry)
24	Scatterometry (satellite)	0	Wind scatterometry
25	Altimetry (satellite)	0	Radar altimetry
26	Spectrometry (satellite)	0	Cross nadir short-wave spectrometry (for chemistry)
		1	Cross nadir IR spectrometry (for chemistry)
		2	Limb sounding short-wave spectrometry
		3	Limb sounding IR spectrometry
		4	Limb sounding sub-millimetre wave spectrometry
30	Calibration dataset (satellite)	0	Subsetted data
		1	Collocated data
		2	On-board calibration data
		3	Bias monitoring
		4	Near-real-time correction
		5	Re-analysis correction
31	Oceanographic data	0	Surface observation
		1	Surface observation along track (TRACKOB)
		2	Spectral wave observation (WAVEOB)
		3	Bathythermal observation (BATHY)
		4	Subsurface floats (profile)
		5	XBT/XCTD profiles (TESAC)
		6	Waves reports
		7	Tsunameter data
		8	<u>Glider data</u>
32	Lidar (ground-based)	0	Wind, cloud, aerosol

COMMON CODE TABLES

Common code table C-13			
DATA CATEGORIES		INTERNATIONAL DATA SUB-CATEGORIES	
BUFR Edition 4, Octet 11 in Section 1 CREX Edition 2, nnn in Group		BUFR Edition 4, Octet 12 (if = 255, it means other sub-category or undefined)	
Annnmmm of Section 1		CREX Edition 2, mmm in Group Annnmmm of Section 1	
Code figure	Name	Code figure	Name (corresponding traditional alphanumeric codes are in brackets)
101	Image data (satellite)	0	Multi-purpose VIS/IR imagery
		1	Conical scanning MW imagery (intermediate frequencies)
		2	Low frequency MW imagery
		3	Ocean colour imagery
		4	Imagery with special viewing geometry
		5	Lightning imagery
		6	High-resolution short-wave imagery for land observation
		7	SMOS data

COMMON CODE TABLES

COMMON CODE TABLE C-14: Atmospheric chemical or physical constituent type

Common Code table { Code table 4.230 in GRIB Edition 2
Code table 0 08 046 in BUFR

<i>Common code table C-14</i>		
Code figure	Meaning	Chemical formula
0	Ozone	O ₃
1	Water vapour	H ₂ O
2	Methane	CH ₄
3	Carbon dioxide	CO ₂
4	Carbon monoxide	CO
5	Nitrogen dioxide	NO ₂
6	Nitrous oxide	N ₂ O
7	Formaldehyde	HCHO
8	Sulphur dioxide	SO ₂
9	Ammonia	NH ₃
10	Ammonium cation	NH ₄ ⁺
11	Nitrogen monoxide	NO
12	Atomic oxygen	O
13	Nitrate radical	NO ₃ •
14	Hydroperoxyl radical	HOO•
15	Dinitrogen pentoxide	N ₂ O ₅
16	Nitrous acid	HONO
17	Nitric acid	HNO ₃
18	Peroxynitric acid	HO ₂ NO ₂
19	Hydrogen peroxide	H ₂ O ₂
20	Dihydrogen	H ₂
21	Atomic nitrogen	N
22	Sulphate anion	SO ₄ ²⁻
23	Atomic Radon	Rn
24	Mercury vapour	Hg(0)
25	Mercury(II) cation	Hg ²⁺
26	Atomic chlorine	Cl
27	Chlorine monoxide	ClO
28	Dichlorine peroxide	Cl ₂ O ₂
29	Hypochlorous acid	HClO
30	Chlorine nitrate	ClONO ₂
31	Chlorine dioxide	ClO ₂
32	Atomic bromine	Br
33	Bromine monoxide	BrO
34	Bromine chloride	BrCl
35	Hydrogen bromide	HBr
36	Hypobromous acid	HBrO
37	Bromine nitrate	BrONO ₂
38	Dioxygen	O ₂
39	Nitryl chloride	NO ₂ Cl
40	Sulphuric acid	H ₂ SO ₄

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
41	Hydrogen sulphide	H ₂ S
42	Sulphur trioxide	SO ₃
43	Bromine	Br ₂
44	Hydrofluoric acid	HF
45	Sulphur hexafluoride	SF ₆
46	Chlorine	Cl ₂
47-9999	Reserved	
10000	Hydroxyl radical	HO•
10001	Methyl peroxy radical	CH ₃ OO•
10002	Methyl hydroperoxide	CH ₃ O ₂ H
<u>10002</u>	<u>Methyl hydroperoxide</u>	<u>CH₃OOH</u>
10004	Methanol	CH ₃ OH
10005	Formic acid	HCOOH
10006	Hydrogen cyanide	HCN
10007	Aceto nitrile	CH ₃ CN
10008	Ethane	C ₂ H ₆
10009	Ethene (= Ethylene)	C ₂ H ₄
10010	Ethyne (= Acetylene)	C ₂ H ₂
10011	Ethanol	C ₂ H ₅ OH
10012	Acetic acid	C ₂ H ₅ OOH
10013	Peroxyacetyl nitrate	CH ₃ C(O)OONO ₂
10014	Propane	C ₃ H ₈
10015	Propene	C ₃ H ₆
10016	Butanes (all isomers)	C ₄ H ₁₀
10017	Isoprene	C ₅ H ₁₀
10018	Alpha pinene	C ₁₀ H ₁₆
10019	Beta pinene	C ₁₀ H ₁₆
10020	Limonene	C ₁₀ H ₁₆
10021	Benzene	C ₆ H ₆
10022	Toluene	C ₇ H ₈
10023	Xylene	C ₈ H ₁₀
10024	Methanesulphonic acid	CH ₃ SO ₃ H
10025	Methylglyoxal (2-oxopropanal)	CH ₃ C(O)CHO
10026	Peroxyacetyl radical	CH ₃ C(O)OO•
10027	Methacrylic acid (2-methylprop-2-enoic acid)	CH ₂ C(CH ₃)COOH
10028	Methacrolein (2-methylprop-2-enal)	CH ₂ C(CH ₃)CHO
10029	Acetone (propan-2-one)	CH ₃ C(O)CH ₃
10030	Ethyl dioxidanyl radical	CH ₃ CH ₂ OO•
10031	Butadiene (buta-1,3-diene)	(CH ₂ CH) ₂
10032	Acetaldehyde (ethanal)	CH ₃ CHO
10033	Glycolaldehyde (hydroxyethanal)	HOCH ₂ CHO
10034	Cresol (methylphenol), all isomers	CH ₃ C ₆ H ₄ OH
10035	Peracetic acid (ethaneperoxoic acid)	CH ₃ C(O)OOH
10036	2-hydroxyethyl oxidanyl radical	HOCH ₂ CH ₂ O•
10037	2-hydroxyethyl dioxidanyl radical	HOCH ₂ CH ₂ OO•
10038	Glyoxal (oxaldehyde)	OCHCHO
10039	Isopropyl dioxidanyl radical	(CH ₃) ₂ CHOO•
10040	Isopropyl hydroperoxide (2-hydroperoxypropane)	(CH ₃) ₂ CHOOH

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
10041	Hydroxyacetone (1-hydroxypropan-2-one)	$\text{CH}_3\text{C}(\text{O})\text{CH}_2\text{OH}$
10042	Peroxyacetic acid (ethaneperoxoic acid)	$\text{CH}_3\text{C}(\text{O})\text{OOH}$
10043	Methyl vinyl ketone (but-3-en-2-one)	$\text{CH}_3\text{C}(\text{O})\text{CHCH}_2$
10044	Phenoxy radical	$\text{C}_6\text{H}_5\text{O}\bullet$
10045	Methyl radical	$\text{CH}_3\bullet$
10046	Carbonyl sulphide (carbon oxide sulphide)	OCS
10047	Dibromomethane	CH_2Br_2
10048	Methoxy radical	$\text{CH}_3\text{O}\bullet$
10049	Tribromomethane	CHBr_3
10050	Formyl radical (oxomethyl radical)	$\text{HOC}\bullet$
10051	Hydroxymethyl dioxidanyl radical	$\text{HOCH}_2\text{OO}\bullet$
10052	Ethyl hydroperoxide	$\text{CH}_3\text{CH}_2\text{OOH}$
10053	3-hydroxypropyl dioxidanyl radical	$\text{HOCH}_2\text{CH}_2\text{CH}_2\text{OO}\bullet$
10054	3-hydroxypropyl hydroperoxide	$\text{HOCH}_2\text{CH}_2\text{CH}_2\text{OOH}$
10055	Methyl-peroxy-nitrate (nitroperoxy-methane)	CH_3OONO_2
10056	2- λ 1-Oxidanyloxy-2-methylbut-3-en-1-ol (4-Hydroxy-3-methyl-1-butene-3-ylperoxy radical)	$\text{HOCH}_2\text{C}(\text{CH}_3)(\text{OO}\bullet)\text{CHCH}_2$
10057	2- λ 1-Oxidanyloxy-3-methylbut-3-en-1-ol (2-hydroxy-1-isopropenylethylperoxy radical)	$\text{HOCH}_2\text{CH}(\text{OO}\bullet)\text{C}(\text{CH}_3)\text{CH}_2$
10058	(Z)-4-hydroperoxy-2-methyl-2-butenal	$\text{CH}_2(\text{OOH})\text{CHC}(\text{CH}_3)\text{CHO}$
10059	(Z)-4-hydroperoxy-3-methyl-2-butenal	$\text{CH}_2(\text{OOH})\text{C}(\text{CH}_3)\text{CHCHO}$
10060–10499	Reserved for other simple organic molecules (e.g. higher aldehydes, alcohols, peroxides, etc.)	
10500	Dimethyl sulphide	CH_3SCH_3 (DMS)
10501	DMSO (dimethyl sulfoxide)	$(\text{CH}_3)_2\text{SO}$
10502–20000	Reserved	
20001	Hydrogen chloride	HCl
20002	CFC-11 (trichlorofluoromethane)	CCl_3F
20003	CFC-12 (dichlorodifluoromethane)	CCl_2F_2
20004	CFC-113 (1,1,2-trichloro-1,2,2-trifluoroethane)	$\text{Cl}_2\text{FC-CClF}_2$
20005	CFC-113a (1,1,1-trichloro-2,2,2-trifluoroethane)	$\text{Cl}_3\text{C-CF}_3$
20006	CFC-114 (1,2-dichloro-1,1,2,2-tetrafluoroethane)	$\text{ClF}_2\text{C-CClF}_2$
20007	CFC-115 (1-chloro-1,1,2,2,2-pentafluoroethane)	$\text{ClF}_2\text{C-CF}_3$
20008	HCFC-22 (chlorodifluoromethane)	CHClF_2
20009	HCFC-141b (1,1-dichloro-1-fluoroethane)	$\text{Cl}_2\text{FC-CH}_3$
20010	HCFC-142b (1-chloro-1,1-difluoroethane)	$\text{ClF}_2\text{C-CH}_3$
20011	Halon-1202 (dibromodifluoromethane)	CBr_2F_2
20012	Halon-1211 (bromochlorodifluoromethane)	CBrClF_2
20013	Halon-1301 (bromotrifluoromethane)	CBrF_3
20014	Halon-2402 (1,2-dibromo-1,1,2,2-tetrafluoroethane)	$\text{BrF}_2\text{C-CBrF}_2$
20015	HCC-40 (methyl chloride)	CH_3Cl
20016	HCC-10 (carbon tetrachloride)	CCl_4
20017	HCC-140a (1,1,1-trichloroethane)	$\text{Cl}_3\text{C-CH}_3$
20018	HBC-40B1 (methyl bromide)	CH_3Br
20019	HCH (hexachlorocyclohexane) all isomers	$\text{C}_6\text{H}_6\text{Cl}_6$
20020	α -HCH (α -hexachlorocyclohexane) both enantiomers	$\alpha\text{-C}_6\text{H}_6\text{Cl}_6$
20021	PCB-153 (2,2',4,4',5,5'-hexachlorobiphenyl)	$(\text{C}_6\text{H}_2\text{Cl}_3)_2$
20022	HCFC 141a (1,1-dichloro-2-fluoro-ethane)	$\text{Cl}_2\text{HC-CH}_2\text{F}$
20023–29999	Reserved	

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
30000	Radioactive pollutant (tracer, defined by originating centre)	
30001–30009	Reserved	
30010	Tritium (Hydrogen 3)	H-3
30011	Tritium organic bounded	H-3o
30012	Tritium inorganic	H-3a
30013	Beryllium 7	Be-7
30014	Beryllium 10	Be-10
30015	Carbon 14	C-14
30016	Carbon 14 CO ₂	C-14CO ₂
30017	Carbon 14 other gases	C-14og
30018	Nitrogen 13	N-13
30019	Nitrogen 16	N-16
30020	Fluorine 18	F-18
30021	Sodium 22	Na-22
30022	Phosphate 32	P-32
30023	Phosphate 33	P-33
30024	Sulphur 35	S-35
30025	Chlorine 36	Cl-36
30026	Potassium 40	K-40
30027	Argon 41	Ar-41
30028	Calcium 41	Ca-41
30029	Calcium 45	Ca-45
30030	Titanium 44	Ti-44
30031	Scandium 46	Sc-46
30032	Vanadium 48	V-48
30033	Vanadium 49	V-49
30034	Chrome 51	Cr-51
30035	Manganese 52	Mn-52
30036	Manganese 54	Mn-54
30037	Iron 55	Fe-55
30038	Iron 59	Fe-59
30039	Cobalt 56	Co-56
30040	Cobalt 57	Co-57
30041	Cobalt 58	Co-58
30042	Cobalt 60	Co-60
30043	Nickel 59	Ni-59
30044	Nickel 63	Ni-63
30045	Zinc 65	Zn-65
30046	Gallium 67	Ga-67
30047	Gallium 68	Ga-68
30048	Germanium 68	Ge-68
30049	Germanium 69	Ge-69
30050	Arsenic 73	As-73
30051	Selenium 75	Se-75
30052	Selenium 79	Se-79
30053	Rubidium 81	Rb-81
30054	Rubidium 83	Rb-83
30055	Rubidium 84	Rb-84

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
30056	Rubidium 86	Rb-86
30057	Rubidium 87	Rb-87
30058	Rubidium 88	Rb-88
30059	Krypton 85	Kr-85
30060	Krypton 85 metastable	Kr-85m
30061	Krypton 87	Kr-87
30062	Krypton 88	Kr-88
30063	Krypton 89	Kr-89
30064	Strontium 85	Sr-85
30065	Strontium 89	Sr-89
30066	Strontium 89/90	Sr-8990
30067	Strontium 90	Sr-90
30068	Strontium 91	Sr-91
30069	Strontium 92	Sr-92
30070	Yttrium 87	Y-87
30071	Yttrium 88	Y-88
30072	Yttrium 90	Y-90
30073	Yttrium 91	Y-91
30074	Yttrium 91 metastable	Y-91m
30075	Yttrium 92	Y-92
30076	Yttrium 93	Y-93
30077	Zirconium 89	Zr-89
30078	Zirconium 93	Zr-93
30079	Zirconium 95	Zr-95
30080	Zirconium 97	Zr-97
30081	Niobium 93 metastable	Nb-93m
30082	Niobium 94	Nb-94
30083	Niobium 95	Nb-95
30084	Niobium 95 metastable	Nb-95m
30085	Niobium 97	Nb-97
30086	Niobium 97 metastable	Nb-97m
30087	Molybdenum 93	Mo-93
30088	Molybdenum 99	Mo-99
30089	Technetium 95 metastable	Tc-95m
30090	Technetium 96	Tc-96
30091	Technetium 99	Tc-99
30092	Technetium 99 metastable	Tc-99m
30093	Rhodium 99	Rh-99
30094	Rhodium 101	Rh-101
30095	Rhodium 102 metastable	Rh-102m
30096	Rhodium 103 metastable	Rh-103m
30097	Rhodium 105	Rh-105
30098	Rhodium 106	Rh-106
30099	Palladium 100	Pd-100
30100	Palladium 103	Pd-103
30101	Palladium 107	Pd-107
30102	Ruthenium 103	Ru-103
30103	Ruthenium 105	Ru-105

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
30104	Ruthenium 106	Ru-106
30105	Silver 108 metastable	Ag-108m
30106	Silver 110 metastable	Ag-110m
30107	Cadmium 109	Cd-109
30108	Cadmium 113 metastable	Cd-113m
30109	Cadmium 115 metastable	Cd-115m
30110	Indium 114 metastable	In-114m
30111	Tin 113	Sn-113
30112	Tin 119 metastable	Sn-119m
30113	Tin 121 metastable	Sn-121m
30114	Tin 122	Sn-122
30115	Tin 123	Sn-123
30116	Tin 126	Sn-126
30117	Antimony 124	Sb-124
30118	Antimony 125	Sb-125
30119	Antimony 126	Sb-126
30120	Antimony 127	Sb-127
30121	Antimony 129	Sb-129
30122	Tellurium 123 metastable	Te-123m
30123	Tellurium 125 metastable	Te-125m
30124	Tellurium 127	Te-127
30125	Tellurium 127 metastable	Te-127m
30126	Tellurium 129	Te-129
30127	Tellurium 129 metastable	Te-129m
30128	Tellurium 131 metastable	Te-131m
30129	Tellurium 132	Te-132
30130	Iodine 123	I-123
30131	Iodine 124	I-124
30132	Iodine 125	I-125
30133	Iodine 126	I-126
30134	Iodine 129	I-129
30135	Iodine 129 elementary gaseous	I-129g
30136	Iodine 129 organic bounded	I-129o
30137	Iodine 131	I-131
30138	Iodine 131 elementary gaseous	I-131g
30139	Iodine 131 organic bounded	I-131o
30140	Iodine 131 gaseous elementary and organic bounded	I-131go
30141	Iodine 131 aerosol	I-131a
30142	Iodine 132	I-132
30143	Iodine 132 elementary gaseous	I-132g
30144	Iodine 132 organic bounded	I-132o
30145	Iodine 132 gaseous elementary and organic bounded	I-132go
30146	Iodine 132 aerosol	I-132a
30147	Iodine 133	I-133
30148	Iodine 133 elementary gaseous	I-133g
30149	Iodine 133 organic bounded	I-133o
30150	Iodine 133 gaseous elementary and organic bounded	I-133go
30151	Iodine 133 aerosol	I-133a

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
30152	Iodine 134	I-134
30153	Iodine 134 elementary gaseous	I-134g
30154	Iodine 134 organic bounded	I-134o
30155	Iodine 135	I-135
30156	Iodine 135 elementary gaseous	I-135g
30157	Iodine 135 organic bounded	I-135o
30158	Iodine 135 gaseous elementary and organic bounded	I-135go
30159	Iodine 135 aerosol	I-135a
30160	Xenon 131 metastable	Xe-131m
30161	Xenon 133	Xe-133
30162	Xenon 133 metastable	Xe-133m
30163	Xenon 135	Xe-135
30164	Xenon 135 metastable	Xe-135m
30165	Xenon 137	Xe-137
30166	Xenon 138	Xe-138
30167	Xenon sum of all Xenon isotopes	Xe-sum
30168	Caesium 131	Cs-131
30169	Caesium 134	Cs-134
30170	Caesium 135	Cs-135
30171	Caesium 136	Cs-136
30172	Caesium 137	Cs-137
30173	Barium 133	Ba-133
30174	Barium 137 metastable	Ba-137m
30175	Barium 140	Ba-140
30176	Cerium 139	Ce-139
30177	Cerium 141	Ce-141
30178	Cerium 143	Ce-143
30179	Cerium 144	Ce-144
30180	Lanthanum 140	La-140
30181	Lanthanum 141	La-141
30182	Praseodymium 143	Pr-143
30183	Praseodymium 144	Pr-144
30184	Praseodymium 144 metastable	Pr-144m
30185	Samarium 145	Sm-145
30186	Samarium 147	Sm-147
30187	Samarium 151	Sm-151
30188	Neodymium 147	Nd-147
30189	Promethium 146	Pm-146
30190	Promethium 147	Pm-147
30191	Promethium 151	Pm-151
30192	Europium 152	Eu-152
30193	Europium 154	Eu-154
30194	Europium 155	Eu-155
30195	Gadolinium 153	Gd-153
30196	Terbium 160	Tb-160
30197	Holmium 166 metastable	Ho-166m
30198	Thulium 170	Tm-170
30199	Ytterbium 169	Yb-169

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
30200	Hafnium 175	Hf-175
30201	Hafnium 181	Hf-181
30202	Tantalum 179	Ta-179
30203	Tantalum 182	Ta-182
30204	Rhenium 184	Re-184
30205	Iridium 192	Ir-192
30206	Mercury 203	Hg-203
30207	Thallium 204	Tl-204
30208	Thallium 207	Tl-207
30209	Thallium 208	Tl-208
30210	Thallium 209	Tl-209
30211	Bismuth 205	Bi-205
30212	Bismuth 207	Bi-207
30213	Bismuth 210	Bi-210
30214	Bismuth 211	Bi-211
30215	Bismuth 212	Bi-212
30216	Bismuth 213	Bi-213
30217	Bismuth 214	Bi-214
30218	Polonium 208	Po-208
30219	Polonium 210	Po-210
30220	Polonium 212	Po-212
30221	Polonium 213	Po-213
30222	Polonium 214	Po-214
30223	Polonium 215	Po-215
30224	Polonium 216	Po-216
30225	Polonium 218	Po-218
30226	Lead 209	Pb-209
30227	Lead 210	Pb-210
30228	Lead 211	Pb-211
30229	Lead 212	Pb-212
30230	Lead 214	Pb-214
30231	Astatine 217	At-217
30232	Radon 219	Rn-219
30233	Radon 220	Rn-220
30234	Radon 222	Rn-222
30235	Francium 221	Fr-221
30236	Francium 223	Fr-223
30237	Radium 223	Ra-223
30238	Radium 224	Ra-224
30239	Radium 225	Ra-225
30240	Radium 226	Ra-226
30241	Radium 228	Ra-228
30242	Actinium 225	Ac-225
30243	Actinium 227	Ac-227
30244	Actinium 228	Ac-228
30245	Thorium 227	Th-227
30246	Thorium 228	Th-228
30247	Thorium 229	Th-229

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
30248	Thorium 230	Th-230
30249	Thorium 231	Th-231
30250	Thorium 232	Th-232
30251	Thorium 234	Th-234
30252	Protactinium 231	Pa-231
30253	Protactinium 233	Pa-233
30254	Protactinium 234 metastable	Pa-234m
30255	Uranium 232	U-232
30256	Uranium 233	U-233
30257	Uranium 234	U-234
30258	Uranium 235	U-235
30259	Uranium 236	U-236
30260	Uranium 237	U-237
30261	Uranium 238	U-238
30262	Plutonium 236	Pu-236
30263	Plutonium 238	Pu-238
30264	Plutonium 239	Pu-239
30265	Plutonium 240	Pu-240
30266	Plutonium 241	Pu-241
30267	Plutonium 242	Pu-242
30268	Plutonium 244	Pu-244
30269	Neptunium 237	Np-237
30270	Neptunium 238	Np-238
30271	Neptunium 239	Np-239
30272	Americium 241	Am-241
30273	Americium 242	Am-242
30274	Americium 242 metastable	Am-242m
30275	Americium 243	Am-243
30276	Curium 242	Cm-242
30277	Curium 243	Cm-243
30278	Curium 244	Cm-244
30279	Curium 245	Cm-245
30280	Curium 246	Cm-246
30281	Curium 247	Cm-247
30282	Curium 248	Cm-248
30283	Curium 243/244	Cm-243244
30284	Plutonium 238/Americium 241	Pu-238Am-241
30285	Plutonium 239/240	Pu-239240
30286	Berkelium 249	Bk-249
30287	Californium 249	Cf-249
30288	Californium 250	Cf-250
30289	Californium 252	Cf-252
30290	Sum aerosol particulates	SumAer
30291	Sum Iodine	SumIod
30292	Sum noble gas	SumNG
30293	Activation gas	ActGas
30294	Cs-137 Equivalent	EquCs137
30295	Carbon-13	C-13

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
30296	Lead	Pb
30297	Tellurium 131	Te-131
30298	Neodymium 137	Nd-137
30299–39999	Reserved	
40000	Singlet sigma oxygen (dioxygen (sigma singlet))	$O_2(^1\Sigma^+_g)$
40001	Singlet delta oxygen (dioxygen (delta singlet))	$O_2(^1\Delta_g)$
40002	Singlet excited oxygen atom	$O(^1D)$
40003	Triplet ground state oxygen atom	$O(^3P)$
40004–59999	Reserved	
60000	HO _x radical (OH+HO ₂)	HO _x •
60001	Total inorganic and organic peroxy radicals (HO ₂ • + RO ₂ •)	ROO•
60002	Passive Ozone	
60003	NO _x expressed as nitrogen	NO _x
60004	All nitrogen oxides (NO _y) expressed as nitrogen	NO _y
60005	Total inorganic chlorine	Cl _x
60006	Total inorganic bromine	Br _x
60007	Total inorganic chlorine except HCl, ClONO ₂ : ClO _x	
60008	Total inorganic bromine except HBr, BrONO ₂ : BrO _x	
60009	Lumped alkanes	
60010	Lumped alkenes	
60011	Lumped aromatic compounds	
60012	Lumped terpenes	
60013	Non-methane volatile organic compounds expressed as carbon	NMVOC
60014	Anthropogenic non-methane volatile organic compounds expressed as carbon	aNMVOC
60015	Biogenic non-methane volatile organic compounds expressed as carbon	bNMVOC
60016	Lumped oxygenated hydrocarbons	OVOC
60017	NO _x expressed as nitrogen dioxide (NO ₂)	NO _x
60018	Organic aldehydes	RCHO
60019	Organic peroxides	ROOH
60020	Organic nitrates	RNO ₃
60021	Ethers	ROR'
60022	Amines	NRR'R''
60023	Ketones	RC(O)R'
60024	Dicarbonyls unsaturated	RC(O)CH ₂ C(O)R'
60025	Hydroxy dicarbonyls unsaturated	RC(O)CHOHC(O)R'
60026	Hydroxy ketones	RC(OH)C(O)R'
60027	Oxides	O _x
60028	Peroxyacyl nitrates	RC(O)OONO ₂
60029	Aromatic peroxide radical (Aryl dioxydanyl radicals)	ArOO•
60030	Biogenic secondary organic compound	
60031	Anthropogenic secondary organic compound	
60032	All hydroxy-peroxides products of the reaction of hydroxy-isoprene adducts with O ₂	ISOPOOH
60033	Anthropogenic volatile organic compounds	aVOC
60034	Biomass burning volatile organic compounds	bbVOC

COMMON CODE TABLES

Common code table C-14

Code figure	Meaning	Chemical formula
60035–61999	Reserved	
62000	Total aerosol	
62001	Dust dry	
62002	Water in ambient	
62003	Ammonium dry	
62004	Nitrate dry	
62005	Nitric acid trihydrate	
62006	Sulphate dry	
62007	Mercury dry	
62008	Sea salt dry	
62009	Black carbon dry	
62010	Particulate organic matter dry	
62011	Primary particulate organic matter dry	
62012	Secondary particulate organic matter dry	
62013	Black carbon hydrophilic dry	
62014	Black carbon hydrophobic dry	
62015	Particulate organic matter hydrophilic dry	
62016	Particulate organic matter hydrophobic dry	
62017	Nitrate hydrophilic dry	
62018	Nitrate hydrophobic dry	
62019	Reserved	
62020	Smoke – high absorption	
62021	Smoke – low absorption	
62022	Aerosol – high absorption	
62023	Aerosol – low absorption	
62024	Reserved	
62025	Volcanic ash	
62026	Particulate matter (PM)	
62027	Reserved	
62028	Total aerosol hydrophilic	
62029	Total aerosol hydrophobic	
62030	Primary particulate inorganic matter dry	
62031	Secondary particulate inorganic matter dry	
62032	Biogenic secondary organic aerosol	
62033	Anthropogenic secondary organic aerosol	
<u>62034</u>	<u>Rain water</u>	<u>H₂O_{rain}</u>
<u>62035</u>	<u>Cloud water</u>	<u>H₂O_{cloud}</u>
<u>62036</u>	<u>Brown carbon dry</u>	
62034 <u>62037</u> –	Reserved	
62099		
62100	Alnus (alder) pollen	
62101	Betula (birch) pollen	
62102	Castanea (chestnut) pollen	
62103	Carpinus (hornbeam) pollen	
62104	Corylus (hazel) pollen	
62105	Fagus (beech) pollen	
62106	Fraxinus (ash) pollen	
62107	Pinus (pine) pollen	
62108	Platanus (plane) pollen	

COMMON CODE TABLES

<i>Common code table C-14</i>		
Code figure	Meaning	Chemical formula
62109	Populus (cottonwood, poplar) pollen	
62110	Quercus (oak) pollen	
62111	Salix (willow) pollen	
62112	Taxus (yew) pollen	
62113	Tilia (lime, linden) pollen	
62114	Ulmus (elm) pollen	
62115	Olea (olive) pollen	
62116–62199	Reserved	
62200	Ambrosia (ragweed, burr-ragweed) pollen	
62201	Artemisia (sagebrush, wormwood, mugwort) pollen	
62202	Brassica (rape, broccoli, Brussels sprouts, cabbage, cauliflower, collards, kale, kohlrabi, mustard, rutabaga) pollen	
62203	Plantago (plantain) pollen	
62204	Rumex (dock, sorrel) pollen	
62205	Urtica (nettle) pollen	
62206–62299	Reserved	
62300	Poaceae (grass family) pollen	
62301–62999	Reserved	
63000–65534	For experimental use at local level	
65535	Missing	

d. REGULATIONS FOR REPORTING TRADITIONAL OBSERVATION DATA IN TABLE-DRIVEN CODE FORMS (TDCF): BUFR OR CREX

B/C1 – Regulations for reporting SYNOP data in TDCF

Annex: Regional regulations for reporting SYNOP data in BUFR/CREX for RA I, RA II, RA III, RA IV and RA VI

B/C5 – Regulations for reporting SYNOP MOBIL data in TDCF

B/C10 – Regulations for reporting SHIP data in TDCF

B/C20 – Regulations for reporting PILOT, PILOT SHIP and PILOT MOBIL data in TDCF

B/C25 – Regulations for reporting TEMP, TEMP SHIP and TEMP MOBIL data in TDCF

Annex I: RA IV BUFR template for TEMP, TEMP SHIP and TEMP MOBIL data

Annex II: List of parameters for representation of additional information on sounding instrumentation

B/C26 – Regulations for reporting TEMP DROP data in TDCF

B/C30 – Regulations for reporting CLIMAT data in TDCF

B/C32 – Regulations for reporting CLIMAT SHIP data in TDCF

General features

- (i) The regulations for reporting data of traditional observations in BUFR or CREX are intended to provide a link between the Manual on Codes, Volume I.1 and Volume II, containing traditional alphanumeric codes (TAC) regulations with detailed description of reporting practices and the Volume I.2, where the code forms FM 94 BUFR and FM 95 CREX are defined.
- (ii) A BUFR/CREX template has been developed for each traditional observation that is considered suitable for migration to table-driven code forms (TDCF). Templates presented prior to the regulations are BUFR templates; if used for CREX, relevant modifications have to be introduced.
- (iii) The regulations for reporting data of each traditional observation in TDCF are numbered in the increasing order in compliance with a standard BUFR/CREX template recommended for the data type. For reference, the number of the corresponding TAC regulation is included at the end of the regulation, written in square brackets.
- (iv) BUFR/CREX templates defined for traditional observation data contain not only the elements reported in the corresponding TAC, but also other important information. The regulations for reporting traditional observations data in BUFR/CREX address also these additional entries (e.g. horizontal and vertical coordinates of the observation site, position of sensors, significance qualifiers).
- (v) With each element introduced within the regulations, the unit and the required precision are specified. If different units are used in BUFR and CREX, the unit in which the element value is reported in CREX is also mentioned. Scaling is expected to be executed by the encoding BUFR or CREX software; in case of manual encoding of a CREX message, however, the scaling shall be included in the reporting procedure.
- (vi) If the unit of the element is defined as a flag table, the element values shall be reported in octal representation in CREX.

REGULATIONS FOR REPORTING TRADITIONAL OBSERVATION DATA IN TDCF: BUFR OR CREX

- (vii) Reporting practices primarily refer to the procedures relevant for producing of the data in BUFR or CREX at the observing site. When data are collected in TAC and converted into BUFR or CREX in the centre, the differences in the reporting procedures, if any, are mentioned.
- (viii) If regional or national reporting practices require inclusion of additional parameters, the regulations provide guidance for addition of the relevant descriptors.
- (ix) A NIL report shall be represented by setting all values to “missing value” except for the identification of the station or observing site and delayed replication factors.

Note: Texts in *italic* within the regulations indicate that special attention should be given to this aspect of the regulation.

Provisional Copy
2023

B/C1 – Regulations for reporting SYNOP data in TDCF

TM 307080 – BUFR template for synoptic reports from fixed land stations suitable for SYNOP data

		Sequence for representation of synoptic reports from a fixed land station suitable for SYNOP data
3 07 080	3 01 090	Surface station identification; time, horizontal and vertical coordinates
	3 02 031	Pressure information
	3 02 035	Basic synoptic “instantaneous” data
	3 02 036	Clouds with bases below station level
	3 02 047	Direction of cloud drift
	0 08 002	Vertical significance (surface observations)
	3 02 048	Direction and elevation of cloud
	3 02 037	State of ground, snow depth, ground minimum temperature
	3 02 043	Basic synoptic “period” data
	3 02 044	Evaporation data
	1 01 002	Replicate 1 descriptor 2 times
	3 02 045	Radiation data (from 1 hour and 24-hour period)
	3 02 046	Temperature change

This BUFR template for synoptic reports from fixed land stations further expands as follows:

				Unit, scale
			Surface station identification; time, horizontal and vertical coordinates	
3 01 090	3 01 004	0 01 001	WMO block number	II Numeric, 0
		0 01 002	WMO station number	iii Numeric, 0
		0 01 015	Station or site name	CCITT IA5, 0
		0 02 001	Type of station	i _x Code table, 0
	3 01 011	0 04 001	Year	Year, 0
		0 04 002	Month	Month, 0
		0 04 003	Day	YY Day, 0
	3 01 012	0 04 004	Hour	GG Hour, 0
		0 04 005	Minute	gg Minute, 0
	3 01 021	0 05 001	Latitude (high accuracy)	Degree, 5
		0 06 001	Longitude (high accuracy)	Degree, 5
	0 07 030		Height of station ground above mean sea level	m, 1
	0 07 031		Height of barometer above mean sea level	m, 1
			Pressure information	
3 02 031	3 02 001	0 10 004	Pressure	P ₀ P ₀ P ₀ P ₀ Pa, –1
		0 10 051	Pressure reduced to mean sea level	PPPP Pa, –1
		0 10 061	3-hour pressure change	ppp Pa, –1
		0 10 063	Characteristic of pressure tendency	a Code table, 0
	0 10 062		24-hour pressure change	p ₂₄ p ₂₄ p ₂₄ Pa, –1
	0 07 004		Pressure (standard level)	a ₃ Pa, –1
	0 10 009		Geopotential height of the standard level	hhh gpm, 0
			Basic synoptic “instantaneous” data	
			<i>Temperature and humidity data</i>	
3 02 035	3 02 032	0 07 032	Height of sensor above local ground (or deck of marine platform) (for temperature and humidity measurement)	m, 2
		0 12 101	Temperature/air temperature	s _n TTT K, 2
		0 12 103	Dewpoint temperature	s _n T _d T _d T _d K, 2

				Unit, scale
		0 13 003	Relative humidity	%, 0
			<i>Visibility data</i>	
	3 02 033	0 07 032	Height of sensor above local ground (or deck of marine platform) (for visibility measurement)	m, 2
		0 20 001	Horizontal visibility VV	m, –1
			<i>Precipitation past 24 hours</i>	
	3 02 034	0 07 032	Height of sensor above local ground (or deck of marine platform) (for precipitation measurement)	m, 2
		0 13 023	Total precipitation past 24 hours $R_{24}R_{24}R_{24}R_{24}$	kg m ⁻² , 1
	0 07 032		Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
			<i>General cloud information</i>	
	3 02 004	0 20 010	Cloud cover (total) N	%, 0
		0 08 002	Vertical significance (surface observations)	Code table, 0
		0 20 011	Cloud amount (of low or middle clouds) N _h	Code table, 0
		0 20 013	Height of base of cloud h	m, –1
		0 20 012	Cloud type (low clouds) C _L	Code table, 0
		0 20 012	Cloud type (middle clouds) C _M	Code table, 0
		0 20 012	Cloud type (high clouds) C _H	Code table, 0
			<i>Individual cloud layers or masses</i>	
	1 01 000		Delayed replication of 1 descriptor	
	0 31 001		Delayed descriptor replication factor	Numeric, 0
	3 02 005	0 08 002	Vertical significance (surface observations)	Code table, 0
		0 20 011	Cloud amount N _s	Code table, 0
		0 20 012	Cloud type C	Code table, 0
		0 20 013	Height of base of cloud h _s h _s	m, –1
			Clouds with bases below station level	
3 02 036	1 05 000		Delayed replication of 5 descriptors	
	0 31 001		Delayed descriptor replication factor	Numeric, 0
	0 08 002		Vertical significance (surface observations)	Code table, 0
	0 20 011		Cloud amount N'	Code table, 0
	0 20 012		Cloud type C'	Code table, 0
	0 20 014		Height of top of cloud H'H'	m, –1
	0 20 017		Cloud top description C _t	Code table, 0
			Direction of cloud drift group 56D _L D _M D _H	
3 02 047	1 02 003		Replicate 2 descriptors 3 times	
	0 08 002		Vertical significance (surface observations) = 7 (low cloud) = 8 (middle cloud) = 9 (high cloud)	Code table, 0
	0 20 054		True direction from which a phenomenon or clouds are moving or in which they are observed D _L , D _M , D _H	Degree true, 0
0 08 002			Vertical significance (surface observations) (set to missing to cancel the previous value)	Code table, 0
			Direction and elevation of cloud gr. 57CD _a e _C	
3 02 048	0 05 021		Bearing or azimuth D _a	Degree true, 2
	0 07 021		Elevation e _C	Degree, 2
	0 20 012		Cloud type C	Code table, 0
	0 05 021		Bearing or azimuth (set to missing to cancel the previous value)	Degree true, 2

				Unit, scale
	0 07 021		Elevation (set to missing to cancel the previous value)	Degree, 2
			State of ground, snow depth, ground minimum temperature	
3 02 037	0 20 062		State of the ground (with or without snow) E or E'	Code table, 0
	0 13 013		Total snow depth sss	m, 2
	0 12 113		Ground minimum temperature, past 12 hours s _n T _g T _g	K, 2
			Basic synoptic “period” data	
			<i>Present and past weather</i>	
3 02 043	3 02 038	0 20 003	Present weather ww	Code table, 0
		0 04 024	Time period or displacement (in hours)	Hour, 0
		0 20 004	Past weather (1) W ₁	Code table, 0
		0 20 005	Past weather (2) W ₂	Code table, 0
			<i>Sunshine data (from 1 hour and 24-hour period)</i>	
	1 01 002		Replicate 1 descriptor 2 times	
	3 02 039	0 04 024	Time period or displacement (in hours)	Hour, 0
		0 14 031	Total sunshine SS and SSS	Minute, 0
			<i>Precipitation measurement</i>	
	3 02 040	0 07 032	Height of sensor above local ground (or deck of marine platform) (for precipitation measurement)	m, 2
		1 02 002	Replicate 2 descriptors 2 times	
		0 04 024	Time period or displacement (in hours) t _R	Hour, 0
		0 13 011	Total precipitation/total water equivalent RRR	kg m ⁻² , 1
			<i>Extreme temperature data</i>	
	3 02 041	0 07 032	Height of sensor above local ground (or deck of marine platform) (for temperature measurement)	m, 2
		0 04 024	Time period or displacement	Hour, 0
		0 04 024	Time period or displacement (see Notes 1 and 2)	Hour, 0
		0 12 111	Maximum temperature, at height and over period specified s _n T _x T _x T _x	K, 2
		0 04 024	Time period or displacement	Hour, 0
		0 04 024	Time period or displacement (see Note 2)	Hour, 0
		0 12 112	Minimum temperature, at height and over period specified s _n T _n T _n T _n	K, 2
			<i>Wind data</i>	
	3 02 042	0 07 032	Height of sensor above local ground (or deck of marine platform) (for wind measurement)	m, 2
		0 02 002	Type of instrumentation for wind measurement i _w	Flag table, 0
		0 08 021	Time significance = 2 Time averaged	Code table, 0
		0 04 025	Time period or displacement = –10 minutes, or number of minutes after a significant change of wind	Minute, 0
		0 11 001	Wind direction dd	Degree true, 0
		0 11 002	Wind speed ff	m s ⁻¹ , 1
		0 08 021	Time significance = missing value	Code table, 0
		1 03 002	Replicate 3 descriptors 2 times	
		0 04 025	Time period or displacement (in minutes)	Minute, 0
		0 11 043	Maximum wind gust direction	Degree true, 0

				Unit, scale
		0 11 041	Maximum wind gust speed 910f _m f _m , 911f _x f _x	m s ⁻¹ , 1
	0 07 032		Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
			Evaporation data	
3 02 044	0 04 024		Time period or displacement (in hours)	Hour, 0
	0 02 004		Type of instrumentation for evaporation measurement or type of crop for which evapotranspiration is reported i _E	Code table, 0
	0 13 033		Evaporation/evapotranspiration EEE	kg m ⁻² , 1
			Radiation data (from 1 hour and 24-hour period)	
1 01 002			Replicate 1 descriptor 2 times	
3 02 045	0 04 024		Time period or displacement (in hours)	Hour, 0
	0 14 002		Long-wave radiation, integrated over period specified 553SS 4FFFF or 553SS 5FFFF, 55SSS 4F ₂₄ F ₂₄ F ₂₄ F ₂₄ or 55SSS 5F ₂₄ F ₂₄ F ₂₄ F ₂₄	J m ⁻² , -3
	0 14 004		Short-wave radiation, integrated over period specified 553SS 6FFFF, 55SSS 6F ₂₄ F ₂₄ F ₂₄ F ₂₄	J m ⁻² , -3
	0 14 016		Net radiation, integrated over period specified 553SS 0FFFF or 553SS 1FFFF, 55SSS 0F ₂₄ F ₂₄ F ₂₄ F ₂₄ or 55SSS 1F ₂₄ F ₂₄ F ₂₄ F ₂₄	J m ⁻² , -4
	0 14 028		Global solar radiation (high accuracy), integrated over period specified 553SS 2FFFF, 55SSS 2F ₂₄ F ₂₄ F ₂₄ F ₂₄	J m ⁻² , -2
	0 14 029		Diffuse solar radiation (high accuracy), integrated over period specified 553SS 3FFFF, 55SSS 3F ₂₄ F ₂₄ F ₂₄ F ₂₄	J m ⁻² , -2
	0 14 030		Direct solar radiation (high accuracy), integrated over period specified 55408 4FFFF, 55508 5F ₂₄ F ₂₄ F ₂₄ F ₂₄	J m ⁻² , -2
			Temperature change group 54g ₀ s _n d _T	
3 02 046	0 04 024		Time period or displacement	Hour, 0
	0 04 024		Time period or displacement (see Note 3)	Hour, 0
	0 12 049		Temperature change over specified period s _n d _T	K, 0

Notes:

- (1) Within RA IV, the maximum temperature at 1200 UTC is reported for the previous calendar day (i.e. the ending time of the period is not equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (2) Within RA III, the maximum daytime temperature and the minimum night-time temperature is reported (i.e. the ending time of the period may not be equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (3) To construct the required time range, descriptor 0 04 024 has to be included two times.
- (4) Maritime countries may use template TM 307079 (BUFR template for synoptic reports from fixed land stations suitable for SYNOP data and for maritime data from coastal and island stations) instead of template TM 307080 if preferable.
- (5) Template TM 307096 (BUFR template for representation of SYNOP data with supplementary information on one hour observations) may be used instead of template TM 307080 if reporting of synoptic data together with one hour AWS data is required.

Regulations:

B/C1.1	Section 1 of BUFR or CREX
B/C1.2	Surface station identification; time, horizontal and vertical coordinates
B/C1.3	Pressure information
B/C1.4	Basic synoptic “instantaneous” data
B/C1.4.1	Temperature and humidity data
B/C1.4.2	Visibility data
B/C1.4.3	Precipitation past 24 hours
B/C1.4.4	General cloud information
B/C1.4.5	Individual cloud layers or masses
B/C1.5	Clouds with bases below station level
B/C1.6	Direction of cloud drift
B/C1.7	Direction and elevation of cloud
B/C1.8	State of ground, snow depth, ground minimum temperature
B/C1.9	“Instantaneous” data required by regional or national reporting practices
B/C1.10	Basic synoptic “period” data
B/C1.10.1	Present and past weather
B/C1.10.2	Sunshine data (from 1 hour and 24-hour period)
B/C1.10.3	Precipitation measurement
B/C1.10.4	Extreme temperature data
B/C1.10.5	Wind data
B/C1.11	Evaporation data
B/C1.12	Radiation data (from 1 hour and 24-hour period)
B/C1.13	Temperature change
B/C1.14	“Period” data required by regional or national reporting practices

Annex: Regional regulations for reporting SYNOP data in TDCF

B/C1.1 Section 1 of BUFR or CREX

B/C1.1.1 Entries required in Section 1 of BUFR

The following entries shall be included in BUFR Section 1:

- BUFR master table;
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Identification of inclusion of optional section;
- Data category (000 for SYNOP data);
- International data sub-category (see Note 1);
- Local data sub-category;
- Version number of master table;
- Version number of local tables;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for SYNOP data);
- Hour (GG in the abbreviated telecommunication header for SYNOP data);
- Minute (00 for SYNOP data);
- Second (00).

Notes:

- (1) If required, the international data sub-category shall be included for SYNOP data as:
 - = 002 at main synoptic times 00, 06, 12, 18 UTC;
 - = 001 at intermediate synoptic times 03, 09, 15, 21 UTC;
 - = 000 at observation times 01, 02, 04, 05, 07, 08, 10, 11, 13, 14, 16, 17, 19, 20, 22 and 23 UTC.

- (2) If an NMHS performs conversion of SYNOP data produced by another NMHS, originating centre in Section 1 shall indicate the converting centre and originating sub-centre shall indicate the producer of SYNOP bulletins. The producer of SYNOP bulletins shall be specified in Common Code table C–12 as a sub-centre of the originating centre, i.e. of the NMHS executing the conversion.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C1.1.2 Entries required in Section 1 of CREX

The following entries shall be included in CREX Section 1:

- CREX master table;
- CREX edition number;
- CREX table version number;
- Version number of BUFR master table;
- Version number of local tables;
- Data category (000 for SYNOP data);
- International data sub-category (see Note 1);
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Number of subsets;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for SYNOP data);
- Hour (GG in the abbreviated telecommunication header for SYNOP data);
- Minute (00 for SYNOP data).

Notes:

- (1) If inclusion of the international data sub-category is required, Note 1 under Regulation B/C1.1.1 applies.
- (2) If an NMHS performs conversion of SYNOP data produced by another NMHS, Note 2 under Regulation B/C1.1.1 applies.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C1.2 Surface station identification; time, horizontal and vertical coordinates <3 01 090>

B/C1.2.1 Fixed station identification

WMO block number (0 01 001) and WMO station number (0 01 002) shall be always reported as a non-missing value.

Station or site name (0 01 015) shall be reported as published in *Weather Reporting* (WMO-No. 9), Volume A – Observing Stations, provided that the station name does not exceed 20 characters. A shortened version of the name shall be reported otherwise.

Type of station (0 02 001) shall be reported to indicate the type of the station operation (manned, automatic or hybrid).

Note: If a station operates as a manned station for a part of the day and as an automatic station for the rest of the day, code figure 2 (Hybrid) may be used in all reports. It is preferable, however, to use code figure 1 (Manned) in reports produced under the supervision of an observer, and a code figure 0 (Automatic) in reports produced while the station operates in the automatic mode.

B/C1.2.2 Time of observation

Year (0 04 001), month (0 04 002), day (0 04 003), hour (0 04 004) and minute (0 04 005) of the actual time of observation shall be reported.

Note: The actual time of observation shall be the time at which the barometer is read. [12.1.6]

B/C1.2.2.1 The time in Section 1 (B/C1.1.1) may be reported instead of the actual time of observation if the actual time of observation differs by 10 minutes or less from the nearest hour. [12.2.8]

B/C1.2.3 Horizontal and vertical coordinates

Latitude (0 05 001) and longitude (0 06 001) of the station shall be reported in degrees with precision in 10^{-5} of a degree.

Height of station ground above mean sea level (0 07 030) and height of barometer above mean sea level (0 07 031) shall be reported in metres with precision in tenths of a metre.

Note: The official altitude of the aerodrome (HA in Volume A) shall not be used to report Height of station ground above mean sea level 0 07 030 in BUFR or CREX messages from aerodromes. Those are two different vertical coordinates. "Height of station ground above mean sea level" for each station should be made available to the encoding centre concerned, which may be a centre within the same NMHS or other NMC/RTH.

B/C1.3 Pressure information <3 02 031>**B/C1.3.1 Pressure at the station level**

Pressure at the station level (0 10 004), i.e. at the level defined by 0 07 031 (height of barometer above mean sea level), shall be reported in pascals (with precision in tens of pascals).

B/C1.3.1.1 The station pressure shall be included in reports for global exchange from land stations, together with either the mean sea level pressure or, in accordance with Regulation B/C1.3.5.1, with the geopotential height of a standard pressure level.

Note: Inclusion of the station pressure at other times is left to the decision of individual Members.

[12.2.4]

B/C1.3.2 Pressure reduced to mean sea level

Pressure reduced to mean sea level (0 10 051) shall be reported in pascals (with precision in tens of pascals).

B/C1.3.2.1 Whenever air pressure at mean sea level can be computed with reasonable accuracy, this pressure shall be reported.

Notes:

- (1) For a station situated in a region of normal synoptic network density, the pressure at mean sea level is considered not to be computed with reasonable accuracy when it introduces a deformation into the analysis of the horizontal pressure field, which is purely local and recurring.
- (2) For a station lying in a data-sparse area of the synoptic network, reasonable accuracy will be obtained when using a reduction method, which has proved to be satisfactory in a region of normal network density and under similar geographic conditions.

[12.2.3.4.1]

B/C1.3.3 Three-hour pressure change and characteristic of pressure tendency

Amount of pressure change at station level, during the three hours preceding the time of observation (0 10 061), either positive, zero or negative, shall be reported in pascals (with precision in tens of pascals).

B/C1.3.3.1 Unless specified otherwise by regional decision, pressure tendency shall be included whenever the three-hourly pressure tendency is available. [12.2.3.5.1]

B/C1.3.3.2 The characteristic of pressure tendency (Code table 0 10 063) over the past three hours shall, whenever possible, be determined on the basis of pressure samples at equi-spaced intervals not exceeding one hour.

Note: Algorithms for selecting the appropriate code figure are included in the *Guide to Meteorological Instruments and Methods of Observation* (WMO-No. 8).

[12.2.3.5.2]

B/C1.3.3.3 Where it is not possible to apply the algorithms specified in Regulation B/C1.3.3.2 in reports from automatic weather stations, the characteristic of pressure tendency shall be reported as 2 when the tendency is positive, as 7 when the tendency is negative, and as 4 when the atmospheric pressure is the same as three hours before. [12.2.3.5.3]

B/C1.3.4 24-hour pressure change

If specified by regional decision, amount of surface pressure change at station level, during 24 hours preceding the time of observation (0 10 062), either positive, zero or negative, shall be reported in pascals (with precision in tens of pascals). [12.4.7.1.2(k), (l)]

B/C1.3.5 Geopotential height of the standard level

Geopotential height of the standard level (0 10 009) shall be reported in geopotential metres. The standard isobaric level is specified by the preceding entry Pressure (0 07 004).

B/C1.3.5.1 By regional decision, a high-level station, which cannot give pressure at mean sea level to a satisfactory degree of accuracy, shall report both the station-level pressure and the geopotential height of an agreed standard isobaric surface. [12.2.3.4.2]

B/C1.4 Basic synoptic “instantaneous” data <3 02 035>**B/C1.4.1 Temperature and humidity data <3 02 032>****B/C1.4.1.1 Height of sensor above local ground**

Height of sensor above local ground (0 07 032) for temperature and humidity measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of temperature and humidity sensors above ground at the point where the sensors are located.

B/C1.4.1.2 Dry-bulb air temperature

Dry-bulb air temperature (0 12 101) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius)

Notes:

- (1) Temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree. This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

B/C1.4.1.2.1 When the data are not available as a result of a temporary instrument failure, this quality shall be included as a missing value. [12.2.3.2]

B/C1.4.1.3 Dewpoint temperature

Dewpoint temperature (0 12 103) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C1.4.1.2 shall apply.

B/C1.4.1.3.1 When the data are not available as a result of a temporary instrument failure, this quality shall be included as a missing value. [12.2.3.3.2]

B/C1.4.1.4 Relative humidity

Relative humidity (0 13 003) shall be reported in units of a per cent.

B/C1.4.1.4.1 *Both dewpoint temperature and relative humidity shall be reported when available.*

B/C1.4.2 Visibility data <3 02 033>**B/C1.4.2.1 Height of sensor above local ground**

Height of sensor above local ground (0 07 032) for visibility measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of visibility sensors above ground at the point where the sensors are located. If visibility is estimated by a human observer, average height of observer's eyes above station ground shall be reported.

B/C1.4.2.2 Horizontal visibility

Horizontal visibility (0 20 001) at surface shall be reported in metres (with precision in tens of metres).

B/C1.4.2.2.1 When the horizontal visibility is not the same in different directions, the shortest distance shall be given for visibility. [12.2.1.3.1]

B/C1.4.2.2.2 Horizontal visibility greater than 81 900 m shall be expressed by 0 20 001 set to 81 900 m; if TDCF data are converted from TAC data, 0 20 001 set to 81 900 m shall indicate horizontal visibility greater than 70 000 m.

B/C1.4.3 Precipitation past 24 hours <3 02 034>**B/C1.4.3.1 Height of sensor above local ground**

Height of sensor above local ground (0 07 032) for precipitation measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the rain gauge rim above ground at the point where the rain gauge is located.

B/C1.4.3.2 Total amount of precipitation during the 24-hour period

Total amount of precipitation during the 24-hour period ending at the time of observation (0 13 023) shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre). [12.4.9]

B/C1.4.3.2.1 The precipitation over the past 24 hours shall be included (not missing) at least once a day at one appropriate time of the main standard times (0000, 0600, 1200, 1800 UTC). [12.4.1]

B/C1.4.3.2.2 Precipitation, when it can be and has to be reported, shall be reported as 0.0 kg m^{-2} if no precipitation were observed during the referenced period. [12.2.5.4]

B/C1.4.3.2.3 Trace shall be reported as " -0.1 kg m^{-2} ".

B/C1.4.4 General cloud information <3 02 004>**B/C1.4.4.1 Total cloud cover**

Total cloud cover (0 20 010) shall embrace the total fraction of the celestial dome covered by clouds irrespective of their genus. It shall be reported in *units of a per cent*.

Note: Total cloud cover shall be reported as 113 when sky is obscured by fog and/or other meteorological phenomena.

B/C1.4.4.1.1 Total cloud cover shall be reported as actually seen by the observer during the observation. [12.2.2.2.1]

B/C1.4.4.1.2 Altocumulus perlucidus or Stratocumulus perlucidus ("mackerel sky") shall be reported as 99% or less (unless overlying clouds appear to cover the whole sky) since breaks are always present in this cloud form even if it extends over the whole celestial dome. [12.2.2.2.2]

B/C1.4.4.1.3 Total cloud cover shall be reported as zero when blue sky or stars are seen through existing fog or other analogous phenomena without any trace of cloud being seen. [12.2.2.2.3]

B/C1.4.4.1.4 When clouds are observed through fog or analogous phenomena, their amount shall be evaluated and reported as if these phenomena were non-existent. [12.2.2.2.4]

B/C1.4.4.1.5 Total cloud cover shall not include the amount resulting from rapidly dissipating condensation trails. [12.2.2.2.5]

B/C1.4.4.1.6 Persistent condensation trails and cloud masses which have obviously developed from condensation trails shall be reported as cloud. [12.2.2.2.6]

B/C1.4.4.2 Vertical significance (surface observations) – Code table 0 08 002

To specify vertical significance (0 08 002) within the sequence 3 02 004, a code figure shall be selected in the following way:

- (a) If low clouds are observed, then code figure 7 (Low cloud) shall be used.
- (b) If there are no low clouds but middle clouds are observed, then code figure 8 (Middle clouds) shall be used.
- (c) If there are no low and there are no middle clouds but high clouds are observed, then code figure 0 shall be used.
- (d) If sky is obscured by fog and/or other phenomena, then code figure 5 (Ceiling) shall be used.
- (e) If there are no clouds (clear sky), then code figure 62 (Value not applicable) shall be used.
- (f) If the cloud cover is not discernible for reasons other than (d) above or observation is not made, then code figure 63 (Missing value) shall be used.

B/C1.4.4.3 Cloud amount (of low or middle clouds) – Code table 0 20 011

Amount of all the low clouds (clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus) present or, if no low clouds are present, the amount of all the middle clouds (clouds of the genera Altocumulus, Altostratus, and Nimbostratus) present.

B/C1.4.4.3.1 Cloud amount shall be reported as follows:

- (a) If there are low clouds, then the total amount of all low clouds, as actually seen by the observer during the observation, shall be reported for the cloud amount.
- (b) If there are no low clouds but there are middle clouds, then the total amount of the middle clouds shall be reported for the cloud amount.
- (c) If there are no low clouds and there are no middle clouds but there are high clouds (clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus), then the cloud amount shall be reported as zero.

[12.2.7.2.1]

- (d) If no clouds are observed (clear sky), then the cloud amount shall be reported as 0.
- (e) If sky is obscured by fog and/or other meteorological phenomena, then the cloud amount shall be reported as 9.
- (f) If cloud cover is indiscernible for reasons other than fog or other meteorological phenomena, or observation is not made, the cloud amount shall be reported as missing.

B/C1.4.4.3.2 Amount of Altocumulus perlucidus or Stratocumulus perlucidus (“mackerel sky”) shall be reported using code figure 7 or less since breaks are always present in this cloud form even if it extends over the whole celestial dome. [12.2.7.2.2]**B/C1.4.4.3.3 When the clouds reported for cloud amount are observed through fog or an analogous phenomenon, the cloud amount shall be reported as if these phenomena were not present. [12.2.7.2.3]****B/C1.4.4.3.4 If the clouds reported for cloud amount include contrails, then the cloud amount shall include the amount of persistent contrails. Rapidly dissipating contrails shall not be included in the value for the cloud amount. [12.2.7.2.4]**

B/C1.4.4.4 Height of base of lowest cloud

Height above surface of the base (0 20 013) of the lowest cloud seen shall be reported in metres (with precision in tens of metres).

Note: The term « height above surface » shall be considered as being the height above the official aerodrome elevation or above station elevation at a non-aerodrome station.

B/C1.4.4.4.1 When the station is in fog, a sandstorm or in blowing snow but the sky is discernible, the base of the lowest cloud shall refer to the base of the lowest cloud observed, if any. When, under the above conditions, the sky is not discernible, the base of the lowest cloud shall be replaced by vertical visibility. [12.4.10.5]

B/C1.4.4.4.2 When no cloud is reported (total cloud cover = 0), the base of the lowest cloud *shall be reported as a missing value.*

B/C1.4.4.4.3 When, by national decision, clouds with bases below the station are reported from the station and clouds with bases below and tops above the station are observed, the base of the lowest cloud *shall be reported having a negative value if the base of cloud is discernible, or as a missing value.*

B/C1.4.4.4.4 If synoptic data are produced in BUFR or CREX by conversion from a TAC report, the following approach shall be used: Height of base of the lowest cloud 0 20 013 shall be derived from the $h_s h_s$ in the first group 8 in section 3, i.e. from the $h_s h_s$ of the lowest cloud. If and only if groups 8 are not reported in section 3, 0 20 013 may be derived from h . The lower limit of the range defined for $h_s h_s$ and for h shall be used. However, if groups 8 are not reported in section 3 and $h = 9$ and $N_h \neq 0$, then 0 20 013 shall be 4 000 m; if groups 8 are not reported in section 3 and $h = 9$ and $N_h = 0$, then 0 20 013 shall be 8 000 m.

B/C1.4.4.5 Cloud type of low, middle and high clouds – Code table 0 20 012

Clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus (low clouds) shall be reported for the first entry 0 20 012, clouds of the genera Altopumulus, Altostratus, and Nimbostratus (middle clouds) shall be reported for the second entry 0 20 012 and clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus (high clouds) shall be reported for the third entry 0 20 012.

B/C1.4.4.5.1 The reporting of type of low, middle and high clouds shall be as specified in the *International Cloud Atlas* (WMO-No. 407), Volume I. [12.2.7.3]

B/C1.4.5 Individual cloud layers or masses**B/C1.4.5.1 Number of individual cloud layers or masses**

The number of individual cloud layers or masses shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of cloud layers or masses shall never be set to missing value.
- (2) The number of cloud layers or masses shall be set to a positive value, not a missing value indicator, in a NIL report.
- (3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

- B/C1.4.5.1.1** When reported from a manned station, the number of individual cloud layers or masses shall in the absence of Cumulonimbus clouds not exceed three. Cumulonimbus clouds, when observed, shall always be reported, so that the total number of individual cloud layers or masses can be four. The selection of layers (or masses) to be reported shall be made in accordance with the following criteria:
- (a) The lowest individual layer (or mass) of any amount (cloud amount at least one octa or less, but not zero);
 - (b) The next higher individual layer (or mass) the amount of which is greater than two octas;
 - (c) The next higher individual layer (or mass) the amount of which is greater than four octas;
 - (d) Cumulonimbus clouds, whenever observed and not reported under (a), (b) and (c) above.
- [12.4.10.1]
- B/C1.4.5.1.2** When the sky is clear, the number of individual cloud layers or masses shall be set to zero.
- B/C1.4.5.1.3** The order of reporting the individual cloud layers or masses shall always be from lower to higher levels. [12.4.10.2]
- B/C1.4.5.2** **Individual cloud layer or mass <3 02 005>**
- Each cloud layer or mass shall be represented by the following four parameters: Vertical significance (0 08 002), amount of individual cloud layer or mass (0 20 011), type of cloud layer or mass (0 20 012) and height of base of individual cloud layer or mass (0 20 013).
- B/C1.4.5.2.1** **Vertical significance (surface observations) – Code table 0 08 002**
- To specify vertical significance (0 08 002) within the sequence 3 02 005, a code figure shall be selected in the following way:
- (a) Code figure 1 shall be used in the first non-Cumulonimbus layer;
 - (b) Code figure 2 shall be used in the second non-Cumulonimbus layer;
 - (c) Code figure 3 shall be used in the third non-Cumulonimbus layer;
 - (d) Code figure 4 shall be used in any Cumulonimbus layer;
 - (e) If sky is obscured by fog and/or other phenomena, then code figure 5 (Ceiling) shall be used;
 - (f) If the cloud cover is not discernible for reasons other than (e) above or observation is not made, then code figure 63 (Missing value) shall be used;
 - (g) If a station operates in the automatic mode and is sufficiently equipped, code figure 21, 22, 23 and 24 shall be used to identify the first, the second, the third and the fourth instrument detected cloud layer, respectively;
 - (h) If a station operates in the automatic mode and no clouds are detected by the cloud detection system, code figure 20 shall be used.
- B/C1.4.5.2.2** **Cloud amount, type and height of base**
- B/C1.4.5.2.2.1** When the sky is clear, in accordance with Regulation B/C1.4.5.1.2 cloud amount, genus, and height shall not be included. [12.4.10.4]
- B/C1.4.5.2.2.2** In determining cloud amounts (Code table 0 20 011) to be reported for individual layers or masses, the observer shall estimate, by taking into consideration the evolution of the sky, the cloud amounts of each individual layer or mass at the different levels, as if no other clouds existed. [12.4.10.3]

B/C1.4.5.2.2.3 Type of a cloud layer or mass (Code table 0 20 012) shall be reported using code figures 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 59 and 63.

B/C1.4.5.2.2.4 If, notwithstanding the existence of fog, sandstorm, duststorm, blowing snow or other obscuring phenomena, the sky is discernible, the partially obscuring phenomena shall be disregarded. If, under the above conditions, the sky is not discernible, the cloud type shall be reported using code figure 59 and the cloud height shall be replaced by vertical visibility.

Note: The vertical visibility is defined as the vertical visual range into an obscuring medium.

[12.4.10.5]

B/C1.4.5.2.2.5 If two or more types of cloud occur with their bases at the same level and this level is one to be reported in accordance with Regulation B/C1.4.5.1.1, the selection for cloud type and amount shall be made with the following criteria:

- (a) If these types do not include Cumulonimbus then cloud genus shall refer to the cloud type that represents the greatest amount, or if there are two or more types of cloud all having the same amount, the highest applicable code figure for cloud genus shall be reported. Cloud amount shall refer to the total amount of cloud whose bases are all at the same level;
- (b) If these types do include Cumulonimbus then one layer shall be reported to describe only this type with cloud genus indicated as Cumulonimbus and the cloud amount as the amount of the Cumulonimbus. If the total amount of the remaining type(s) of cloud (excluding Cumulonimbus) whose bases are all at the same level is greater than that required by Regulation B/C1.4.5.1.1, then another layer shall be reported with type being selected in accordance with (a) and amount referring to the total amount of the remaining cloud (excluding Cumulonimbus).

[12.4.10.6]

B/C1.4.5.2.2.6 Regulations B/C1.4.4.1.3 to B/C1.4.4.1.6, inclusive, shall apply. [12.4.10.7]

B/C1.4.5.2.2.7 Height above surface of the cloud base (0 20 013) shall be reported in metres (with precision in tens of metres).

Note: The term « height above surface » shall be considered as being the height above the official aerodrome elevation or above station elevation at a non-aerodrome station.

B/C1.5 Clouds with bases below station level <3 02 036>

B/C1.5.1 Number of cloud layers with bases below station level

The number of cloud layers with bases below station level shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of cloud layers with bases below station level shall never be set to a missing value.
- (2) The number of cloud layers with bases below station level shall be set to a positive value in a NIL report.
- (3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

- B/C1.5.1.1** Inclusion of these data shall be determined by national decision. The number of cloud layers with bases below station level shall be always set to zero in reports from a station at which observations of clouds with bases below station level are not executed.
- B/C1.5.1.2** When no cloud layers with bases below station are observed, the number of cloud layers with bases below station level shall be set to zero.
- B/C1.5.1.3** If the station is in continuous or almost continuous cloud, the number of cloud layers with bases below station level shall be set to one, with all parameters reported as missing except for vertical significance 0 08 002 that shall be set to 10 (cloud layer with a base below and tops above station level). [12.5.4]
- B/C1.5.1.4** If clouds with bases below station level are not discernible due to fog and/or other phenomena or observation is not made, then the number of cloud layers with bases below station level shall be set to one, with all parameters reported as missing except for vertical significance 0 08 002 that shall be set to 11.
- B/C1.5.1.5** When two or more cloud layers with their bases below station level occur at different levels, two or more cloud layers shall be reported. [12.5.5]
- B/C1.5.1.6** Clouds with bases below and tops above station level shall be reported as the first layer within the sequence 3 02 036, provided that the station is out of cloud sufficiently frequently to enable the various features to be recognized. Other low clouds present with tops below station level shall be reported as the following layers (one or more) within the sequence 3 02 036. [12.5.3]
- Notes:
- (1) Clouds with bases below and tops above station level shall be reported also in sequences 3 02 004 and 3 02 005. [12.5.3]
 - (2) Clouds with tops below station level shall be reported only in sequence 3 02 036, and any co-existent clouds with bases above station level shall be reported only in sequences 3 02 004 and 3 02 005. [12.5.2]
- B/C1.5.2** **Individual cloud layer with base below station level**
- Each cloud layer with base below station level shall be represented by the following five parameters: Vertical significance (0 08 002), amount of clouds with base below station level (0 20 011), type of clouds with base below station level (0 20 012), altitude of the upper surface of clouds (0 20 014) and cloud top description (0 20 017).
- B/C1.5.2.1** **Vertical significance (surface observations) – Code table 0 08 002**
- Code figure 10 shall be used for cloud layers with bases below and tops above station level; code figure 11 shall be used for cloud layers with bases and tops below station level.
- B/C1.5.2.2** **Amount of clouds with base below station level – Code table 0 20 011**
- B/C1.5.2.2.1** Regulations B/C1.4.4.1.1 to B/C1.4.4.1.6, inclusive, shall apply. [12.5.8]
- B/C1.5.2.2.2** Spaces occupied by mountains emerging from the cloud layers shall be counted as occupied by clouds. [12.5.9]
- B/C1.5.2.3** **Type of clouds with base below station level – Code table 0 20 012**
- Type of clouds with bases below station level shall be reported using code figures 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 and 63.

B/C1.5.2.4 Height of top of clouds above mean sea level

Height of top of clouds (0 20 014) shall be used to report the height above mean sea level of the upper surface of clouds, and shall be expressed in metres (with precision in tens of metres).

B/C1.5.2.4.1 Height of top of clouds with bases below and tops above station level shall be reported, provided that the upper surface of clouds can be observed. [12.5.3 (b)]

B/C1.5.2.5 Cloud top description – Code table 0 20 017

B/C1.5.2.5.1 Description of top of clouds with bases below and tops above station level shall be reported, provided that the station is out of cloud sufficiently frequently to enable the features to be recognized.

B/C1.5.2.5.2 Rapidly dissipating condensation trails shall not be reported. However, the top of persistent condensation trails and cloud masses which have obviously developed from condensation trails (and whose bases are below station level) shall be reported in Sequence 3 02 036. [12.5.6], [12.5.7]

B/C1.6 Direction of cloud drift <3 02 047>

This information is required from land stations mainly in the tropics. [12.4.7.5]

B/C1.6.1 Vertical significance (surface observations) – Code table 0 08 002

To specify vertical significance (0 08 002) within the sequence 3 02 047, code figures shall be selected in the following way:

- (a) Code figure 7 (Low cloud) shall be used in the first replication;
- (b) Code figure 8 (Middle clouds) shall be used in the second replication;
- (c) Code figure 9 (High cloud) shall be used in the third replication.

B/C1.6.2 True direction from which clouds are moving

True direction from which low, middle, or high clouds are moving (0 20 054) shall be reported in degrees true as follows:

- (a) True direction from which the low clouds are moving shall be included in the first replication;
- (b) True direction from which the middle clouds are moving shall be included in the second replication;
- (c) True direction from which the high clouds are moving shall be included in the third replication.

B/C1.7 Direction and elevation of cloud <3 02 048>

This information is required from land stations mainly in the tropics. [12.4.7.5]

B/C1.7.1 Direction of cloud

True direction (0 05 021), from which orographic clouds or clouds with vertical development are seen, shall be *reported in degrees true*. The cloud genus shall be specified by the third entry of the sequence 3 02 048, i.e. by Cloud type – Code table 0 20 012.

Note: It is considered sufficient to report direction of cloud in degrees true, although 0 05 021 (Bearing or azimuth) is defined with higher accuracy (hundredths of a degree true).

B/C1.7.2 Elevation of cloud

Elevation angle (0 07 021) of the top of the cloud shall be reported in degrees. The cloud genus shall be specified by the following entry, i.e. by Cloud type – Code table 0 20 012.

Note: It is considered sufficient to report elevation of the top of cloud in degrees, although 0 07 021 (Elevation angle) is defined with higher accuracy (hundredths of a degree).

B/C1.8 State of ground, snow depth, ground minimum temperature <3 02 037>**B/C1.8.1 State of ground** (with or without snow) – Code table 0 20 062

State of ground without snow or with snow shall be reported using Code table 0 20 062. The synoptic hour at which this datum is reported shall be determined by regional decision. In addition to the synoptic hour, this datum should be reported at other synoptic hours, i.e. four times a day.

B/C1.8.2 Total snow depth

Total snow depth (0 13 013) shall be reported in metres (with precision in hundredths of a metre). The synoptic hour at which this datum is reported shall be determined by regional decision. In addition to the synoptic hour, this datum should be reported at other synoptic hours, i.e. four times a day.

B/C1.8.2.1 When total snow depth has to be reported, it is reported as 0.00 m if no snow, ice and other forms of solid precipitation on the ground are observed at the time of observation. A snow depth value of “–0.01 m” shall indicate a little (less than 0.005 m) snow. A snow depth value of “–0.02 m” shall indicate “snow cover not continuous”.

B/C1.8.2.2 The measurement shall include snow, ice and all other forms of solid precipitation on the ground at the time of observation. [12.4.6.1]

B/C1.8.2.3 When the depth is not uniform, the average depth over a representative area shall be reported. [12.4.6.2]

B/C1.8.3 Ground minimum temperature, past 12 hours

Ground minimum temperature from the previous 12 hours (0 12 113) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Ground minimum temperature shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree. This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Ground minimum temperature t (in degrees Celsius) shall be converted into ground minimum temperature T (in kelvin) using equation: $T = t + 273.15$.
- (3) The period of time covered by ground minimum temperature and the synoptic hour at which this temperature is reported shall be determined by regional decision. If ground minimum temperature is to be reported from the period of previous night, then “ground minimum temperature, past 12 hours” (0 12 113) shall be reported as a missing value. In this case, ground minimum temperature of the previous night (0 12 122) shall be reported as shown in Common sequences 3 07 081, 3 07 082 and 3 07 083 suitable for SYNOP data in compliance with reporting practices in RA I, RA II and RA III, respectively.

B/C1.9 “Instantaneous” data required by regional or national reporting practices

If regional or national reporting practices require inclusion of additional “instantaneous” parameters, the sequence descriptor 3 07 080 shall be supplemented by the required element descriptors being preceded by a relevant time period descriptor set to zero, i.e. 0 04 024 = 0 or 0 04 025 = 0.

Note: “Instantaneous” parameter is a parameter that is not coupled to a time period descriptor, e.g. 0 04 024, 0 04 025.

B/C1.9.1 “Instantaneous” data required by reporting practices in RA I

Regulations for reporting additional “instantaneous” parameters, required by regional reporting practices in RA I, are shown in the annex to B/C1.

B/C1.9.2 “Instantaneous” data required by reporting practices in RA II

Regulations for reporting additional “instantaneous” parameters, required by regional reporting practices in RA II, are shown in the annex to B/C1.

B/C1.9.3 “Instantaneous” data required by reporting practices in RA III

Regulations for reporting additional “instantaneous” parameters, required by regional reporting practices in RA III, are shown in the annex to B/C1.

B/C1.9.4 “Instantaneous” data required by reporting practices in RA IV

Regulations for reporting additional “instantaneous” parameters, required by regional reporting practices in RA IV, are shown in the annex to B/C1.

B/C1.9.5 “Instantaneous” data required by reporting practices in RA V

No regional requirements are indicated for reporting SYNOP data in RA V.

B/C1.9.6 “Instantaneous” data required by reporting practices in RA VI

Regulations for reporting additional “instantaneous” parameters, required by regional reporting practices in RA VI, are shown in the annex to B/C1.

B/C1.10 Basic synoptic “period” data <3 02 043>**B/C1.10.1 Present and past weather <3 02 038>****B/C1.10.1.1**

Present weather (Code table 0 20 003) and past weather (1) (Code table 0 20 004) and past weather (2) (Code table 0 20 005) shall be reported as non-missing values if present and past conditions are known. In case of a report from a manually operated station after a period of closure or at start up, when past weather conditions for the period applicable to the report are unknown, past weather (1) and past weather (2) reported as missing shall indicate that previous conditions are unknown. This regulation shall also apply to automatic reporting stations with the facility to report present and past weather. [12.2.6.1]

B/C1.10.1.2

Code figures 0, 1, 2, 3, 100, 101, 102 and 103 for present weather and code figures 0, 1, 2 and 10 for past weather (1) and past weather (2) shall be considered to represent phenomena without significance. [12.2.6.2]

B/C1.10.1.3

Present and past weather shall be *reported if observation was made (data available), regardless significance of the phenomena.*

Note: If data are produced and collected in traditional codes and present weather and past weather is omitted in a SYNOP report (no significant phenomena observed),

code figure 508 shall be used for present weather and code figure 10 for past weather (1) and past weather (2) when converted into BUFR or CREX.

B/C1.10.1.4 If no observation was made (data not available), code figure 509 shall be used for present weather and both past weather (1) and past weather (2) shall be reported as missing.

B/C1.10.1.5 Present weather from a manned weather station

B/C1.10.1.5.1 If more than one form of weather is observed, the highest applicable code figure from the range <00 to 99> shall be selected for present weather. Code figure 17 shall have precedence over code figures 20–49. Other weather may be reported using additional entries 0 20 003 or 0 20 021 to 0 20 026 applying Regulation B/C1.9. [12.2.6.4.1]

B/C1.10.1.5.2 In coding 01, 02, or 03, there is no limitation on the magnitude of the change of the cloud amount. Code figures 00, 01, and 02 can each be used when the sky is clear at the time of observation. In this case, the following interpretation of the specifications shall apply:

- 00 is used when the preceding conditions are not known;
- 01 is used when the clouds have dissolved during the past hour;
- 02 is used when the sky has been continuously clear during the past hour.

[12.2.6.4.2]

B/C1.10.1.5.3 When the phenomenon is not predominantly water droplets, the appropriate code figure shall be selected without regard to visibility. [12.2.6.4.3]

B/C1.10.1.5.4 The code figure 05 shall be used when the obstruction to vision consists predominantly of lithometeors. [12.2.6.4.4]

B/C1.10.1.5.5 National instructions shall be used to indicate the specifications for code figures 07 and 09. [12.2.6.4.5]

B/C1.10.1.5.6 The visibility restrictions on code figure 10 shall be 1 000 metres or more. The specification refers only to water droplets and ice crystals. [12.2.6.4.6]

B/C1.10.1.5.7 For code figures 11 or 12 to be reported, the apparent visibility shall be less than 1 000 metres. [12.2.6.4.7]

B/C1.10.1.5.8 For code figure 18, the following criteria for reporting squalls shall be used:

- (a) When wind speed is measured: A sudden increase of wind speed of at least eight metres per second, the speed rising to 11 metres per second or more and lasting for at least one minute;
- (b) When the Beaufort scale is used for estimating wind speed: A sudden increase of wind speed by at least three stages of the Beaufort scale, the speed rising to force 6 or more and lasting for at least one minute.

[12.2.6.4.8]

B/C1.10.1.5.9 Code figures 20–29 shall never be used when precipitation is observed at the time of observation. [12.2.6.4.9]

B/C1.10.1.5.10 For code figure 28, visibility shall have been less than 1 000 metres.

Note: The specification refers only to visibility restrictions which occurred as a result of water droplets or ice crystals.

[12.2.6.4.10]

- B/C1.10.1.5.11** For synoptic coding purposes, a thunderstorm shall be regarded as being at the station from the time thunder is first heard, whether or not lightning is seen or precipitation is occurring at the station. A thunderstorm shall be reported if thunder is heard within the normal observational period preceding the time of the report. A thunderstorm shall be regarded as having ceased at the time thunder is last heard and the cessation is confirmed if thunder is not heard for 10–15 minutes after this time. [12.2.6.4.11]
- B/C1.10.1.5.12** The necessary uniformity in reporting code figures 36, 37, 38, and 39, which may be desirable within certain regions, shall be obtained by means of national instructions. [12.2.6.4.12]
- B/C1.10.1.5.13** A visibility restriction « less than 1 000 metres » shall be applied to code figures 42–49. In the case of code figures 40 or 41, the apparent visibility in the fog or ice fog patch or bank shall be less than 1 000 metres. Code figures 40–47 shall be used when the obstructions to vision consist predominantly of water droplets or ice crystals, and 48 or 49 when the obstructions consist predominantly of water droplets. [12.2.6.4.13]
- B/C1.10.1.5.14** When referring to precipitation, the phrase « at the station » in the code table shall mean « at the point where the observation is normally taken ». [12.2.6.4.14]
- B/C1.10.1.5.15** The precipitation shall be encoded as intermittent if it has been discontinuous during the preceding hour, without presenting the character of a shower. [12.2.6.4.15]
- B/C1.10.1.5.16** The intensity of precipitation shall be determined by the intensity at the time of the observation. [12.2.6.4.16]
- B/C1.10.1.5.17** Code figures 80–90 shall be used only when the precipitation is of the shower type and takes place at the time of the observation.
- Note: Showers are produced by convective clouds. They are characterized by their abrupt beginning and end and by the generally rapid and sometimes great variations in the intensity of the precipitation. Drops and solid particles falling in a shower are generally larger than those falling in non-showery precipitation. Between showers openings may be observed unless stratiform clouds fill the intervals between the cumuliform clouds.
- [12.2.6.4.17]
- B/C1.10.1.5.18** In reporting code figure 98, the observer shall be allowed considerable latitude in determining whether precipitation is or is not occurring, if it is not actually visible. [12.2.6.4.18]
- B/C1.10.1.6 Present weather from an automatic weather station**
- B/C1.10.1.6.1** The highest applicable code figure shall be selected. [12.2.6.5.1]
- B/C1.10.1.6.2** In coding code figures 101, 102, and 103, there is no limitation on the magnitude of the change of the cloud amount. Code figures 100, 101, and 102 can each be used when the sky is clear at the time of observation. In this case, the following interpretation of the specifications shall apply:
- Code figure 100 is used when the preceding conditions are not known;
 - Code figure 101 is used when the clouds have dissolved during the past hour;
 - Code figure 102 is used when the sky has been continuously clear during the past hour.
- [12.2.6.5.2]

- B/C1.10.1.6.3** When the phenomenon is not predominantly water droplets, the appropriate code figure shall be selected without regard to the visibility. [12.2.6.5.3]
- B/C1.10.1.6.4** The code figures 104 and 105 shall be used when the obstruction to vision consists predominantly of lithometeors. [12.2.6.5.4]
- B/C1.10.1.6.5** The visibility restriction on code figure 110 shall be 1 000 metres or more. The specification refers only to water droplets and ice crystals. [12.2.6.5.5]
- B/C1.10.1.6.6** For code figure 118, the following criteria for reporting squalls shall be used:
A sudden increase of wind speed of at least eight metres per second, the speed rising to 11 metres per second or more and lasting for at least one minute.
[12.2.6.5.6]
- B/C1.10.1.6.7** Code figures 120–126 shall never be used when precipitation is observed at the time of observation. [12.2.6.5.7]
- B/C1.10.1.6.8** For code figure 120, visibility shall have been less than 1 000 metres.

Note: The specification refers only to visibility restrictions which occurred as a result of water droplets or ice crystals.
[12.2.6.5.8]
- B/C1.10.1.6.9** For synoptic coding purposes, a thunderstorm shall be regarded as being at the station from the time thunder is first detected, whether or not lightning is detected or precipitation is occurring at the station. A thunderstorm shall be reported in present weather if thunder is detected within the normal observational period preceding the time of the report. A thunderstorm shall be regarded as having ceased at the time thunder is last detected and the cessation is confirmed if thunder is not detected for 10–15 minutes after this time. [12.2.6.5.9]
- B/C1.10.1.6.10** A visibility restriction « less than 1 000 metres » shall be applied to code figures 130–135. [12.2.6.5.10]
- B/C1.10.1.6.11** The precipitation shall be encoded as intermittent if it has been discontinuous during the preceding hour, without presenting the character of a shower.
[12.2.6.5.11]
- B/C1.10.1.6.12** The intensity of precipitation shall be determined by the intensity at the time of observation. [12.2.6.5.12]
- B/C1.10.1.6.13** Code figures 180–189 shall be used only when the precipitation is intermittent or of the shower type and takes place at the time of observation.

Note: Showers are produced by convective clouds. They are characterized by their abrupt beginning and end and by the generally rapid and sometimes great variations in the intensity of the precipitation. Drops and solid particles falling in a shower are generally larger than those falling in non-showery precipitation. Between showers openings may be observed unless stratiform clouds fill the intervals between the cumuliform clouds.
[12.2.6.5.13]
- B/C1.10.1.7 Past weather reported from a manned weather station**
- B/C1.10.1.7.1 Time period**
The time period (0 04 024) covered by past weather (1) and past weather (2) shall be expressed as a *negative value* in hours:

- (a) Six hours, for observations at 0000, 0600, 1200, and 1800 UTC;
- (b) Three hours for observations at 0300, 0900, 1500, and 2100 UTC;
- (c) Two hours for intermediate observations if taken every two hours;
- (d) *One hour* for intermediate observations if taken every hour.

[12.2.6.6.1]

B/C1.10.1.7.2 The code figures for past weather (1) and past weather (2) shall be selected in such a way that past and present weather together give as complete a description as possible of the weather in the time interval concerned. For example, if the type of weather undergoes a complete change during the time interval concerned, the code figures selected for past weather (1) and past weather (2) shall describe the weather prevailing before the type of weather indicated by present weather began. [12.2.6.6.2]

B/C1.10.1.7.3 When the past weather (1) and past weather (2) are used in hourly reports, Regulation B/C1.10.1.7.1 (d) shall apply. [12.2.6.6.3]

B/C1.10.1.7.4 If, using Regulation B/C1.10.1.7.2, more than one code figure may be given to past weather (1), the highest figure shall be reported for past weather (1) and the second highest code figure shall be reported for past weather (2). [12.2.6.6.4]

B/C1.10.1.7.5 If the weather during the period has not changed so that only one code figure may be selected for past weather, then that code figure shall be reported for both past weather (1) and past weather (2). [12.2.6.6.5]

B/C1.10.1.8 Past weather reported from an automatic weather station

B/C1.10.1.8.1 Time period

The time period (0.04 024) covered by past weather (1) and past weather (2) shall be expressed as *a negative value* in hours:

- (a) Six hours for observations at 0000, 0600, 1200, and 1800 UTC;
- (b) Three hours for observations at 0300, 0900, 1500, and 2100 UTC;
- (c) Two hours for intermediate observations if taken every two hours;
- (d) *One hour* for intermediate observations if taken every hour.

[12.2.6.7.1]

B/C1.10.1.8.2 The code figures for past weather (1) and past weather (2) shall be selected so that the maximum capability of the automatic station to discern past weather is utilized, and so that past and present weather together give as complete a description as possible of the weather in the time interval concerned. [12.2.6.7.2]

B/C1.10.1.8.3 In cases where the automatic station is capable only of discerning very basic weather conditions, the lower code figures representing basic and generic phenomena may be used. If the automatic station has higher discrimination capabilities, the higher code figures representing more detailed explanation of the phenomena shall be used. For each basic type of phenomenon, the highest code figure within the discrimination capability of the automatic station shall be reported. [12.2.6.7.3]

B/C1.10.1.8.4 If the type of weather during the time interval concerned undergoes complete and discernible changes, the code figures selected for past weather (1) and past weather (2) shall describe the weather prevailing before the type of weather indicated by present weather began. The highest figure shall be reported for past

weather (1) and the second highest code figure shall be reported for past weather (2). [12.2.6.7.4]

B/C1.10.1.8.5 If a discernible change in weather has not occurred during the period, so that only one code figure may be selected for the past weather, then that code figure shall be reported for both past weather (1) and past weather (2). For example, rain during the entire period shall be reported as code figure 14 for both past weather (1) and past weather (2) in the case of an automatic station incapable of differentiating types of precipitation, or code figure 16 for both past weather (1) and past weather (2) in the case of a station with the higher discrimination capability. [12.2.6.7.5]

B/C1.10.2 **Sunshine data (from 1 hour and 24-hour period) <1 01 002><3 02 039>**

B/C1.10.2.1 **Period of reference for sunshine duration**

Time period in hours (0 04 024) shall be included as follows:

- (a) one hour in the first replication (reported as –1);
- (b) 24 hours in the second replication (reported as –24).

B/C1.10.2.2 **Duration of sunshine**

Duration of sunshine from the time period specified by the preceding parameter 0 04 024, shall be reported in minutes.

B/C1.10.2.2.1 The duration of sunshine over the previous hour shall be reported by national decision. When reported, it shall be included in the first replication.

B/C1.10.2.2.2 The duration of sunshine over the previous 24 hours shall, by regional decision, be reported at all stations capable of doing so and included at either 0000 UTC, 0600 UTC, 1200 UTC or 1800 UTC. When reported, it shall be included in the second replication. [12.4.7.4.2]

B/C1.10.3 **Precipitation measurement <3 02 040>**

B/C1.10.3.1 **Height of sensor above local ground**

Height of sensor above local ground (0 07 032) for precipitation measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the rain gauge rim above ground at the point where the rain gauge is located.

B/C1.10.3.2 **Period of reference for amount precipitation**

Time period (0 04 024) for amount of precipitation shall be reported as a *negative value* in hours. It shall be determined:

- (a) by regional decision (e.g. –6, –12, –24) in the first replication;
- (b) by national decision (e.g. –1, –3) in the second replication.

B/C1.10.3.3 **Total amount of precipitation**

Total amount of precipitation, which has fallen during the period of reference for amount of precipitation, shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre).

B/C1.10.3.3.1 Precipitation, when it can be and has to be reported, shall be reported as 0.0 kg m⁻² if no precipitation were observed during the referenced period. [12.2.5.4]

B/C1.10.3.3.2 Trace shall be reported as “–0.1 kg m⁻²”.

B/C1.10.4 Extreme temperature data <3 02 041>

B/C1.10.4.1 Height of sensor above local ground

Height of sensor above local ground (0 07 032) for temperature measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of temperature sensor(s) above ground at the point where the sensors are located.

B/C1.10.4.2 Periods of reference for extreme temperatures

Time period for maximum temperature and time period for minimum temperature (0 04 024) shall be determined by regional decision and reported as *negative values* in hours. [12.4.4]

Notes:

- (1) If the period for maximum temperature or the period for minimum temperature ends at the nominal time of report, the second value of 0 04 024 shall be reported as 0.
- (2) If the period for maximum temperature or the period for minimum temperature does not end at the nominal time of report, the first value of 0 04 024 shall indicate the beginning of the period of reference and the second value of 0 04 024 shall indicate the end of the period of reference. E.g. to report the maximum temperature for the previous calendar day from a station in RA IV, value of the first 0 04 024 shall be set to –30 and value of the second 0 04 024 shall be set to –6, provided that the nominal time of the report 12 UTC corresponds to 6 a.m. local time.

B/C1.10.4.3 Maximum and minimum temperature

Maximum and minimum temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Extreme temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree.

Note: Notes 1 and 2 under Regulation B/C1.4.1.2 shall apply.

B/C1.10.5 Wind data <3 02 042>

B/C1.10.5.1 Height of sensor above local ground

Height of sensor above local ground (0 07 032) for wind measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the sensors above ground at the point where the sensors are located.

B/C1.10.5.2 Type of instrumentation for wind measurement – Flag table 0 02 002

This datum shall be used to specify whether the wind speed was measured by certified instruments (bit No. 1 set to 1) or estimated on the basis of the Beaufort wind scale (bit No. 1 set to 0), and to indicate the original units for wind speed measurement. Bit No. 2 set to 1 indicates that wind speed was originally measured in knots and bit No. 3 set to 1 indicates that wind speed was originally measured in kilometres per hour. Setting both bits No. 2 and No. 3 to 0 indicates that wind speed was originally measured in metres per second.

In CREX, type of instrumentation for wind measurement (0 02 002) shall be reported in octal representation. For example, if wind speed was measured by

instruments in knots (bit No. 1 and bit No. 2 set to 1), then this datum shall be reported as 14.

B/C1.10.5.3 Wind direction and speed

The mean direction and speed of the wind over the 10-minute period immediately preceding the observation shall be reported. The time period (0 04 025) shall be included as –10. However, when the 10-minute period includes a discontinuity in the wind characteristics, only data obtained after the discontinuity shall be used for reporting the mean values, and hence the period (0 04 025) in these circumstances shall be correspondingly reduced. [12.2.2.3.1]

The time period is preceded by a time significance qualifier (0 08 021) that shall be set to 2 (Time averaged).

The wind direction (0 11 001) shall be reported in degrees true and the wind speed (0 11 002) shall be reported in metres per second (with precision in tenths of a metre per second).

Note: Surface wind direction measured at a station within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian.

B/C1.10.5.3.1 In the absence of wind instruments, the wind speed shall be estimated on the basis of the Beaufort wind scale. The Beaufort number obtained by estimation is converted into metres per second by use of the relevant wind speed equivalent column on the Beaufort scale, and this speed is reported for wind speed. [12.2.2.3.2]

B/C1.10.5.3.2 Calm shall be reported by setting wind direction to 0 and wind speed to 0. Variable shall be reported by setting wind direction to 0 and wind speed to a positive *non-missing* value.

B/C1.10.5.4 Maximum wind gust direction and speed

Time period for maximum wind gust direction and speed (0 04 025) shall be determined by regional or national decision and reported as a negative value in minutes.

Direction of the maximum wind gust (0 11 043) shall be reported in degrees true and speed of the maximum wind gust (0 11 041) shall be reported in metres per second (with precision in tenths of a metre per second).

B/C1.11 Evaporation data <3 02 044>

B/C1.11.1 Period of reference for evaporation data

Evaporation or evapotranspiration during the previous 24 hours shall be reported. Time period in hours (0 04 024) shall be included as –24.

B/C1.11.2 Indicator of type of instrument for evaporation measurement or the type of crops – Code table 0 02 004

B/C1.11.3 Evaporation or evapotranspiration

Amount of either evaporation or evapotranspiration (0 13 033) shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre) at 0000 UTC, 0600 UTC or 1200 UTC. [12.4.7.2.2]

B/C1.12 Radiation data (from 1 hour and 24-hour period) <1 01 002><3 02 045>**B/C1.12.1 Period of reference for radiation data**

Radiation integrated over the previous hour and over the previous 24 hours may be reported. Time period in hours (0 04 024) shall be included as follows:

- (a) one hour in the first replication (reported as –1);
- (b) 24 hours in the second replication (reported as –24).

B/C1.12.2 Amount of radiation

If included, amount of radiation integrated over the time period specified by the preceding parameter 0 04 024 shall be reported in joules per square metre (with precision in thousands of a joule per square metre for radiation type (a) and (b); with precision in ten-thousands of a joule per square metre for radiation type (c); with precision in hundreds of a joule per square metre for radiation types (d) to (f)).

B/C1.12.2.1 The radiation data may take one or more of the following forms:

- (a) Long-wave radiation (0 14 002); the positive sign shall be used to specify downward long-wave radiation and the negative sign to specify upward long-wave radiation;
 - (b) Short-wave radiation (0 14 004);
 - (c) Net radiation (0 14 016); the corresponding sign shall be used to specify positive and negative net radiation;
 - (d) Global solar radiation (0 14 028);
 - (e) Diffuse solar radiation (0 14 029);
 - (f) Direct solar radiation (0 14 030).
- [12.4.7.4.3], [12.4.7.4.4]

Note: Data width and/or reference value of radiation descriptors were changed with introduction of the Version number 14 of WMO FM 94 BUFR Tables.

B/C1.13 Temperature change <3 02 046>

This information is required by regional or national decision from islands or other widely separated stations.

B/C1.13.1 Period of reference for temperature change

The temperature change shall be reported for the period of time between the time of the observation and the time of the occurrence of temperature change. To construct the required period, time period 0 04 024 shall be included twice; the first one corresponding to period covered by past weather (1) and past weather (2), the second one specified by the time of the occurrence of temperature change. Both values of 0 04 024 shall be negative and expressed in hours.

Note: The period is the number of whole hours, disregarding the minutes. For example, if the time of occurrence is 45 minutes after the time of the observation, the time period is considered to be zero hours. If the time of occurrence is 1 hour or more, but less than 2 hours after the observation, the time period shall be considered to be 1 hour, etc.

B/C1.13.2 Temperature change over period specified

Temperature change (0 12 049) shall be reported in kelvin in BUFR, in degrees Celsius in CREX.

- B/C1.13.2.1** For a change of temperature to be reported, the change shall be equal to or more than 5°C and occur in less than 30 minutes during the period covered by past weather (1) and past weather (2). [12.4.7.3]

B/C1.14 “Period” data required by regional or national reporting practices

If regional reporting practices in a Region require inclusion of additional “period” parameters, the corresponding “regional” common sequence (see the annex to B/C1) shall be supplemented by relevant descriptors. If national reporting practices require inclusion of additional “period” parameters, either the common sequence 3 07 080 or any of the common sequences 3 07 081 to 3 07 086, whichever is the most convenient, shall be supplemented by relevant descriptors

Notes:

- (1) “Period” parameter is a parameter that is coupled to a time period descriptor, e.g. 0 04 024, 0 04 025.
- (2) No additional “period” parameters are currently required by regional regulations for SYNOP data in the *Manual on Codes* (WMO-No. 306), Volume II.

Provisional Copy
2023

ANNEX to B/C1 – Regional regulations for reporting SYNOP data in TDCF

Regional regulations for reporting SYNOP data in BUFR/CREX for RA I

TM 307081 – BUFR template for synoptic reports from fixed land stations suitable for SYNOP data in compliance with reporting practices in RA I

3 07 081:

		Unit, scale
3 01 090	Surface station identification; time, horizontal and vertical coordinates	
3 02 031	Pressure information	
3 02 035	Basic synoptic “instantaneous” data	
3 02 036	Clouds with bases below station level	
3 02 047	Direction of cloud drift	
0 08 002	Vertical significance (surface observations) (= missing to cancel the previous value)	Code table, 0
3 02 048	Direction and elevation of cloud	
3 02 037	State of ground, snow depth, ground minimum temperature (past 12 hours)	
0 12 122	Ground minimum temperature of the preceding night $s_n T_q T_q$	K, 2
0 13 056	Character and intensity of precipitation R_c	Code table, 0
0 13 057	Time of beginning or end of precipitation R_t	Code table, 0
0 20 101	Locust (acridian) name L_n	Code table, 0
0 20 102	Locust (maturity) colour L_c	Code table, 0
0 20 103	Stage of development of locusts L_d	Code table, 0
0 20 104	Organization state of swarm or band of locusts L_g	Code table, 0
0 20 105	Size of swarm or band of locusts and duration of passage of swarm s_L	Code table, 0
0 20 106	Locust population density d_L	Code table, 0
0 20 107	Direction of movements of locust swarm D_L	Code table, 0
0 20 108	Extent of vegetation v_e	Code table, 0
3 02 043	Basic synoptic “period” data	
3 02 044	Evaporation data	
1 01 002	Replicate 1 descriptor 2 times	
3 02 045	Radiation data (from 1 hour and 24-hour period)	
3 02 046	Temperature change	

Regulations:

General

- (i) BUFR template TM 307081 shall not be mandatory for Members in Region I. Either the template TM 307080 or any of the templates TM 307081, TM 307182, TM 307083 to TM 307086, whichever is the most convenient, may be used.
- (ii) Regulations B/C1.1 to B/C1.9, inclusive, shall apply.
- (iii) Regulations B/C1.10 to B/C1.14, inclusive, shall apply.

B/C1.9.1 “Instantaneous” data required by reporting practices in RA I**B/C1.9.1.1 Ground minimum temperature of the preceding night**

Ground minimum temperature of the preceding night (0 12 122) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Notes 1, 2 and 3 under Regulation B/C1.8.3 shall apply.
- (2) This datum shall be reported by all Members at 0600 UTC. [1/12.6.1]

B/C1.9.1.2 Character, intensity and time of beginning or end of precipitation

Character and intensity of precipitation (Code table 0 13 056) and Time of beginning or end of precipitation (Code table 0 13 057) shall be reported by all Members at 0600 UTC to meet requirements of agrometeorological monitoring in the Region. [1/12.6.1] Inclusion of these data into reports at 0000 and 1200 UTC shall be left to national decision. [1/12.6.3]

B/C1.9.1.3 Locust control-related observations

Following data shall be reported by all Members capable of doing so:

- (a) Locust (acridian) name (Code table 0 20 101);
- (b) Locust (maturity) color (Code table 0 20 102);
- (c) Stage of development of locusts (Code table 0 20 103);
- (d) Organization state of swarm or band of locusts (Code table 0 20 104);
- (e) Size of swarm or band of locusts and duration of passage of swarm (Code table 0 20 105);
- (f) Locust population density (Code table 0 20 106);
- (g) Direction of movements of locust swarm (Code table 0 20 107);
- (h) Extent of vegetation (Code table 0 20 108).

[1/12.14.1]

Regional regulations for reporting SYNOP data in BUFR/CREX for RA II

TM 307182 – BUFR template for synoptic reports from fixed land stations suitable for SYNOP data in compliance with reporting practices in RA II

3 07 182:

		Unit, scale
3 01 090	Surface station identification; time, horizontal and vertical coordinates	
3 02 031	Pressure information	
3 02 035	Basic synoptic “instantaneous” data	
3 02 036	Clouds with bases below station level	
3 02 047	Direction of cloud drift	
0 08 002	Vertical significance (surface observations) (= missing to cancel the previous value)	Code table, 0
3 02 048	Direction and elevation of cloud	
3 02 037	State of ground, snow depth, ground minimum temperature (past 12 hours)	
0 12 120	Ground temperature $s_n T'_g T'_g$	K, 2
0 12 122	Ground minimum temperature of the preceding night $s_n T_g T_g$	K, 2
3 02 043	Basic synoptic “period” data	
3 02 044	Evaporation data	
1 01 002	Replicate 1 descriptor 2 times	
3 02 045	Radiation data (from 1 hour and 24-hour period)	
3 02 046	Temperature change	

Regulations:

General

- (i) BUFR template TM 307182 shall not be mandatory for Members in Region II. Either the template TM 307080 or any of the templates TM 307081, TM 307182, TM 307083 to TM 307086, whichever is the most convenient, may be used.
- (ii) Regulations B/C1.1 to B/C1.9, inclusive, shall apply.
- (iii) Regulations B/C1.10 to B/C1.14, inclusive, shall apply.
- (iv) BUFR template TM 307182 is recommended to be used instead of TM 307082 to allow reporting of Ground temperature (0 12 120).

B/C1.9.2 “Instantaneous” data required by reporting practices in RA II

B/C1.9.2.1 Ground temperature

Ground temperature measured at the time of observation (0 12 120) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Notes 1 and 2 under Regulation B/C1.8.3 shall apply.
- (2) Inclusion of this datum into reports at least at 0000 and 1200 UTC shall be left to national decision. [2/12.6.1]

B/C1.9.2.2 Ground minimum temperature of the preceding night

Ground minimum temperature of the preceding night (0 12 122) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1, 2 and 3 under Regulation B/C1.8.3 shall apply.

Provisional Copy
2023

Regional regulations for reporting SYNOP data in BUFR/CREX for RA III

TM 307083 – BUFR template for synoptic reports from fixed land stations suitable for SYNOP data in compliance with reporting practices in RA III

3 07 083:

		Unit, scale
3 01 090	Surface station identification; time, horizontal and vertical coordinates	
3 02 031	Pressure information	
3 02 035	Basic synoptic “instantaneous” data	
3 02 036	Clouds with bases below station level	
3 02 047	Direction of cloud drift	
0 08 002	Vertical significance (surface observations) (= missing to cancel the previous value)	Code table, 0
3 02 048	Direction and elevation of cloud	
3 02 037	State of ground, snow depth, ground minimum temperature (past 12 hours)	
0 12 122	Ground minimum temperature of the preceding night $s_n T_g T_g$	K, 2
3 02 043	Basic synoptic “period” data	
3 02 044	Evaporation data	
1 01 002	Replicate 1 descriptor 2 times	
3 02 045	Radiation data (from 1 hour and 24-hour period)	
3 02 046	Temperature change	

Regulations:

General

- (i) BUFR template TM 307083 shall not be mandatory for Members in Region III. Either the template TM 307080 or any of the templates TM 307081, TM 307182, TM 307083 to TM 307086, whichever is the most convenient, may be used.
- (ii) Regulations B/C1.1 to B/C1.9, inclusive, shall apply.
- (iii) Regulations B/C1.10 to B/C1.14, inclusive, shall apply.

B/C1.9.3 “Instantaneous” data required by reporting practices in RA III

B/C1.9.3.1 Ground minimum temperature of the preceding night

Ground minimum temperature of the preceding night (0 12 122) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Notes 1, 2 and 3 under Regulation B/C1.8.3 shall apply.
- (2) This datum shall be included into reports at 1200 UTC, if possible. [3/12.7.2]

Regional regulations for reporting SYNOP data in BUFR/CREX for RA IV

TM 307084 – BUFR template for synoptic reports from fixed land stations suitable for SYNOP data in compliance with reporting practices in RA IV

3 07 084:

		Unit, scale
3 01 090	Surface station identification; time, horizontal and vertical coordinates	
3 02 031	Pressure information	
3 02 035	Basic synoptic “instantaneous” data	
3 02 036	Clouds with bases below station level	
3 02 047	Direction of cloud drift	
0 08 002	Vertical significance (surface observations) (= missing to cancel the previous value)	Code table, 0
3 02 048	Direction and elevation of cloud	
3 02 037	State of ground, snow depth, ground minimum temperature (past 12 hours)	
0 20 055	State of sky in the tropics C_s	Code table, 0
1 01 000	Delayed replication of 1 descriptor	
0 31 001	Delayed descriptor replication factor	Numeric, 0
2 05 001	Signify character	CCITT IA5, 0
3 02 043	Basic synoptic “period” data	
3 02 044	Evaporation data	
1 01 002	Replicate 1 descriptor 2 times	
3 02 045	Radiation data (from 1 hour and 24-hour period)	
3 02 046	Temperature change	

Regulations:

General

- (i) BUFR template TM 307084 shall not be mandatory for Members in Region IV. Either the template TM 307080 or any of the templates TM 307081, TM 307182, TM 307083 to TM 307086, whichever is the most convenient, may be used.
- (ii) Regulations B/C1.1 to B/C1.9, inclusive, shall apply.
- (iii) Regulations B/C1.10 to B/C1.14, inclusive, shall apply.

B/C1.9.4 “Instantaneous” data required by reporting practices in RA IV

B/C1.9.4.1 State of sky in tropics

State of sky in tropics (Code table 0 02 055) shall be reported only by stations in the southern part of Region IV, below 1 000 m elevation and within 500 kilometres of the shore, and only during the part of the year in which tropical weather is observed. Direction of cloud drift shall be reported using sequence 3 02 047. [4/12.4.2]

B/C1.9.4.2 Additional information in plain language

Information in plain language shall be reported as a character field, using delayed replication of the operator descriptor 2 05 001. The value of the delayed replication factor 0 31 001 shall correspond with the number of characters required for the reported information (space characters included). For example, if the word TORNADO is included in the report (tornado has been observed at, or within sight of, the station [4/12.14.1]), delayed replication factor 0 31 001 shall be set to 7.

Provisional Copy
2023

Regional regulations for reporting SYNOP data in BUFR/CREX for RA VI

TM 307086 – BUFR template for synoptic reports from fixed land stations suitable for SYNOP data in compliance with reporting practices in RA VI

3 07 086:

			Unit, scale
3 01 090		Surface station identification; time, horizontal and vertical coordinates	
3 02 031		Pressure information	
3 02 035		Basic synoptic “instantaneous” data	
3 02 036		Clouds with bases below station level	
0 08 002		Vertical significance (surface observations) (= missing to cancel the previous value)	Code table, 0
3 02 037		State of ground, snow depth, ground minimum temperature	
3 02 066		Dangerous weather phenomena	
		Groups 919M_wD_a and 96119 in SYNOP	
	0 20 023	Other weather phenomena (1 = Dust/sand whirl, 9 = Funnel cloud not touching surface, 10 = Funnel cloud touching surface, 12 = Waterspout) M _w	Flag table, 0
	0 20 024	Intensity of phenomena (1 = Light, 2 = Moderate, 3 = Heavy, 4 = Violent)	Code table, 0
	0 20 027	Phenomenon occurrence (1 = At time of observation, 3 = In time period for past weather)	Flag table, 0
	0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed D _a	Degree true, 0
		Group 918s_qD_p in SYNOP	
	0 20 023	Other weather phenomena (2 = Squalls) s _q	Flag table, 0
	0 20 027	Phenomenon occurrence (1 = At time of observation, 3 = In time period for past weather)	Flag table, 0
	0 20 054	True direction from which a phenomenon or clouds are moving or in which they are observed D _p	Degree true, 0
		Group 929S₈S'₈ in SYNOP	
	0 20 025	Obscuration (13 = Snow)	Flag table, 0
	0 20 026	Character of obscuration (5 = Low drifting, 6 = Blowing) S ₈	Code table, 0
	0 20 027	Phenomenon occurrence (1 = At time of observation, 3 = In time period for past weather)	Flag table, 0
	0 20 040	Evolution of drift of snow S' ₈	Code table, 0
		Group 932RR	
	0 20 066	Maximum diameter of hailstones RR	m, 3
	0 20 027	Phenomenon occurrence (1 = At time of observation, 3 = In time period for past weather)	Flag table, 0
		Groups 934RR – 937RR in SYNOP	
	0 20 021	Type of precipitation (15 = Glaze, 16 = Rime, 20 = Wet snow)	Flag table, 0
	0 20 067	Diameter of deposit RR	m, 3
	0 20 027	Phenomenon occurrence (1 = At time of observation, 3 = In time period for past weather)	Flag table, 0

			Unit, scale
3 02 043		Basic synoptic “period” data	
3 02 044		Evaporation data	
1 01 002		Replicate 1 descriptor 2 times	
3 02 045		Radiation data (from 1 hour and 24-hour period)	

Note: Groups 56D_LD_MD_H, 57CD_ae_C and 54g₀s_nd_T are not used in RA VI and therefore the corresponding sequence descriptors 3 02 047, 3 02 048 and 3 02 046 are not included in the RA VI regional template for SYNOP data.

Regulations:

General

- (i) BUFR template TM 307086 shall not be mandatory for Members in Region VI. Either the template TM 307080 or any of the templates TM 307081, TM 307182, TM 307083 to TM 307086, whichever is the most convenient, may be used.
- (ii) Regulations B/C1.1 to B/C1.9, inclusive, shall apply.
- (iii) Regulations B/C1.10 to B/C1.14, inclusive, shall apply.

B/C1.9.6 “Instantaneous” data required by reporting practices in RA VI

B/C1.9.6.1 Dangerous weather phenomena

Sequence 3 02 066 should be used for regional exchange of data on dangerous phenomena. Reporting of other phenomena shall be left to national decision. [6/12.12.2]

B/C1.9.6.1.1 Tornado, waterspout, whirlwinds and dust devils

Tornadoes, waterspouts, whirlwinds and dust devils between observation times shall be reported using two parameters: Other weather phenomena (Flag table 0 20 023) and Intensity of phenomena (Code table 0 20 024). Occurrence of the phenomenon (Flag table 0 20 027) shall be specified by setting bit No. 3 to 1 (In time period for past weather).

B/C1.9.6.1.2 Squall

Squalls between observation times shall be reported using Flag table 0 20 023 (bit No. 2 set to 1). Occurrence of the phenomenon (Flag table 0 20 027) shall be specified by setting bit No. 3 to 1 (In time period for past weather). True direction from which the squall approaches the station (0 20 054) shall be reported in degrees true. If more detailed information on occurrence and the nature and/or type of the squall is to be reported, 3 07 086 should be supplemented by two consecutive 0 04 024, by special phenomena 0 20 063 (using code figures 50 to 59) and by 0 20 054 (true direction from which the squall approaches the station).

B/C1.9.6.1.3 Drifting and blowing snow

Drifting and blowing snow shall be reported using two parameters: Obscuration (Flag table 0 20 025) and Character of obscuration (Code table 0 20 026). Occurrence of the phenomenon (Flag table 0 20 027) shall be specified by setting to 1 either bit No. 1 (At time of observation) or bit No. 3 (In time period for past weather) or both. Evolution of drift of snow shall be reported using Code table 0 20 040.

B/C1.9.6.1.4 Maximum diameter of hailstones

Maximum diameter of hailstones (0 20 066) shall be reported in metres (with precision in thousandths of a metre). Occurrence of the phenomenon (Flag table 0 20 027) shall be specified by setting to 1 either bit No. 1 (At time of observation) or bit No. 3 (In time period for past weather) or both.

B/C1.9.6.1.5 Frozen deposit

Diameter of frozen deposit (0 20 067) shall be reported in metres (with precision in thousandths of a metre). The preceding entry Type of precipitation (Flag table 0 20 021) shall specify type of the frozen deposit, i.e. bit No. 15 set to 1 shall indicate deposit of glaze, bit No. 16 set to 1 shall indicate deposit of rime and bit No. 20 set to 1 shall indicate deposit of wet snow; compound deposit shall be indicated by at least two of the above mentioned bits set to 1. Occurrence of the phenomenon (Flag table 0 20 027) shall be specified by setting to 1 either bit No. 1 (At time of observation) or bit No. 3 (In time period for past weather) or both.

Provisional Copy
2023

Provisional Copy
2023

B/C5 – Regulations for reporting SYNOP MOBIL data in TDCF

TM 307090 – BUFR template for synoptic reports from mobile land stations suitable for SYNOP MOBIL data

		Sequence for representation of synoptic reports from a mobile land station suitable for SYNOP MOBIL data
3 07 090	3 01 092	Mobile surface station identification, date/time, horizontal and vertical coordinates
	3 02 031	Pressure information
	3 02 035	Basic synoptic “instantaneous” data
	3 02 036	Clouds with bases below station level
	3 02 047	Direction of cloud drift
	0 08 002	Vertical significance (surface observations)
	3 02 048	Direction and elevation of cloud
	3 02 037	State of ground, snow depth, ground minimum temperature
	3 02 043	Basic synoptic “period” data
	3 02 044	Evaporation data
	1 01 002	Replicate 1 descriptor 2 times
	3 02 045	Radiation data (from 1 hour and 24-hour period)
	3 02 046	Temperature change

This BUFR template for synoptic reports from mobile land stations further expands as follows:

				Unit, scale
			Mobile surface station identification, date/time, horizontal and vertical coordinates	
3 01 092	0 01 011		Ship or mobile land station identifier D...D	CCITT IA5, 0
	0 01 003		WMO Region number/geographical area A ₁	Code table, 0
	0 02 001		Type of station i _x	Code table, 0
	3 01 011	0 04 001	Year	Year, 0
		0 04 002	Month	Month, 0
		0 04 003	Day YY	Day, 0
	3 01 012	0 04 004	Hour GG	Hour, 0
		0 04 005	Minute gg	Minute, 0
	3 01 021	0 05 001	Latitude (high accuracy) L _a L _a L _a	Degree, 5
		0 06 001	Longitude (high accuracy) L _o L _o L _o	Degree, 5
	0 07 030		Height of station ground above mean sea level	m, 1
	0 07 031		Height of barometer above mean sea level	m, 1
	0 33 024		Station elevation quality mark i _m	Code table, 0
			Pressure information	
3 02 031	3 02 001	0 10 004	Pressure P ₀ P ₀ P ₀ P ₀	Pa, –1
		0 10 051	Pressure reduced to mean sea level PPPP	Pa, –1
		0 10 061	3-hour pressure change ppp	Pa, –1
		0 10 063	Characteristic of pressure tendency a	Code table, 0
		0 10 062	24-hour pressure change p ₂₄ P ₂₄ P ₂₄	Pa, –1
	0 07 004		Pressure (standard level) a ₃	Pa, –1
	0 10 009		Geopotential height (of the standard level) hhh	gpm, 0
			Basic synoptic “instantaneous” data	
3 02 035			<i>Temperature and humidity data</i>	
	3 02 032	0 07 032	Height of sensor above local ground (or deck of marine platform) (for temperature and humidity measurement)	m, 2
		0 12 101	Temperature/air temperature s _n TTT	K, 2

				Unit, scale
		0 12 103	Dewpoint temperature $s_n T_d T_d T_d$	K, 2
		0 13 003	Relative humidity	%, 0
			<i>Visibility data</i>	
	3 02 033	0 07 032	Height of sensor above local ground (or deck of marine platform) (for visibility measurement)	m, 2
		0 20 001	Horizontal visibility VV	m, -1
			<i>Precipitation past 24 hours</i>	
	3 02 034	0 07 032	Height of sensor above local ground (or deck of marine platform) (for precipitation measurement)	m, 2
		0 13 023	Total precipitation past 24 hours $R_{24} R_{24} R_{24} R_{24}$	kg m ⁻² , 1
	0 07 032		Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
			<i>General cloud information</i>	
	3 02 004	0 20 010	Cloud cover (total) N	%, 0
		0 08 002	Vertical significance (surface observations)	Code table, 0
		0 20 011	Cloud amount (of low or middle clouds) N_h	Code table, 0
		0 20 013	Height of base of cloud h	m, -1
		0 20 012	Cloud type (low clouds C_L) C_L	Code table, 0
		0 20 012	Cloud type (middle clouds C_M) C_M	Code table, 0
		0 20 012	Cloud type (high clouds C_H) C_H	Code table, 0
			<i>Individual cloud layers or masses</i>	
	1 01 000		Delayed replication of 1 descriptor	
	0 31 001		Delayed descriptor replication factor	Numeric, 0
	3 02 005	0 08 002	Vertical significance (surface observations)	Code table, 0
		0 20 011	Cloud amount N_s	Code table, 0
		0 20 012	Cloud type C	Code table, 0
		0 20 013	Height of base of cloud $h_s h_s$	m, -1
			Clouds with bases below station level	
3 02 036	1 05 000		Delayed replication of 5 descriptors	
	0 31 001		Delayed descriptor replication factor	Numeric, 0
	0 08 002		Vertical significance (surface observations)	Code table, 0
	0 20 011		Cloud amount N'	Code table, 0
	0 20 012		Cloud type C'	Code table, 0
	0 20 014		Height of top of cloud $H'H'$	m, -1
	0 20 017		Cloud top description C_t	Code table, 0
			Direction of cloud drift group 56 $D_L D_M D_H$	
3 02 047	1 02 003		Replicate 2 descriptors 3 times	
	0 08 002		Vertical significance (surface observations) = 7 (low cloud) = 8 (middle cloud) = 9 (high cloud)	Code table, 0
	0 20 054		True direction from which a phenomenon or clouds are moving or in which they are observed D_L, D_M, D_H	Degree true, 0
0 08 002			Vertical significance (surface observations) (set to missing to cancel the previous value)	Code table, 0
			Direction and elevation of cloud gr. 57 $C_D a_e C$	
3 02 048	0 05 021		Bearing or azimuth D_a	Degree true, 2
	0 07 021		Elevation e_C	Degree, 2
	0 20 012		Cloud type C	Code table, 0

				Unit, scale
	0 05 021		Bearing or azimuth (set to missing to cancel the previous value)	Degree true, 2
	0 07 021		Elevation (set to missing to cancel the previous value)	Degree, 2
			State of ground, snow depth, ground minimum temperature	
3 02 037	0 20 062		State of the ground (with or without snow) E or E'	Code table, 0
	0 13 013		Total snow depth sss	m, 2
	0 12 113		Ground minimum temperature, past 12 hours $s_n T_g T_g$	K, 2
			Basic synoptic “period” data	
			<i>Present and past weather</i>	
3 02 043	3 02 038	0 20 003	Present weather ww	Code table, 0
		0 04 024	Time period or displacement (in hours)	Hour, 0
		0 20 004	Past weather (1) W_1	Code table, 0
		0 20 005	Past weather (2) W_2	Code table, 0
			<i>Sunshine data (from 1 hour and 24-hour period)</i>	
	1 01 002		Replicate 1 descriptors 2 times	
	3 02 039	0 04 024	Time period or displacement (in hours)	Hour, 0
		0 14 031	Total sunshine SS and SSS	Minute, 0
			<i>Precipitation measurement</i>	
	3 02 040	0 07 032	Height of sensor above local ground (or deck of marine platform) (for precipitation measurement)	m, 2
		1 02 002	Replicate 2 descriptors 2 times	
		0 04 024	Time period or displacement (in hours) t_R	Hour, 0
		0 13 011	Total precipitation/total water equivalent (of snow) RRR	kg m ⁻² , 1
			<i>Extreme temperature data</i>	
	3 02 041	0 07 032	Height of sensor above local ground (or deck of marine platform) (for temperature measurement)	m, 2
		0 04 024	Time period or displacement	Hour, 0
		0 04 024	Time period or displacement (see Notes 1 and 2)	Hour, 0
		0 12 111	Maximum temperature, at height and over period specified $s_n T_x T_x T_x$	K, 2
		0 04 024	Time period or displacement	Hour, 0
		0 04 024	Time period or displacement (see Note 2)	Hour, 0
		0 12 112	Minimum temperature, at height and over period specified $s_n T_n T_n T_n$	K, 2
			<i>Wind data</i>	
	3 02 042	0 07 032	Height of sensor above local ground (or deck of marine platform) (for wind measurement)	m, 2
		0 02 002	Type of instrumentation for wind measurement i_w	Flag table, 0
		0 08 021	Time significance (= 2 (time averaged))	Code table, 0
		0 04 025	Time period or displacement (= –10 minutes, or number of minutes after a significant change of wind)	Minute, 0
		0 11 001	Wind direction dd	Degree true, 0
		0 11 002	Wind speed ff	m s ⁻¹ , 1
		0 08 021	Time significance (= missing value)	Code table, 0

				Unit, scale
		1 03 002	Replicate 3 descriptors 2 times	
		0 04 025	Time period or displacement (in minutes)	Minute, 0
		0 11 043	Maximum wind gust direction	Degree true, 0
		0 11 041	Maximum wind gust speed $910f_m f_m, 911f_x f_x$	$m s^{-1}$, 1
	0 07 032		Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
			Evaporation data	
3 02 044	0 04 024		Time period or displacement (in hours)	Hour, 0
	0 02 004		Type of instrument for evaporation measurement or type of crop for which evapotranspiration is reported i_E	Code table, 0
	0 13 033		Evaporation/evapotranspiration EEE	$kg m^{-2}$, 1
			Radiation data (from 1 hour and 24-hour period)	
1 01 002			Replicate 1 descriptor 2 times	
3 02 045	0 04 024		Time period or displacement (in hours)	Hour, 0
	0 14 002		Long-wave radiation, integrated over period specified $553SS\ 4FFFF$ or $553SS\ 5FFFF$, $55SSS\ 4F_{24}F_{24}F_{24}F_{24}$ or $55SSS\ 5F_{24}F_{24}F_{24}F_{24}$	$J m^{-2}$, -3
	0 14 004		Short-wave radiation, integrated over period specified $553SS\ 6FFFF$, $55SSS\ 6F_{24}F_{24}F_{24}F_{24}$	$J m^{-2}$, -3
	0 14 016		Net radiation, integrated over period specified $553SS\ 0FFFF$ or $553SS\ 1FFFF$, $55SSS\ 0F_{24}F_{24}F_{24}F_{24}$ or $55SSS\ 1F_{24}F_{24}F_{24}F_{24}$	$J m^{-2}$, -4
	0 14 028		Global solar radiation (high accuracy), integrated over period specified $553SS\ 2FFFF$, $55SSS\ 2F_{24}F_{24}F_{24}F_{24}$	$J m^{-2}$, -2
	0 14 029		Diffuse solar radiation (high accuracy), integrated over period specified $553SS\ 3FFFF$, $55SSS\ 3F_{24}F_{24}F_{24}F_{24}$	$J m^{-2}$, -2
	0 14 030		Direct solar radiation (high accuracy), integrated over period specified $55408\ 4FFFF$, $55508\ 5F_{24}F_{24}F_{24}F_{24}$	$J m^{-2}$, -2
			Temperature change group $54g_0s_n d_T$	
3 02 046	0 04 024		Time period or displacement	Hour, 0
	0 04 024		Time period or displacement (see Note 3)	Hour, 0
	0 12 049		Temperature change over specified period $s_n d_T$	K, 0

Notes:

- (1) Within RA-IV, the maximum temperature at 1200 UTC is reported for the previous calendar day (i.e. the ending time of the period is not equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (2) Within RA-III, the maximum daytime temperature and the minimum night-time temperature is reported (i.e. the ending time of the period may not be equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (3) To construct the required time range, descriptor 0 04 024 has to be included two times.

Regulations:

B/C5.1	Section 1 of BUFR or CREX
B/C5.2	Mobile surface station identification, date/time, horizontal and vertical coordinates
B/C5.3	Pressure information
B/C5.4	Basic synoptic “instantaneous” data
B/C5.4.1	Temperature and humidity data
B/C5.4.2	Visibility data
B/C5.4.3	Precipitation past 24 hours
B/C5.4.4	General cloud information
B/C5.4.5	Individual cloud layers or masses
B/C5.5	Clouds with bases below station level
B/C5.6	Direction of cloud drift
B/C5.7	Direction and elevation of cloud
B/C5.8	State of ground, snow depth, ground minimum temperature
B/C5.9	“Instantaneous” data required by regional or national reporting practices
B/C5.10	Basic synoptic “period” data
B/C5.10.1	Present and past weather
B/C5.10.2	Sunshine data (from 1 hour and 24-hour period)
B/C5.10.3	Precipitation measurement
B/C5.10.4	Extreme temperature data
B/C5.10.5	Wind data
B/C5.11	Evaporation data
B/C5.12	Radiation data (from 1 hour and 24-hour period)
B/C5.13	Temperature change
B/C5.14	“Period” data required by regional or national reporting practices

B/C5.1 Section 1 of BUFR or CREX

B/C5.1.1 Entries required in Section 1 of BUFR

The following entries shall be included in BUFR Section 1:

- BUFR master table;
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Identification of inclusion of optional section;
- Data category (000 for SYNOP MOBIL data);
- International data sub-category (see Note 1);
- Local data sub-category;
- Version number of master table;
- Version number of local tables;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for SYNOP MOBIL data);
- Hour (GG in the abbreviated telecommunication header for SYNOP MOBIL data);
- Minute (00 for SYNOP MOBIL data);
- Second (00).

Notes:

- (1) If required, the international data sub-category shall be included for SYNOP MOBIL data as:
 - = 005 at main synoptic times 00, 06, 12, 18 UTC;
 - = 004 at intermediate synoptic times 03, 09, 15, 21 UTC;

= 003 at observation times 01, 02, 04, 05, 07, 08, 10, 11, 13, 14, 16, 17, 19, 20, 22 and 23 UTC.

- (2) If an NMHS performs conversion of SYNOP MOBIL data produced by another NMHS, originating centre in Section 1 shall indicate the converting centre and originating sub-centre shall indicate the producer of SYNOP MOBIL bulletins. The producer of SYNOP MOBIL bulletins shall be specified in Common Code table C-12 as a sub-centre of the originating centre, i.e. of the NMHS executing the conversion.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C5.1.2

Entries required in Section 1 of CREX

The following entries shall be included in CREX Section 1:

- CREX master table;
- CREX edition number;
- CREX table version number;
- Version number of BUFR master table;
- Version number of local tables;
- Data category (000 for SYNOP MOBIL data);
- International data sub-category (see Note 1);
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Number of subsets;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for SYNOP MOBIL data);
- Hour (GG in the abbreviated telecommunication header for SYNOP MOBIL data);
- Minute (00 for SYNOP MOBIL data).

Notes:

- (1) If inclusion of the international data sub-category is required, Note 1 under Regulation B/C5.1.1 applies.
- (2) If an NMHS performs conversion of SYNOP MOBIL data produced by another NMHS, Note 2 under Regulation B/C5.1.1 applies.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C5.2

Mobile surface station identification, date/time, horizontal and vertical coordinates <3 01 092>

B/C5.2.1

Mobile surface station identification

Mobile land station identifier (0 01 011) shall be always reported as a non-missing value. In the absence of a suitable call sign, the word MOBIL shall be used for mobile land station identifier. [12.1.7(c)]

WMO regional number (0 01 003) shall be reported to indicate the geographical area in which the mobile station has been deployed.

Type of station (Code table 0 02 001) shall be reported to indicate the type of the station operation (manned, automatic or hybrid).

Note: If a station operates as a manned station for a part of the day and as an automatic station for the rest of the day, code figure 2 (Hybrid) may be used in all reports. It is preferable, however, to use code figure 1 (Manned) in reports produced under the

supervision of an observer, and a code figure 0 (Automatic) in reports produced while the station operates in the automatic mode.

B/C5.2.2 Time of observation

Year (0 04 001), month (0 04 002), day (0 04 003), hour (0 04 004) and minute (0 04 005) of the actual time of observation shall be reported.

Note: The actual time of observation shall be the time at which the barometer is read. [12.1.6]

B/C5.2.2.1 The time in Section 1 (B/C1.1.1) may be reported instead of the actual time of observation if the actual time of observation differs by 10 minutes or less from the nearest hour. [12.2.8]

B/C5.2.3 Horizontal and vertical coordinates

Latitude (0 05 001) and longitude (0 06 001) of the station shall be reported in degrees with precision in 10^{-5} of a degree.

Height of station ground above mean sea level (0 07 030) and height of barometer above mean sea level (0 07 031) shall be reported in metres with precision in tenths of a metre.

B/C5.2.4 Station elevation quality mark – Code table 0 33 024

Station elevation quality mark shall be reported to indicate the accuracy of the vertical coordinates of the mobile station.

B/C5.3 Pressure information <3 02 031>

B/C5.3.1 Pressure at the station level

Pressure at the station level (0 10 004), i.e. at the level defined by 0 07 031 (height of barometer above mean sea level), shall be reported in pascals (with precision in tens of pascals).

B/C5.3.1.1 The station pressure shall be included in reports for global exchange from land stations, together with either the mean sea level pressure or, in accordance with Regulation B/C5.3.5.1, with the geopotential height of a standard pressure level.

Note: Inclusion of the station pressure at other times is left to the decision of individual Members.

[12.2.4]

B/C5.3.2 Pressure reduced to mean sea level

Pressure reduced to mean sea level (0 10 051) shall be reported in pascals (with precision in tens of pascals).

B/C5.3.2.1 Whenever air pressure at mean sea level can be computed with reasonable accuracy, this pressure shall be reported.

Notes:

- (1) For a station situated in a region of normal synoptic network density, the pressure at mean sea level is considered not to be computed with reasonable accuracy when it introduces a deformation into the analysis of the horizontal pressure field, which is purely local and recurring.
- (2) For a station lying in a data-sparse area of the synoptic network, reasonable accuracy will be obtained when using a reduction method, which has proved to be

satisfactory in a region of normal network density and under similar geographic conditions.

[12.2.3.4.1]

B/C5.3.3 Three-hour pressure change and characteristic of pressure tendency

Amount of pressure change at station level, during the three hours preceding the time of observation (0 10 061), either positive, zero or negative, shall be reported in pascals (with precision in tens of pascals).

B/C5.3.3.1 Unless specified otherwise by regional decision, pressure tendency shall be included whenever the three-hourly pressure tendency is available. [12.2.3.5.1]

B/C5.3.3.2 The characteristic of pressure tendency (Code table 0 10 063) over the past three hours shall, whenever possible, be determined on the basis of pressure samples at equi-spaced intervals not exceeding one hour.

Note: Algorithms for selecting the appropriate code figure are included in the *Guide to Meteorological Instruments and Methods of Observation* (WMO-No. 8).

[12.2.3.5.2]

B/C5.3.3.3 Where it is not possible to apply the algorithms specified in Regulation B/C5.3.3.2 in reports from automatic weather stations, the characteristic of pressure tendency shall be reported as 2 when the tendency is positive, as 7 when the tendency is negative, and as 4 when the atmospheric pressure is the same as three hours before. [12.2.3.5.3]

B/C5.3.4 24-hour pressure change

If specified by regional decision, amount of surface pressure change at station level, during 24 hours preceding the time of observation (0 10 062), either positive, zero or negative, shall be reported in pascals (with precision in tens of pascals). [12.4.7.1.2(k), (l)]

B/C5.3.5 Geopotential height of the standard level

Geopotential height of the standard level (0 10 009) shall be reported in geopotential metres. The standard isobaric level is specified by the preceding entry Pressure (0 07 004).

B/C5.3.5.1 By regional decision, a high-level station which cannot give pressure at mean sea level to a satisfactory degree of accuracy shall report both the station-level pressure and the geopotential height of an agreed standard isobaric surface. [12.2.3.4.2]

B/C5.4 Basic synoptic “instantaneous” data <3 02 035>

B/C5.4.1 Temperature and humidity data <3 02 032>

B/C5.4.1.1 Height of sensor above local ground

Height of sensor above local ground (0 07 032) for temperature and humidity measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of temperature and humidity sensors above ground at the point where the sensors are located.

B/C5.4.1.2 Dry-bulb air temperature

Dry-bulb air temperature (0 12 101) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree. This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

B/C5.4.1.2.1 When the data are not available as a result of a temporary instrument failure, this quality shall be included as a missing value. [12.2.3.2]

B/C5.4.1.3 Dewpoint temperature

Dewpoint temperature (0 12 103) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C5.4.1.2 shall apply.

B/C5.4.1.3.1 When the data are not available as a result of a temporary instrument failure, this quality shall be included as a missing value. [12.2.3.3.2]

B/C5.4.1.4 Relative humidity

Relative humidity (0 13 003) shall be reported in units of a per cent.

B/C5.4.1.4.1 *Both dewpoint temperature and relative humidity shall be reported when available.*

B/C5.4.2 Visibility data <3 02 033>**B/C5.4.2.1 Height of sensor above local ground**

Height of sensor above local ground (0 07 032) for visibility measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of visibility sensors above ground at the point where the sensors are located. If visibility is estimated by a human observer, average height of observer's eyes above station ground shall be reported.

B/C5.4.2.2 Horizontal visibility

Horizontal visibility (0 20 001) at surface shall be reported in metres (with precision in tens of metres).

B/C5.4.2.2.1 When the horizontal visibility is not the same in different directions, the shortest distance shall be given for visibility. [12.2.1.3.1]

B/C5.4.2.2.2 Horizontal visibility greater than 81 900 m shall be expressed by 0 20 001 set to 81 900 m; if TDCF data are converted from TAC data, 0 20 001 set to 81 900 m shall indicate horizontal visibility greater than 70 000 m.

B/C5.4.3 Precipitation past 24 hours <3 02 034>**B/C5.4.3.1 Height of sensor above local ground**

Height of sensor above local ground (0 07 032) for precipitation measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the rain gauge rim above ground at the point where the rain gauge is located.

B/C5.4.3.2 Total amount of precipitation during the 24-hour period

Total amount of precipitation during the 24-hour period ending at the time of observation (0 13 023) shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre). [12.4.9]

B/C5.4.3.2.1 The precipitation over the past 24 hours shall be included (not missing) at least once a day at one appropriate time of the main standard times (0000, 0600, 1200, 1800 UTC). [12.4.1]

B/C5.4.3.2.2 Precipitation, when it can be and has to be reported, shall be reported as 0.0 kg m⁻² if no precipitation were observed during the referenced period. [12.2.5.4]

B/C5.4.3.2.3 Trace shall be reported as “–0.1 kg m⁻²”.

B/C5.4.4 General cloud information <3 02 004>**B/C5.4.4.1 Total cloud cover**

Total cloud cover (0 20 010) shall embrace the total fraction of the celestial dome covered by clouds irrespective of their genus. It shall be reported in *units of a per cent*.

Note: Total cloud cover shall be reported as 113 when sky is obscured by fog and/or other meteorological phenomena.

B/C5.4.4.1.1 Total cloud cover shall be reported as actually seen by the observer during the observation. [12.2.2.2.1]

B/C5.4.4.1.2 Altocumulus perlucidus or Stratocumulus perlucidus (“mackerel sky”) shall be reported as 99% or less (unless overlying clouds appear to cover the whole sky) since breaks are always present in this cloud form even if it extends over the whole celestial dome. [12.2.2.2.2]

B/C5.4.4.1.3 Total cloud cover shall be reported as zero when blue sky or stars are seen through existing fog or other analogous phenomena without any trace of cloud being seen. [12.2.2.2.3]

B/C5.4.4.1.4 When clouds are observed through fog or analogous phenomena, their amount shall be evaluated and reported as if these phenomena were non-existent. [12.2.2.2.4]

B/C5.4.4.1.5 Total cloud cover shall not include the amount resulting from rapidly dissipating condensation trails. [12.2.2.2.5]

B/C5.4.4.1.6 Persistent condensation trails and cloud masses which have obviously developed from condensation trails shall be reported as cloud. [12.2.2.2.6]

B/C5.4.4.2 Vertical significance (surface observations) – Code table 0 08 002

To specify vertical significance (0 08 002) within the sequence 3 02 004, a code figure shall be selected in the following way:

- (a) If low clouds are observed, then code figure 7 (Low cloud) shall be used;
- (b) If there are no low clouds but middle clouds are observed, then code figure 8 (Middle clouds) shall be used;
- (c) If there are no low and there are no middle clouds but high clouds are observed, then code figure 0 shall be used;
- (d) If sky is obscured by fog and/or other phenomena, then code figure 5 (Ceiling) shall be used;
- (e) If there are no clouds (clear sky), then code figure 62 (Value not applicable) shall be used;
- (f) If the cloud cover is not discernible for reasons other than (d) above or observation is not made, then code figure 63 (Missing value) shall be used.

B/C5.4.4.3 Cloud amount (of low or middle clouds) – Code table 0 20 011

Amount of all the low clouds (clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus) present or, if no low clouds are present, the amount of all the middle clouds (clouds of the genera Altocumulus, Altostratus, and Nimbostratus) present.

B/C5.4.4.3.1 Cloud amount shall be reported as follows:

- (a) If there are low clouds, then the total amount of all low clouds, as actually seen by the observer during the observation shall be reported for the cloud amount;
- (b) If there are no low clouds but there are middle clouds, then the total amount of the middle clouds shall be reported for the cloud amount;
- (c) If there are no low clouds and there are no middle clouds but there are high clouds (clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus), then the cloud amount shall be reported as zero;

[12.2.7.2.1]

- (d) If no clouds are observed (clear sky), then the cloud amount shall be reported as 0;
- (e) If sky is obscured by fog and/or other meteorological phenomena, then the cloud amount shall be reported as 9;
- (f) If cloud cover is indiscernible for reasons other than fog or other meteorological phenomena, or observation is not made, the cloud amount shall be reported as missing.

B/C5.4.4.3.2 Amount of Altocumulus perlucidus or Stratocumulus perlucidus (“mackerel sky”) shall be reported using code figure 7 or less since breaks are always present in this cloud form even if it extends over the whole celestial dome. [12.2.7.2.2]**B/C5.4.4.3.3 When the clouds reported for cloud amount are observed through fog or an analogous phenomenon, the cloud amount shall be reported as if these phenomena were not present. [12.2.7.2.3]****B/C5.4.4.3.4 If the clouds reported for cloud amount include contrails, then the cloud amount shall include the amount of persistent contrails. Rapidly dissipating contrails shall not be included in the value for the cloud amount. [12.2.7.2.4]**

B/C5.4.4.4 Height of base of lowest cloud

Height above surface of the base (0 20 013) of the lowest cloud seen shall be reported in metres (with precision in tens of metres).

Note: The term « height above surface » shall be considered as being the height above the official aerodrome elevation or above station elevation at a non-aerodrome station.

B/C5.4.4.4.1 When the station is in fog, a sandstorm or in blowing snow but the sky is discernable, the base of the lowest cloud shall refer to the base of the lowest cloud observed, if any. When, under the above conditions, the sky is not discernible, the base of the lowest cloud shall be replaced by vertical visibility. [12.4.10.5]

B/C5.4.4.4.2 When no cloud is reported (total cloud cover = 0) the base of the lowest cloud *shall be reported as a missing value.*

B/C5.4.4.4.3 When, by national decision, clouds with bases below the station are reported from the station and clouds with bases below and tops above the station are observed, the base of the lowest cloud *shall be reported having a negative value if the base of cloud is discernible, or as a missing value.*

B/C5.4.4.4.4 If synoptic data are produced in BUFR or CREX by conversion from a TAC report, the following approach shall be used: Height of base of the lowest cloud 0 20 013 shall be derived from the $h_s h_s$ in the first group 8 in section 3, i.e. from the $h_s h_s$ of the lowest cloud. If and only if groups 8 are not reported in section 3, 0 20 013 may be derived from h . The lower limit of the range defined for $h_s h_s$ and for h shall be used. However, if groups 8 are not reported in section 3 and $h = 9$ and $N_h \neq 0$, then 0 20 013 shall be 4 000 m; if groups 8 are not reported in section 3 and $h = 9$ and $N_h = 0$, then 0 20 013 shall be 8 000 m.

B/C5.4.4.5 Cloud type of low, middle and high clouds – Code table 0 20 012

Clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus (low clouds) shall be reported for the first entry 0 20 012, clouds of the genera Altostratus, Altostratus, and Nimbostratus (middle clouds) shall be reported for the second entry 0 20 012 and clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus (high clouds) shall be reported for the third entry 0 20 012.

B/C5.4.4.5.1 The reporting of type of low, middle and high clouds shall be as specified in the *International Cloud Atlas* (WMO-No. 407), Volume I. [12.2.7.3]

B/C5.4.5 Individual cloud layers or masses**B/C5.4.5.1 Number of individual cloud layers or masses**

The number of individual cloud layers or masses shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of cloud layers or masses shall never be set to a missing value.
- (2) The number of cloud layers or masses shall be set to a positive value in a NIL report.
- (3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

- B/C5.4.5.1.1** When reported from a manned station, the number of individual cloud layers or masses shall in the absence of Cumulonimbus clouds not exceed three. Cumulonimbus clouds, when observed, shall always be reported, so that the total number of individual cloud layers or masses can be four. The selection of layers (or masses) to be reported shall be made in accordance with the following criteria:
- (a) The lowest individual layer (or mass) of any amount (cloud amount at least one octa or less, but not zero);
 - (b) The next higher individual layer (or mass) the amount of which is greater than two octas;
 - (c) The next higher individual layer (or mass) the amount of which is greater than four octas;
 - (d) Cumulonimbus clouds, whenever observed and not reported under (a), (b) and (c) above.
- [12.4.10.1]
- B/C5.4.5.1.2** When the sky is clear, the number of individual cloud layers or masses shall be set to zero.
- B/C5.4.5.1.3** The order of reporting the individual cloud layers or masses shall always be from lower to higher levels. [12.4.10.2]
- B/C5.4.5.2** **Individual cloud layer or mass <3 02 005>**
- Each cloud layer or mass shall be represented by the following four parameters: Vertical significance (0 08 002), amount of individual cloud layer or mass (0 20 011), type of cloud layer or mass (0 20 012) and height of base of individual cloud layer or mass (0 20 013).
- B/C5.4.5.2.1** **Vertical significance (surface observations) – Code table 0 08 002**
- To specify vertical significance (0 08 002) within the sequence 3 02 005, a code figure shall be selected in the following way:
- (a) Code figure 1 shall be used in the first non-Cumulonimbus layer;
 - (b) Code figure 2 shall be used in the second non-Cumulonimbus layer;
 - (c) Code figure 3 shall be used in the third non-Cumulonimbus layer;
 - (d) Code figure 4 shall be used in any Cumulonimbus layer;
 - (e) If sky is obscured by fog and/or other phenomena, then code figure 5 (Ceiling) shall be used;
 - (f) If the cloud cover is not discernible for reasons other than (e) above or observation is not made, then code figure 63 (Missing value) shall be used;
 - (g) If a station operates in the automatic mode and is sufficiently equipped, code figure 21, 22, 23 and 24 shall be used to identify the first, the second, the third and the fourth instrument detected cloud layer, respectively;
 - (h) If a station operates in the automatic mode and no clouds are detected by the cloud detection system, code figure 20 shall be used.
- B/C5.4.5.2.2** **Cloud amount, type and height of base**
- B/C5.4.5.2.2.1** When the sky is clear, in accordance with Regulation B/C5.4.5.1.2 cloud amount, genus, and height shall not be included. [12.4.10.4]
- B/C5.4.5.2.2.2** In determining cloud amounts (Code table 0 20 011) to be reported for individual layers or masses, the observer shall estimate, by taking into consideration the evolution of the sky, the cloud amounts of each individual layer or mass at the different levels, as if no other clouds existed. [12.4.10.3]

B/C5.4.5.2.2.3 Type of a cloud layer or mass (Code table 0 20 012) shall be reported using code figures 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 59 and 63.

B/C5.4.5.2.2.4 If, notwithstanding the existence of fog, sandstorm, duststorm, blowing snow or other obscuring phenomena, the sky is discernible, the partially obscuring phenomena shall be disregarded. If, under the above conditions, the sky is not discernible, the cloud type shall be reported using *code figure 59* and the cloud height shall be replaced by vertical visibility.

Note: The vertical visibility is defined as the vertical visual range into an obscuring medium.

[12.4.10.5]

B/C5.4.5.2.2.5 If two or more types of cloud occur with their bases at the same level and this level is one to be reported in accordance with Regulation B/C5.4.5.1.1, the selection for cloud type and amount shall be made with the following criteria:

- (a) If these types do not include Cumulonimbus then cloud genus shall refer to the cloud type that represents the greatest amount, or if there are two or more types of cloud all having the same amount, the highest applicable code figure for cloud genus shall be reported. Cloud amount shall refer to the total amount of cloud whose bases are all at the same level;
- (b) If these types do include Cumulonimbus then one layer shall be reported to describe only this type with cloud genus indicated as Cumulonimbus and the cloud amount as the amount of the Cumulonimbus. If the total amount of the remaining type(s) of cloud (excluding Cumulonimbus) whose bases are all at the same level is greater than that required by Regulation B/C5.4.5.1.1, then another layer shall be reported with type being selected in accordance with (a) and amount referring to the total amount of the remaining cloud (excluding Cumulonimbus).

[12.4.10.6]

B/C5.4.5.2.2.6 Regulations B/C5.4.4.1.3 to B/C5.4.4.1.6, inclusive, shall apply. [12.4.10.7]

B/C5.4.5.2.2.7 Height above surface of the cloud base (0 20 013) shall be reported in metres (with precision in tens of metres).

Note: The term « height above surface » shall be considered as being the height above the official aerodrome elevation or above station elevation at a non-aerodrome station.

B/C5.5 Clouds with bases below station level <3 02 036>

B/C5.5.1 Number of cloud layers with bases below station level

The number of cloud layers with bases below station level shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of cloud layers with bases below station level shall never be set to a missing value.
- (2) The number of cloud layers with bases below station level shall be set to a positive value in a NIL report.
- (3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

- B/C5.5.1.1** Inclusion of these data shall be determined by national decision. The number of cloud layers with bases below station level shall be always set to zero in reports from a station at which observations of clouds with bases below station level are not executed.
- B/C5.5.1.2** When no cloud layers with bases below station are observed, the number of cloud layers with bases below station level shall be set to zero.
- B/C5.5.1.3** If the station is in continuous or almost continuous cloud, the number of cloud layers with bases below station level shall be set to one, with all parameters reported as missing except for vertical significance 0 08 002 that shall be set to 10 (cloud layer with a base below and tops above station level). [12.5.4]
- B/C5.5.1.4** If clouds with bases below station level are not discernible due to fog and/or other phenomena or observation is not made, then the number of cloud layers with bases below station level shall be set to one, with all parameters reported as missing except for vertical significance 0 08 002 that shall be set to 11.
- B/C5.5.1.5** When two or more cloud layers with their bases below station level occur at different levels, two or more cloud layers shall be reported. [12.5.5]
- B/C5.5.1.6** Clouds with bases below and tops above station level shall be reported as the first layer within the sequence 3 02 036, provided that the station is out of cloud sufficiently frequently to enable the various features to be recognized. Other low clouds present with tops below station level shall be reported as the following layers (one or more) within the sequence 3 02 036. [12.5.3]
- Notes:
- (1) Clouds with bases below and tops above station level shall be reported also in sequences 3 02 004 and 3 02 005. [12.5.3]
 - (2) Clouds with tops below station level shall be reported only in sequence 3 02 036, and any co-existent clouds with bases above station level shall be reported only in sequences 3 02 004 and 3 02 005. [12.5.2]
- B/C5.5.2** **Individual cloud layer with base below station level**
- Each cloud layer with base below station level shall be represented by the following five parameters: Vertical significance (0 08 002), amount of clouds with base below station level (0 20 011), type of clouds with base below station level (0 20 012), altitude of the upper surface of clouds (0 20 014) and cloud top description (0 20 017).
- B/C5.5.2.1** **Vertical significance (surface observations) – Code table 0 08 002**
- Code figure 10 shall be used for cloud layers with bases below and tops above station level; code figure 11 shall be used for cloud layers with bases and tops below station level.
- B/C5.5.2.2** **Amount of clouds with base below station level – Code table 0 20 011**
- B/C5.5.2.2.1** Regulations B/C5.4.4.1.1 to B/C5.4.4.1.6, inclusive, shall apply. [12.5.8]
- B/C5.5.2.2.2** Spaces occupied by mountains emerging from the cloud layers shall be counted as occupied by clouds. [12.5.9]

- B/C5.5.2.3 Type of clouds with base below station level – Code table 0 20 012**
Type of clouds with bases below station level shall be reported using code figures 0, 1, 2, 3, 4, 5, 6, 7, 8, 9 and 63.
- B/C5.5.2.4 Height of top of clouds above mean sea level**
Height of top of clouds above mean sea level (0 20 014) shall be reported in metres (with precision in tens of metres).
- B/C5.5.2.4.1** Height of top of clouds with bases below and tops above station level shall be reported, provided that the upper surface of clouds can be observed. [12.5.3 (b)]
- B/C5.5.2.5 Cloud top description – Code table 0 20 017**
- B/C5.5.2.5.1** Description of top of clouds with bases below and tops above station level shall be reported, provided that the station is out of cloud sufficiently frequently to enable the features to be recognized.
- B/C5.5.2.5.2** Rapidly dissipating condensation trails shall not be reported. However, the top of persistent condensation trails and cloud masses which have obviously developed from condensation trails (and whose bases are below station level) shall be reported in Sequence 3 02 036. [12.5.6], [12.5.7]
- B/C5.6 Direction of cloud drift <3 02 047>**
This information is required from land stations mainly in the tropics. [12.4.7.5]
- B/C5.6.1 Vertical significance (surface observations) – Code table 0 08 002**
To specify vertical significance (0 08 002) within the sequence 3 02 047, code figures shall be selected in the following way:
(a) Code figure 7 (Low cloud) shall be used in the first replication;
(b) Code figure 8 (Middle clouds) shall be used in the second replication;
(c) Code figure 9 (High cloud) shall be used in the third replication.
- B/C5.6.2 True direction from which clouds are moving**
True direction from which low, middle, or high clouds are moving (0 20 054) shall be reported in degrees true as follows:
(a) True direction from which the low clouds are moving shall be included in the first replication;
(b) True direction from which the middle clouds are moving shall be included in the second replication;
(c) True direction from which the high clouds are moving shall be included in the third replication.
- B/C5.7 Direction and elevation of cloud <3 02 048>**
This information is required from land stations mainly in the tropics. [12.4.7.5]
- B/C5.7.1 Direction of cloud**
True direction (0 05 021), from which orographic clouds or clouds with vertical development are seen, shall be *reported in degrees true*. The cloud genus shall be specified by the third entry of the sequence 3 02 048, i.e. by Cloud type – Code table 0 20 012.

Note: It is considered sufficient to report direction of cloud in degrees true, although 0 05 021 (Bearing or azimuth) is defined with higher accuracy (hundredths of a degree true).

B/C5.7.2 Elevation of cloud

Elevation angle (0 07 021) of the top of the cloud shall be reported in degrees. The cloud genus shall be specified by the following entry, i.e. by Cloud type – Code table 0 20 012.

Note: It is considered sufficient to report elevation of the top of cloud in degrees, although 0 07 021 (Elevation angle) is defined with higher accuracy (hundredths of a degree).

B/C5.8 State of ground, snow depth, ground minimum temperature <3 02 037>**B/C5.8.1 State of ground** (with or without snow) – Code table 0 20 062

State of ground without snow or with snow shall be reported using Code table 0 20 062. The synoptic hour at which this datum is reported shall be determined by regional decision.

B/C5.8.2 Total snow depth

Total snow depth (0 13 013) shall be reported in metres (with precision in hundredths of a metre). The synoptic hour at which this datum is reported shall be determined by regional decision.

B/C5.8.2.1 When total snow depth has to be reported, it is reported as 0.00 m if no snow, ice and other forms of solid precipitation on the ground are observed at the time of observation. A snow depth value of “–0.01 m” shall indicate a little (less than 0.005 m) snow. A snow depth value of “–0.02 m” shall indicate “snow cover not continuous”.

B/C5.8.2.2 The measurement shall include snow, ice and all other forms of solid precipitation on the ground at the time of observation. [12.4.6.1]

B/C5.8.2.3 When the depth is not uniform, the average depth over a representative area shall be reported. [12.4.6.2]

B/C5.8.3 Ground minimum temperature, past 12 hours

Ground minimum temperature from the previous 12 hours (0 12 113) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Ground minimum temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree. Notes 1 and 2 under Regulation B/C5.4.1.2 shall apply.
- (2) The period of time covered by ground minimum temperature and the synoptic hour at which this temperature is reported shall be determined by regional decision. If ground minimum temperature is to be reported from the period of previous night, then “ground minimum temperature, past 12 hours” (0 12 113) shall be reported as a missing value. In this case, ground minimum temperature of the previous night (0 12 122) shall be reported in compliance with Regulation B/C5.9.

B/C5.9 “Instantaneous” data required by regional or national reporting practices

If regional or national reporting practices require inclusion of additional “instantaneous” parameters, the sequence descriptor 3 07 090 shall be supplemented by the required element descriptors being preceded by a relevant time period descriptor set to zero, i.e. 0 04 024 = 0 or 0 04 025 = 0.

Notes:

- (1) “Instantaneous” parameter is a parameter that is not coupled to a time period descriptor, e.g. 0 04 024, 0 04 025.
- (2) No regional requirements are currently indicated for reporting SYNOP MOBIL data in the *Manual on Codes* (WMO-No. 306), Volume II.

B/C5.10 Basic synoptic “period” data <3 02 043>**B/C5.10.1 Present and past weather <3 02 038>**

B/C5.10.1.1 Present weather (Code table 0 20 003) and past weather (1) (Code table 0 20 004) and past weather (2) (Code table 0 20 005) shall be reported as non-missing values if present and past conditions are known. In case of a report from a manually operated station after a period of closure or at start up, when past weather conditions for the period applicable to the report are unknown, past weather (1) and past weather (2) reported as missing shall indicate that previous conditions are unknown. This regulation shall also apply to automatic reporting stations with the facility to report present and past weather. [12.2.6.1]

B/C5.10.1.2 Code figures 0, 1, 2, 3, 100, 101, 102 and 103 for present weather and code figures 0, 1, 2 and 10 for past weather (1) and past weather (2) shall be considered to represent phenomena without significance. [12.2.6.2]

B/C5.10.1.3 Present and past weather shall be *reported if observation was made (data available), regardless significance of the phenomena.*

Note: If data are produced and collected in traditional codes and present weather and past weather is omitted in a SYNOP report (no significant phenomena observed), code figure 508 shall be used for present weather and code figure 10 for past weather (1) and past weather (2) when converted into BUFR or CREX.

B/C5.10.1.4 If no observation was made (data not available), code figure 509 shall be used for present weather and both past weather (1) and past weather (2) shall be reported as missing.

B/C5.10.1.5 Present weather from a manned weather station

B/C5.10.1.5.1 If more than one form of weather is observed, the highest applicable code figure from the range <00 to 99> shall be selected for present weather. Code figure 17 shall have precedence over code figures 20–49. Other weather may be reported using additional entries 0 20 003 or 0 20 021 to 0 20 026 applying Regulation B/C5.9. [12.2.6.4.1]

B/C5.10.1.5.2 In coding 01, 02, or 03, there is no limitation on the magnitude of the change of the cloud amount. Code figures 00, 01, and 02 can each be used when the sky is clear at the time of observation. In this case, the following interpretation of the specifications shall apply:

- 00 is used when the preceding conditions are not known;
- 01 is used when the clouds have dissolved during the past hour;
- 02 is used when the sky has been continuously clear during the past hour.

[12.2.6.4.2]

B/C5.10.1.5.3 When the phenomenon is not predominantly water droplets, the appropriate code figure shall be selected without regard to visibility. [12.2.6.4.3]

B/C5.10.1.5.4 The code figure 05 shall be used when the obstruction to vision consists predominantly of lithometeors. [12.2.6.4.4]

- B/C5.10.1.5.5** National instructions shall be used to indicate the specifications for code figures 07 and 09. [12.2.6.4.5]
- B/C5.10.1.5.6** The visibility restrictions on code figure 10 shall be 1 000 metres or more. The specification refers only to water droplets and ice crystals. [12.2.6.4.6]
- B/C5.10.1.5.7** For code figures 11 or 12 to be reported, the apparent visibility shall be less than 1000 metres. [12.2.6.4.7]
- B/C5.10.1.5.8** For code figure 18, the following criteria for reporting squalls shall be used:
- (a) When wind speed is measured: A sudden increase of wind speed of at least eight metres per second, the speed rising to 11 metres per second or more and lasting for at least one minute;
 - (b) When the Beaufort scale is used for estimating wind speed: A sudden increase of wind speed by at least three stages of the Beaufort scale, the speed rising to force 6 or more and lasting for at least one minute.
- [12.2.6.4.8]
- B/C5.10.1.5.9** Code figures 20–29 shall never be used when precipitation is observed at the time of observation. [12.2.6.4.9]
- B/C5.10.1.5.10** For code figure 28, visibility shall have been less than 1 000 metres.
- Note: The specification refers only to visibility restrictions which occurred as a result of water droplets or ice crystals.
- [12.2.6.4.10]
- B/C5.10.1.5.11** For synoptic coding purposes, a thunderstorm shall be regarded as being at the station from the time thunder is first heard, whether or not lightning is seen or precipitation is occurring at the station. A thunderstorm shall be reported if thunder is heard within the normal observational period preceding the time of the report. A thunderstorm shall be regarded as having ceased at the time thunder is last heard and the cessation is confirmed if thunder is not heard for 10–15 minutes after this time. [12.2.6.4.11]
- B/C5.10.1.5.12** The necessary uniformity in reporting code figures 36, 37, 38, and 39, which may be desirable within certain regions, shall be obtained by means of national instructions. [12.2.6.4.12]
- B/C5.10.1.5.13** A visibility restriction « less than 1 000 metres » shall be applied to code figures 42–49. In the case of code figures 40 or 41, the apparent visibility in the fog or ice fog patch or bank shall be less than 1 000 metres. Code figures 40–47 shall be used when the obstructions to vision consist predominantly of water droplets or ice crystals, and 48 or 49 when the obstructions consist predominantly of water droplets. [12.2.6.4.13]
- B/C5.10.1.5.14** When referring to precipitation, the phrase « at the station » in the code table shall mean « at the point where the observation is normally taken ». [12.2.6.4.14]
- B/C5.10.1.5.15** The precipitation shall be encoded as intermittent if it has been discontinuous during the preceding hour, without presenting the character of a shower. [12.2.6.4.15]
- B/C5.10.1.5.16** The intensity of precipitation shall be determined by the intensity at the time of the observation. [12.2.6.4.16]

B/C5.10.1.5.17 Code figures 80–90 shall be used only when the precipitation is of the shower type and takes place at the time of the observation.

Note: Showers are produced by convective clouds. They are characterized by their abrupt beginning and end and by the generally rapid and sometimes great variations in the intensity of the precipitation. Drops and solid particles falling in a shower are generally larger than those falling in non-showery precipitation. Between showers openings may be observed unless stratiform clouds fill the intervals between the cumuliform clouds.

[12.2.6.4.17]

B/C5.10.1.5.18 In reporting code figure 98, the observer shall be allowed considerable latitude in determining whether precipitation is or is not occurring, if it is not actually visible. [12.2.6.4.18]

B/C5.10.1.6 Present weather from an automatic weather station

B/C5.10.1.6.1 The highest applicable code figure shall be selected. [12.2.6.5.1]

B/C5.10.1.6.2 In coding code figures 101, 102, and 103, there is no limitation on the magnitude of the change of the cloud amount. Code figures 100, 101, and 102 can each be used when the sky is clear at the time of observation. In this case, the following interpretation of the specifications shall apply:

- Code figure 100 is used when the preceding conditions are not known;
- Code figure 101 is used when the clouds have dissolved during the past hour;
- Code figure 102 is used when the sky has been continuously clear during the past hour.

[12.2.6.5.2]

B/C5.10.1.6.3 When the phenomenon is not predominantly water droplets, the appropriate code figure shall be selected without regard to the visibility. [12.2.6.5.3]

B/C5.10.1.6.4 The code figures 104 and 105 shall be used when the obstruction to vision consists predominantly of lithometeors. [12.2.6.5.4]

B/C5.10.1.6.5 The visibility restriction on code figure 110 shall be 1 000 metres or more. The specification refers only to water droplets and ice crystals. [12.2.6.5.5]

B/C5.10.1.6.6 For code figure 118, the following criteria for reporting squalls shall be used:
A sudden increase of wind speed of at least eight metres per second, the speed rising to 11 metres per second or more and lasting for at least one minute.

[12.2.6.5.6]

B/C5.10.1.6.7 Code figures 120–126 shall never be used when precipitation is observed at the time of observation. [12.2.6.5.7]

B/C5.10.1.6.8 For code figure 120, visibility shall have been less than 1 000 metres.

Note: The specification refers only to visibility restrictions, which occurred as a result of water droplets or ice crystals.

[12.2.6.5.8]

B/C5.10.1.6.9 For synoptic coding purposes, a thunderstorm shall be regarded as being at the station from the time thunder is first detected, whether or not lightning is detected or precipitation is occurring at the station. A thunderstorm shall be reported in present weather if thunder is detected within the normal observational period preceding the time of the report. A thunderstorm shall be regarded as having

ceased at the time thunder is last detected and the cessation is confirmed if thunder is not detected for 10–15 minutes after this time. [12.2.6.5.9]

- B/C5.10.1.6.10** A visibility restriction « less than 1 000 metres » shall be applied to code figures 130–135. [12.2.6.5.10]
- B/C5.10.1.6.11** The precipitation shall be encoded as intermittent if it has been discontinuous during the preceding hour, without presenting the character of a shower. [12.2.6.5.11]
- B/C5.10.1.6.12** The intensity of precipitation shall be determined by the intensity at the time of observation. [12.2.6.5.12]
- B/C5.10.1.6.13** Code figures 180–189 shall be used only when the precipitation is intermittent or of the shower type and takes place at the time of observation.

Note: Showers are produced by convective clouds. They are characterized by their abrupt beginning and end and by the generally rapid and sometimes great variations in the intensity of the precipitation. Drops and solid particles falling in a shower are generally larger than those falling in non-showery precipitation. Between showers openings may be observed unless stratiform clouds fill the intervals between the cumuliform clouds.

[12.2.6.5.13]

B/C5.10.1.7 Past weather reported from a manned weather station

B/C5.10.1.7.1 Time period

The time period (0 04 024) covered by past weather (1) and past weather (2) shall be expressed as a *negative value* in hours:

- (a) Six hours, for observations at 0000, 0600, 1200, and 1800 UTC;
- (b) Three hours for observations at 0300, 0900, 1500, and 2100 UTC;
- (c) Two hours for intermediate observations if taken every two hours;
- (d) *One hour* for intermediate observations if taken every hour.

[12.2.6.6.1]

- B/C5.10.1.7.2** The code figures for past weather (1) and past weather (2) shall be selected in such a way that past and present weather together give as complete a description as possible of the weather in the time interval concerned. For example, if the type of weather undergoes a complete change during the time interval concerned, the code figures selected for past weather (1) and past weather (2) shall describe the weather prevailing before the type of weather indicated by present weather began. [12.2.6.6.2]

- B/C5.10.1.7.3** When the past weather (1) and past weather (2) are used in hourly reports, Regulation B/C5.10.1.7.1 (d) shall apply. [12.2.6.6.3]

- B/C5.10.1.7.4** If, using Regulation B/C5.10.1.7.2, more than one code figure may be given to past weather (1), the highest figure shall be reported for past weather (1) and the second highest code figure shall be reported for past weather (2). [12.2.6.6.4]

- B/C5.10.1.7.5** If the weather during the period has not changed so that only one code figure may be selected for past weather, then that code figure shall be reported for both past weather (1) and past weather (2). [12.2.6.6.5]

B/C5.10.1.8 Past weather reported from an automatic weather station**B/C5.10.1.8.1 Time period**

The time period (0 04 024) covered by past weather (1) and past weather (2) shall be expressed as a *negative value* in hours:

- (a) Six hours for observations at 0000, 0600, 1200, and 1800 UTC;
- (b) Three hours for observations at 0300, 0900, 1500, and 2100 UTC;
- (c) Two hours for intermediate observations if taken every two hours;
- (d) *One hour* for intermediate observations if taken every hour.

[12.2.6.7.1]

B/C5.10.1.8.2 The code figures for past weather (1) and past weather (2) shall be selected so that the maximum capability of the automatic station to discern past weather is utilized, and so that past and present weather together give as complete a description as possible of the weather in the time interval concerned. [12.2.6.7.2]

B/C5.10.1.8.3 In cases where the automatic station is capable only of discerning very basic weather conditions, the lower code figures representing basic and generic phenomena may be used. If the automatic station has higher discrimination capabilities, the higher code figures representing more detailed explanation of the phenomena shall be used. For each basic type of phenomenon, the highest code figure within the discrimination capability of the automatic station shall be reported. [12.2.6.7.3]

B/C5.10.1.8.4 If the type of weather during the time interval concerned undergoes complete and discernible changes, the code figures selected for past weather (1) and past weather (2) shall describe the weather prevailing before the type of weather indicated by present weather began. The highest figure shall be reported for past weather (1) and the second highest code figure shall be reported for past weather (2). [12.2.6.7.4]

B/C5.10.1.8.5 If a discernible change in weather has not occurred during the period, so that only one code figure may be selected for the past weather, then that code figure shall be reported for both past weather (1) and past weather (2). For example, rain during the entire period shall be reported as code figure 14 for both past weather (1) and past weather (2) in the case of an automatic station incapable of differentiating types of precipitation, or code figure 16 for both past weather (1) and past weather (2) in the case of a station with the higher discrimination capability. [12.2.6.7.5]

B/C5.10.2 Sunshine data (from 1 hour and 24-hour period) <1 01 002><3 02 039>**B/C5.10.2.1 Period of reference for sunshine duration**

Time period in hours (0 04 024) shall be included as follows:

- (a) one hour in the first replication (reported as –1);
- (b) 24 hours in the second replication (reported as –24).

B/C5.10.2.2 Duration of sunshine

Duration of sunshine from the time period specified by the preceding parameter 0 04 024, shall be reported in minutes.

B/C5.10.2.2.1 The duration of sunshine over the previous hour shall be reported by national decision. When reported, it shall be included in the first replication.

B/C5.10.2.2.2 The duration of sunshine over the previous 24 hours shall, by regional decision, be reported at all stations capable of doing so and included at either 0000 UTC, 0600 UTC, 1200 UTC or 1800 UTC. When reported, it shall be included in the second replication. [12.4.7.4.2]

B/C5.10.3 Precipitation measurement <3 02 040>

B/C5.10.3.1 Height of sensor above local ground

Height of sensor above local ground (0 07 032) for precipitation measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the rain gauge rim above ground at the point where the rain gauge is located.

B/C5.10.3.2 Period of reference for amount of precipitation

Time period (0 04 024) for amount of precipitation shall be reported as a *negative value* in hours. It shall be determined:

- (a) By regional decision (e.g. –6, –12, –24) in the first replication;
- (b) By national decision (e.g. –1, –3) in the second replication.

B/C5.10.3.3 Total amount of precipitation

Total amount of precipitation, which has fallen during the period of reference for amount of precipitation, shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre).

B/C5.10.3.3.1 Precipitation, when it can be and has to be reported, shall be reported as 0.0 kg m⁻² if no precipitation were observed during the referenced period. [12.2.5.4]

B/C5.10.3.3.2 Trace shall be reported as “–0.1 kg m⁻²”.

B/C5.10.4 Extreme temperature data <3 02 041>

B/C5.10.4.1 Height of sensor above local ground

Height of sensor above local ground (0 07 032) for temperature measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of temperature sensor(s) above ground at the point where the sensors are located.

B/C5.10.4.2 Periods of reference for extreme temperatures

Time period for maximum temperature and time period for minimum temperature (0 04 024) shall be determined by regional decision and reported as *negative values* in hours. [12.4.4]

Notes:

- (1) If the period for maximum temperature or the period for minimum temperature ends at the nominal time of report, the second value of 0 04 024 shall be reported as 0.
- (2) If the period for maximum temperature or the period for minimum temperature does not end at the nominal time of report, the first value of 0 04 024 shall indicate the beginning of the period of reference and the second value of 0 04 024 shall indicate the end of the period of reference. E.g. to report the maximum temperature for the previous calendar day from a station in RA IV, value of the first 0 04 024 shall be set to –30 and value of the second 0 04 024 shall be set to –6, provided that the nominal time of the report 12 UTC corresponds to 6 a.m. local time.

B/C5.10.4.3 Maximum and minimum temperature

Maximum and minimum temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C5.4.1.2 shall apply.

B/C5.10.5 Wind data <3 02 042>**B/C5.10.5.1 Height of sensor above local ground**

Height of sensor above local ground (0 07 032) for wind measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the sensors above ground at the point where the sensors are located.

B/C5.10.5.2 Type of instrumentation for wind measurement – Flag table 0 02 002

This datum shall be used to specify whether the wind speed was measured by certified instruments (bit No. 1 set to 1) or estimated on the basis of the Beaufort wind scale (bit No. 1 set to 0), and to indicate the original units for wind speed measurement. Bit No. 2 set to 1 indicates that wind speed was originally measured in knots and bit No. 3 set to 1 indicates that wind speed was originally measured in kilometres per hour. Setting both bits No. 2 and No. 3 to 0 indicates that wind speed was originally measured in metres per second.

B/C5.10.5.3 Wind direction and speed

The mean direction and speed of the wind over the 10-minute period immediately preceding the observation shall be reported. The time period (0 04 025) shall be included as –10. However, when the 10-minute period includes a discontinuity in the wind characteristics, only data obtained after the discontinuity shall be used for reporting the mean values, and hence the period (0 04 025) in these circumstances shall be correspondingly reduced. [12.2.2.3.1]

The time period is preceded by a time significance qualifier (0 08 021) that shall be set to 2 (Time averaged).

The wind direction (0 11 001) shall be reported in degrees true and the wind speed (0 11 002) shall be reported in metres per second (with precision in tenths of a metre per second).

Note: Surface wind direction measured at a station within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian.

B/C5.10.5.3.1 In the absence of wind instruments, the wind speed shall be estimated on the basis of the Beaufort wind scale. The Beaufort number obtained by estimation is converted into metres per second by use of the relevant wind speed equivalent column on the Beaufort scale, and this speed is reported for wind speed. [12.2.2.3.2]

B/C5.10.5.3.2 Calm shall be reported by setting wind direction to 0 and wind speed to 0. Variable shall be reported by setting wind direction to 0 and wind speed to a positive *non-missing* value.

B/C5.10.5.4 Maximum wind gust direction and speed

Time period for maximum wind gust direction and speed (0 04 025) shall be determined by regional or national decision and reported as a negative value in minutes.

Direction of the maximum wind gust (0 11 043) shall be reported in degrees true and speed of the maximum wind gust (0 11 041) shall be reported in metres per second (with precision in tenths of a metre per second).

B/C5.11 Evaporation data <3 02 044>

B/C5.11.1 Period of reference for evaporation data

Evaporation or evapotranspiration during the previous 24 hours shall be reported. Time period in hours (0 04 024) shall be included as –24.

B/C5.11.2 Indicator of type of instrument for evaporation measurement or the type of crops – Code table 0 02 004

B/C5.11.3 Evaporation or evapotranspiration

Amount of either evaporation or evapotranspiration (0 13 033) shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre) at 0000 UTC, 0600 UTC or 1200 UTC. [12.4.7.2.2]

B/C5.12 Radiation data (from 1 hour and 24-hour period) <1 01 002><3 02 045>

B/C5.12.1 Period of reference for radiation data

Radiation integrated over the previous hour and over the previous 24 hours may be reported. Time period in hours (0 04 024) shall be included as follows:

- (a) one hour in the first replication (reported as –1);
- (b) 24 hours in the second replication (reported as –24).

B/C5.12.2 Amount of radiation

If included, amount of radiation integrated over the time period specified by the preceding parameter 0 04 024 shall be reported in joules per square metre (with precision in thousands of a joule per square metre for radiation type (a) and (b); with precision in ten-thousands of a joule per square metre for radiation type (c); with precision in hundreds of a joule per square metre for radiation types (d) to (f)).

B/C5.12.2.1 The radiation data may take one or more of the following forms:

- (a) Long-wave radiation (0 14 002); the positive sign shall be used to specify downward long-wave radiation and the negative sign to specify upward long-wave radiation;
- (b) Short-wave radiation (0 14 004);
- (c) Net radiation (0 14 016); the corresponding sign shall be used to specify positive and negative net radiation);
- (d) Global solar radiation (0 14 028);
- (e) Diffuse solar radiation (0 14 029);
- (f) Direct solar radiation (0 14 030).

[12.4.7.4.3], [12.4.7.4.4]

Note: Data width and/or reference value of radiation descriptors were changed with introduction of the Version number 14 of WMO FM 94 BUFR Tables.

B/C5.13 Temperature change <3 02 046>

This information is required by regional or national decision from islands or other widely separated stations.

B/C5.13.1 Period of reference for temperature change

The temperature change shall be reported for the period of time between the time of the observation and the time of the occurrence of temperature change. To construct the required period, time period 0 04 024 shall be included twice; the first one corresponding to period covered by past weather (1) and past weather (2), the second one specified by the time of the occurrence of temperature change. Both values of 0 04 024 shall be negative and expressed in hours.

Note: The period is the number of whole hours, disregarding the minutes. For example, if the time of occurrence is 45 minutes after the time of the observation, the time period is considered to be zero hours. If the time of occurrence is 1 hour or more, but less than 2 hours after the observation, the time period go shall be considered to be 1 hour, etc.

B/C5.13.2 Temperature change over period specified

Temperature change (0 12 049) shall be reported in kelvin in BUFR, in degrees Celsius in CREX.

B/C5.13.2.1 For a change of temperature to be reported, the change shall be equal to or more than 5°C and occur in less than 30 minutes during the period covered by past weather (1) and past weather (2). [12.4.7.3]**B/C5.14 “Period” data required by regional or national reporting practices**

If regional or national reporting practices require inclusion of additional “period” parameters, the common sequence 3 07 090 shall be supplemented by relevant descriptors.

Notes:

- (1) “Period” parameter is a parameter that is coupled to a time period descriptor, e.g. 0 04 024, 0 04 025.
- (2) No regional requirements are currently indicated for reporting SYNOP MOBIL data in the *Manual on Codes* (WMO-No. 306), Volume II.

B/C10 – Regulations for reporting SHIP data in TDCF

TM 308009 – BUFR template for synoptic reports from sea stations suitable for SHIP data

		Sequence for representation of synoptic reports from a sea station suitable for SHIP data
3 08 009	3 01 093	Ship identification, movement, date/time, horizontal and vertical coordinates
	3 02 001	Pressure and 3-hour pressure change
	3 02 054	Ship “instantaneous” data
	0 08 002	Vertical significance (surface observations)
	3 02 055	Icing and ice
	3 02 057	Ship marine data
	3 02 060	Ship “period” data

This BUFR template for synoptic reports from sea stations further expands as follows:

				Unit, scale
			Ship identification, movement, date/time, horizontal and vertical coordinates	
3 01 093	3 01 036	0 01 011	Ship or mobile land station identifier D...D	CCITT IA5, 0
		0 01 012	Direction of motion of moving observing platform (see Note 1) D _s	Degree true, 0
		0 01 013	Speed of motion of moving observing platform (see Note 2) v _s	m s ⁻¹ , 0
		0 02 001	Type of station i _x	Code table, 0
		0 04 001	Year	Year, 0
		0 04 002	Month	Month, 0
		0 04 003	Day YY	Day, 0
		0 04 004	Hour GG	Hour, 0
		0 04 005	Minute gg	Minute, 0
		0 05 002	Latitude (coarse accuracy) L _a L _a L _a	Degree, 2
		0 06 002	Longitude (coarse accuracy) L _o L _o L _o	Degree, 2
	0 07 030		Height of station ground (platform) above mean sea level	m, 1
	0 07 031		Height of barometer above mean sea level	m, 1
			Pressure and 3-hour pressure change	
3 02 001	0 10 004		Pressure P ₀ P ₀ P ₀ P ₀	Pa, -1
	0 10 051		Pressure reduced to mean sea level PPPP	Pa, -1
	0 10 061		3-hour pressure change ppp	Pa, -1
	0 10 063		Characteristic of pressure tendency a	Code table, 0
			Ship “instantaneous” data	
			<i>Ship temperature and humidity data</i>	
3 02 054	3 02 052	0 07 032	Height of sensor above local ground (or deck of marine platform) (for temperature and humidity measurement)	m, 2
		0 07 033	Height of sensor above water surface (for temperature and humidity measurement)	m, 1
		0 12 101	Temperature/air temperature s _n TTT	K, 2
		0 02 039	Method of wet-bulb temperature measurement	Code table, 0
		0 12 102	Wet-bulb temperature s _w T _b T _b T _b	K, 2
		0 12 103	Dewpoint temperature s _n T _d T _d T _d	K, 2
		0 13 003	Relative humidity	%, 0

				Unit, scale
<i>Ship visibility data</i>				
	3 02 053	0 07 032	Height of sensor above local ground (or deck of marine platform) (for visibility measurement)	m, 2
		0 07 033	Height of sensor above water surface (for visibility measurement)	m, 1
		0 20 001	Horizontal visibility VV	m, -1
	0 07 033		Height of sensor above water surface (set to missing to cancel the previous value)	m, 1
<i>Precipitation past 24 hours</i>				
	3 02 034	0 07 032	Height of sensor above local ground (or deck of marine platform) (for precipitation measurement)	m, 2
		0 13 023	Total precipitation past 24 hours $R_{24}R_{24}R_{24}R_{24}$	kg m ⁻² , 1
	0 07 032		Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
<i>General cloud information</i>				
	3 02 004	0 20 010	Cloud cover (total) N	%, 0
		0 08 002	Vertical significance (surface observations)	Code table, 0
		0 20 011	Cloud amount (of low or middle clouds) N _h	Code table, 0
		0 20 013	Height of base of cloud h	m, -1
		0 20 012	Cloud type (low clouds) C _L	Code table, 0
		0 20 012	Cloud type (middle clouds) C _M	Code table, 0
		0 20 012	Cloud type (high clouds) C _H	Code table, 0
	1 01 000		Delayed replication of 1 descriptor	
	0 31 001		Delayed descriptor replication factor	Numeric, 0
	3 02 005	0 08 002	Vertical significance (surface observations)	Code table, 0
		0 20 011	Cloud amount N _s	Code table, 0
		0 20 012	Cloud type C	Code table, 0
		0 20 013	Height of base of cloud h _s h _s	m, -1
0 08 002			Vertical significance (surface observations) (set to missing to cancel the previous value)	Code table, 0
Icing and ice				
3 02 055	0 20 031		Ice deposit (thickness) E _s E _s	m, 2
	0 20 032		Rate of ice accretion R _s	Code table, 0
	0 20 033		Cause of ice accretion I _s	Flag table, 0
	0 20 034		Sea-ice concentration c _i	Code table, 0
	0 20 035		Amount and type of ice b _i	Code table, 0
	0 20 036		Ice situation z _i	Code table, 0
	0 20 037		Ice development S _i	Code table, 0
	0 20 038		Bearing of ice edge D _i	Degree true, 0
Ship marine data				
3 02 057	3 02 056		Sea/water temperature (method of measurement, and depth below sea surface)	
		0 02 038	Method of water temperature measurement	Code table, 0
		0 07 063	Depth below sea/water surface (cm) (for sea-surface temperature measurement)	m, 2
		0 22 043	Sea/water temperature s _s T _w T _w T _w	K, 2
		0 07 063	Depth below sea/water surface (cm) (set to missing to cancel the previous value)	m, 2
<i>Waves</i>				
	3 02 021	0 22 001	Direction of waves	Degree true, 0
		0 22 011	Period of waves P _{wa} P _{wa}	s, 0

				Unit, scale
		0 22 021	Height of waves $H_{wa}H_{wa}$	m, 1
	3 02 024	0 22 002	Direction of wind waves	Degree true, 0
		0 22 012	Period of wind waves P_wP_w	s, 0
		0 22 022	Height of wind waves H_wH_w	m, 1
		1 01 002	Replicate 1 descriptor 2 times	
		3 02 023	Swell waves (2 systems of swell) $d_{w1}d_{w1}, P_{w1}P_{w1}, H_{w1}H_{w1}$ $d_{w2}d_{w2}, P_{w2}P_{w2}, H_{w2}H_{w2}$	
			Ship “period” data	
			<i>Present and past weather</i>	
3 02 060	3 02 038	0 20 003	Present weather ww	Code table, 0
		0 04 024	Time period or displacement (in hours)	Hour, 0
		0 20 004	Past weather (1) W_1	Code table, 0
		0 20 005	Past weather (2) W_2	Code table, 0
			<i>Precipitation measurement</i>	
	3 02 040	0 07 032	Height of sensor above local ground (or deck of marine platform) (for precipitation measurement)	m, 2
		1 02 002	Replicate 2 descriptors 2 times	
		0 04 024	Time period or displacement (in hours) t_R	Hour, 0
		0 13 011	Total precipitation/total water equivalent (of snow) RRR	kg m ⁻² , 1
			<i>Ship extreme temperature data</i>	
	3 02 058	0 07 032	Height of sensor above local ground (or deck of marine platform) (for temperature measurement)	m, 2
		0 07 033	Height of sensor above water surface (for temperature measurement)	m, 1
		0 04 024	Time period or displacement	Hour, 0
		0 04 024	Time period or displacement (see Notes 3 and 4)	Hour, 0
		0 12 111	Maximum temperature, at height and over period specified $s_nT_xT_xT_x$	K, 2
		0 04 024	Time period or displacement	Hour, 0
		0 04 024	Time period or displacement (see Note 4)	Hour, 0
		0 12 112	Minimum temperature, at height and over period specified $s_nT_nT_nT_n$	K, 2
			<i>Ship wind data</i>	
	3 02 059	0 07 032	Height of sensor above local ground (or deck of marine platform) (for wind measurement)	m, 2
		0 07 033	Height of sensor above water surface (for wind measurement)	m, 1
		0 02 002	Type of instrumentation for wind measurement i_w	Flag table, 0
		0 08 021	Time significance (= 2 Time averaged)	Code table, 0
		0 04 025	Time period or displacement (= –10 minutes, or number of minutes after a significant change of wind)	Minute, 0
		0 11 001	Wind direction dd	Degree true, 0
		0 11 002	Wind speed ff	m s ⁻¹ , 1
		0 08 021	Time significance (= missing value)	Code table, 0
		1 03 002	Replicate 3 descriptors 2 times	
		0 04 025	Time period or displacement (in minutes)	Minute, 0
		0 11 043	Maximum wind gust direction	Degree true, 0
		0 11 041	Maximum wind gust speed $910f_mf_m, 911f_xf_x$	m s ⁻¹ , 1

Notes:

- (1) 0 01 012: Means course made good (average course over the ground) during the three hours preceding the time of observation.
- (2) 0 01 013: Means speed made good (average speed over the ground) during the three hours preceding the time of observation.
- (3) Within RA IV, the maximum temperature at 1200 UTC is reported for the previous calendar day (i.e. the ending time of the period is not equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (4) Within RA III, the maximum daytime temperature and the minimum night-time temperature is reported (i.e. the ending time of the period may not be equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (5) If “plain language” text is reported within Section 2, this information can be conveyed in BUFR via the use of an appropriate 2 05 YYY field as an extra descriptor following the above basic template.
- (6) If WMO block and station number is to be included in reports from a fixed sea station, sequence descriptor <3 08 009> may be preceded by sequence descriptor <3 01 001>.

Provisional Copy
2023

Regulations:

B/C10.1	Section 1 of BUFR or CREX
B/C10.2	Ship identification, movement, date/time, horizontal and vertical coordinates
B/C10.3	Pressure and 3-hour pressure change
B/C10.4	Ship “instantaneous” data
B/C10.4.1	Ship temperature and humidity data
B/C10.4.2	Ship visibility data
B/C10.4.3	Precipitation past 24 hours
B/C10.4.4	General cloud information
B/C10.4.5	Individual cloud layers or masses
B/C10.5	Icing and ice
B/C10.6	Ship marine data
B/C10.7	“Instantaneous” data required by regional or national reporting practices
B/C10.8	Ship “period” data
B/C10.8.1	Present and past weather
B/C10.8.2	Precipitation measurement
B/C10.8.3	Ship extreme temperature data
B/C10.8.4	Ship wind data
B/C10.9	“Period” data required by regional or national reporting practices

B/C10.1 Section 1 of BUFR or CREX

B/C10.1.1 Entries required in Section 1 of BUFR

The following entries shall be included in BUFR Section 1:

- BUFR master table;
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Identification of inclusion of optional section;
- Data category (001 for SHIP data);
- International data sub-category (see Note 1);
- Local data sub-category;
- Version number of master table;
- Version number of local tables;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for SHIP data);
- Hour (GG in the abbreviated telecommunication header for SHIP data);
- Minute (00 for SHIP data);
- Second (00).

Notes:

- (1) If required, the international data sub-category shall be included for SHIP data as 000 at all observation times 00, 01, 02, ..., 23 UTC.
- (2) If an NMHS performs conversion of SHIP data produced by another NMHS, originating centre in Section 1 shall indicate the converting centre and originating sub-centre shall indicate the producer of SHIP bulletins. The producer of SHIP bulletins shall be specified in Common Code table C-12 as a sub-centre of the originating centre, i.e. of the NMHS executing the conversion.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C10.1.2 Entries required in Section 1 of CREX

The following entries shall be included in CREX Section 1:

- CREX master table;
- CREX edition number;
- CREX table version number;
- Version number of BUFR master table;
- Version number of local tables;
- Data category (001 for SHIP data);
- International data sub-category (see Note 1);
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Number of subsets;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for SHIP data);
- Hour (GG in the abbreviated telecommunication header for SHIP data);
- Minute (00 for SHIP data).

Notes:

- (1) If inclusion of the international data sub-category is required, Note 1 under Regulation B/C10.1.1 applies.
- (2) If an NMHS performs conversion of SHIP data produced by another NMHS, Note 2 under Regulation B/C10.1.1 applies.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C10.2 Ship identification, movement, date/time, horizontal and vertical coordinates <3 01 093>

B/C10.2.1 Ship identification, movement, type of station

Ship identifier (0 01 011) shall be always reported as a non-missing value. In the absence of a suitable call sign, the word SHIP shall be used for ship identifier in reports of sea stations other than buoys, drilling rigs and oil- and gas-production platforms. [12.1.7(b)]

If required, WMO block number (0 01 001) and WMO station number (0 01 002) may be included in reports from a fixed sea station.

Note: Note 6 under TM 308009 shall apply.

B/C10.2.2 Ship movement

Direction of motion of moving observing platform (0 01 012) shall be reported in degrees true to indicate course made good (average course over the ground) during the three hours preceding the time of observation.

Speed of motion of moving observing platform (0 01 013) shall be reported in metres per second to indicate speed made good (average speed over the ground) during the three hours preceding the time of observation.

B/C10.2.2.1 Direction and speed of motion of moving observing platform shall always be included in reports from stations, which have observed maritime conditions, and in reports from ships being requested to include this information as a routine procedure. [12.3.1.1]

B/C10.2.2.2 Direction and speed of motion of moving observing platform may be included as missing values in reports from ships that have not been directly recruited and instrumented by an NMHS, except when reporting from an area for which the

ship report collecting centre, in order to meet a requirement of a search and rescue centre, has requested inclusion of direction and speed of ship motion as a routine procedure. [12.3.1.2(b)]

B/C10.2.2.3 Stationary position of ship shall be reported by 0 01 012 set to 0 and 0 01 013 set to 0. Course of ship unknown ($D_s = 9$) shall be reported by 0 01 012 set to 509.

B/C10.2.3 Type of station

Type of station (0 02 001) shall be reported to indicate the type of the station operation (manned, automatic or hybrid).

Note: If a station operates as a manned station for a part of the day and as an automatic station for the rest of the day, code figure 2 (Hybrid) may be used in all reports. It is preferable, however, to use code figure 1 (manned) in reports produced under the supervision of an observer, and a code figure 0 (Automatic) in reports produced while the station operates in the automatic mode.

B/C10.2.4 Time of observation

Year (0 04 001), month (0 04 002), day (0 04 003), hour (0 04 004) and minute (0 04 005) of the actual time of observation shall be reported.

Note: The actual time of observation shall be the time at which the barometer is read. [12.1.6]

B/C10.2.4.1 The time in Section 1 (B/C1.1.1) may be reported instead of the actual time of observation if the actual time of observation differs by 10 minutes or less from the nearest hour. [12.2.8]

B/C10.2.5 Horizontal and vertical coordinates

Latitude (0 05 002) and longitude (0 06 002) of the station shall be reported in degrees with precision in hundredths of a degree.

Height of station ground above mean sea level (0 07 030) and height of barometer above mean sea level (0 07 031) shall be reported in metres with precision in tenths of a metre.

B/C10.3 Pressure and 3-hour pressure change <3 02 001>

B/C10.3.1 Pressure at the station level

Pressure at the station level (0 10 004), i.e. at the level defined by 0 07 031 (height of barometer above mean sea level), shall be reported in pascals (with precision in tens of pascals).

Note: Inclusion of the station pressure in reports from sea stations is left to the decision of individual Members.

B/C10.3.2 Pressure reduced to mean sea level

Pressure reduced to mean sea level (0 10 051) shall be reported in pascals (with precision in tens of pascals).

B/C10.3.2.1 In reports from ships, air pressure at mean sea level shall be reported. [12.1.3.6], [12.1.3.7]

B/C10.3.3 Three-hour pressure change and characteristic of pressure tendency

Amount of pressure change at station level, during the three hours preceding the time of observation (0 10 061), either positive, zero or *negative*, shall be reported in pascals (with precision in tens of pascals).

B/C10.3.3.1 Unless specified otherwise by regional decision, pressure tendency shall be included whenever the three-hourly pressure tendency is available. [12.2.3.5.1]

B/C10.3.3.2 The characteristic of pressure tendency (Code table 0 10 063) over the past three hours shall, whenever possible, be determined on the basis of pressure samples at equi-spaced intervals not exceeding one hour.

Note: Algorithms for selecting the appropriate code figure are included in the *Guide to Meteorological Instruments and Methods of Observation* (WMO-No. 8).

[12.2.3.5.2]

B/C10.3.3.3 Where it is not possible to apply the algorithms specified in Regulation B/C10.3.3.2 in reports from automatic weather stations, the characteristic of pressure tendency shall be reported as 2 when the tendency is positive, as 7 when the tendency is negative, and as 4 when the atmospheric pressure is the same as three hours before. [12.2.3.5.3]

B/C10.4 Ship “instantaneous” data <3 02 054>**B/C10.4.1 Ship temperature and humidity data <3 02 052>****B/C10.4.1.1 Height of sensor above marine deck platform and height of sensor above water surface**

Height of sensor above marine deck platform (0 07 032) for temperature and humidity measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of temperature and humidity sensors above marine deck platform at the point where the sensors are located.

Height of sensor above water surface (0 07 033) for temperature and humidity measurement shall be reported in metres (with precision in tenths of a metre).

This datum represents the actual height of temperature and humidity sensors above marine water surface of sea or lake.

B/C10.4.1.2 Dry-bulb air temperature

Dry-bulb air temperature (0 12 101) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree. This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

B/C10.4.1.2.1 When the data are not available as a result of a temporary instrument failure, this quality shall be included as a missing value. [12.2.3.2]

B/C10.4.1.3 Wet-bulb temperature and method of its measurement

Wet-bulb temperature (0 12 102) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Method of wet-bulb temperature measurement shall be reported by the preceding entry (Code table 0 02 039). Wet-bulb temperature data shall be reported with precision in hundredths of a degree even if they are available with the accuracy in tenths of a degree.

Note: Notes 1 and 2 under Regulation B/C10.4.1.2 shall apply.

B/C10.4.1.3.1 When wet-bulb temperature is used to derive dewpoint value in a ship report, 0 12 102 shall be included to report the wet-bulb temperature measurement. [12.3.6]

B/C10.4.1.4 Dewpoint temperature

When available, dewpoint temperature (0 12 103) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C10.4.1.2 shall apply.

B/C10.4.1.5 Relative humidity

Relative humidity (0 13 003) shall be reported in units of a per cent.

B/C10.4.1.5.1 *Both dewpoint temperature and relative humidity shall be reported when available.*

B/C10.4.2 Ship visibility data <3 02 053>**B/C10.4.2.1 Height of sensor above marine deck platform and height of sensor above water surface**

Height of sensor above marine deck platform (0 07 032) for visibility measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of visibility sensors above marine deck platform at the point where the sensors are located. If visibility is estimated by a human observer, the average height of observer's eyes above marine deck platform shall be reported.

Height of sensor above water surface (0 07 033) for visibility measurement shall be reported in metres (with precision in tenths of a metre).

This datum represents the actual height of visibility sensors above the level of water surface of sea or lake. If visibility is estimated by a human observer, the average height of observer's eyes above the level of water surface of sea or lake at the time of observation shall be reported.

B/C10.4.2.2 Horizontal visibility

Horizontal visibility (0 20 001) at surface shall be reported in metres (with precision in tens of metres).

B/C10.4.2.2.1 When the horizontal visibility is not the same in different directions, the shortest distance shall be given for visibility. [12.2.1.3.1]

B/C10.4.2.2.2 Horizontal visibility greater than 81 900 m shall be expressed by 0 20 001 set to 81 900 m; if TDCF data are converted from SHIP data, 0 20 001 set to 50 000 m shall indicate horizontal visibility equal to or greater than 50 000 m. [12.2.1.3.2]

B/C10.4.3 Precipitation past 24 hours <3 02 034>**B/C10.4.3.1 Height of sensor above marine deck platform**

Height of sensor above marine deck platform (0 07 032) for precipitation measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the rain gauge rim above marine deck platform at the point where the rain gauge is located.

Note: Height of sensor above water surface (0 07 033) is not required for precipitation measurement. Therefore, there is an entry 0 07 033, directly preceding the sequence 3 02 034, that is set to a missing value to cancel the previous value.

B/C10.4.3.2 Total amount of precipitation during the 24-hour period

Total amount of precipitation during the 24-hour period ending at the time of observation (0 13 023) shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre). [12.4.9]

B/C10.4.3.2.1 The precipitation over the past 24 hours shall be included (not missing) at least once a day at one appropriate time of the main standard times (0000, 0600, 1200, 1800 UTC). [12.4.1]**B/C10.4.3.2.2** Precipitation, when it can be and has to be reported, shall be reported as 0.0 kg m^{-2} if no precipitation were observed during the referenced period. [12.2.5.4]**B/C10.4.3.2.3** Trace shall be reported as “ -0.1 kg m^{-2} ”.**B/C10.4.4 General cloud information <3 02 004>****B/C10.4.4.1 Total cloud cover**

Total cloud cover (0 20 010) shall embrace the total fraction of the celestial dome covered by clouds irrespective of their genus. It shall be reported in *units of a per cent*.

Notes:

(1) Total cloud cover shall be reported as 113 when sky is obscured by fog and/or other meteorological phenomena.

(2) When cloud cover is observed in oktas the cloud cover shall be converted to per cent, with fractional numbers rounded up (e.g. 1 okta = 12.5%, rounded to 13 %).

B/C10.4.4.1.1 Total cloud cover shall be reported as actually seen by the observer during the observation. [12.2.2.2.1]**B/C10.4.4.1.2** Altocumulus perlucidus or Stratocumulus perlucidus (“mackerel sky”) shall be reported as 99% or less (unless overlying clouds appear to cover the whole sky) since breaks are always present in this cloud form even if it extends over the whole celestial dome. [12.2.2.2.2]**B/C10.4.4.1.3** Total cloud cover shall be reported as zero when blue sky or stars are seen through existing fog or other analogous phenomena without any trace of cloud being seen. [12.2.2.2.3]**B/C10.4.4.1.4** When clouds are observed through fog or analogous phenomena, their amount shall be evaluated and reported as if these phenomena were non-existent. [12.2.2.2.4]

- B/C10.4.4.1.5** Total cloud cover shall not include the amount resulting from rapidly dissipating condensation trails. [12.2.2.2.5]
- B/C10.4.4.1.6** Persistent condensation trails and cloud masses, which have obviously developed from condensation trails, shall be reported as cloud. [12.2.2.2.6]
- B/C10.4.4.2** **Vertical significance** – Code table 0 08 002
- To specify vertical significance (0 08 002) within the sequence 3 02 004, a code figure shall be selected in the following way:
- (a) If low clouds are observed, then code figure 7 (Low cloud) shall be used;
 - (b) If there are no low clouds but middle clouds are observed, then code figure 8 (Middle clouds) shall be used;
 - (c) If there are no low and there are no middle clouds but high clouds are observed, then code figure 0 shall be used;
 - (d) If sky is obscured by fog and/or other phenomena, then code figure 5 (Ceiling) shall be used;
 - (e) If there are no clouds (clear sky), then code figure 62 (Value not applicable) shall be used
 - (f) If the cloud cover is not discernible for reasons other than (d) above or observation is not made, then code figure 63 (Missing value) shall be used.
- B/C10.4.4.3** **Cloud amount (of low or middle clouds)** – Code table 0 20 011
- Amount of all the low clouds (clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus) present or, if no low clouds are present, the amount of all the middle clouds (clouds of the genera Altopumulus, Altostratus, and Nimbostratus) present.
- B/C10.4.4.3.1** Cloud amount shall be reported as follows:
- (a) If there are low clouds, then the total amount of all low clouds, as actually seen by the observer during the observation shall be reported for the cloud amount;
 - (b) If there are no low clouds but there are middle clouds, then the total amount of the middle clouds shall be reported for the cloud amount;
 - (c) If there are no low clouds and there are no middle clouds but there are high clouds (clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus), then the cloud amount shall be reported as zero;
- [12.2.7.2.1]
- (d) If no clouds are observed (clear sky), then the cloud amount shall be reported as 0;
 - (e) If sky is obscured by fog and/or other meteorological phenomena, then the cloud amount shall be reported as 9;
 - (f) If cloud cover is indiscernible for reasons other than fog or other meteorological phenomena, or observation is not made, the cloud amount shall be reported as missing.
- B/C10.4.4.3.2** Amount of Altopumulus perlucidus or Stratocumulus perlucidus (“mackerel sky”) shall be reported using code figure 7 or less since breaks are always present in this cloud form even if it extends over the whole celestial dome. [12.2.7.2.2]
- B/C10.4.4.3.3** When the clouds reported for cloud amount are observed through fog or an analogous phenomenon, the cloud amount shall be reported as if these phenomena were not present. [12.2.7.2.3]

- B/C10.4.4.3.4** If the clouds reported for cloud amount include contrails, then the cloud amount shall include the amount of persistent contrails. Rapidly dissipating contrails shall not be included in the value for the cloud amount. [12.2.7.2.4]
- B/C10.4.4.4** **Height of base of lowest cloud**
Height above surface of the base (0 20 013) of the lowest cloud seen shall be reported in metres (with precision in tens of metres).

Note: The term « height above surface » shall be considered as being the height above water surface of sea or lake.
- B/C10.4.4.4.1** When clouds are observed through fog or analogous phenomena but the sky is discernible, the base of the lowest cloud shall refer to the base of the lowest cloud observed, if any. When, under the above conditions, the sky is not discernible, the base of the lowest cloud shall be replaced by vertical visibility. [12.4.10.5]
- B/C10.4.4.4.2** When no cloud is reported (total cloud cover = 0) the base of the lowest cloud *shall be reported as a missing value.*
- B/C10.4.4.4.3** If synoptic data are produced in BUFR or CREX by conversion from a TAC report, the following approach shall be used: Height of base of the lowest cloud 0 20 013 shall be derived from the $h_s h_s$ in the first group 8 in section 3, i.e. from the $h_s h_s$ of the lowest cloud. If and only if groups 8 are not reported in section 3, 0 20 013 may be derived from h . The lower limit of the range defined for $h_s h_s$ and for h shall be used. However, if groups 8 are not reported in section 3 and $h = 9$ and $N_h \neq 0$, then 0 20 013 shall be 4 000 m; if groups 8 are not reported in section 3 and $h = 9$ and $N_h = 0$, then 0 20 013 shall be 8 000 m.
- B/C10.4.4.5** **Cloud type of low, middle and high clouds** – Code table 0 20 012
Clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus (low clouds) shall be reported for the first entry 0 20 012, clouds of the genera Altopumulus, Altostratus, and Nimbostratus (middle clouds) shall be reported for the second entry 0 20 012 and clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus (high clouds) shall be reported for the third entry 0 20 012.
- B/C10.4.4.5.1** The reporting of type of low, middle and high clouds shall be as specified in the *International Cloud Atlas* (WMO-No. 407), Volume I. [12.2.7.3]
- B/C10.4.5** **Individual cloud layers or masses**
- B/C10.4.5.1** **Number of individual cloud layers or masses**
The number of individual cloud layers or masses shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:
(1) The number of cloud layers or masses shall never be set to missing value.
(2) The number of cloud layers or masses shall be set to a positive value in a NIL report.
(3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.
- B/C10.4.5.1.1** When reported from a manned station, the number of individual cloud layers or masses shall in the absence of Cumulonimbus clouds not exceed three.

Cumulonimbus clouds, when observed, shall always be reported, so that the total number of individual cloud layers or masses can be four. The selection of layers (or masses) to be reported shall be made in accordance with the following criteria:

- (a) The lowest individual layer (or mass) of any amount (cloud amount at least one octa or less, but not zero);
- (b) The next higher individual layer (or mass) the amount of which is greater than two octas;
- (c) The next higher individual layer (or mass) the amount of which is greater than four octas;
- (d) Cumulonimbus clouds, whenever observed and not reported under (a), (b) and (c) above.

[12.4.10.1]

B/C10.4.5.1.2 When the sky is clear, the number of individual cloud layers or masses shall be set to zero.

B/C10.4.5.1.3 The order of reporting the individual cloud layers or masses shall always be from lower to higher levels. [12.4.10.2]

B/C10.4.5.2 Individual cloud layer or mass <3 02 005>
Each cloud layer or mass shall be represented by the following four parameters: Vertical significance (0 08 002), amount of individual cloud layer or mass (0 20 011), type of cloud layer or mass (0 20 012) and height of base of individual cloud layer or mass (0 20 013).

B/C10.4.5.2.1 Vertical significance – Code table 0 08 002
To specify vertical significance (0 08 002) within the sequence 3 02 005, a code figure shall be selected in the following way:

- (a) Code figure 1 shall be used in the first non-Cumulonimbus layer;
- (b) Code figure 2 shall be used in the second non-Cumulonimbus layer;
- (c) Code figure 3 shall be used in the third non-Cumulonimbus layer;
- (d) Code figure 4 shall be used in any Cumulonimbus layer;
- (e) If sky is obscured by fog and/or other phenomena, then code figure 5 (Ceiling) shall be used;
- (f) If the cloud cover is not discernible for reasons other than (e) above or observation is not made, then code figure 63 (Missing value) shall be used;
- (g) If a station operates in the automatic mode and is sufficiently equipped, code figure 21, 22, 23 and 24 shall be used to identify the first, the second, the third and the fourth instrument detected cloud layer, respectively;
- (h) If a station operates in the automatic mode and no clouds are detected by the cloud detection system, code figure 20 shall be used.

B/C10.4.5.2.2 Cloud amount, type and height of base

B/C10.4.5.2.2.1 When the sky is clear, in accordance with Regulation B/C10.4.5.1.2 cloud amount, genus, and height shall not be included. [12.4.10.4]

B/C10.4.5.2.2.2 In determining cloud amounts (Code table 0 20 011) to be reported for individual layers or masses, the observer shall estimate, by taking into consideration the evolution of the sky, the cloud amounts of each individual layer or mass at the different levels, as if no other clouds existed. [12.4.10.3]

B/C10.4.5.2.2.3 Type of a cloud layer or mass (Code table 0 20 012) shall be reported using code figures 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 59 and 63.

B/C10.4.5.2.2.4 If, notwithstanding the existence of fog or other obscuring phenomena, the sky is discernible, the partially obscuring phenomena shall be disregarded. If, under the above conditions, the sky is not discernible, the cloud type shall be reported using *code figure 59* and the cloud height shall be replaced by vertical visibility.

Note: The vertical visibility is defined as the vertical visual range into an obscuring medium.

[12.4.10.5]

B/C10.4.5.2.2.5 If two or more types of cloud occur with their bases at the same level and this level is one to be reported in accordance with Regulation B/C10.4.5.1.1, the selection for cloud type and amount shall be made with the following criteria:

- (a) If these types do not include Cumulonimbus then cloud genus shall refer to the cloud type that represents the greatest amount, or if there are two or more types of cloud all having the same amount, the highest applicable code figure for cloud genus shall be reported. Cloud amount shall refer to the total amount of cloud whose bases are all at the same level;
- (b) If these types do include Cumulonimbus then one layer shall be reported to describe only this type with cloud genus indicated as Cumulonimbus and the cloud amount as the amount of the Cumulonimbus. If the total amount of the remaining type(s) of cloud (excluding Cumulonimbus) whose bases are all at the same level is greater than that required by Regulation B/C10.4.5.1.1, then another layer shall be reported with type being selected in accordance with (a) and amount referring to the total amount of the remaining cloud (excluding Cumulonimbus).

[12.4.10.6]

B/C10.4.5.2.2.6 Regulations B/C10.4.4.1.3 to B/C10.4.4.1.6, inclusive, shall apply. [12.4.10.7]

B/C10.4.5.2.2.7 Height above surface of the cloud base (0 20 013) shall be reported in metres (with precision in tens of metres).

Note: The term « height above surface » shall be considered as being the height above water surface of sea or lake.

B/C10.5 Icing and ice <3 02 055>

B/C10.5.1 Icing

Thickness of ice deposit (0 20 031) shall be reported in metres (with precision in hundredths of a metre).

Rate of ice accretion (0 20 032) shall be reported using corresponding Code table.

Cause of ice accretion (0 20 033) shall be reported using corresponding Flag table.

B/C10.5.1.1 When the ice accretion on ships is reported in plain language, this information shall be conveyed in BUFR/CREX via the use of an appropriate 2 05 YYY field as an extra descriptor following the basic template.

B/C10.5.1.2 When the ice accretion on ships is reported in plain language, it shall be preceded by the word ICING. [12.3.5]

B/C10.5.2 Ice

Sea-ice concentration (0 20 034) shall be reported using corresponding Code table.

Amount and type of ice (0 20 035) shall be reported using corresponding Code table.

Ice situation (0 20 036) shall be reported using corresponding Code table.

Ice development (0 20 037) shall be reported using corresponding Code table.

Bearing of ice edge (0 20 038) shall be reported in degrees true.

B/C10.5.2.1 The reporting of sea ice and ice of land origin using the sequence <0 20 034, 0 20 035, 0 20 036, 0 20 037, 0 20 038> shall not supersede the reporting of sea ice and icebergs in accordance with the International Convention for the Safety of Life at Sea. [12.3.7.1]

B/C10.5.2.2 The sequence <0 20 034, 0 20 035, 0 20 036, 0 20 037, 0 20 038> shall be reported whenever sea ice and/or ice of land origin are observed from the ship's position at the time of observation, unless the ship is required to report ice conditions by means of a special sea-ice code. [12.3.7.2]

B/C10.5.2.3 When an ice edge is crossed or sighted between observational hours, it shall be reported as a plain-language addition in the form "ice edge lat. long." (with position in degrees and minutes). This information shall be conveyed in BUFR/CREX via the use of an appropriate 2 05 YYY field as an extra descriptor following the basic template. [12.3.7.3]

B/C10.5.2.4 If the ship is in the open sea reporting an ice edge, the sea-ice concentration (0 20 034) and ice development (0 20 037) shall be reported only if the ship is close to the ice (i.e. within 0.5 nautical mile). [12.3.7.4]

B/C10.5.2.5 If the ship is in an open lead more than 1.0 nautical mile wide, sea-ice concentration (0 20 034) shall be set to 1 and bearing of ice edge (0 20 038) to 0. If the ship is in fast ice with ice boundary beyond limit of visibility, sea-ice concentration (0 20 034) shall be set to 1 and bearing of ice edge (0 20 038) to missing. [12.3.7.5]

B/C10.5.2.6 If no sea ice is visible and the sequence <0 20 034, 0 20 035, 0 20 036, 0 20 037, 0 20 038> is used to report ice of land origin only, 0 20 035 shall be used to report the amount of ice of land origin, and 0 20 034 and 0 20 036 shall be set to 0, and 0 20 037 and 0 20 038 shall be set to missing; e.g. <0,2,0, missing, missing> would mean 6–10 icebergs in sight, but no sea ice. [12.3.7.6]

B/C10.5.2.7 In coding concentration or arrangement of sea ice (0 20 034) that condition shall be reported which is of the most navigational significance. [12.3.7.7]

B/C10.5.2.8 The bearing of the principal ice edge reported shall be to the closest part of that edge. [12.3.7.8]

B/C10.5.2.9 The requirements for sea-ice reporting are covered in the following way by the associated parameters:

Sea-ice concentration – Code table 0 20 034

(a) The purpose of the code figure 0 in code table 0 20 034 is to establish in relation to code figure 0 in code table 0 20 036 and code table 0 20 035 whether the floating ice that is visible is only ice of land origin;

- (b) The possible variation in sea-ice concentration and arrangement within an area of observation are almost infinite. However, the field of reasonably accurate observation from a ship's bridge is limited. For this reason, and also because minor variations are of temporary significance, the choice of concentrations and arrangements has been restricted for reporting purposes to those representing significantly different conditions from a navigational point of view. The code figures 2–9 have been divided into two sections depending on:
- (i) Whether sea-ice concentration within the area of observation is more or less uniform (code figures 2–5); or
 - (ii) Whether there are marked contrasts in concentration or arrangement (code figures 6–9).

Amount and type of ice – Code table 0 20 035

- (a) This code provides a scale of increasing navigational hazard;
- (b) Growlers and bergy bits, being much smaller and lower in the water than icebergs, are more difficult to see either by eye or radar. This is especially so if there is heavy sea running. For this reason, code figures 4 and 5 represent more hazardous conditions than code figures 1 to 3.

Ice situation – Code table 0 20 036

- (a) The purpose of this parameter is to establish:
 - (i) Whether the ship is in pack ice or is viewing floating ice (i.e. sea ice and/or ice of land origin) from the open sea; and
 - (ii) A qualitative estimate, dependent on the sea-ice navigation capabilities of the reporting ship, of the penetrability of the sea ice and of the recent trend in conditions;
- (b) The reporting of the conditions represented by code figures 1–9 in Code table 0 20 036 can be used to help in the interpretation of reports from the two code tables (ice concentration 0 20 034 and ice development 0 20 037).

Ice development – Code table 0 20 037

- (a) This code table represents a series of increasing navigational difficulties for any given concentration; i.e. if the concentration is, for example, 8/10ths, then new ice would hardly have any effect on navigation while predominantly old ice would provide difficult conditions requiring reductions in speed and frequent course alternations;
- (b) The correlation between the stage of development of sea ice and its thickness is explained in the *Guide to Meteorological Instruments and Methods of Observation* (WMO-No. 8).

Bearing of ice edge – 0 20 038

There is no provision in this code for the reporting of distance from the ice edge. It will be assumed by those receiving the report that the bearing has been given to the closest part of the ice edge. From the reported code figures for ice concentration 0 20 034 and ice development 0 20 037, it will be clear whether the ship is in ice or within 0.5 nautical mile of the ice edge. If the ship is in open water and more than 0.5 nautical mile from the ice edge, the ice edge will be assumed to be aligned at right angles to the bearing which is reported.

B/C10.6 Ship marine data <3 02 057>

B/C10.6.1 Sea/water temperature <3 02 056>

Method of sea/water temperature measurement shall be reported by Code table 0 02 038; depth below sea/water surface (0 07 063) shall be reported in metres (with precision in hundredths of a metre). Sea/water temperature (0 22 043) shall

be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Sea/water temperature data shall be reported with precision in hundredths of a degree even if they are available with the accuracy in tenths of a degree.

Note: Notes 1 and 2 under Regulation B/C10.4.1.2 shall apply.

B/C10.6.1.1 Sea/water temperature shall always be included in reports from ocean weather stations, when data are available. [12.3.2]

B/C10.6.2 Instrumental wave data <3 02 021>

Direction of waves (0 22 001) shall be used to reported true direction (direction from which the waves are coming) in degrees true.

Period of waves (0 22 011) shall be reported in seconds.

Height of waves (0 22 021) shall be reported in metres with precision in tenths of a metre.

Note: Height of waves shall be reported with precision in tenths of a metre even if the data are available with lower accuracy and reported in TAC in units of 0.5 metre. [12.3.3.2]

B/C10.6.2.1 These data shall always be included in reports from ocean weather stations, when data are available. [12.3.3.1]

B/C10.6.2.2 The sequence 3 02 021 shall be used to report instrumental wave data. [12.3.3.2]

B/C10.6.2.3 When the sea is calm (no waves and no swell) direction of waves, period of waves and height of waves shall be reported as 0. [12.3.3.4(a)], [12.3.3.5(a)]

B/C10.6.2.4 If instrumental wave data are not available for direction, period or height of waves, as the case may be, 0 22 001, 0 22 011 or 0 22 021 shall be set to missing. [12.3.3.4(c)]

B/C10.6.3 Wind waves and swell waves <3 02 024>

Direction of wind waves (0 22 002) shall be used to reported true direction (direction from which the waves are coming) in degrees true.

Period of wind waves (0 22 012) shall be reported in seconds.

Height of wind waves (0 22 022) shall be reported in metres with precision in tenths of a metre.

Direction of swell waves (0 22 003) shall be used to reported true direction (direction from which the waves are coming) in degrees true.

Period of swell waves (0 22 013) shall be reported in seconds.

Height of swell waves (0 22 023) shall be reported in metres with precision in tenths of a metre.

B/C10.6.3.1 Wind wave data and swell wave data shall always be included in reports from ocean weather stations, when data are available. [12.3.3.1], [12.3.4.4]

B/C10.6.3.2 The sequence <0 22 002, 0 22 012, 0 22 022> shall be used to report wind waves, when instrumental wave data are not available. [12.3.3.3]

B/C10.6.3.3 When the sea is calm (no waves and no swell) direction, period and height of wind waves shall be reported as 0. [12.3.3.4(a)]

- B/C10.6.3.4** If wind wave data are not available (owing to confused sea or for any other reason) for direction, period or height of wind waves, as the case may be, 0 22 002, 0 22 012 or 0 22 022 shall be set to missing. [12.3.3.4(b), (d)]
- B/C10.6.3.5** Swell wave data shall be reported only when swell waves can be distinguished from wind waves. [12.3.4.1]
- B/C10.6.3.6** When the sea is calm (no waves and no swell) direction, period and height of swell waves shall be reported as 0.
- B/C10.6.3.7** If swell waves cannot be distinguished from wind waves, direction 0 22 003, period 0 22 013 and height 0 22 023 of swell waves shall be set to missing.
- B/C10.6.3.8** If only one system of swell is observed, direction, period and height of swell waves shall be reported in the first replication of <3 02 023> = <0 22 003, 0 22 013, 0 22 023>. All elements in the second replication of <3 02 023> shall be set to missing. [12.3.4.2]
- B/C10.6.3.9** If a second system of swell is observed, its direction, period and height shall be reported in the second replication of <3 02 023> = <0 22 003, 0 22 013, 0 22 023>. The corresponding data for the first system of swell shall be reported as prescribed by Regulation B/C10.6.3.8. [12.3.4.3]
- B/C10.7** **“Instantaneous” data required by regional or national reporting practices**
If regional or national reporting practices require inclusion of additional “instantaneous” parameters, the sequence descriptor 3 08 009 shall be supplemented by the required element descriptors being preceded by a relevant time period descriptor set to zero, i.e. 0 04 024 = 0 or 0 04 025 = 0.
- Notes:
- (1) “Instantaneous” parameter is a parameter that is not coupled to a time period descriptor, e.g. 0 04 024, 0 04 025.
 - (2) No regional requirements are currently indicated for reporting SHIP data from sea stations in the *Manual on Codes* (WMO-No. 306), Volume II.
- B/C10.8** **Ship “period” data <3 02 060>**
- B/C10.8.1** **Present and past weather <3 02 038>**
- B/C10.8.1.1** Present weather (Code table 0 20 003) and past weather (1) (Code table 0 20 004) and past weather (2) (Code table 0 20 005) shall be reported as non-missing values if present and past conditions are known. In case of a report from a manually operated station after a period of closure or at start up, when past weather conditions for the period applicable to the report are unknown, past weather (1) and past weather (2) reported as missing shall indicate that previous conditions are unknown. This regulation shall also apply to automatic reporting stations with the facility to report present and past weather. [12.2.6.1]
- B/C10.8.1.2** Code figures 0, 1, 2, 3, 100, 101, 102 and 103 for present weather and code figures 0, 1, 2 and 10 for past weather (1) and past weather (2) shall be considered to represent phenomena without significance. [12.2.6.2]
- B/C10.8.1.3** Present and past weather shall be *reported if observation was made (data available), regardless significance of the phenomena.*
- Note: If data are produced and collected in traditional codes and present weather and past weather is omitted in a SHIP report (no significant phenomena observed), code

figure 508 shall be used for present weather and code figure 10 for past weather (1) and past weather (2) when converted into BUFR or CREX.

B/C10.8.1.4 If no observation was made (data not available), code figure 509 shall be used for present weather and both past weather (1) and past weather (2) shall be reported as missing.

B/C10.8.1.5 Present weather from a manned weather station

B/C10.8.1.5.1 If more than one form of weather is observed, the highest applicable code figure from the range <00 to 99> shall be selected for present weather. Code figure 17 shall have precedence over code figures 20–49. Other weather may be reported using additional entries 0 20 003 or 0 20 021 to 0 20 026 applying Regulation B/C10.7. [12.2.6.4.1]

B/C10.8.1.5.2 In coding 01, 02, or 03, there is no limitation on the magnitude of the change of the cloud amount. Code figures 00, 01, and 02 can each be used when the sky is clear at the time of observation. In this case, the following interpretation of the specifications shall apply:

- 00 is used when the preceding conditions are not known;
- 01 is used when the clouds have dissolved during the past hour;
- 02 is used when the sky has been continuously clear during the past hour.

[12.2.6.4.2]

B/C10.8.1.5.3 When the phenomenon is not predominantly water droplets, the appropriate code figure shall be selected without regard to visibility. [12.2.6.4.3]

B/C10.8.1.5.4 The code figure 05 shall be used when the obstruction to vision consists predominantly of lithometeors. [12.2.6.4.4]

B/C10.8.1.5.5 National instructions shall be used to indicate the specifications for code figures 07 and 09. [12.2.6.4.5]

B/C10.8.1.5.6 The visibility restrictions on code figure 10 shall be 1 000 metres or more. The specification refers only to water droplets and ice crystals. [12.2.6.4.6]

B/C10.8.1.5.7 For code figures 11 or 12 to be reported, the apparent visibility shall be less than 1 000 metres. [12.2.6.4.7]

B/C10.8.1.5.8 For code figure 18, the following criteria for reporting squalls shall be used:

- (a) When wind speed is measured: A sudden increase of wind speed of at least eight metres per second, the speed rising to 11 metres per second or more and lasting for at least one minute;
- (b) When the Beaufort scale is used for estimating wind speed: A sudden increase of wind speed by at least three stages of the Beaufort scale, the speed rising to force 6 or more and lasting for at least one minute.

[12.2.6.4.8]

B/C10.8.1.5.9 Code figures 20–29 shall never be used when precipitation is observed at the time of observation. [12.2.6.4.9]

B/C10.8.1.5.10 For code figure 28, visibility shall have been less than 1 000 metres.

Note: The specification refers only to visibility restrictions which occurred as a result of water droplets or ice crystals.

[12.2.6.4.10]

- B/C10.8.1.5.11** For synoptic coding purposes, a thunderstorm shall be regarded as being at the station from the time thunder is first heard, whether or not lightning is seen or precipitation is occurring at the station. A thunderstorm shall be reported if thunder is heard within the normal observational period preceding the time of the report. A thunderstorm shall be regarded as having ceased at the time thunder is last heard and the cessation is confirmed if thunder is not heard for 10–15 minutes after this time. [12.2.6.4.11]
- B/C10.8.1.5.12** The necessary uniformity in reporting code figures 36, 37, 38, and 39, which may be desirable within certain regions, shall be obtained by means of national instructions. [12.2.6.4.12]
- B/C10.8.1.5.13** A visibility restriction « less than 1 000 metres » shall be applied to code figures 42–49. In the case of code figures 40 or 41, the apparent visibility in the fog or ice fog patch or bank shall be less than 1 000 metres. Code figures 40–47 shall be used when the obstructions to vision consist predominantly of water droplets or ice crystals, and 48 or 49 when the obstructions consist predominantly of water droplets. [12.2.6.4.13]
- B/C10.8.1.5.14** When referring to precipitation, the phrase « at the station » in the code table shall mean « at the point where the observation is normally taken ». [12.2.6.4.14]
- B/C10.8.1.5.15** The precipitation shall be encoded as intermittent if it has been discontinuous during the preceding hour, without presenting the character of a shower. [12.2.6.4.15]
- B/C10.8.1.5.16** The intensity of precipitation shall be determined by the intensity at the time of the observation. [12.2.6.4.16]
- B/C10.8.1.5.17** Code figures 80–90 shall be used only when the precipitation is of the shower type and takes place at the time of the observation.
- Note: Showers are produced by convective clouds. They are characterized by their abrupt beginning and end and by the generally rapid and sometimes great variations in the intensity of the precipitation. Drops and solid particles falling in a shower are generally larger than those falling in non-showery precipitation. Between showers openings may be observed unless stratiform clouds fill the intervals between the cumuliform clouds.
- [12.2.6.4.17]
- B/C10.8.1.5.18** In reporting code figure 98, the observer shall be allowed considerable latitude in determining whether precipitation is or is not occurring, if it is not actually visible. [12.2.6.4.18]
- B/C10.8.1.6 Present weather from an automatic weather station**
- B/C10.8.1.6.1** The highest applicable code figure shall be selected. [12.2.6.5.1]
- B/C10.8.1.6.2** In coding code figures 101, 102, and 103, there is no limitation on the magnitude of the change of the cloud amount. Code figures 100, 101, and 102 can each be used when the sky is clear at the time of observation. In this case, the following interpretation of the specifications shall apply:
- Code figure 100 is used when the preceding conditions are not known;
 - Code figure 101 is used when the clouds have dissolved during the past hour;
 - Code figure 102 is used when the sky has been continuously clear during the past hour.

[12.2.6.5.2]

- B/C10.8.1.6.3** When the phenomenon is not predominantly water droplets, the appropriate code figure shall be selected without regard to the visibility. [12.2.6.5.3]
- B/C10.8.1.6.4** The code figures 104 and 105 shall be used when the obstruction to vision consists predominantly of lithometeors. [12.2.6.5.4]
- B/C10.8.1.6.5** The visibility restriction on code figure 110 shall be 1 000 metres or more. The specification refers only to water droplets and ice crystals. [12.2.6.5.5]
- B/C10.8.1.6.6** For code figure 118, the following criteria for reporting squalls shall be used:
A sudden increase of wind speed of at least eight metres per second, the speed rising to 11 metres per second or more and lasting for at least one minute.
[12.2.6.5.6]
- B/C10.8.1.6.7** Code figures 120–126 shall never be used when precipitation is observed at the time of observation. [12.2.6.5.7]
- B/C10.8.1.6.8** For code figure 120, visibility shall have been less than 1 000 metres.

Note: The specification refers only to visibility restrictions, which occurred as a result of water droplets or ice crystals.
[12.2.6.5.8]
- B/C10.8.1.6.9** For synoptic coding purposes, a thunderstorm shall be regarded as being at the station from the time thunder is first detected, whether or not lightning is detected or precipitation is occurring at the station. A thunderstorm shall be reported in present weather if thunder is detected within the normal observational period preceding the time of the report. A thunderstorm shall be regarded as having ceased at the time thunder is last detected and the cessation is confirmed if thunder is not detected for 10–15 minutes after this time. [12.2.6.5.9]
- B/C10.8.1.6.10** A visibility restriction « less than 1 000 metres » shall be applied to code figures 130–135. [12.2.6.5.10]
- B/C10.8.1.6.11** The precipitation shall be encoded as intermittent if it has been discontinuous during the preceding hour, without presenting the character of a shower.
[12.2.6.5.11]
- B/C10.8.1.6.12** The intensity of precipitation shall be determined by the intensity at the time of observation. [12.2.6.5.12]
- B/C10.8.1.6.13** Code figures 180–189 shall be used only when the precipitation is intermittent or of the shower type and takes place at the time of observation.

Note: Showers are produced by convective clouds. They are characterized by their abrupt beginning and end and by the generally rapid and sometimes great variations in the intensity of the precipitation. Drops and solid particles falling in a shower are generally larger than those falling in non-showery precipitation. Between showers openings may be observed unless stratiform clouds fill the intervals between the cumuliform clouds.
[12.2.6.5.13]
- B/C10.8.1.7 Past weather reported from a manned weather station**
- B/C10.8.1.7.1 Time period**
The time period (0 04 024) covered by past weather (1) and past weather (2) shall be expressed as a *negative value* in hours:

- (a) Six hours, for observations at 0000, 0600, 1200, and 1800 UTC;
- (b) Three hours for observations at 0300, 0900, 1500, and 2100 UTC;
- (c) Two hours for intermediate observations if taken every two hours;
- (d) *One hour* for intermediate observations if taken every hour.

[12.2.6.6.1]

B/C10.8.1.7.2 The code figures for past weather (1) and past weather (2) shall be selected in such a way that past and present weather together give as complete a description as possible of the weather in the time interval concerned. For example, if the type of weather undergoes a complete change during the time interval concerned, the code figures selected for past weather (1) and past weather (2) shall describe the weather prevailing before the type of weather indicated by present weather began. [12.2.6.6.2]

B/C10.8.1.7.3 When the past weather (1) and past weather (2) are used in hourly reports, Regulation B/C10.8.1.7.1 (d) shall apply. [12.2.6.6.3]

B/C10.8.1.7.4 If, using Regulation B/C10.8.1.7.2, more than one code figure may be given to past weather (1), the highest figure shall be reported for past weather (1) and the second highest code figure shall be reported for past weather (2). [12.2.6.6.4]

B/C10.8.1.7.5 If the weather during the period has not changed so that only one code figure may be selected for past weather, then that code figure shall be reported for both past weather (1) and past weather (2). [12.2.6.6.5]

B/C10.8.1.8 Past weather reported from an automatic weather station

B/C10.8.1.8.1 Time period

The time period (0.04 024) covered by past weather (1) and past weather (2) shall be expressed as *a negative value* in hours:

- (a) Six hours for observations at 0000, 0600, 1200, and 1800 UTC;
- (b) Three hours for observations at 0300, 0900, 1500, and 2100 UTC;
- (c) Two hours for intermediate observations if taken every two hours;
- (d) *One hour* for intermediate observations if taken every hour.

[12.2.6.7.1]

B/C10.8.1.8.2 The code figures for past weather (1) and past weather (2) shall be selected so that the maximum capability of the automatic station to discern past weather is utilized, and so that past and present weather together give as complete a description as possible of the weather in the time interval concerned. [12.2.6.7.2]

B/C10.8.1.8.3 In cases where the automatic station is capable only of discerning very basic weather conditions, the lower code figures representing basic and generic phenomena may be used. If the automatic station has higher discrimination capabilities, the higher code figures representing more detailed explanation of the phenomena shall be used. For each basic type of phenomenon, the highest code figure within the discrimination capability of the automatic station shall be reported. [12.2.6.7.3]

B/C10.8.1.8.4 If the type of weather during the time interval concerned undergoes complete and discernible changes, the code figures selected for past weather (1) and past weather (2) shall describe the weather prevailing before the type of weather indicated by present weather began. The highest figure shall be reported for past

weather (1) and the second highest code figure shall be reported for past weather (2). [12.2.6.7.4]

B/C10.8.1.8.5 If a discernible change in weather has not occurred during the period, so that only one code figure may be selected for the past weather, then that code figure shall be reported for both past weather (1) and past weather (2). For example, rain during the entire period shall be reported as code figure 14 for both past weather (1) and past weather (2) in the case of an automatic station incapable of differentiating types of precipitation, or code figure 16 for both past weather (1) and past weather (2) in the case of a station with the higher discrimination capability. [12.2.6.7.5]

B/C10.8.2 Precipitation measurement <3 02 040>

B/C10.8.2.1 Height of sensor above marine deck platform

Height of sensor above marine deck platform (0 07 032) for precipitation measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the rain gauge rim above marine deck platform at the point where the rain gauge is located.

B/C10.8.2.2 Period of reference for amount precipitation

Time period (0 04 024) for amount of precipitation shall be reported as a *negative value* in hours. It shall be determined:

- (a) By regional decision (e.g. –6, –12, –24) in the first replication;
- (b) By national decision (e.g. –1, –3) in the second replication.

B/C10.8.2.3 Total amount of precipitation

Total amount of precipitation, which has fallen during the period of reference for amount of precipitation, shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre).

B/C10.8.2.3.1 Precipitation, when it can be and has to be reported, shall be reported as 0.0 kg m^{-2} if no precipitation were observed during the referenced period. [12.2.5.4]

B/C10.8.2.3.2 Trace shall be reported as “–0.1 kg m^{-2} ”.

B/C10.8.3 Ship extreme temperature data <3 02 058>

B/C10.8.3.1 Height of sensor above marine deck platform and height of sensor above water surface

Height of sensor above marine deck platform (0 07 032) for temperature measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of temperature sensors above marine deck platform at the point where the sensors are located.

Height of sensor above water surface (0 07 033) for temperature measurement shall be reported in metres (with precision in tenths of a metre).

This datum represents the actual height of temperature sensors above marine water surface of sea or lake.

B/C10.8.3.2 Periods of reference for extreme temperatures

Time period for maximum temperature and time period for minimum temperature (0 04 024) shall be determined by regional decision and reported as *negative values* in hours. [12.4.4]

Notes:

- (1) If the period for maximum temperature or the period for minimum temperature ends at the nominal time of report, the second value of 0 04 024 shall be reported as 0.
- (2) If the period for maximum temperature or the period for minimum temperature does not end at the nominal time of report, the first value of 0 04 024 shall indicate the beginning of the period of reference and the second value of 0 04 024 shall indicate the end of the period of reference. E.g. to report the maximum temperature for the previous calendar day from a station in RA IV, value of the first 0 04 024 shall be set to –30 and value of the second 0 04 024 shall be set to –6, provided that the nominal time of the report 12 UTC corresponds to 6 a.m. local time.

B/C10.8.3.3 Maximum and minimum temperature

Maximum and minimum temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C10.4.1.2 shall apply.

B/C10.8.4 Ship wind data <3 02 059>**B/C10.8.4.1 Height of sensor above marine deck platform and height of sensor above water surface**

Height of sensor above marine deck platform (0 07 032) for wind measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of wind sensors above marine deck platform at the point where the sensors are located.

Height of sensor above water surface (0 07 033) for wind measurement shall be reported in metres (with precision in tenths of a metre).

This datum represents the actual height of wind sensors above marine water surface of sea or lake.

B/C10.8.4.2 Type of instrumentation for wind measurement – Flag table 0 02 002

This datum shall be used to specify whether the wind speed was measured by certified instruments (bit No. 1 set to 1) or estimated on the basis of the Beaufort wind scale (bit No. 1 set to 0), and to indicate the original units for wind speed measurement. Bit No. 2 set to 1 indicates that wind speed was originally measured in knots and bit No. 3 set to 1 indicates that wind speed was originally measured in kilometres per hour. Setting both bits No. 2 and No. 3 to 0 indicates that wind speed was originally measured in metres per second.

B/C10.8.4.3 Wind direction and speed

The mean direction and speed of the wind over the 10-minute period immediately preceding the observation shall be reported. The time period (0 04 025) shall be included as –10. However, when the 10-minute period includes a discontinuity in the wind characteristics, only data obtained after the discontinuity shall be used for reporting the mean values, and hence the period (0 04 025) in these circumstances shall be correspondingly reduced. [12.2.2.3.1]

The time period is preceded by a time significance qualifier (0 08 021) that shall be set to 2 (Time averaged).

The wind direction (0 11 001) shall be reported in degrees true and the wind speed (0 11 002) shall be reported in metres per second (with precision in tenths of a metre per second).

Note: Surface wind direction measured at a station within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian.

B/C10.8.4.3.1 In the absence of wind instruments, the wind speed shall be estimated on the basis of the Beaufort wind scale. The Beaufort number obtained by estimation is converted into metres per second by use of the relevant wind speed equivalent column on the Beaufort scale, and this speed is reported for wind speed. [12.2.2.3.2]

B/C10.8.4.3.2 Calm shall be reported by setting wind direction to 0 and wind speed to 0. Variable shall be reported by setting wind direction to 0 and wind speed to a positive *non-missing* value.

B/C10.8.4.4 **Maximum wind gust direction and speed**
Time period for maximum wind gust direction and speed (0 04 025) shall be determined by regional or national decision and reported as a negative value in minutes.
Direction of the maximum wind gust (0 11 043) shall be reported in degrees true and speed of the maximum wind gust (0 11 041) shall be reported in metres per second (with precision in tenths of a metre per second).

B/C10.9 **“Period” data required by regional or national reporting practices**
If regional reporting practices in a Region require inclusion of additional “period” parameters, the corresponding “regional” common sequence (see the annex to B/C1) shall be supplemented by relevant descriptors. If national reporting practices require inclusion of additional “period” parameters, the common sequence 3 08 009 shall be supplemented by relevant descriptors.

Notes:

- (1) “Period” parameter is a parameter that is coupled to a time period descriptor, e.g. 0 04 024, 0 04 025.
- (2) No additional “period” parameters are currently required by regional regulations for SHIP data in the *Manual on Codes* (WMO-No. 306), Volume II.

Provisional Copy
2023

B/C20 – Regulations for reporting PILOT, PILOT SHIP and PILOT MOBIL data in TDCF

General

A BUFR (or CREX) message should be sent when the 100-hPa level is reached. In any case, a BUFR (or CREX) message shall be produced when the sounding is completed containing data from the entire sounding.

BUFR templates for wind vertical profiles suitable for PILOT, PILOT SHIP and PILOT MOBIL observation data:

TM 309050 – BUFR template for wind vertical profiles with pressure as the vertical coordinate

		Sequence for representation of PILOT, PILOT SHIP and PILOT MOBIL observation type data with pressure as the vertical coordinate
3 09 050	3 01 110	Identification of launch site and instrumentation for wind measurements
	3 01 113	Date/time of launch
	3 01 114	Horizontal and vertical coordinates of launch site
	1 01 000	Delayed replication of 1 descriptor
	0 31 002	Extended delayed descriptor replication factor
	3 03 050	Wind data at a pressure level with radiosonde position
	1 01 000	Delayed replication of 1 descriptor
	0 31 001	Delayed descriptor replication factor
	3 03 051	Wind shear data at a pressure level with radiosonde position

TM 309051 – BUFR template for wind vertical profiles with height as the vertical coordinate

		Sequence for representation of PILOT, PILOT SHIP and PILOT MOBIL observation type data with height as the vertical coordinate
3 09 051	3 01 110	Identification of launch site and instrumentation for wind measurements
	3 01 113	Date/time of launch
	3 01 114	Horizontal and vertical coordinates of launch site
	1 01 000	Delayed replication of 1 descriptor
	0 31 002	Extended delayed descriptor replication factor
	3 03 052	Wind data at a height level with radiosonde position
	1 01 000	Delayed replication of 1 descriptor
	0 31 001	Delayed descriptor replication factor
	3 03 053	Wind shear data at a height level with radiosonde position

BUFR template TM 309050 for wind vertical profiles (*with pressure as the vertical coordinate*) is further expanded as follows:

			Unit, scale
		Identification of launch site and instrumentation for wind measurements	
3 01 110	3 01 001	WMO block and station numbers	Numeric
	0 01 011	Ship or mobile land station identifier	CCITT IA5
	0 02 011	Radiosonde type	Code table

			Unit, scale
	0 02 014	Tracking technique/status of system used	Code table
	0 02 003	Type of measuring equipment used	Code table
		Date/time of launch	
3 01 113	0 08 021	Time significance (= 18 Launch time)	Code table
	3 01 011	Year	Year
		Month	Month
		Day	Day
	3 01 013	Hour	Hour
		Minute	Minute
		Second	Second
		Horizontal and vertical coordinates of launch site	
3 01 114	3 01 021	Latitude/longitude (high accuracy)	Degree, 5
	0 07 030	Height of station ground above mean sea level	m, 1
	0 07 031	Height of barometer above mean sea level	m, 1
	0 07 007	Height (of release of sonde above mean sea level)	m
	0 33 024	Station elevation quality mark (for mobile stations)	Code table
		Wind data at pressure levels	
1 01 000		Delayed replication of 1 descriptor	
0 31 002		Extended delayed descriptor replication factor	Numeric
		<i>Wind data at a pressure level with radiosonde position</i>	
3 03 050	0 04 086	Long time period or displacement (since launch time)	Second
	0 08 042	Extended vertical sounding significance	Flag table
	0 07 004	Pressure	Pa, -1
	0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
	0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
	0 11 001	Wind direction	Degree true
	0 11 002	Wind speed	m s ⁻¹ , 1
		Wind shear data	
1 01 000		Delayed replication of 1 descriptor	
0 31 001		Delayed descriptor replication factor	Numeric
		<i>Wind shear data at a pressure level with radiosonde position</i>	
3 03 051	0 04 086	Long time period or displacement (since launch time)	Second
	0 08 042	Extended vertical sounding significance	Flag table
	0 07 004	Pressure	Pa, -1
	0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
	0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
	0 11 061	Absolute wind shear in 1 km layer below	m s ⁻¹ , 1
	0 11 062	Absolute wind shear in 1 km layer above	m s ⁻¹ , 1

Notes:

- (1) Time of launch 3 01 013 shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry for seconds shall be put to zero.
- (2) Long time displacement 0 04 086 represents the time offset from the launch time 3 01 013 (in seconds).
- (3) Latitude displacement 0 05 015 represents the latitude offset from the latitude of the launch site. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site.

- (4) If maximum wind data and/or wind shear data are reported with height as the vertical coordinate in Parts A or C of Pilot report, while the whole vertical wind profile is reported with pressure as the vertical coordinate, the data may be converted into BUFR using sequence 3 09 050 because the maximum wind data are as significant levels also included in Parts B or D (being identified by pressure as the vertical coordinate), provided that Part B and D are available when the entire wind profile is produced in BUFR or CREX.

BUFR template TM 309051 for wind vertical profiles (*with height as the vertical coordinate*) is further expanded as follows:

			Unit, scale
		Identification of launch site and instrumentation for wind measurements	
3 01 110	3 01 001	WMO block and station numbers	Numeric
	0 01 011	Ship or mobile land station identifier	CCITT IA5
	0 02 011	Radiosonde type	Code table
	0 02 014	Tracking technique/status of system used	Code table
	0 02 003	Type of measuring equipment used	Code table
		Date/time of launch	
3 01 113	0 08 021	Time significance (= 18 Launch time)	Code table
	3 01 011	Year	Year
		Month	Month
		Day	Day
	3 01 013	Hour	Hour
		Minute	Minute
		Second	Second
		Horizontal and vertical coordinates of launch site	
3 01 114	3 01 021	Latitude/longitude (high accuracy)	Degree, 5
	0 07 030	Height of station ground above mean sea level	m, 1
	0 07 031	Height of barometer above mean sea level	m, 1
	0 07 007	Height (of release of sonde above mean sea level)	m
	0 33 024	Station elevation quality mark (for mobile stations)	Code table
		Wind data at heights	
1 01 000		Delayed replication of 1 descriptor	
0 31 002		Extended delayed descriptor replication factor	Numeric
		<i>Wind data at a height level with radiosonde position</i>	
3 03 052	0 04 086	Long time period or displacement (since launch time)	Second
	0 08 042	Extended vertical sounding significance	Flag table
	0 07 009	Geopotential height	gpm
	0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
	0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
	0 11 001	Wind direction	Degree true
	0 11 002	Wind speed	m s ⁻¹ , 1
		Wind shear data at a height level with radiosonde position	
1 01 000		Delayed replication of 1 descriptor	
0 31 001		Delayed descriptor replication factor	Numeric
		<i>Wind shear data at a height level with radiosonde position</i>	
3 03 053	0 04 086	Long time period or displacement (since launch time)	Second
	0 08 042	Extended vertical sounding significance	Flag table
	0 07 009	Geopotential height	gpm

			Unit, scale
	0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
	0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
	0 11 061	Absolute wind shear in 1 km layer below	m s^{-1} , 1
	0 11 062	Absolute wind shear in 1 km layer above	m s^{-1} , 1

Notes:

- (1) Time of launch 3 01 013 shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry for seconds shall be put to zero.
- (2) Long time displacement 0 04 086 represents the time offset from the launch time 3 01 013 (in seconds).
- (3) Latitude displacement 0 05 015 represents the latitude offset from the latitude of the launch site. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site.

Provisional Copy
2023

Regulations:

B/C20.1	Section 1 of BUFR or CREX
B/C20.2	Identification of launch site and instrumentation for wind measurement
B/C20.3	Date/time of launch
B/C20.4	Horizontal and vertical coordinates of launch site
B/C20.5	Wind data at pressure levels
B/C20.6	Wind data at height levels
B/C20.7	Criteria for reporting standard and significant levels
B/C20.8	Wind shear data at pressure levels
B/C20.9	Wind shear data at heights
B/C20.10	Data required by regional or national reporting practices

B/C20.1 Section 1 of BUFR or CREX

B/C20.1.1 Entries required in Section 1 of BUFR

The following entries shall be included in BUFR Section 1:

- BUFR master table;
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Identification of inclusion of optional section;
- Data category (002 for all PILOT type data);
- International data sub-category (see Note 1);
- Local data sub-category;
- Version number of master table;
- Version number of local tables;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for all PILOT type data);
- Hour (GG in the abbreviated telecommunication header, e.g. = 00, 06, 12 or 18 for all PILOT type data);
- Minute (00 for all PILOT type data);
- Second (00).

Notes:

- (1) If required, the international data sub-category shall be included at all observation times as follows:
 - = 001 for PILOT data;
 - = 002 for PILOT SHIP data;
 - = 003 for PILOT MOBIL data.
- (2) If an NMHS performs conversion of PILOT, PILOT SHIP or PILOT MOBIL data produced by another NMHS, originating centre in Section 1 shall indicate the converting centre and originating sub-centre shall indicate the producer of PILOT, PILOT SHIP or PILOT MOBIL bulletins. The producer of PILOT, PILOT SHIP or PILOT MOBIL bulletins shall be specified in Common Code table C-12 as a sub-centre of the originating centre, i.e. of the NMHS executing the conversion.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C20.1.2 Entries required in Section 1 of CREX

The following entries shall be included in CREX Section 1:

- CREX master table;

- CREX edition number;
- CREX table version number;
- Version number of BUFR master table;
- Version number of local tables;
- Data category (002 for all PILOT type data);
- International data sub-category (see Note 1);
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Number of subsets;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for all PILOT type data);
- Hour (GG in the abbreviated telecommunication header, e.g. = 00, 06, 12 or 18 for all PILOT type data);
- Minute (00 for all PILOT type data).

Notes:

- (1) If inclusion of the international data sub-category is required, Note 1 under Regulation B/C20.1.1 applies.
- (2) If an NMHS performs conversion of PILOT, PILOT SHIP or PILOT MOBIL data produced by another NMHS, Note 2 under Regulation B/C20.1.1 applies.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C20.2 Identification of launch site and instrumentation for wind measurement <3 01 110>

B/C20.2.1 Identification of launch site

WMO block number (0 01 001) and WMO station number (0 01 002) shall be always reported as a non-missing value in reports from a fixed land station. WMO block and station number may be included in reports from a fixed sea station if available.

Ship or mobile land station identifier (0 01 011) shall be always reported not exceeding 9 characters in reports from ships or mobile stations. Ship or mobile station identifier 0 01 011 shall be always set to a missing value in reports from a fixed land station. [32.2.1]

B/C20.2.2 Instrumentation for wind measurement

Radiosonde type (Code table 0 02 011), tracking techniques/status of system used (Code table 0 02 014) and type of measuring equipment used (Code table 0 02 003) shall be reported.

B/C20.3 Date/time of launch <3 01 113>

Time significance (0 08 021) shall be always set to 18 to indicate that the following entries specify the date and time of launching the radiosonde.

Date of launch <3 01 011> and time of launch <3 01 013> shall be reported, i.e. year (0 04 001), month (0 04 002), day (0 04 003) and hour (0 04 004), minute (0 04 005) and second (0 04 006) of the actual time of launch shall be reported.

Note: Time of launch <3 01 013> shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry 0 04 006 for seconds shall be set to zero.

B/C20.4 Horizontal and vertical coordinates of launch site <3 01 114>

Latitude (0 05 001) and longitude (0 06 001) of the launch site shall be reported in degrees with precision in 10^{-5} of a degree.

Height of station ground above mean sea level (0 07 030) and height of barometer above mean sea level (0 07 031) shall be reported in metres with precision in tenths of a metre.

Height of release of sonde above mean sea level (0 07 007) shall be reported in metres.

Station elevation quality mark (Code table 0 33 024) shall be reported to indicate the accuracy of the vertical coordinates of the mobile land station. Fixed land stations and sea stations shall report this datum as a missing value. [32.2.1]

Note: The official altitude of the aerodrome (HA in Volume A) shall not be used to report Height of station ground above mean sea level 0 07 030 in BUFR or CREX messages from aerodromes. Those are two different vertical coordinates. "Height of station ground above mean sea level" for each station should be made available to the encoding centre concerned, which may be a centre within the same NMHS or other NMC/RTH.

B/C20.5 Wind data at pressure levels

Wind data at pressure levels shall be always reported using *template TM 309050* and shall be included in descending order with respect to pressure. Data at each pressure level shall be included only once. For example, if a significant level with respect to wind and a standard level coincide, data for that level shall be included only once, the multiple attributes being indicated by Extended vertical sounding significance (Flag table 0 08 042) as specified in Regulation B/C20.5.2.2.

Note: If data are produced and collected in traditional PILOT codes, the order of pressure levels may correspond to the order of levels in Parts A, B, C and D, when converted into BUFR or CREX. In this case, data at a level may be included more than once.

B/C20.5.1 Number of reported pressure levels

The number of reported pressure levels shall be indicated by Extended delayed descriptor replication factor 0 31 002 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of pressure levels shall never be set to a missing value.
- (2) The number of pressure levels shall be set to a positive value in a NIL report.
- (3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

B/C20.5.1.1 All required data from the entire ascent shall be reported in a BUFR (or CREX) message that shall be produced when the sounding is completed. In interest of timely data delivery, however, a BUFR (or CREX) message should be sent when level 100 hPa is reached.

B/C20.5.2 Wind data at a pressure level with radiosonde position <3 03 050>**B/C20.5.2.1 Long time displacement (since launch time)**

Long time displacement (0 04 086) represents the time offset from the launch time specified in Regulation B/C20.3, and shall be reported in seconds if available.

B/C20.5.2.2 Extended vertical sounding significance – Flag table 0 08 042

This datum shall be used to specify vertical sounding significance in the following way:

- (a) Bit No. 1 set to 1 indicates surface (see Regulation B/C20.7.1);
- (b) Bit No. 2 set to 1 indicates a standard level (see Regulation B/C20.7.2);
- (c) Bit No. 4 set to 1 indicates a maximum wind level (see Regulation B/C20.7.3);
- (d) Bit No. 7 set to 1 indicates a level significant with respect to wind (see Regulation B/C20.7.4);
- (e) Bit No. 12 set to 1 indicates beginning of missing wind data bit No. 13 set to 1 indicates end of missing wind data (see Regulation B/C20.7.5);
- (f) Bit No. 14 set to 1 indicates the top of wind sounding;
- (g) Bit No. 15 set to 1 indicates a level determined by regional decision;
- (h) Bit No. 17 set to 1 indicates a pressure level originally identified by height as the vertical coordinate;
- (i) All bits set to 0 indicate a level determined by national decision;
- (j) All bits set to 1 indicate a missing value.

B/C20.5.2.3 Pressure

Pressure (0 07 004) shall be reported in pascals (with precision in tens of pascals).

Notes:

- (1) Pressure as the vertical coordinate shall be used when template TM 309050 is applied.
- (2) Pressure as the only vertical coordinate shall be used in a report. [32.3.1.4]

B/C20.5.2.4 Latitude and longitude displacements

Latitude displacement (0 05 015) represents the latitude offset from the latitude of the launch site specified in Regulation B/C20.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site specified in Regulation B/C20.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available.

B/C20.5.2.5 Wind direction and speed

The wind direction (0 11 001) shall be reported in degrees true and the wind speed (0 11 002) shall be reported in metres per second (with precision in tenths of a metre per second).

Note: Wind direction measured at a station within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian.

B/C20.6 Wind data at height levels

Wind data at height levels shall be always reported using *template TM 309051* and shall be included in ascending order with respect to altitude. Data at each height level shall be included only once. For example, if a significant level with respect to wind and a standard level coincide, data for that level shall be included only once, the multiple attributes being indicated by Extended vertical sounding significance (Flag table 0 08 042) as specified in Regulation B/C20.5.2.2.

Note: If data are produced and collected in traditional PILOT codes, the order of height levels may correspond to the order of levels in Parts A, B, C and D, when converted into BUFR or CREX. In this case, data at a level may be included more than once.

B/C20.6.1 Number of reported height levels

The number of reported height levels shall be indicated by Extended delayed descriptor replication factor 0 31 002 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of height levels shall never be set to a missing value.
- (2) The number of height levels shall be set to a positive value in a NIL report.
- (3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

B/C20.6.1.1 Regulation B/C20.5.1.1 shall apply.

B/C20.6.2 Wind data at a height level with radiosonde position <3 03 052>**B/C20.6.2.1 Long time displacement (since launch time)**

Long time displacement (0 04 086) represents the time offset from the launch time specified in Regulation B/C20.3, and shall be reported in seconds if available.

B/C20.6.2.2 Extended vertical sounding significance – Flag table 0 08 042

Regulation B/C20.5.2.2 shall apply.

B/C20.6.2.3 Geopotential height

Geopotential height of the level (0 07 009) shall be reported in geopotential metres.

Notes:

- (1) Geopotential height as the vertical coordinate shall be used when template TM 309051 is applied.
- (2) Geopotential height as the only vertical coordinate shall be used in a report. [32.3.1.4]

B/C20.6.2.4 Latitude and longitude displacements

Regulation B/C20.5.2.4 shall apply.

B/C20.6.2.5 Wind direction and speed

Regulation B/C20.5.2.5 shall apply.

B/C20.7 Criteria for reporting standard and significant levels**B/C20.7.1 Surface**

The surface level shall be always reported.

Note: The value of Extended vertical sounding significance 0 08 042 at the surface level shall indicate that this level is also a level significant with respect to wind, i.e. bit No. 1 and also bit No. 7 shall be set to 1.

B/C20.7.2 Standard levels

B/C20.7.2.1 The standard levels of 850, 700, 500, 400, 300, 250, 200, 150, 100, 70, 50, 30, 20 and 10 hPa shall be reported in descending order with respect to pressure (in ascending order with respect to altitude). [32.2.2.1]

B/C20.7.2.2 When pressure measurements are not available, wind data shall be reported using geopotential approximations to the standard isobaric surfaces. [32.2.2.2]

B/C20.7.2.3 When wind data at a standard level are not available, the corresponding entries for that level shall be reported as missing values. [32.2.2.3]

B/C20.7.2.4 When the standard levels are located by means of pressure equipment and if the pressure element failed during the ascent, the remaining standard levels to be reported shall be indicated by 0 08 042 – bit No. 2 set to 1 (standard level) and by bit No. 17 set to 1 (a pressure level originally identified by height as the vertical coordinate). [32.2.2.4]

B/C20.7.3 Maximum wind level(s)

B/C20.7.3.1 When a maximum wind level (one or more) is reported, the corresponding number of levels shall be included in the report indicated by 0 08 042 – bit No. 4 set to 1. [32.2.3.3]

Notes:

(1) Criteria for determining maximum wind levels are given in Regulations B/C20.7.3.3 and B/C20.7.3.4 below.

(2) As a maximum wind level is also a level significant with respect to wind, bit No. 7 as well as bit No. 4 shall be set to 1 in the Extended vertical sounding significance 0 08 042.

B/C20.7.3.2 When no maximum wind level is observed, no level shall be indicated by bit No. 4 of 0 08 042 set to 1. [32.2.3.4.5]

B/C20.7.3.3 A maximum wind level:

- (a) Shall be determined by consideration of the list of significant levels for wind speed, as obtained by means of the relevant recommended or equivalent national method (see Note under Regulation B/C20.7.4.2) and *not* by consideration of the original wind-speed curve;
- (b) Shall be located above the 500-hPa isobaric surface and shall correspond to a speed of more than 30 metres per second.

Note: A maximum wind level is defined as a level at which the wind speed is greater than that observed immediately above and below that level.

[32.2.3.1]

- B/C20.7.3.4** Whenever more than one maximum wind level exists, these levels shall be reported as follows:
- (a) The level of greatest maximum wind speed shall be always included;
 - (b) The other levels shall be included in the report only if their speed exceeds those of the two adjacent minima by at least 10 metres per second;
 - (c) Furthermore, the highest level attained by the sounding shall be indicated as a maximum wind level, provided:
 - (i) It satisfies the criteria set forth in Regulation B/C20.7.3.3 above;
 - (ii) It constitutes the level of the greatest speed of the whole sounding.
- [32.2.3.2]

- B/C20.7.3.5** When the greatest wind speed observed throughout the sounding occurred at the top of the sounding, this level shall be indicated by 0 08 042 – bit No. 4 set to 1 (maximum wind level), bit No. 7 set to 1 (level significant with respect to wind) and bit No. 14 set to 1 (top of wind sounding). [32.2.3.4.3], [32.2.3.4.4]

- B/C20.7.3.6** In compliance with Regulation B/C20.5.2.3 or B/C20.6.2.3, maximum wind level data shall be reported with the same vertical coordinate as the other data in the profile, using template TM 309050 or template TM 309051 for the entire sounding.

Note: If data are produced and collected in traditional PILOT codes, maximum wind data may be reported with height as the vertical coordinate in Parts A or C of Pilot report, while the whole vertical wind profile is reported with pressure as the vertical coordinate. Even in this case, the maximum wind data may be converted into BUFR using sequence 3 09 050 because the maximum wind data were selected from the list of significant levels with respect to wind. And these significant levels are included in Parts B or D of Pilot report, identified by pressure as the vertical coordinate. [32.3.1.4]

B/C20.7.4 Levels significant with respect to wind

- B/C20.7.4.1** Significant wind levels shall be chosen so that the data from them *alone* shall make it possible to reconstruct the wind profile with sufficient accuracy for practical use. [32.3.1.1]

- B/C20.7.4.2** Criteria for determining significant levels with respect to changes in wind speed and direction:
- (a) The direction and speed curves (in function of the log of pressure or altitude) can be reproduced with their prominent characteristics;
 - (b) These curves can be reproduced with the accuracy of at least 10 degrees true for direction and five metres per second for speed.

Note: To satisfy these criteria, the following method of successive approximations is recommended, but other methods of attaining equivalent results may suit some national practices better and may be used:

- (i) The surface level and highest level for which wind data are available constitute the first and the last significant levels. The deviation from the linearly interpolated values between these two levels is then considered. If no direction deviates by more than 10 degrees true and no speed by more than five metres per second, no other significant level need be reported. Whenever one parameter deviates by more than the limit specified in paragraph (b) above the level of greatest deviation becomes a supplementary significant level for both parameters.
- (ii) The additional significant levels so introduced divide the sounding into two layers. In each separate layer, the deviation from the linearly interpolated values between the base and the top are then considered. The process used in paragraph (i) above is repeated and yields other significant levels. These additional levels in turn modify the layer distribution, and the method is applied again until any level is approximated to the above-mentioned specified values.

B/C20.7.5 Beginning and end of missing wind data

B/C20.7.5.1 If wind profile data are reported with pressure as the vertical coordinate, a layer for which wind data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 50 hPa thick. The boundary levels are the levels closest to the bottom and the top of the layer for which the observed data are available. The boundary levels are not required to meet “significant wind level” criteria. [32.3.1.5.2]

B/C20.7.5.2 If wind profile data are reported with height as the vertical coordinate, a layer for which wind data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 1 500 geopotential metres thick. The boundary levels are the levels closest to the bottom and the top of the layer for which the observed data are available. The boundary levels are not required to meet “significant wind level” criteria. [32.3.1.5.1]

B/C20.8 Wind shear data at pressure levels**B/C20.8.1 Number and order of levels for which wind shear is reported**

B/C20.8.1.1 The number of levels with wind shear data shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of levels with wind shear data shall never be set to a missing value.
- (2) The number of levels with wind shear data shall be set to a positive value in a NIL report.
- (3) The number of levels with wind shear data shall be set to zero if data for vertical wind shear are not computed and required. [32.2.3.5]
- (4) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

B/C20.8.1.2 Whenever wind shear data are reported for more than one level, these maximum wind levels shall be included in the same order as in the sequence <3 03 050>, i.e. in descending order with respect to pressure.

B/C20.8.2 Wind shear data at a pressure level with radiosonde position <3 03 051>**B/C20.8.2.1 Long time displacement (since launch time)**

Long time displacement (0 04 086) represents the time offset from the launch time specified in Regulation B/C20.3, and shall be reported in seconds if available.

B/C20.8.2.2 Extended vertical sounding significance – Flag table 0 08 042

A level, for which wind shear data are reported, shall be indicated by vertical sounding significance 0 08 042 – bit No. 4 set to 1 (maximum wind level) and by bit No. 7 set to 1 (level significant with respect to wind). Moreover, if the top of the wind sounding corresponds to the highest wind speed observed throughout the ascent, this level shall be indicated also by bit No. 14 set to 1 (top of wind sounding).

B/C20.8.2.3 Pressure

Pressure (0 07 004) shall be reported in pascals with precision in tens of pascals.

B/C20.8.2.4 Latitude and longitude displacements

Latitude displacement (0 05 015) represents the latitude offset from the latitude of the launch site specified in Regulation B/C20.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site specified in Regulation B/C20.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available.

B/C20.8.2.5 Wind shear data

Absolute wind shear in 1 km layer below (0 11 061) and absolute wind shear in 1-km layer above (0 11 062) shall be reported in metres per second (with precision in tenths of a metre per second), if data for vertical wind shear are computed and required. [32.2.3.5]

B/C20.9 Wind shear data at heights**B/C20.9.1 Number and order of levels for which wind shear is reported**

B/C20.9.1.1 Regulation B/C20.8.1.1 shall apply.

B/C20.9.1.2 Whenever wind shear data are reported for more than one level, these maximum wind levels shall be included in the same order as in the sequence <3 03 052>, i.e. in ascending order with respect to altitude.

B/C20.9.2 Wind shear data at a height level with radiosonde position <3 03 053>**B/C20.9.2.1 Long time displacement (since launch time)**

Long time displacement (0 04 086) represents the time offset from the launch time specified in Regulation B/C20.3, and shall be reported in seconds if available.

B/C20.9.2.2 Extended vertical sounding significance – Flag table 0 08 042

Regulation B/C20.8.2.2 shall apply.

B/C20.9.2.3 Geopotential height

Geopotential height of the level (0 07 009) shall be reported in geopotential metres.

B/C20.9.2.4 Latitude and longitude displacements

Regulation B/C20.8.2.4 shall apply.

B/C20.9.2.5 Wind shear data

Regulation B/C20.8.2.5 shall apply.

B/C20.10 Data required by regional or national reporting practices

If regional or national reporting practices require inclusion of wind data at additional levels, these data shall be reported using sequence <3 03 050> for wind data at a pressure level or sequence <3 03 052> for wind data at a height level. Regulation B/C20.5 or Regulation B/C20.6 shall apply.

Notes:

- (1) A level determined by regional decision shall be indicated by Extended vertical sounding significance 0 08 042 – bit No. 15 set to 1.
- (2) A level determined by national decision shall be indicated by Extended vertical sounding significance 0 08 042 – all bits set to 0.

B/C20.10.1 Additional data required by reporting practices in RA I

Wind data at additional levels 600, 900, 2 100, 3 900, 4 500, 5 100, 21 000 m, and all successive levels at 3 000 m intervals, shall be reported in compliance with Regulation B/C20.10 and Note 1 under this regulation. [1/32.2], [1/32.4.1]

B/C20.10.2 Additional data required by reporting practices in RA II

B/C20.10.2.1 Wind data at additional levels 300, 600, 900, 2 100, 3 600, 4 500, 6 000 m shall be reported in compliance with Regulation B/C20.10 and Note 1 under this regulation. [2/32.3]

B/C20.10.2.2 The inclusion of wind shear data shall be left to national decision. Members are recommended to include these data as often as possible. [2/32.2]

B/C20.10.3 Additional data required by reporting practices in RA III

Wind data at additional levels 300, 600, 900, 2 100, 2 400, 4 200, 6 000, 8 100, 33 000 m, and all successive levels at 3 000 m intervals, shall be reported in compliance with Regulation B/C20.10 and Note 1 under this regulation. [3/32.2], [3/32.4.1]

B/C20.10.4 Additional data required by reporting practices in RA IV

Wind data at additional levels 300, 600, 900, 1 200, 1 800, 2 100, 2 400, 2 700, 3 600, 4 200, 4 800, 6 000, 7 500, 9 000, 15 000 m, and all successive levels at 3 000 m intervals, shall be reported in compliance with Regulation B/C20.10 and Note 1 under this regulation. [4/32.2], [4/32.4.1]

B/C20.10.5 Additional data required by reporting practices in RA V

Wind data at additional levels 900, 2 100, 4 200 m shall be reported in compliance with Regulation B/C20.10 and Note 1 under this regulation. [5/32.3]

B/C20.10.6 Additional data required by reporting practices in RA VI

B/C20.10.6.1 Wind data at additional levels 900, 800, 600 hPa (with pressure as the vertical coordinate) and at levels 1 000, 2 000, 4 000 m or 900, 2 100, 4 200 m (with height as the vertical coordinate), shall be reported in compliance with Regulation B/C20.10 and Note 1 under this regulation. [6/32.3.1]

B/C20.10.6.2 The inclusion of wind shear data shall be left to national decision. Members are recommended to include these data as often as possible. [6/32.2], [6/32.5]

B/C25 – Regulations for reporting TEMP, TEMP SHIP and TEMP MOBIL data in TDCF

General

A BUFR (or CREX) message shall be sent when the 100-hPa level is reached. Subsequently, a BUFR (or CREX) message shall be produced when the sounding is completed containing data from the entire sounding. If the sounding is terminated below 100-hPa level, only the later message shall be produced.

If high-resolution data are reported, only one BUFR message shall be sent when the 100-hPa level is reached and only one BUFR message shall be produced when the sounding is completed, provided that all standard and significant levels are properly identified in compliance with the relevant B/C25 Regulations.

TM 309052 – BUFR template for P, T, U and wind vertical profiles suitable for TEMP, TEMP SHIP and TEMP MOBIL observation data

		Sequence for representation of TEMP, TEMP SHIP and TEMP MOBIL observation type data
3 09 052	3 01 111	Identification of launch site and instrumentation for P, T, U and wind measurements
	3 01 113	Date/time of launch
	3 01 114	Horizontal and vertical coordinates of launch site
	3 02 049	Cloud information reported with vertical soundings
	0 22 043	Sea/water temperature
	1 01 000	Delayed replication of 1 descriptor
	0 31 002	Extended delayed descriptor replication factor
	3 03 054	Temperature, dewpoint and wind data at a pressure level with radiosonde position
	1 01 000	Delayed replication of 1 descriptor
	0 31 001	Delayed descriptor replication factor
	3 03 051	Wind shear data at a pressure level with radiosonde position

This BUFR template for P, T, U and wind profiles further expands as follows:

		Identification of launch site and instrumentation for P, T, U and wind measurements	Unit, scale
3 01 111	3 01 001	WMO block and station numbers	Numeric
	0 01 011	Ship or mobile land station identifier	CCITT IA5
	0 02 011	Radiosonde type	Code table
	0 02 013	Solar and infrared radiation correction	Code table
	0 02 014	Tracking technique/status of system used	Code table
	0 02 003	Type of measuring equipment used	Code table
		Date/time of launch	
3 01 113	0 08 021	Time significance (= 18 Launch time)	Code table
	3 01 011	Year	Year
		Month	Month
		Day	Day
	3 01 013	Hour	Hour
		Minute	Minute
		Second	Second

			Unit, scale
		Horizontal and vertical coordinates of launch site	
3 01 114	3 01 021	Latitude/longitude (high accuracy)	Degree, 5
	0 07 030	Height of station ground above mean sea level	m, 1
	0 07 031	Height of barometer above mean sea level	m, 1
	0 07 007	Height (of release of sonde above mean sea level)	m
	0 33 024	Station elevation quality mark (for mobile stations)	Code table
		Cloud information reported with vertical soundings	
3 02 049	0 08 002	Vertical significance (surface observations)	Code table
	0 20 011	Cloud amount (of low or middle clouds N_h)	Code table
	0 20 013	Height of base of cloud (h)	m, -1
	0 20 012	Cloud type (low clouds C_L)	Code table
	0 20 012	Cloud type (middle clouds C_M)	Code table
	0 20 012	Cloud type (high clouds C_H)	Code table
	0 08 002	Vertical significance (surface observations) (= missing value)	Code table
0 22 043		Sea/water temperature (for ship stations)	K, 2
		Temperature, dewpoint and wind data at pressure levels	
1 01 000		Delayed replication of 1 descriptor	
0 31 002		Extended delayed descriptor replication factor	Numeric
		<i>Temperature, dewpoint and wind data at a pressure level with radiosonde position</i>	
3 03 054	0 04 086	Long time period or displacement (since launch time)	Second
	0 08 042	Extended vertical sounding significance	Flag table
	0 07 004	Pressure	Pa, -1
	0 10 009	Geopotential height	gpm
	0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
	0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
	0 12 101	Temperature/air temperature	K, 2
	0 12 103	Dewpoint temperature	K, 2
	0 11 001	Wind direction	Degree true
	0 11 002	Wind speed	$m\ s^{-1}$, 1
		Wind shear data	
1 01 000		Delayed replication of 1 descriptor	
0 31 001		Delayed descriptor replication factor	Numeric
		<i>Wind shear data at a pressure level with radiosonde position</i>	
3 03 051	0 04 086	Long time period or displacement (since launch time)	Second
	0 08 042	Extended vertical sounding significance	Flag table
	0 07 004	Pressure	Pa, -1
	0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
	0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
	0 11 061	Absolute wind shear in 1 km layer below	$m\ s^{-1}$, 1
	0 11 062	Absolute wind shear in 1 km layer above	$m\ s^{-1}$, 1

Notes:

- (1) Time of launch 3 01 013 shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry for seconds shall be put to zero.
- (2) Long time displacement 0 04 086 represents the time offset from the launch time 3 01 013 (in seconds).

- (3) Latitude displacement 0 05 015 represents the latitude offset from the latitude of the launch site. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site.
- (4) If additional information on sounding is available, the sequence <3 09 052> shall be preceded by sequences suitable for reporting additional information on sounding systems.
- (5) If the sounding data are obtained from upper-air systems where pressure is derived from geopotential height by integration of hydrostatic equation, the geopotential calculation method shall be recorded using 0 02 191 within the preceding sequences.
- (6) When a station is capable of reporting pressure and geopotential height with higher precision, the sequence 3 09 057 (Sequence for representation of TEMP, TEMP SHIP and TEMP MOBIL observation type data with higher precision of pressure and geopotential height) can be used instead of TM309052.

Provisional Copy
2023

Regulations:

B/C25.1	Section 1 of BUFR or CREX
B/C25.2	Identification of launch site and instrumentation for P, T, U and wind measurements
B/C25.3	Date/time of launch
B/C25.4	Horizontal and vertical coordinates of launch site
B/C25.5	Cloud information reported with vertical soundings
B/C25.6	Sea/water temperature
B/C25.7	Temperature, dewpoint and wind data at pressure levels
B/C25.8	Criteria for reporting standard and significant levels
B/C25.9	Wind shear data
B/C25.10	Data required by regional or national reporting practices
Annex I	Regional regulations for reporting TEMP, TEMP SHIP and TEMP MOBIL data in TDCF
Annex II	List of parameters for representation of additional information on sounding instrumentation

B/C25.1 Section 1 of BUFR or CREX

B/C25.1.1 Entries required in Section 1 of BUFR

The following entries shall be included in BUFR Section 1:

- BUFR master table;
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Identification of inclusion of optional section;
- Data category (002 for all TEMP type data);
- International data sub-category (see Note 1);
- Local data sub-category;
- Version number of master table;
- Version number of local tables;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for TEMP, TEMP SHIP and TEMP MOBIL type data);
- Hour (GG in the abbreviated telecommunication header e.g. = 00, 06, 12 or 18 for TEMP, TEMP SHIP and TEMP MOBIL type data);
- Minute (00 for TEMP, TEMP SHIP and TEMP MOBIL type data);
- Second (00).

Notes:

- (1) If required, the international data sub-category shall be included at all observation times as follows:
 - = 004 for TEMP data;
 - = 005 for TEMP SHIP data;
 - = 006 for TEMP MOBIL data.
- (2) If an NMHS performs conversion of TEMP, TEMP SHIP or TEMP MOBIL data produced by another NMHS, originating centre in Section 1 shall indicate the converting centre and originating sub-centre shall indicate the producer of TEMP, TEMP SHIP or TEMP MOBIL bulletins. The producer of TEMP, TEMP SHIP or TEMP MOBIL bulletins shall be specified in Common Code table C-12 as a sub-centre of the originating centre, i.e. of the NMHS executing the conversion.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C25.1.2 Entries required in Section 1 of CREX

The following entries shall be included in CREX Section 1:

- CREX master table;
- CREX edition number;
- CREX table version number;
- Version number of BUFR master table;
- Version number of local tables;
- Data category (002 for all TEMP type data);
- International data sub-category (see Note 1);
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Number of subsets;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for TEMP, TEMP SHIP and TEMP MOBIL type data);
- Hour (GG in the abbreviated telecommunication header, e.g. = 00, 06, 12 or 18 for TEMP, TEMP SHIP and TEMP MOBIL type data);
- Minute (00 for TEMP, TEMP SHIP and TEMP MOBIL type data).

Notes:

- (1) If inclusion of the international data sub-category is required, Note 1 under Regulation B/C25.1.1 applies.
- (2) If an NMHS performs conversion of TEMP, TEMP SHIP or TEMP MOBIL data produced by another NMHS, Note 2 under Regulation B/C25.1.1 applies.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C25.2 Identification of launch site and instrumentation for P, T, U and wind measurements <3 01 111>**B/C25.2.1 Identification of launch site**

WMO block number (0 01 001) and WMO station number (0 01 002) shall be always reported as a non-missing value in reports from a fixed land station. WMO block and station number may be included in reports from a fixed sea station if available.

Ship or mobile land station identifier (0 01 011) shall be always reported not exceeding 9 characters in reports from ships or mobile stations. Ship or mobile station identifier 0 01 011 shall be always set to a missing value in reports from a fixed land station. [35.2.1]

B/C25.2.2 Instrumentation for P, T, U and wind measurement

Radiosonde type (Code table 0 02 011), solar and infrared radiation correction (Code table 0 02 013), tracking techniques/status of system used (Code table 0 02 014) and type of measuring equipment used (Code table 0 02 003) shall be reported. [35.2.5]

B/C25.3 Date/time of launch <3 01 113>

Time significance (0 08 021) shall be always set to 18 to indicate that the following entries specify the date and time of launching the radiosonde.

Date of launch <3 01 011> and time of launch <3 01 013> shall be reported, i.e. year (0 04 001), month (0 04 002), day (0 04 003) and hour (0 04 004), minute

(0 04 005) and second (0 04 006) of the actual time of launch shall be reported. [35.2.5]

Note: Time of launch <3 01 013> shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry 0 04 006 for seconds shall be set to zero.

B/C25.4 Horizontal and vertical coordinates of launch site <3 01 114>

Latitude (0 05 001) and longitude (0 06 001) of the launch site shall be reported in degrees with precision in 10^{-5} of a degree.

Height of station ground above mean sea level (0 07 030) and height of barometer above mean sea level (0 07 031) shall be reported in metres with precision in tenths of a metre.

Height of release of sonde above mean sea level (0 07 007) shall be reported in metres.

Station elevation quality mark (Code table 0 33 024) shall be reported to indicate the accuracy of the vertical coordinates of the mobile land station. Fixed land stations and sea stations shall report this datum as a missing value. [35.2.1]

Note: The official altitude of the aerodrome (HA in Volume A) shall not be used to report Height of station ground above mean sea level 0 07 030 in BUFR or CREX messages from aerodromes. Those are two different vertical coordinates. "Height of station ground above mean sea level" for each station should be made available to the encoding centre concerned, which may be a centre within the same NMHS or other NMC/RTH.

B/C25.5 Cloud information reported with vertical sounding <3 02 049>

B/C25.5.1 Vertical significance (surface observations) – Code table 0 08 002

To specify vertical significance (0 08 002) within the sequence 3 02 049, a code figure shall be selected in the following way:

- (a) If low clouds are observed, then code figure 7 (Low cloud) shall be used;
- (b) If there are no low clouds but middle clouds are observed, then code figure 8 (Middle clouds) shall be used;
- (c) If there are no low and there are no middle clouds but high clouds are observed, then code figure 0 shall be used;
- (d) If sky is obscured by fog and/or other phenomena, then code figure 5 (Ceiling) shall be used;
- (e) If there are no clouds (clear sky), then code figure 62 (Value not applicable) shall be used;
- (f) If the cloud cover is not discernible for reasons other than (d) above or observation is not made, then code figure 63 (Missing value) shall be used.

B/C25.5.2 Cloud amount (of low or middle clouds) – Code table 0 20 011

Amount of all the low clouds (clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus) present or, if no low clouds are present, the amount of all the middle clouds (clouds of the genera Altopumulus, Altostratus, and Nimbostratus) present.

B/C25.5.2.1 Cloud amount shall be reported as follows:

- (a) If there are low clouds, then the total amount of all low clouds, as actually seen by the observer during the observation shall be reported for the cloud amount;

- (b) If there are no low clouds but there are middle clouds, then the total amount of the middle clouds shall be reported for the cloud amount;
- (c) If there are no low clouds and there are no middle clouds but there are high clouds (clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus), then the cloud amount shall be reported as zero.

[35.3.4.1], [12.2.7.2.1]

B/C25.5.2.2 Amount of Altocumulus perlucidus or Stratocumulus perlucidus (“mackerel sky”) shall be reported using code figure 7 or less since breaks are always present in this cloud form even if it extends over the whole celestial dome. [35.3.4.1], [12.2.7.2.2]

B/C25.5.2.3 When the clouds reported for cloud amount are observed through fog or an analogous phenomenon, the cloud amount shall be reported as if these phenomena were not present. [35.3.4.1], [12.2.7.2.3]

B/C25.5.2.4 If the clouds reported for cloud amount include contrails, then the cloud amount shall include the amount of persistent contrails. Rapidly dissipating contrails shall not be included in the value for the cloud amount. [35.3.4.1], [12.2.7.2.4]

B/C25.5.3 Height of base of lowest cloud

Height above surface of the base (0 20 013) of the lowest cloud seen shall be reported in metres (with precision in tens of metres).

Note: The term « height above surface » shall be considered as being the height above the official aerodrome elevation or above station elevation at a non-aerodrome station or the height above water surface of sea or lake.

B/C25.5.3.1 When the station is in fog, a sandstorm or in blowing snow but the sky is discernible, the base of the lowest cloud shall refer to the base of the lowest cloud observed, if any. When, under the above conditions, the sky is not discernible, the base of the lowest cloud shall be replaced by vertical visibility. [35.3.4.1], [12.4.10.5]

B/C25.5.3.2 When no cloud is reported (total cloud cover = 0) the base of the lowest cloud *shall be reported as a missing value.*

B/C25.5.3.3 When, by national decision, clouds with bases below the station are reported from the station and clouds with bases below and tops above the station are observed, the base of the lowest cloud *shall be reported having a negative value if the base of cloud is discernible, or as a missing value.*

B/C25.5.4 Cloud type of low, middle and high clouds – Code table 0 20 012

Clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus (low clouds) shall be reported for the first entry 0 20 012, clouds of the genera Altocumulus, Altostratus, and Nimbostratus (middle clouds) shall be reported for the second entry 0 20 012 and clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus (high clouds) shall be reported for the third entry 0 20 012.

B/C25.5.4.1 The reporting of type of low, middle and high clouds shall be as specified in the *International Cloud Atlas* (WMO-No. 407), Volume I. [35.3.4.1], [12.2.7.3]

B/C25.6 Sea/water temperature

Sea/water temperature (0 22 043) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Sea/water temperature data shall be reported

with precision in hundredths of a degree even if they are available with the accuracy in tenths of a degree.

Note: Notes 1 and 2 under Regulation B/C25.7.2.6 shall apply.

B/C25.6.1 Sea/water temperature shall always be included in reports from sea stations, when data are available. [35.2.5]

B/C25.7 Temperature, dewpoint and wind data at pressure levels

Temperature, dewpoint and wind data at pressure levels obtained during the radiosonde ascent shall be included in descending order with respect to pressure. Data at each pressure level shall be included only once. For example, if a significant level with respect to air temperature and relative humidity and a standard isobaric surface coincide, data for that level shall be included only once, the multiple attributes being indicated by Extended vertical sounding significance (Flag table 0 08 042) as specified in Regulation B/C25.7.2.2.

Note: If data are produced and collected in traditional TEMP codes, the order of pressure levels may correspond to the order of levels in Parts A, B, C and D, when converted into BUFR or CREX. In this case, data at a level may be included more than once.

B/C25.7.1 Number of reported pressure levels

The number of reported pressure levels shall be indicated by Extended delayed descriptor replication factor 0 31 002 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of pressure levels shall never be set to a missing value.
- (2) The number of pressure levels shall be set to a positive value in a NIL report.
- (3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

B/C25.7.1.1 All required data from the entire radiosonde ascent shall be reported in a BUFR (or CREX) message that shall be produced when the sounding is completed. In interest of timely data delivery, however, a BUFR (or CREX) message should be sent when level 100 hPa is reached.

B/C25.7.2 Temperature, dewpoint and wind data at a pressure level with radiosonde position <3 03 054>

B/C25.7.2.1 Long time displacement (since launch time)

Long time displacement (0 04 086) represents the time offset from the launch time specified in Regulation B/C25.3, and shall be reported in seconds if available.

B/C25.7.2.2 Extended vertical sounding significance – Flag table 0 08 042

This datum shall be used to specify vertical sounding significance in the following way:

- (a) Bit No. 1 set to 1 indicates surface (see Regulation B/C25.8.1);
- (b) Bit No. 2 set to 1 indicates a standard level (see Regulation B/C25.8.2);
- (c) Bit No. 3 set to 1 indicates a tropopause level (see Regulation B/C25.8.3);
- (d) Bit No. 4 set to 1 indicates a maximum wind level (see Regulation B/C25.8.4);

- (e) Bit No. 5 set to 1 indicates a level significant with respect to temperature (see Regulation B/C25.8.5);
- (f) Bit No. 6 set to 1 indicates a level significant with respect to relative humidity (see Regulation B/C25.8.6);
- (g) Bit No. 7 set to 1 indicates a level significant with respect to wind (see Regulation B/C25.8.7);
- (h) Bit No. 8 set to 1 indicates beginning of missing temperature data and bit No. 9 set to 1 indicates end of missing temperature data (see Regulation B/C25.8.8);
- (i) Bit No. 10 set to 1 indicates beginning of missing humidity data and bit No. 11 set to 1 indicates end of missing humidity data (see Regulation B/C25.8.9);
- (j) Bit No. 12 set to 1 indicates beginning of missing wind data bit No. 13 set to 1 indicates end of missing wind data (see Regulation B/C25.8.10);
- (k) Bit No. 14 set to 1 indicates the top of wind sounding;
- (l) Bit No. 15 set to 1 indicates a level determined by regional decision;
- (m) All bits set to 0 indicate a level determined by national decision or a level of no significance that has been included when high-resolution data are reported;
- (n) All bits set to 1 indicate a missing value.

B/C25.7.2.3 Pressure

Pressure (0 07 004) shall be reported in pascals (with precision in tens of pascals).

B/C25.7.2.4 Geopotential height

Geopotential height of the level (0 10 009) shall be reported in geopotential metres.

B/C25.7.2.5 Radiosonde drift – latitude and longitude displacements

Latitude displacement (0 05 015) represents the latitude offset from the latitude of the launch site specified in Regulation B/C25.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site specified in Regulation B/C25.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available.

B/C25.7.2.6 Temperature

Temperature (0 12 101) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree.

Notes:

- (1) This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

B/C25.7.2.7 Dewpoint temperature

Dewpoint temperature (0 12 103) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C25.7.2.6 shall apply.

B/C25.7.2.7.1 Dewpoint temperature data shall be derived using the function (or a near equivalent) for a relationship between saturation vapour pressure over water and air temperature (specified in the *Technical Regulations* (WMO-No. 49)). Dewpoint temperature data shall not be reported when the air temperature is outside the range stated by WMO for the application of the function; a lesser range may be used as a national practice. [35.3.1.1]

B/C25.7.2.8 Wind direction and speed

The wind direction (0 11 001) shall be reported in degrees true and the wind speed (0 11 002) shall be reported in metres per second (with precision in tenths of a metre per second).

Note: Wind direction measured at a station within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian.

B/C25.7.2.8.1 When during an ascent the pressure data can no longer be obtained, but wind data can be obtained, the wind data so obtained shall not be reported in the BUFR (or CREX) message in which data are described by the common sequence 3 09 052. These wind data so obtained may be reported using BUFR template TM 309051 suitable PILOT, PILOT SHIP or PILOT MOBIL data. [35.1.5]

B/C25.7.2.8.2 Only wind data obtained from the radiosonde ascent by either visual or electronic means shall be included in the BUFR (or CREX) message in which data are described by the common sequence 3 09 052. Wind data obtained by means other than a radiosonde-type ascent shall not be included in a message under common sequence 3 09 052. [35.1.6]

B/C25.8 Criteria for reporting standard and significant levels**B/C25.8.1 Surface**

The surface level shall be always reported.

Note: The value of Extended vertical sounding significance 0 08 042 at the surface level shall indicate that this level is also a level significant with respect to temperature, relative humidity and wind, i.e. not only bit No. 1 but also bits Nos. 5, 6 and 7 shall be set to 1.

B/C25.8.2 Standard levels

B/C25.8.2.1 The standard levels of 1 000, 925, 850, 700, 500, 400, 300, 250, 200, 150, 100, 70, 50, 30, 20 and 10 hPa shall be reported in ascending order with respect to altitude. [35.2.2.1]

B/C25.8.2.2 When the geopotential of a standard level is lower than the altitude of the reporting station, the time displacement, latitude displacement and longitude displacement for that level shall be set to zero and the air temperature, dewpoint temperature and wind data for that level shall be reported as missing values. [35.2.2.2]

B/C25.8.2.3 When air temperature, dewpoint temperature or wind data at a standard level are not available, the corresponding entries for that level shall be reported as missing values.

B/C25.8.2.4 Whenever it is desired to extrapolate a sounding for the computation of the geopotential at a standard level, the following rules shall apply:

- (a) Extrapolation is permissible if, and only if, the pressure difference between the minimum pressure of the sounding and the isobaric surface for which the extrapolated value is being computed does not exceed one quarter of the pressure at which the extrapolated value is desired, provided the extrapolation does not extend through a pressure interval exceeding 25 hPa;
- (b) For the purpose of geopotential calculation, and for this purpose only, the sounding will be extrapolated, using two points only of the sounding curve on a T-log p diagram, namely that at the minimum pressure reached by the sounding and that at the pressure given by the sum of this minimum pressure and the pressure difference, mentioned in (a) above.

[35.2.2.4]

B/C25.8.3 Tropopause level(s)

B/C25.8.3.1 When a tropopause (one or more) is observed, the corresponding number of levels shall be included (indicated by 0 08 042 – bit No. 3 set to 1).

Note: For a definition of tropopause, see the *International Meteorological Vocabulary* (WMO-No. 182).

[35.2.3.1]

B/C25.8.3.2 When no tropopause data are observed, no level shall be indicated by bit No. 3 of 0 08 042 set to 1. [35.2.3.2]

B/C25.8.4 Maximum wind level(s)

B/C25.8.4.1 When a maximum wind level (one or more) is reported, the corresponding number of levels shall be included in the report indicated by 0 08 042 – bit No. 4 set to 1. [35.2.4.1]

Notes:

- (1) Criteria for determining maximum wind levels are given in Regulations B/C25.8.4.3 and B/C25.8.4.4 below. [35.2.4.1]
- (2) As a maximum wind level is also a level significant with respect to wind, bit No. 7 as well as bit No. 4 shall be set to 1 in the Extended vertical sounding significance 0 08 042.

B/C25.8.4.2 When no maximum wind level is observed, no level shall be indicated by bit No. 4 of 0 08 042 set to 1. [35.2.4.2]

B/C25.8.4.3 A maximum wind level:

- (a) Shall be determined by consideration of the list of significant levels for wind speed, as obtained by means of the relevant recommended or equivalent national method (see the Note under Regulation B/C25.8.7.2) and *not* by consideration of the original wind-speed curve;
- (b) Shall be located above the 500-hPa isobaric surface and shall correspond to a speed of more than 30 metres per second.

Note: A maximum wind level is defined as a level at which the wind speed is greater than that observed immediately above and below that level.

[35.2.4.1], [32.2.3.1]

B/C25.8.4.4 Whenever more than one maximum wind level exists, these levels shall be reported as follows:

- (a) The level of greatest maximum wind speed shall be always included;
- (b) The other levels shall be included in the report only if their speed exceeds those of the two adjacent minima by at least 10 metres per second;
- (c) Furthermore, the highest level attained by the sounding shall be indicated as a maximum wind level, provided:
 - (i) It satisfies the criteria set forth in Regulation B/C25.8.4.3 above;
 - (ii) It constitutes the level of the greatest speed of the whole sounding.

[35.2.4.1], [32.2.3.2]

B/C25.8.4.5 If the top of the wind sounding corresponds to the highest wind speed observed throughout the ascent, this level shall be indicated by 0 08 042 – bit No. 4 set to 1 (maximum wind level), bit No. 7 set to 1 (level significant with respect to wind) and bit No. 14 set to 1 (top of wind sounding).

Note: For the purpose of the above regulation, the “top of the wind sounding” is to be understood as the highest level for which wind data are available.

[35.2.4.3]

B/C25.8.5 Levels significant with respect to temperature

B/C25.8.5.1 The reported significant levels *alone* shall make it possible to reconstruct the air temperature profile within the limits of the criteria specified.

If the criteria for determination of significant levels with respect to air temperature are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

[35.3.1.1]

B/C25.8.5.2 The following shall be included as “mandatory” significant temperature levels:

- (a) Surface level and the highest level of the sounding;
- (b) A level between 110 and 100 hPa;
- (c) Bases and tops of inversions and isothermal layers which are at least 20 hPa thick, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher;
- (d) Bases and tops of inversion layers which are characterized by a change in temperature of at least 2.5 °C, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher.

Note: The inversion layers of (c) and (d) may be comprised of several thinner inversion layers separated by thin layers of temperature lapse. To allow for this situation, the tops of the inversion layers of (c) and (d) shall each be at a level such that no further inversion layers, whether thick or thin, shall occur for at least 20 hPa above the level.

[35.3.1.2]

B/C25.8.5.3 The following shall be included as “additional” significant levels. They shall be selected in the order given, thereby giving priority to representing the temperature profile. As far as possible, these additional levels shall be the actual levels at which prominent changes in the lapse rate of air temperature occur:

- (a) Levels which are necessary to ensure that the temperature obtained by linear interpolation (on a T-log P or essentially similar diagram) between adjacent significant levels shall not depart from the observed temperature by more than 1 °C below the first significant level reported above the 300-hPa level or the first tropopause, whichever level is the lower, or by more than 2 °C thereafter;
- (b) Levels which are necessary to limit the interpolation error on diagrams other than T-log P. These levels shall be such that the pressure at one significant level divided by the pressure of the preceding significant layer shall exceed 0.6 for levels up to the first tropopause and shall be determined by use of the method for selecting additional levels but with application of tighter criteria.

[35.3.1.3]

B/C25.8.5.4 When a significant level with respect to air temperature and a standard level coincide, data for that level shall be reported only once.

B/C25.8.6 Levels significant with respect to relative humidity

B/C25.8.6.1 The reported significant levels *alone* shall make it possible to reconstruct the relative humidity profiles within the limits of the criteria specified.

If the criteria for determination of significant levels with respect to relative humidity are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

[35.3.1.1]

B/C25.8.6.2 The following shall be included as “mandatory” significant humidity levels:

- (a) Surface level and the highest level of the sounding;
- (b) A level between 110 and 100 hPa;
- (c) Bases and tops of inversions and isothermal layers which are at least 20 hPa thick, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher;
- (d) Bases and tops of inversion layers which are characterized by a change in relative humidity of at least 20 per cent, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher.

Note: The Note under Regulation B/C25.8.5.2 shall apply.

[35.3.1.2]

B/C25.8.6.3 The following shall be included as “additional” significant levels. They shall be selected in the order given, thereby giving priority to representing the temperature profile. As far as possible, these additional levels shall be the actual levels at which prominent changes in the lapse rate of air temperature occur:

- (a) Levels which are necessary to ensure that the relative humidity obtained by linear interpolation between adjacent significant levels shall not depart by more than 15 per cent from the observed values. (The criterion of 15 per cent refers to an amount of relative humidity and NOT to the percentage of the observed value, e.g. if an observed value is 50 per cent, the interpolated value shall lie between 35 per cent and 65 per cent.);

- (b) Levels which are necessary to limit the interpolation error on diagrams other than T-log P. These levels shall be such that the pressure at one significant level divided by the pressure of the preceding significant layer shall exceed 0.6 for levels up to the first tropopause and shall be determined by use of the method for selecting additional levels but with application of tighter criteria.

[35.3.1.3]

B/C25.8.6.4 When a significant layer with respect to relative humidity and a standard level coincide, data for that level shall be reported only once.

B/C25.8.7 Levels significant with respect to wind

B/C25.8.7.1 Significant wind levels shall be chosen so that the data from them *alone* shall make it possible to reconstruct the wind profile with sufficient accuracy for practical use. [35.3.2.1]

If the criteria for determination of significant levels with respect to wind speed and direction are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

B/C25.8.7.2 Criteria for determining significant levels with respect to changes in wind speed and direction:

- (a) The direction and speed curves (in function of the log of pressure or altitude) can be reproduced with their prominent characteristics;
- (b) These curves can be reproduced with the accuracy of at least 10 degrees true for direction and five metres per second for speed.

Note: To satisfy these criteria, the following method of successive approximations is recommended, but other methods of attaining equivalent results may suit some national practices better and may be used:

- (i) The surface level and highest level for which wind data are available constitute the first and the last significant levels. The deviation from the linearly interpolated values between these two levels is then considered. If no direction deviates by more than 10 degrees true and no speed by more than five metres per second, no other significant level need be reported. Whenever one parameter deviates by more than the limit specified in paragraph (b) above the level of greatest deviation becomes a supplementary significant level for both parameters;
- (ii) The additional significant levels so introduced divide the sounding into two layers. In each separate layer, the deviation from the linearly interpolated values between the base and the top are then considered. The process used in paragraph (i) above is repeated and yields other significant levels. These additional levels in turn modify the layer distribution, and the method is applied again until any level is approximated to the above-mentioned specified values.

[35.3.2.1], [32.3.1.1]

B/C25.8.8 Beginning and end of missing temperature data

B/C25.8.8.1 A layer for which temperature data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 20 hPa thick. The boundary levels are the levels closest to the bottom and the top of the layer for which temperature data are available. The boundary levels are not required to meet “significant temperature level” criteria. [35.3.1.6]

B/C25.8.9 Beginning and end of missing humidity data

B/C25.8.9.1 A layer for which dewpoint temperature data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 20 hPa thick. The boundary levels are the levels closest to the bottom and the top

of the layer for which dewpoint temperature data are available. The boundary levels are not required to meet “significant humidity level” criteria. [35.3.1.6]

B/C25.8.10 Beginning and end of missing wind data

B/C25.8.10.1 A layer for which wind data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 50 hPa thick. The boundary levels are the levels closest to the bottom and the top of the layer for which the observed data are available. The boundary levels are not required to meet “significant wind level” criteria. [35.3.2.2]

B/C25.9 Wind shear data

B/C25.9.1 Number and order of levels for which wind shear is reported

B/C25.9.1.1 The number of levels with wind shear data shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of levels with wind shear data shall never be set to a missing value.
- (2) The number of levels with wind shear data shall be set to a positive value in a NIL report.
- (3) The number of levels with wind shear data shall be set to zero if data for vertical wind shear are not computed and required. [35.2.4.4]
- (4) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

B/C25.9.1.2 Whenever wind shear data are reported for more than one level, these maximum wind levels shall be included in the same order as in the sequence <3 03 054>, i.e. in descending order with respect to pressure.

B/C25.9.2 Wind shear data at a pressure level with radiosonde position <3 03 051>

B/C25.9.2.1 Long time displacement (since launch time)

Long time displacement (0 04 086) represents the time offset from the launch time specified in Regulation B/C25.3, and shall be reported in seconds if available.

B/C25.9.2.2 Extended vertical sounding significance – Flag table 0 08 042

A level, for which wind shear data are reported, shall be indicated by vertical sounding significance 0 08 042 – bit No. 4 set to 1 (maximum wind level) and by bit No. 7 set to 1 (level significant with respect to wind). Moreover, if the top of the wind sounding corresponds to the highest wind speed observed throughout the ascent, this level shall be indicated also by bit No. 14 set to 1 (top of wind sounding).

B/C25.9.2.3 Pressure

Pressure (0 07 004) shall be reported in pascals with precision in tens of pascals.

B/C25.9.2.4 Latitude and longitude displacements

Latitude displacement (0 05 015) represents the latitude offset from the latitude of the launch site specified in Regulation B/C25.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site specified in Regulation B/C25.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available.

B/C25.9.2.5 Wind shear data

Absolute wind shear in 1 km layer below (0 11 061) and absolute wind shear in 1-km layer above (0 11 062) shall be reported in metres per second (with precision in tenths of a metre per second), if data for vertical wind shear are computed and required. [35.2.4.4]

B/C25.10 Data required by regional or national reporting practices

If regional or national reporting practices require inclusion of temperature, humidity and/or wind data at additional levels, these data shall be reported using sequence <3 03 054> for Temperature, dewpoint, wind at a pressure level. Regulation B/C25.7 shall apply.

Notes:

- (1) A level determined by regional decision shall be indicated by Extended vertical sounding significance 0 08 042 – bit No. 15 set to 1.
- (2) A level determined by national decision shall be indicated by Extended vertical sounding significance 0 08 042 – all bits set to 0.

B/C25.10.1 Additional data required by reporting practices in RA I

Temperature, dewpoint, wind data at additional levels shall be reported in compliance with Regulation B/C25.10.

B/C25.10.2 Additional data required by reporting practices in RA II

B/C25.10.2.1 No additional data are required by regional reporting practices in RA II.

B/C25.10.2.2 The inclusion of wind shear data shall be left to national decision. Members are recommended to include these data as often as possible. [2/35.2]

B/C25.10.3 Additional data required by reporting practices in RA III

No regional requirements are indicated for reporting TEMP, TEMP SHIP and TEMP MOBIL data in RA III.

B/C25.10.4 Additional data required by reporting practices in RA IV

B/C25.10.4.1 When available, temperature, dewpoint, wind data for levels 7, 5, 3, 2 and 1 hPa shall be reported in compliance with Regulation B/C25.10. [4/35.2.1]

B/C25.10.4.2 When required, additional information shall be reported using RA IV BUFR template for data representation of TEMP, TEMP SHIP and TEMP MOBIL data as shown in Annex I to Part B/C25. [4/35.1], [4/35.2.2]

B/C25.10.5 Additional data required by reporting practices in RA V

No regional requirements are indicated for reporting TEMP, TEMP SHIP and TEMP MOBIL data in RA V.

B/C25.10.6 Additional data required by reporting practices in RA VI

B/C25.10.6.1 The inclusion of wind shear data shall be left to national decision. Members are recommended to include these data as often as possible. [6/35.1]

B/C25.10.6.2 Wind direction and speed shall be reported:
(i) For 900 or 1 000 metres above the surface;
(ii) For 800 hPa level;
(iii) For 600 hPa level.
[6/35.2.2]

Provisional Copy
2023

ANNEX I TO B/C25 – Regional regulations for reporting TEMP, TEMP SHIP and TEMP MOBIL data in TDCF

RA IV BUFR template for TEMP, TEMP SHIP and TEMP MOBIL data

The RA IV Regional coding procedures for TEMP and TEMP SHIP data require data representation of additional information that is specified in the *Manual on Codes* (WMO-No. 306), Volume II, by supplementary groups 101A_{df}A_{df} (Code table 421 for A_{df}A_{df} – Form of additional data reported). The sequence <3 09 052> for representation of TEMP, TEMP SHIP and TEMP MOBIL data is supplemented by additional parameters to allow data representation of this information, if it is required.

		Unit, scale
3 09 052	Sequence for representation of TEMP, TEMP SHIP and TEMP MOBIL observation type data	
	Reason for no report or incomplete report	
0 35 035	Reason for termination	Code table
	Corrected data	
1 04 000	Delayed replication of 4 descriptors	
0 31 001	Delayed descriptor replication factor	Numeric
2 04 001	Add associated field (of 1 bit in length)	
0 31 021	Associated field significance = 21 (indicator of correction)	Code table
	Associated field set to 1 (corrected value)	
3 03 054	Temperature, dewpoint and wind data at a pressure level with radiosonde position	
2 04 000	Cancel Add associated field	
0 08 042	Extended vertical sounding significance = missing (to cancel the previous value)	Flag table
	Stability index and mean wind data	
0 13 047	Modified Showalter stability index	K
0 11 044	Mean wind direction for surface – 1 500 m (5 000 feet)	Degree true
0 11 045	Mean wind speed for surface – 1 500 m (5 000 feet)	m s ⁻¹ , 1
0 11 054	Mean wind direction for 1 500 m – 3 000 m	Degree true
0 11 055	Mean wind speed for 1 500 m – 3 000 m	m s ⁻¹ , 1
	Doubtful data	
1 12 000	Delayed replication of 12 descriptors	
0 31 001	Delayed descriptor replication factor	Numeric
1 11 002	Replicate 11 descriptors 2 times	
0 04 086	Long time period or displacement (since launch time)	Second
0 08 040	Flight level significance In the 1st replication = 4 (Begin doubtful temperature, height data) In the 2nd replication = 9 (End doubtful temperature, height data)	Code table
0 07 004	Pressure	Pa, –1
0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
1 01 000	Delayed replication of 1 descriptor	
0 31 000	Short delayed descriptor replication factor	Numeric
0 10 009	Geopotential height	gpm

		Unit, scale
1 01 000	Delayed replication of 1 descriptor	
0 31 000	Short delayed descriptor replication factor	Numeric
0 12 101	Temperature/air temperature	K, 2
Extrapolated geopotential data		
1 08 000	Delayed replication of 8 descriptors	
0 31 001	Delayed descriptor replication factor	Numeric
0 04 086	Long time period or displacement (since launch time)	Second
0 08 040	Flight level significance = 31 (Incremented height level (generated))	Code table
0 07 004	Pressure	Pa, –1
0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
0 10 009	Geopotential height	gpm
0 11 001	Wind direction	Degree true
0 11 002	Wind speed	m s ⁻¹ , 1

Note: The “Modified Showalter stability index” 0 13 047 is defined as the temperature difference between the ambient 500 hPa temperature and the temperature a parcel of air, initially at a selected base level, would have if brought from its condensation level to the 500 hPa surface by a moist adiabatic process. Positive values denote stable conditions, while negative values denote unstable conditions. The base level is 850 hPa, 800hPa or 750 hPa, if the station elevation is less than 1 000, 1 000 to 1 400 or 1 401 to 2 000 gpm above mean sea level, respectively.

ANNEX II TO B/C25 – List of parameters for representation of additional information on sounding instrumentation

Additional information on radiosonde ascent

		(Additional information on radiosonde ascent)
3 01 128	0 01 081	Radiosonde serial number
	0 01 082	Radiosonde ascension number
	0 01 083	Radiosonde release number
	0 01 095	Observer identification
	0 02 015	Radiosonde completeness
	0 02 016	Radiosonde configuration
	0 02 017	Correction algorithms for humidity measurements
	0 02 066	Radiosonde ground receiving system
	0 02 067	Radiosonde operating frequency
	0 02 080	Balloon manufacturer
	0 02 081	Type of balloon
	0 02 082	Weight of balloon
	0 02 083	Type of balloon shelter
	0 02 084	Type of gas used in balloon
	0 02 085	Amount of gas used in balloon
	0 02 086	Balloon flight train length
	0 02 095	Type of pressure sensor
	0 02 096	Type of temperature sensor
	0 02 097	Type of humidity sensor
	0 02 103	Radome
	0 02 191	Geopotential height calculation
	0 25 061	Software identification and version number
	0 35 035	Reason for termination

B/C26 – Regulations for reporting TEMP DROP data in TDCF

TM 309053 – BUFR template for P, T, U and wind vertical profiles suitable for TEMP DROP observation data

		Sequence for representation TEMP DROP observation type data
3 09 053	3 01 112	Identification of launch point and instrumentation of dropsonde
	3 01 113	Date/time of launch
	3 01 114	Horizontal and vertical coordinates of launch site
	1 01 000	Delayed replication of 1 descriptor
	0 31 002	Extended delayed descriptor replication factor
	3 03 054	Temperature, dewpoint and wind data at a pressure level with radiosonde position
	1 01 000	Delayed replication of 1 descriptor
	0 31 001	Delayed descriptor replication factor
	3 03 051	Wind shear data at a pressure level with radiosonde position

This BUFR template for P, T, U and wind profiles further expands as follows:

			Unit, scale
		Identification of launch point and instrumentation of dropsonde	
3 01 112	0 01 006	Aircraft flight number	CCITT IA5
	0 02 011	Radiosonde type	Code table
	0 02 013	Solar and infrared radiation correction	Code table
	0 02 014	Tracking technique/status of system used	Code table
	0 02 003	Type of measuring equipment used	Code table
		Date/time of launch	
3 01 113	0 08 021	Time significance (= 18 Launch time)	Code table
	3 01 011	Year	Year
		Month	Month
		Day	Day
	3 01 013	Hour	Hour
		Minute	Minute
		Second	Second
		Horizontal and vertical coordinates of launch site	
3 01 114	3 01 021	Latitude/longitude (high accuracy)	Degree, 5
	0 07 030	Height of station ground above mean sea level	m, 1
	0 07 031	Height of barometer above mean sea level	m, 1
	0 07 007	Height (of release of sonde above mean sea level)	m
	0 33 024	Station elevation quality mark (for mobile stations)	Code table
		Temperature, dewpoint and wind data at pressure levels	
1 01 000		Delayed replication of 1 descriptor	
0 31 002		Extended delayed descriptor replication factor	Numeric
		<i>Temperature, dewpoint and wind data at a pressure level with radiosonde position</i>	
3 03 054	0 04 086	Long time period or displacement (since launch time)	Second
	0 08 042	Extended vertical sounding significance	Flag table
	0 07 004	Pressure	Pa, -1
	0 10 009	Geopotential height	gpm
	0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5

			Unit, scale
	0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
	0 12 101	Temperature/air temperature	K, 2
	0 12 103	Dewpoint temperature	K, 2
	0 11 001	Wind direction	Degree true
	0 11 002	Wind speed	m s ⁻¹ , 1
		Wind shear data	
1 01 000		Delayed replication of 1 descriptor	
0 31 001		Delayed descriptor replication factor	Numeric
		<i>Wind shear data at a pressure level with radiosonde position</i>	
3 03 051	0 04 086	Long time period or displacement (since launch time)	Second
	0 08 042	Extended vertical sounding significance	Flag table
	0 07 004	Pressure	Pa, -1
	0 05 015	Latitude displacement (high accuracy) – since launch site	Degree, 5
	0 06 015	Longitude displacement (high accuracy) – since launch site	Degree, 5
	0 11 061	Absolute wind shear in 1 km layer below	m s ⁻¹ , 1
	0 11 062	Absolute wind shear in 1 km layer above	m s ⁻¹ , 1

Notes:

- (1) Time of launch 3 01 013 shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry for seconds shall be put to zero.
- (2) Long time displacement 0 04 086 represents the time offset from the launch time 3 01 013 (in seconds).
- (3) Latitude displacement 0 05 015 represents the latitude offset from the latitude of the launch site. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site.

Regulations:

B/C26.1	Section 1 of BUFR or CREX
B/C26.2	Identification of launch point and instrumentation of dropsonde
B/C26.3	Date/time of launch
B/C26.4	Horizontal and vertical coordinates of launch site
B/C26.5	Temperature, dewpoint and wind data at pressure levels
B/C26.6	Criteria for reporting standard and significant levels
B/C26.7	Wind shear data
B/C26.8	Data required by regional or national reporting practices

B/C26.1 Section 1 of BUFR or CREX

B/C26.1.1 Entries required in Section 1 of BUFR

The following entries shall be included in BUFR Section 1:

- BUFR master table;
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Identification of inclusion of optional section;
- Data category (002 for all TEMP type data);
- International data sub-category (see Note 1);
- Local data sub-category;
- Version number of master table;
- Version number of local tables;
- Year (see Note 3);
- Month;
- Day (YY in the abbreviated telecommunication header for TEMP DROP type data);
- Hour (GG in the abbreviated telecommunication header for TEMP DROP type data);
- Minute (00 for TEMP DROP type data);
- Second (00).

Notes:

- (1) If required, the international data sub-category shall be included at all observation times as follows:
= 007 for TEMP DROP data.
- (2) If an NMHS performs conversion of TEMP DROP data produced by another NMHS, originating centre in Section 1 shall indicate the converting centre and originating sub-centre shall indicate the producer of TEMP DROP bulletins. The producer of TEMP DROP bulletins shall be specified in Common Code table C-12 as a sub-centre of the originating centre, i.e. of the NMHS executing the conversion.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C26.1.2 Entries required in Section 1 of CREX

The following entries shall be included in CREX Section 1:

- CREX master table;
- CREX edition number;
- CREX table version number;
- Version number of BUFR master table;
- Version number of local tables;
- Data category (002 for all TEMP type data);

- International data sub-category (see Note 1);
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Number of subsets;
- Year;
- Month;
- Day (YY in the abbreviated telecommunication header for TEMP DROP type data);
- Hour (GG in the abbreviated telecommunication header for TEMP DROP type data);
- Minute (00 for TEMP DROP type data).

Notes:

- (1) If inclusion of the international data sub-category is required, Note 1 under Regulation B/C26.1.1 applies.
- (2) If an NMHS performs conversion of TEMP DROP data produced by another NMHS, Note 2 under Regulation B/C26.1.1 applies.
- (3) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C26.2 Identification of launch point and instrumentation of dropsonde <3 01 112>

B/C26.2.1 Identification of launch point of dropsonde

Aircraft identifier (0 01 006) shall be always reported.

B/C26.2.2 Instrumentation for P, T, U and wind measurement

Radiosonde type (Code table 0 02 011), solar and infrared radiation correction (Code table 0 02 013), tracking techniques/status of system used (Code table 0 02 014) and type of measuring equipment used (Code table 0 02 003) shall be reported. [35.2.5]

B/C26.3 Date/time of launch <3 01 113>

Time significance (0 08 021) shall be always set to 18 to indicate that the following entries specify the date and time of launching the dropsonde.

Date of launch <3 01 011> and time of launch <3 01 013> shall be reported, i.e. year (0 04 001), month (0 04 002), day (0 04 003) and hour (0 04 004), minute (0 04 005) and second (0 04 006) of the actual time of launch shall be reported. [35.2.5]

Note: Time of launch <3 01 013> shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry 0 04 006 for seconds shall be set to zero.

B/C26.4 Horizontal and vertical coordinates of launch site <3 01 114>

Latitude (0 05 001) and longitude (0 06 001) of the launch site shall be reported in degrees with precision in 10^{-5} of a degree.

Height of station ground above mean sea level (0 07 030) shall be reported as a missing value.

Height of barometer above mean sea level (0 07 031) shall be reported in metres with precision in tenths of a metre.

Height of release of dropsonde above mean sea level (0 07 007) shall be reported in metres.

Station elevation quality mark (Code table 0 33 024) shall be reported as a missing value. [35.2.1]

B/C26.5 Temperature, dewpoint and wind data at pressure levels

Temperature, dewpoint and wind data at pressure levels obtained during the dropsonde descent shall be included in descending order with respect to pressure. Data at each pressure level shall be included only once. For example, if a significant level with respect to air temperature and relative humidity and a standard isobaric surface coincide, data for that level shall be included only once, the multiple attributes being indicated by Extended vertical sounding significance (Flag table 0 08 042) as specified in Regulation B/C26.5.2.2.

Note: If data are produced and collected in traditional TEMP DROP code, the order of pressure levels may correspond to the order of levels in Parts A, B, C and D, when converted into BUFR or CREX. In this case, data at a level may be included more than once.

B/C26.5.1 Number of reported pressure levels

The number of reported pressure levels shall be indicated by Extended delayed descriptor replication factor 0 31 002 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of pressure levels shall never be set to a missing value.
- (2) The number of pressure levels shall be set to a positive value in a NIL report.
- (3) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

B/C26.5.2 Temperature, dewpoint and wind data at a pressure level with radiosonde position <3 03 054>

B/C26.5.2.1 Long time displacement (since launch time)

Long time displacement (0 04 086) represents the time offset from the launch time specified in Regulation B/C26.3, and shall be reported in seconds if available.

B/C26.5.2.2 Extended vertical sounding significance – Flag table 0 08 042

This datum shall be used to specify vertical sounding significance in the following way:

- (a) Bit No. 1 set to 1 indicates a surface (see Regulation B/C26.6.1);
- (b) Bit No. 2 set to 1 indicates a standard level (see Regulation B/C26.6.2);
- (c) Bit No. 3 set to 1 indicates a tropopause level (see Regulation B/C26.6.3);
- (d) Bit No. 4 set to 1 indicates a maximum wind level (see Regulation B/C26.6.4);
- (e) Bit No. 5 set to 1 indicates a level significant with respect to temperature (see Regulation B/C26.6.5);
- (f) Bit No. 6 set to 1 indicates a level significant with respect to relative humidity (see Regulation B/C26.6.6);
- (g) Bit No. 7 set to 1 indicates a level significant with respect to wind (see Regulation B/C26.6.7);
- (h) Bit No. 8 set to 1 indicates beginning of missing temperature data and bit No. 9 set to 1 indicates end of missing temperature data (see Regulation B/C26.6.8);

- (i) Bit No. 10 set to 1 indicates beginning of missing humidity data and bit No. 11 set to 1 indicates end of missing humidity data (see Regulation B/C26.6.9);
- (j) Bit No. 12 set to 1 indicates beginning of missing wind data bit No. 13 set to 1 indicates end of missing wind data (see Regulation B/C26.6.10);
- (k) Bit No. 14 set to 1 indicates the top of wind sounding (the lowest level for which wind data are available);
- (l) Bit No. 15 set to 1 indicates a level determined by regional decision;
- (m) All bits set to 0 indicate a level determined by national decision;
- (n) All bits set to 1 indicate a missing value.

B/C26.5.2.3 Pressure

Pressure (0 07 004) shall be reported in pascals (with precision in tens of pascals).

B/C26.5.2.4 Geopotential height

Geopotential height of the level (0 10 009) shall be reported in geopotential metres.

B/C26.5.2.5 Radiosonde drift - latitude and longitude displacements

Latitude displacement (0 05 015) represents the latitude offset from the latitude of the launch site specified in Regulation B/C26.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site specified in Regulation B/C26.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available.

B/C26.5.2.6 Temperature

Temperature (0 12 101) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree.

Notes:

- (1) This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

B/C26.5.2.7 Dewpoint temperature

Dewpoint temperature (0 12 103) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C26.5.2.6 shall apply.

- B/C26.5.2.7.1** Dewpoint temperature data shall be derived using the function (or a near equivalent) for a relationship between saturation vapour pressure over water and air temperature (specified in the *Technical Regulations* (WMO-No. 49)). Dewpoint temperature data shall not be reported when the air temperature is outside the range stated by WMO for the application of the function; a lesser range may be used as a national practice. [35.3.1.1]

B/C26.5.2.8 Wind direction and speed

The wind direction (0 11 001) shall be reported in degrees true and the wind speed (0 11 002) shall be reported in metres per second (with precision in tenths of a metre per second).

Note: Wind direction measured in sounding originated from a launch site within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian.

B/C26.5.2.8.1 Only wind data obtained from the radiosonde descent by electronic means shall be included in the BUFR (or CREX) message in which data are described by the common sequence 3 09 053. Wind data obtained by means other than a radiosonde-type descent shall not be included in a message under common sequence 3 09 053. [35.1.7]

B/C26.6 Criteria for reporting standard and significant levels**B/C26.6.1 Surface level**

If extrapolated surface data are included in the report, the level shall be indicated by bit No. 1 of 0 08 042 set to 1.

B/C26.6.2 Standard levels

B/C26.6.2.1 The standard levels of 1 000, 925, 850, 700, 500, 400, 300, 250, 200, 150, 100, 70, 50, 30, 20 and 10 hPa shall be reported in descending order with respect to pressure. [35.2.2.1]

B/C26.6.2.2 When air temperature, dewpoint temperature or wind data at a standard level are not available, the corresponding entries for that level shall be reported as missing values.

B/C26.6.2.3 Whenever it is desired to extrapolate a sounding for the computation of the geopotential at a standard level, the following rules shall apply:

- (a) Extrapolation is permissible if, and only if, the pressure difference between the minimum pressure of the sounding and the isobaric surface for which the extrapolated value is being computed does not exceed one quarter of the pressure at which the extrapolated value is desired, provided the extrapolation does not extend through a pressure interval exceeding 25 hPa;
- (b) For the purpose of geopotential calculation, and for this purpose only, the sounding will be extrapolated, using two points only of the sounding curve on a T-log p diagram, namely that at the minimum pressure reached by the sounding and that at the pressure given by the sum of this minimum pressure and the pressure difference, mentioned in (a) above.

[35.2.2.4]

B/C26.6.3 Tropopause level(s)

B/C26.6.3.1 When a tropopause (one or more) is observed, the corresponding number of levels shall be included (indicated by 0 08 042 – bit No. 3 set to 1).

Note: For a definition of tropopause, see the *International Meteorological Vocabulary* (WMO-No. 182).

[35.2.3.1]

B/C26.6.3.2 When no tropopause data are observed, no level shall be indicated by bit No. 3 of 0 08 042 set to 1. [35.2.3.2]

B/C26.6.4 Maximum wind level(s)

B/C26.6.4.1 When a maximum wind level (one or more) is reported, the corresponding number of levels shall be included in the report indicated by 0 08 042 – bit No. 4 set to 1.

Notes:

- (1) Criteria for determining maximum wind levels are given in Regulations B/C26.6.4.3 and B/C26.6.4.4 below. [35.2.4.1]
- (2) As a maximum wind level is also a level significant with respect to wind, bit No. 7 as well as bit No. 4 shall be set to 1 in the Extended vertical sounding significance 0 08 042.

B/C26.6.4.2 When no maximum wind level is observed, no level shall be indicated by bit No. 4 of 0 08 042 set to 1. [35.2.4.2]

B/C26.6.4.3 A maximum wind level:

- (a) Shall be determined by consideration of the list of significant levels for wind speed, as obtained by means of the relevant recommended or equivalent national method (see the Note under Regulation B/C26.6.7.2) and *not* by consideration of the original wind-speed curve;
- (b) Shall be located above the 500-hPa isobaric surface and shall correspond to a speed of more than 30 metres per second.

Note: A maximum wind level is defined as a level at which the wind speed is greater than that observed immediately above and below that level.

[35.2.4.1], [32.2.3.1]

B/C26.6.4.4 Whenever more than one maximum wind level exists, these levels shall be reported as follows:

- (a) The level of greatest maximum wind speed shall be always included;
- (b) The other levels shall be included in the report only if their speed exceeds those of the two adjacent minima by at least 10 metres per second.

[35.2.4.1], [32.2.3.2]

B/C26.6.4.5 If the top of the wind sounding corresponds to the highest wind speed observed throughout the descent, this level shall be indicated by 0 08 042 – bit No. 4 set to 1 (maximum wind level), bit No. 7 set to 1 (level significant with respect to wind) and bit No. 14 set to 1 (top of wind sounding).

Notes:

- (1) For the purpose of the above regulation, the “top of the wind sounding” is to be understood as the lowest level (termination level of the sounding) for which wind data are available. [35.2.4.3]
- (2) Although not very probable, the situation described in the above regulation cannot be excluded.

B/C26.6.5 Levels significant with respect to temperature

B/C26.6.5.1 The reported significant levels *alone* shall make it possible to reconstruct the air temperature profile within the limits of the criteria specified.

If the criteria for determination of significant levels with respect to air temperature are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

[35.3.1.1]

- B/C26.6.5.2** The following shall be included as “mandatory” significant temperature levels:
- (a) Aircraft reference level and termination level of the sounding (the lowest level of the sounding);
 - (b) A level between 110 and 100 hPa;
 - (c) Bases and tops of inversions and isothermal layers which are at least 20 hPa thick, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher;
 - (d) Bases and tops of inversion layers which are characterized by a change in temperature of at least 2.5 °C, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher.

Note: The inversion layers of (c) and (d) may be comprised of several thinner inversion layers separated by thin layers of temperature lapse. To allow for this situation, the tops of the inversion layers of (c) and (d) shall each be at a level such that no further inversion layers, whether thick or thin, shall occur for at least 20 hPa above the level.

[35.3.1.2]

- B/C26.6.5.3** The following shall be included as “additional” significant levels. They shall be selected in the order given, thereby giving priority to representing the temperature profile. As far as possible, these additional levels shall be the actual levels at which prominent changes in the lapse rate of air temperature occur:

- (a) Levels which are necessary to ensure that the temperature obtained by linear interpolation (on a T-log P or essentially similar diagram) between adjacent significant levels shall not depart from the observed temperature by more than 1 °C below the first significant level reported above the 300-hPa level or the first tropopause, whichever level is the lower, or by more than 2 °C thereafter;
- (b) Levels which are necessary to limit the interpolation error on diagrams other than T-log P. These levels shall be such that the pressure at one significant level divided by the pressure of the preceding significant layer shall exceed 0.6 for levels up to the first tropopause and shall be determined by use of the method for selecting additional levels but with application of tighter criteria.

[35.3.1.3]

- B/C26.6.5.4** When a significant level with respect to air temperature and a standard level coincide, data for that level shall be reported only once.

B/C26.6.6 Levels significant with respect to relative humidity

- B/C26.6.6.1** The reported significant levels *alone* shall make it possible to reconstruct the relative humidity profiles within the limits of the criteria specified.

If the criteria for determination of significant levels with respect to relative humidity are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

[35.3.1.1]

- B/C26.6.6.2** The following shall be included as “mandatory” significant humidity levels:
- (a) Aircraft reference level and termination level of the sounding (the lowest level of the sounding);
 - (b) A level between 110 and 100 hPa;
 - (c) Bases and tops of inversions and isothermal layers which are at least 20 hPa thick, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher;

- (d) Bases and tops of inversion layers which are characterized by a change in relative humidity of at least 20 per cent, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher.

Note: The Note under Regulation B/C26.6.5.2 shall apply.

[35.3.1.2]

B/C26.6.6.3 The following shall be included as “additional” significant levels. They shall be selected in the order given, thereby giving priority to representing the temperature profile. As far as possible, these additional levels shall be the actual levels at which prominent changes in the lapse rate of air temperature occur:

- (a) Levels which are necessary to ensure that the relative humidity obtained by linear interpolation between adjacent significant levels shall not depart by more than 15 per cent from the observed values (The criterion of 15 per cent refers to an amount of relative humidity and NOT to the percentage of the observed value, e.g. if an observed value is 50 per cent, the interpolated value shall lie between 35 per cent and 65 per cent.);
- (b) Levels which are necessary to limit the interpolation error on diagrams other than T-log P. These levels shall be such that the pressure at one significant level divided by the pressure of the preceding significant layer shall exceed 0.6 for levels up to the first tropopause and shall be determined by use of the method for selecting additional levels but with application of tighter criteria.

[35.3.1.3]

B/C26.6.6.4 When a significant layer with respect to relative humidity and a standard level coincide, data for that level shall be reported only once.

B/C26.6.7 Levels significant with respect to wind

B/C26.6.7.1 Significant wind levels shall be chosen so that the data from them *alone* shall make it possible to reconstruct the wind profile with sufficient accuracy for practical use. [35.3.2.1]

If the criteria for determination of significant levels with respect to wind speed and direction are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

B/C26.6.7.2 Criteria for determining significant levels with respect to changes in wind speed and direction:

- (a) The direction and speed curves (in function of the log of pressure or altitude) can be reproduced with their prominent characteristics;
- (b) These curves can be reproduced with the accuracy of at least 10 degrees true for direction and five metres per second for speed.

Note: To satisfy these criteria, the following method of successive approximations is recommended, but other methods of attaining equivalent results may suit some national practices better and may be used:

- (i) The lowest level for which wind data are available and the aircraft reference level constitute the first and the last significant levels. The deviation from the linearly interpolated values between these two levels is then considered. If no direction deviates by more than 10 degrees true and no speed by more than five metres per second, no other significant level need be reported. Whenever one parameter deviates by more than the limit specified in paragraph (b) above the level of greatest deviation becomes a supplementary significant level for both parameters;
- (ii) The additional significant levels so introduced divide the sounding into two layers. In each separate layer, the deviation from the linearly interpolated values between the

base and the top are then considered. The process used in paragraph (i) above is repeated and yields other significant levels. These additional levels in turn modify the layer distribution, and the method is applied again until any level is approximated to the above-mentioned specified values.

[35.3.2.1], [32.3.1.1]

B/C26.6.8 Beginning and end of missing temperature data

B/C26.6.8.1 A layer for which temperature data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 20 hPa thick. The boundary levels are the levels closest to the bottom (beginning of the missing data) and the top (end of the missing data) of the layer for which temperature data are available. The boundary levels are not required to meet “significant temperature level” criteria. [35.3.1.6]

B/C26.6.9 Beginning and end of missing humidity data

B/C26.6.9.1 A layer for which dewpoint temperature data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 20 hPa thick. The boundary levels are the levels closest to the bottom (beginning of the missing data) and the top (end of the missing data) of the layer for which dewpoint temperature data are available. The boundary levels are not required to meet “significant humidity level” criteria. [35.3.1.6]

B/C26.6.10 Beginning and end of missing wind data

B/C26.6.10.1 A layer for which wind data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 50 hPa thick. The boundary levels are the levels closest to the bottom (beginning of the missing data) and the top (end of the missing data) of the layer for which the observed data are available. The boundary levels are not required to meet “significant wind level” criteria. [35.3.2.2]

B/C26.7 Wind shear data

B/C26.7.1 Number and order of levels for which wind shear is reported

B/C26.7.1.1 The number of levels with wind shear data shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of levels with wind shear data shall never be set to a missing value.
- (2) The number of levels with wind shear data shall be set to a positive value in a NIL report.
- (3) The number of levels with wind shear data shall be set to zero if data for vertical wind shear are not computed and required. [35.2.4.4]
- (4) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

B/C26.7.1.2 Whenever wind shear data are reported for more than one level, these maximum wind levels shall be included in the same order as in the sequence <3 03 054>, i.e. in descending order with respect to pressure.

B/C26.7.2 Wind shear data at a pressure level with radiosonde position <3 03 051>**B/C26.7.2.1 Long time displacement (since launch time)**

Long time displacement (0 04 086) represents the time offset from the launch time specified in Regulation B/C26.3, and shall be reported in seconds if available.

B/C26.7.2.2 Extended vertical sounding significance – Flag table 0 08 042

A level, for which wind shear data are reported, shall be indicated by vertical sounding significance 0 08 042 – bit No. 4 set to 1 (maximum wind level) and by bit No. 7 set to 1 (level significant with respect to wind).

B/C26.7.2.3 Pressure

Pressure (0 07 004) shall be reported in pascals with precision in tens of pascals.

B/C26.7.2.4 Latitude and longitude displacements

Latitude displacement (0 05 015) represents the latitude offset from the latitude of the launch site specified in Regulation B/C26.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site specified in Regulation B/C26.4, and shall be reported in degrees with precision in 10^{-5} of a degree if available.

B/C26.7.2.5 Wind shear data

Absolute wind shear in 1 km layer below (0 11 061) and absolute wind shear in 1-km layer above (0 11 062) shall be reported in metres per second (with precision in tenths of a metre per second), if data for vertical wind shear are computed and required. [35.2.4.4]

B/C26.8 Data required by regional or national reporting practices

If regional or national reporting practices require inclusion of temperature, humidity and/or wind data at additional levels, these data shall be reported using sequence <3 03 054> for Temperature, dewpoint, wind at a pressure level. Regulation B/C26.5 shall apply.

Notes:

- (1) A level determined by regional decision shall be indicated by Extended vertical sounding significance 0 08 042 – bit No. 15 set to 1.
- (2) A level determined by national decision shall be indicated by Extended vertical sounding significance 0 08 042 – all bits set to 0.

B/C26.8.1 Additional data required by reporting practices

No regional requirements are indicated for reporting TEMP DROP data in the *Manual on Codes* (WMO-No. 306), Volume II.

B/C30 – Regulations for reporting CLIMAT data in TDCF

TM 307073 – BUFR template for reports of monthly values from a land station suitable for CLIMAT data

		Representation of CLIMAT data of the actual month and for monthly normals
3 07 073	3 07 071	Monthly values from a land station
	3 07 072	Monthly normals for a land station

				Unit, scale
Monthly values of a land station (data of CLIMAT Sections 0, 1, 3 and 4) Sequence BUFR descriptor <3 07 071> expands as shown in the leftmost column below.				
			Surface station identification; time, horizontal and vertical coordinates	
			<i>Surface station identification</i>	
3 01 090	3 01 004	0 01 001	WMO block number	Numeric, 0
		0 01 002	WMO station number	Numeric, 0
		0 01 015	Station or site name	CCITT IA5, 0
		0 02 001	Type of station	Code table, 0
	3 01 011	0 04 001	Year (see Note 1)	Year, 0
		0 04 002	Month (see Note 1)	Month, 0
		0 04 003	Day (= 1) (see Note 1)	Day, 0
	3 01 012	0 04 004	Hour (= 0) (see Note 1)	Hour, 0
		0 04 005	Minute (= 0) (see Note 1)	Minute, 0
	3 01 021	0 05 001	Latitude (high accuracy)	Degree, 5
		0 06 001	Longitude (high accuracy)	Degree, 5
	0 07 030		Height of station ground above mean sea level	m, 1
	0 07 031		Height of barometer above mean sea level	m, 1
			Monthly mean values of pressure, temperature, extreme temperatures and vapour pressure	
0 04 074			Short time period or displacement (= UTC – LT) (see Note 1)	Hour, 0
0 04 023			Time period or displacement (= number of days in the month)	Day, 0
0 08 023			First-order statistics (= 4; mean value)	Code table, 0
0 10 004			Pressure $\overline{P_0 P_0 P_0 P_0}$	Pa, –1
0 10 051			Pressure reduced to mean sea level \overline{PPPP}	Pa, –1
0 07 004			Pressure (standard level) (for lowland stations = missing value)	Pa, –1
0 10 009			Geopotential height (of the standard level) (for lowland stations = missing value) \overline{PPPP}	gpm, 0
0 07 032			Height of sensor above local ground (or deck of marine platform) (see Note 2)	m, 2
0 12 101			Temperature/air temperature $\overline{s_n TTT}$	K, 2
0 02 051			Indicator to specify observing method for extreme temperatures (see Note 2) i_y	Code table, 0

				Unit, scale
0 04 051			Principal time of daily reading of maximum temperature $G_x G_x$	Hour, 0
0 12 118			Maximum temperature at height specified, past 24 hours $s_n T_x T_x T_x$	K, 2
0 04 052			Principal time of daily reading of minimum temperature $G_n G_n$	Hour, 0
0 12 119			Minimum temperature at height specified, past 24 hours $s_n T_n T_n T_n$	K, 2
0 13 004			Vapour pressure _____ eee	Pa, -1
0 08 023			First-order statistics (set to missing to cancel the previous value)	Code table, 0
0 12 151			Standard deviation of daily mean temperature $s_t S_t S_t$	K, 2
0 07 032			Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
			Number of days in the month for which values are missing	
1 02 005			Replicate 2 descriptors 5 times	
0 08 050			Qualifier for number of missing values in calculation of statistic (= 1; pressure) (= 2; temperature) (= 4; vapour pressure) (= 7; maximum temperature) (= 8; minimum temperature)	Code table, 0
0 08 020			Total number of missing entities (with respect to accumulation or average) (days) $m_p m_p$ (for pressure) $m_T m_T$ (for temperature) $m_e m_e$ (for vapour pressure) m_{Tx} (for maximum temperature) m_{Tn} (for minimum temperature)	Numeric, 0
			Monthly duration of sunshine	
0 14 032			Total sunshine $S_1 S_1 S_1$	Hour, 0
0 14 033			Total sunshine $p_s p_s p_s$	%, 0
0 08 050			Qualifier for number of missing values in calculation of statistic (= 6; sunshine duration)	Code table, 0
0 08 020			Total number of missing entities (with respect to accumulation or average) (days) $m_s m_s$	Numeric, 0
			Number of days with parameters beyond certain thresholds; number of days with thunderstorm and hail	
1 02 018			Replicate 2 descriptors 18 times	
0 08 052			Condition for which number of days of occurrence follows (= 0; wind $\geq 10 \text{ m s}^{-1}$) (= 1; wind $\geq 20 \text{ m s}^{-1}$) (= 2; wind $\geq 30 \text{ m s}^{-1}$) (= 3; max. T $< 273.15 \text{ K}$) (= 4; max. T $\geq 298.15 \text{ K}$) (= 5; max. T $\geq 303.15 \text{ K}$) (= 6; max. T $\geq 308.15 \text{ K}$)	Code table, 0

				Unit, scale
			(= 7; max. $T \geq 313.15 \text{ K}$) (= 8; min. $T < 273.15 \text{ K}$) (= 16; sss > 0.00 m) (= 17; sss > 0.01 m) (= 18; sss > 0.10 m) (= 19; sss > 0.50 m) (= 20; horizontal visibility < 50 m) (= 21; horizontal visibility < 100 m) (= 22; horizontal visibility < 1000 m) (= 23; hail) (= 24; thunderstorm)	
0 08 022			Total number (with respect to accumulation or average) (of days) $f_{10}f_{10}$ (wind $\geq 10 \text{ m s}^{-1}$) $f_{20}f_{20}$ (wind $\geq 20 \text{ m s}^{-1}$) $f_{30}f_{30}$ (wind $\geq 30 \text{ m s}^{-1}$) $T_{x0}T_{x0}$ ($T_x < 273.15 \text{ K}$) $T_{25}T_{25}$ ($T_x \geq 298.15 \text{ K}$) $T_{30}T_{30}$ ($T_x \geq 303.15 \text{ K}$) $T_{35}T_{35}$ ($T_x \geq 308.15 \text{ K}$) $T_{40}T_{40}$ ($T_x \geq 313.15 \text{ K}$) $T_{n0}T_{n0}$ ($T_n < 273.15 \text{ K}$) s_0s_0 (sss > 0.00 m) s_1s_1 (sss > 0.01 m) $s_{10}s_{10}$ (sss > 0.10 m) $s_{50}s_{50}$ (sss > 0.50 m) V_1V_1 (h. viz. < 50 m) V_2V_2 (h. viz. < 100 m) V_3V_3 (h. viz. < 1000 m) $D_{gr}D_{gr}$ (hail) $D_{ts}D_{ts}$ (thunderstorm)	Numeric, 0
			Occurrence of extreme values of temperature and wind speed	
0 07 032			Height of sensor above local ground (or deck of marine platform)	m, 2
0 08 053			Day of occurrence qualifier (= 0; on 1 day only) (= 1; on 2 or more days)	Code table, 0
0 04 003			Day $y_x y_x$	Day, 0
0 12 152			Highest daily mean temperature $s_n T_{xd} T_{xd} T_{xd}$	K, 2
0 08 053			Day of occurrence qualifier (= 0; on 1 day only) (= 1; on 2 or more days)	Code table, 0
0 04 003			Day $y_n y_n$	Day, 0
0 12 153			Lowest daily mean temperature $s_n T_{nd} T_{nd} T_{nd}$	K, 2
0 08 053			Day of occurrence qualifier (= 0; on 1 day only) (= 1; on 2 or more days)	Code table, 0
0 04 003			Day $y_{ax} y_{ax}$	Day, 0
0 08 023			First-order statistics (= 2; maximum value)	Code table, 0
0 12 101			Temperature/air temperature $s_n T_{ax} T_{ax} T_{ax}$	K, 2
0 08 053			Day of occurrence qualifier (= 0; on 1 day only) (= 1; on 2 or more days)	Code table, 0
0 04 003			Day $y_{an} y_{an}$	Day, 0
0 08 023			First-order statistics (= 3; minimum value)	Code table, 0
0 12 101			Temperature/air temperature $s_n T_{an} T_{an} T_{an}$	K, 2
0 08 023			First-order statistics (set to missing to cancel)	Code table, 0

				Unit, scale
			the previous value)	
0 07 032			Height of sensor above local ground (or deck of marine platform)	m, 2
0 02 002			Type of instrumentation for wind measurement	Flag table, 0
0 08 053			Day of occurrence qualifier (= 0; on 1 day only) (= 1; on 2 or more days)	Code table, 0
0 04 003			Day $y_{fx}y_{fx}$	Day, 0
0 11 046			Maximum instantaneous wind speed $f_{xf}f_x$	$m\ s^{-1}$, 1
0 08 053			Day of occurrence qualifier (set to missing to cancel the previous value)	Code table, 0
			Monthly precipitation data	
0 04 003			Day (= 1) (see Note 3)	Day, 0
0 04 004			Hour (= 6) (see Note 3)	Hour, 0
0 04 023			Time period or displacement (= number of days in the month) (see Note 3)	Day, 0
0 07 032			Height of sensor above local ground (or deck of marine platform) (see Note 2)	m, 2
0 13 060			Total accumulated precipitation $R_1R_1R_1R_1$	$kg\ m^{-2}$, 1
0 13 051			Frequency group, precipitation R_d	Code table, 0
0 04 053			Number of days with precipitation equal to or more than 1 mm $n_r n_r$	Numeric, 0
0 08 050			Qualifier for number of missing values in calculation of statistic (= 5; precipitation)	Code table, 0
0 08 020			Total number of missing entities (with respect to accumulation or average) (days) $m_R m_R$ (for precipitation)	Numeric, 0
			Number of days with precipitation beyond certain thresholds	
1 02 006			Replicate 2 descriptors 6 times	
0 08 052			Condition for which number of days of occurrence follows (= 10; precipitation $\geq 1.0\ kg\ m^{-2}$) (= 11; precipitation $\geq 5.0\ kg\ m^{-2}$) (= 12; precipitation $\geq 10.0\ kg\ m^{-2}$) (= 13; precipitation $\geq 50.0\ kg\ m^{-2}$) (= 14; precipitation $\geq 100.0\ kg\ m^{-2}$) (= 15; precipitation $\geq 150.0\ kg\ m^{-2}$)	Code table, 0
0 08 022			Total number (with respect to accumulation or average) (of days) R_1R_1 (precipitation $\geq 1.0\ kg\ m^{-2}$) R_5R_5 (precipitation $\geq 5.0\ kg\ m^{-2}$) $R_{10}R_{10}$ (precipitation $\geq 10.0\ kg\ m^{-2}$) $R_{50}R_{50}$ (precipitation $\geq 50.0\ kg\ m^{-2}$) $R_{100}R_{100}$ (precipitation $\geq 100.0\ kg\ m^{-2}$) $R_{150}R_{150}$ (precipitation $\geq 150.0\ kg\ m^{-2}$)	Numeric, 0
			Occurrence of extreme precipitation	
0 08 053			Day of occurrence qualifier (= 0; on 1 day only) (= 1; on 2 or more days)	Code table, 0
0 04 003			Day $y_r y_r$	Day, 0
0 13 052			Highest daily amount of precipitation $R_x R_x R_x$	$kg\ m^{-2}$, 1
0 07 032			Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2

				Unit, scale
Monthly normals for a land station (data of CLIMAT Section 2)				
Sequence BUFR descriptor <3 07 072> expands as shown in the leftmost column below.				
			Normals of pressure, temperatures, vapour pressure, standard deviation of daily mean temperature, and sunshine duration	
0 04 001			Year (of beginning of the reference period)	Year, 0
0 04 001			Year (of ending of the reference period)	Year, 0
0 04 002			Month	Month, 0
0 04 003			Day (= 1) (see Note 1)	Day, 0
0 04 004			Hour (= 0) (see Note 1)	Hour, 0
0 04 074			Short time period or displacement (= UTC – LT) (see Note 1)	Hour, 0
0 04 022			Time period or displacement (= 1)	Month, 0
0 08 023			First-order statistics (= 4; mean value)	Code table, 0
0 10 004			Pressure $P_0 P_0 P_0 P_0$	Pa, –1
0 10 051			Pressure reduced to mean sea level $PPPP$	Pa, –1
0 07 004			Pressure (standard level)	Pa, –1
0 10 009			Geopotential height (of the standard level) $PPPP$	gpm, 0
0 07 032			Height of sensor above local ground (or deck of marine platform) (see Note 2)	m, 2
0 12 101			Temperature/air temperature $s_n TTT$	K, 2
0 02 051			Indicator to specify observing method for extreme temperatures (see Note 2) i_y	Code table, 0
0 04 051			Principal time of daily reading of maximum temperature $G_x G_x$	Hour, 0
0 12 118			Maximum temperature at height specified, past 24 h $s_n T_x T_x T_x$	K, 2
0 04 052			Principal time of daily reading of minimum temperature $G_n G_n$	Hour, 0
0 12 119			Minimum temperature at height specified, past 24 h $s_n T_n T_n T_n$	K, 2
0 13 004			Vapour pressure eee	Pa, –1
0 12 151			Standard deviation of daily mean temperature $S_t S_t S_t$	K, 2
0 07 032			Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
0 14 032			Total sunshine $S_1 S_1 S_1$	Hour, 0
0 08 023			First-order statistics (set to missing to cancel the previous value)	Code table, 0
			Normals of precipitation	
0 04 001			Year (of beginning of the reference period)	Year, 0
0 04 001			Year (of ending of the reference period)	Year, 0
0 04 002			Month	Month, 0
0 04 003			Day (= 1) (see Note 3)	Day, 0

				Unit, scale
0 04 004			Hour (= 6) (see Note 3)	Hour, 0
0 04 022			Time period or displacement (= 1)	Month, 0
0 07 032			Height of sensor above local ground (or deck of marine platform) (see Note 2)	m, 2
0 08 023			First-order statistics (= 4; mean value)	Code table, 0
0 13 060			Total accumulated precipitation $R_1 R_1 R_1 R_1$	kg m ⁻² , 1
0 04 053			Number of days with precipitation equal to or more than 1 mm $n_r n_r$	Numeric, 0
0 08 023			First-order statistics (set to missing to cancel the previous value)	Code table, 0
			Number of missing years	
1 02 008			Replicate 2 descriptors 8 times	
0 08 050			Qualifier for number of missing values in calculation of statistic (= 1; pressure) (= 2; temperature) (= 3; extreme temperatures) (see Note 4) (= 4; vapour pressure) (= 5; precipitation) (= 6; sunshine duration) (= 7; maximum temperature) (see Note 4) (= 8; minimum temperature) (see Note 4)	Code table, 0
0 08 020			Total number of missing entities (with respect to accumulation or average) (years) $y_P y_P$ (for pressure) $y_T y_T$ (for temperature) $y_{Tx} y_{Tx}$ (for extreme temperatures) (see Note 4) $y_e y_e$ (for vapour pressure) $y_R y_R$ (for precipitation) $y_S y_S$ (for sunshine duration) for maximum temperature (see Note 4) for minimum temperature (see Note 4)	Numeric, 0

Notes:

- (1) The time identification refers to the beginning of the one-month period. Except for precipitation measurements, the one-month period is recommended to correspond to the local time (LT) month.
- (2) If the height of the sensor or observing method for extreme temperatures was changed during the period specified, the value shall be that which existed for the greater part of the period.
- (3) In case of precipitation measurements, the one-month period begins at 06 UTC on the first day of the month and ends at 06 UTC on the first day of the following month.
- (4) The number of missing years within the reference period from the calculation of normal for mean extreme air temperature should be given, if available, for both the calculation of normal maximum temperature and for the calculation of normal minimum temperature in addition to the number of missing years for the extreme air temperatures reported under 0 08 020 preceded by 0 08 050 in which the figure 3 is used.

Regulations:

B/C30.1	Section 1 of BUFR or CREX
B/C30.2	Monthly values of a land station
B/C30.2.1	Surface station identification; time, horizontal and vertical coordinates
B/C30.2.2	Monthly mean values of pressure, temperature, extreme temperatures and vapour pressure; standard deviation of daily mean temperature
B/C30.2.3	Monthly duration of sunshine
B/C30.2.4	Number of days with parameters beyond certain thresholds; number of days with thunderstorm and hail
B/C30.2.5	Occurrence of extreme values of temperature and wind speed
B/C30.2.6	Monthly precipitation data
B/C30.2.7	Number of days with precipitation beyond certain thresholds
B/C30.2.8	Occurrence of extreme precipitation
B/C30.3	Monthly normals for a land station
B/C30.3.1	Normals of pressure, temperatures, vapour pressure, standard deviation of daily mean temperature, and sunshine duration
B/C30.3.2	Normals of precipitation
B/C30.3.3	Number of missing years
B/C30.4	Regional or national reporting practices

B/C30.1 Section 1 of BUFR or CREX

B/C30.1.1 Entries required in Section 1 of BUFR

The following entries shall be included in BUFR Section 1:

- BUFR master table;
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Identification of inclusion of optional section;
- Data category (000 for CLIMAT data);
- International data sub-category (see Note 1);
- Local data sub-category;
- Version number of master table;
- Version number of local tables;
- Year (see Notes 2 and 4);
- Month (for which the monthly values are reported) (see Note 2);
- Day (01) (see Note 2);
- Hour (00) (see Note 2);
- Minute (00) (see Note 2);
- Second (00) (see Note 2).

Notes:

- (1) If required, the international data sub-category shall be included for CLIMAT data as 020.
- (2) The time identification refers to the beginning of the month for which the monthly mean values are reported.
- (3) If an NMHS performs conversion of CLIMAT data produced by another NMHS, originating centre in Section 1 shall indicate the converting centre and originating sub-centre shall indicate the producer of CLIMAT bulletins. The producer of CLIMAT bulletins shall be specified in Common Code table C–12 as a sub-centre of the originating centre, i.e. of the NMHS executing the conversion.
- (4) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C30.1.2 Entries required in Section 1 of CREX

The following entries shall be included in CREX Section 1:

- CREX master table;
- CREX edition number;
- CREX table version number;
- Version number of BUFR master table;
- Version number of local tables;
- Data category (000 for CLIMAT data);
- International data sub-category (see Note 1);
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Number of subsets;
- Year (see Notes 2 and 4);
- Month (for which the monthly values are reported) (see Note 2);
- Day (01) (see Note 2);
- Hour (00) (see Note 2);
- Minute (00) (see Note 2).

Notes:

- (1) If inclusion of the international data sub-category is required, Note 1 under Regulation B/C30.1.1 applies.
- (2) Note 2 under Regulation B/C30.1.1 applies.
- (3) If an NMHS performs conversion of CLIMAT data produced by another NMHS, Note 3 under Regulation B/C30.1.1 applies.
- (4) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C30.2 Monthly values from a land station <3 07 071>**B/C30.2.1 Surface station identification; time, horizontal and vertical coordinates <3 01 090>****B/C30.2.1.1 Station identification**

WMO block number station (0 01 001) and WMO station number (0 01 002) shall be always reported as a non-missing value.

Station or site name (0 01 015) shall be reported as published in *Weather Reporting* (WMO-No. 9), Volume A – Observing Stations, provided that the station name does not exceed 20 characters. A shortened version of the name shall be reported otherwise.

Type of station (0 02 001) shall be reported to indicate the type of the station operation (manned, automatic or hybrid).

B/C30.2.1.2 Date/time (of beginning of the month)

Date <3 01 011> and time <3 01 012> shall be reported, i.e. year (0 04 001), month (0 04 002), day (0 04 003) and hour (0 04 004), minute (0 04 005) of beginning of the month for which the monthly values are reported. Day (0 04 003) shall be set to 1 and both hour (0 04 004) and minute (0 04 005) shall be set to 0.

B/C30.2.1.3 Horizontal and vertical coordinates

Latitude (0 05 001) and longitude (0 06 001) of the station shall be reported in degrees with precision in 10^{-5} of a degree.

Height of station ground above mean sea level (0 07 030) and height of barometer above mean sea level (0 07 031) shall be reported in metres with precision in tenths of a metre.

Note: The official altitude of the aerodrome (HA in Volume A) shall not be used to report Height of station ground above mean sea level 0 07 030 in BUFR or CREX messages from aerodromes. Those are two different vertical coordinates. "Height of station ground above mean sea level" for each station should be made available to the encoding centre concerned, which may be a centre within the same NMHS or other NMC/RTH.

B/C30.2.2 Monthly mean values of pressure, temperature, extreme temperatures and vapour pressure; standard deviation of daily mean temperature

The monthly mean values of pressure, pressure reduced to mean sea level or geopotential height, temperature, extreme temperatures and vapour pressure shall be reported. Any missing element shall be reported as a missing value.

B/C30.2.2.1 Reference period for the data of the month

Monthly data (with the exception of precipitation data) are recommended to be reported for one-month period, corresponding to the local time (LT) month [*Handbook on CLIMAT and CLIMAT TEMP Reporting* (WMO/TD-No.1188)]. In that case, short time displacement (0 04 074) shall specify the difference between UTC and LT (set to *non-positive values in the eastern hemisphere, non-negative values in the western hemisphere*).

Time period (0 04 023) represents the number of days in the month for which the data are reported, and shall be expressed as a *positive value* in days.

Note: A BUFR (or CREX) message shall contain reports for one specific month only. [71.1.4]

B/C30.2.2.2 First-order statistics – Code table 0 08 023

This datum shall be set to 4 (mean value) to indicate that the following entries represent mean values of the elements (pressure, pressure reduced to mean sea level or geopotential height, temperature, extreme temperatures and vapour pressure) averaged over the one-month period.

B/C30.2.2.3 Monthly mean value of pressure

Monthly mean value of pressure shall be reported using 0 10 004 (Pressure) in pascals (with precision in tens of pascals).

B/C30.2.2.4 Monthly mean value of pressure reduced to mean sea level

Monthly mean value of pressure reduced to mean sea level shall be reported using 0 10 051 (Pressure reduced to mean sea level) in pascals (with precision in tens of pascals), if the air pressure at mean sea level can be computed with reasonable accuracy.

B/C30.2.2.5 Monthly mean value of geopotential height

Monthly mean value of geopotential height of a standard level shall be reported using 0 10 009 (Geopotential height) in geopotential metres from high-level stations which cannot give pressure at mean sea level to a satisfactory degree of accuracy. The standard isobaric level is specified by the preceding entry Pressure (0 07 004).

B/C30.2.2.6 Height of sensor above local ground

Height of sensor above local ground (0 07 032) for temperature and humidity measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of temperature and humidity sensors above ground at the point where the sensors are located.

Note: If the height of the sensor was changed during the period specified, the value shall be that which existed for the greater part of the period.

B/C30.2.2.7 Monthly mean value of temperature

Monthly mean value of temperature shall be reported using 0 12 101 (Temperature/air temperature) in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Temperature data shall be reported with precision in hundredths of a degree even if they are available with the accuracy in tenths of a degree.

Notes:

- (1) This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

B/C30.2.2.8 Indicator to specify observing method for extreme temperatures – Code table 0 02 051

This datum shall be set to 1 (maximum/minimum thermometers) or to 2 (automated instruments) or to 3 (thermograph) to indicate observing method for extreme temperatures.

Note: If the observing method for extreme temperatures was changed during the period specified, the code figure shall be that which existed for the greater part of the period.

B/C30.2.2.9 Monthly mean value of maximum temperature

Monthly mean value of maximum temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.
- (2) The monthly mean value of maximum temperature shall be reported using 0 12 118 (Maximum temperature at height specified, past 24 hours). The height is specified by the preceding entry 0 07 032. Principal time of daily reading of maximum temperature (0 04 051) indicates the end of the 24-hour period to which the daily maximum temperature refers.

B/C30.2.2.10 Monthly mean value of minimum temperature

Monthly mean value of minimum temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.
- (2) The monthly mean value of minimum temperature shall be reported using 0 12 119 (Minimum temperature at height specified, past 24 hours). The height is specified by

the preceding entry 0 07 032. Principal time of daily reading of minimum temperature (0 04 052) indicates the end of the 24-hour period to which the daily minimum temperature refers.

B/C30.2.2.11 Monthly mean value of vapour pressure

Monthly mean value of vapour pressure shall be reported using 0 13 004 (Vapour pressure) in pascals (with precision in tens of pascals).

B/C30.2.2.12 First-order statistics – Code table 0 08 023

This datum shall be set to missing to indicate that the following entries do not represent the monthly mean values.

B/C30.2.2.13 Standard deviation of daily mean temperature

Standard deviation of daily mean temperature (0 12 151) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). [71.3.1]

B/C30.2.2.14 Number of days in the month for which values are missing

Number of days in the month for which values are missing shall be reported using Total number of missing entities (0 08 020) being preceded by Qualifier for number of missing values in calculation of statistic (0 08 050) in each of the required five replications (1 02 005).

Qualifier for number of missing values in calculation of statistic (0 08 050) is:

- Set to 1 (pressure) in the first replication;
- Set to 2 (temperature) in the second replication;
- Set to 4 (vapour pressure) in the third replication;
- Set to 7 (maximum temperature) in the fourth replication;
- Set to 8 (minimum temperature) in the fifth replication.

The number of days in the month for which values of the parameter are missing, shall be reported using 0 08 020 in the corresponding replication.

B/C30.2.3 Monthly duration of sunshine

B/C30.2.3.1 Total sunshine duration

The monthly values of total duration of sunshine shall be reported in hours using Total sunshine (0 14 032) and the percentage of the normal that that value represents shall be reported using Total sunshine (0 14 033). Any missing element shall be reported as a missing value.

Notes:

- (1) If the percentage of the normal is 1% or less but greater than 0, Total sunshine 0 14 033 shall be set to 1.
- (2) If the normal is zero hours, *Total sunshine 0 14 033 shall be set to 510.*
- (3) If the normal is not defined, Total sunshine 0 14 033 shall be set to missing.

[71.3.3]

B/C30.2.3.2 Number of days in the month for which sunshine data are missing

Number of days in the month for which sunshine data are missing shall be reported using Total number of missing entities (0 08 020) being preceded by Qualifier for number of missing values in calculation of statistic (0 08 050) set to 6 (sunshine duration).

B/C30.2.4 Number of days with parameters beyond certain thresholds; number of days with thunderstorm and hail

Number of days in the month with parameters beyond certain thresholds and with thunderstorm and hail shall be reported using Total number (0 08 022) being preceded by Condition for which number of days of occurrence follows (0 08 052) in each of the required eighteen replications (1 02 018).

Condition for which number of days of occurrence follows (0 08 052) is:

- Set to 0 (mean wind speed over 10-minute period $\geq 10 \text{ m s}^{-1}$);
- Set to 1 (mean wind speed over 10-minute period $\geq 20 \text{ m s}^{-1}$);
- Set to 2 (mean wind speed over 10-minute period $\geq 30 \text{ m s}^{-1}$);
- Set to 3 (maximum temperature $< 273.15 \text{ K}$);
- Set to 4 (maximum temperature $\geq 298.15 \text{ K}$);
- Set to 5 (maximum temperature $\geq 303.15 \text{ K}$);
- Set to 6 (maximum temperature $\geq 308.15 \text{ K}$);
- Set to 7 (maximum temperature $\geq 313.15 \text{ K}$);
- Set to 8 (minimum temperature $< 273.15 \text{ K}$);
- Set to 16 (snow depth $> 0.00 \text{ m}$);
- Set to 17 (snow depth $> 0.01 \text{ m}$);
- Set to 18 (snow depth $> 0.10 \text{ m}$);
- Set to 19 (snow depth $> 0.50 \text{ m}$);
- Set to 20 (horizontal visibility $< 50 \text{ m}$);
- Set to 21 (horizontal visibility $< 100 \text{ m}$);
- Set to 22 (horizontal visibility $< 1\,000 \text{ m}$);
- Set to 23 (occurrence of hail);
- Set to 24 (occurrence of thunderstorm) in the last replication.

The number of days in the month with parameters beyond the specified thresholds and with thunderstorm and hail shall be reported using 0 08 022 in the corresponding replication.

Note: Number of days in the month with horizontal visibility beyond the specified thresholds is the number of days with visibility less than 50, 100 and 1 000 m, respectively, *irrespective of the duration of the period* during which horizontal visibility below the specified thresholds was observed or recorded.

B/C30.2.5 Occurrence of extreme values of temperature and wind speed

B/C30.2.5.1 Height of sensor above local ground (for temperature)

Height of sensor above local ground (0 07 032) for temperature measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of temperature sensor above ground at the point where the sensor is located.

B/C30.2.5.2 Occurrence of the highest daily mean temperature

The day on which the highest daily mean temperature occurred shall be reported using Day (0 04 003). If the highest daily mean temperature occurred on only one day, the preceding entry 0 08 053 (Day of occurrence qualifier) shall be set to 0. If the highest daily mean temperature occurred on more than one day, the first day shall be reported for 0 04 003 and the preceding entry 0 08 053 shall be set to 1. [71.6.1]

Highest daily mean temperature (0 12 152) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.

B/C30.2.5.3 Occurrence of the lowest daily mean temperature

The day on which the lowest daily mean temperature occurred shall be reported using Day (0 04 003). If the lowest daily mean temperature occurred on only one day, the preceding entry 0 08 053 (Day of occurrence qualifier) shall be set to 0. If the lowest daily mean temperature occurred on more than one day, the first day shall be reported for 0 04 003 and the preceding entry 0 08 053 shall be set to 1. [71.6.1]

Lowest daily mean temperature (0 12 153) shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.

B/C30.2.5.4 Occurrence of the highest air temperature of the month

The day on which the highest air temperature occurred shall be reported using Day (0 04 003). If the highest air temperature occurred on only one day, the preceding entry 0 08 053 (Day of occurrence qualifier) shall be set to 0. If the highest air temperature occurred on more than one day, the first day shall be reported for 0 04 003 and the preceding entry 0 08 053 shall be set to 1. [71.6.1]

The highest air temperature of the month shall be reported using 0 12 101 (Temperature/air temperature), preceded by first-order statistics (0 08 023) set to 2 (maximum value). The temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.

B/C30.2.5.5 Occurrence of the lowest air temperature of the month

The day on which the lowest air temperature occurred shall be reported using Day (0 04 003). If the lowest air temperature occurred on only one day, the preceding entry 0 08 053 (Day of occurrence qualifier) shall be set to 0. If the lowest air temperature occurred on more than one day, the first day shall be reported for 0 04 003 and the preceding entry 0 08 053 shall be set to 1. [71.6.1]

The lowest air temperature of the month shall be reported using 0 12 101 (Temperature/air temperature), preceded by first-order statistics (0 08 023) set to 3 (minimum value). The temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.

B/C30.2.5.6 Height of sensor above local ground (for wind measurement)

Height of sensor above local ground (0 07 032) for wind measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of wind sensors above ground at the point where the sensors are located.

B/C30.2.5.7 Type of instrumentation for wind measurement – Flag table 0 02 002

This datum shall be used to specify whether the wind speed was measured by certified instruments (bit No. 1 set to 1) or estimated on the basis of the Beaufort wind scale (bit No. 1 set to 0), and to indicate the original units for wind speed measurement. Bit No. 2 set to 1 indicates that wind speed was originally measured in knots and bit No. 3 set to 1 indicates that wind speed was originally measured in kilometres per hour. Setting both bits No. 2 and No. 3 to 0 indicates that wind speed was originally measured in metres per second.

In CREX, type of instrumentation for wind measurement (0 02 002) shall be reported in octal representation. For example, if wind speed was measured by instruments in knots (bit No. 1 and bit No. 2 set to 1), then this datum shall be reported as 14.

B/C30.2.5.8 Occurrence of the highest instantaneous wind speed of the month

The day on which the highest instantaneous wind speed occurred shall be reported using Day (0 04 003). If the highest instantaneous wind speed occurred on only one day, the preceding entry 0 08 053 (Day of occurrence qualifier) shall be set to 0. If the highest instantaneous wind speed occurred on more than one day, the first day shall be reported for 0 04 003 and the preceding entry 0 08 053 shall be set to 1. [71.6.1]

The highest instantaneous wind speed of the month shall be reported using 0 11 046 (Maximum instantaneous wind speed) in metres per second (with precision in tenths of a metre per second).

B/C30.2.6 Monthly precipitation data**B/C30.2.6.1 Date/time (of beginning of the one-month period for precipitation data)**

Day (0 04 003) and hour (0 04 004) of the beginning of the one-month period for monthly precipitation data are reported. Day (0 04 003) shall be set to 1 and hour (0 04 004) shall be set to 6.

Notes:

- (1) In case of precipitation measurements, a month begins at 0600 hours UTC on the first day of the month and ends at 0600 hours UTC on the first day of the following month [*Handbook on CLIMAT and CLIMAT TEMP Reporting* (WMO/TD-No.1188)].
- (2) Year (0 04 001), month (0 04 002) and minute (0 04 005) of the beginning of the one-month period specified in the Regulation B/C30.2.1.2 apply.

B/C30.2.6.2 Period of reference for precipitation data of the month

Time period (0 04 023) represents the number of days in the month for which the monthly mean data are reported, and shall be expressed as a *positive value* in days.

Note: A BUFR (or CREX) message shall contain reports for one specific month only. [71.1.4]

B/C30.2.6.3 Height of sensor above local ground

Height of sensor above local ground (0 07 032) for precipitation measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the rain gauge rim above ground at the point where the rain gauge is located.

Note: If the height of the sensor was changed during the period specified, the value shall be that which existed for the greater part of the period.

B/C30.2.6.4 Total amount of precipitation of the month

Total accumulated precipitation (0 13 060) which has fallen during the month shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre).

Note: Trace shall be reported as “–0.1 kg m⁻²”.

B/C30.2.6.5 Indication of frequency group

Frequency group in which the total amount of precipitation of the month falls shall be reported using Code table 0 13 051 (Frequency group; precipitation).

Note: If for a particular month the total amount of precipitation is zero, the code figure for 0 13 051 shall be given by the highest number of quintile which has 0.0 as lower limit (e.g. in months with no rainfall in the 30-year period, 0 13 051 shall be set to 5). [71.3.2]

B/C30.2.6.6 Number of days with precipitation equal to or greater than 1 mm

Number of days in the month with precipitation equal to or greater than 1 kilogram per square metre shall be reported using 0 04 053 (Number of days in the month with precipitation equal to or greater than 1 mm).

B/C30.2.6.7 Number of days in the month for which precipitation data is missing

Number of days in the month for which precipitation is missing shall be reported using Total number of missing entities (0 08 020) being preceded by Qualifier for number of missing values in calculation of statistic (0 08 050) set to 5 (precipitation).

B/C30.2.7 Number of days with precipitation beyond certain thresholds

Number of days in the month with precipitation beyond certain thresholds shall be reported using Total number (0 08 022) being preceded by Condition for which number of days of occurrence follows (0 08 052) in each of the required six replications (1 02 006).

Condition for which number of days of occurrence follows (0 08 052) is:

- Set to 10 (precipitation $\geq 1.0 \text{ kg m}^{-2}$) in the first replication;
- Set to 11 (precipitation $\geq 5.0 \text{ kg m}^{-2}$);
- Set to 12 (precipitation $\geq 10.0 \text{ kg m}^{-2}$);
- Set to 13 (precipitation $\geq 50.0 \text{ kg m}^{-2}$);
- Set to 14 (precipitation $\geq 100.0 \text{ kg m}^{-2}$);
- Set to 15 (precipitation $\geq 150.0 \text{ kg m}^{-2}$) in the last replication.

The number of days in the month with precipitation beyond the specified thresholds shall be reported using 0 08 022 in the corresponding replication.

B/C30.2.8 Occurrence of extreme precipitation

The day on which the highest daily amount of precipitation occurred shall be reported using Day (0 04 003). If the highest daily amount of precipitation occurred on only one day, the preceding entry 0 08 053 (Day of occurrence qualifier) shall be set to 0. If the highest daily amount of precipitation occurred on more than one day, the first day shall be reported for 0 04 003 and the preceding entry 0 08 053 shall be set to 1. [71.6.1]

Highest daily amount of precipitation (0 13 052) shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre).

Note: Trace shall be reported as “–0.1 kg m⁻²”.

B/C30.3 Monthly normals for a land station <3 07 072>

Meteorological Services shall submit to the Secretariat complete normal data of the elements for stations to be included in the CLIMAT bulletins. The same shall apply when Services consider it necessary to make amendments to previously published normal values. [71.4.1]

B/C30.3.1 Normals of pressure, temperatures, vapour pressure, standard deviation of daily mean temperature, and sunshine duration

Normal values of pressure, pressure reduced to mean sea level or geopotential height, temperature, extreme temperatures, vapour pressure, standard deviation of daily mean temperature, and sunshine duration shall be reported. Any missing element shall be reported as a missing value.

B/C30.3.1.1 Reference period for normal data

Reference period for calculation of the normal values of the elements shall be reported using two consecutive entries 0 04 001 (Year). The first 0 04 001 shall express the year of beginning of the reference period and the second 0 04 001 shall express the year of ending of the reference period.

Note: The normal data reported shall be deduced from observations made over a specific period defined by the *Technical Regulations* (WMO-No. 49). [71.4.2]

B/C30.3.1.2 Specification of the one-month period for which normals are reported

The one-month period for which the normal values are reported shall be specified by month (0 04 002), day (0 04 003) being set to 1, hour (0 04 004) being set to 0, short time displacement (0 04 074) being set to (UTC – LT) and time period (0 04 022) being set to 1, i.e. 1 month.

Short time displacement (0 04 074) shall be set to *non-positive values in the eastern hemisphere, non-negative values in the western hemisphere*.

B/C30.3.1.3 First-order statistics – Code table 0 08 023

This datum shall be set to 4 (mean value) to indicate that the following entries represent mean values of the elements (pressure, pressure reduced to mean sea level or geopotential height, temperature, extreme temperatures, vapour pressure, standard deviation of daily mean temperature and sunshine duration) averaged over the reference period specified in Regulation B/C30.3.1.1.

B/C30.3.1.4 Normal value of pressure

Normal value of pressure shall be reported using 0 10 004 (Pressure) in pascals (with precision in tens of pascals).

B/C30.3.1.5 Normal value of pressure reduced to mean sea level

Normal value of pressure reduced to mean sea level shall be reported using 0 10 051 (Pressure reduced to mean sea level) in pascals (with precision in tens of pascals), if the air pressure at mean sea level can be computed with reasonable accuracy.

B/C30.3.1.6 Normal value of geopotential height

Normal value of geopotential height of a standard level shall be reported using 0 10 009 (Geopotential height) in geopotential metres from high-level stations which cannot give pressure at mean sea level to a satisfactory degree of accuracy. The standard isobaric level is specified by the preceding entry Pressure (0 07 004).

B/C30.3.1.7 Height of sensor above local ground

Regulation B/C30.2.2.6 shall apply.

B/C30.3.1.8 Normal value of temperature

Normal value of temperature shall be reported using 0 12 101 (Temperature/air temperature) in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.

B/C30.3.1.9 Indicator to specify observing method for extreme temperatures – Code table 0 02 051

Regulation B/C30.2.2.8 shall apply.

B/C30.3.1.10 Normal value of maximum temperature

Normal value of maximum temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

(1) Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.

(2) Note 2 under Regulation B/C30.2.2.9 shall apply.

B/C30.3.1.11 Normal value of minimum temperature

Normal value of minimum temperature shall be reported in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

(1) Notes 1 and 2 under Regulation B/C30.2.2.7 shall apply.

(2) Note 2 under Regulation B/C30.2.2.10 shall apply.

B/C30.3.1.12 Normal value of vapour pressure

Normal value of vapour pressure shall be reported using 0 13 004 (Vapour pressure) in pascals (with precision in tens of pascals).

B/C30.3.1.13 Normal value of standard deviation of daily mean temperature

Normal value of standard deviation of daily mean temperature shall be reported using 0 12 151 in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

B/C30.3.1.14 Normal of monthly sunshine duration

Normal of monthly sunshine duration shall be reported in hours using 0 14 032 (Total sunshine).

B/C30.3.2 Normals of precipitation

Normal values of monthly amount of precipitation and of number of days in the month with precipitation equal to or greater than 1 mm, shall be reported. Any missing element shall be reported as a missing value.

B/C30.3.2.1 Reference period for normal values of precipitation

Reference period for calculation of the normal values of precipitation shall be reported using two consecutive entries 0 04 001 (Year). The first 0 04 001 shall express the year of beginning of the reference period and the second 0 04 001 shall express the year of ending of the reference period.

Note: The note under Regulation B/C30.3.1.1 shall apply.

B/C30.3.2.2 Specification of the one-month period for which normals are reported

The one-month period for which the normals of precipitation are reported shall be specified by month (0 04 002), day (0 04 003) being set to 1, hour (0 04 004) *being set to 6* and time period (0 04 022) being set to 1, i.e. 1 month.

Note: Note 1 under Regulation B/C30.2.6.1 shall apply.

B/C30.3.2.3 Height of sensor above local ground

Regulation B/C30.2.6.3 shall apply.

B/C30.3.2.4 First-order statistics – Code table 0 08 023

This datum shall be set to 4 (mean value) to indicate that the following entries represent mean values of precipitation data, averaged over the reference period specified in Regulation B/C30.3.2.1.

B/C30.3.2.5 Normal value of monthly amount of precipitation

Normal value of monthly amount of precipitation shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre) using 0 13 060 (Total accumulated precipitation).

Note: Trace shall be reported as “–0.1 kg m⁻²”.

B/C30.3.2.6 Normal value of number of days with precipitation ≥ 1 mm

Normal value of number of days in the month with precipitation equal to or greater than 1 kilogram per square metre shall be reported using 0 04 053 (Number of days in the month with precipitation equal to or greater than 1 mm).

B/C30.3.3 Number of missing years

Number of missing years within the reference period shall be reported using Total number of missing entities (0 08 020) being preceded by Qualifier for number of missing values in calculation of statistic (0 08 050) in each of the required eight replications (1 02 008).

Qualifier for number of missing values in calculation of statistic (0 08 050) is:

- Set to 1 (pressure) in the first replication;
- Set to 2 (temperature);
- Set to 3 (extreme temperatures);
- Set to 4 (vapour pressure);
- Set to 5 (precipitation);
- Set to 6 (sunshine duration);
- Set to 7 (maximum temperature);
- Set to 8 (minimum temperature) in the last replication.

The number of missing years within the reference period for calculation of the normal values of the element shall be reported using 0 08 020 in the corresponding replication.

Note: The number of missing years within the reference period from the calculation of normal for mean extreme air temperature should be given, if available, for both the calculation of normal maximum temperature and for the calculation of normal minimum temperature in addition to the number of missing years for the extreme air temperatures reported under 0 08 020 preceded by 0 08 050 in which Figure 3 is used.

B/C30.4 Regional or national reporting practices

B/C30.4.1 Data required by regional or national reporting practices

No additional data are currently required by regional or national reporting practices for CLIMAT data in the *Manual on Codes* (WMO-No. 306), Volume II.

B/C30.4.2 Reference period for the data of the month

If the regional or national reporting practices require reporting monthly data (with the exception of precipitation data) for one-month period different from the local time month as recommended in Regulation B/C30.2.2.1, short time displacement (0 04 074) shall be adjusted accordingly.

B/C30.4.3 Date/time (of beginning of the period for monthly precipitation data)

If the regional or national reporting practices require reporting monthly precipitation data for period different from the period recommended in Note 1 to Regulation B/C30.2.6.1, then hour (0 04 004) shall be adjusted accordingly. This regulation does not apply if the beginning of the period for monthly precipitation data starts on the last day of the previous month in UTC.

B/C30.4.4 Date/time (of beginning of the one-month period for precipitation data on the last day of the previous month)

If the regional or national reporting practices require reporting monthly precipitation data for period which starts on the last day of the previous month in UTC, template TM 307078 should be used. The beginning of the period for monthly precipitation data shall be specified by short time displacement (0 04 074) set to a relevant negative value. The beginning of one-month period for which the normals of precipitation are reported, shall be specified in a similar way.

Provisional Copy
2023

B/C32 – Regulations for reporting CLIMAT SHIP data in TDCF

TM 308013 – BUFR template for reports of monthly values from an ocean weather station suitable for CLIMAT SHIP data

		Representation of CLIMAT SHIP data of the actual month and for monthly normals
3 08 013	3 08 011	Monthly values from an ocean weather station – CLIMAT SHIP
	3 08 012	Monthly normals for an ocean weather station

			Unit, scale
Monthly values from an ocean weather station (data of CLIMAT SHIP Section 1) Sequence BUFR descriptor <3 08 011> expands as shown in the leftmost column below.			
		Station identification, date/time, horizontal and vertical coordinates	
0 01 011		Ship or mobile land station identifier	CCITT IA5, 0
0 02 001		Type of station	Code table, 0
3 01 011	0 04 001	Year (see Note 1)	Year, 0
	0 04 002	Month (see Note 1)	Month, 0
	0 04 003	Day (= 1) (see Note 1)	Day, 0
3 01 012	0 04 004	Hour (= 0) (see Note 1)	Hour, 0
	0 04 005	Minute (= 0) (see Note 1)	Minute, 0
3 01 023	0 05 002	Latitude (coarse accuracy) $L_a L_a L_a$	Degree, 2
	0 06 002	Longitude (coarse accuracy) $L_o L_o L_o L_o$	Degree, 2
0 07 030		Height of station ground (platform) above mean sea level	m, 1
0 07 031		Height of barometer above mean sea level	m, 1
		Monthly mean values of pressure, temperature, vapour pressure and sea/water temperature	
0 04 074		Short time period or displacement (= UTC – LT) (see Note 1)	Hour, 0
0 04 023		Time period or displacement (= number of days in the month)	Day, 0
0 08 023		First-order statistics (= 4; mean value)	Code table, 0
0 10 051		Pressure reduced to mean sea level \overline{PPPP}	Pa, –1
0 07 032		Height of sensor above local ground (or deck of marine platform) (for temperature measurement) (see Note 2)	m, 2
0 07 033		Height of sensor above water surface (for temperature measurement) (see Note 2)	m, 1
0 12 101		Temperature/air temperature $\overline{s_n TTT}$	K, 2
0 13 004		Vapour pressure \overline{eee}	Pa, –1
0 07 032		Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
0 07 033		Height of sensor above water surface (set to missing to cancel the previous value)	m, 1

			Unit, scale
		<i>Sea-surface temperature, method of measurement, and depth below sea surface</i>	
3 02 056	0 02 038	Method of water temperature and/or salinity measurement (see Note 2)	Code table, 0
	0 07 063	Depth below sea/water surface (cm) (for sea-surface temperature measurement) (see Note 2)	m, 2
	0 22 043	Sea/water temperature $\overline{s_n T_w T_w T_w}$	K, 2
	0 07 063	Depth below sea/water surface (cm) (set to missing to cancel the previous value)	m, 2
0 08 023		First-order statistics (set to missing to cancel the previous value)	Code table, 0
		Monthly precipitation data	
0 04 003		Day (= 1) (see Note 3)	Day, 0
0 04 004		Hour (= 6) (see Note 3)	Hour, 0
0 04 023		Time period or displacement (= number of days in the month) (see Note 3)	Day, 0
0 07 032		Height of sensor above local ground (or deck of marine platform) (see Note 2)	m, 2
0 13 060		Total accumulated precipitation $R_1 R_1 R_1 R_1$	kg m ⁻² , 1
0 13 051		Frequency group, precipitation R_d	Code table, 0
0 04 053		Number of days with precipitation equal to or more than 1 mm $n_r n_r$	Numeric, 0
0 07 032		Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
Monthly normals for an ocean weather station (data of CLIMAT SHIP Section 2)			
Sequence BUFR descriptor <3 08 012> expands as shown in the leftmost column below.			
		Normals of pressure, temperature, vapour pressure and sea/water temperature	Unit, scale
0 04 001		Year (of beginning of the reference period)	Year, 0
0 04 001		Year (of ending of the reference period)	Year, 0
0 04 002		Month	Month, 0
0 04 003		Day (= 1) (see Note 1)	Day, 0
0 04 004		Hour (= 0) (see Note 1)	Hour, 0
0 04 074		Short time period or displacement (= UTC – LT) (see Note 1)	Hour, 0
0 04 022		Time period or displacement (= 1)	Month, 0
0 08 023		First-order statistics (= 4; mean value)	Code table, 0
0 10 051		Pressure reduced to mean sea level \overline{PPPP}	Pa, –1
0 07 032		Height of sensor above local ground (or deck of marine platform) (for temperature measurement) (see Note 2)	m, 2
0 07 033		Height of sensor above water surface (for temperature measurement) (see Note 2)	m, 1
0 12 101		Temperature/air temperature $\overline{s_n TTT}$	K, 2
0 13 004		Vapour pressure \overline{eee}	Pa, –1

			Unit, scale
0 07 032		Height of sensor above local ground (or deck of marine platform) (set to missing to cancel the previous value)	m, 2
0 07 033		Height of sensor above water surface (set to missing to cancel the previous value)	m, 1
		<i>Sea-surface temperature, method of measurement, and depth below sea surface</i>	
3 02 056	0 02 038	Method of water temperature and/or salinity measurement (see Note 2)	Code table, 0
	0 07 063	Depth below sea/water surface (cm) (for sea-surface temperature measurement) (see Note 2)	m, 2
	0 22 043	Sea/water temperature $\overline{s_n T_w T_w T_w}$	K, 2
	0 07 063	Depth below sea/water surface (cm) (set to missing to cancel the previous value)	m, 2
0 08 023		First-order statistics (set to missing to cancel the previous value)	Code table, 0
		Normals of precipitation	
0 04 001		Year (of beginning of the reference period)	Year, 0
0 04 001		Year (of ending of the reference period)	Year, 0
0 04 002		Month	Month, 0
0 04 003		Day (= 1) (see Note 3)	Day, 0
0 04 004		Hour (= 6) (see Note 3)	Hour, 0
0 04 022		Time period or displacement (= 1)	Month, 0
0 07 032		Height of sensor above local ground (or deck of marine platform) (for precipitation measurement) (see Note 2)	m, 2
0 08 023		First-order statistics (= 4; mean value)	Code table, 0
0 13 060		Total accumulated precipitation $R_1 R_1 R_1 R_1$	kg m ⁻² , 1
0 04 053		Number of days with precipitation equal to or more than 1 mm $n_r n_r$	Numeric, 0
0 08 023		First-order statistics (set to missing to cancel the previous value)	Code table, 0

Notes:

- (1) The time identification refers to the beginning of the one-month period. Except for precipitation measurements, the one-month period is recommended to correspond to the local time (LT) month.
- (2) If the height/depth of sensors or method of sea/water temperature measurement was changed during the period specified, the value shall be that which existed for the greater part of the period.
- (3) In case of precipitation measurements, the one-month period begins at 06 UTC on the first day of the month and ends at 06 UTC on the first day of the following month.

Regulations:

B/C32.1	Section 1 of BUFR or CREX
B/C32.2	Monthly values from an ocean weather station – CLIMAT SHIP
B/C32.2.1	Station identification, date/time, horizontal and vertical coordinates
B/C32.2.2	Monthly mean values of pressure, temperature, vapour pressure and sea/water temperature
B/C32.2.3	Monthly precipitation data
B/C32.3	Monthly normals for an ocean weather station
B/C32.3.1	Normals of pressure, temperature, vapour pressure and sea/water temperature
B/C32.3.2	Normals of precipitation
B/C32.4	Regional or national reporting practices

B/C32.1 Section 1 of BUFR or CREX

B/C32.1.1 Entries required in Section 1 of BUFR

The following entries shall be included in BUFR Section 1:

- BUFR master table;
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Identification of inclusion of optional section;
- Data category (001 for CLIMAT SHIP data);
- International data sub-category (see Note 1);
- Local data sub-category;
- Version number of master table;
- Version number of local tables;
- Year (see Notes 2 and 4);
- Month (for which the monthly values are reported) (see Note 2);
- Day (01) (see Note 2);
- Hour (00) (see Note 2);
- Minute (00) (see Note 2);
- Second (00) (see Note 2).

Notes:

- (1) If required, the international data sub-category shall be included for CLIMAT SHIP data as 020.
- (2) The time identification refers to the beginning of the month for which the monthly mean values are reported.
- (3) If an NMHS performs conversion of CLIMAT SHIP data produced by another NMHS, originating centre in Section 1 shall indicate the converting centre and originating sub-centre shall indicate the producer of CLIMAT SHIP bulletins. The producer of CLIMAT SHIP bulletins shall be specified in Common Code table C-12 as a sub-centre of the originating centre, i.e. of the NMHS executing the conversion.
- (4) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C32.1.2 Entries required in Section 1 of CREX

The following entries shall be included in CREX Section 1:

- CREX master table;
- CREX edition number;
- CREX table version number;
- Version number of BUFR master table;
- Version number of local tables;
- Data category (001 for CLIMAT SHIP data);

- International data sub-category (see Note 1);
- Identification of originating/generating centre;
- Identification of originating/generating sub-centre;
- Update sequence number;
- Number of subsets;
- Year (see Notes 2 and 4);
- Month (for which the monthly values are reported) (see Note 2);
- Day (01) (see Note 2);
- Hour (00) (see Note 2);
- Minute (00) (see Note 2).

Notes:

- (1) If inclusion of the international data sub-category is required, Note 1 under Regulation B/C32.1.1 applies.
- (2) Note 2 under Regulation B/C32.1.1 applies.
- (3) If an NMHS performs conversion of CLIMAT SHIP data produced by another NMHS, Note 3 under Regulation B/C32.1.1 applies.
- (4) Date (year, month and day) and time (hour, minute and second) are the most typical time in the BUFR message contents and specified in UTC.

B/C32.2 Monthly values from an ocean weather station – CLIMAT SHIP <3 08 011>

B/C32.2.1 Station identification, date/time, horizontal and vertical coordinates

B/C32.2.1.1 Station identification

Ship identifier (0 01 011) shall be always reported as a non-missing value.

Type of station (0 02 001) shall be reported to indicate the type of the station operation (manned, automatic or hybrid).

B/C32.2.1.2 Date/time (of beginning of the month)

Date <3 01 011> and time <3 01 012> shall be reported, i.e. year (0 04 001), month (0 04 002), day (0 04 003) and hour (0 04 004), minute (0 04 005) of beginning of the month for which the monthly values are reported. Day (0 04 003) shall be set to 1 and both hour (0 04 004) and minute (0 04 005) shall be set to 0.

B/C32.2.1.3 Horizontal and vertical coordinates

Latitude (0 05 002) and longitude (0 06 002) of the station shall be reported in degrees with precision in hundredths of a degree.

Height of station platform above mean sea level (0 07 030) and height of barometer above mean sea level (0 07 031) shall be reported in metres with precision in tenths of a metre.

B/C32.2.2 Monthly mean values of pressure, temperature, vapour pressure and sea/water temperature

The monthly mean values of pressure reduced to mean sea level, temperature, vapour pressure and sea/water temperature shall be reported. Any missing element shall be reported as a missing value.

B/C32.2.2.1 Reference period for the data of the month

Monthly data (with the exception of precipitation data) are recommended to be reported for one-month period, corresponding to the local time (LT) month [*Handbook on CLIMAT and CLIMAT TEMP Reporting* (WMO/TD-No.1188)]. In that case, short time displacement (0 04 074) shall specify the difference

between UTC and LT (set to *non-positive values in the eastern hemisphere, non-negative values in the western hemisphere*).

Time period (0 04 023) represents the number of days in the month for which the data are reported, and shall be expressed as a *positive value* in days.

Note: A BUFR (or CREX) message shall contain reports for one specific month only.
[72.1.3]

B/C32.2.2.2 First-order statistics – Code table 0 08 023

This datum shall be set to 4 (mean value) to indicate that the following entries represent mean values of the elements (pressure reduced to mean sea level, temperature, vapour pressure and sea/water temperature) averaged over the one-month period.

B/C32.2.2.3 Monthly mean value of pressure reduced to mean sea level

Monthly mean value of pressure reduced to mean sea level shall be reported using 0 10 051 (Pressure reduced to mean sea level) in pascals (with precision in tens of pascals).

B/C32.2.2.4 Height of sensor above marine deck platform and height of sensor above water surface

Height of sensor above marine deck platform (0 07 032) for temperature and humidity measurement shall be reported in metres (with precision in hundredths of a metre). This datum represents the actual height of temperature and humidity sensors above marine deck platform at the point where the sensors are located.

Height of sensor above water surface (0 07 033) for temperature and humidity measurement shall be reported in metres (with precision in tenths of a metre). This datum represents the actual height of temperature and humidity sensors above water surface of sea or lake.

Note: If the heights of the sensors were changed during the period specified, the value shall be that which existed for the greater part of the period.

B/C32.2.2.5 Monthly mean value of temperature

Monthly mean value of temperature shall be reported using 0 12 101 (Temperature/air temperature) in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Temperature data shall be reported with precision in hundredths of a degree even if they are available with the accuracy in tenths of a degree.

Notes:

- (1) This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

B/C32.2.2.6 Monthly mean value of vapour pressure

Monthly mean value of vapour pressure shall be reported using 0 13 004 (Vapour pressure) in pascals (with precision in tens of pascals).

B/C32.2.2.7 Monthly mean value of sea-surface temperature, method of its measurement and depth below sea/water surface

Method of sea/water temperature measurement shall be reported by Code table 0 02 038; depth below sea/water surface (0 07 063) shall be reported in metres (with precision in hundredths of a metre).

Monthly mean value of sea-surface temperature shall be reported using 0 22 043 (Sea/water temperature) in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius). Sea/water temperature data shall be reported with precision in hundredths of a degree even if they are available with the accuracy in tenths of a degree.

Notes:

- (1) If the method of sea/water temperature measurement or the depth of the sensor below sea/water surface was changed during the period specified, the value shall be that which existed for the greater part of the period.
- (2) Notes 1 and 2 under Regulation B/C32.2.2.5 shall apply.

B/C32.2.2.8 First-order statistics – Code table 0 08 023

This datum shall be set to missing to indicate that the following entries do not represent the monthly mean values.

B/C32.2.3 Monthly precipitation data

B/C32.2.3.1 Date/time (of beginning of the one-month period for precipitation data)

Day (0 04 003) and hour (0 04 004) of the beginning of the one-month period for monthly precipitation data are reported. Day (0 04 003) shall be set to 1 and hour (0 04 004) shall be set to 6.

Notes:

- (1) In case of precipitation measurements, a month begins at 0600 hours UTC on the first day of the month and ends at 0600 hours UTC on the first day of the following month [*Handbook on CLIMAT and CLIMAT TEMP Reporting* (WMO/TD-No.1188)].
- (2) Year (0 04 001), month (0 04 002) and minute (0 04 005) of the beginning of the month specified in Regulation B/C32.2.1.2 apply.

B/C32.2.3.2 Period of reference for precipitation data of the month

Time period (0 04 023) represents the number of days in the month for which the monthly mean data are reported, and shall be expressed as a *positive value* in days.

Note: A BUFR (or CREX) message shall contain reports for one specific month only. [72.1.3]

B/C32.2.3.3 Height of sensor above marine deck platform

Height of sensor above marine deck platform (0 07 032) for precipitation measurement shall be reported in metres (with precision in hundredths of a metre).

This datum represents the actual height of the rain gauge rim above marine deck platform at the point where the rain gauge is located.

Note: If the height of the sensor was changed during the period specified, the value shall be that which existed for the greater part of the period.

B/C32.2.3.4 Total amount of precipitation of the month

Total accumulated precipitation (0 13 060) which has fallen during the month shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre).

Note: Trace shall be reported as “–0.1 kg m⁻²”.

B/C32.2.3.5 Indication of frequency group

Frequency group in which the total amount of precipitation of the month falls shall be reported using Code table 0 13 051 (Frequency group; precipitation).

Note: If for a particular month the total amount of precipitation is zero, the code figure for 0 13 051 shall be given by the highest number of quintile which has 0.0 as lower limit (e.g. in months with no rainfall in the 30-year period, 0 13 051 shall be set to 5). [72.1.4.2]

B/C32.2.3.6 Number of days with precipitation equal to or greater than 1 mm

Number of days in the month with precipitation equal to or greater than 1 kilogram per square metre shall be reported using 0 04 053 (Number of days in the month with precipitation equal to or greater than 1 mm).

Note: When the monthly total precipitation is not available, both 0 13 060 and 0 04 053 shall be set to missing. [72.1.4.1]

B/C32.3 Monthly normals for an ocean weather station <3 08 012>

Meteorological Services shall submit to the Secretariat complete normal data of the elements for stations to be included in the CLIMAT SHIP bulletins. The same shall apply when Services consider it necessary to make amendments to previously published normal values. [72.2.1]

B/C32.3.1 Normals of pressure, temperature, vapour pressure and sea/water temperature

Normal values of pressure reduced to mean sea level, temperature, vapour pressure and sea/water temperature shall be reported. Any missing element shall be reported as a missing value.

B/C32.3.1.1 Reference period for normal data

Reference period for calculation of the normal values of the elements shall be reported using two consecutive entries 0 04 001 (Year). The first 0 04 001 shall express the year of beginning of the reference period and the second 0 04 001 shall express the year of ending of the reference period.

Note: The normal data of pressure, temperature and sea/water temperature reported shall be deduced from observations made over a 30-year normal period. [72.2.2]

B/C32.3.1.2 Specification of the one-month period for which normals are reported

The one-month period for which the normal values are reported shall be specified by month (0 04 002), day (0 04 003) being set to 1, hour (0 04 004) being set to 0, short time displacement (0 04 074) being set to (UTC – LT) and time period (0 04 022) being set to 1, i.e. 1 month.

Short time displacement (0 04 074) shall be set to *non-positive values in the eastern hemisphere, non-negative values in the western hemisphere*.

B/C32.3.1.3 First-order statistics – Code table 0 08 023

This datum shall be set to 4 (mean value) to indicate that the following entries represent mean values of the elements (pressure reduced to mean sea level,

temperature, vapour pressure and sea/water temperature) averaged over the reference period specified in Regulation B/C32.3.1.1.

B/C32.3.1.4 Normal value of pressure reduced to mean sea level

Normal value of pressure reduced to mean sea level shall be reported using 0 10 051 (Pressure reduced to mean sea level) in pascals (with precision in tens of pascals).

B/C32.3.1.5 Height of sensor above marine deck platform and height of sensor above water surface

Regulation B/C32.2.2.4 shall apply.

B/C32.3.1.6 Normal value of temperature

Normal value of temperature shall be reported using 0 12 101 (Temperature/air temperature) in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Note: Notes 1 and 2 under Regulation B/C32.2.2.5 shall apply.

B/C32.3.1.7 Normal value of vapour pressure

Normal value of vapour pressure shall be reported using 0 13 004 (Vapour pressure) in pascals (with precision in tens of pascals).

B/C32.3.1.8 Normal value of sea-surface temperature, method of measurement and depth below sea/water surface

Method of sea/water temperature measurement shall be reported by Code table 0 02 038; depth below sea/water surface (0 07 063) shall be reported in metres (with precision in hundredths of a metre).

Normal value of sea-surface temperature shall be reported using 0 22 043 (Sea/water temperature) in kelvin (with precision in hundredths of a kelvin); if produced in CREX, in degrees Celsius (with precision in hundredths of a degree Celsius).

Notes:

- (1) Note 1 under Regulation B/C32.2.2.7 shall apply.
- (2) Notes 1 and 2 under Regulation B/C32.2.2.5 shall apply.

B/C32.3.2 Normals of precipitation

Normal values of monthly amount of precipitation and of number of days in the month with precipitation equal to or greater than 1 mm, shall be reported. Any missing element shall be reported as a missing value.

B/C32.3.2.1 Reference period for normal values of precipitation

Reference period for calculation of the normal values of precipitation shall be reported using two consecutive entries 0 04 001 (Year). The first 0 04 001 shall express the year of beginning of the reference period and the second 0 04 001 shall express the year of ending of the reference period.

B/C32.3.2.2 Specification of the one-month period for which normals are reported

The one-month period for which the normals of precipitation are reported shall be specified by month (0 04 002), day (0 04 003) being set to 1, hour (0 04 004) being set to 6 and time period (0 04 022) being set to 1, i.e. 1 month.

Note: Note 1 under Regulation B/C32.2.3.1 shall apply.

B/C32.3.2.3 Height of sensor above local marine deck platform

Regulation B/C32.2.3.3 shall apply.

B/C32.3.2.4 First-order statistics – Code table 0 08 023

This datum shall be set to 4 (mean value) to indicate that the following entries represent mean values of precipitation data, averaged over the reference period specified in Regulation B/C32.3.2.1.

B/C32.3.2.5 Normal value of monthly amount of precipitation

Normal value of monthly amount of precipitation shall be reported in kilograms per square metre (with precision in tenths of a kilogram per square metre) using 0 13 060 (Total accumulated precipitation).

Note: Trace shall be reported as “–0.1 kg m⁻²”.

B/C32.3.2.6 Normal value of number of days with precipitation ≥ 1 mm

Normal value of number of days in the month with precipitation equal to or greater than 1 kilogram per square metre shall be reported using 0 04 053 (Number of days in the month with precipitation equal to or greater than 1 mm).

B/C32.4 Regional or national reporting practices

B/C32.4.1 Data required by regional or national reporting practices

No additional data are currently required by regional or national reporting practices for CLIMAT SHIP data in the *Manual on Codes* (WMO-No. 306), Volume II.

B/C32.4.2 Reference period for the data of the month

If the regional or national reporting practices require reporting monthly data (with the exception of precipitation data) for one-month period different from the local time month as recommended in Regulation B/C32.2.2.1, short time displacement (0 04 074) shall be adjusted accordingly.

B/C32.4.3 Date/time (of beginning of the one-month period for precipitation data)

If the regional or national reporting practices require reporting monthly precipitation data for one-month period different from the period recommended in Note 1 to Regulation B/C32.2.3.1, then hour (0 04 004) shall be adjusted accordingly. This regulation does not apply if the beginning of the period for monthly precipitation data starts on the last day of the previous month in UTC.

B/C32.4.4 Date/time (of beginning of the one-month period for precipitation data on the last day of the previous month)

If the regional or national reporting practices require reporting monthly precipitation data for period which starts on the last day of the previous month in UTC, template TM 308023 should be used. The beginning of the period for monthly precipitation data shall be specified by short time displacement (0 04 074) set to a relevant negative value. The beginning of one-month period for which the normals of precipitation are reported, shall be specified in a similar way.

e. Regulations for reporting GBON parameters

GBON 1 REPORTING GBON OBSERVATIONS FROM SURFACE LAND FIXED STATIONS

GBON 1.1 BUFR sequences for surface land fixed stations

The following BUFR sequences should be used for reporting GBON variables from surface land fixed stations. BUFR sequences different from the ones listed below may be used if the reporting practices for GBON variables in GBON 1.2 can be applied.

GBON 1.1.1 BUFR Sequence for representation of SYNOP with supplementary information on one-hour observations <3 07 096>

<u>Row #</u>	<u>TABLE REFERENCE</u>	<u>TABLE REFERENCES</u>	<u>ELEMENT NAME</u>
	<u>F X Y</u>		
<u>1</u>	<u>3 07 096</u>	<u>(Sequence for representation of SYNOP with supplementary information on one-hour observations)</u>	
<u>2</u>		<u>3 01 090</u>	<u>Surface station identification: time, horizontal and vertical coordinates</u>
<u>3</u>		<u>3 01 089</u>	<u>National station identification</u>
<u>4</u>		<u>0 08 010</u>	<u>Surface qualifier (temperature data)</u>
<u>5</u>		<u>3 01 091</u>	<u>Surface station instrumentation</u>
<u>6</u>		<u>3 02 084</u>	<u>"Instantaneous" data of sequence 3 07 096</u>
<u>7</u>		<u>3 02 085</u>	<u>"Period" data of sequence 3 07 096</u>
<u>8</u>		<u>0 33 005</u>	<u>Quality information (AWS data)</u>
<u>9</u>		<u>0 33 006</u>	<u>Internal measurement status information (AWS)</u>

GBON BUFR template 3 07 096 further expands as follows.

#	FX	Y Expansion	Element name	Description	Unit, Scale	GBON Regulation
1	3 01 090		Surface station identification; time, horizontal and vertical co-ordinates		-	
2		3 01 004	Surface station identification	-	-	
3			0 01 001	WMO block number	Numeric, 0	GBON 1.2.1.3
4			0 01 002	WMO station number	Numeric, 0	GBON 1.2.1.3
5			0 01 015	Station or site name	CCITT IA5, 0	
6			0 02 001	Type of station	Code table, 0	GBON 1.2.1.4
7		3 01 011	Year, month, day	-	-	GBON 1.2.1.5
8			0 04 001	Year	a, 0	
9			0 04 002	Month	mon, 0	
10			0 04 003	Day	d, 0	
11		3 01 012	Hour, minute	-	-	GBON 1.2.1.5
12			0 04 004	Hour	h, 0	
13			0 04 005	Minute	min, 0	
14		3 01 021	Latitude/longitude (high accuracy)	-	-	
15			0 05 001	Latitude (high accuracy)	deg, 5	GBON 1.2.1.6
16			0 06 001	Longitude (high accuracy)	deg, 5	GBON 1.2.1.6

#	FX Y Expansion				Element name	Description	Unit, Scale	GBON Regulation
<u>17</u>	<u>3 01 090</u> (continued)	<u>0 07 030</u>			<u>Height of station ground above mean sea level</u>		<u>m, 1</u>	<u>GBON 1.2.1.7</u>
<u>18</u>		<u>0 07 031</u>			<u>Height of barometer above mean sea level</u>		<u>m, 1</u>	<u>GBON 1.2.1.7</u>
<u>19</u>	<u>3 01 089</u>	<u>National station identification</u>			-	-	-	
<u>20</u>		<u>0 01 101</u>			<u>State identifier</u>		<u>Code table, 0</u>	
<u>21</u>		<u>0 01 102</u>			<u>National station number</u>		<u>Numeric, 0</u>	
<u>22</u>	<u>0 08 010</u>				<u>Surface qualifier (for temperature data)</u>		<u>Code table, 0</u>	
<u>23</u>	<u>3 01 091</u>	<u>Surface station instrumentation</u>				-	-	
<u>24</u>		<u>0 02 180</u>			<u>Main present weather detecting system</u>		<u>Code table, 0</u>	
<u>25</u>		<u>0 02 181</u>			<u>Supplementary present weather sensor</u>		<u>Flag table, 0</u>	
<u>26</u>		<u>0 02 182</u>			<u>Visibility measurement system</u>		<u>Code table, 0</u>	
<u>27</u>		<u>0 02 183</u>			<u>Cloud detection system</u>		<u>Code table, 0</u>	
<u>28</u>		<u>0 02 184</u>			<u>Type of lightning detection sensor</u>		<u>Code table, 0</u>	
<u>29</u>		<u>0 02 179</u>			<u>Type of sky condition algorithm</u>		<u>Code table, 0</u>	
<u>30</u>		<u>0 02 186</u>			<u>Capability to detect precipitation phenomena</u>		<u>Flag table, 0</u>	

#	FX Y Expansion		Element name		Description	Unit, Scale	GBON Regulation
31	<u>3 01 091</u> (continued)	<u>0 02 187</u>			<u>Capability to detect other weather phenomena</u>	<u>Flag table, 0</u>	
32		<u>0 02 188</u>			<u>Capability to detect obscuration</u>	<u>Flag table, 0</u>	
33		<u>0 02 189</u>			<u>Capability to discriminate lightning strikes</u>	<u>Flag table, 0</u>	
34	<u>3 02 084</u>	<u>"Instantaneous" data of sequence 307096</u>			-	-	
35		<u>3 02 031</u>	<u>Pressure information</u>	-	-	-	
36			<u>3 02 001</u>	<u>Pressure and 3-hour pressure change</u>			
37			<u>3 02 001</u>	<u>0 10 004</u>	<u>Pressure</u>	<u>Station level</u>	<u>Pa, -1</u> <u>GBON 1.2.2.1,</u> <u>GBON 1.2.2.2</u>
38			<u>3 02 001</u>	<u>0 10 051</u>	<u>Pressure reduced to mean sea level</u>	<u>Pa, -1</u>	<u>GBON 1.2.2.2</u>
39			<u>3 02 001</u>	<u>0 10 061</u>	<u>3-hour pressure change</u>	<u>Pa, -1</u>	
40			<u>3 02 001</u>	<u>0 10 063</u>	<u>Characteristic of pressure tendency</u>	<u>Code table, 0</u>	
41			<u>0 10 062</u>		<u>24-hour pressure change</u>	<u>Pa, -1</u>	
42			<u>0 07 004</u>		<u>Pressure</u>	<u>Standard level</u>	<u>Pa, -1</u>
43			<u>0 10 009</u>		<u>Geopotential height</u>	<u>gpm, 0</u>	<u>GBON 1.2.2.2</u>
44		<u>3 02 072</u>	<u>Temperature and humidity data</u>		-	-	
45			<u>0 07 032</u>		<u>Height of sensor above local ground (or deck of marine platform)</u>	<u>m, 2</u>	<u>GBON 1.2.2.3</u>

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
46	3 02 084 (continued)		0 07 033		Height of sensor above water surface	m, 1	
47			0 12 101		Temperature/air temperature	Scale: 2 K, 2	GBON 1.2.2.4
48			0 12 103		Dewpoint temperature	Scale: 2 K, 2	GBON 1.2.2.5, GBON 1.2.2.7
49			0 13 003		Relative humidity	%, 0	GBON 1.2.2.6, GBON 1.2.2.7
50		1 03 000	Delayed replication of 3 descriptors				
51		0 31 000	Short delayed descriptor replication factor			Numeric, 0	
52		1 01 005	Replicate one descriptor five times				
53		3 07 063	Depth below land surface and soil temperature			-	
54			0 07 061		Depth below land surface	m, 2	
55			0 12 130		Soil temperature	Scale: 2 K, 2	
56		0 07 061			Depth below land surface	Set to missing (cancel)	
57		-			Visibility data		
58		1 01 000			Delayed replication of 1 descriptor		
59		0 31 000			Short delayed descriptor replication factor	Numeric, 0	
60		3 02 069	Visibility data			-	
61			0 07 032		Height of sensor above local ground (or deck of marine platform)	m, 2	

#	FXI Expansion				Element name	Description	Unit, Scale	GBON Regulation
62	3 02 084 (continued)		0 07 033		Height of sensor above water surface		m, 1	
63			0 33 041		Attribute of following value		Code table, 0	
64			0 20 001		Horizontal visibility		m, -1	
65		0 07 032			Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)		
66		0 07 033			Height of sensor above water surface	Set to missing (cancel)		
67		-			Marine data			
68		1 05 000			Delayed replication of 5 descriptors			
69		0 31 000			Short delayed descriptor replication factor		Numeric, 0	
70		0 20 031			Ice deposit (thickness)		m, 2	
71		0 20 032			Rate of ice accretion (estimated)		Code table, 0	
72		0 02 038			Method of water temperature and/or salinity measurement		Code table, 0	
73		0 22 043			Sea/water temperature	Scale: 2	K, 2	
74		3 02 021	Waves	-	-	-	-	
75			0 22 001		Direction of waves		degree true, 0	
76			0 22 011		Period of waves		s, 0	

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
77	3 02 084 (continued)		0 22 021		Height of waves	m, 1	
78					State of ground and snow depth measurement		
79		1 01 000			Delayed replication of 1 descriptor		
80		0 31 000			Short delayed descriptor replication factor	Numeric, 0	
81		3 02 078	State of ground and snow depth measurement			-	
82			0 02 176		Method of state of ground measurement	Code table, 0	GBON 1.2.2.8
83			0 20 062		State of ground (with or without snow)	Code table, 0	GBON 1.2.2.8
84			0 02 177		Method of snow depth measurement	Code table, 0	GBON 1.2.2.9
85			0 13 013		Total snow depth	m, 2	GBON 1.2.2.9
86		0 12 113			Ground minimum temperature, past 12 hours	Scale: 2 K, 2	
87		-			Cloud data		
88		1 01 000			Delayed replication of 1 descriptor		
89		0 31 000			Short delayed descriptor replication factor	Numeric, 0	
90		3 02 004	General cloud information			-	
91			0 20 010		Cloud cover (total)	%, 0	

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
<u>92</u>	<u>3 02 084</u> <u>(continued)</u>		<u>0 08 002</u>		<u>Vertical significance (surface observations)</u>	<u>Code table, 0</u>	
<u>93</u>			<u>0 20 011</u>		<u>Cloud amount</u>	<u>Code table, 0</u>	
<u>94</u>			<u>0 20 013</u>		<u>Height of base of cloud</u>	<u>m, -1</u>	
<u>95</u>			<u>0 20 012</u>		<u>Cloud type</u>	<u>Code table, 0</u>	
<u>96</u>			<u>0 20 012</u>		<u>Cloud type</u>	<u>Code table, 0</u>	
<u>97</u>			<u>0 20 012</u>		<u>Cloud type</u>	<u>Code table, 0</u>	
<u>98</u>		<u>1 05 000</u>			<u>Delayed replication of 5 descriptors</u>		
<u>99</u>		<u>0 31 001</u>			<u>Delayed descriptor replication factor</u>	<u>Numeric, 0</u>	
<u>100</u>		<u>0 08 002</u>			<u>Vertical significance (surface observations)</u>	<u>Code table, 0</u>	
<u>101</u>		<u>0 20 011</u>			<u>Cloud amount</u>	<u>Code table, 0</u>	
<u>102</u>		<u>0 20 012</u>			<u>Cloud type</u>	<u>Code table, 0</u>	
<u>103</u>		<u>0 33 041</u>			<u>Attribute of following value</u>	<u>Code table, 0</u>	
<u>104</u>		<u>0 20 013</u>			<u>Height of base of cloud</u>	<u>m, -1</u>	
<u>105</u>		<u>3 02 036</u>	<u>Clouds with bases below station level</u>			-	

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
<u>106</u>	<u>3 02 084</u> (continued)		<u>1 05 000</u>		<u>Delayed replication of 5 descriptors</u>		
<u>107</u>			<u>0 31 001</u>		<u>Delayed descriptor replication factor</u>	<u>Numeric, 0</u>	
<u>108</u>			<u>0 08 002</u>		<u>Vertical significance (surface observations)</u>	<u>Code table, 0</u>	
<u>109</u>			<u>0 20 011</u>		<u>Cloud amount</u>	<u>Code table, 0</u>	
<u>110</u>			<u>0 20 012</u>		<u>Cloud type</u>	<u>Code table, 0</u>	
<u>111</u>			<u>0 20 014</u>		<u>Height of top of cloud</u>	<u>m, -1</u>	
<u>112</u>			<u>0 20 017</u>		<u>Cloud top description</u>	<u>Code table, 0</u>	
<u>113</u>					<u>Direction of cloud drift</u> <u>6D_LD_MD_H</u>		
<u>114</u>		<u>1 01 000</u>			<u>Delayed replication of 1 descriptor</u>		
<u>115</u>		<u>0 31 000</u>			<u>Short delayed descriptor replication factor</u>	<u>Numeric, 0</u>	
<u>116</u>		<u>3 02 047</u>	<u>Direction of cloud drift</u>	-	-	-	
<u>117</u>			<u>1 02 003</u>		<u>Replicate 2 descriptors 3 times</u>		
<u>118</u>			<u>0 08 002</u>		<u>Vertical significance (surface observations)</u>	<u>Code table, 0</u>	

#	FX Expansion			Element name	Description	Unit, Scale	GBON Regulation
<u>119</u>	<u>3 02 084</u> (continued)		<u>0 20 054</u>		<u>True direction from which a phenomenon or clouds are moving or in which they are observed</u>	<u>degree true, 0</u>	
<u>120</u>		<u>0 08 002</u>			<u>Vertical significance (surface observations)</u>	<u>Code table, 0</u>	
<u>121</u>		<u>1 01 000</u>			<u>Delayed replication of 1 descriptor</u>		
<u>122</u>		<u>0 31 000</u>			<u>Short delayed descriptor replication factor</u>	<u>Numeric, 0</u>	
<u>123</u>		<u>3 02 048</u>	<u>Direction and elevation of cloud</u>		-	-	
<u>124</u>			<u>0 05 021</u>		<u>Bearing or azimuth</u>	<u>Degree true, 2</u>	
<u>125</u>			<u>0 07 021</u>		<u>Elevation</u>	<u>Elevation angle</u>	<u>Degree, 2</u>
<u>126</u>			<u>0 20 012</u>		<u>Cloud type</u>	<u>Code table, 0</u>	
<u>127</u>			<u>0 05 021</u>		<u>Bearing or azimuth</u>	<u>Set to missing (cancel)</u>	
<u>128</u>			<u>0 07 021</u>		<u>Elevation</u>	<u>Set to missing (cancel)</u>	
<u>129</u>	<u>3 02 085</u>	<u>"Period" data of sequence 3 07 096</u>				-	-
<u>130</u>		<u>1 05 000</u>			<u>Delayed replication of 5 descriptors</u>		
<u>131</u>		<u>0 31 000</u>			<u>Short delayed descriptor replication factor</u>	<u>Numeric, 0</u>	

#	FXE Expansion				Element name	Description	Unit, Scale	GBON Regulation
<u>132</u>	<u>3 02 085</u> (continued)	<u>0 20 003</u>			<u>Present weather</u>		<u>Code</u> <u>table, 0</u>	
<u>133</u>		<u>1 03 002</u>			<u>Replicate 3 descriptors 2 times</u>			
<u>134</u>		<u>0 04 024</u>			<u>Time period or displacement</u>	<u>= -1 hour in</u> <u>the first</u> <u>replication, =</u> <u>-x hours in</u> <u>the second</u> <u>replication, x</u> <u>corresponding</u> <u>to the time</u> <u>period of</u> <u>W1W2 in the</u> <u>SYNOP report</u>	<u>h, 0</u>	
<u>135</u>		<u>0 20 004</u>			<u>Past weather (1)</u>		<u>Code</u> <u>table, 0</u>	
<u>136</u>		<u>0 20 005</u>			<u>Past weather (2)</u>		<u>Code</u> <u>table, 0</u>	
<u>137</u>					<u>Intensity of precipitation, size</u> <u>of precipitation element</u>			
<u>138</u>		<u>1 01 000</u>			<u>Delayed replication of 1</u> <u>descriptor</u>			
<u>139</u>		<u>0 31 000</u>			<u>Short delayed descriptor</u> <u>replication factor</u>		<u>Numeric,</u> <u>0</u>	
<u>140</u>		<u>3 02 175</u>	<u>Intensity of precipitation, size of precipitation element</u>			-	-	
<u>141</u>			<u>0 08 021</u>		<u>Time significance</u>		<u>Code</u> <u>table, 0</u>	

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
142	3 02 085 (continued)		0 04 025		Time period or displacement	min, 0	
143			0 13 155		Intensity of precipitation (high accuracy)	kg m⁻²s⁻¹, 5	GBON 1.2.2.8
144			0 13 058		Size of precipitating element	m, 4	
145			0 08 021		Time significance	Code table, 0	
146					Precipitation, obscuration and other phenomena		
147		1 02 000			Delayed replication of 2 descriptors		
148		0 31 000			Short delayed descriptor replication factor	Numeric, 0	
149		0 04 025			Time period or displacement	≡ - 10 minutes min, 0	
150		3 02 076	Precipitation, obscuration and other phenomena			-	
151			0 20 021		Type of precipitation	Flag table, 0	
152			0 20 022		Character of precipitation	Code table, 0	
153			0 26 020		Duration of precipitation	(see Note 1) min, 0	
154			0 20 023		Other weather phenomena	Flag table, 0	
155			0 20 024		Intensity of phenomena	Code table, 0	

#	FX Y Expansion				Element name	Description	Unit, Scale	GBON Regulation
<u>156</u>	<u>3 02 085</u> (continued)	<u>3 02 076</u> (continued)	<u>0 20 025</u>		<u>Obscuration</u>		<u>Flag table, 0</u>	
<u>157</u>			<u>0 20 026</u>		<u>Character of obscuration</u>		<u>Code table, 0</u>	
<u>158</u>					<u>Lightning data</u>			
<u>159</u>		<u>1 02 000</u>			<u>Delayed replication of 2 descriptors</u>			
<u>160</u>		<u>0 31 000</u>			<u>Short delayed descriptor replication factor</u>		<u>Numeric, 0</u>	
<u>161</u>		<u>0 04 025</u>			<u>Time period or displacement</u>	<u>= -10 minutes</u>	<u>min, 0</u>	
<u>162</u>		<u>0 13 059</u>			<u>Number of flashes (thunderstorm)</u>		<u>Numeric, 0</u>	
<u>163</u>		-			<u>Wind data</u>			
<u>164</u>		<u>0 07 032</u>			<u>Height of sensor above local ground (or deck of marine platform)</u>		<u>m, 2</u>	<u>GBON 1.2.2.16</u>
<u>165</u>		<u>0 07 033</u>			<u>Height of sensor above water surface</u>		<u>m, 1</u>	
<u>166</u>		<u>0 08 021</u>			<u>Time significance</u>	<u>= 2 Time averaged</u>	<u>Code table, 0</u>	<u>GBON 1.2.2.18</u>
<u>167</u>		<u>0 04 025</u>			<u>Time period or displacement</u>	<u>= -10 minutes, or number of minutes after a significant change of wind</u>	<u>min, 0</u>	<u>GBON 1.2.2.17</u>

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
168	3 02 085 (continued)	0 11 001		Wind direction		degree true, 0	GBON 1.2.2.15
169		0 11 002		Wind speed		m/s, 1	GBON 1.2.2.15
170		0 08 021		Time significance	Set to missing		
171		1 03 003		Replicate 3 descriptors 3 times			
172		0 04 025		Time period or displacement	= -10 minutes in the first replication, = -60 minutes in the second replication, = -60x3 or 60x6 minutes in the third replication	min, 0	GBON 1.2.2.20
173		0 11 043		Maximum wind gust direction		degree true, 0	GBON 1.2.2.19
174		0 11 041		Maximum wind gust speed		m/s, 1	GBON 1.2.2.19
175		0 04 025		Time period or displacement	= -10 minutes	min, 0	
176		0 11 016		Extreme counterclockwise wind direction of a variable wind		degree true, 0	
177		0 11 017		Extreme clockwise wind direction of a variable wind		degree true, 0	
178				Extreme temperature data			
179		3 02 077	Extreme temperature data		-	-	

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
<u>180</u>	<u>3 02 085</u> (continued)		<u>0 07 032</u>		Height of sensor above local ground (or deck of marine platform)	m, 2	
<u>181</u>			<u>0 07 033</u>		Height of sensor above water surface	m, 1	
<u>182</u>			<u>0 04 025</u>		Time period or displacement	min, 0	
<u>183</u>			<u>0 12 111</u>		Maximum temperature, at height and over period specified	Scale: 2 K, 2	
<u>184</u>			<u>0 12 112</u>		Minimum temperature, at height and over period specified	Scale: 2 K, 2	
<u>185</u>			<u>0 07 032</u>		Height of sensor above local ground (or deck of marine platform)	Ground temperature m, 2	
<u>186</u>			<u>0 04 025</u>		Time period or displacement	min, 0	
<u>187</u>			<u>0 12 112</u>		Minimum temperature at height and over period specified	Scale: 2; Ground temperature K, 2	
<u>188</u>		<u>0 07 033</u>			Height of sensor above water surface	Set to missing (cancel)	
<u>189</u>		<u>3 02 041</u>	<u>Extreme temperature data</u>			-	
<u>190</u>			<u>0 07 032</u>		Height of sensor above local ground (or deck of marine platform)	Temperature measurement m, 2	
<u>191</u>			<u>0 04 024</u>		Time period or displacement	h, 0	

#	FXY Expansion				Element name	Description	Unit, Scale	GBON Regulation
<u>192</u>	<u>3 02 085</u> (continued)		<u>0 04 024</u>		<u>Time period or displacement</u>	<u>(see Notes 2 and 3)</u>	<u>h, 0</u>	
<u>193</u>			<u>0 12 111</u>		<u>Maximum temperature, at height and over period specified</u>	<u>Scale:2</u>	<u>K, 2</u>	
<u>194</u>			<u>0 04 024</u>		<u>Time period or displacement</u>		<u>h, 0</u>	
<u>195</u>			<u>0 04 024</u>		<u>Time period or displacement</u>	<u>(see Note 2></u>	<u>h, 0</u>	
<u>196</u>			<u>0 12 112</u>		<u>Maximum temperature, at height and over period specified</u>	<u>Scale: 2</u>	<u>K, 2</u>	
<u>197</u>					<u>Precipitation measurement</u>			
<u>198</u>		<u>1 06 000</u>			<u>Delayed replication of 6 descriptors</u>			
<u>199</u>		<u>0 31 000</u>			<u>Short delayed descriptor replication factor</u>		<u>Numeric, 0</u>	
<u>200</u>		<u>0 07 032</u>			<u>Height of sensor above local ground (or deck of marine platform)</u>		<u>m, 2</u>	<u>GBON 1.2.2.14</u>
<u>201</u>		<u>0 02 175</u>			<u>Method of precipitation measurement</u>		<u>Code table, 0</u>	
<u>202</u>		<u>0 02 178</u>			<u>Method of liquid content measurement of precipitation</u>		<u>Code table, 0</u>	
<u>203</u>		<u>1 02 005</u>			<u>Replicate 2 descriptors 5 times</u>			

#	FX Y Expansion	Element name		Description	Unit, Scale	GBON Regulation	
204	3 02 085 (continued)	0 04 024		Time period or displacement	= -1 hour in the first replication, = -3, -6, -12 and -24 hours in the other replications	h, 0	GBON 1.2.2.13
205		0 13 011		Total precipitation/total water equivalent		kg m ⁻² , 1	GBON 1.2.2.12
206		0 07 032		Height of sensor above local ground (or deck of marine platform)	Set to missing (cancel)		
207		-		Evaporation data			
208		1 03 000		Delayed replication of 3 descriptors			
209		0 31 000		Short delayed descriptor replication factor		Numeric, 0	
210		0 02 185		Method of evaporation measurement		Code table, 0	
211		1 01 002		Replicate 1 descriptor 2 times			
212		3 02 044	Evaporation data	-	-	-	
213			0 04 024	Time period or displacement	Hours	h, 0	
214			0 02 004	Type of instrumentation for evaporation measurement or type of crop for which evapotranspiration is reported		Code table, 0	
215			0 13 033	Evaporation/evapotranspiration		kg m ⁻² , 1	

#	FX Y Expansion		Element name	Description	Unit, Scale	GBON Regulation
<u>216</u>	<u>3 02 085</u> (continued)			<u>Total sunshine data</u>		
<u>217</u>		<u>1 02 000</u>		<u>Delayed replication of 2 descriptors</u>		
<u>218</u>		<u>0 31 000</u>		<u>Short delayed descriptor replication factor</u>	<u>Numeric, 0</u>	
<u>219</u>		<u>1 01 002</u>		<u>Replicate 1 descriptor 2 times</u>		
<u>220</u>		<u>3 02 039</u>	<u>Sunshine data (from 1 hour and 24-hour period)</u>		-	
<u>221</u>			<u>0 04 024</u>	<u>Time period or displacement</u>	<u>Hours</u>	<u>h, 0</u>
<u>222</u>			<u>0 14 031</u>	<u>Total sunshine</u>		<u>min, 0</u>
<u>223</u>				<u>Radiation data</u>		
<u>224</u>		<u>1 02 000</u>		<u>Delayed replication of 2 descriptors</u>		
<u>225</u>		<u>0 31 000</u>		<u>Short delayed descriptor replication factor</u>	<u>Numeric, 0</u>	
<u>226</u>		<u>1 01 002</u>		<u>Replicate 1 descriptor 2 times</u>		
<u>227</u>		<u>3 02 045</u>	<u>Radiation data (from 1 hour and 24-hour period)</u>		-	
<u>228</u>		<u>3 02 045</u> (continued)	<u>0 04 024</u>	<u>Time period or displacement</u>	<u>Hours</u>	<u>h, 0</u>
<u>229</u>			<u>0 14 002</u>	<u>Long-wave radiation, integrated over period specified</u>		<u>J m⁻², -3</u>
<u>230</u>			<u>0 14 004</u>	<u>Short-wave radiation, integrated over period specified</u>		<u>J m⁻², -3</u>

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
<u>231</u>	<u>3 02 085</u> (continued)		<u>0 14 016</u>		<u>Net radiation, integrated over period specified</u>	<u>J m⁻², -4</u>	
<u>232</u>			<u>0 14 028</u>		<u>Global solar radiation (high accuracy), integrated over period specified</u>	<u>J m⁻², -2</u>	
<u>233</u>			<u>0 14 029</u>		<u>Diffuse solar radiation (high accuracy), integrated over period specified</u>	<u>J m⁻², -2</u>	
<u>234</u>			<u>0 14 030</u>		<u>Direct solar radiation (high accuracy), integrated over period specified</u>	<u>J m⁻², -2</u>	
<u>235</u>					<u>Temperature change group 54q0sndT</u>		
<u>236</u>		<u>1 01 000</u>			<u>Delayed replication of 1 descriptor</u>		
<u>237</u>		<u>0 31 000</u>			<u>Short delayed descriptor replication factor</u>	<u>Numeric, 0</u>	
<u>238</u>		<u>3 02 046</u>	<u>Temperature change</u>		-	-	
<u>239</u>		<u>3 02 046</u> (continued)	<u>0 04 024</u>		<u>Time period or displacement</u>	<u>h, 0</u>	
<u>240</u>			<u>0 04 024</u>		<u>Time period or displacement</u> (see Note 4)	<u>h, 0</u>	
<u>241</u>			<u>0 12 049</u>		<u>Temperature change over specified period</u>	<u>K, 0</u>	
<u>242</u>					<u>First-order statistics of P, W, T, U data</u>		

#	FX Y Expansion		Element name		Description	Unit, Scale	GBON Regulation
243	<u>3 02 085</u> (continued)	<u>1 01 000</u>			<u>Delayed replication of 1 descriptor</u>		
244		<u>0 31 000</u>			<u>Short delayed descriptor replication factor</u>	<u>Numeric, 0</u>	
245		<u>3 02 083</u>	<u>First order statistics of P, W, T, U data</u>		-	-	
246			<u>0 04 025</u>		<u>Time period or displacement</u>	<u>min, 0</u>	
247			<u>0 08 023</u>		<u>First order statistics</u>	<u>Code table, 0</u>	
248			<u>0 10 004</u>		<u>Pressure</u>	<u>Pa, -1</u>	
249			<u>0 11 001</u>		<u>Wind direction</u>	<u>degree true, 0</u>	
250			<u>0 11 002</u>		<u>Wind speed</u>	<u>m/s, 1</u>	
251			<u>0 12 101</u>		<u>Temperature/air temperature</u>	<u>Scale: 2 K, 2</u>	
252			<u>0 13 003</u>		<u>Relative humidity</u>	<u>%, 0</u>	
253			<u>0 08 023</u>		<u>First-order statistics</u>	<u>Set to missing</u>	
254	<u>0 33 005</u>	-			<u>Quality information (AWS data)</u>	<u>(see Note 5)</u>	<u>Flag table, 0</u>
255	<u>0 33 006</u>	-			<u>Internal measurement status information (AWS)</u>	<u>Code table, 0</u>	

Notes:

- (1) Duration of precipitation <0 26 020> represents number of minutes in which precipitation was registered.
- (2) Within RA III, the maximum daytime temperature and the minimum night-time temperature is reported (i.e. the ending time of the period may not be equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.

- (3) Within RA IV, the maximum temperature at 1200 UTC is reported for the previous calendar day (i.e. the ending time of the period is not equal to the nominal time of the report). To construct the required time range, descriptor 0 04 024 has to be included two times. If the period ends at the nominal time of the report, value of the second 0 04 024 shall be set to 0.
- (4) To construct the required time range, descriptor 0 04 024 has to be included two times.
- (5) To represent Intensity of precipitation, type of precipitation and state of functionality, 0 20 024 <Code table>, 0 20 021 (Flag table) and 0 33 005 (Flag table) are used, respectively.

GBON 1.1.2 BUFR sequence Snow observation, snow density, snow water equivalent <3 07 103>

<u>TABLE REFERENCE</u>	<u>TABLE REFERENCES</u>	<u>ELEMENT NAME</u>
<u>F X Y</u>		
<u>3 07 103</u>	<u>(Snow observation, snow density, snow water equivalent)</u>	
	<u>3 01 150</u>	<u>WIGOS identifier</u>
	<u>3 07 101</u>	<u>Snow observation</u>
	<u>0 13 117</u>	<u>Snow density (liquid water content)</u>
	<u>0 03 028</u>	<u>Method of snow water equivalent measurement</u>
	<u>0 13 163</u>	<u>Snow water equivalent</u>

GBON BUFR template 3 07 103 further expands as follows.

#	FXY Expansion	Element name	Description	Unit, Scale	GBON Regulation
<u>1</u>	<u>3 01 150</u>	<u>WIGOS identifier</u>	-	-	<u>GBON 1.2.1.2</u>
<u>2</u>		<u>0 01 125</u>	<u>WIGOS identifier series</u>	<u>Numeric, 0</u>	
<u>3</u>		<u>0 01 126</u>	<u>WIGOS issuer of identifier</u>	<u>Numeric, 0</u>	
<u>4</u>		<u>0 01 127</u>	<u>WIGOS issue number</u>	<u>Numeric, 0</u>	
<u>5</u>		<u>0 01 128</u>	<u>WIGOS local identifier (character)</u>	<u>CCITT IA5, 0</u>	
<u>6</u>	<u>3 07 101</u>	<u>Snow observation</u>	-	-	-
<u>7</u>		<u>3 01 089</u>	<u>National station identification</u>	-	-
<u>8</u>		<u>0 01 101</u>	<u>State identifier</u>	<u>Code table, 0</u>	
<u>9</u>		<u>0 01 102</u>	<u>National station number</u>	<u>Numeric, 0</u>	
<u>10</u>		<u>0 01 019</u>	<u>Long station or site name</u>	<u>CCITT IA5, 0</u>	
<u>11</u>		<u>0 02 001</u>	<u>Type of station</u>		<u>GBON 1.2.1.4</u>
<u>12</u>		<u>3 01 011</u>	<u>Year, month, day</u>	-	<u>GBON 1.2.1.5</u>
<u>13</u>		<u>0 04 001</u>	<u>Year</u>	<u>a, 0</u>	
<u>14</u>		<u>0 04 002</u>	<u>Month</u>	<u>mon, 0</u>	
<u>15</u>		<u>0 04 003</u>	<u>Day</u>	<u>d, 0</u>	
<u>16</u>		<u>3 01 012</u>	<u>Hour, minute</u>	-	

#	FXY Expansion			Element name	Description	Unit, Scale	GBON Regulation
<u>17</u>	<u>3 07 101</u> (continued)		<u>0 04 004</u>	Hour		<u>h, 0</u>	
<u>18</u>			<u>0 04 005</u>	Minute		<u>min, 0</u>	
<u>19</u>		<u>3 01 021</u>	<u>Latitude/longitude (high accuracy)</u>		-	-	
<u>20</u>			<u>0 05 001</u>	<u>Latitude (high accuracy)</u>		<u>deg, 5</u>	<u>GBON 1.2.1.6</u>
<u>21</u>			<u>0 06 001</u>	<u>Longitude (high accuracy)</u>		<u>deg, 5</u>	<u>GBON 1.2.1.6</u>
<u>22</u>		<u>0 07 030</u>		<u>Height of station ground above mean sea level</u>		<u>m, 1</u>	<u>GBON 1.2.1.7</u>
<u>23</u>		<u>0 07 032</u>		<u>Height of sensor above local ground (or deck of marine platform)</u>		<u>m, 2</u>	<u>GBON 1.2.2.3</u>
<u>24</u>		<u>0 12 101</u>		<u>Temperature/air temperature</u>		<u>K, 2</u>	<u>GBON 1.2.2.4</u>
<u>25</u>		<u>0 07 032</u>		<u>Height of sensor above local ground (or deck of marine platform)</u>		<u>m, 2</u>	<u>GBON 1.2.2.3</u>
<u>26</u>		<u>0 02 177</u>		<u>Method of snow depth measurement</u>		<u>Code table, 0</u>	<u>GBON 1.2.2.8</u>
<u>27</u>		<u>0 20 062</u>		<u>State of the ground (with or without snow)</u>		<u>Code table, 0</u>	<u>GBON 1.2.2.8</u>
<u>28</u>		<u>0 13 013</u>		<u>Total snow depth</u>		<u>m, 2</u>	<u>GBON 1.2.2.9</u>
<u>29</u>	<u>0 13 117</u>			<u>Snow density (liquid water content)</u>		<u>kg m-3, 0</u>	<u>GBON 1.2.2.10*</u>

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
30	0 03 028			Method of snow water equivalent measurement		Code table, 0	GBON 1.2.2.10*
31	0 13 163			Snow water equivalent		kg m-2, 0	GBON 1.2.2.10*

GBON 1.2 REPORTING PRACTICES FOR SURFACE FIXED LAND STATIONS

GBON 1.2.1 Station identification, time, coordinates

GBON 1.2.1.1 Sequence for WIGOS station identifier

The sequence WIGOS station identifier (WSI) <3 01 150> shall be added before the first element if not included in the sequence.

GBON 1.2.1.2 WSI values

The elements of sequence WSI <3 01 150> shall not be set to missing and shall have the values corresponding with the station record in <https://oscar.wmo.int/surface>.

GBON 1.2.1.3 Traditional station identifier

WMO block number <0 01 001> and WMO station number <0 01 002> shall report the traditional station identifiers (TSI) when available to ensure the continuity of data use, otherwise set to missing value.

GBON 1.2.1.4 Type of station

Type of station <0 02 001> shall be reported to indicate the type of the station operation (manned, automatic or hybrid). If a station operates as a manned station for a part of the day and as an automatic station for the rest of the day, code figure 2 (Hybrid) may be used in all reports. It is preferable, however, to use code figure 1 (Manned) in reports produced under the supervision of an observer, and a code figure 0 (Automatic) in reports produced while the station operates in the automatic mode.

GBON 1.2.1.5 Time of observation

Year <0 04 001>, month <0 04 002>, day <0 04 003>, hour <0 04 004> and minute <0 04 005> of the actual time of observation shall be reported. The actual time of observation shall be the time at which the barometer is read.

GBON 1.2.1.6 Station location

Latitude <0 05 001> and longitude <0 06 001> of the station shall be reported in degrees with precision in 10^{-5} of a degree.

GBON 1.2.1.7 Station and barometer height

Height of station ground above mean sea level <0 07 030> and height of barometer above mean sea level <0 07 031> shall be reported in metres with precision in tenths of a metre.

GBON 1.2.2 GBON required parameters

In accordance with GBON provisions the *Manual on WIGOS* (WMO-No. 1160), paragraph 3.2.2) a GBON surface land observing station shall observe a minimum number of required variables. The reporting practices for the GBON required variables are described in the following section. The BUFR template <3 07 096> provides the necessary elements to report a full SYNOP observation in BUFR. The variables normally reported in a SYNOP are recommended for GBON stations and their reporting practices are described in regulation B/C1. Reporting of variables not required by GBON is recommended but shall not affect the required GBON transmission schedule, nor substantially delay the reporting.

Snow is a GBON required parameter and shall be reported using BUFR template <3 07 103> (see 1.1.2) and the relevant elements in template <3 07 096>. Two different messages shall be produced for the BUFR templates <3 07 096> and <3 07 103> if the station is reporting snow and other GBON parameters.

GBON 1.2.2.1 Pressure units

Pressure <0 10 004> at the station level, for example at the level defined by height of barometer above mean sea level <0 07 031>, shall be reported in pascals with precision in tens of pascals.

GBON 1.2.2.2 Pressure accuracy

Pressure <0 10 004> at the station level shall be included with the pressure reduced to mean sea level <0 10 051>. High-level stations that cannot report pressure reduced to mean sea level <0 10 051> with a satisfactory degree of accuracy can report with the geopotential height <0 10 009> of a standard isobaric surface as agreed by regional decision.

GBON 1.2.2.3 Sensor height for temperature and humidity

Height of sensor above local ground <0 07 032> for temperature and humidity data <3 02 072> shall be reported in metres with precision in hundredths of a metre. This datum represents the actual height of temperature and humidity sensors above ground at the point where the sensors are located.

GBON 1.2.2.4 Temperature units accuracy

Temperature/air temperature <0 12 101> shall be reported in kelvin with precision in hundredths of a kelvin.

Notes:

(1) Temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree. This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.

(2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

GBON 1.2.2.5 Dewpoint temperature units

Dewpoint temperature <0 12 103> shall be reported in kelvin (with precision in hundredths of a kelvin).

Note: Notes 1 and 2 under Regulation GBON 1.2.2.4 shall apply.

GBON 1.2.2.6 Relative humidity units

Relative humidity <0 13 003> shall be reported in units of a per cent.

GBON 1.2.2.7 Instrument failure

When the data are not available as a result of a temporary instrument failure, these values shall be included as missing values.

GBON 1.2.2.8 State of ground

State of ground (with or without snow) <0 20 062> and method of state of ground measurement <0 02 176> shall be reported. The synoptic hour at which this datum is reported shall be determined by regional decision. In addition to the synoptic hour, this datum should be reported at other synoptic hours, i.e. four times a day.

GBON 1.2.2.9 Snow depth

Total snow depth <0 13 013> and method of snow depth measurement <0 02 177> shall be reported when total snow depth is observed or set to missing when it's not observed.

GBON 1.2.2.9.1 Snow depth units

Total snow depth <0 13 013> shall be reported in metres (with precision in hundredths of a metre). The synoptic hour at which this datum is reported shall be determined by regional decision. In addition to the synoptic hour, this datum should be reported at other synoptic hours, i.e. four times a day.

GBON 1.2.2.9.2 No snow depth to report

Total snow depth shall be reported as 0.00 m if absence of snow, ice and other forms of solid precipitation on the ground is observed at the time of observation. A snow depth value of “-0.01 m” shall indicate a little (less than 0.005 m) snow. A snow depth value of “-0.02 m” shall indicate “snow cover not continuous”.

GBON 1.2.2.9.3 Snow depth definition

The measurement shall include snow, ice and all other forms of solid precipitation on the ground at the time of observation.

GBON 1.2.2.9.4 Snow depth is not uniform

When the depth is not uniform, the average depth over a representative area shall be reported.

GBON 1.2.2.10 Additional snow observations in sequence 3 07 103

When observed, snow density (liquid water content) <0 13 117>, method of snow water equivalent measurement <0 03 028> and snow water equivalent <0 13 163> shall be reported with sequence 3 07 103 (see GBON 1.1.2).

GBON 1.2.2.11 Intensity of precipitation

Intensity of precipitation (high accuracy) <0 13 155> shall be determined by the intensity at the time of the observation.

GBON 1.2.2.12 Total precipitation/total water equivalent

Total precipitation/total water equivalent <0 13 011> shall be reported for the last 24 hours in kilograms per square metre (with precision in tenths of a kilogram per square metre). If no precipitation was observed during the period of reference, it shall be reported as 0.0 kg m⁻². Trace shall be reported as “-0.1 kg m⁻²”.

GBON 1.2.2.13 Total precipitation/total water equivalent time period

Time period or displacement <0 04 024> for total precipitation/total water equivalent <0 13 011> shall be reported as -24 hours.

GBON 1.2.2.14 Total precipitation/total water equivalent sensor height

Height of sensor above local ground (or deck of marine platform) <0 07 032> for total precipitation/total water equivalent <0 13 011> shall be reported in metres (with precision in hundredths of a metre). This datum represents the actual height of the rain gauge rim above ground at the point where the rain gauge is located.

GBON 1.2.2.15 Wind direction and speed

The wind direction <0 11 001> shall be reported in degrees true and the wind speed <0 11 002> shall be reported in metres per second (with precision in tenths of a metre per second). Surface wind direction measured at a station within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian.

Calm shall be reported by setting wind direction to 0 and wind speed to 0. Variable shall be reported by setting wind direction to 0 and wind speed to a positive *non-missing* value.

GBON 1.2.2.16 Wind sensor height

Height of sensor above local ground (or deck of marine platform) <0 07 032> for wind measurement shall be reported in metres (with precision in hundredths of a metre). This datum represents the actual height of the sensors above ground at the point where the sensors are located.

GBON 1.2.2.17 Wind time period

The time period or displacement <0 04 025> for wind shall be reported as -10 minutes. However, when the 10-minute period includes a discontinuity in the wind characteristics, only data obtained after the discontinuity shall be used for reporting the mean values, and hence the period <0 04 025> in these circumstances shall be correspondingly reduced.

GBON 1.2.2.18 Wind time period

Time significance <0 08 021>qualifier for time period or displacement <0 04 025> for wind shall be set to 2 (time averaged).

GBON 1.2.2.19 Wind gust

Maximum wind gust direction <0 11 043> shall be reported in degrees true and speed of the maximum wind gust speed <0 11 041> shall be reported in metres per second (with precision in tenths of a metre per second).

GBON 1.2.2.20 Wind gust time period

Time period or displacement <0 04 025> for maximum wind gust direction <0 11 043> maximum wind gust speed <0 11 041> shall be determined by regional or national decision and reported as a negative value in minutes.

GBON 2 REPORTING GBON UPPER AIR OBSERVATIONS

GBON 2.1 BUFR sequences for upper air stations

The following BUFR sequence should be used for reporting GBON variables from upper air stations. BUFR sequences different from the one listed below may be used if the reporting practices for GBON variables in GBON 2.2 can be applied

GBON 2.1.1 BUFR Sequence for representation of TEMP, TEMP SHIP and TEMP MOBIL observation type data with higher precision of pressure and geopotential height <3 09 057>

ROW #	TABLE REFERENCE	TABLE REFERENCES	ELEMENT NAME
	F X Y		
1	3 09 057	(Sequence for representation of TEMP, TEMP SHIP and TEMP MOBIL observation type data with higher precision of pressure and geopotential height)	
2		3 01 150	WIGOS Identifier
3		3 01 111	Identification of launch site and instrumentation for P, T, U and wind measurements
4		3 01 128	Additional information on radiosonde ascent
5		3 01 113	Date/time of launch
6		3 01 114	Horizontal and vertical coordinates of launch site
7		3 02 049	Cloud information reported with vertical soundings
8		0 22 043	Sea/water temperature
9		1 01 000	Delayed replication of 1 descriptor
10		0 31 002	Extended delayed descriptor replication factor
11		3 03 056	Temperature, dewpoint and wind data at a pressure level with radiosonde position and higher precision of pressure and geopotential height
12		1 01 000	Delayed replication of 1 descriptor

<u>ROW #</u>	<u>TABLE REFERENCE</u> F X Y	<u>TABLE REFERENCES</u>	<u>ELEMENT NAME</u>
<u>13</u>	<u>3 09 057</u> (continued)	<u>0 31 001</u>	<u>Delayed descriptor replication factor</u>

GBON BUFR template 3 07 057 further expands as follows.

<u>#</u>	<u>FXY Expansion</u>		<u>Element name</u>	<u>Description</u>	<u>Unit, Scale</u>	<u>GBON Regulation</u>
<u>1</u>	<u>3 09 057</u>	<u>Sequence for representation of TEMP, TEMP SHIP and TEMP MOBIL observation type data with higher precision of pressure and geopotential height</u>				
<u>2</u>		<u>3 01 150</u>	<u>WIGOS identifier</u>	-	-	
<u>3</u>			<u>0 01 125</u>	<u>WIGOS identifier series</u>	<u>Numeric, 0</u>	
<u>4</u>			<u>0 01 126</u>	<u>WIGOS issuer of identifier</u>	<u>Numeric, 0</u>	
<u>5</u>			<u>0 01 127</u>	<u>WIGOS issue number</u>	<u>Numeric, 0</u>	

#	FX Y Expansion			Element name	Description	Unit, Scale	GBON Regulation
6	3 09 057 (continued)		0 01 128		WIGOS local identifier (character)	CCITT IA5, 0	
7		3 01 111	Identification of launch site and instrumentation for P, T, U and wind measurements				
8			3 01 001	WMO block and station numbers		-	-
9				0 01 001	WMO block number	Numeric, 0	
10				0 01 002	WMO station number	Numeric, 0	
11			0 01 011		Ship or mobile land station identifier	CCITT IA5, 0	
12			0 02 011		Radiosonde type	Code table, 0	
13			0 02 013		Solar and infrared radiation correction	Code table, 0	
14			0 02 014		Tracking technique/status of system used	Code table, 0	
15			0 02 003		Type of measuring equipment used	Code table, 0	
16		3 01 128	Additional information on radiosonde ascent		-	-	-
17			0 01 081		Radiosonde serial number	CCITT IA5, 0	
18			0 01 082		Radiosonde ascension number	Numeric, 0	
19			0 01 083		Radiosonde release number	Numeric, 0	

#	FX Y Expansion				Element name	Description	Unit, Scale	GBON Regulation
20	3 09 057 (continued)	3 01 128 (continued)	0 01 095		Observer identification		CCITT IA5, 0	
21			0 02 015		Radiosonde completeness		Code table, 0	
22			0 02 016		Radiosonde configuration		Flag table, 0	
23			0 02 017		Correction algorithms for humidity measurements		Code table, 0	
24			0 02 066		Radiosonde ground receiving system		Code table, 0	
25			0 02 067		Radiosonde operating frequency		Hz, -5	
26			0 02 080		Balloon manufacturer		Code table, 0	
27			0 02 081		Type of balloon		Code table, 0	
28			0 02 082		Weight of balloon		kg, 3	
29			0 02 083		Type of balloon shelter		Code table, 0	
30			0 02 084		Type of gas used in balloon		Code table, 0	
31			0 02 085		Amount of gas used in balloon		kg, 3	
32			0 02 086		Balloon flight train length		m, 1	
33			0 02 095		Type of pressure sensor		Code table, 0	

#	FX Y Expansion				Element name		Description	Unit, Scale	GBON Regulation
34	3 09 057 (continued)	3 01 128 (continued)	0 02 096		Type of temperature sensor			Code table, 0	
35			0 02 097		Type of humidity sensor			Code table, 0	
36			0 02 103		Radome			Flag table, 0	
37			0 02 191		Geopotential height calculation			Code table, 0	
38			0 25 061		Software identification and version number			CCITT IA5, 0	
39			0 35 035		Reason for termination			Code table, 0	
40		3 01 113	Date/time of launch		-	-	-	-	-
41			0 08 021		Time significance		= 18 Launch time	(see Note 11)	
42			3 01 011	Year, month, day		Launch time		-	-
43				0 04 001	Year			a, 0	
44				0 04 002	Month			mon, 0	
45				0 04 003	Day			d, 0	
46			3 01 013	Hour, minute, second			Launch time	-	-
47				0 04 004	Hour			h, 0	
48				0 04 005	Minute			min, 0	
49		3 01 114	Horizontal and vertical coordinates of launch site			-	-	-	-
50			3 01 021	Latitude/longitude (high accuracy)		-	-	-	-

#	FX Y Expansion				Element name	Description	Unit, Scale	GBON Regulation
51	3 09 057 (continued)			0 05 001	Latitude (high accuracy)		deg, 5	
52				0 06 001	Longitude (high accuracy)		deg, 5	
53			0 07 030		Height of station ground above mean sea level		m, 1	
54			0 07 031		Height of barometer above mean sea level		m, 1	
55			0 07 007		Height		m, 0	
56			0 33 024		Station elevation quality mark (for mobile stations)		Code table, 0	
57		3 02 049	Cloud information reported with vertical soundings		-	-	-	-
58			0 08 002		Vertical significance (surface observations)		Code table, 0	
59			0 20 011		Cloud amount	Low or middle clouds Nh	Code table, 0	
60			0 20 013		Height of base of cloud	h	m, -1	
61			0 20 012		Cloud type	Low clouds CL	Code table, 0	
62			0 20 012		Cloud type	Middle clouds CM	Code table, 0	
63			0 20 012		Cloud type	High clouds CH	Code table, 0	
64			0 08 002		Vertical significance (surface observations)	Set to missing	Code table, 0	
65		0 22 043			Sea/water temperature	Scale: 2	K, 2	

#	FX Y Expansion				Element name	Description	Unit, Scale	GBON Regulation
66	<u>3 09 057</u> (continued)	<u>1 01 000</u>			<u>Delayed replication of 1 descriptor</u>			
67		<u>0 31 002</u>			<u>Extended delayed descriptor replication factor</u>			
68		<u>3 03 056</u>	<u>Temperature, dewpoint and wind data at a pressure level with radiosonde position and higher precision of pressure and geopotential height</u>					
69			<u>0 04 086</u>		<u>Long time period or displacement</u>	<u>Since launch time</u>	<u>s, 0</u>	
70			<u>0 08 042</u>		<u>Extended vertical sounding significance</u>		<u>Flag table, 0</u>	
71			<u>2 07 001</u>		<u>Increase scale, reference value and data width</u>			
72			<u>0 07 004</u>		<u>Pressure</u>	<u>Scale: 0</u>	<u>Pa, -1</u>	
73			<u>0 10 009</u>		<u>Geopotential height</u>	<u>Scale: 1</u>	<u>gpm, 0</u>	
74			<u>2 07 000</u>		<u>Increase scale, reference value and data width</u>	<u>Cancel</u>		
75			<u>0 05 015</u>		<u>Latitude displacement (high accuracy)</u>	<u>Since launch site</u>	<u>deg, 5</u>	
76			<u>0 06 015</u>		<u>Longitude displacement (high accuracy)</u>	<u>Since launch site</u>	<u>deg, 5</u>	
77			<u>0 12 101</u>		<u>Temperature/air temperature</u>	<u>Scale: 2</u>	<u>K, 2</u>	
78			<u>0 12 103</u>		<u>Dewpoint temperature</u>	<u>Scale: 2</u>	<u>K, 2</u>	
79			<u>0 11 001</u>		<u>Wind direction</u>		<u>degree true, 0</u>	
80			<u>0 11 002</u>		<u>Wind speed</u>		<u>m/s, 1</u>	
81		<u>1 01 000</u>			<u>Delayed replication of 1 descriptor</u>			

#	FX Y Expansion				Element name	Description	Unit, Scale	GBON Regulation
82	3 09 057 (continued)	0 31 001			Delayed descriptor replication factor			
83		3 03 051	Wind shear data at a pressure level with radiosonde position				-	-
84			0 04 086		Long time period or displacement	Since launch time	s, 0	
85			0 08 042		Extended vertical sounding significance		Flag table, 0	
86			0 07 004		Pressure		Pa, -1	
87			0 05 015		Latitude displacement (high accuracy)	Since launch site	deg, 5	
88			0 06 015		Longitude displacement (high accuracy)	Since launch site	deg, 5	
89			0 11 061		Absolute wind shear in 1 km layer below		m/s, 1	
90			0 11 062		Absolute wind shear in 1 km layer above		m/s, 1	

GBON 2.2 REPORTING PRACTICES

GBON 2.2.1 Identification of launch site and instrumentation for P, T, U and wind measurements <3 01 111>

GBON 2.2.1.1 Sequence for WIGOS station identifier

The sequence WIGOS station identifier (WSI) <3 01 150> shall be added before the first element if not included in the sequence.

GBON 2.2.1.2 WSI values

The elements of sequence WSI <3 01 150> shall not be set to missing and shall have the values corresponding with the station record in <https://oscar.wmo.int/surface>.

GBON 2.2.1.3 Identification of launch site

WMO block number <0 01 001> and WMO station number <0 01 002> shall be always reported as a non-missing value in reports from a fixed land station. WMO block and station number may be included in reports from a fixed sea station if available.

Ship or mobile land station identifier <0 01 011> shall be always reported not exceeding 9 characters in reports from ships or mobile stations. Ship or mobile station identifier <0 01 011> shall be always set to a missing value in reports from a fixed land station.

GBON 2.2.1.4 Instrumentation for P, T, U and wind measurement

Radiosonde type <0 02 011>, solar and infrared radiation correction <0 02 013>, tracking techniques/status of system used <0 02 014> and type of measuring equipment used <0 02 003> shall be reported.

GBON 2.2.2 Date/time of launch <3 01 113>

Time significance <0 08 021> shall always be set to 18 to indicate that the following entries specify the date and time of launching the radiosonde.

The true time of launch shall be reported with year, month day <3 01 011> and hour, minute, second <3 01 013>.

Time of launch <3 01 013> shall be reported with the highest possible accuracy available. If the launch time is not available with second accuracy, the entry <0 04 006> for seconds shall be set to zero.

GBON 2.2.3 Horizontal and vertical coordinates of launch site <3 01 114>

Latitude (high accuracy) <0 05 001> and longitude (high accuracy) <0 06 001> of the launch site shall be reported in degrees with precision in 10^{-5} of a degree.

Height of station ground above mean sea level <0 07 030> and height of barometer above mean sea level <0 07 031> shall be reported in metres with precision in tenths of a metre.

Height <0 07 007> of release of sonde above mean sea level shall be reported in metres.

Station elevation quality mark <0 33 024> shall be reported to indicate the accuracy of the vertical coordinates of the mobile land station. Fixed land stations and sea stations shall report this datum as a missing value.

Note: The official altitude of the aerodrome (HA) shall not be used to report Height of station ground above mean sea level <0 07 030> in BUFR messages from aerodromes. Those are two different vertical coordinates. "Height of station ground above mean sea level" for each station should be made available to the encoding centre concerned, which may be a centre within the same NMHS or other NMC/RTH.

GBON 2.2.4 Cloud information reported with vertical sounding <3 02 049>

GBON 2.2.4.1 Vertical significance (surface observations) – Code table 0 08 002

To specify vertical significance <0 08 002> within the sequence 3 02 049, a code figure shall be selected in the following way:

- (a) If low clouds are observed, then code figure 7 (Low cloud) shall be used;
- (b) If there are no low clouds but middle clouds are observed, then code figure 8 (Middle clouds) shall be used;
- (c) If there are no low and there are no middle clouds but high clouds are observed, then code figure 0 shall be used;
- (d) If sky is obscured by fog and/or other phenomena, then code figure 5 (Ceiling) shall be used;
- (e) If there are no clouds (clear sky), then code figure 62 (Value not applicable) shall be used;
- (f) If the cloud cover is not discernible for reasons other than (d) above or observation is not made, then code figure 63 (Missing value) shall be used.

GBON 2.2.4.2 Cloud amount (of low or middle clouds) – Code table 0 20 011

Amount of all the low clouds (clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus) present or, if no low clouds are present, the amount of all the middle clouds (clouds of the genera Altopumulus, Altostratus, and Nimbostratus) present.

GBON 2.2.4.2.1 Cloud amount shall be reported as follows:

- (a) If there are low clouds, then the total amount of all low clouds, as actually seen by the observer during the observation shall be reported for the cloud amount;
- (b) If there are no low clouds but there are middle clouds, then the total amount of the middle clouds shall be reported for the cloud amount;
- (c) If there are no low clouds and there are no middle clouds but there are high clouds (clouds of the genera Cirrus, Cirrocumulus, and Cirrostratus), then the cloud amount shall be reported as zero.

GBON 2.2.4.2.2

Amount of Altocumulus perlucidus or Stratocumulus perlucidus ("mackerel sky") shall be reported using code figure 7 or less since breaks are always present in this cloud form even if it extends over the whole celestial dome.

GBON 2.2.4.2.3

When the clouds reported for cloud amount are observed through fog or an analogous phenomenon, the cloud amount shall be reported as if these phenomena were not present.

GBON 2.2.4.2.4

If the clouds reported for cloud amount include contrails, then the cloud amount shall include the amount of persistent contrails. Rapidly dissipating contrails shall not be included in the value for the cloud amount.

GBON 2.2.4.3 Height of base of lowest cloud

Height above surface of the base <0 20 013> of the lowest cloud seen shall be reported in metres (with precision in tens of metres).

Note: The term « height above surface » shall be considered as being the height above the official aerodrome elevation or above station elevation at a non-aerodrome station or the height above water surface of sea or lake.

GBON 2.2.4.3.1

When the station is in fog, a sandstorm or in blowing snow but the sky is discernible, the base of the lowest cloud shall refer to the base of the lowest cloud observed, if any. When, under the above conditions, the sky is not discernible, the base of the lowest cloud shall be replaced by vertical visibility.

GBON 2.2.4.3.2

When no cloud is reported (total cloud cover = 0) the base of the lowest cloud *shall be reported as a missing value.*

GBON 2.2.4.3.3

When, by national decision, clouds with bases below the station are reported from the station and clouds with bases below and tops above the station are observed, the base of the lowest cloud *shall be reported having a negative value if the base of cloud is discernible, or as a missing value.*

GBON 2.2.4.4 Cloud type of low, middle and high clouds – Code table 0 20 012

Clouds of the genera Stratocumulus, Stratus, Cumulus, and Cumulonimbus (low clouds) shall be reported for the first entry 0 20 012, clouds of the genera Altopumulus, Altostratus, and Nimbostratus (middle clouds) shall be reported for the second entry 0 20 012 and clouds of the genera Cirrus, Cirrosumulus, and Cirrostratus (high clouds) shall be reported for the third entry 0 20 012.

GBON 2.2.4.4.1

The reporting of type of low, middle and high clouds shall be as specified in the *International Cloud Atlas* (WMO-No. 407), Volume I.

GBON 2.2.5Sea/water temperature

Sea/water temperature <0 22 043> shall be reported in kelvin (with precision in hundredths of a kelvin). Sea/water temperature data shall be reported with precision in hundredths of a degree even if they are available with the accuracy in tenths of a degree.

Notes:

(1) This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.

(2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

GBON 2.2.5.1 Sea/water temperature shall always be included in reports from sea stations, when data are available.

GBON 2.2.6Temperature, dewpoint and wind data at pressure levels

Temperature, dewpoint and wind data at pressure levels obtained during the radiosonde ascent shall be included in descending order with respect to pressure. Data at each pressure level shall be included only once. For example, if a significant level with respect to air temperature and relative humidity and a standard isobaric surface coincide, data for that level shall be included only once, the multiple attributes being indicated by Extended vertical sounding significance <0 08 042> as specified in GBON 2.2.6.2.2

GBON 2.2.6.1 Number of reported pressure levels

The number of reported pressure levels shall be indicated by Extended delayed descriptor replication factor <0 31 002> in BUFR.

The number of pressure levels shall never be set to a missing value and set to a positive value in a NIL report. If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

GBON 2.2.6.1.1

All required data from the entire radiosonde ascent shall be reported in a BUFR message that shall be produced when the sounding is completed. In interest of timely data delivery, however, a BUFR message should be sent when level 100 hPa is reached.

GBON 2.2.6.2 Temperature, dewpoint and wind data at a pressure level with radiosonde position <3 03 056>

GBON 2.2.6.2.1 Long time displacement (since launch time)

Long time period or displacement <0 04 086> represents the time offset from the launch time specified in Regulation GBON 2.2.2, and shall be reported in seconds if available.

GBON 2.2.6.2.2 Extended vertical sounding significance – Flag table 0 08 042

This datum shall be used to specify vertical sounding significance in the following way (see Regulation GBON 2.2.7):

- (a) Bit No. 1 set to 1 indicates surface;
- (b) Bit No. 2 set to 1 indicates a standard level;
- (c) Bit No. 3 set to 1 indicates a tropopause level;
- (d) Bit No. 4 set to 1 indicates a maximum wind;
- (e) Bit No. 5 set to 1 indicates a level significant with respect to temperature
- (f) Bit No. 6 set to 1 indicates a level significant with respect to relative humidity;
- (g) Bit No. 7 set to 1 indicates a level significant with respect to wind;
- (h) Bit No. 8 set to 1 indicates beginning of missing temperature data and bit No. 9 set to 1 indicates end of missing temperature data;
- (i) Bit No. 10 set to 1 indicates beginning of missing humidity data and bit No. 11 set to 1 indicates end of missing humidity data;
- (j) Bit No. 12 set to 1 indicates beginning of missing wind data bit No. 13 set to 1 indicates end of missing wind data;
- (k) Bit No. 14 set to 1 indicates the top of wind sounding;
- (l) Bit No. 15 set to 1 indicates a level determined by regional decision;
- (m) All bits set to 0 indicate a level determined by national decision or a level of no significance that has been included when high-resolution data are reported;
- (n) All bits set to 1 indicate a missing value.

GBON 2.2.6.2.3 Pressure

Pressure <0 07 004> shall be reported in pascals (with precision of pascals).

GBON 2.2.6.2.4 Geopotential height

Geopotential height <0 10 009> of the level shall be reported in geopotential metres.

GBON 2.2.6.2.5 Radiosonde drift – latitude and longitude displacements

Latitude displacement <0 05 015> represents the latitude offset from the latitude of the launch site specified in Regulation GBON 2.2.3, and shall be reported in degrees with precision in 10^{-5} of a degree if available. Longitude displacement <0 06 015> represents the longitude offset from the longitude of the launch site specified in Regulation GBON 2.2.3, and shall be reported in degrees with precision in 10^{-5} of a degree if available.

GBON 2.2.6.2.6 Temperature

Temperature <0 12 101> shall be reported in kelvin (with precision in hundredths of a kelvin). Temperature data shall be reported with precision in hundredths of a degree even if they are measured with the accuracy in tenths of a degree.

Notes:

- (1) This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

Ay<

Dewpoint temperature <0 12 103> shall be reported in kelvin (with precision in hundredths of a kelvin).

Notes:

- (1) This requirement is based on the fact that conversion from the Kelvin to the Celsius scale has often resulted into distortion of the data values.
- (2) Temperature t (in degrees Celsius) shall be converted into temperature T (in kelvin) using equation: $T = t + 273.15$.

GBON 2.2.6.2.7.1

Dewpoint temperature data shall be derived using the function (or a near equivalent) for a relationship between saturation vapour pressure over Water and air temperature (specified in the *Technical Regulations* (WMO-No. 49)). Dewpoint temperature data shall not be reported when the air temperature is outside the range stated by WMO for the application of the function; a lesser range may be used as a national practice.

GBON 2.2.6.2.8 Wind direction and speed

The wind direction <0 11 001> shall be reported in degrees true and the wind speed <0 11 002> shall be reported in metres per second (with precision in tenths of a metre per second).

Wind direction measured at a station within 1° of the North Pole or within 1° of the South Pole shall be reported in such a way that the azimuth ring shall be aligned with its zero coinciding with the Greenwich 0° meridian. *The wind direction at each level should be consistent with the reported longitude at that level.*

GBON 2.2.6.2.8.1.1

When during an ascent the pressure data can no longer be obtained, but wind data can be obtained, the wind data so obtained shall not be

Reported in the BUFR message in which data are described by the common sequence 3 09 056. These wind data so obtained may be reported using BUFR template TM 309051 suitable PILOT, PILOT SHIP or PILOT MOBIL data.

GBON 2.2.6.2.8.1.2

Only wind data obtained from the radiosonde ascent by either visual or electronic means shall be included in the BUFR message in

Which data are described by the common sequence 3 09 057. Wind data obtained by means other than a radiosonde-type ascent shall not be included in a message under common sequence 3 09 057.

GBON 2.2.7 Criteria for reporting standard and significant levels

GBON 2.2.7.1 Surface

The surface level shall be always reported.

Note: The value of extended vertical sounding significance <0 08 042> at the surface level shall indicate that this level is also a level significant with respect to temperature, relative humidity and wind, i.e. not only bit No. 1 but also bits Nos. 5, 6 and 7 shall be set to 1.

GBON 2.2.7.2 Standard levels

GBON 2.2.7.2.1

The standard levels of 1 000, 925, 850, 700, 500, 400, 300, 250, 200, 150, 100, 70, 50, 30, 20 and 10 hPa shall be reported in ascending order with respect to altitude.

GBON 2.2.7.2.2

When the geopotential of a standard level is lower than the altitude of the reporting station, the time displacement, latitude displacement and longitude displacement for that level shall be set to zero and the air temperature, dewpoint temperature and wind data for that level shall be reported as missing values.

GBON 2.2.7.2.3

When air temperature, dewpoint temperature or wind data at a standard level are not available, the corresponding entries for that level shall be reported as missing values.

GBON 2.2.7.2.4

Whenever it is desired to extrapolate a sounding for the computation of the geopotential at a standard level, the following rules shall apply:

- (a) Extrapolation is permissible if, and only if, the pressure difference between the minimum pressure of the sounding and the isobaric surface for which the extrapolated value is being computed does not exceed one quarter of the pressure at which the extrapolated value is desired, provided the extrapolation does not extend through a pressure interval exceeding 25 hPa;
- (b) For the purpose of geopotential calculation, and for this purpose only, the sounding will be extrapolated, using two points only of the sounding curve on a T-log p diagram, namely that at the minimum pressure reached by the sounding and that at the pressure given by the sum of this minimum pressure and the pressure difference, mentioned in (a) above.

GBON 2.2.7.3 Tropopause level(s)

GBON 2.2.7.3.1

When a tropopause (one or more) is observed, the corresponding number of levels shall be included (indicated by <0 08 042> bit No. 3 set to 1).

GBON 2.2.7.3.2

When no tropopause data are observed, no level shall be indicated by bit No. 3 of <0 08 042> set to 1.

GBON 2.2.7.4 Maximum wind level(s)

GBON 2.2.7.4.1

When a maximum wind level (one or more) is reported, the corresponding number of levels shall be included in the report indicated by bit No. set to 1 in Extended vertical sounding significance <0 08 042>.

Notes:

- (1) Criteria for determining maximum wind levels are given in Regulations below.
- (2) As a maximum wind level is also a level significant with respect to wind, bit No. 7 as well as bit No. 4 shall be set to 1 in the Extended vertical sounding significance <0 08 042>.

GBON 2.2.7.4.2

When no maximum wind level is observed, no level shall be indicated by bit No. 4 of <0 08 042> set to 1.

GBON 2.2.7.4.3

A maximum wind level:

- (a) Shall be determined by consideration of the list of significant levels for wind speed, as obtained by means of the relevant recommended or equivalent national method (see the Note under Regulation GBON 2.2.7.7.2) and *not* by consideration of the original wind-speed curve;
- (b) Shall be located above the 500-hPa isobaric surface and shall correspond to a speed of more than 30 metres per second.

Note: A maximum wind level is defined as a level at which the wind speed is greater than that observed immediately above and below that level.

GBON 2.2.7.4.4

Whenever more than one maximum wind level exists, these levels shall be reported as follows:

- (a) The level of greatest maximum wind speed shall be always included;

- (b) The other levels shall be included in the report only if their speed exceeds those of the two adjacent minima by at least 10 metres per second;
- (c) Furthermore, the highest level attained by the sounding shall be indicated as a maximum wind level, provided:
- (i) It satisfies the criteria set forth in Regulation GBON 2.2.5.4.3 above;
 - (ii) It constitutes the level of the greatest speed of the whole sounding.

GBON 2.2.7.4.5

If the top of the wind sounding corresponds to the highest wind speed observed throughout the ascent, this level shall be indicated by Extended vertical sounding significance <0 08 042> – bit No. 4 set to 1 (maximum wind level), bit No. 7 set to 1 (level significant with respect to wind) and bit No. 14 set to 1 (top of wind sounding).

Note: For the purpose of the above regulation, the “top of the wind sounding” is to be understood as the highest level for which wind data are available.

GBON 2.2.7.5 Levels significant with respect to temperature

GBON 2.2.7.5.1

The reported significant levels alone shall make it possible to reconstruct the air temperature profile within the limits of the criteria specified.

If the criteria for determination of significant levels with respect to air temperature are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

GBON 2.2.7.5.2

The following shall be included as “mandatory” significant temperature levels:

- (a) Surface level and the highest level of the sounding;
- (b) A level between 110 and 100 hPa;
- (c) Bases and tops of inversions and isothermal layers which are at least 20 hPa thick, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher;
- (d) Bases and tops of inversion layers which are characterized by a change in temperature of at least 2.5 °C, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher.
- (e) The inversion layers of (c) and (d) may be comprised of several thinner inversion layers separated by thin layers of temperature lapse. To allow for this situation, the tops of the inversion layers of (c) and (d) shall each be at a level such that no further inversion layers, whether thick or thin, shall occur for at least 20 hPa above the level.

GBON 2.2.7.5.3

The following shall be included as “additional” significant levels. They shall be selected in the order given, thereby giving priority to representing the temperature profile. As far as possible, these additional levels shall be the actual levels at which prominent changes in the lapse rate of air temperature occur:

- (a) Levels which are necessary to ensure that the temperature obtained by linear interpolation (on a T-log P or essentially similar diagram) between adjacent significant levels shall not depart from the observed temperature by more than 1 °C below the first significant level reported above the 300-hPa level or the first tropopause, whichever level is the lower, or by more than 2 °C thereafter;
- (b) Levels which are necessary to limit the interpolation error on diagrams other than T-log P. These levels shall be such that the pressure at one significant level divided by the pressure of the preceding significant layer shall exceed 0.6 for levels up to the first tropopause and shall be determined by use of the method for selecting additional levels but with application of tighter criteria.

GBON 2.2.7.5.4

When a significant level with respect to air temperature and a standard level coincide, data for that level shall be reported only once.

GBON 2.2.7.6 **Levels significant with respect to relative humidity**

GBON 2.2.7.6.1

The reported significant levels alone shall make it possible to reconstruct the relative humidity profiles within the limits of the criteria specified.

If the criteria for determination of significant levels with respect to relative humidity are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

GBON 2.2.7.6.2

The following shall be included as “mandatory” significant humidity levels:

- (a) Surface level and the highest level of the sounding;
- (b) A level between 110 and 100 hPa;
- (c) Bases and tops of inversions and isothermal layers which are at least 20 hPa thick, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher;

(d) Bases and tops of inversion layers which are characterized by a change in relative humidity of at least 20 per cent, provided that the base of the layer occurs below the 300-hPa level or the first tropopause, whichever is the higher.

Note: The inversion layers of (c) and (d) may be comprised of several thinner inversion layers separated by thin layers of temperature lapse. To allow for this situation, the tops of the inversion layers of (c) and (d) shall each be at a level such that no further inversion layers, whether thick or thin, shall occur for at least 20 hPa above the level.

GBON 2.2.7.6.3

The following shall be included as “additional” significant levels. They shall be selected in the order given, thereby giving priority to representing the temperature profile. As far as possible, these additional levels shall be the actual levels at which prominent changes in the lapse rate of air temperature occur:

- (a) Levels which are necessary to ensure that the relative humidity obtained by linear interpolation between adjacent significant levels shall not depart by more than 15 per cent from the observed values. (The criterion of 15 per cent refers to an amount of relative humidity and NOT to the percentage of the observed value, e.g. if an observed value is 50 per cent, the interpolated value shall lie between 35 per cent and 65 per cent.);
- (b) Levels which are necessary to limit the interpolation error on diagrams other than T-log P. These levels shall be such that the pressure at one significant level divided by the pressure of the preceding significant layer shall exceed 0.6 for levels up to the first tropopause and shall be determined by use of the method for selecting additional levels but with application of tighter criteria.

GBON 2.2.7.6.4

When a significant layer with respect to relative humidity and a standard level coincide, data for that level shall be reported only once.

GBON 2.2.7.7 Levels significant with respect to wind

GBON 2.2.7.7.1

Significant wind levels shall be chosen so that the data from them alone shall make it possible to reconstruct the wind profile with sufficient accuracy for practical use.

If the criteria for determination of significant levels with respect to wind speed and direction are satisfied at a particular point of altitude, data for all variables (if available) shall be reported for that level.

GBON 2.2.7.7.2

Criteria for determining significant levels with respect to changes in wind speed and direction:

- (a) The direction and speed curves (in function of the log of pressure or altitude) can be reproduced with their prominent characteristics;
- (b) These curves can be reproduced with the accuracy of at least 10 degrees true for direction and five metres per second for speed.

Note: To satisfy these criteria, the following method of successive approximations is recommended, but other methods of attaining equivalent results may suit some national practices better and may be used:

- (i) The surface level and highest level for which wind data are available constitute the first and the last significant levels. The deviation from the linearly interpolated values between these two levels is then considered. If no direction deviates by more than 10 degrees true and no speed by more than five metres per second, no other significant level need be reported. Whenever one parameter deviates by more than the limit specified in paragraph (b) above the level of greatest deviation becomes a supplementary significant level for both parameters;
- (ii) The additional significant levels so introduced divide the sounding into two layers. In each separate layer, the deviation from the linearly interpolated values between the base and the top are then considered. The process used in paragraph (i) above is repeated and yields other significant levels. These additional levels in turn modify the layer distribution, and the method is applied again until any level is approximated to the above-mentioned specified values.

GBON 2.2.7.8 Beginning and end of missing temperature data

GBON 2.2.7.8.1

A layer for which temperature data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 20 hPa thick. The boundary levels are the levels closest to the bottom and the top of the layer for which temperature data are available. The boundary levels are not required to meet "significant temperature level" criteria.

GBON 2.2.7.9 Beginning and end of missing humidity data

GBON 2.2.7.9.1

A layer for which dewpoint temperature data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 20 hPa thick. The boundary levels are the levels closest to the bottom and the top of the layer for which dewpoint temperature data are available. The boundary levels are not required to meet "significant humidity level" criteria.

GBON 2.2.7.10 Beginning and end of missing wind data

GBON 2.2.7.10.1

A layer for which wind data are missing shall be indicated by reporting the boundary levels of the layer, provided that the layer is at least 50 hPa thick. The boundary levels are the levels closest to the bottom and the top of the layer for which the observed data are available. The boundary levels are not required to meet "significant wind level" criteria.

GBON 2.2.8 Wind shear data

GBON 2.2.8.1 Number and order of levels for which wind shear is reported

GBON 2.2.8.1.1

The number of levels with wind shear data shall be indicated by Delayed descriptor replication factor 0 31 001 in BUFR and by a four-digit number in the Data Section corresponding to the position of the replication descriptor in the Data Description Section of CREX.

Notes:

- (1) The number of levels with wind shear data shall never be set to a missing value.
- (2) The number of levels with wind shear data shall be set to a positive value in a NIL report.
- (3) The number of levels with wind shear data shall be set to zero if data for vertical wind shear are not computed and required.
- (4) If data compression is to be used, BUFR Regulation 94.6.3, Note 2, sub-note ix shall apply.

GBON 2.2.8.1.2

Whenever wind shear data are reported for more than one level, these maximum wind levels shall be included in the same order as in the sequence <3 03 056>, i.e. in descending order with respect to pressure.

GBON 2.2.8.2 Wind shear data at a pressure level with radiosonde position <3 03 051>

GBON 2.2.8.2.1 Long time displacement (since launch time)

Long-time displacement <0 04 086> represents the time offset from the launch time specified in Regulation GBON 2.2.2, and shall be reported in seconds if available.

GBON 2.2.8.2.2 Extended vertical sounding significance – Flag table 0 08 042

A level, for which wind shear data are reported, shall be indicated by vertical sounding significance <0 08 042> – bit No. 4 set to 1 (maximum wind level) and by bit No. 7 set to 1 (level significant with respect to wind). Moreover, if the top of the wind sounding corresponds to the highest wind speed observed throughout the ascent, this level shall be indicated also by bit No. 14 set to 1 (top of wind sounding).

GBON 2.2.8.2.3 Pressure

Pressure <0 07 004> shall be reported in pascals with precision in tens of pascals.

GBON 2.2.8.2.4 Latitude and longitude displacements

Latitude displacement <0 05 015> represents the latitude offset from the latitude of the launch site specified in Regulation GBON 2.2.3, and shall be reported in degrees with precision in 10⁻⁵ of a degree if available. Longitude displacement 0 06 015 represents the longitude offset from the longitude of the launch site specified in Regulation GBON 2.2.3, and shall be reported in degrees with precision in 10⁻⁵ of a degree if available.

GBON 2.2.8.2.5 Wind shear data

Absolute wind shear in 1 km layer below <0 11 061> and absolute wind shear in 1 km layer above <0 11 062> shall be reported in metres per second (with precision in tenths of a metre per second), if data for vertical wind shear are computed and required.

GBON 2.2.9 Data required by regional or national reporting practices

If regional or national reporting practices require inclusion of temperature, humidity and/or wind data at additional levels, these data shall be reported using sequence <3 03 056> for temperature, dewpoint, wind at a pressure level. Regulation GBON 2.2.6 shall apply.

(1) A level determined by regional decision shall be indicated by Extended vertical sounding significance <0 08 042> – bit No. 15 set to 1.

(2) A level determined by national decision shall be indicated by Extended vertical sounding significance <0 08 042> – all bits set to 0.

GBON 2.2.9.1 Additional data required by reporting practices in RA I

Temperature, dewpoint, wind data at additional levels shall be reported in compliance with Regulation GBON 2.2.9.

GBON 2.2.9.2 Additional data required by reporting practices in RA II

GBON 2.2.9.2.1

No additional data are required by regional reporting practices in RA II.

GBON 2.2.9.2.2

The inclusion of wind shear data shall be left to national decision. Members are recommended to include these data as often as possible.

GBON 2.2.9.3 Additional data required by reporting practices in RA III

No regional requirements are indicated for reporting TEMP, TEMP SHIP and TEMP MOBIL data in RA III.

GBON 2.2.9.4 Additional data required by reporting practices in RA IV

GBON 2.2.9.4.1

When available, temperature, dewpoint, wind data for levels 7, 5, 3, 2 and 1 hPa shall be reported in compliance with Regulation GBON 2.2.9.

GBON 2.2.9.4.2

When required, additional information shall be reported using RA IV BUFR template for data representation of TEMP, TEMP SHIP and TEMP MOBIL data as shown in Annex I to Part B/C25.

GBON 2.2.9.5 Additional data required by reporting practices in RA V

No regional requirements are indicated for reporting TEMP, TEMP SHIP and TEMP MOBIL data in RA V.

GBON 2.2.9.6 Additional data required by reporting practices in RA VI

GBON 2.2.9.6.1

The inclusion of wind shear data shall be left to national decision. Members are recommended to include these data as often as possible.

GBON 2.2.9.6.2

Wind direction and speed shall be reported:

(i) For 900 or 1 000 metres above the surface;

(ii) For 800 hPa level;

(iii) For 600 hPa level.

Provisional Copy
2023

Attachment I

EXAMPLES OF TEMPLATES FOR THE TRANSMISSION IN BUFR OR CREX OF OTHER DATA TYPES

These templates, some of which have not yet been validated, can be found on the WMO Web server at <https://community.wmo.int/activity-areas/wmo-codes/manual-codes/volume-i2/template-examples>.

Provisional Copy
2023

Provisional Copy
2023

Attachment II

LIST OF ALPHANUMERIC CODE TABLES RELATED TO BUFR AND CREX CODE TABLES AND FLAG TABLES

BUFR/CREX code or flag table	Related code table, regulation or code form in alphanumeric codes	Remarks
0 01 003	A ₁ – Code table 0161	—
0 01 007	I ₆ I ₆ I ₆	Common Code table C–5
0 01 031	F ₁ F ₂ , F ₃ F ₃ F ₃	Common Code table C–1
0 01 032	—	Defined by originating/generating centre
0 01 033	F ₁ F ₂ , F ₃ F ₃ F ₃	Common Code table C–1
0 01 034	F ₁ F ₂ , F ₃ F ₃ F ₃	See Common Code table C–12
0 02 001*	i _x – Code table 1860	—
0 02 002	i _u – Code table 1853	—
0 02 003	a ₄ – Code table 0265	—
0 02 004	i _E – Code table 1806	—
0 02 011	r _a r _a – Code table 3685 (0–89)	Defined in common Code table C–2
0 02 012	—	To be developed
0 02 013	s _r – Code table 3849	—
0 02 014	s _a s _a – Code table 3872	—
0 02 015	r _a r _a – Code table 3685 (91–95)	Defined in common Code table C–2
0 02 016	—	—
0 02 019	—	Common Code table C–8
0 02 021	I ₃	—
0 02 022	I ₄ – Code table 1765	—
0 02 023	w _i – Code table 4639	—
0 02 030	k ₅ – Code table 2266	—
0 02 031	k ₃ – Code table 2264	—
	k ₄ – Code table 2265	—
0 02 032	k ₁ – Code table 2262	Numerical variation in each table
0 02 033	k ₂ – Code table 2263	—
0 02 034	X _t X _t – Code table 4780	—
0 02 038	s _s – Code table 3850	—
0 02 039	s _w – Code table 3855	—
0 02 040	k ₆ – Code table 2267	—
0 02 042	i _c – Code table 1833	—
0 02 044	I _m – Code table 1744	—
0 02 045	I _p – Code table 1747	—
0 02 051	i _y – Code table 1857	—
0 02 061	s ₁ – Code table 3866	—
0 02 062	s ₂ – Code table 3867	—
0 02 149	B _t B _t – Code table 0370	Additional entries in Code table 0 02 149
0 02 160	R _w – Code table 3555	—

* See note at the end of this attachment.

ATTACHMENT II

BUFR/CREX code or flag table	Related code table, regulation or code form in alphanumeric codes	Remarks
0 04 059	g – Code table 1400	More flexible than Code table 1400
0 04 080	m _S , m _T , m _C – Code table 2604	—
0 08 001	TEMP/TEMP SHIP – Sections 2 to 6	—
0 08 002	SYNOP/SHIP – Regulation 12.4.10.1	—
0 08 004	AMDAR – Regulation 42.2	—
0 08 009	i _p i _p i _p – AMDAR	—
0 08 011	F _t – Code table 1152	—
0 08 014	METAR/SPECI – Regulation 15.7.6	—
0 08 016	METAR/SPECI – Regulation 15.14	—
0 08 017	METAR/SPECI – Regulation 15.14.3	—
0 08 050	CLIMAT – Qualifier for number of missing values	—
0 08 052	CLIMAT – Condition for which number of days of occurrence	—
0 08 053	CLIMAT – Day of occurrence	—
0 08 054	METAR/SPECI – Regulation 15.5.6	—
0 08 079	METAR/SPECI/TAF – Product status	—
0 10 063	a – Code table 0200	—
0 11 031	i – Code table 1800	—
	B _A – Code table 0302	—
0 13 041	s _p – Code table 3847	—
0 13 051	R _d – Code table 3534	—
0 19 100	t _e – Code table 4035	—
0 19 101	A _C – Code table 0104	—
0 19 102	S _C – Code table 3704	—
0 19 103	W _C – Code table 4504	—
0 19 104	a _C – Code table 0204	—
0 19 105	r _t – Code table 3652	—
0 19 107	t _m – Code table 4044	—
0 19 108	A _t – Code table 0152	—
0 19 109	W _f – Code table 4536	—
0 19 110	a _t – Code table 0252	—
0 20 003*	ww – Code table 4677	—
	w _a w _a – Code table 4680	—
	w ₁ w ₁ – Code table 4687	—
0 20 004	W ₁ – Code table 4561	—
	W _{a1} – Code table 4531	—
0 20 005	W ₂ – Code table 4561	—
	W _{a2} – Code table 4531	—
0 20 009	METAR/SPECI	—
0 20 011	N – Code table 2700	—
0 20 012	C – Code table 0500	—
	C _H – Code table 0509	—
	C _M – Code table 0515	—
	C _L – Code table 0513	—
0 20 017	C _t – Code table 0552	—
0 20 018	METAR/SPECI – Regulation 15.7.4.3	—
0 20 032	R _S – Code table 3551	—
0 20 033	I _S – Code table 1751	—
0 20 034	c _i – Code table 0639	—

* See note at the end of this attachment.

ATTACHMENT II

BUFR/CREX code or flag table	Related code table, regulation or code form in alphanumeric codes	Remarks
0 20 035	b _i – Code table 0439	—
0 20 036	z _i – Code table 5239	—
0 20 037	S _i – Code table 3739	—
0 20 040	S' ₈ – Code table 3776	—
0 20 041	I _c – Code table 1733	Additional entries in Code table 0 20 041
0 20 055	C _s – Code table 430 (Vol. II)	—
0 20 062	E – Code table 0901	—
	E' – Code table 0975	—
0 20 063	S _P S _P S _P S _P – Code table 3778	—
	A – Code table 0101	—
	A ₃ – Code table 0163	—
	C _c – Code table 0533	—
	S ₀ – Code table 3761	—
	S _q – Code table 3848	—
	T _w – Code table 3955	—
	Z ₀ – Code table 5161	—
0 20 071	A _i – Code table 0139	—
0 20 085	METAR/SPECI – Regulation 15.13.6.1	—
0 20 086	E _R – Code table 0919	—
0 20 087	C _R – Code table 0519	—
0 20 089	B _R B _R – Code table 0366	—
0 20 090	C _s – Code table 0521	—
0 20 101	L _n – Code table 162 (Vol. II)	—
0 20 102	L _c – Code table 169 (Vol. II)	—
0 20 103	L _d – Code table 160 (Vol. II)	—
0 20 104	L _g – Code table 161 (Vol. II)	—
0 20 105	s _L – Code table 173 (Vol. II)	—
0 20 106	d _L – Code table 139 (Vol. II)	—
0 20 107	D _L – Code table 140 (Vol. II)	—
0 20 108	v _e – Code table 182 (Vol. II)	—
0 20 136	C _a – Code table 0531	—
	C ₀ – Code table 0561	—
	N _m – Code table 2745	—
	N _t – Code table 2752	—
	N _v – Code table 2754	—
0 20 137	n ₃ – Code table 2863	—
0 22 061	S – Code table 3700	—
0 22 067	I _X I _X I _X – Code table 1770	Common Code table C–3
0 22 068	X _R X _R – Code table 4770	Common Code table C–4
0 23 001	A _a – Code table 0131	—
0 23 002	AA – Code table 0177	—
0 23 003	B _T – Code table 0324	—
0 23 004	P _a – Code table 3131	—
0 23 005	A _c – Code table 0133	—
0 23 006	A _e – Code table 0135	—
0 23 007	E _c – Code table 0933	—
0 23 008 } 0 23 009 }	E _s – Code table 0943	—
0 23 016	R _e – Code table 3535	—
0 23 018	E _e – Code table 0935	—
0 23 031	R _p – Code table 3548	—

ATTACHMENT II

BUFR/CREX code or flag table	Related code table, regulation or code form in alphanumeric codes	Remarks
0 23 032	I _n – Code table 1743	—
0 24 003	R _c – Code table 3533	—
0 25 041	D _s – Code table 0700	—
0 25 042	v _s – Code table 4451	—
0 25 086	Q _z – Code table 3318	—
0 29 001	grgr – Code table 1487	—
0 33 020	Q _d , Q _{d1} , Q _{d2} , Q _l , Q _t – Code table 3334	—
0 33 021	Q _p , Q _{TW} – Code tables 3315 - 3319	—
0 33 022	Q _N – Code table 3313	—
0 33 023	Q _L – Code table 3311	—
0 33 024	i _m – Code table 1845	—
0 33 027	Q _A – Code table 3302	—

Note: Encoding/decoding of SYNOP/SHIP i_x – Code table 1860

		to/from BUFR code tables	
Code figure	Type of station operation	0 02 001 Type of station	0 20 003 Present weather
1	Manned station (group 7wwW ₁ W ₂ included) (but actually missing)	1 (1)	00–99 (200–299) (510)
2	Manned station (group 7ww W ₁ W ₂ omitted, no significant phenomenon to report)	1	508
3	Manned station (group 7ww W ₁ W ₂ omitted, no observation, data not available)	1	509
4	Automatic station (group 7ww W ₁ W ₂ included, using Code tables 4677 and 4561) (but actually missing)	0 (0)	00–99 (200–299) (510)
5	Automatic station (group 7w _a w _a W _{a1} W _{a2} omitted, no significant phenomenon to report)	0	508
6	Automatic station (group 7 w _a w _a W _{a1} W _{a2} omitted, no observation, data not available)	0	509
7	Automatic station (group 7 w _a w _a W _{a1} W _{a2} included, using Code tables 4680 and 4531) (but actually missing)	0 (0)	100–199 (200–299) (510)

Provisional Copy
2023

For more information, please contact:

World Meteorological Organization

7 bis, avenue de la Paix – P.O. Box 2300 – CH 1211 Geneva 2 – Switzerland

Strategic Communications Office

Tel.: +41 (0) 22 730 87 40/83 14 – Fax: +41 (0) 22 730 80 27

Email: communications@wmo.int

public.wmo.int